WEST VIRGINIA
SECRETARY OF STATE
BETTY IRELAND
ADMINISTRATIVE LAW DIVISION

Form #3

Do Not Mark In This Box

RECEIVED

2007 JUL 26 PM 2:02

SECRETARY OF STATE
STATE OF WEST VIRGINIA

NOTICE OF AGENCY APPROVAL OF A PROPOSED RULE AND FILING WITH THE LEGISLATIVE RULE-MAKING REVIEW COMMITTEE

AGENCY: West Virginia Department of Environmental Protection - Division of Air Quality TITLE NUMBER: 45

CITE AUTHORITY: WV Code §22-5-4 and 22-18-1 et seq.

AMENDMENT TO AN EXISTING RULE: YES X NO ____

IF YES, SERIES NUMBER OF RULE BEING AMENDED: 25

TITLE OF RULE BEING AMENDED: To Prevent and Control Air Pollution from Hazardous Waste Treatment, Storage, or Disposal Facilities

IF NO, SERIES NUMBER OF RULE BEING PROPOSED: ____

TITLE OF RULE BEING PROPOSED: ____

THE ABOVE PROPOSED LEGISLATIVE RULE HAVING GONE TO A PUBLIC HEARING OR A PUBLIC COMMENT PERIOD IS HEREBY APPROVED BY THE PROMULGATING AGENCY FOR FILING WITH THE SECRETARY OF STATE AND THE LEGISLATIVE RULE-MAKING REVIEW COMMITTEE FOR THEIR REVIEW.

Authorized Signature

WEST VIRGINIA
SECRETARY OF STATE
Betty Ireland
ADMINISTRATIVE LAW DIVISION

Form #1

Do Not Mark In This Box

FILED

2007 JUN -6 PM 4:25

OFFICE WEST VIRGINIA
SECRETARY OF STATE

NOTICE OF A PUBLIC HEARING ON A PROPOSED RULE

AGENCY: WV Department of Environmental Protection - Division of Air Quality TITLE NUMBER: 45

RULE TYPE: Legislative CITE AUTHORITY: WV Code §22-5-4 and 22-18-1 et seq.

AMENDMENT TO AN EXISTING RULE: YES [X] NO [ ]

IF YES, SERIES NUMBER OF RULE BEING AMENDED: 25

TITLE OF RULE BEING AMENDED: To Prevent and Control Air Pollution from Hazardous Waste Treatment, Storage, or Disposal Facilities

IF NO, SERIES NUMBER OF RULE BEING PROPOSED: _____

TITLE OF RULE BEING PROPOSED: _____

DATE OF PUBLIC HEARING: July 9, 2007 TIME: 6:00 p.m.

LOCATION OF PUBLIC HEARING: West Virginia Department of Environmental Protection
Dolly Sods Conference Room
601 57th Street, SE
Charleston, WV 25304

COMMENTS LIMITED TO: ORAL [ ] WRITTEN [ ] BOTH [X]

DATE WRITTEN COMMENT PERIOD ENDS: July 9, 2007 TIME: 6:00 p.m.

WRITTEN COMMENTS MAY BE MAILED TO:
Public Information Office
Department of Environmental Protection
601 57th Street, SE
Charleston, WV 25304

The Department requests that persons wishing to make comments at the hearing make an effort to submit written comments in order to facilitate the review of these comments.

Legislative Rule-Making Review Committee

The issues to be heard shall be limited to the proposed rule.

ATTACH A **BRIEF** SUMMARY OF YOUR PROPOSAL

JUN - 6 2007

Authorized Signature

QUESTIONNAIRE

(Please include a copy of this form with each filing of your rule: Notice of Public Hearing or Comment Period; Proposed Rule, and if needed, Emergency and Modified Rule.)

DATE: July 26, 2007

TO: LEGISLATIVE RULE-MAKING REVIEW COMMITTEE

FROM: (*Agency Name, Address & Phone No.*) WV Department of Environmental Protection
Division of Air Quality
601 57th Street, S.E.
Charleston, West Virginia 25304
Phone: 304-926-0499 ext. 1237

LEGISLATIVE RULE TITLE: 45CSR25 - To Prevent and Control Air Pollution from Hazardous Waste Treatment, Storage or Disposal Facilities

1. Authorizing statute(s) citation W.Va. Code §§22-5-4 and 22-18-1 et seq.

2. a. Date filed in State Register with Notice of Hearing or Public Comment Period:

June 6, 2007

b. What other notice, including advertising, did you give of the hearing?

Published notice on June 9th in The Charleston Daily Mail and The Charleston Gazette. Posted on the Department of Environmental Protection's web site under "Calendar of Events".

c. Date of Public Hearing(s) ***or*** Public Comment Period ended:

July 9, 2007

d. Attach list of persons who appeared at hearing, comments received, amendments, reasons for amendments.

Attached _____ No comments received X

e. Date you filed in State Register the agency approved proposed Legislative Rule following public hearing: (be exact)

July 26, 2007

f. **Name, title, address and <u>phone/fax/e-mail numbers</u>** of agency person(s) to receive all *written correspondence* regarding this rule: (Please type)

John A. Benedict, Director
601 57th Street, S.E.
Charleston, WV 25304

Phone: 304 926-0499
Fax: 304 926-0488
e-mail: jbenedict@wvdep.org

Tamra Mowrer, Administrative Secretary
601 57th Street, S.E.
Charleston, WV 25304

Phone: 304 926-0499
Fax: 304 926-0488
e-mail: tmowrer@wvdep.org

g. **<u>IF DIFFERENT</u> FROM ITEM 'f'**, please give **Name, title, address and phone number(s)** of agency person(s) who wrote and/or has responsibility for the contents of this rule: (Please type)

James Mason, Technical Analyst II
601 57th Street, S.E.
Charleston, WV 25304

Phone: 304 926-0499 ext. 1200
Fax: 304 926-0479

3. If the statute under which you promulgated the submitted rules requires certain findings and determinations to be made as a condition precedent to their promulgation:

a. Give the date upon which you filed in the State Register a notice of the time and place of a hearing for the taking of evidence and a general description of the issues to be decided.

N/A

b. Date of hearing or comment period:

N/A

c. On what date did you file in the State Register the findings and determinations required together with the reasons therefor?

N/A

d. Attach findings and determinations and reasons:

Attached N/A

DEPARTMENT OF ENVIRONMENTAL PROTECTION
DIVISION OF AIR QUALITY

BRIEFING DOCUMENT

Rule Title: 45CSR25 - "Control of Air Pollution from Hazardous Waste Treatment, Storage and Disposal Facilities."

A. AUTHORITY: W.Va. Code §§22-5-4 and 22-18-6.

B. SUMMARY OF RULE:

This rule establishes and adopts emission standards for the treatment, storage and disposal of hazardous waste promulgated by the United States Environmental Protection Agency (U.S. EPA) pursuant to the Resource Conservation and Recovery Act, as amended (RCRA). This rule codifies general procedures and criteria to implement emission standards set forth in 40 CFR Parts 260, 261, 262, 264, 265, 266, 270 and 279, as listed in Table 25-A of the rule. The rule also adopts associated appendices, reference methods, performance specifications and other test methods which are appended to these standards. Any person who constructs, reconstructs, modifies or operates any hazardous waste treatment, storage, or disposal facility must comply with the West Virginia Hazardous Waste Management System, the codified federal emission standards, and this rule.

45CSR25 establishes a program of regulation over the treatment, storage, and disposal of hazardous wastes in order to achieve and maintain such levels of air quality as will protect the public health and safety and the environment from the effects of improper, inadequate, or unsound treatment, storage, or disposal of hazardous wastes.

This revised rule incorporates by reference the following provisions of 40 CFR Parts 260, 261, 264, 265, 266 and 270 promulgated as of June 1, 2007: National Emission Standards for Hazardous Air Pollutants: Final Standards for Hazardous Air Pollutants for Hazardous Waste Combustors (Phase I Final Replacement Standards and Phase II), Resource Conservation and Recovery Act Burden Reduction Initiative, and Waste Management System; Testing and Monitoring Activities, Methods Innovation Rule; SW-846 Final Update IIIB; Hazardous Waste and Used Oil; Corrections to Errors in the Code of Federal Regulations; Modification of the Hazardous Waste Program; Cathode Ray Tubes; Hazardous Waste Management System; Identification and Listing of Hazardous Waste; and Final Exclusion.

C. STATEMENT OF CIRCUMSTANCES WHICH REQUIRE RULE:

Promulgation of this rule will enable the Department of Environmental Protection to continue to be the primary enforcement authority for the RCRA Hazardous Waste Management System in West Virginia. Revisions to this rule are necessary to maintain consistency with current federal regulations, the Office of Waste Management's Hazardous Waste Management System rule 33CSR20, and to fulfill the State's responsibilities under the CAA. Revisions to the rule include revised title, improved citing to federal counterpart language, annual incorporation by reference updates, revised definition of pathological waste, clarified language for pathological waste incinerators, a new exclusion for pathological waste incinerators subject to 45CSR6 or 45CSR18, and general language clarification and correction.

D. FEDERAL COUNTERPART REGULATIONS - INCORPORATION BY REFERENCE/DETERMINATION OF STRINGENCY:

A federal counterpart to this proposed rule exists. In accordance with the Secretary's recommendation, and with limited exception, the Division of Air Quality proposes that the rule incorporate by reference the federal counterparts. Because the proposed rule incorporates by reference the federal counterpart, no determination of stringency is required.

E. CONSTITUTIONAL TAKINGS DETERMINATION:

In accordance with W.Va. Code §§22-1A-1 and 3(c), the Secretary has determined that this rule will not result in taking of private property within the meaning of the Constitutions of West Virginia and the United States of America.

F. CONSULTATION WITH THE ENVIRONMENTAL PROTECTION ADVISORY COUNCIL:

At its May 21, 2007, and May 30, 2007 meetings, the Environmental Protection Advisory Council reviewed and discussed this rule. (See attached minutes for Council's discussion).

West Virginia Department of Environmental Protection

ADVISORY COUNCIL MEETING MINUTES

Monday – May 21, 2007
1:00 p.m. – 3:00 p.m.
601 57th Street, SE, Charleston, WV
West Virginia Room – 3rd Floor

ATTENDEES:

Advisory Council Members:

Rick Roberts
Karen Price
Bill Raney
Lisa Dooley
Larry Harris
Jackie Hallinan

DEP:

Randy Huffman, Deputy Cabinet Secretary/Director –Division of Mining & Reclamation
Karen G. Watson, Assistant General Counsel
Ken Ellison, Director - Division of Land Restoration
Lisa McClung, Director – Division of Water and Waste Management
John Benedict, Director – Division of Air Quality
Lewis Halstead, DMR
Ken Politan, DMR
Charlie Sturey, DMR
Jessica Greathouse, Chief Communication Officer – WVDEP – Public Information Office
James Martin, Chief, Office of Oil & Gas
Carroll Cather, DWWM
Pam Nixon, Advocate
David L. Vande Linde, Blasting
Jim Mason, DAQ
Mike Zeto, DWWM – EE
Matt Sweeney, DWWM

VISITORS:

Ann Bradley, Spilman Thomas & Battle
Charlie Burd, IOGA
Don Garvin, WVEC
Dave Yaussy, Robinson & McElwee

Randy Huffman, Deputy Cabinet Secretary - West Virginia Department of Environmental Protection called the meeting to order at 1:00 p.m.

Karen Price stated that the Council did not have enough time to review the rules, therefore was requesting to have another meeting to discuss further and the remaining of the Council agreed. The Council will meet May 30, 2007 at 10:00 a.m. – WVDEP – 601 57th Street, SE – Charleston, WV 25304 – West Virginia Room (3001).

Deputy Cabinet Secretary Huffman apologized for the short time period regarding the rules getting out to Council. Randy Huffman then introduced Karen Watson, Assistant General Counsel to discuss with the Council the DEP bills that had passed in the 2007 Regular Legislative Session:

- SB 337 – Establishing New Greenhouse Gas Inventory Program
  Approved by Governor – April 4, 2007

- SB 425 – Relating to Water Pollution Control Revolving Fund
  Approved by Governor – April 4, 2007

- SB 465 – Establishing Dam Safety Rehabilitation Revolving Fund
  Approved by Governor – March 27, 2007

- SB 490 – Relating to Underground Storage Tank Insurance Fund
  Approved by Governor – April 3, 2007

- SB 524 – Requiring Proof of Lawful Disposal of Solid Waste
  Approved by Governor – March 28, 2007

- SB 588 – Removing Tax Expiration Date on Manufacturing or Production of Synthetic Fuel From Coal
  Approved by Governor – April 4, 2007

Karen Watson then gave a brief summary of each proposed rule for the 2008 legislative session:

Air Quality

45CSR6 – Control of Air Pollution from Combustion of Refuse

SUMMARY

Proposed Rule 6 is now a basic open burning/ incinerator rule. Revised scope includes 'statutory air pollution,' addition of new language for posted operating instructions and open burning or incineration of animal or poultry carcasses during a declared state of emergency. Except for temporary Air Curtain Incinerators for land clearing debris (DOH jobs) and incineration of animal or poultry remains, most Air Curtain Incinerators will now be exempted under Rule 6 and placed under Rule 18.

COMMENT

Mr. Harris: Why does it allow low-level radioactive waste?

DEP Response: To allow crematories to dispose of bodies with chemo drugs. Does not allow high-level radioactive compounds related to research.

~~Council wanted to know if the agency would accept comments in writing after the meeting (e-mail in~~ comments)

DEP Response: Yes

45CSR8 – Ambient Air Quality Standards

SUMMARY

NAAQS rules 45CSR8, 45CSR9 & 45CSR12 have been combined for the 2008 legislative session. Rule 8 is now the complete NAAQS incorporation by reference rule, and 45CSR9 & 45CSR12 will be repealed and replaced. Revisions to SO_2 & PM NAAQS include correction of SO_2 annual primary standard from 0.003 to 0.030 ppm, addition of annual and 24-hour $PM_{2.5}$ standards, and addition of measurement methods for $PM_{2.5}$. Revisions to CO & Ozone NAAQS include revocation of one-hour ozone standard except for Berkeley & Jefferson counties, identification of one-hour ozone maintenance areas, and addition of 8-hour primary and secondary ozone standards. Revisions to NO_2 and Lead NAAQS include addition of primary and secondary standards for lead, and addition of measurement methods for lead. Revisions also include general language updates, improved citing and consistency.

COMMENT

Mr. Harris: Are we sure we are protecting the public's health? We should not be lowering standards so that our energy being transmitted to other states doesn't pollute our air. Are we aware of EPA's Science Advisory Panel?

DEP Response: CAIR aims to lower emissions at power plants. Utility controls are helping us meet targets earlier. EPA's regional approach has generally been successful and we are seeing tremendous benefits. The agency is aware of the EPA's panel, and EPA is considering more stringent regulations but has not done so yet.

45CSR16 – Standards of Performance for New Stationary Sources

SUMMARY

Revisions to rule incorporate annual incorporation by reference updates and exclusions.

COMMENT

No questions.

45CSR18 – Control of Air Pollution from Combustion of Solid Waste

SUMMARY

CISWI Rule 18 combines and incorporates by reference all current federal Section 111/129 combustion regulation into one rule. Old Rule 24 will be repealed and replaced. New exemption section is consistent with revised Rules 6, 25 and 34. Revisions also include revised scope, extensive federal counterpart language updates, improved citing and consistency.

COMMENT

No questions.

45CSR25 – Control of Air Pollution from Hazardous Waste Treatment, Storage and Disposal Facilities

SUMMARY

Revisions to the proposed rule include general annual incorporation by reference and revisions required to maintain consistency with the DWWM's rule 33CSR20 and federal counterpart regulation. Addition of direct incorporation by reference of new provisions published in the Federal Register. Language for pathological waste incinerators is revised for clarity.

COMMENT

No questions.

45CSR34 – Emission Standards for Hazardous Air Pollutants

SUMMARY

Rule 34 now combines all NESHAP regulations previously adopted under both Rules 15 & 34. Old Rule 15 will be repealed and replaced. Revisions to Rule 34 incorporate annual NESHAP updates under Parts 61 & 63. Some Part 63 standards affecting non-major sources of hazardous air pollutants are being excluded from incorporation by reference: Oil and Natural Gas; Polyvinyl Chloride and Copolymers; Primary Copper Smelting; Secondary Copper Smelting; and Primary Nonferrous Metals.

COMMENT

No questions.

45CSR39 – Control of Annual Nitrogen Oxides Emissions

SUMMARY

Annual CAIR NOx Rule - Incorporates revisions to 40 CFR Part 96.

COMMENT

No questions.

45CSR40 - Control of Ozone Season Nitrogen Oxides Emissions

SUMMARY

Ozone Season CAIR NOx Rule - Incorporates revisions 40 CFR to Part 96.

COMMENT

No questions.

45CSR41 – Control of Annual Sulfur Dioxide Emissions

SUMMARY

Annual CAIR SO_2 Rule - Incorporates revisions to 40 CFR Part 96.

COMMENT

No questions.

45CSR42 – Greenhouse Gas Emissions Inventory Program

SUMMARY

The Greenhouse Gas Inventory Program Rule is authorized by SB337 passed in the 2007 legislative session. The rule establishes a program which requires the reporting and inventory of greenhouse gas emissions by stationary sources which emit more than a *de minimis* amount; inventories greenhouse gas emissions from stationary, area, mobile and biogenic sources, and accounts for reductions, capture and sequestration; provides for: a periodic compilation of a greenhouse gas inventory; a determination whether WV is a net sink or emitter; development of a registry for voluntary reductions; and a determination whether greenhouse gas can be developed as an asset for economic development.

COMMENT

Mr. Raney: Is the exclusion still there for coal preparation activities?

DEP Response: Yes, section 3.2. (45CSR42)

Mr. Raney: How do we quantify sequestration?

DEP Response: Don't think we will get down to stationary source level. Agency will look at area

sources and biogenic activities. Once we get information, we will compile in an inventory.

Division of Water and Waste Management

33CSR9 – Standards for Beneficial use of Filtrate from Water Treatment Plants

SUMMARY

This legislative rule establishes a mechanism and requirements for the permitting, siting, bonding, and use of water treatment plant sludge from water treatment plants that has beneficial properties. This rule applies to the beneficial use of water treatment plant sludge and to any person who seeks approval from the Secretary to beneficially use such sludge within the state. This rule is intended to enhance the resource recovery and recycling goals of article fifteen of chapter twenty-two of the West Virginia Code and to encourage the beneficial use of water treatment plant filtrate. Section 22-15-23 of the West Virginia Code and this rule, and not the provisions of W. Va. Code § 22-15-10 or 33 CSR 1, shall govern the beneficial use of water treatment plant sludge. This rule does not apply to sewage sludge, products derived from sewage sludge, sludges regulated under 33 CSR 8, or materials regulated as hazardous waste under W. Va. Code §§22-18-1, et seq.

COMMENT

Lisa Dooley: Public notice of permits – who bears the cost – there has to be a more efficient way of getting notices out than Class I legal ads. This is a suggestion for the future.

DEP Response: Applicant bears cost – DEP is trying other methods of getting the information out – but not everyone has access to e-mail.

400 people on DEP's mailing list to receive permits by e-mail and we have between 30-40 who receive permits by US mail.

33CSR20 – Hazardous Waste Management System

SUMMARY

This amendment will adopt by reference approximately two years of changes to federal regulations by adopting the federal regulations in effect as of June 1, 2007 consisting of changes that correct errors in previously enacted Dye and Pigment rule and Manifest rule, allow more hazardous waste, allow greater flexibility in SW-846 testing and monitoring, allow more mercury containing devices to be managed as universal waste, streamline permitting process through a standardized permit, allow additional headworks and de minimus waste exemptions, reference Clean Air Act standards for hazardous waste combustors, allow a series of paperwork burden reductions for hazardous waste management facilities, corrects errors in 40 CFR (federal regulations) and excludes cathode ray tubes from the definition of solid waste under certain conditions. Language corrections, updated references and a change as the result of an EPA comment regarding annual groundwater monitoring at corrective action sites are also included in the amended rule. The rule amendment is not projected to require additional operating expenses above current levels as the amendments are generally de-regulatory in nature.

COMMENT

No questions.

33CSR30 – Underground Storage Tanks

SUMMARY

There are several new provisions to reflect the 2005 Federal Energy Act, including: secondary containment requirements for new or replaced thanks or piping; secondary containment requirements for new or replaced fuel dispenser systems; tank eligibility for delivery, deposit or acceptance – enables agency to prevent deposit or delivery to a tank that is not in compliance; and training requirements for individuals who operate, maintain or are responsible to address emergencies from spills or releases from underground storage tank systems.

COMMENT

No questions.

47CSR2 – Requirements Governing Water Quality Standards

SUMMARY

The proposed revisions reflect updates identified during the federally-mandated triennial review of the Water Quality Standards rule. These include proposed additions to the trout water list, new criteria for nutrients, revisions to criteria in Appendix E and a use redesignation in the Guyandotte River Basin.

COMMENT

Mr. Raney: Would like to have the trout water list stay within the agency and be able to discuss the science on a case-by-base basis before the EQB, not the Legislature.

DEP Response: The DEP believes the scientific basis for the proposed trout streams is clear and does not need to be litigated before the EQB.

Mr. Harris: Commented on the changes in Appendix E and asked whether the formula change for copper and cadmium resulted in a more or less stringent standard.

DEP Response: The changes in Appendix E are recommended by EPA, updating MCL's, etc. The revised hardness formulas represent EPA's latest science.

47CSR10 – National Pollutant Discharge Elimination System (NPDES)

SUMMARY

The proposed revisions to the National Pollutant Discharge Elimination System Rule reflect updates/additions made to the various federal regulations that govern the NPDES program. The proposed changes also include specific language in section 14 of the rule relating to the Pretreatment Program to ensure that the rule is consistent with the most recent federal pretreatment regulations in 40 CFR Part 403.

COMMENT

No questions.

47CSR34 – Dam Safety

SUMMARY

The proposed revisions establish requirements governing the disbursement and use of moneys in the Dam Safety Rehabilitation Revolving Fund, authorized by SB 465 in the 2007 legislative session.

COMMENT

Ms. Hallinan: Any progress being made in reducing the number of deficient dams?

DEP Response: Not very much. The fund initiative is badly needed.

60CSR5 – Antidegradation Implementation Procedures

SUMMARY

Antidegradation is a requirement of the federal Clean Water Act intended to preserve the existing quality of the State's waters and to prevent and/or minimize future degradation. The rule was first adopted in 2001 and establishes four levels, or tiers, of protection for state waters, Tiers 1, 2, 2.5 and 3. Each tier provides a graduated level of protection used during the NPDES permit issuance process. The proposed revisions to the rule carry forward the agency's antidegradation implementation efforts, and move the Tier 2.5 streams that had been on the "presumptive" list in Appendix C to a final proposed list in Appendix A. The agency is proposing a total of 156 streams be included on the list. The list of 156 waters is comprised of the 37 waters that did not receive objections in the formal objection period, those waters that contain reproducing trout and are 100% on public land, those waters listed as high quality on public land based on their high biological scores, and Loop Creek.

COMMENT

Mr. Harris: Suggested we file with 309 streams instead of 156 streams because Legislature will further reduce.

Jackie Hallinan: The program is a good idea.

Meeting was adjourned by Deputy Cabinet Secretary Randy Huffman.

West Virginia Department of Environmental Protection

ADVISORY COUNCIL MEETING MINUTES

Wednesday – May 30, 2007
10:00 a.m. – 12:00 p.m.
601 57th Street, SE, Charleston, WV
West Virginia Room – 3rd Floor

ATTENDEES:

Advisory Council Members:

Rick Roberts
Karen Price
Bill Raney
Larry Harris - Teleconference
Jackie Hallinan

DEP:

Randy Huffman, Deputy Cabinet Secretary/Director –Division of Mining & Reclamation
Karen G. Watson, Assistant General Counsel
Lisa McClung, Director – Division of Water and Waste Management
John Benedict, Director – Division of Air Quality
Jessica Greathouse, Chief Communication Officer – WVDEP – Public Information Office
Pam Nixon, Advocate
Jim Mason, DAQ
Mike Zeto, DWWM – EE
John Morgan, DWWM
Scott Mandirola, DWWM
Greg Adolfson, PIO

VISITORS:

Dave Yaussy
Brittany Carns
Joe Gollehon
Gregory Hoyer
Jeff Mauzy
Amy Christy

Randy Huffman, Deputy Cabinet Secretary - West Virginia Department of Environmental Protection called the meeting to order at 10:00 a.m. Advisory Council Member Larry Harris joined the meeting via teleconference. Deputy Cabinet Secretary Huffman then turned the meeting over to Karen Watson, Assistant General Counsel for the West Virginia Department of Environmental Protection. Karen informed the Council that the agency had received comments from several Council members and those comments would be appended to the minutes. (see attached) She explained the agency

had representatives from each of the programs to answer questions for the rules identified in those comments. She also explained the agency had made several changes in the rules as a result of those comments.

Air Quality

45CSR6 – Control of Air Pollution from Combustion of Refuse

SUMMARY

Proposed Rule 6 is now a basic open burning/ incinerator rule. Revised scope includes 'statutory air pollution,' addition of new language for posted operating instructions and open burning or incineration of animal or poultry carcasses during a declared state of emergency. Except for temporary Air Curtain Incinerators for land clearing debris (DOH jobs) and incineration of animal or poultry remains, most Air Curtain Incinerators will now be exempted under Rule 6 and placed under Rule 18.

COMMENT

Larry Harris: Had raised the issue of "low-level radioactive waste" in the last meeting.

DEP Response: DEP has removed the chemotherapeutic waste and low-level radioactive waste provisions from the proposed rule. The proposed rule does not in any way affect current medical waste incineration rules now on the books.

45CSR8 – Ambient Air Quality Standards

SUMMARY

NAAQS rules 45CSR8, 45CSR9 & 45CSR12 have been combined for the 2008 legislative session. Rule 8 is now the complete NAAQS incorporation by reference rule, and 45CSR9 & 45CSR12 will be repealed and replaced. Revisions to SO_2 & PM NAAQS include correction of SO_2 annual primary standard from 0.003 to 0.030 ppm, addition of annual and 24-hour $PM_{2.5}$ standards, and addition of measurement methods for $PM_{2.5}$. Revisions to CO & Ozone NAAQS include revocation of one-hour ozone standard except for Berkeley & Jefferson counties, identification of one-hour ozone maintenance areas, and addition of 8-hour primary and secondary ozone standards. Revisions to NO_2 and Lead NAAQS include addition of primary and secondary standards for lead, and addition of measurement methods for lead. Revisions also include general language updates, improved citing and consistency.

COMMENT

Karen Price: Section 4.2.c – $PM_{2.5}$ Maximum 24-Hour Average Concentration. The level for the 24-hour primary and secondary standard states 35 ug/m^3. This should be 65 ug/m^3, pursuant to 40 CFR 50.7.

DEP Response: On October 17, 2006, the federal NAAQS regulation changed from 65 to 35.

Larry Harris: Restated his concern that the standards may not be stringent enough to protect public health. He also restated his question about the antidegradation language struck from the rule.

DEP Response: DEP cannot lower the NAAQS standards below that of federal levels unless the provisions for the stringency test in §22-1-3a are fully met. 45CSR14, in its entirety, has wholly replaced the intent of the relic anti-degradation language struck in proposed Rule 8.

45CSR39 – Control of Annual Nitrogen Oxides Emissions

45CSR40 - Control of Ozone Season Nitrogen Oxides Emissions

Ozone Season CAIR NOx Rule - Incorporates revisions 40 CFR to Part 96.

Annual CAIR NOx Rule - Incorporates revisions to 40 CFR Part 96.

45CSR41 – Control of Annual Sulfur Dioxide Emissions

Annual CAIR SO_2 Rule - Incorporates revisions to 40 CFR Part 96.

COMMENT

Karen Price: Asked why the opt-in language was deleted from each of these rules.

DEP Response: has removed the opt-in provisions in the three CAIR rules so that West Virginia can say that CAIR equals NOx RACT for EGUs under the PM2.5 implementation rule.

45CSR42 – Greenhouse Gas Emissions Inventory Program

SUMMARY

The Greenhouse Gas Inventory Program Rule is authorized by SB337 passed in the 2007 legislative session. The rule establishes a program which requires the reporting and inventory of greenhouse gas emissions by stationary sources which emit more than a *de minimis* amount; inventories greenhouse gas emissions from stationary, area, mobile and biogenic sources, and accounts for reductions, capture and sequestration; provides for: a periodic compilation of a greenhouse gas inventory; a determination whether WV is a net sink or emitter; development of a registry for voluntary reductions; and a determination whether greenhouse gas can be developed as an asset for economic development.

COMMENT

Karen Price and Larry Harris: Both asked about the definitions of "anthropogenic" and "biogenic" in the rule and asked for examples of each.

DEP Response: An example of an anthropogenic source is the coal extraction process and an example of a biogenic source is the erosion of soil exposing a coal seam. The agency does not plan

to ask sources to report biogenic activities. In order to receive credit a source must report all of its emissions.

Karen Price: Can the reporting requirement in section 4.1 be made consistent with the emissions inventory requirements.

DEP Response: The date in the rule is March 31st and is the same as the emissions inventory date.

Karen Price: Does not believe fees should be required for greenhouse gas reporting.

DEP Response: The agency will consider the issue.

Karen Price: The last sentence in section 5.3 allowing the Secretary to request information is not authorized by statute.

DEP Response: It is authorized by the statute.

Karen Price: There should be a reasonable protocol for reporting emissions.

DEP Response: D AQ purposely wrote the rule in a manner flexible to the Secretary, as greenhouse gas reduction quantification protocols are still being developed at this time.

Karen Price: Is WV going to sign on to the climate registry or are we going to have our own?

DEP Response: In order to trade, we have to be consistent with other programs, but we do not want to be more specific in the rule.

Bill Raney: The exemption in section 3.2 includes language referring to sources covered by chapter 22-3 as well as sources required to report emissions. We are concerned this may take the exemption in the statute away.

DEP Response: While the agency did not want to require mining extraction to report emissions, thermal dryers associated with coal prep plants often have huge emissions of greenhouse gases. That is the reason the statute and rule only exempt sources permitted under chapter 22-3.

Division of Water and Waste Management

33CSR9 – Standards for Beneficial use of Filtrate from Water Treatment Plants

SUMMARY

This legislative rule establishes a mechanism and requirements for the permitting, siting, bonding, and use of water treatment plant sludge from water treatment plants that has beneficial properties. This rule applies to the beneficial use of water treatment plant sludge and to any person who seeks approval from the Secretary to beneficially use such sludge within the state. This rule is intended to enhance the resource recovery and recycling goals of article fifteen of chapter twenty-two of the West Virginia Code and to encourage the beneficial use of water treatment plant filtrate. Section 22-

15-23 of the West Virginia Code and this rule, and not the provisions of W. Va. Code § 22-15-10 or 33 CSR 1, shall govern the beneficial use of water treatment plant sludge. This rule does not apply to sewage sludge, products derived from sewage sludge, sludges regulated under 33 CSR 8, or materials regulated as hazardous waste under W. Va. Code §§22-18-1, et seq.

COMMENT

Larry Harris: DEP made changes to this rule during the Interims process last year, and the rule now requires a permit for both short-term and long-term applications. This is a good change. However, we feel that most of the information required in Section 7.3. Permit Application Requirements for long-term permits should also be required for short-term permits.

DEP Response: The requirements of section 7.3 were intended to be directed toward facilities that proposed to land apply filtrate as the beneficial use. It was intended to be applicable to both, if land application was the proposed method of reuse. Section 7.3 will be revised to more clearly reflect the applicability of the requirement for both long-term and short-term, if land application is the proposed beneficial reuse.

Rick Roberts and Larry Harris: Regarding the environmental effects of disposal of sludge are the values in Table 1 of the rule sufficient?

DEP Response: The Table 1 values are the same as the sewage sludge levels in DEP's other rules, and the agency believes they are supported by sound science.

Rick Roberts and Larry Harris: Mr. Harris expressed concern with the distinction between "beneficial reuse" and "disposal." Mr. Roberts believes that his concern is satisfied by the language in section 3.1.b.1.

Rick Roberts: The rule should include general permits as proposed.

Larry Harris: Only individual permits should be allowed under the rule.

DEP Response: There will be public notice in the general permit process.

33CSR30 – Underground Storage Tanks

SUMMARY

There are several new provisions to reflect the 2005 Federal Energy Act, including: secondary containment requirements for new or replaced thanks or piping; secondary containment requirements for new or replaced fuel dispenser systems; tank eligibility for delivery, deposit or acceptance – enables agency to prevent deposit or delivery to a tank that is not in compliance; and training requirements for individuals who operate, maintain or are responsible to address emergencies from spills or releases from underground storage tank systems.

COMMENT

Karen Price: Section 6.1. states "....including any person who accepts a delivery order, accepts payment, delivers or deposits product into an underground storage tank.....". The portion that states "...accepts payment..." should be removed from this section because those individuals within a company who accept payment or make payments most often do not know anything about the underground storage tank (UST), the operation of the UST, or the current regulatory status of the UST.

DEP Response: This language will give the agency a better handle on transporters and middle-men involved in the process.

Karen Price: Section 7.3.a.1. states "....the methodology for verifying attendance, the date, time and location of the course, the name of the offering organization, the credentials of the instructors, and a certification that the technology or methods.....".

1. The portion that states "..the date, time and location of the course,...." should be deleted. For large companies with many UST installations and locations there can be numerous individuals that need to be trained. Training will most likely occur on multiple dates, times, and locations that may not always be known until just prior to the training event. When new employees are hired training might occur on short notice and for one individual. The burden of having to report the dates, time and locations would hinder and slow down the training process and restrict a company's ability to comply.

2. The portion that states "...the credentials of the instructors..." should be removed. Credentials will vary from instructor to instructor new instructors might be utilized, and a company might not know which instructors will be used at the various training sessions until just prior to the training session. In addition, the course content is the main issue of concern and should be the main focus in obtaining State approval of a training program.

DEP Response: Regarding dates, times and location of the training the agency will not require the information prior to the training. As far as the credentials of the instructor the agency needs this information as part of its curriculum review, in this case before the training.

Karen Price: Section 7.3.a.2 - This section states that a nonrefundable application fee of $280 must be submitted with the application. Larger companies may have one training program, but administer the training on multiple dates, times and locations. Having to submit an application for approval of the training program each time the program is administered would be cost prohibitive, burdensome, and would hinder the training process.

DEP Response: The agency agrees and believes the rule only requires a one-time fee.

Rick Roberts: Regarding the $5.00 per ton fee, how does a source measure the tonnage? Perhaps the agency should consider using a cubic-yard approach.

DEP Response: The agency will consider.

47CSR2 – Requirements Governing Water Quality Standards

SUMMARY

The proposed revisions reflect updates identified during the federally-mandated triennial review of the Water Quality Standards rule. These include proposed additions to the trout water list, new criteria for nutrients, revisions to criteria in Appendix E and a use redesignation in the Guyandotte River Basin.

COMMENT

Larry Harris: Does the use removal in section 7.2.d follow the federal Clean Water Act requirements?

DEP Response: Yes, the agency followed all the requirements, federal and state, and required extensive information from the company. The agency also conducted two public meetings.
Bill Raney: Mr. Raney repeated his concern with the listing of trout waters in the rule and the fact that the list has to be approved by the Legislature. Karen Price agreed with this comment. Jackie Hallinan and Larry Harris did not agree with this comment.

Karen Price: Questioned the need for Appendix D, because the Category C use applies to all state waters.

DEP Response: Agency will consider.

Karen Price: Will the agency consider not making use removals go through the legislative process.

DEP Response: The agency decided not to include any language pertaining to this issue at this point in time, but will be subjecting this issue to the public participation process in the coming months.

60CSR5 – Antidegradation Implementation Procedures

SUMMARY

Antidegradation is a requirement of the federal Clean Water Act intended to preserve the existing quality of the State's waters and to prevent and/or minimize future degradation. The rule was first adopted in 2001 and establishes four levels, or tiers, of protection for state waters, Tiers 1, 2, 2.5 and 3. Each tier provides a graduated level of protection used during the NPDES permit issuance process. The proposed revisions to the rule carry forward the agency's antidegradation implementation efforts, and move the Tier 2.5 streams that had been on the "presumptive" list in Appendix C to a final proposed list in Appendix A. The agency is proposing a total of 156 streams be included on the list. The list of 156 waters is comprised of the 37 waters that did not receive objections in the formal objection period, those waters that contain reproducing trout and are 100% on public land, those waters listed as high quality on public land based on their high biological scores, and Loop Creek.

COMMENT

Larry Harris: Scientific criteria should be used to add or delete streams from the Tier 2.5 list.

Rick Roberts: Can the SRF program give priority to facilities impacted by the Tier 2.5 list?

DEP Response: Agency will take this under advisement.

Larry Harris: Is the nomination process adequate?

DEP Response: The agency believes the process is generally adequate and workable. If, however a large number of streams are nominated at one time, the individual notification requirements may be difficult and costly.

At this point in the meeting, Bill Raney submitted written comments regarding several mining rules. (see attached)

60CSR8 - Environmental Excellence Program

Greg Adolfson summarized the rule revisions. He said the changes would provide more flexibility for the agency to approve or disapprove of incentives in the program, as well as other flexibilities.

SUMMARY

Changes are being proposed to the Environmental Excellence Program Rule (60CSR8) to better align with and follow the momentum of the United States Environmental Protection Agency's National Environmental Performance Track Program. Additionally, the primary purpose for the changes is to give more flexibility to the Department of Environmental Protection Cabinet Secretary in areas such as: Eligibility Criteria for Participation (section 4); Environmental Performance Record (section 5); Environmental Management System (section 6); Public Participation (section 8); Incentives (section 9); Procedures for Application (section 10); and Annual Performance Report (section 14). Language, such as "may include, but will not be limited to, the following," has been added to allow for this flexibility.

COMMENT

Rick Roberts: Why is section 6.2 completely deleted?

DEP Response: The section is not completed deleted, just the 1996 standards. This will allow the agency to use the most current standards.

Bill Raney: How many companies are participating in the program?

DEP Response: There are two in the National Program, Toyota and Dow.

Mr. Raney: Suggested we start with 39.

Mr. Harris: Asked about section 2.11 in the definitions regarding "trading" and if it includes cross-pollutant trading.

DEP Response: The definitions were unchanged from the ones the EQB first adopted in 2001. The agency does not think it allows cross-pollutant trading.

Division of Mining and Reclamation

38CSR2 – Surface Mining Reclamation Rule

SUMMARY

§38-2-3.2.g. Notice of Technical Completeness is new language and is to provide the public an opportunity to review the application once technical review is completed. §38-2-5.4.e.1 is removing language that is contrary to returning the natural drainway to its original pattern, profile, and dimensions once drainage control structure is removed. The changes in §38-2-5.6 clarify what operations may be exempt from conducting a "Surface Water Runoff Analysis", monitoring requirements and removes phase-in compliance schedule that expired on June 19, 2006. Changes to §38-2-6 removes duplication of rules for Blasting and after this change, all the requirements for blasting will be contained in Surface Mining Blasting Rule, Title 199 Series 1. New §38-2-11.8 titled "Bond Credit for Reclamation of Bond Forfeiture Site under a No Cost Reclamation Contract" encourages qualified operators to undertake reclamation of bond forfeiture sites for the purpose of eliminating hazards to human health and safety, abating pollution of surface and ground waters and the contribution of sediment to adjacent areas, and restoring land to beneficial uses. Changes in §38-2-14.15.c.2 and 14.15.d.3 are clarifying contemporaneous reclamation rules on excess spoil disposal. The changes in 14.15.e remove a phase-in compliance schedule that expired in 2004. The changes in §38-2-23 are being made to make the mining rule consistent with the proposed changes in the State's NPDES Mining Rules.

COMMENT

No questions.

47CSR5A – Individual State Certification of Activities Requiring a Federal Permit

SUMMARY

The proposed amendments to this rule are being made to adopt into rule requirements that have been applied through past practices for coal related activities requiring mitigation and issuance of a 401 State Certification of a 404 Permit. Ratios for monetary compensation for temporary impacts are detailed. Monetary compensation for permanent impacts to wetlands from coal related activities are made the same as non-coal related. Additional economic and stream measurement information is being requested to be added to the 401 application.

COMMENT

Mr. Harris: How do we determine the "ordinary high water mark" under section 4.2.f.4 and how is it determined on a small stream?

DEP Response: The US Army Corps of Engineers is responsible for determining "waters of the U.S." under the rule.

Mr. Harris: What are the differences between coal and non-coal impacts and how are they determined?

DEP Response: Rule has to be consistent with statute.

47CSR30 – WV/NPDES Rules for Coal Mining Facilities

SUMMARY

The proposed amendments to this rule are being made to allow general clean-up of sections referencing outdated names of agencies and references to the EQB governing rule making. This rule addresses the Secretary as being the person as head of all actions. References to the "Director" are changed to "Secretary" to eliminate the need to distinguish between the Director of Mining and Reclamation and the Director of Water and Waste Management when issuing a coal related WV/NPDES permit. This rule adds provision for storm-water coverage for certain minimal activities without the requirement for modification through application to the permit. This rule also provides for an advanced approval of transfer of a WV/NPDES Permit to coincide with the advanced approval of the corresponding Article 3 Permit. This rule clarifies provisions related to coal remining operations and provides a remining water quality standard variance for any parameter of concern.

COMMENT

No questions.

199CSR1 - Surface Mining Blasting Rule

SUMMARY

The proposed amendments change the following sections: 2.27. Adds the definition of "other structure" (structures built by the permittee); 2.38 Clarifies definition of "surface mine operation"; 3.2.C. Plan for blasting should include seismic monitoring when within 1000 ft of a structure, and performance specifications for blasting seismographs; 3.4. Areas of blasting that will be regulated for shaft and slope development; 3.6.c.3. Requiring field practice guidelines for blasting seismographs; 3.7a Request for alternate limits must have written consent of the owner; 3.9. Minimum qualifications and continuing education requirements for surveyor; 4.1.b. Allows the agency to consider blasting experience of applicants that was gained prior to the last three years; 4.5.d. Requires applicants who have been suspended or revoked in other states to show cause as to why should be issued a certification; 4.9.a.2 process for issuing a temporary suspension to a blaster and appeal rights; 4.13 Clarifies blasters responsibility of training the blasting crew; 5.2.a.3&4 Clarifies

the investigations process on a claim of blasting damage; 6.1 Requiring that any arbitrators that are removed from the list must be done with cause; and 7.3 Detonators and initiation systems are not considered for calculation of fees.

COMMENT

No questions.

Office of Oil and Gas

35CSR3 – Coalbed Methane Wells Rule

SUMMARY

The WVDEP, Office of Oil and Gas is proposing to revise existing rule 35CSR3. Series 3 is a legislative rule in place to enforce the provisions in WV Code §22-21-1 et seq., Coalbed Methane Wells and Units, commonly referred to at the Coalbed Methane Act. The revisions will: Address the establishment of special field rules to promote the orderly development of coalbed methane fields; Protect the correlative rights of all owners located within the geographic area for which special field rules are established; Provide a process by which the Review Board may hold a hearing on an application for special field rules and issue such rules; Insert language (Section 17) which was inadvertently deleted from the rule during the 2006 legislative session. This language existed in the rule prior to the revisions in 2006.

COMMENT

Is this the same rule that went through last year?

DEP Response: Yes, except for two sections that had changes:

16.2.e – advertisement "15 days"

16.1.6.1 – "FOIA" issue that came out of the LRMRC.

Mr. Raney: Is this the product of the stakeholders group?

DEP Response: Yes.

Ms. Hallinan: What is a field rule?

DEP Response: Special spacing procedure for coalbed methane wells. It deals with pooling and royalty issues.

Division of Land Restoration

33CSR10 – Recycling Assistance Grant Program

SUMMARY
This rule sets out guidelines and procedures for providing assistance grants to local governments and other interested parties for the purpose of planning, initiating, expanding, or upgrading recycling programs, provide related public education programs, and assist in recycling market procurement efforts.

COMMENT

No questions.

60CSR3 – Voluntary Remediation and Redevelopment Rule

SUMMARY

This legislative rule establishes the eligibility, procedures, standards and legal documents required for voluntary and brownfield cleanups and updates risk protocol standards, including updates to the deminimis table. It also includes changes to the land use covenant section to incorporate the components of the Uniform Covenant Act.

COMMENT

Ms. Dooley: Are there grant dollars for brownfields?

DEP Response: Yes

The next scheduled Advisory Council Meeting will be on May 30, 2007 at 10:00 a.m. Mr. Huffman asked the Council members to notify the DEP of which rules they want to discuss so the right agency person can be at the meeting. He also asked them to submit comments prior to the meeting if possible.

DO, temperature, and fecal coliform. We feel that they can assess these parameters and should not treat them separately.

45CSR42 Greenhouse Gases

The fact that the DEP is beginning to deal with the process of greenhouse gases that lead to global warming is commendable. Some questions on the rule were raised by Dr. Kotcon:

The greenhouse gases emissions inventory rule (45-42-1) needs to be
>strengthened considerably. The sections on emissions inventory
>(section 5, pages 3-4) is so vague as to be meaningless, especially
>as it deals with sequestration for area sources and sinks. I do not
>see how any meaningful data can be generated with this language.
How would the carbon sequestration be estimated? Has there been studies estimating the biogenic incorporation of CO2 per acre of woodland, for example? The rule appears to be a vague in how it would be implemented.

Air Quality and Emission Rules (see below)

45CSR8 Ambient Air Quality Standards

Don Garvin pointed out that the the antidegradation language was removed from this rule, and it was explained that the agency feels these provisions are now covered in 45-CSR-14("Prevention of Significant Deterioration.") However, the language that was stricken does not appear in 45-CSR-14, and the stricken language is the ONLY statement in the rules of West Virginia's antidegradation policy for air quality. The environmental community still believes the stricken language should be restored.

Here is what should be reinstated:

§45-8-2. Anti-Degradation Policy.

2.1. Pursuant to the best interests of the State of West Virginia, it is the objective of the Secretary to obtain and maintain the cleanest air possible, consistent with the best available technology.

2.2. Where the present ambient air is of better quality than the established standards, the Secretary will develop long-range plans to protect the difference between the present quality and the established standards. The plans will be based upon the best available forecasts of probable land and air uses in these areas of high air quality.

2.3. The air quality of these areas will not be lowered unless it has been clearly demonstrated to the Secretary that such a change is justifiable as a result of necessary economic or social development and will not result in statutory air pollution. This will require that any industrial, public, or private project or development which could constitute a new source of air pollutants, within an area of such high air quality, provide the best practicable control available under existing technology as part of the initial project or development.

45CSR41 Control of Annual SO2 emissions

45CSR6 Control of Air Pollution from Refuse Combustion

45CSR39 Nitrogen Oxides

I raised the general concern whether the standards for air quality were consistent with the EPA guidelines or not. Further, were any recognized health authorities consulted when these levels were determined? I also raised the issue that West Virginia is increasing supplying electricity to the population east of our mountains. New transmission lines are proposed that are to be connected with coal burning power plants. Billy Jack Gregg, Consumer Advocate for the WV PSC has pointed out that the states receiving our generated power will not permit generation plants in their region. They are concerned about air pollution and its various effects. But they need power, so they turn to West Virginia. This helps the coal industry and generation plants, but puts the health of West Virginians in jeopardy. I feel that our air quality and emission limits should be even more stringent than the EPA calls for in order to protect our citizens. This should be particularly true for power plants that export electricity.

Dr. Kotcon has raised the following issues:

45-CSR-8 Ambient Air Quality Standards

The standards for PM2.5 and Ozone are not adequately protective. I recommend that the standards be lowered from 15 $\mu g/m^3$ to 13 $\mu g/m^3$ in section 4.2.b., and from 0.08 ppm to 0.07 ppm in section 4.4.b.

The air standards (45-8-1) retains the standards for PM2.5 and ozone
>that the EPA Clean Air Scientific Advisory Council has already
>determined to be inadequate. Keeping these old standards will kill
>dozens or hundreds of West Virginians each year.

>The rule on refuse combustion (45-6-1) attempts to revise the
>definition of low-level radioactive waste and revives the
>Below-Regulatory_Concern (BRC) issue from some years ago. It also
>creates a large number of exemptions for "temporary" pollution
>sources. I am not yet sure if this re-opens old battles over
>medical waste incineration, but this was a really hot issue a few
>years back.

Comment submitted by Karen Price at Council meeting 5/30/07

Questions/Comments on DEP's 2007 Proposed Rules

- **45 CSR 8 Ambient Air Quality Standards**

Section 4.2.c – $PM_{2.5}$ Maximum 24-Hour Average Concentration. The level for the 24-hour primary and secondary standard states 35 ug/m^3. This should be 65 ug/m^3, pursuant to 40 CFR 50.7.

- **45 CSR 39, 45 CSR 40, 45 CSR 41**

The opt-in unit language is deleted from each of these rules. What is the purpose for the deletion of these provisions?

- **33 CSR 30, Underground Storage Tank Rules**

Section 6.1. states "....including any person who accepts a delivery order, accepts payment, delivers or deposits product into an underground storage tank....." The portion that states "....accepts payment...." should be removed from this section because those individuals within a company who accept payment or make payments most often do not know anything about the underground storage tank (UST), the operation of the UST, or the current regulatory status of the UST.

Section 7.3.a.1. states " ...the methodology for verifying attendance, the date, time and location of the course, the name of the offering organization, the credentials of the instructors, and a certification that the technology or methods....."

1. The portion that states "..the date, time and location of the course,...." should be deleted. For large companies with many UST installations and locations there can be numerous individuals that need to be trained. Training will most likely occur on multiple dates, times, and locations that may not always be known until just prior to the training event. When new employees are hired training might

occur on short notice and for one individual. The burden of having to repor the dates, time and locations would hinder and slow down the training process and restrict a company's ability to comply.

2. The portion that states "...the credentials of the instructors..." should be removed. Credentials will vary from instructor to instructor new instructors might be utilized, and a company might not know which instructors will be used at the various training sessions until just prior to the training session. In addition, the course content is the main issue of concern and should be the main focus in obtaining State approval of a training program.

Section 7.3.a.2 - This section states that a nonrefundable application fee of $280 must be submitted with the application. Larger companies may have one training program, but administer the training on multiple dates, times and locations. Having to submit an application for approval of the training program each time the program is administered would be cost prohibitive, burdensome, and would hinder the training process. The State should clarify or make provision for a company to submit one application for the training program that will be administered to all company UST facilities. This will make the $280 application fee reasonable and the application process less burdensome.

APPENDIX B

FISCAL NOTE FOR PROPOSED RULES

Rule Title: 45CSR25 - "Control of Air Pollution from Hazardous Waste Treatment, Storage and Disposal Facilities"

Type of Rule: ___X__ Legislative _____Interpretive _____Procedural

Agency: Division of Air Quality

Address: 601 57th Street SE
Charleston, WV 25304

Phone Number: 926-0475 Email: tmowrer@wvdep.org

Fiscal Note Summary

Summarize in a clear and concise manner what impact this measure will have on costs and revenues of state government.

No impact above that resulting from currently applicable federal emission standards.

Fiscal Note Detail

Show over-all effect in Item 1 and 2 and, in Item 3, give an explanation of Breakdown by fiscal year, including long-range effect.

FISCAL YEAR

Effect of Proposal	2008 Increase/Decrease (use "-")	2009 Increase/Decrease (use "-")	Fiscal Year (Upon Full Implementation)
1. Estimated Total Cost	$ 0	$ 0	$ 0
Personal Services	0	0	0
Current Expenses	0	0	0
Repairs & Alterations	0	0	0
Assets	0	0	0
Equipment	0	0	0
Other	0	0	0
2. Estimated Total Revenues	0	0	0

Rule Title: 45CSR25 - "Control of Air Pollution from Hazardous Waste Treatment, Storage and Disposal Facilities"

3. Explanation of above estimates (including long-range effect):
Please include any increase or decrease in fees in your estimated total revenues.

The above estimates reflect that there will be no anticipated changes in costs to administer this rule.

MEMORANDUM

Please identify any areas of vagueness, technical defects, reasons the proposed rule **would not** have a fiscal impact, and/or any special issues **not** captured elsewhere on this form.

Date: June 1, 2007

Signature of Agency Head or Authorized Representative

John A. Benedict, Director

RECEIVED

2007 JUL 26 PM 2:03

SECRETARY OF STATE
STATE OF WEST VIRGINIA

TITLE 45
LEGISLATIVE RULE
DEPARTMENT OF ENVIRONMENTAL PROTECTION
~~OFFICE~~ DIVISION OF AIR QUALITY

SERIES 25
~~TO PREVENT AND~~ CONTROL OF AIR POLLUTION FROM HAZARDOUS WASTE TREATMENT, STORAGE~~, OR~~ AND DISPOSAL FACILITIES

§45-25-1. General.

1.1. Scope.

1.1.a. This rule establishes and adopts a program of regulation over air emissions and emission standards for the treatment, storage and disposal of hazardous waste promulgated by the United States Environmental Protection Agency (U.S. EPA) pursuant to the Resource Conservation and Recovery Act, as amended (RCRA). This rule codifies general procedures and criteria to implement emission standards set forth in the ~~Code of Federal Regulations~~ 40 CFR Parts 260, 261, 262, 264, 265, 266, 270 and 279 as listed in Table 25-A. The Secretary hereby adopts these standards by reference. The Secretary also adopts associated reference methods, performance specifications and other test methods which are appended to these standards.

1.1.b. The purpose of this rule is to achieve and maintain such levels of air quality that will protect the public health and safety and the environment from the effects of improper, inadequate, or unsound treatment, storage, or disposal of hazardous waste. Further, all persons engaged in the treatment, storage, or disposal of hazardous waste shall give careful consideration to the effects of the resultant emissions on the air quality or the areas affected by such any hazardous waste or constituent thereof in such quantities as to cause ambient air concentrations which may be injurious to human health or welfare which would interfere with the enjoyment of life or property.

1.1.c. Neither compliance with the provisions of this rule nor the absence of specific language to cover particular situations constitutes approval or implies consent or condonement of any emission which is released in any locality in a manner or amount as to cause or contribute to statutory air pollution. Neither does it exempt nor excuse any person from complying with other applicable laws, ordinances, regulations, or orders of governmental entities having jurisdiction over hazardous waste treatment, storage or disposal facilities.

1.1.d. This rule is promulgated pursuant to W.Va. Code §§22-18-1 et seq., and 22-5-1 et seq. Recognizing that each article has its own enforcement sections, it is the intent of the Secretary that enforcement ~~will~~ shall be implemented in accordance with W.Va. Code §22-18-1 et seq., where practicable.

1.1.e. Permit applications ~~will~~ shall be processed in accordance with the permitting procedures as set forth in W.Va. Code §22-18-1 et seq., 33CSR20, and this rule.

1.2. Authority. -- W.Va. Code §§22-5-4 and 22-18-1 et seq.

1.3. Filing Date. -- ~~April 28, 2006~~.

1.4. Effective Date. -- ~~June 1, 2006~~.

1.5. Incorporation By Reference.

1.5.a. Federal Counterpart Regulation. The Secretary has determined that a federal

counterpart regulation exists, and in accordance with the Secretary's recommendation, with limited exception, this rule incorporates by reference the provisions contained in ~~the Code of Federal Regulations~~ 40 CFR Parts 260, 261, 262, 264, 265, 266, 270 and 279 as listed in Table 25-A, effective ~~June 1, 2005~~ June 1, 2007.

1.5.b. This rule incorporates by reference the provisions contained in 33CSR20, "Hazardous Waste Management System" that are in effect on the date this rule becomes effective, except for any provision in 33CSR20 which incorporates by reference the Code of Federal Regulations.

~~1.5.c. This rule incorporates by reference the provisions of 40 CFR 262 as amended and finalized at 69 Federal Register 62217 (October 25, 2004).~~

1.6. Former Rules. -- This legislative rule amends 45CSR25 "To Prevent and Control Air Pollution From Hazardous Waste Treatment, Storage, or Disposal" which was filed ~~May 20 2005~~ April 28, 2006, and which became effective ~~June 1, 2005~~ June 1, 2006.

§45-25-2. Definitions.

2.1. "Air Pollutants" means solids, liquids, or gases which, if discharged into the air, may result in statutory air pollution.

2.2. "Air Pollution", "statutory air pollution" has the meaning ascribed to it in W.Va. Code §22-5-2.

2.3. "Air Pollution Control Equipment" means any equipment used for collecting or converting hazardous waste emissions for the purpose of preventing or reducing emissions of these materials into the open air from hazardous waste treatment, storage, or disposal facilities.

2.4. "Best Available Control Technology" or "BACT", means an emission standard based on the maximum degree of reduction for each pollutant which would be emitted from any hazardous waste treatment, storage or disposal facility which the Secretary, on a case-by-case basis, taking into account energy, environmental and economic impacts and other costs, determines is achievable for the facility through application of production processes or available methods, systems, or techniques. If the Secretary determines that technological or economic limitations on the application of measurement methodology to a particular emissions unit would make the imposition of an emissions standard infeasible, a design, equipment, work practice, operational standard or combination thereof may be prescribed instead to satisfy the requirement for the application of best available control technology. the standard ~~will~~ shall, to the extent possible, set forth the emission reduction achievable by implementation of the design, equipment, work practice or operational standard, and ~~must~~ shall provide for compliance by means which achieve equivalent results.

2.5. "CAA" means the federal Clean Air Act, as amended; 42 U.S.C. §7401 et seq.

2.6. "CFR" means the Code of Federal Regulations published by the Office of the Federal Register, National Archives and Records Service, General Services Administration.

2.7. "CWA" means the Clean Water Act (formerly referred to as the Federal Water Pollution Control Act), Public Law 92-500, as amended by Public Law 95-217 and Public Law 95-576; 33 U.S.C. §1251 et seq.

2.8. "Department of Environmental Protection" or "DEP" means that Department of the West Virginia Department of Environmental Protection which is created by the provisions of W.Va. Code §22-1-1 et seq.

2.9. "Facility mailing list" means the mailing list for a facility maintained by U.S. EPA in accordance with 40 CFR §124.10(c)(1)(ix).

2.10. "Hazardous waste" means a hazardous waste as defined in 40 CFR §261.3.

2.11. "Infectious Medical Waste" ~~will~~ shall have the meaning ascribed to it in 64CSR56 "Infectious Medical Waste", (July 1, 1999), promulgated by the West Virginia Division of Health.

2.12. "Particulate Matter" means any material, except uncombined water, that exists in a finely divided form as a liquid or solid.

2.13. "Pathological Waste ~~Incinerator~~" means ~~an incinerator used to thermally treat infectious medical~~ waste material consisting of only human or animal remains, anatomical parts or tissue, the bags or containers used to collect and transport the waste material, and animal bedding (if applicable).

2.14. "RCRA" means the federal Solid Waste Disposal Act as amended by the Resource Conservation and Recovery Act, as amended; 42 U.S.C. §6901 et seq.

2.15. "RCRA Permit" means "West Virginia hazardous waste permit". The following additional requirements ~~will~~ shall apply to obtain a hazardous waste management permit in West Virginia. All references in 40 CFR Part 270 to 40 CFR Part 124 ~~will~~ shall be deemed to be references to the applicable provisions of subsections 5.1 through 5.14. To the extent of any inconsistency with 40 CFR Part 270, the specific provisions contained herein ~~will~~ shall govern.

2.16. "Secretary" means the Secretary of the West Virginia Department of Environmental Protection or other person to whom the Secretary has delegated authority or duties pursuant to W.Va. Code §§22-1-6 or 22-1-8.

2.17. "Steady State" means that all conditions at all points in the thermal treatment process are in stable, normal operating conditions.

2.18. "U.S. EPA" means the United States Environmental Protection Agency.

2.19. Other words or phrases not herein defined and used in this rule ~~will~~ shall have the meaning as ascribed in W.Va. Code §§22-5-1 et seq., or 22-18-1 et seq., or 33CSR20 "Hazardous Waste Management ~~Regulations~~ System" governing the State Hazardous Waste Management Act.

§45-25-3. Adoption of Standards.

3.1. The Secretary hereby adopts and incorporates by reference the definitions, lists, tables, appendices, conditions, or requirements from 33CSR20 "Hazardous Waste Management Rule", effective ~~June 1, 2006~~ June 1, 2007, except for any provisions in 33CSR20 which incorporate by reference the Code of Federal Regulations. In case of a conflict between the Division of Air Quality and the Division of Water and Waste Management as to whether a material is a waste and if so, whether the material is a hazardous waste, the Secretary has final administrative authority to resolve the conflict.

3.2. Unless otherwise indicated, the Secretary hereby adopts and incorporates by reference the provisions contained in ~~the Code of Federal Regulations, effective June 1, 2005,~~ 40 CFR Parts 260, 261, 262, 264, 265, 266, 270 and 279 as listed in Table 25-A, effective June 1, 2007, with the following modifications:

3.2.a. Whenever the term "United States" is used, it ~~will~~ shall also mean the State of West Virginia;

3.2.b. Whenever the terms "Administrator," "Regional Administrator," "Assistant Administrator for Solid Waste and Emergency Response" or "Secretary" are used, the term means the Secretary of the West Virginia Department of Environmental Protection;

3.2.c. Whenever the term "Environmental

Protection Agency" is used the term also means the West Virginia Department of Environmental Protection; and

3.2.d. The distance provisions of 40 CFR §265.382 apply only to the open burning or open detonation of military explosives in a manner that presents an uncontrolled fragment release hazard. The applicable distance provisions of the American Table of Distances for Commercial Explosives, effective June 19, 1991, and of the Department of Defense Contractors Safety Manual for Ammunition and Explosives (DOD 4145.26-M), as amended April 11, 1988, apply otherwise.

§45-25-4. Requirements.

4.1. Owners and operators of hazardous waste treatment, storage, and disposal facilities regulated by the provisions of this rule ~~will~~ shall maintain a list of all permits or construction approvals received or applied for under any of the following programs and their counterpart programs administered by the Secretary, where appropriate:

4.1.a. Hazardous Waste Management Program under RCRA and 33CSR20;

4.1.b. Prevention of Significant Deterioration (PSD) Program under 45CSR14 or the CAA;

4.1.c. Nonattainment program under 45CSR19 or the CAA;

4.1.d. National Emission Standards for Hazardous Air Pollutants (NESHAP) preconstruction approval under ~~45CSR15,~~ 45CSR34 or the CAA;

4.1.e. Standards of Performance for New Stationary Sources under 45CSR16 or the CAA; and

4.1.f. Other relevant air pollution control permits including local permits.

4.2. Owners and operators of hazardous waste treatment, storage and disposal facilities covered under this rule must comply with the personnel training requirements as specified by 40 CFR §264.16. An outline of the training program and a description of how the training program is designed to meet actual job tasks must be submitted to the Secretary with Part B of the permit application.

4.3. Owners and operators of hazardous waste tanks, containers, surface impoundments, landfills, waste piles, land treatment, miscellaneous units, thermal treatment units, incinerators, and boiler and industrial furnace facilities must design, construct, maintain, and operate these facilities to minimize the possibility of a fire, explosion, or any unplanned, sudden, or non-sudden release of hazardous waste constituents to the air which could threaten human health or the environment.

4.4. Owners and operators of hazardous waste management facilities that treat, store, or dispose of ignitable or reactive wastes, or mix incompatible waste or incompatible wastes and other materials, must prevent reactions which:

4.4.a. Produce uncontrolled toxic mists, fumes, dust or gases in sufficient quantities to threaten human health or the environment, and

4.4.b. Produce uncontrolled flammable fumes or gases in sufficient quantities to pose a risk of fire or explosion.

4.5. The owners and operators of the hazardous waste treatment, storage and disposal facilities ~~must~~ shall manage all hazardous waste placed in a container in accordance with the applicable air emission requirements as listed in Table 25-A.

4.6. The owners and operators of the hazardous waste treatment, storage and disposal

facilities ~~must~~ shall manage all hazardous waste placed in a tank in accordance with the applicable air emission requirements as listed in Table 25-A.

4.7. The owners and operators of the hazardous waste treatment, storage and disposal facilities ~~must~~ shall manage all hazardous waste placed in a surface impoundment in accordance with the applicable air emission requirements as listed in Table 25-A.

4.8. The owners and operators of the hazardous waste treatment, storage and disposal facilities ~~must~~ shall manage all hazardous waste placed in a miscellaneous unit in accordance with the applicable air pollution standard requirements of 40 CFR 264 including but not limited to subparts AA, BB, and CC.

4.9. A hazardous waste pile must be fully enclosed or otherwise designed to prevent dispersal of the waste by wind.

4.10. Hazardous waste landfills must be covered or otherwise managed to prevent wind dispersal of the waste.

4.11. All landfills, surface impoundments, and land treatment facilities ~~must~~ shall be located, designed, constructed, operated, maintained, and closed in a manner that will assure protection of human health and the environment. Protection of human health and the environment ~~must~~ shall include prevention of adverse effects on air quality considering:

4.11.a. The volume and physical and chemical characteristics of the waste in the facility, including its potential for volatilization and wind dispersal;

4.11.b. The existing quality of the air, including other sources of contamination and their cumulative impact on the air;

4.11.c. The potential for health risks caused by human exposure to waste constituents;

4.11.d. The potential damage to wildlife, crops, vegetation, and physical structures caused by exposure to waste constituents;

4.11.e. The potential for interference with the enjoyment of life or property; and

4.11.f. The persistence and permanence of the potential adverse effects.

4.12. Owners and operators of hazardous waste treatment, storage, or disposal facilities ~~must~~ shall utilize best available control technology ("BACT") to limit the discharge of hazardous waste constituents to the atmosphere during:

4.12.a. Process turn-arounds;

4.12.b. Cleaning of process equipment;

4.12.c. Planned process shutdowns; and

4.12.d. Tank truck, railroad tank car, and barge cleaning.

4.13. The Secretary may, on a case-by-case basis, establish performance standards for hazardous waste incinerators for control of emissions of metals, hydrogen halides, and elemental halogen, based on a finding that the standards are necessary to limit the emission rates of these constituents to levels which do not pose an unacceptable risk to human health and environment. The Secretary may require the following data from the permit applicant:

4.13.a. Emissions of POHCs, hazardous combustion by-products, metals and hydrogen halides, including:

4.13.a.1. Mass emission rates from the stack, and

4.13.a.2. Concentration in the gas stream exiting the stack; and

4.13.b. Air dispersion estimates for those substances, including:

4.13.b.1. Meteorological data, and

4.13.b.2. Description of the air dispersion models, and

4.13.b.3. Assumptions underlying the air dispersion models used; and

4.13.c. Expected human and environmental exposure, including:

4.13.c.1. Topographic considerations,

4.13.c.2. Population distributions,

4.13.c.3. Population activities, and

4.13.c.4. Modes, intensity, and duration of exposure; and

4.13.d. Consequences of exposure, including:

4.13.d.1. Dose-response curves for carcinogens,

4.13.d.2. Health effects based on human or animal studies for other toxic constituents,

4.13.d.3. Potential for accumulation of toxic constituents in the human body, and

4.13.d.4. Statements of expected risk to individuals or populations.

4.14. Emergency Permit. -- Notwithstanding any other provision in 40 CFR §270.61, in the event the Secretary finds an imminent and substantial danger to human health or the environment, the Secretary may issue a temporary permit to a facility to allow treatment, storage, or disposal of hazardous waste at a non-permitted facility, or hazardous waste not covered by the permit for a facility with an effective permit. This emergency permit:

4.14.a. May be oral or written. If oral, it ~~must~~ shall be followed within five (5) days by written emergency permit;

4.14.b. ~~must~~ Shall not exceed ninety (90) days in duration;

4.14.c. ~~must~~ Shall clearly specify the hazardous wastes to be received, and the manner and location of the treatment, storage, or disposal;

4.14.d. May be terminated by the Secretary at any time without prior notice if it is determined that termination is appropriate to protect human health or the environment; and

4.14.e. ~~must~~ Shall be accompanied by public notice as described under section 7 and include the following:

4.14.e.1. Name and address of the office granting the emergency authorization,

4.14.e.2. Name and location of the permitted hazardous waste management facility,

4.14.e.3. A brief description of the wastes involved,

4.14.e.4. A brief description of the action authorized and reasons for authorizing it,

4.14.e.5. Duration of the emergency permit; and

4.14.f. ~~will~~ Shall incorporate, to the extent possible and not inconsistent with the emergency situation, all applicable requirements of this rule.

4.15. Pathological Waste Incinerators. -- The owner and operator of a pathological waste incinerator is not subject to the requirements of this ~~regulation. However, mixtures~~ rule unless the incinerator is charged with any mixture of

infectious medical waste and hazardous waste listed in 40 CFR 261 Subpart D ~~are subject to the requirements of this rule and the~~. The owner and operator of a pathological waste incinerator ~~must~~ shall design, construct and operate the facility in accordance with all ~~other~~ applicable ~~regulations~~ rules promulgated by the Secretary including, but not limited to, this rule, 45CSR6, ~~and~~ 45CSR13, 45CSR14, 45CSR18, 45CSR19, 45CSR30 and 45CSR34, as applicable.

§45-25-5. Permit Process.

5.1. Pre-application Public Meeting and Notice

5.1.a. Applicability. -- The requirements of subsection 5.1 ~~will~~ shall apply to West Virginia hazardous waste management Part B permit applications seeking initial permits for hazardous waste management units. These requirements ~~will~~ shall also apply to West Virginia hazardous waste management Part B permit applications seeking renewal of permits for hazardous waste management units, where the renewal application is proposing a significant change in facility operations. A "significant change" is any change that would qualify as a Class 3 permit modification pursuant to 40 CFR §270.42. These requirements do not apply to permit modifications under 40 CFR §270.42 or to applications that are submitted for the sole purpose of conducting post-closure activities or post-closure activities and corrective action at a facility.

5.1.b. Prior to the submission of a West Virginia hazardous waste management Part B permit application for a facility, the applicant must hold at least one meeting with the public in order to solicit questions from the community and inform the community of proposed hazardous waste management activities. The applicant ~~will~~ shall post a sign-in sheet or otherwise provide a voluntary opportunity for attendees to provide their names and addresses.

5.1.c. The applicant ~~will~~ shall submit a summary of the meeting, along with the list of attendees and their addresses developed under subdivision 5.1.b, and copies of any written comments or materials submitted at the meeting, to the Secretary as a part of the Part B application, in accordance with 40 CFR §270.14(b).

5.1.d. The applicant must provide public notice of the pre-application meeting at least thirty (30) days prior to the meeting. The applicant must maintain, and provide to the Secretary upon request, documentation of the notice.

5.1.d.1. The applicant ~~will~~ shall provide public notice in all of the following forms:

5.1.d.1.A. A newspaper advertisement. -- The applicant ~~will~~ shall publish a notice, fulfilling the requirements in paragraph 5.1.d.2, in a newspaper of general circulation in the county or equivalent jurisdiction that hosts the proposed location of the facility. In addition, the Secretary ~~will~~ shall instruct the applicant to publish the notice in newspapers of general circulation in adjacent counties or equivalent jurisdictions, where the Secretary determines that the publication is necessary to inform the affected public. The notice must be published as a display advertisement;

5.1.d.1.B. A visible and accessible sign. -- The applicant ~~will~~ shall post a notice on a clearly marked sign at or near the facility, fulfilling the requirements in paragraph 5.1.d.2. If the applicant places the sign on the facility property, then the sign must be large enough to be readable from the nearest point where the public would pass by the site;

5.1.d.1.C. A broadcast media announcement. -- The applicant ~~will~~ shall broadcast a notice, fulfilling the requirements in paragraph 5.1.d.2, at least once on at least one local radio station or television station. The applicant may employ another medium with prior approval of the Secretary; and

5.1.d.1.D. A notice to the permitting agency. -- The applicant ~~will~~ shall send a copy of the newspaper notice to the Secretary and the Secretary ~~will~~ shall forward copies to the appropriate units of State and local government having jurisdiction over the area where the facility is, or is proposed to be, located; and to each state agency having any authority under State law with respect to the construction or operation of the facility.

5.1.d.2. The notices required under paragraph 5.1.d.1 must include:

5.1.d.2.A. The date, time, and location of the meeting;

5.1.d.2.B. A brief description of the purpose of the meeting;

5.1.d.2.C. A brief description of the facility and proposed operations, including the address or a map (e.g., a sketched or copied street map) of the facility location;

5.1.d.2.D. A statement encouraging people to contact the facility at least seventy-two (72) hours before the meeting if they need special access to participate in the meeting; and

5.1.d.2.E. The name, address, and telephone number of a contact person for the applicant.

5.2. Public Notice Requirements at the Application Stage.

5.2.a. Applicability. -- The requirements of subsection 5.2 ~~will~~ shall apply to all West Virginia hazardous waste management Part B permit applications seeking initial permits for hazardous waste management units. These requirements ~~will~~ shall also apply to hazardous waste management Part B permit applications seeking renewal of permits for hazardous waste management units upon the expiration of the existing permit. These requirements do not apply to permit modifications under 40 CFR §270.42 or permit applications submitted for the sole purpose of conducting post-closure activities or post-closure activities and corrective action at a facility.

5.2.b. Notification at application submittal. -- The Secretary ~~will~~ shall provide public notice as required in subsection 5.2 when a Part B permit application has been submitted. The Secretary ~~will~~ shall provide public notice to:

5.2.b.1. The applicant;

5.2.b.2. All persons on a mailing list developed under subparagraph 5.8.d.1.D;

5.2.b.3. The appropriate units of state and local government having jurisdiction over the area where the facility is proposed to be located; and to each state agency having any authority under State law with respect to the construction or operation of the facility, that a Part B permit application has been submitted to the Secretary and is available for review; and

5.2.b.4. Any person otherwise entitled to receive notice under subdivision 5.2.b may waive the right to receive notice for any classes and categories of permits.

5.2.c. The notice ~~will~~ shall be published within a reasonable period of time after the application is received by the Secretary. The notice must include:

5.2.c.1. The name and telephone number of the applicant's contact person;

5.2.c.2. The name and telephone number of the Secretary's contact office, and a mailing address to which information, opinions, and inquiries may be directed throughout the permit review process;

5.2.c.3. An address to which people can write in order to be put on the facility mailing list;

5.2.c.4. The location where copies of the permit application and any supporting documents can be viewed and copied;

5.2.c.5. A brief description of the facility and proposed operations, including the address or a map (e.g., a sketched or copied street map) of the facility location on the front page of the notice; and

5.2.c.6. The date that the application was submitted.

5.2.d. Concurrent with the notice required under subdivision 5.2.b, the Secretary must place the permit application and any supporting documents in a location accessible to the public in the vicinity of the facility or at the Secretary's office.

5.3. Information Repository.

5.3.a. Applicability. -- The following requirements apply to all applicants seeking West Virginia hazardous waste management permits for hazardous waste management units.

5.3.b. The Secretary may assess the need, on a case-by-case basis, for an information repository. When assessing the need for an information repository, the Secretary ~~will~~ shall consider a variety of factors, including: the level of public interest; the type of facility; the presence of an existing repository; and the proximity to the nearest copy of the administrative record. If the Secretary determines, at any time after submittal of a permit application, that there is a need for a repository, then the Secretary ~~will~~ shall notify the facility that it must establish and maintain an information repository.

5.3.c. The information repository ~~will~~ shall contain all documents, reports, data, and information deemed necessary by the Secretary to fulfill the purposes for which the repository is established. The Secretary ~~will~~ shall have the discretion to limit the contents of the repository.

5.3.d. The information repository ~~will~~ shall be located and maintained at a site chosen by the facility. If the Secretary finds the site unsuitable for the purposes and persons for which it was established, due to problems with the location, hours of availability, access, or other relevant considerations, then the Secretary ~~will~~ shall specify a more appropriate site.

5.3.e. The Secretary ~~will~~ shall specify requirements for informing the public about the information repository. At a minimum, the Secretary ~~will~~ shall require the facility to provide a written notice about the information repository to all individuals on the facility mailing list.

5.3.f. The facility owner/operator shall be responsible for maintaining and updating the repository with appropriate information throughout a time period specified by the Secretary. The Secretary may close the repository at his or her discretion, based on the factors in subdivision 5.3.b.

5.4. Application for a Permit.

5.4.a. Any person who requires a permit ~~must~~ shall complete, sign, and submit to the Secretary an appropriate application. Applications are not required for hazardous waste permits by rule pursuant to 40 CFR §270.60. The Secretary ~~will~~ shall not begin the processing of a permit until the applicant has fully complied with the application requirements for that permit. Permit applications must comply with the signature and certification requirements of 40 CFR §270.11.

5.4.b. The Secretary ~~will~~ shall review every application for completeness. Each application submitted by a new hazardous waste management facility, should be reviewed for completeness by the Secretary within 30 days of its receipt. Each application submitted by an existing hazardous waste management facility (both Part A and Part B of the application), should be reviewed for completeness within 60 days of receipt. Upon completing the review, the Secretary ~~will~~ shall

notify the applicant in writing whether the application is complete. If the application is incomplete, the Secretary ~~will~~ shall list the information necessary to make the application complete. When the application is for an existing hazardous waste management facility, the Secretary ~~will~~ shall specify in the notice of deficiency a date for submitting the necessary information. The Secretary ~~will~~ shall notify the applicant that the application is complete upon receiving this information. After the application is completed, the Secretary may request additional information from the applicant but only when necessary to clarify, modify or supplement previously submitted materials. The request for additional information will not render an application incomplete.

5.4.c. If the applicant fails or refuses to correct deficiencies in the application, the permit may be denied and appropriate enforcement actions may be taken under the applicable statutory provisions of W.Va. Code §§22-18-1 et seq. and 22-5-1 et seq.

5.4.d. If the Secretary decides that a site visit is necessary for any reason in conjunction with the processing of an application, he or she ~~will~~ shall notify the applicant and a date ~~will~~ shall be scheduled.

5.4.e. The effective date of an application is the date on which the Secretary notifies the applicant that the application is complete as provided for in subdivision 5.4.b.

5.4.f. For each application the Secretary ~~will~~ shall, no later than the effective date of the application, prepare and mail to the applicant a project decision schedule. The schedule ~~will~~ shall specify target dates by which the Secretary intends to:

5.4.f 1. Prepare a draft permit;

5.4.f.2. Give public notice;

5.4.f.3. Complete the public comment period, including any public hearing; and

5.4.f.4. Issue a final permit.

5.5. Modification, Revocation and Reissuance, or Termination of Permits.

5.5.a. Permits may be modified, revoked and reissued, or terminated either at the request of an interested person (including the permittee) or upon the Secretary's initiative. However, permits may only be modified, revoked and reissued, or terminated for the reasons specified in 40 CFR §§270.41 or 270.43. All requests ~~must~~ shall be in writing and contain facts or reasons supporting the request.

5.5.b. If the Secretary decides the request is not justified, he or she ~~will~~ shall send the requester a brief written response giving a reason for the decision. Denials of requests for modification, revocation and reissuance, or termination are not subject to public notice, comment, or hearings. Denials by the Secretary may be appealed to the Air Quality Board in accordance with W.Va. Code §22B-1-1 et.seq.

5.5.b.1. If the Secretary tentatively decides to modify or revoke and reissue a permit under 40 CFR §§270.41 or 270.42(c), he or she ~~will~~ shall prepare a draft permit under subsection 5.6 incorporating the proposed changes. The Secretary may request additional information and, in the case of a modified permit, may require the submission of an updated application. In the case of a revoked and reissued permit, the Secretary ~~will~~ shall require the submission of a new application.

5.5.b.2. In a permit modification, only those conditions to be modified ~~will~~ shall be reopened when a new draft permit is prepared. All other aspects of the existing permit ~~will~~ shall remain in effect for the duration of the unmodified permit. When a permit is revoked and reissued, the entire permit is reopened just as if the permit

had expired and was being reissued. During any revocation and reissuance proceeding the permittee ~~must~~ shall comply with all conditions of the existing permit until a new final permit is reissued.

5.5.b.3. "Classes 1 and 2 Modifications" as defined in 40 CFR §§270.42(a) and (b) are not subject to the requirements of this subsection.

5.5.c. If the Secretary tentatively decides to terminate a permit under 40 CFR §270.43, he or she ~~will~~ shall issue a Notice of Intent to Terminate. A Notice of Intent to Terminate is a type of draft permit which follows the same procedures as any draft permit prepared under subsection 5.6.

5.6. Draft Permits.

5.6.a. Once an application is complete, the Secretary ~~will~~ shall tentatively decide whether to prepare a draft permit or to deny the application.

5.6.b. If the Secretary tentatively decides to deny the permit application, he or she ~~will~~ shall issue a Notice of Intent to Deny. A Notice of Intent to Deny the permit application is a type of draft permit which follows the same procedures as a draft permit. If the Secretary's final decision is that the tentative decision to deny the permit application was incorrect, he or she ~~will~~ shall withdraw the Notice of Intent to Deny and proceed to prepare a draft permit.

5.6.c. If the Secretary tentatively decides to issue a permit, he or she ~~will~~ shall prepare a draft permit that contains the following information:

5.6.c.1. All conditions under 40 CFR §§270.30 and 270.32;

5.6.c.2. All compliance schedules under 40 CFR §270.33;

5.6.c.3. All monitoring requirements under 40 CFR §270.31; and

5.6.c.4. Standards for treatment, storage, disposal and other permit conditions under 40 CFR §270.30.

5.6.d. All draft permits prepared by the Secretary ~~must~~ shall be accompanied by a fact sheet if required under subdivision 5.7.a and ~~will~~ shall be based on the administrative record, publicly noticed and made available for public comment.

5.6.e. In addition to the requirements of subsection 5.6, public notice of the preparation of a draft permit ~~will~~ shall be given by the methods contained in 40 CFR §§270.2, 270.14, 270.30, 270.62, and 270.66.

5.7. Fact Sheet.

5.7.a. A fact sheet ~~will~~ shall be prepared for each draft permit which the Secretary finds is the subject of wide-spread public interest or raises major issues. The fact sheet ~~will~~ shall briefly set forth the principal facts and the significant factual, legal, and methodological and policy questions considered in preparing the draft permit. The Secretary ~~will~~ shall send the fact sheet to the applicant and, on request, to any other person.

5.7.b. The fact sheet ~~must~~ shall include when applicable:

5.7.b.1. A brief description of the type of facility or activity which is the subject of the draft permit;

5.7.b.2. The type and quantity of waste, fluids, or pollutants which are proposed to be or are being treated, stored, disposed of, injected, emitted, or discharged;

5.7.b.3. A brief summary of the basis for the draft permit conditions including references to applicable statutory or regulatory provisions and appropriate supporting references to the administrative record;

5.7.b.4. Reasons why any requested variances or alternatives to required standards do or do not appear justified;

5.7.b.5. A description for reaching a final decision on a draft permit including;

5.7.b.5.A. The beginning and the ending dates of the comment period and the address where comments will be received;

5.7.b.5.B. Procedures for requesting a hearing and the nature of that hearing; and

5.7.b.5.C. Any other procedures by which the public may participate in the final decision; and

5.7.b.6. Name and telephone number of a person to contact for additional information.

5.8. Public Notice of Permit Actions and Public Comment Period.

5.8.a. Scope. The Secretary shall give public notice if the following actions have occurred:

5.8.a.1. A draft permit has been prepared; and

5.8.a.2. A hearing has been scheduled.

5.8.b. No public notice is required when a request for permit modification, revocation and reissuance, or termination is denied under subsection 5.5. Written notice of that denial ~~will~~ shall be given to the requester and to the permittee.

5.8.c. Timing. -- Public notice of the preparation of a draft permit, including a Notice of Intent to Deny a Permit Application, required under subdivision 5.8.a ~~must~~ shall allow at least forty-five (45) days for public comment. Public notice of a public hearing ~~must~~ shall be given at least thirty (30) days before the hearing. Public notice of the hearing may be given at the same time as public notice of the draft permit and the two notices may be combined.

5.8.d. Methods. -- Public notice of activities described in subdivision 5.8.a ~~will~~ shall be provided by the following methods:

5.8.d.1. By mailing a copy of a notice to the following persons (any person otherwise entitled to receive notice under this paragraph may waive his or her rights to receive notice for any classes and categories of permits):

5.8.d.1.A. The applicant;

5.8.d.1.B. Any other agency which the Secretary knows has issued or is required to issue a RCRA, UIC, PSD (or other permit under the Clean Air Act), W.Va. Code §22-5-1 et. seq., NPDES, 33 U.S.C. §1344, or sludge management permit for the same facility or activity;

5.8.d.1.C. Federal and state agencies with jurisdiction over fish, shell fish and wildlife resources and over coastal zones management plans, the advisory council on historic preservation, and the state historic preservation office, as applicable;

5.8.d.1.D. Persons on a mailing list developed by:

5.8.d.1.D.i. Including those who request in writing to be on the list;

5.8.d.1.D.ii. Soliciting persons for "area lists" from participants in past permit proceedings in that area; and

5.8.d.1.D.iii. Notifying the public of the opportunity to be put on the mailing list through periodic publication in the public press and in regional and state funded newsletters, environmental bulletins, or state law journals. The Secretary may update the mailing lists from time to time by requesting written indications of

continued interest from those listed. The Secretary may delete from the lists the name of any person who fails to respond to the request;

5.8.d.1.E. To any unit of local government having jurisdiction over the area where the facility is proposed to be located; and

5.8.d.1.F. To each state agency having any authority under state law with respect to the construction or operation of the facility.

5.8.d.2. Publication of a notice in a daily or weekly major local newspaper of general circulation and broadcast over local radio stations;

5.8.d.3. In a manner constituting legal notice to the public under state laws; and

5.8.d.4. Any other method reasonably calculated to give actual notice of the action in question to the person potentially affected by it, including press releases or any other forum or medium to elicit public participation.

5.8.e. Public notices. -- All public notices issued ~~must~~ shall contain the following minimum information:

5.8.e.1. Name and address of the office processing the permit action for which notice is being given;

5.8.e.2. Name and address of the permittee or the permit applicant and, if different, of the facility or activity regulated by the permit;

5.8.e.3. A brief description of the business conducted at the facility or activity described in the permit application or the draft permit;

5.8.e.4. Name, address and telephone number of a person from who interested persons may obtain further information, including copies of the draft permit and fact sheet and the application;

5.8.e.5. A brief description of the comment procedures required by subsections 5.9 and 5.10 and the time and place of any hearing that will be held, including a statement of procedures to request a hearing (unless a hearing has already been scheduled) and other procedures by which the public may participate in the final decision;

5.8.e.6. The location of the administrative record, the times that which the record ~~will~~ shall be open for public inspection; and

5.8.e.7. Any additional information considered necessary or proper.

5.8.f. Public notices for hearings. -- In addition to the general public notice described in subdivision 5.8.e, the public notice of a hearing ~~must~~ shall contain the following information:

5.8.f.1. Reference to the date of previous public notices relating to the permit;

5.8.f.1.A. Date, time, and place of the hearing; and

5.8.f.1.B. A brief description of the nature and purpose of the hearing, including the applicable rules and procedures;

5.8.g. In addition to the general public notice described in subdivision, all persons identified in subparagraphs 5.8.d.1.A, 5.8.d.1.B, and 5.8.d.1.C ~~will~~ shall be mailed a copy of the fact sheet, the permit application and the draft permit, as applicable.

5.9. Public Comments and Requests for Public Hearing. -- During the public comment period provided under subsection 5.8, any interested person may submit written comments on the draft permit and may request a public hearing, if no hearing has already been scheduled. A request for a public hearing ~~must~~ shall be in writing and state the nature of the issues proposed to be raised in the hearing. All comments ~~will~~ shall be

considered in making the final decision and ~~will~~ shall be answered as provided in subsection 5.13.

5.10. Public Hearings.

5.10.a. The Secretary ~~will~~ shall hold a public hearing whenever he or she finds, on the basis of requests, a significant degree of public interest in a draft permit.

5.10.b. The Secretary may also hold a public hearing at his or her discretion, whenever, for instance, a hearing might clarify one or more issues involved in the permit decision.

5.10.c. The Secretary ~~will~~ shall hold a public hearing whenever he or she receives written notice of opposition to a draft permit and a request for a hearing within forty-five (45) days of public notice under subdivision 5.8.c; whenever possible the Secretary ~~will~~ shall schedule a hearing at a location in convenient to the nearest population center to the proposed facility.

5.10.d. Public notice of the hearing ~~will~~ shall be given as specified in subsection 5.8.

5.10.e. Whenever a public hearing will be held the Secretary ~~will~~ shall designate a presiding officer for the hearings who ~~will~~ shall be responsible for its scheduling and orderly conduct.

5.10.f. Any person may submit oral or written statements and data concerning the draft permit. Reasonable limits may be set upon the time allowed for oral statements, and the submission of statements in writing may be required. The public comment period under subsection 5.8 ~~will~~ shall automatically be extended to the close of any public hearing. The hearing officer may also extend the comment period by so stating at the hearing.

5.10.g. A tape recording or written transcript of the hearing ~~will~~ shall be made available to the public.

5.11. Reopening of the Public Comment Period.

5.11.a. If any data, information, or arguments submitted during the public comment period appear to raise substantial new questions concerning a permit, the Secretary may take one or more of the following actions:

5.11.a.1. Prepare a new draft permit, appropriately modified, under subsection 5.6;

5.11.a.2. Prepare a revised fact sheet under subsection 5.7 and reopen the comment period; and

5.11.a.3. Reopen or extend the comment period under subsection 5.11 to give interested persons an opportunity to comment on the information or arguments submitted.

5.11.b. Comments filed during the reopened comment period ~~will~~ shall be limited to the substantial new questions that caused its reopening. The public notice under subsection 5.8 ~~will~~ shall define the scope of the reopening.

5.11.c. Public notice of any of the above actions ~~will~~ shall be issued under subsection 5.8.

5.12. Issuance and Effective Date of Permit.

5.12.a. After the close of the public comment period on a draft permit the Secretary ~~will~~ shall issue a final permit decision. The Secretary ~~will~~ shall notify the applicant and each person who has submitted written comments or requested notice of the final permit decision. The notice ~~will~~ shall include reference to the procedures for appealing a decision on the permit. A final permit decision means a final decision to issue, deny, modify, or revoke and reissue, or terminate a permit.

5.12.b. A final permit decision ~~will~~ shall

become effective thirty (30) days after the service of Notice of Decision unless:

5.12.b.1. A later effective date is specified in the decision;

5.12.b.2. Review is requested or an evidentiary hearing is requested; or

5.12.b.3. No comments requested change in the draft permit, in which case the permit ~~will~~ shall become effective immediately upon issuance.

5.13. Response to Comments.

5.13.a. At the time that any final permit decision is issued, the Secretary ~~will~~ shall issue a response to comments. This response ~~will~~ shall:

5.13.a.1. Specify which provisions, if any, of the draft permit have been changed in the final permit decision, and the reasons for the change; and

5.13.a.2. Briefly describe and respond to all significant comments on the draft permit or the permit application raised during the public comment period, or during any hearing.

5.13.b. The response to comments ~~will~~ shall be available to the public.

5.14. Administrative Record.

5.14.a. The provisions of a draft permit prepared under subsection 5.6 ~~will~~ shall be based on the administrative record consisting of:

5.14.a.1. The application and any supporting data furnished by the applicant;

5.14.a.2. The draft permit or notice of intent to deny the application or to terminate the permit;

5.14.a.3. The fact sheet if required;

5.14.a.4. All documents cited in the fact sheet; and

5.14.a.5. Other documents contained in the supporting file for the draft permit.

5.14.b. The Secretary ~~will~~ shall base final permit decisions on the administrative record consisting of:

5.14.b.1. Administrative record for the draft permit;

5.14.b.2. All comments received during the public comment period provided under subsection 5.5, including any extension or reopening under subsection 5.11;

5.14.b.3. The tape or transcript of any hearing(s) held under subsection 5.10;

5.14.b.4. Any written material submitted at the hearing;

5.14.b.5. The response to comments required by subsection 5.13 which identified and supports any change made in the draft permit and any new material placed in the record under subsection 5.13;

5.14.b.6. Other documents contained in the supporting file for the permit;

5.14.b.7. An addendum to the fact sheet if needed; and

5.14.b.8. The final permit.

5.14.c. The administrative record ~~will~~ shall be complete on the date the final permit is issued.

5.14.d. Material readily available at the issuing agency office or published material that is generally available, and that is included in the administrative record under subdivisions 5.14.a and 5.14.b, need not be physically included with

the rest of the record as long as it is specifically referred to in the fact sheet or in the addendum to the fact sheet.

5.15. Public Access to Information.

5.15.a. Any record, report, or information and any permit, permit application, and related documentation within the Secretary's possession ~~will~~ shall be available to the public for inspection and copying; provided, however, that upon a satisfactory showing to the Secretary that the records, reports, permit documentation, or information, or any part hereof would, if made public, divulge methods or processes or activities entitled to protection as trade secrets, the Secretary ~~will~~ shall consider, treat, and protect the records as confidential pursuant to W.Va. Code §§22-18-1-et seq. and 22-5-1-et seq.

5.15.b. It ~~will~~ shall be the responsibility of the person claiming any information as confidential under the provision of subdivision 5.15.a to comply with the requirements of 45CSR31.

5.16. The provisions of 40 CFR §270.12 are excepted from incorporation by reference. Availability of information provided under this rule is controlled by the provisions of W.Va. Code, §§22-18-1 et seq. and 22-5-1 et seq.

§45-25-6. Exclusions and Exemptions.

6.1. Wastes and materials excluded in 33CSR20, are excluded from the requirements of this rule.

6.2. Except for recyclable materials exempt pursuant to 33CSR§20-3, hazardous wastes that are stored prior to recycling are subject to all applicable provisions of section 4.

6.3. The provisions of 62 Federal Register 52622-52642, dated October 8, 1997 (Project XL Site-Specific Rulemaking for Merck & Co., Inc., Stonewall Plant, Elkton, VA: Final Rule) are hereby excluded. These provisions include 40 CFR §§264.1030(d), 264.1050(g), 264.1080(e), 265.1030(c), 265.1050(f), and 265.1080(e).

6.4. Any pathological waste incinerator not subject to this rule under subsection 4.15 shall be subject to 45CSR6 or 45CSR18, as applicable.

§45-25-7. Application Fee.

7.1. Any person who applies for a permit for the construction and/or operation of an air emitting hazardous waste treatment, storage, or disposal facility ~~must~~ shall submit as part of the application a money order or cashier's check payable to the "Air Pollution Control Fund" of the State Treasury. the fee ~~will~~ shall be determined by the schedule set forth below:

Activity	Fee
a. Hazardous Waste Management Facilities:	
Treatment design capacity more than 1,000 ton/yr	$5,000
Treatment design capacity less than 1,000 ton/yr	$5,000
b. Class 2, 3 Modifications or Renewals of Permits and 40 CFR §270.41 for Hazardous Waste Management Facilities	$1,000
c. Class 1 Modifications	$ 500

7.2. These application fees ~~will~~ shall be in addition to any fee required under any other rule of the West Virginia Department of Environmental Protection.

§45-25-8. Inconsistency Between Rules.

8.1. In the event of any inconsistency between this rule and any other rule of the West Virginia Department of Environmental Protection, the

inconsistency ~~will~~ shall be resolved by the determination of the Secretary and the determination ~~will~~ shall be based upon the application of the more stringent provision, term, condition, method or rule.

TABLE 25-A

Item No.	CFR No.	Part No.	Subpart No.	Title
1.	40 CFR -	264, 265 -	O -	Incinerator
2.	40 CFR -	270.19 -	B -	Specific Requirements for Incinerators
	-	270.42 -	D -	Permit Modification at the Request of the Permittee
		-	Appendix -	Appendix I
3.	40 CFR -	270.62 -	F -	Hazardous Waste Incinerator Permits
4.	40 CFR -	270.72 -	G -	Changes During Interim Status
5.	40 CFR -	264 -	X -	Miscellaneous Units
6.	40 CFR -	270.23 -	B -	Specific Requirements for Miscellaneous Units
7.	40 CFR -	264, 265 -	AA -	Air Emission Standards for Process Vents
8.	40 CFR -	270.24 -	B -	Specific Requirements for for Process Vents
9.	40 CFR -	264, 265 -	BB -	Air Emission Standards for Equipment Leaks
10.	40 CFR -	270.25 -	B -	Specific Requirements for Equipment Leaks
11.	40 CFR -	264, 265 -	CC -	Air Emission Standards
		264.179, 265.178	I	for Tanks, Surface
		264.200, 265.202	J	Impoundments, and Containers
		264.232, 265.231	K	
		265 -	Appendix -	Appendix VI
12.	40 CFR -	270.14(b)(5) -	A -	General Information
13.	40 CFR -	270.27 -	B -	Specific Requirements for Air Emissions Control for Tanks, Surface Impoundments and Containers
14.	40 CFR -	265 -	P -	Thermal Treatment

Item No.	CFR No.	Part No.	Subpart No.	Title
15.	40 CFR	266	H	Hazardous Waste Burned in Boilers and Industrial Furnaces
			Appendices	Appendix 1 to XIII
16.	40 CFR	270.22	B	Specific Requirements for Boilers and Industrial Furnaces Burning Hazardous Wastes
17.	40 CFR	270.66	F	Permits for Boiler and Industrial Furnaces Burning Hazardous Waste
18.	40 CFR	279.23	C	On-site Burning In Space Heater
19.	40 CFR	279	G	Standards for Used Oil Burners Who Burn Off-Specification Used Oil for Energy Recovery
20.	40 CFR	270.14(b)(22)	B	Permit Application
21.	40 CFR	270.1(c)(2)(viii)(C)-	A	General Information
22.	40 CFR	270.30(m)	B	Information repository
23.	40 CFR	261.6(c)(1)	A	Requirements for Recyclable Materials
		261.4		Exclusions
24.	40 CFR	261.38	D	Comparable/Syngas Fuel Exclusion
25.	40 CFR	262.34	C	Accumulation Time
26.	40 CFR	260.11	B	References
27.	40 CFR	264.15(b)(4)	B	General Inspection Requirement
28.	40 CFR	264.73(b)(6)	E	Operating Records
29.	40 CFR	270.235	I	Options for Incinerators and Cement and Lightweight Aggregate Kilns to Minimize Emissions from Startup, Shutdown, and Malfunction Events.

contribution or a percentage of the amount of the employee's HSA contribution (matching contributions), are the contributions subject to the section 4980G comparability rules?

A–2: No. The comparability rules do not apply to HSA contributions that an employer makes through a section 125 cafeteria plan. Thus, where matching contributions are made by an employer through a cafeteria plan, the contributions are not subject to the comparability rules of section 4980G. However, contributions, including matching contributions, to an HSA made under a cafeteria plan are subject to the section 125 nondiscrimination rules (eligibility rules, contributions and benefits tests and key employee concentration tests). See Q & A–1 of this section.

Q–3: If under the employer's cafeteria plan, employees who are eligible individuals and who participate in health assessments, disease management programs or wellness programs receive an employer contribution to an HSA and the employees have the right to elect to make pre-tax salary reduction contributions to their HSAs, are the contributions subject to the comparability rules?

A–3: (a) *In general.* No. The comparability rules do not apply to employer contributions to an HSA made through a cafeteria plan. See Q & A–1 of this section.

(b) *Examples.* The following examples illustrate the rules in this § 54.4980G–5. The examples read as follows:

Example 1. Employer A's written cafeteria plan permits employees to elect to make pre-tax salary reduction contributions to their HSAs. Employees making this election have the right to receive cash or other taxable benefits in lieu of their HSA pre-tax contribution. The section 125 cafeteria plan nondiscrimination rules and not the comparability rules apply because the HSA contributions are made through the cafeteria plan.

Example 2. Employer B's written cafeteria plan permits employees to elect to make pre-tax salary reduction contributions to their HSAs. Employees making this election have the right to receive cash or other taxable benefits in lieu of their HSA pre-tax contribution. Employer B automatically contributes a non-elective matching contribution or seed money to the HSA of each employee who makes a pre-tax HSA contribution. The section 125 cafeteria plan nondiscrimination rules and not the comparability rules apply to Employer B's HSA contributions because the HSA contributions are made through the cafeteria plan.

Example 3. Employer C's written cafeteria plan permits employees to elect to make pre-tax salary reduction contributions to their HSAs. Employees making this election have the right to receive cash or other taxable benefits in lieu of their HSA pre-tax contribution. Employer C makes a non-elective contribution to the HSAs of all employees who complete a health risk assessment and participate in Employer C's wellness program. Employees do not have the right to receive cash or other taxable benefits in lieu of Employer C's non-elective contribution. The section 125 cafeteria plan nondiscrimination rules and not the comparability rules apply to Employer C's HSA contributions because the HSA contributions are made through the cafeteria plan.

Example 4. Employer D's written cafeteria plan permits employees to elect to make pre-tax salary reduction contributions to their HSAs. Employees making this election have the right to receive cash or other taxable benefits in lieu of their HSA pre-tax contribution. Employees participating in the plan who are eligible individuals receive automatic employer contributions to their HSAs. Employees make no election with respect to Employer D's contribution and do not have the right to receive cash or other taxable benefits in lieu of Employer D's contribution but are permitted to make their own pre-tax salary reduction contributions to fund their HSAs. The section 125 cafeteria plan nondiscrimination rules and not the comparability rules apply to Employer D's HSA contributions because the HSA contributions are made through the cafeteria plan.

Q–4: May all or part of the excise tax imposed under section 4980G be waived?

A–4: In the case of a failure which is due to reasonable cause and not to willful neglect, all or a portion of the excise tax imposed under section 4980G may be waived to the extent that the payment of the tax would be excessive relative to the failure involved. See sections 4980G(b) and 4980E(c).

Approved: July 14, 2006.

Mark E. Matthews,

Deputy Commissioner for Services and Enforcement.

Eric Solomon,

Acting Deputy Assistant Secretary (Tax Policy).

[FR Doc. E6–11991 Filed 7–28–06; 8:45 am]

BILLING CODE 4830–01–P

ENVIRONMENTAL PROTECTION AGENCY

40 CFR Part 261

[FRL–8204–4]

Hazardous Waste Management System; Identification and Listing of Hazardous Waste; Final Exclusion

AGENCY: Environmental Protection Agency (EPA).

ACTION: Direct final rule.

SUMMARY: EPA is taking direct final action to codify a longstanding generator-specific delisting determination for brine purification muds (K071) generated by Olin Corporation (Olin) at its facility in Charleston, Tennessee. This rule will amend the Code of Federal Regulations to reflect the delisting, which was granted by EPA in December 1981 and by the Tennessee Department of Environment and Conservation in June 1983 after full notice and comment. The rule will not impose any new requirements on Olin or any other member of the regulated community.

DATES: This rule is effective on September 29, 2006 without further notice unless we receive adverse comment by August 30, 2006. If we receive adverse comments, we will publish a timely withdrawal in the **Federal Register** informing the public that this rule will not take effect.

ADDRESSES: Submit comments, identified by docket number EPA–R04–RCRA–2006–0478, by one of the following methods:

- *Federal eRulemaking Portal: www.regulations.gov.* Follow the on-line instructions.
- *E-mail: lippert.kristin@epa.gov.*
- *Mail or deliver:* Kristin Lippert, North Enforcement and Compliance Section, Mail Code 4WD–RCRA, RCRA Enforcement and Compliance Branch, U.S. Environmental Protection Agency, Region 4, Sam Nunn Atlanta Federal Center, 61 Forsyth Street, SW., Atlanta, Georgia 30303.

Instructions: All comments will be included in the public docket without change and may be made available online at *www.regulations.gov*, including any personal information provided, unless the comment includes Confidential Business Information (CBI) or other information whose disclosure is restricted by statute. Information that you consider CBI or otherwise protected should be clearly identified as such and should not be submitted through *www.regulations.gov* or e-mail. *www.regulations.gov* is an "anonymous access" system, and EPA will not know your identity or contact information unless you provide it in the body of your comment. If you send e-mail directly to EPA, your e-mail address will be automatically captured and included as part of the public comment. If EPA cannot read your comment due to technical difficulties and cannot contact you for clarification, EPA may not be able to consider your comment.

Docket: The index to the docket for this action is available electronically at

www.regulations.gov and in hard copy at the EPA Library, U.S. Environmental Protection Agency, Region 4, Sam Nunn Atlanta Federal Center, 61 Forsyth Street SW., Atlanta, Georgia 30303. While all documents in the docket are listed in the index, some information may be publicly available only at the hard copy location (e.g., copyrighted material), and some may not be publicly available in either location (e.g., CBI).

FOR FURTHER INFORMATION CONTACT: For general and technical information about this Direct Final Rule, contact Kristin Lippert, North Enforcement and Compliance Section, Mail Code 4WD–RCRA, RCRA Enforcement and Compliance Branch, U.S. Environmental Protection Agency, Region 4, Sam Nunn Atlanta Federal Center, 61 Forsyth Street SW., Atlanta, Georgia 30303 or call (404) 562–8605.

SUPPLEMENTARY INFORMATION: The information in this section is organized as follows:

I. Legal Background
II. Olin's Petition to Delist its Waste
III. Evaluation of Olin's Petition
IV. History of this Rulemaking
V. Final Action and Effective Date
VI. Regulatory Impact
VII. Regulatory Flexibility Act
VIII. Executive Order 12875
IX. Executive Order 12898
X. Executive Order 13211
XI. Paperwork Reduction Act
XII. Unfunded Mandates Reform Act
XIII. Executive Order 13045
XIV. Executive Order 13175
XV. National Technology Transfer and Advancement Act
XVI. Executive Order 13132 Federalism
XVII. Submission to Congress and General Accounting Office

I. Legal Background

On January 16, 1981, as part of its final and interim final regulations implementing section 3001 of the Resource Conservation and Recovery Act (RCRA), EPA published an amended list of hazardous wastes from non-specific and specific sources. This list has been amended several times and is published in Title 40 Code of Federal Regulations (40 CFR) 261.31 and 261.32. These wastes are listed as hazardous because: (1) They exhibit one or more of the characteristics of hazardous waste identified in subpart C of part 261 (i.e., ignitability, corrosivity, reactivity, and toxicity); or (2) they meet the criteria for listing contained in 40 CFR 261.11(a)(2) or (a)(3).

Individual waste streams may vary, however, depending on raw materials, industrial processes, and other factors. Thus, while a waste that is described in these regulations generally is hazardous, a specific waste from an individual facility meeting the listing description may not be. For this reason, 40 CFR 260.20 and 260.22 provide an exclusion procedure, called delisting, which allows persons to demonstrate that a specific waste generated at a particular facility should not be regulated as a hazardous waste.

II. Olin's Petition to Delist its Waste

On July 13, 1981, Olin petitioned EPA to amend 40 CFR part 261 to exclude sodium chloride purification muds generated at Olin's facility in Charleston, Tennessee. The muds meet the listing description for EPA Hazardous Waste No. K071—brine purification muds from the mercury cell process in chlorine production, where separately prepurified brine is not used.

Olin's petition included a description of its production and treatment processes. Olin's Charleston facility manufactures chlorine using a mercury cell chlor-alkali process. The chlor-alkali production process at Charleston involves the preparation of a strong brine from rock salt, which then circulates through mercury where part of the dissolved sodium chloride is separated by electrolysis into chlorine and sodium. The chlorine is collected and processed into liquid chlorine and the sodium amalgamates with the mercury of the cell and is separated and decomposed to form sodium hydroxide. The weak brine leaves the cells, is dechlorinated, resaturated, and purified. The purification (settling and filtration) of the resaturated brine produces brine muds which contain low levels of mercury carried over from the cells. The muds are dewatered using gravity. Liquid brine and dissolved mercury drain out and are returned to the brine system.

Olin's petition also included a description of total constituent and EP toxicity analyses of the muds for mercury, the constituent of concern for K071, and provided a plan for continuous testing of the muds prior to disposal.

III. Evaluation of Olin's Petition

Based on the information submitted by Olin, EPA granted a conditional temporary exclusion for Olin's sodium chloride purification muds on December 16, 1981 (46 FR 61272, December 16, 1981). The exclusion is conditioned on Olin's testing of samples from each batch of mud for mercury prior to disposal. Batches with a mercury concentration of 0.05 parts per million (ppm) or less are considered nonhazardous and are disposed of in Olin's on-site solid waste landfill. Batches that exceed 0.05 ppm of mercury are considered hazardous and are disposed of accordingly. EPA requested public comments on the delisting of Olin's brine purification muds. No adverse comments were received by the Agency.

At EPA's direction on September 28, 1981, Olin also submitted a delisting petition to the Tennessee Division of Solid Waste Management because, at that time, Tennessee had Phase 1 Interim Authorization. On February 17, 1982, Tennessee published notice of its tentative decision to grant Olin's delisting petition and requested public comments. No public comments were received by Tennessee. On June 28, 1983, Tennessee granted final approval of Olin's petition. Under the terms of the final approval, Olin must analyze samples from every batch of mud before disposal and submit the results to Tennessee on a quarterly basis. If a batch exceeds a mercury concentration of 0.05 ppm, Olin must handle the batch as a hazardous waste.

In 1984, Congress passed the Hazardous and Solid Waste Amendments ("HSWA") to RCRA. HSWA included additional criteria for evaluating proposed exclusions of certain listed waste. In anticipation of HSWA, EPA and Tennessee asked Olin to supply additional information that would allow evaluation of Olin's delisting under HSWA's proposed criteria. Olin complied, supplying detailed information supporting the delisting determination previously made by the agencies. Subsequently, both agencies confirmed that final exclusions, such as Olin's delisting, which were granted before November 8, 1984 were not affected by HSWA.

IV. History of This Rulemaking

In 2004, Olin contacted EPA seeking confirmation that use of potassium chloride as a raw material in the mercury cell process would not affect application of Olin's delisting to brine purification muds generated in that process, provided the muds meet the criteria of the delisting. Olin determined that use of potassium chloride as a raw material in the production process will not alter the composition or characteristics of the resulting brine purification muds with respect to mercury, the constituent of concern, nor will use of potassium chloride introduce any other hazardous constituents into the muds. EPA agreed with Olin's determination and concluded that Olin did not need a modification to its current delisting in order to use the delisting to manage muds generated in the potassium chloride process.

In the course of EPA's review of Olin's determination regarding use of potassium chloride, the Agency noted that Olin's delisting is not listed in the Code of Federal Regulations. EPA is issuing this direct final rule to correct this oversight.

V. Final Action and Effective Date

By this rule, EPA is taking direct final action to incorporate Olin's longstanding delisting into the Code of Federal Regulations. EPA is publishing this as a direct final rule because the Agency views this as a non-controversial amendment to the Code of Federal Regulations and anticipates no adverse comments. Interested parties had two prior opportunities to comment on Olin's delisting petition, first at the federal level and later at the state level, and no adverse comments were submitted. EPA sees no reason to provide a third comment period.

This rule will be effective upon publication in the **Federal Register**. Section 3010(b) of RCRA allows rules to become effective immediately when the regulated community does not need time to come into compliance. That is the case here because this rule will codify Olin's longstanding delisting for brine purification muds by amending the Code of Federal Regulations to reflect the delisting. The rule does not impose any new requirements on Olin or any other member of the regulated community. This reason also provides a basis for making this rule effective immediately, upon publication, under the Administrative Procedure Act pursuant to 5 U.S.C. 553(d).

VI. Regulatory Impact

Because EPA is issuing today's rule under the Federal RCRA delisting program, only states subject to federal RCRA delisting provisions are affected. This exclusion may not be effective in states that have received EPA's authorization to make their own delisting decisions.

Under section 3009 of RCRA, EPA allows states to impose their own non-RCRA regulatory requirements that are more stringent than EPA's requirements. These more stringent requirements may include a provision that prohibits a federally issued exclusion from taking effect in the state. EPA urges petitioners to contact the state regulatory authority to establish the status of their wastes under state law.

EPA has also authorized some states to administer a delisting program in place of the federal program, that is, to make state delisting decisions. Therefore, this exclusion does not apply in those authorized states. If Olin manages brine purification muds in any state with delisting authorization, Olin must obtain delisting authorization from the state before Olin can manage the brine purification muds as nonhazardous in that state.

Under Executive Order 12866 (58 FR 51735, October 4, 1993), EPA must conduct an "assessment of the potential costs and benefits" for all "significant" regulatory actions. Today's rule is not significant because its effect is to reduce the overall costs and economic impact of EPA's hazardous waste management regulations. This reduction is achieved by excluding waste generated at a specific facility from EPA's lists of hazardous wastes, thus enabling a facility to manage its waste as nonhazardous. Because there is no additional impact from today's rule, the rule is not a significant regulation, and no cost/benefit assessment is required. The Office of Management and Budget (OMB) has also exempted this rule from the requirement for OMB review under Section (6) of Executive Order 12866.

VII. Regulatory Flexibility Act

Under the Regulatory Flexibility Act, 5 U.S.C. 601–612, whenever an agency is required to publish a general notice of rulemaking for any proposed or final rule, it must prepare and make available for public comment a regulatory flexibility analysis which describes the impact of the rule on small entities (that is, small businesses, small organizations, and small governmental jurisdictions). No regulatory flexibility analysis is required, however, if the Administrator or delegated representative certifies that the rule will not have a significant economic impact on a substantial number of small entities.

Today's rule will not have any impact on small entities since its effect is to reduce the overall costs of EPA's hazardous waste regulations on one facility. Accordingly, EPA hereby certifies that this rule will not have a significant economic impact on a substantial number of small entities. This rule, therefore, does not require a regulatory flexibility analysis.

VIII. Executive Order 12875

Under Executive Order 12875, EPA may not issue a regulation that is not required by statute and that creates a mandate upon a state, local, or tribal government, unless the Federal government provides the funds necessary to pay the direct compliance costs incurred by those governments. If the mandate is unfunded, EPA must provide to the Office of Management and Budget a description of the extent of EPA's prior consultation with representatives of affected state, local, and tribal governments, the nature of their concerns, copies of written communications from the governments, and a statement supporting the need to issue the regulation. In addition, Executive Order 12875 requires EPA to develop an effective process permitting elected officials and other representatives of state, local, and tribal governments "to provide meaningful and timely input in the development of regulatory proposals containing significant unfunded mandates." Today's rule does not create a mandate on state, local or tribal governments. The rule does not impose any enforceable duties on these entities. Accordingly, the requirements of section 1(a) of Executive Order 12875 do not apply to this rule.

IX. Executive Order 12898

Executive Order 12898, "Federal Actions to Address Environmental Justice in Minority Populations and Low-Income Population" (February 11, 1994), is designed to address the environmental and human health conditions of minority and low-income populations. EPA is committed to addressing environmental justice concerns and has assumed a leadership role in environmental justice initiatives to enhance environmental quality for all citizens of the United States. The Agency's goals are to ensure that no segment of the population, regardless of race, color, national origin, income, or net worth bears disproportionately high and adverse human health and environmental impacts as a result of EPA's policies, programs, and activities. In response to Executive Order 12898, and to concerns voiced by many groups outside the Agency, EPA's Office of Solid Waste and Emergency Response (OSWER) formed an Environmental Justice Task Force to analyze the array of environmental justice issues specific to waste programs and to develop an overall strategy to identify and address these issues (OSWER Directive No. 9200.3–17). Today's final rule applies to a single waste at a single facility. We have no data indicating that today's final rule would result in disproportionately negative impacts on minority or low income communities.

X. Executive Order 13211

Executive Order 13211, "Actions Concerning Regulations That Affect Energy Supply, Distribution, or Use" (May 18, 2001), addresses the need for regulatory actions to more fully consider the potential energy impacts of the proposed rule and resulting actions.

Under the Order, agencies are required to prepare a Statement of Energy Effects when a regulatory action may have significant adverse effects on energy supply, distribution, or use, including impacts on price and foreign supplies. Additionally, the requirements obligate agencies to consider reasonable alternatives to regulatory actions with adverse effects and the impacts the alternatives might have upon energy supply, distribution, or use. Today's final rule applies to a single waste at a single facility and is not likely to have any significant adverse impact on factors affecting energy supply. EPA believes that *66 FR 28355* Executive Order 13211 is not relevant to this action.

XI. Paperwork Reduction Act

This final rule does not impose an information collection burden under the provisions of the Paperwork Reduction Act of 1995 (44 U.S.C. 3501 et seq.). Because there are no paperwork requirements as part of this final rule, EPA is not required to prepare an Information Collection Request (ICR) in support of today's action.

XII. Unfunded Mandates Reform Act

Under section 202 of the Unfunded Mandates Reform Act of 1995 (UMRA), Public Law 104–4, which was signed into law on March 22, 1995, EPA generally must prepare a written statement for rules with Federal mandates that may result in estimated costs to State, local, and tribal governments in the aggregate, or to the private sector, of $100 million or more in any one year.

When such a statement is required for EPA rules, under section 205 of the UMRA EPA must identify and consider alternatives, including the least costly, most cost-effective, or least burdensome alternative that achieves the objectives of the rule. EPA must select that alternative, unless the Administrator explains in the final rule why it was not selected or it is inconsistent with law.

Before EPA establishes regulatory requirements that may significantly or uniquely affect small governments, including tribal governments, EPA must develop under section 203 of the UMRA a small government agency plan. The plan must provide for notifying potentially affected small governments, giving them meaningful and timely input in the development of EPA's regulatory proposals with significant Federal intergovernmental mandates, and informing, educating, and advising them on compliance with the regulatory requirements.

The UMRA generally defines a Federal mandate for regulatory purposes as one that imposes an enforceable duty upon state, local, or tribal governments or the private sector.

EPA finds that today's rule is deregulatory in nature and does not impose any enforceable duty on any State, local, or tribal governments or the private sector. Therefore, no statement is required under section 205 of the UMRA. In addition, this rule does not establish any regulatory requirements for small governments and so does not require a small government agency plan under UMRA section 203.

XIII. Executive Order 13045

Executive Order 13045 (62 FR 19885, April 23, 1997), entitled "Protection of Children from Environmental Health Risks and Safety Risks," applies to any rule that EPA determines: (1) Is economically significant as defined under Executive Order 12866; and (2) the environmental health or safety risk addressed by the rule has a disproportionate effect on children. If the regulatory action meets both criteria, EPA must evaluate the environmental health or safety effects of the planned rule on children, and explain why the planned regulation is preferable to other potentially effective and reasonably feasible alternatives considered by EPA. Today's rule is not subject to Executive Order 13045 because the rule is not economically significant as defined under Executive Order 12866.

XIV. Executive Order 13175

Under Executive Order 13175 (65 FR 67249, November 6, 2000), EPA may not issue a regulation that has tribal implications, that imposes substantial direct compliance costs on Indian tribal governments, and that is not required by statute, unless funds necessary to pay the direct costs incurred by the Indian tribal government or the tribe in complying with the regulation are provided by the Federal government or EPA takes certain steps prior to the formal promulgation of the regulation. Those steps include: (1) Consulting with tribal officials early in the process of developing the proposed regulation; (2) providing to the Director of OMB, in a separately identified section of the regulation's preamble, a description of the extent of EPA's prior consultation with tribal officials, a summary of the nature of their concerns and EPA's position supporting the need to issue the regulation, and a statement of the extent to which the concerns of tribal officials have been met; and (3) making available to the Director of OMB any written communications submitted to EPA by tribal officials.

Today's rule does not have tribal implications because it will not have a substantial direct effect on one or more Indian tribes, on the relationship between the Federal government and Indian tribes, or on the distribution of power and responsibilities between the Federal government and Indian tribes, as specified in Executive Order 13175. Accordingly, the requirements of Executive Order 13175 do not apply to this rule.

XV. National Technology Transfer and Advancement Act

Under section 12(d) of the National Technology Transfer and Advancement Act of 1995, 15 U.S.C. 272 note, EPA is directed to use voluntary consensus standards in its regulatory activities unless to do so would be inconsistent with applicable law or otherwise impractical. Voluntary consensus standards are technical standards (e.g., materials specifications, test methods, sampling procedures, business practices) developed or adopted by voluntary consensus standard bodies. Where available and potentially applicable voluntary consensus standards are not used by EPA, the Act requires that EPA provide Congress, through OMB, with an explanation of the reasons for not using such standards.

Today's rule does not establish any new technical standards and, therefore, EPA is not required to consider the use of voluntary consensus standards in developing this rule.

XVI. Executive Order 13132 Federalism

Executive Order 13132 (64 FR 43255, August 10, 1999), entitled "Federalism," requires EPA to develop an accountable process to ensure "meaningful and timely input by State and local officials in the development of regulatory policies that have federalism implications." "Policies that have federalism implications" are defined in the Executive Order to include regulations that have "substantial direct effects on the States, on the relationship between the national government and the States, or on the distribution of power and responsibilities among the various levels of government."

Under section 6 of Executive Order 13132, EPA may not issue a regulation that has federalism implications, that imposes substantial direct compliance costs, and that is not required by statute, unless the Federal government provides the funds necessary to pay the direct compliance costs incurred by State and local governments, or EPA consults with

State and local officials early in the process of developing the proposed regulation. EPA also may not issue a regulation that has federalism implications and that preempts State law unless EPA consults with State and local officials early in the process of developing the proposed regulation.

Today's rule does not have federalism implications. It does not have a substantial direct effect on States, on the relationship between the national government and the States, or on the distribution of power and responsibilities among the various levels of government, as specified in Executive Order 13132, because the rule only affects one facility.

XVII. Submission to Congress and Government Accountability Office

The Congressional Review Act, 5 U.S.C. 801 et seq., as added by the Small Business Regulatory Enforcement Fairness Act of 1996, generally provides that before a rule may take effect, the agency promulgating the rule must submit a rule report, which includes a copy of the rule, to each House of Congress and to the Comptroller General of the United States.

Under section 804 of the Congressional Review Act, rules of particular applicability are exempted from the requirements of section 801. See 5 U.S.C. 804(3). EPA is not required to submit a rule report regarding today's action under section 801 because this is a rule of particular applicability. This rule is effective on September 29, 2006.

List of Subjects in 40 CFR Part 261

Environmental protection, Hazardous waste, Recycling, and Reporting and recordkeeping requirements.

Authority: Section 3001(f) RCRA, 42 U.S.C. 6921(f).

Dated: July 18, 2006.

Beverly H. Banister,

Acting Director, Waste Management Division, Region 4.

■ For the reasons set out in the preamble, 40 CFR part 261 is amended as follows:

PART 261—IDENTIFICATION AND LISTING OF HAZARDOUS WASTE

■ 1. The authority citation for part 261 continues to read as follows:

Authority: 42 U.S.C. 6905, 6912(a), 6921, 6922, and 6938.

■ 2. In Table 2 of Appendix IX of Part 261, the following waste is added in alphabetical order by facility to read as follows:

Appendix IX to Part 261—Wastes Excluded Under §§ 260.20 and 260.22

* * * * *

TABLE 2.—WASTES EXCLUDED FROM SPECIFIC SOURCES

Facility	Address	Waste description
*	*	* * * * *
Olin Corporation	Charleston, TN ..	Sodium chloride purification muds and potassium chloride purification muds (both classified as EPA Hazardous Waste No. K071) that have been batch tested using EPA's Toxicity Characteristic Leaching Procedure and have been found to contain less than 0.05 ppm mercury. Purification muds that have been found to contain less than 0.05 ppm mercury will be disposed in Olin's on-site non-hazardous waste landfill or another Subtitle D landfill. Purification muds that exceed this level will be considered a hazardous waste.
*	*	* * * * *

[FR Doc. 06–6587 Filed 7–28–06; 8:45 am]
BILLING CODE 6560–50–P

ENVIRONMENTAL PROTECTION AGENCY

40 CFR Part 300

[EPA–HQ–SFUND–1987–0002; FRL–8204–2]

National Oil and Hazardous Substances Pollution Contingency Plan; National Priorities List

AGENCY: Environmental Protection Agency (EPA).

ACTION: Notice of partial deletion of the Rocky Mountain Arsenal National Priorities List Site from the National Priorities List.

SUMMARY: The Environmental Protection Agency (EPA) Region 8 announces the deletion of the Internal Parcel of the Rocky Mountain Arsenal National Priorities List (RMA/NPL) Site from the National Priorities List (NPL). All areas originally proposed for deletion (71 FR 24627), except for a three-acre area which encompasses the Rail Yard Treatment System, are being deleted (see map). The Rail Yard Treatment System is excluded from the Internal Parcel due to a delay in developing the Interim Construction Completion Report. With the Rail Yard area excluded, the Internal Parcel consists of 7,396 acres (11.5 square miles) of the On-Post Operable Unit of RMA. The NPL constitutes Appendix B of 40 CFR part 300, which is the National Oil and Hazardous Substances Pollution Contingency Plan (NCP), which EPA promulgated pursuant to section 105 of the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA), as amended. EPA and the State of Colorado, through the Colorado Department of Public Health and Environment (CDPHE), have determined that the Internal Parcel of the RMA/NPL Site poses no significant threat to public health or the environment and, therefore, no further remedial measures pursuant to CERCLA are appropriate.

This partial deletion pertains to the surface media (soil, surface water, sediment), structures, and groundwater of the Internal Parcel of the On-Post OU of the RMA/NPL Site. The Internal Parcel includes groundwater that is east of E Street with the exception of a small area in the northwest corner of Section 6. The Rail Yard Treatment System and the rest of the On-Post OU, including groundwater below RMA that is west of E Street and the small area in the northwest corner of Section 6, as well as the Off-Post OU will remain on the NPL. This partial deletion of the Internal Parcel will not change Appendix B of 40 CFR part 300, which was previously amended in January 2003 (68 FR 2699) to reflect that a partial deletion of 1.5 square miles from the RMA/NPL Site had occurred.

DATES: This partial deletion of the Internal Parcel is effective on July 31, 2006.

FOR FURTHER INFORMATION CONTACT: Ms. Jennifer Chergo, Community Involvement Coordinator (8OC), U.S. Environmental Protection Agency, Region 8, 999 18th Street, Suite 300, Denver, Colorado 80202–2466;

Federal Register

Friday,
July 28, 2006

Part III

Environmental Protection Agency

40 CFR Parts 9, 260, 261, et al.
Hazardous Waste Management System; Modification of the Hazardous Waste Program; Cathode Ray Tubes; Final Rule

ENVIRONMENTAL PROTECTION AGENCY

40 CFR Parts 9, 260, 261, and 271

[RCRA–2004–0010; FRL–8203–1]

RIN 2050–AE52

Hazardous Waste Management System; Modification of the Hazardous Waste Program; Cathode Ray Tubes

AGENCY: Environmental Protection Agency.

ACTION: Final rule.

SUMMARY: A cathode ray tube (CRT) is the glass video display component of an electronic device (usually a computer or television monitor). In this rule, the Environmental Protection Agency (EPA) is amending its regulations under the Resource Conservation and Recovery Act (RCRA) to streamline management requirements for recycling of used CRTs and glass removed from CRTs. The amendments exclude these materials from the RCRA definition of solid waste if certain conditions are met. This rule is intended to encourage recycling and reuse of used CRTs and CRT glass. EPA proposed this rule on June 12, 2002 (67 FR 40508).

DATES: This final rule is effective on January 29, 2007.

ADDRESSES: EPA has established a docket for this action under Docket ID No. RCRA–2004–0010. All documents in the docket are listed on the *http://www.regulations.gov* Web site. Although listed in the index, some information may not be publicly available, such as confidential business information (CBI) or other information whose disclosure is restricted by statute. Certain other material, such as copyrighted material, is not placed on the Internet and will be publicly available only in hard copy form. Publicly available docket materials are available either electronically through *http://www.regulations.gov* or in hard copy at the RCRA Docket, EPA/DC, EPA West, Room B102, 1301 Constitution Ave., Washington, DC. The Public Reading Room is open from 8:30 a.m. to 4:30 p.m., Monday through Friday, excluding legal holidays. The telephone number for the Public Reading Room is (202) 566–1744, and the telephone number for the RCRA Docket is (202) 566–0270.

FOR FURTHER INFORMATION CONTACT: Ms. Marilyn Goode, Office of Solid Waste, Mail Code 5304W, U.S. Environmental Protection Agency, 1200 Pennsylvania Avenue, NW., Washington, DC 20460, (703) 308–8800, electronic mail: *goode.marilyn@epa.gov.*

SUPPLEMENTARY INFORMATION: The contents of this final rule are listed in the following outline:

Contents of the Final Rule

I. General Information
A. Does This Rule Apply To Me?
B. What Are the Statutory Authorities for This Final Rule?
C. Acronyms Used in the Rule
II. Summary of This Rule and Clarification of Existing Policies
A. CRTs From Households and Conditionally Exempt Small Quantity Generators
B. Reuse and Repair of Used CRTs
C. CRTs and CRT Glass Sent for Recycling
D. Export of Used CRTs
E. Disposal of CRTs
F. Circuit Boards
G. Other Electronic Material
III. Background
IV. Rationale for This Rule and Response to Comments
A. Used, Intact CRTs Sent for Recycling
B. Used, Broken CRTs Sent for Recycling
C. Used CRT Processing
D. Exports and Imports
E. Universal Waste
F. Definitions
G. Disposal
H. Enforcement
V. State Authority
A. Applicability of Rules in Authorized States
B. Effect on State Authorization
C. Interstate Transport
VI. Statutory and Executive Order Reviews
A. Executive Order 12866: Regulatory Planning and Review
B. Paperwork Reduction Act
C. Regulatory Flexibility Act
D. Unfunded Mandates Reform Act
E. Executive Order 13132: Federalism
F. Executive Order 13175: Consultation and Coordination With Indian Tribal Governments
G. Executive Order 13045: Protection of Children From Environmental Health and Safety Risks
H. Executive Order 13211
I. National Technology Transfer and Advancement Act of 1995
J. Environmental Justice
K. Congressional Review Act

I. General Information

A. Does This Rule Apply to Me?

This rule potentially affects all persons who send used cathode ray tubes (CRTs) and CRT glass for recycling, as well as all persons who recycle these materials. The rule does not affect households or conditionally exempt small quantity generators (CESQGs). If you have any questions about the applicability of this rule, consult the person listed under **FOR FURTHER INFORMATION CONTACT.**

B. What Are the Statutory Authorities for This Final Rule?

Today's rule is promulgated under the authority of Sections 2002(a), 3001, 3002, 3004, and 3006 of the Solid Waste Disposal Act of 1970, as amended by the Resource Conservation and Recovery Act of 1976 (RCRA), and as amended by the Hazardous and Solid Waste Amendments of 1984 (HSWA), 42 U.S.C. 3007, 6912(a), 6921, 6922, 6924, 6926, 6927, and 6938.

C. Acronyms Used in the Rule

CES Computers and Electronics Subcommittee
CFR Code of Federal Regulations
CRT Cathode Ray Tube
CSI Common Sense Initiative
DOT Department of Transportation
FPD Flat Panel Display
HDTV High Definition Television
LCD Liquid Crystal Display
LDR Land Disposal Restrictions
OECD Organization for Economic Cooperation and Development
OSHA Occupational Safety and Health Administration
RCRA Resource Conservation and Recovery Act
TC Toxicity Characteristic
TCLP Toxicity Characteristic Leaching Procedure
TSDF Treatment, Storage, and Disposal Facility
TV Television
UWR Universal Waste Rule
WTE Waste-to-Energy

II. Summary of This Rule and Clarification of Existing Policies

On June 12, 2002, EPA published a **Federal Register** notice seeking comment on a proposed rule change that would streamline management requirements for used CRTs and processed CRT glass (see 67 FR 40508 and following pages). In the same notice, EPA proposed to add mercury-containing equipment to the Federal list of universal wastes. This part of the proposal was finalized on August 5, 2005 (70 FR 45507).

The proposed requirements for used CRTs and processed CRT glass would exclude these materials from the RCRA definition of solid waste if they were sent for recycling under certain conditions. The purpose of the proposed amendments was to encourage increased reuse, recycling, and better management of this growing wastestream, while maintaining necessary environmental protection. The conditions proposed were intended to ensure that the materials were handled as commodities rather than as wastes.

The Agency received many comments in response to its June 12, 2002 notice. Numerous commenters supported the proposed rule, while other commenters suggested changes to all or part of our proposal. After considering all comments, we are finalizing the

proposal substantially as proposed, with two significant modifications. The final rule, similarly to the proposed rule, contains an exclusion from the definition of solid waste for used CRTs and processed glass removed from CRTs (see 40 CFR 261.4(a)(23)). The conditions for meeting the exclusion are found in 40 CFR 261.39. The first change from the proposal concerns exported CRTs. The Agency is promulgating notice and consent requirements for all used CRTs (whether broken or intact) that are exported for recycling (see 40 CFR 261.40 and 261.39(a)(5)). We are also promulgating a one-time notification requirement for used CRTs exported for reuse (see 40 CFR 261.41). The second change from the proposal concerns speculative accumulation requirements, which the final rule imposes on used, intact CRTs (see 40 CFR 261.4(a)(23)(i)).

EPA believes that today's rule will encourage recycling, protect human health and the environment, and ensure that the subject materials are handled as commodities rather than as wastes. Today's rule does not limit or constrain the Agency in exercising its discretion to promulgate additional rulemaking relating to the definition of solid waste. Specifically, the Agency maintains the discretion to promulgate additional regulations that aim to encourage legitimate recycling of waste.

Following is a brief summary of today's rule, along with some clarifications of existing policies applicable to used CRTs.

A. CRTs From Households and Conditionally Exempt Small Quantity Generators (CESQGs)

Under previously existing regulations, CRTs from households are exempt from Federal hazardous waste management requirements, even when they are sent for recycling or disposal. Non-residential generators of less than 100 kilograms (about 220 lbs) of hazardous waste in a calendar month, including CRTs, are known as conditionally exempt small quantity generators (CESQGs) and are not subject to most RCRA Subtitle C management requirements. These provisions are not changed by today's rule. For a more detailed description of requirements applicable to these generators, see the discussion in the proposal at 67 FR 40511.

B. Reuse and Repair of Used CRTs

In today's rule, we are reaffirming our long-standing policy that any user sending a CRT to a collector or reseller for potential reuse is not a RCRA generator. Materials used and taken out of service by one person are not wastes if another person uses them in the same way. Many businesses take usable CRTs out of service only because they are upgrading their systems to take advantage of rapid advances in electronic technology. These organizations do not have the technical knowledge to decide whether a unit can be reused as a computer or television.

The Agency also confirms today that used CRTs undergoing repairs (such as rewiring or replacing defective parts) before resale or distribution are not being reclaimed, and are considered to be products in use rather than solid wastes. These repairs do not constitute waste management. For a fuller discussion of this issue, see the proposal at 67 FR 40511. However, under today's rule, CRTs exported abroad for reuse are subject to a one-time notification requirement, which is discussed later in this section.

C. CRTs and CRT Glass Sent for Recycling

Many CRTs that cannot be reused are sent for recycling, which consists of disassembly to recover valuable materials from the CRTs, such as lead or glass. For a complete discussion of the different types of recycling, see the proposal at 67 FR 40510. Following is a summary of how CRTs and CRT glass sent for recycling within the United States are regulated under today's rule.

Unused CRTs

Today's rule clarifies that persons who send unused CRTs for recycling are not subject to RCRA regulations. Sometimes manufacturers of off-specification CRTs send them to glass processors, glass-to-glass manufacturers, or smelters. Although these types of recycling may constitute reclamation, EPA does not regulate unused commercial chemical products that are reclaimed. For a more detailed discussion of this issue, see the proposal at 67 FR 40511.

Used, Intact CRTs

Today's rule provides that used, intact CRTs sent for recycling (e.g., glass processing, glass manufacturing, or smelting) that occurs within the United States are not solid wastes, unless they are speculatively accumulated by a CRT collector or glass processor (see 40 CFR 261.4(a)(23)(i)).

Used, Broken CRTs

Under today's rule, used, broken CRTs (those whose vacuum has been released) are not solid wastes when sent for recycling that occurs within the United States if they are packaged and labeled or if they are stored in a building (see §§ 261.4(a)(23)(iii) and 261.39(a)(1)–(3)). Like used, intact CRTs, they may not be speculatively accumulated (see § 261.39(a)(4)).

Requirements for CRT Processing

Today's rule provides that to qualify for the exclusion from the definition of solid waste, CRT glass processing as defined in 40 CFR 260.10 must take place in a building, and no activities may be performed that use temperatures high enough to volatilize lead (see 40 CFR 261.39(b)).

Processed CRT Glass

Under today's rule, processed CRT glass (glass removed from CRTs) that is sent to a CRT glass manufacturer or a lead smelter is not a solid waste, unless it is speculatively accumulated (see 40 CFR 261.39(c)). If it is sent to other types of recycling, it may be excluded from the definition of solid waste if it meets the criteria of 40 CFR 261.2(e)(ii). All processed CRT glass legitimately used in a manner constituting disposal must be packaged and labeled and must also comply with the applicable requirements of 40 CFR part 266, subpart C (see 40 CFR 261.39(a)(1)–(4) and (d)). Subpart C applies to recycled materials placed on the land.

D. Exports of Used CRTs

Under today's rule, used, intact CRTs exported for recycling are not solid wastes provided they are not speculatively accumulated and provided the exporter notifies EPA of the export and receives a subsequent written consent from the receiving country allowing the CRTs to be imported for recycling (see 40 CFR 261.40 and 261.39(a)(5)). Used, broken CRTs exported for recycling are not solid wastes provided the exporters comply with the same notification and consent requirements applicable to used, intact CRTs. They must also be packaged and labeled, and they may not be speculatively accumulated (see § 261.39(a)(5) and (a)(1)–(4)).

Today's rule also provides that used intact CRTs exported for reuse are not solid wastes if the exporter sends a one-time notification to the EPA Regional Administrator. The notification must contain a statement that the notifier plans to export used, intact CRTs for reuse, as well as contact information (see § 261.41).

E. Disposal of CRTs

Today's rule clarifies that if a person (other than a household) decides to send used or unused CRTs directly to a landfill or incinerator, that person

would be considered the generator of a solid waste. The person making the decision must determine if the CRTs exhibit a hazardous waste characteristic under 40 CFR part 261, subpart C, either testing the CRTs or using process knowledge to make this determination. If the used or unused CRTs are determined to be hazardous and if a decision is made to dispose of them, the non-residential user, reseller, or manufacturer must comply with all applicable hazardous waste generator requirements of 40 CFR part 262. If hazardous waste CRTs are shipped to a hazardous waste landfill, they must also comply with applicable land disposal restrictions (LDRs). LDRs do not apply to CRTs generated by households or CESQGs. For a more complete description of disposal requirements for CRTs, see the proposal at 47 FR 40512.

In addition, we note the possibility of conducting research and development on CRT-related disposal and recycling technologies pursuant to the treatability study exemption under 40 CFR 261.4(e) and (f). The exemption allows researchers to store and use up to 1000 kg. of non-acute hazardous waste without triggering most Subtitle C requirements. In treatability studies, a hazardous waste is subjected to a treatment process to determine whether the waste is amenable to a treatment process, what pretreatment (if any is required), optimal process conditions, treatment process efficiency, and characteristics and volumes of residues (see 40 CFR 260.10). Examples of treatability studies that could fall under this exemption include physical, chemical, biological, or thermal treatment, solidification, volume or toxicity reduction, and recycling feasibility (see 53 FR 27290, 27293, July 19, 1988).

F. Circuit Boards

In 1992, the Agency issued a memorandum to its EPA Regional Waste Management Directors stating that used whole circuit boards are considered to be scrap metal when sent for reclamation, and therefore exempt from regulation under RCRA. The Agency also addressed circuit boards in the Land Disposal Restrictions Phase IV rulemaking (see 62 FR 25998, May 12, 1997). In that rulemaking, the Agency provided an exclusion from the definition of solid waste at 40 CFR 261.4(a)(14) for shredded circuit boards being reclaimed, provided they are stored in containers sufficient to prevent a release to the environment prior to recovery and provided they are free of mercury switches, mercury relays, nickel-cadmium batteries and lithium batteries.

Subsequently, on May 26, 1998 (63 FR 28556), the Agency clarified that the scrap metal exemption applies to whole used circuit boards that contain minor battery or mercury switch components and that are sent for continued use, reuse, or recovery. In that notice, EPA stated that it was not the Agency's intent to regulate under RCRA circuit boards containing minimal quantities of mercury and batteries that are protectively packaged to minimize dispersion of metal constituents. However, once these materials are removed from the boards, they become a newly generated waste subject to a hazardous waste determination. If they meet the criteria to be classified as a hazardous waste, they must be handled as hazardous waste; otherwise they must be managed as a solid waste.

G. Other Electronic Material

With respect to non-CRT electronic materials, the Agency uses the same line of reasoning that is outlined above for CRTs to determine that the materials are not solid wastes if they are reused or only require repair and are not sent for processing or reclamation. That is, if an original user sends electronic materials to a reseller because he lacks the specialized knowledge needed to determine whether the units can be reused as products, the original user is not a RCRA generator. The materials are not considered solid wastes until a decision is made to recycle them in other ways or dispose of them.

III. Background

Under Subtitle C of RCRA, a solid waste is a hazardous waste if it exhibits one or more of the characteristics of ignitability, corrosivity, reactivity, or toxicity in 40 CFR part 261, subpart C, or if it is a listed hazardous waste in 40 CFR part 261, subpart D. The RCRA regulations set forth requirements for hazardous waste generators, transporters, and owners and operators of treatment, storage, and disposal facilities (TSDFs). Generators are required to determine whether their waste is hazardous, either by testing the waste or applying their knowledge of the waste in light of the materials or processes used (see 40 CFR 262.11). EPA regulations also contain exclusions for certain materials from the definition of solid waste or hazardous waste (40 CFR 261.4(a) and (b)). In addition, the Agency has developed streamlined rules for particular wastes, including recyclable wastes (40 CFR part 266) and universal wastes such as batteries, pesticides, mercury-containing equipment, and lamps that are widely generated by different industries (40 CFR part 273).

CRTs are vacuum tubes, made primarily of glass, which constitute the video display components of televisions, computer monitors, and other electronic devices. Other types of CRTs include medical, automotive, oscilloscope, appliance, and military and control tower CRTs. A CRT is assembled into a monitor, which includes several other parts, such as a plastic cabinet, electromagnetic shields, circuit boards, connectors, and cabling. The preamble to the proposed rule provides more detailed information on the nature of the industry (see 67 FR 40509).

Manufacturers generally employ significant quantities of lead in the glass used to make color CRTs. Televisions and color computer monitors contain an average of four pounds of lead (the exact amount depends on the size and make). Lead is a toxic metal that can cause delayed neurological development in children and other adverse health effects in adults, including increased blood pressure, nephritis, and cerebro-vascular disease. It is reasonably anticipated to be a human carcinogen. See, e.g., Iris Database Toxicity Profile No. 0277: Lead and Compounds (Inorganic), EPA 2004 [1] and 53 FR 31522, August 18, 1988. The amount of lead used by some manufacturers appears to be decreasing. However, according to recent studies performed at the University of Florida, most color CRTs leach lead in the TCLP test at concentrations above the TC regulatory level of 5 milligrams per liter (mg/l). In one study, Musson *et al.* (2000) found that 21 of 30 color CRTs tested exceeded the TC value, with an average lead level of 22.2 mg/l in TCLP leachate.[2] In a 2004 study,[3] the average concentration of lead in leach tests of color computer

[1] *http://www.epa.gov/iris/subst/0277.htm.*

[2] Characterization of Lead Leachability from Cathode Ray Tubes Using the Toxicity Characteristic Leaching Procedure, Stephen Musson et al., Department of Environmental Engineering Sciences, University of Florida, Environmental Science and Technology, Vol. 34, no. 20, 2000. The investigators in this study also believed that variability in the subsampling technique used in the study (neck, funnel and face glass were all tested separately) led to an underestimate of lead leachability. Additional testing showed that the glass frit used to seal the face to the funnel, and which has a very high total lead concentration, was undersampled. The investigators concluded that CRT subsampling that included a representative amount of the frit would have resulted in all 30 of the color CRTs exceeding the TC regulatory value of 5 mg/l in the TCLP.

[3] *www.ees.ufl.edu/homepp/townsend/Research/ElectronicLeaching/default.asp.*

monitors [4] was 47.7 mg/l. These levels are considerably above the toxicity characteristic regulatory level of 5 mg/l that is used to classify lead-containing wastes as hazardous (40 CFR 261.24(b)). This result is not surprising because CRT glass generally accounts for over 60 percent of the weight of the monitor. The 2000 Musson *et al.* study also showed that for monochrome CRTs, the average lead leachate concentration was 0.03 mg/l. These data appear to indicate that black and white monitors do not generally fail the TC. Other hazardous constituents sometimes present in CRT glass are mercury, cadmium, and arsenic. However, these constituents are found in very low concentrations that are unlikely to exceed the TC concentration limits.

From 1994 through 1998, EPA's Common Sense Initiative (CSI) explored the environmental regulation of six industry sectors and looked for ways to make environmental regulation "cleaner, cheaper, and smarter". The CSI Computers and Electronics Subcommittee (CES) formed a workgroup to examine regulatory barriers to pollution prevention and electronic waste recycling. The workgroup explored the problems of managing mounting volumes of outdated computer and electronics equipment.

As a result of the finding of the CES Subcommittee, the CSI Council issued a document titled *Recommendation on Cathode Ray Tube (CRT) Glass-to-Glass Recycling.* In this document, the Council recommended streamlined regulatory requirements for CRTs to encourage recycling and better management. The recommendations included streamlined requirements for packaging, labeling, and transportation; general performance standards for glass processors; and export provisions. The CSI Council also recommended an exclusion from the definition of solid waste for processed glass that is used to make new CRT glass.

Since the recommendations of the CRT Council, the recycling of CRTs and CRT glass has evolved and various stakeholders have made occasional suggestions to the Agency about how to address changing practices.

IV. Rationale for This Rule and Response to Comments

A. Used, Intact CRTs Sent for Recycling

Used, intact CRTs are CRTs remaining within the monitor whose vacuum has not been released. In its June 12, 2002 notice, the Agency proposed to exclude these materials from the definition of solid waste, unless they were disposed. These materials, when sent for recycling, would not have been subject to regulation under RCRA Subtitle C, including the speculative accumulation limits of 40 CFR 261.1(c)(8) (see also 40 CFR 261.2(c)(4)). Under the proposal, used, intact CRTs could therefore have been held for long periods of time without being considered abandoned and thereby becoming solid wastes.

EPA determined that intact CRTs are highly unlikely to release lead to the environment because the lead is contained in the plastic housing and the glass matrix (see 67 FR 40513). Because of this low likelihood of release, EPA proposed reduced requirements for used, intact CRTs by excluding them from the definition of solid waste. Unused CRTs are already considered commercial chemical products which are excluded from the definition of solid waste when recycled, even if they are reclaimed or speculatively accumulated (see 50 FR 14219, April 11, 1985). Used and unused intact CRTs are identical in appearance. Consequently, it would be difficult to distinguish between used and unused intact CRTs destined for recycling, and there appeared to be no environmental basis for such a distinction.

The Agency continues to believe that lead contained in used, intact CRTs is generally unlikely to be released to the environment. However, views expressed by commenters have led the Agency to change the proposed speculative accumulation requirements for these materials. Today's rule provides that used, intact CRTs are subject to the speculative accumulation requirements of 40 CFR 261.1(c)(8) if they are accumulated by glass processors or collectors (see 40 CFR 261.4(a)(23)(i)). Today's rule also modifies requirements applicable to used, intact CRTs that are exported. The export requirements are discussed in a separate section below. Following are the significant comments received, and our responses.

Response to Comments

Commenters were divided about imposing speculative accumulation requirements on used, intact CRTs. Some commenters supported our proposal to impose no accumulation limits on intact CRTs. These commenters claimed that intact CRTs being recycled were more commodity-like than waste-like, and that there is virtually no possibility of environmental releases from intact CRTs. One commenter said that intact CRTs are likely to be stored in containers or buildings, at least while they have resale value.

Other commenters, particularly States, wanted to subject used, intact CRTs to the speculative accumulation provisions because they were concerned about the possibility of abandonment. However, one commenter stated that this problem might be better addressed under state solid waste authorities than under federal law.

The Agency agrees with those commenters who expressed concern about potential abandonment of used, intact CRTs, particularly by glass processors and by persons who collect CRTs for recycling. Although broken CRTs and processed CRT glass are likely to pose a greater immediate risk of environmental releases, we believe that this possibility also exists for intact CRTs that are stored for long periods of time, particularly if a collector of such materials abandons them instead of sending them for recycling. Such indefinite storage, in the Agency's view, indicates that the materials are waste-like rather than commodity-like in nature.

EPA has also reconsidered its earlier statement that it is very difficult to distinguish between unused and used intact CRTs. The two types of materials are not normally stored together. Unused intact CRTs are generally returned to the manufacturer by consumers or retailers, after which they are sent directly to recyclers. Prolonged storage of unused intact CRTs by consumers, retailers, or manufacturers is unlikely.

Nor do we agree with the commenter who stated that speculative accumulation is better addressed by state solid waste authorities, rather than

[4] The data in this study were generated using a modified version of EPA's TCLP. The authors used a modified TCLP because standard TCLP particle size reduction and waste subsampling for debris-like materials can pose difficulties. In the "Large Scale Leaching Procedure," the computer monitor or television was disassembled and all the parts placed in a large leaching vessel without particle size reduction. Other aspects of the standard TCLP test design (e.g., the 20:1 liquid-solid ratio) were maintained. Particle size reduction is intended to simulate the physical breakdown of wastes over time, and also facilitate achieving equilibrium in an 18-hour leaching period. Such reduction typically increases the leaching of metals in the TCLP, because it increases the surface area exposed to the leaching fluid. However, Townsend showed earlier in this same paper that when the waste contains a significant amount of iron, particle size reduction facilitates iron oxidation and the formation of binding sites on the iron. These oxidized iron binding sites adsorb metals from the leaching solution and can result in lower leaching of metals in the TCLP. However, the CRTs from computers and color televisions contained only small amounts of iron (3% and 6% of the total, respectively) and the authors concluded that the presence of the iron was not a significant factor in the overall results. The Agency agrees with these conclusions. We note that the regular, unmodified TCLP is still the legal standard for classifying materials as hazardous wastes.

federal law. Some state definitions of solid waste are based on the federal definition, and these States would find it more difficult to use their authorities to require removal of abandoned CRTs.

For these reasons, today's rule imposes the speculative accumulation requirements of 40 CFR 261.1(c)(8) on collectors of CRTs and glass processors (see 40 CFR 261.(a)(23)(i)). Speculative accumulation requirements also apply to used CRTs that are exported for recycling (see 40 CFR 261.4(a)(23)(ii) and 261.40)).

However, we are not imposing speculative accumulation requirements on persons who use computers or televisions and then send the intact CRTs to collectors and glass processors. Such persons are not likely to accumulate CRTs in circumstances that will lead to environmental releases, nor is there an economic incentive for them to store intact CRTs indefinitely. Because of the new speculative accumulation requirement, we have also added a definition of "CRT collector" to 40 CFR 260.10 ("a person who receives used, intact CRTs for recycling, repair, resale, or donation").

B. Used, Broken CRTs Sent for Recycling

Labeling and Storage

Some users and collectors of CRTs separate the CRT from its housing and release the vacuum. They then send the monitor with its broken glass to a recycler (often a glass processor). This practice saves shipping costs and enables the glass processor to pay more for the broken CRTs received. At other times, the CRTs are first broken by the processor or other recycler. CRTs whose glass has been broken by releasing the vacuum are non-reusable and non-repairable and therefore could potentially be solid wastes at the time such breakage occurs.

In the proposal, EPA proposed to add a new section (40 CFR 261.39(a)) which provided that used, broken CRTs sent for recycling would not be solid wastes if they were stored in a building with a roof, floor, and walls, or if they were stored in a container (*i.e.*, a package or a vehicle) which was constructed, filled, and closed to minimize identifiable releases of CRT glass (including fine solid materials) to the environment. The containers were to be labeled or marked clearly with one of the following phrases: "Waste cathode ray tube(s)—contains leaded glass," or "Used cathode ray tube(s)—contains leaded glass." The containers must also be labeled "do not mix with other glass materials." When transported, the broken CRTs would have had to be in a container meeting the conditions described above. Used, broken CRTs destined for recycling could not be speculatively accumulated as defined in 40 CFR 261.1(c)(8).

The Agency stated that, if these materials are properly containerized and labeled when stored or shipped prior to recycling, they resemble articles in commerce or commodities more than wastes. Breakage is a first step toward recycling the leaded glass components of the CRT. Also, materials held in conditions that safeguard against loss are more likely to be valuable commodities destined for legitimate recycling. In addition, the proposed packaging requirements would ensure that the possibility of releases to the environment from the broken CRTs is very low. For these reasons, an exclusion from the definition of solid waste was considered appropriate if the broken CRTs were handled under the conditions proposed.

The Agency has decided to promulgate the regulations applicable to storage and labeling of used, broken CRTs substantially as proposed. EPA has determined that used, broken CRTs are not solid wastes if they are sent for recycling within the United States under the conditions specified in 40 CFR 261.39(a)(1)–(4). However, the Agency has made certain modifications to the proposed conditions in response to comments received. These changes are described below. Today's rule also modifies the proposed requirements applicable to used, broken CRTs that are exported. The export requirements are discussed in a separate section below, along with requirements for imports.

Response to Comments

Several commenters suggested changes to our proposed labeling requirements for used, broken CRTs being transported or stored. Some commenters wanted requirements which they believed were more accurate or specific than the ones proposed. For example, under our proposal, processed glass going to certain types of recycling would have to be packaged and labeled identically to used, broken CRTs (see proposed 40 CFR 261.39(d), 47 FR 40525). One commenter pointed out that processed glass can no longer be considered a "cathode ray tube." This commenter therefore suggested that applicable labeling requirements for processed glass be changed to "processed cathode ray tube glass" or "glass removed from cathode ray tubes." Similarly, another commenter stated that used broken CRTs may be in such small pieces that the materials might not be recognizable as "cathode ray tubes." This commenter suggested that a useful alternative requirement (which could be used in addition to our proposed language) would be to label containers of broken CRTs with the phrase "leaded glass" and some indication of the source of the glass—e.g., "leaded glass from televisions." Another commenter pointed out that one of our proposed alternative labeling phrases ("waste cathode ray tubes—contains leaded glass") was not necessary, since the cathode ray tubes would not be wastes if they were packaged and labeled in accordance with the regulations.

The Agency agrees that these suggestions are more accurate than our proposed regulations, and has modified the final rule accordingly. Section 261.39(a)(2) of today's rule specifies that each container in which a used, broken CRT is contained must be labeled or marked clearly with one of the following phrases: "used cathode ray tubes—contains leaded glass" or "leaded glass from televisions or computers."

One commenter urged complete flexibility in labeling requirements. Another suggested that the Agency not specify the exact wording of labels in the regulations, but instead should require that contents be "marked with words that identify the contents of the containers." This latter commenter believed that labelers would then have more discretion and would not be subject to enforcement actions for failing to use the precise words specified in the regulations.

The Agency does not agree with these comments. Requiring no specified words or phrases for labeling in the regulations does not provide sufficient legal notice to either regulators or the regulated community, and could, if anything, lead to more enforcement actions than a precisely worded requirement.

Other commenters believed that several of our proposed requirements were unnecessary. For example, some commenters objected to EPA's proposed requirement that broken CRTs be stored either in a container or a building. One commenter believed that these materials should not be classified as solid wastes if they were stored on a concrete pad or the equivalent, since this practice should be adequate for a coarse solid material which is insoluble in water. Other commenters suggested replacing our proposed requirements with a requirement that storage of CRT glass must take place in "environmentally contained areas (water and particle containment)" or must be "stored in a manner that meets other environmental

regulations that control or limit release to the environment."

EPA disagrees with these comments. In the first place, storing broken CRTs outdoors prior to processing is inconsistent with the premise that these materials are commodity-like, because they can easily be damaged if exposed to excessive wind or moisture, unless they are packaged. Language requiring storage in "environmentally contained areas" is too vague to provide guidance to the regulated community on the measures required to ensure appropriate handling of commodity-like materials. Similarly, a requirement that materials be "stored in a manner that meets other environmental regulations" would be redundant, since they are required to comply with all applicable environmental regulations in any event. Therefore, the final rule does not contain these suggested requirements.

One commenter pointed out that containers holding used, broken CRTs may also hold other portions of electronic equipment such as the plastic housing that contains the CRT. This commenter requested that the Agency clarify that these other associated materials need not be segregated from CRTs during storage. We agree with this commenter that such segregation was not our intent and the rule does not require such segregation.

Speculative Accumulation

In our June 12, 2002 notice, we proposed to require that used, broken CRTs and processed CRT glass be subject to the speculative accumulation provisions of 40 CFR 261.1(c)(8). These provisions generally specify that materials are speculatively accumulated, unless 75 percent of the materials (calculated by weight or by volume) are recycled within a calendar year. We inquired whether a longer accumulation period (such as two or more years) should be provided for CRTs to allow recycling markets to grow, especially since there appeared to be few environmental concerns with storage if these materials are properly packaged and labeled. After evaluating comments received on this issue, we have decided to finalize the speculative accumulation requirements as proposed for used, broken CRTs and processed CRT glass. The comments received, and our responses, are described below.

Response to Comments

Some commenters (principally states) supported the current speculative accumulation provisions for broken CRTs (or, in some cases, the one-year accumulation period of the universal waste rule). These commenters were concerned about the possible environmental effects of a longer accumulation time, and generally believed that the one-year time frame allowed in 40 CFR 261.1(c)(8) was enough to accumulate sufficient quantities for recovery and find outlets for recycling.

Other commenters (generally representing industry) supported extending speculative accumulation requirements for broken CRTs. Some supported extensions of two or more years, and a few wanted no limits at all. These commenters argued that longer time limits would allow persons handling used CRTs to accumulate the materials in larger numbers, which would make shipping less expensive. They also believed that extended speculative accumulation times would allow markets to develop more fully, thus encouraging recycling.

EPA agrees with those commenters who stated that markets are likely to increase for CRT glass. Although some commenters were concerned about lack of markets, these commenters did not submit quantitative data that would be sufficient, in the Agency's view, to justify treating these materials differently from other materials that are excluded from the definition of solid waste on condition that they not be speculatively accumulated. We note that markets for all of these materials frequently fluctuate. For these reasons, we believe that used broken CRTs and processed CRT glass should be subject to the usual requirements that they not be speculatively accumulated.

One commenter suggested extending the speculative accumulation period for processed glass, stating that processed glass must sometimes be stored at glass manufacturing facilities for long periods of time due to the lack of current need for glass with the particular lead content found in the stored glass. However, another commenter supported the use of variances under 40 CFR 260.30(a) to extend accumulation times when necessary for persons developing new glass technologies. We agree with this commenter. Such variances are available on a case-by-case basis if the applicant can demonstrate that sufficient amounts of the material in question can be recycled or transferred for recycling within the following year. The variances can be renewed annually by filing a new application. We note that these variances are available not only to glass processors and to persons developing new glass technologies, but also to any person storing used CRTs who needs additional storage time. Because they are site-specific and allow individual circumstances to be taken into account, the variances are more appropriate than an extension covering many different kinds of facilities.

One commenter stated that since most facilities will rarely encounter broken CRTs, it would be burdensome to try to distinguish them from intact CRTs; therefore, they should be subject to the same speculative accumulation requirements. EPA does not agree with this commenter. If CRTs are to be recycled, they must be broken at some point in order to be disassembled. Nor is it difficult to determine visually whether the vacuum tube on a CRT has been released. In any event, we note that the importance of distinguishing between broken and intact CRTs is not relevant for purposes of speculative accumulation, since under today's rule both are subject to the requirements of 40 CFR 261.1(c)(8).

Another commenter stated that the purpose of the original speculative accumulation provisions was to alleviate concerns about sham recycling and to provide a way to determine storage periods and turnover rates for materials that did not have well-defined markets. Since there are current markets for CRT glass, this commenter reasoned that the speculative accumulation provisions should not apply to these materials. We disagree with this commenter; the speculative accumulation provisions have never been limited to materials with particular types of markets. In any event, markets for most commodities usually change over time.

A few commenters suggested a period shorter than one year for accumulation of used CRTs. Two commenters said that 180 days should be sufficient to allow CRTs to be recycled, and that longer periods could encourage sham operations. These commenters who suggested shorter accumulation times, such as 180 days, did not submit data indicating that CRTs could be effectively recycled in such a short time period. Therefore, we are not adopting these suggestions.

EPA notes that a few commenters may have been confused about the relationship between the current speculative accumulation provisions and the classification of CRTs as solid wastes. The speculative accumulation provisions apply to materials that are not solid wastes at the beginning of the accumulation period; if they are not recycled in sufficient quantities within the specified period, they become solid wastes (and, if they are hazardous waste, subject to all applicable Subtitle C requirements). If used CRTs were classified as spent materials as soon as they were taken out of service, they

would instead be subject to the shorter accumulation times (90 or 180–270 days) allowed for generators of hazardous wastes pursuant to 40 CFR 262.34, rather than the one-year period allowed under 40 CFR 261.1(c)(8).

Use Constituting Disposal

In our June 12, 2002 notice, we proposed a condition prohibiting land placement of processed CRT glass, unless it met the use constituting disposal requirements of Part 266, Subpart C. We solicited comment on whether to impose the same prohibition on broken CRTs as well. We asked for information about the current uses for broken CRTs or processed CRT glass that involved use constituting disposal. We received very little data on this issue, although a few commenters mentioned the use of processed glass in road building materials. Because we have no information about this practice that would justify distinguishing it from use constituting disposal of processed CRT glass, today's rule imposes the same prohibition on both kinds of materials (see 40 CFR 261.39(a)(4) and (d)). We also note that for materials to be used in a manner constituting disposal, such recycling must be legitimate rather than a form of treatment. For guidance in determining such legitimacy, see the Memorandum entitled "F006 Recycling" from Sylvia K. Lowrance to Hazardous Waste Division Directors, April 26, 1989.

C. Used CRT Processing

Requirements for CRT Processors

The Agency also proposed an exclusion from the definition of solid waste for used CRTs undergoing glass processing, if certain conditions were met (see proposed 40 CFR 261.39(b)). CRT glass processing was defined in proposed 40 CFR 260.10 as the receiving of intact or broken used CRTs, intentionally breaking them, sorting or otherwise managing glass removed from CRT monitors, and cleaning coatings from the glass. CRT users and collectors sometimes break CRTs before sending them to a processor. Therefore, under the proposal, breaking used CRTs would not by itself subject a facility to the CRT glass processing conditions. In order to be classified as a CRT glass processor, the facility would have to perform all of the enumerated activities.

Under the proposal, used, broken CRTs undergoing glass processing would not have been solid wastes if they were stored in a building with a roof, floor, and walls. If they were not stored inside a building, they would have to be packaged and labeled under conditions identical to those proposed for used, broken CRTs prior to processing, including the prohibition on speculative accumulation. All glass processing activities would have to be conducted in a building with a roof, floor, and walls. In addition, no activities could be performed during glass processing that used temperatures high enough to volatilize lead from CRTs.

The CSI Council had recommended that glass processors install and maintain systems sufficient to minimize releases of glass and glass particulates via wind dispersal, runoff, and direct releases to soil. We solicited comment in the proposal on whether to require additional performance standards for glass processors. However, we did not propose the general performance standard recommended by the CSI Council, citing the Council's statement that storing broken CRTs and CRT glass in buildings or closed containers (as we proposed) were examples of ways to control wind dispersal, runoff, and direct releases to soil.

We also did not propose the CSI Council recommendation that glass processors implement a procedure for advising local communities of the nature of their activities, including the potential for resident and worker exposure to lead or chemical coatings. We stated our belief that matters of local notice and public participation are generally best decided at the state, county, or municipal level. However, we solicited comment on whether to require such procedures under federal regulations in the case of CRT recycling, and the reasons why these procedures would be needed.

EPA stated, at the time of proposal, that the conditions proposed for used, broken CRTs being processed indicate that the materials in question are more commodity-like than waste-like. Used, broken CRTs that are not managed in accordance with these requirements would not be valuable, product-like materials. The opportunity for loss or releases of the materials would indicate that they are wastes. As specifically recommended by the CSI Council, we also proposed that processors be required to conduct their activities without using temperatures high enough to volatilize lead from broken CRTs. Besides increasing the risk of releases to the environment, such practices could be a sign of waste management rather than production.

EPA has determined that used, broken CRTs being processed under these conditions resemble commodities more than wastes. For this reason, we are finalizing these conditions substantially as proposed. However, we have revised some of our proposed language in response to comments received. Significant comments, our responses, and the changes are discussed below.

Response to Comments

Several commenters believed that our proposed temperature requirement was unnecessary, noting that workers' exposure to lead was already covered by OSHA requirements at 29 CFR part 1910, and that a high temperature (or thermal processing) is not by itself an indication that waste management is occurring. Several commenters stated that lead volatilization and other lead releases would also be covered by applicable provisions of the Clean Air Act and the Clean Water Act. Other commenters supported the proposed temperature requirements, in part because they believed that use of high temperature requirements are in fact an indication of waste management. Some commenters asked EPA to specify a particular temperature, beyond which processing would be prohibited.

EPA agrees with those commenters who believed that CRT processing conducted with high temperatures may indicate waste management, because high temperatures are more likely to release lead and other contaminants into the environment, thereby leading to possible loss of materials. Such waste management could occur even if OSHA requirements apply. We are therefore retaining our prohibition on using temperatures high enough to volatilize lead, as proposed. However, we are not adding a specific temperature to the prohibition because the relevant scientific literature reveals differing temperatures for volatilization of lead, possibly depending on various conditions (see, e.g., Volatilization Studies of a Lanthanide Lead Borosilicate Glass, WSRC–MS–98–00240, R.F. Schumacher, D.S. McIntyre, D.K. Peeler, J.M. Parteizs; [5] and Effect of Heating on the Sintering Behavior and the Piezoelectric Properties of Lead Zirconate Titnate Ceramics, Jungho Ryu, Jong-Jin Choi, and Hyoun-EeKim, Journal of the American Ceramic Society, Vol. 84, No. 4, pp. 902–904, April 2001). We therefore believe that this requirement is more appropriately expressed as a performance standard than as a numeric value.

Some commenters mistakenly thought that the proposed temperature requirement would apply to "end users" of recycled CRT glass such as glass furnaces or smelters. One commenter

[5] *http://sti.srs.gov/fulltext/ms9800240/ms9800240.html.*

asked EPA to impose a performance standard on both CRT processors and glass manufacturers (and presumably smelters as well) that would ensure that no temperatures would be employed that released toxic metals into the work environment or the surrounding air. Another commenter suggested requiring that CRT processors be required to monitor for fugitive emissions of lead, silica, and mercury. The Agency does not agree with those commenters who suggested additional requirements for glass manufacturers and smelters, or emissions monitoring for CRT processors. EPA did not solicit comment on any of these measures and they are inappropriate for commodity-like materials. They could also be duplicative of requirements that are already applicable under OSHA, the Clean Air Act, the Clean Water Act, and RCRA.

One commenter stated that EPA's proposed requirement that CRTs undergoing processing be stored (unless packaged) in a building "with a roof, floor, and walls" could lead to placing CRTs in locations with inadequate containment. This commenter suggested replacing the Agency's proposed requirement with a provision calling for "storage within a permanently constructed building consisting of at least a roof and three walls permanently affixed to an impermeable floor placed on the ground."

We remain unconvinced that such requirements are necessary for buildings where CRTs are processed. For example, it is not clear that CRT processing would pose environmental risks (or that CRTs would be handled as wastes instead of commodities) if such processing work took place in a temporary building, since no liquids are involved in the processing. We also note that spills or releases would in any event be considered solid wastes.

One commenter disagreed with EPA's statement in our proposal that persons who break CRTs before sending them to processors should not be subject to our proposed conditions for CRT glass processing. Breaking CRTs and separating components constitute reclamation and should require a permit, according to this commenter.

EPA disagrees that breaking CRTs and separating components should require a permit. These actions may be performed by almost anyone sending a CRT to a recycler. The requirements of 40 CFR 261.39(a) concerning storage, transportation, labeling, and speculative accumulation are adequate to ensure that broken CRTs are handled as commodities; there is no need to impose other subtitle C requirements required under 40 CFR parts 264 and 265. Nor is there a need to subject persons who merely break CRTs to the provisions concerning high temperature activities. The Agency does not necessarily disagree with the commenter that breaking CRTs and separating the components constitutes reclamation. Nevertheless, when a person receives broken CRTs that are packaged and labeled in accordance with today's rule, the materials are commodity-like and the person or facility in question should not have to comply with the provisions of a hazardous waste storage permit. Moreover, EPA generally does not regulate reclamation processes themselves. States are of course free to impose more stringent requirements if they believe such requirements are justified.

Some commenters urged that EPA impose environmental management standards, emissions and ventilation standards, notification requirements, recordkeeping and tracking of wastes, employee training, and worker health and safety protections. Some of these commenters suggested that these requirements should also be applicable to persons sending CRTs for recycling, as well as processors. Some suggestions were substantially identical to certain practices required under the universal waste rule, such as employee training, container standards, notification, and tracking. Other commenters, however, suggested requirements that were much more stringent than those applicable to universal waste handlers. For example, a few commenters said that additional worker health and safety provisions were needed under our rule, and one commenter expressed concerns that the OSHA permissible exposure limits (PELs) at 29 CFR part 1910 do not apply to handlers of materials that are not solid wastes.

We have responded elsewhere in this notice to those commenters who argued that the Agency should impose the universal waste requirements of notification, tracking, and employee training on CRT processors. With respect to OSHA requirements, we disagree with the commenter who said that the worker health and safety provisions of that statute do not apply to people handling materials that are not solid wastes; the permissible exposure limits (PELs) of section 1910 of the OSHA regulations are not tied to EPA's RCRA definitions. Additional worker health and safety requirements are not necessary.

Some commenters, on the other hand, believed that several of our proposed requirements were unnecessary. For example, some commenters objected to EPA's proposed requirement that broken CRTs be stored either in a container or a building. One commenter believed that these materials should not be classified as solid wastes if they were stored on a concrete pad or the equivalent, since this practice should be adequate for a coarse solid material which is insoluble in water. We continue to believe, however, that storing broken CRTs outdoors prior to processing is inconsistent with the premise that they are commodity-like, since they can easily be damaged by excessive moisture or wind unless they are packaged. The same is true for processing CRTs outdoors, even if the processing takes place on a concrete pad. However, we note that under today's rule, intact CRTs may be stored on concrete pads or on the ground without packaging and labeling (see 40 CFR 261.4(a)(23)). In the case of intact CRTs, packaging or storage in a building is generally not necessary to minimize releases to the environment, since the CRTs are contained in their housing. However, if prolonged storage outdoors renders the CRTs unfit for recycling, they would become solid wastes, subject to full Subtitle C regulation provided they were also hazardous wastes. In addition, the exclusion in today's rule does not affect the obligation to respond to and remediate any releases of hazardous wastes that may occur.

Other commenters suggested replacing our proposed requirements with a requirement that processing and storage of CRT glass must take place in "environmentally contained areas (water and particle containment)" or must be "stored in a manner that meets other environmental regulations that control or limit release to the environment." EPA disagrees with this suggestion because requiring processing to be conducted in "environmentally contained areas" is too vague to provide guidance to the regulated community on the measures required to ensure that they are handled in a commodity-like manner. Similarly, a requirement that materials be "stored in a manner that meets other environmental regulations" would be redundant, since they are required to meet other applicable environmental regulations in any event.

With respect to public notice requirements (which we did not propose), many commenters argued that such notice for CRT processing operations should be conducted pursuant to pre-existing state and local requirements, and should not be imposed as a function of our proposed conditional exclusion. Some commenters pointed out that local notice and public meetings are governed

by various state or local requirements concerning siting, zoning, or licensing. They believed that matters of local notice and public participation are generally best decided at the state, county, or municipal level. One commenter pointed out that additional opportunities for public involvement are also afforded under existing federal laws, such as the Emergency Planning and Community Right-to-Know Act and, in the case of potential worker exposures, the Occupational Safety and Health Act. This commenter feared that imposing additional requirements for public notice could increase costs for CRT processors, thereby undermining the goal of CRT recycling.

Other commenters, however, supported the CSI Council recommendation that glass processors be required to notify local communities of their activities. They thought that a federal public notice requirement was important for the health and well-being of communities that house CRT glass processors. They also believed that workers at these facilities should know of any health or safety risks involved with their daily activities. One commenter stated that it was not sufficient to defer to local authority to provide notice, and that such notice was a federal responsibility that must be retained.

In response to these comments, EPA continues to believe that federal public notice requirements for CRT recycling are unnecessary. In general, we have not mandated such requirements for hazardous waste recycling facilities, unless they obtain RCRA permits for storage of hazardous waste prior to recycling. Since glass processors are managing materials that are commodity-like if handled pursuant to today's conditions, it would be inappropriate to impose the same public notice requirements that are imposed on facilities that store hazardous wastes. In addition, the public may learn of these facilities through other notices or filings at the state, county, or municipal level.

Some commenters appeared to believe (incorrectly) that our proposal would have required processed glass to be packaged or stored in a building. However, we note that under the proposal (and under today's final rule) processed CRT glass sent to a CRT glass manufacturer or to a lead smelter would not have to be either packaged or stored in a building (see 40 CFR 261.39(c)). Under today's final rule, processed glass sent to other kinds of recycling need not be packaged or labeled if it is legitimately reused as an effective substitute for a commercial chemical product (this exclusion is explained further later in today's notice).

Even though we are not significantly modifying our proposed requirements for glass processors, we believe that some of our proposed language could benefit from clarification. We are therefore revising some of this language. First, we note that the proposed storage requirements for broken CRTs prior to processing (storage in a building or in a properly labeled container) would also have applied under our proposal to CRTs actually undergoing processing. This application was not our intent because CRTs cannot physically remain in a container while being processed. Therefore, we are revising proposed 40 CFR 261.39(b) to remove the reference to labeling and placement in a container. Used broken CRTs undergoing processing need only be stored in a building, and may not be speculatively accumulated.

Second, we note that one of the activities encompassed in today's definition of "CRT processing" at 40 CFR 260.10 ("receiving broken or intact CRTs") generally need not (and sometimes cannot) take place in a building. We are therefore removing our proposed requirement that all CRTs be "processed within a building." Instead, today's rule requires that "all activities specified in paragraphs (2) and (3) of the definition of "CRT processing" in 40 CFR 260.10 must take place within a building." This means that only breaking or separating CRTs, or sorting or otherwise managing glass removed from CRT monitors, must be performed in a building. Actual receipt of the CRTs may occur outside.

Exclusions for Processed CRT Glass

Under the proposal, processed glass from used CRTs would be excluded from the definition of solid waste if it were sent for recycling to a CRT glass manufacturer or a lead smelter (40 CFR 261.39(c)). If it were sent to any other kind of recycling, it would be excluded if it were stored, labeled, and transported similarly to used, broken CRTs (40 CFR 261.39(d)). In neither case could the processed glass be speculatively accumulated. If it were used in a manner constituting disposal, all processed glass from used CRTs would have to comply with the storage, labeling, and transportation requirements applicable to used, broken CRTs and the applicable requirements of 40 CFR part 266, subpart C.

In the proposal, we explained that processed glass from used CRTs destined for a CRT glass manufacturer or a lead smelter meets the regulatory criteria in 40 CFR 260.31(c) for a variance from the definition of solid waste. Accordingly, the Agency decided that the resulting material is commodity-like and should be excluded from the definition of solid waste. In particular, the Agency tentatively found that processed CRT glass sent to glass manufacturers or lead smelters needs minimal further processing and has economic value and strong end markets. We also found that processed CRT glass is similar to materials that glass manufacturers and lead smelters use as feedstock, and that it is handled to minimize loss. For a more complete discussion of these criteria and the Agency's findings, see the proposal at 67 FR 40514. As noted below, no comments on these findings have caused the Agency to change them, so we are adopting them as final. We also believe that recycling CRT glass at lead smelters appears to be just as legitimate as glass-to-glass recycling, and that an exclusion for this material could turn out to be useful if the growing use of flat screens decreases the potential for glass-to-glass recycling.

The Agency solicited comment on whether processed glass destined for lead smelters should be eligible for the exclusion. Processed glass is sent to lead smelters for reclamation of lead and also for use as a flux agent (to promote fusing of metals or to prevent the formation of oxides). The Agency also solicited comment on whether to exclude processed glass from the definition of solid waste without packaging and labeling requirements if it were sent to copper smelters for use as a flux agent. In addition, we solicited comment on an identical exclusion for processed glass sent for recycling into other glass materials, such as optical beads, decorative objects, radiation shielding materials, and acoustic barriers. We requested information from commenters about whether processed CRT glass sent for these glass uses or to copper smelters was commodity-like.

After evaluating all comments received, the Agency is retaining our exclusion for processed CRT glass sent to glass-to-glass manufacturers and lead smelters as proposed. Processed glass sent to copper smelters and other glass uses is not a solid waste if it is legitimately used or reused without reclamation as an effective substitute for a commercial product, or as an ingredient in an industrial process to make a product pursuant to 40 CFR 261.2(e)(1)(i) or (ii)). Processed glass sent for any of these types of recycling may not be speculatively accumulated. If it is used in a manner constituting disposal, all processed glass from used CRTs must comply with the storage,

labeling, and transportation requirements applicable to used, broken CRTs and the applicable requirements of 40 CFR part 266, subpart C. In order to be eligible for today's exclusion, importers of processed glass from used CRTs must comply with these requirements as soon as these materials enter the United States.

The significant comments received on this issue and our response to them are described below.

Response to Comments

Commenters who addressed the issue of CRT glass sent to lead smelters generally supported our proposed exclusion from the definition of solid waste for processed glass sent to this destination (without packaging and labeling requirements). These commenters thought that CRT glass sent to lead smelters (for reclamation and use as a flux agent) is commodity-like. Because the Agency agrees with these comments, and for the reasons stated in the proposal (see 67 FR 40514), we find that processed CRT glass is commodity-like and we are finalizing the exclusion at 40 CFR 261.39(c) as proposed.

One commenter believed that the Agency should allow processed glass to be sent to glass manufacturers or lead smelters without any conditions, including those for speculative accumulation. This commenter noted that processed glass sent for these uses already fit the criteria for a "partially reclaimed" variance from the definition of solid waste under 40 CFR 260.31(c); hence, no conditions should be required. The Agency disagrees with this commenter. Even if the processed glass meets the criteria for the variance in question, the speculative accumulation requirement is necessary to ensure that the materials are actually recycled and not abandoned. We also note that the conditions under which such variances are granted are site-specific and vary according to circumstances. They frequently include conditions relating to storage and land disposal.

A few other commenters believed that our proposed exclusions for processed CRT glass were unnecessary, since processed glass sent to a lead smelter is used directly as an ingredient in a production process, and would therefore qualify for the use/reuse exclusion at 40 CFR 261.2(e). Alternatively, they said that if reclamation is required, the glass would be a characteristic by-product destined for reclamation, which again would not be a waste, unless speculatively accumulated (see 40 CFR 261.2(c)(3) and (4)).

Although the Agency has not specifically addressed the regulatory status of processed CRT glass sent to smelters, we note that these commenters' interpretations do not appear to be consistent with previous regulatory interpretations or with regulatory definitions (see the Response to Comment document in the rulemaking record for further discussion of the regulatory interpretations and definitions). In any event, the more specific regulatory exclusions promulgated today for CRT glass provide greater clarity to the regulated community than the more general provisions cited by the commenter.

Some commenters, on the other hand, objected to allowing CRT glass to go to smelters without additional controls. One commenter cited financial and environmental problems caused by smelters located in the commenter's state, and another believed that CRT glass should be restricted from going to smelters because it could lead to an increase in lead air emissions or lead content in the slag from these facilities.

EPA does not agree with the commenter who cited general concerns about smelters as a rationale for restricting processed CRT glass sent to these facilities. The commenter was concerned about financial and environmental problems caused by smelters in one state and did not tie these concerns to the use of processed CRT glass. EPA believes that these concerns are outside the scope of this rulemaking, and that they should be addressed, if necessary, in the context of rulemakings applicable specifically to smelters.

Many commenters supported allowing a similar exclusion for processed glass sent to copper smelters. They pointed out that such glass is used as a flux agent in a very similar manner at copper smelters, and that it seems unjustified to impose different conditions on materials destined for virtually identical uses. One commenter noted that at least one copper smelter has product specifications for recycled flux materials spelled out in its authority to operate issued by the relevant government agency. The specification includes a minimum flux value and maximum contaminant level. The commenter stated that CRT glass met these criteria.

Another commenter pointed out that virgin copper concentrate already contains approximately 1% lead. Therefore, lead is a constituent that is already present in the copper smelting process and is already being managed in process residues. According to this commenter, the use of processed CRT glass will not significantly increase the amount of lead already resulting from the copper smelting process and being managed in the slag or air pollution control sludge.

Some commenters were also concerned about the capacity of CRT glass manufacturers to absorb the large volume of CRT glass that is generated in this country. They urged the Agency to take this concern into account and encourage recycling by allowing similar exclusions for processed CRT glass sent to glass manufacturing, lead smelting, or copper smelting.

The Agency agrees with those commenters who pointed out that the degree of processing that is required for use in a copper smelter appears to be the same as that required for use in a lead smelter. The economics also may be similar for fluxes used in both kinds of smelters. Processed glass is composed mainly of silica, which is useful as a flux, although lead is not recovered when CRT glass is used as a flux at a copper smelter. Nevertheless, the Agency has been unable to confirm that CRT glass is accepted at actual copper smelters. For this reason, we cannot currently make a finding that CRT glass sent to copper smelters is commodity-like, and we are not finalizing our proposed exclusion. However, we note that if the processed CRT glass were legitimately used or reused without reclamation as an effective substitute for a commercial product (i.e., as a flux agent), it could be excluded as an effective substitute for a commercial product under 40 CFR 261.2(e)(ii) (see letter from Michael Shapiro to Christian Richter of the American Foundrymen's Society, March 8, 1995).

With respect to processed CRT glass sent for recycling into other glass uses, commenters were divided. Some believed that these uses were likely to be commodity-like; others disagreed. Commenters submitted very little data about these uses. Since the Agency has at present very little information about their status as commodities, we are not finalizing our proposed exclusion. However, similarly to the case of processed glass sent to copper smelters, if the glass is legitimately used or reused as an effective substitute for a commercial chemical product, or used as an ingredient in an industrial process to make a product (provided the materials are not being reclaimed), it could be excluded from the definition of solid waste under 40 CFR 261.2(e)(i) or (ii).

D. Exports and Imports

Under the June 12, 2002 proposal, exporters of used CRTs for reuse or

recycling would not have been required to submit any notifications prior to export. Processed glass imported into the United States would be excluded if it complied with the proposed conditions. Because the imported processed glass would not be a hazardous waste if it met the conditions of the exclusion, it would not be subject to the hazardous waste import requirements of subpart F of 40 CFR part 262. The CSI Council had recommended that entities exporting CRT and CRT glass be subject to various notice and consent provisions, depending on whether the CRT glass was coated or uncoated and on the destination of the materials (for a complete description of the CSI recommendations, see the proposal at 67 FR 40516). For example, the CSI Council recommended that CRTs and coated CRT glass should be subject to the same notice and consent provisions as exporters of hazardous waste in subparts E or H of 40 CFR part 262.

In our proposal, the Agency stated its belief that we did not have legal authority to require notification under 40 CFR part 262, subparts E and H, or the authority to require additional notifications, for CRTs or CRT glass that were not solid wastes because they were in compliance with our proposed conditions. We noted that if used CRTs were added to the universal waste program, we would have the authority to require notification at least for exported broken CRTs. We solicited comment on whether the need for export notification requirements recommended by the CSI would warrant adding used CRTs to the universal waste program, and whether these requirements would be unduly burdensome.

EPA's proposal elicited many comments and some additional data on the export of CRTs for recycling. These comments and data convinced us that exported CRTs often are not handled as valuable commodities. For this reason, we have reconsidered our earlier position about imposing notification requirements on exports. Therefore, today's rule requires exporters of CRTs for recycling to comply with the notice and consent requirements that are similar to those found in 40 CFR part 262, subparts E and H for exports of hazardous waste. The rule also requires exporters of CRTs for reuse to submit a one-time notification to EPA. In order to be eligible for today's exclusion, importers of used, broken CRTs must comply with the packaging, labeling, and speculative accumulation requirements of 40 CFR 261.39(a)(1)–(4) as soon as the materials enter the United States.

The new export requirements, significant comments received, and our responses to the comments are described in more detail below.

Response to Comments

Many commenters who addressed this question expressed concern about exporting CRTs and other electronics for recycling, especially to developing countries. These commenters argued that our proposed rule would exacerbate the effects of market dynamics, lack of existing regulatory controls, and the absence of a domestic recycling infrastructure and would increase the amount of electronic waste that is shipped abroad and managed inappropriately (see also the report entitled Exporting Harm: The High-Tech Trashing of Asia, prepared by the Basel Action Network and the Silicon Valley Toxics Coalition, February 25, 2002). One commenter further argued that our proposal would prevent the growth of a domestic electronics recycling industry by making it easier to export electronics.

To address such concerns, some commenters suggested that the Agency adopt notice and consent procedures for exported CRTs similar to those currently found at 40 CFR part 262, subparts E and H for exports of hazardous waste. Some of these commenters said that EPA should impose notification requirements on exported CRTs as an additional condition of the exclusion from the definition of solid waste. They believed that the Agency has adequate authority to impose such conditions without adding these materials to the universal waste rule.

After evaluating these comments, the Agency has decided to impose notice and consent requirements as a condition of today's exclusion from the definition of solid waste on CRTs exported for recycling. The comments, and data submitted by the commenters, have convinced us that unfettered export of CRTs for recycling could lead to environmental harm. Information in the record shows that exported electronics may not be handled as valuable commodities in foreign countries. In fact, there is documentation that they are sometimes managed so carelessly that they pose possible human health and environmental risks from such practices as open burning, land disposal, and dumping into rivers. Notice and consent requirements mean that the receiving country will be informed of the proposed export, after which the country may consent or not, based on its analysis of whether the receiving facility can properly recycle the CRTs as commodities in an environmentally sound manner. EPA has therefore decided to ensure that the importing countries are able to consent (or withhold consent) when CRTs are proposed to be recycled within their borders.

EPA believes that sections 2002, 3002, 3007, and 3017 of RCRA provide authority to impose this condition, because used CRTs sent abroad are sufficiently waste-like to justify this requirement, and because notice and consent help ensure that the CRTs are not discarded. We have therefore reconsidered our earlier position (discussed in the preamble of our proposed rule at 67 FR 40516) about imposing notice and consent requirements on CRTs exported for recycling. EPA has the authority to ensure that CRTs exported for recycling are handled in a manner consistent with commodity-like status.

EPA considered simply requiring exporters of CRTs for recycling to comply with the current notice and consent requirements in 40 CFR part 262. These requirements, however, rely on the hazardous waste manifest and other Subtitle C provisions that EPA is not imposing on used CRTs. Consequently, we are promulgating separate (although very similar) export requirements that will apply exclusively to conditionally exempt CRTs exported for recycling. In addition, the notice and consent requirements promulgated today do not apply to processed glass that is exported, since there is no information available to us indicating that this material is not handled as a commodity when exported.

Under today's rule, used CRTs exported for recycling are not solid wastes provided the exporter notifies EPA and obtains a subsequent written consent forwarded by EPA from the receiving country. The provisions that we are promulgating today in 40 CFR 261.39(a)(5)(i)–(ix) and 40 CFR 261.40 require exporters of used CRTs destined for recycling (whether broken or intact) to notify EPA of an intended export 60 days before the initial shipment is intended to be shipped off-site. The notification may cover export activities extending over a 12 month or shorter period. The notification must include contact information about the exporter and the recycler, including any alternate recycler. The notification must include a description of the manner in which the CRTs will be recycled. It must also include the frequency and rate at which CRTs will be exported, the period of time over which they will be exported, the means of transport, the estimated total quantity of CRTs, and information

about transit countries through which the CRTs will pass. Notifications must be sent to EPA's Office of Enforcement and Compliance Assurance, which will notify the receiving country and any transit countries. When the receiving country consents in writing to the receipt of the CRTs, EPA will forward the written consent to the exporter. The exporter may proceed with shipment only after he has received a copy of the written consent from EPA. If the receiving country does not consent to receipt of the CRTs or withdraws a prior consent, EPA will notify the exporter in writing. EPA will also notify the exporter of any responses from transit countries. Exporters must keep copies of notifications and consents for a period of three years following receipt of the consent.

EPA has decided to require exporters of used, intact CRTs sent abroad for recycling to meet the same requirements as those applicable to exporters of used, broken CRTs. Although used, intact CRTs are more commodity-like than used, broken CRTs, they are more likely to be exported, and information in the record does not indicate that they are less likely to be discarded or handled as low-value materials abroad. We believe that used, intact CRTs are sufficiently waste-like when exported for recycling to be subject to a condition requiring notice and consent prior to export. Notice and consent help ensure that the CRTs are not discarded.

Some commenters urged EPA to forbid all exports of CRTs to developing countries. EPA does not agree with this suggestion because RCRA does not provide the authority to unconditionally ban exports of solid and hazardous wastes if the exporter complies with the existing regulatory requirements governing the export of these materials. We also disagree with this suggestion for practical reasons. Such a ban would prevent even the safe recycling of hazardous wastes abroad and would discourage resource recovery and reuse.

Some commenters believed that our proposed rule was inconsistent with various international agreements involving the export of hazardous waste. In particular, one commenter stated, the proposal is inconsistent with legal obligations under the treaty law of the Organization for Economic Cooperation and Development (OECD), the Basel Convention on the Control of Transboundary Movements of Hazardous Wastes and their Disposal, and the Stockholm Declaration. As noted above, the Agency is sympathetic to concerns about the potential risks of exporting CRTs for recycling. Therefore, to ensure that CRTs exported for recycling are handled in a manner consistent with commodity-like status, we are requiring that these materials be subject to the notice and consent requirements described in detail above. We believe that these requirements address most of this commenter's concerns. The Response to Comment document in the record to this rulemaking addresses these concerns in more detail.

Other commenters argued that notice and consent requirements, besides being unnecessary, were likely to discourage the export of CRTs for desirable recycling by making such export more burdensome. Another commenter noted that glass recyclers need to sell recovered CRT glass to developing countries, because the volume of obsolete CRT equipment will increase just as the domestic demand for CRT glass parts will be reduced because of new technology such as flat panel screens.

We disagree with those commenters who said that an export notification and consent requirement would be burdensome. The Agency estimates that these requirements will impose a burden of approximately four hours per year (on average) per respondent. We believe that this burden is not excessive especially since it helps ensure that exported CRTs are handled in ways consistent with an exclusion from the definition of solid waste. We also do not believe that these requirements will significantly affect the quantity of CRTs or CRT glass exported for recycling, since the relative amount of such materials recycled domestically and abroad depend principally on other economic factors.

One commenter suggested (in lieu of a notice and consent procedure) that EPA require exporters to keep records, such as shipping papers, that would allow tracking of CRT shipments or the amount paid by the shipper for the material. The Agency has rejected this approach because it would not give notice to the receiving country, nor would it give the country the opportunity to refuse consent to a shipment. It is therefore not sufficient to ensure that the material is treated as a commodity. The receiving country should be notified to help ensure that the CRTs will be recycled in an environmentally sound manner. Requiring an exporter to show evidence of payment would not involve the receiving country, and would thus not be a sufficient requirement.

The Agency notes that intact CRTs exported for reuse are identical in appearance to those exported for recycling. Consequently, to help ensure that the intact CRTs are actually reused abroad, we are requiring persons who export used, intact CRTs for reuse to submit a one-time notification to the Regional Administrator with contact information and a statement that the notifier plans to export used, intact CRTs for reuse. These notifications will allow regulatory authorities to contact the notifier, when appropriate, to ask for verification that the CRTs are exported for reuse instead of recycling or disposal. These persons must keep copies of normal business records demonstrating that each shipment of exported CRTs will be reused, and this documentation must be retained for three years from the date the CRTs were exported. Examples of normal business records include those that document the transfer of used equipment to the consignee for reuse, including name and address of the consignee, description of the shipment, and conformance with any product specifications, as well as the amount paid (if any) for the exported material. We believe that our right to require such basic notification is inherent in our authority to regulate discarded materials, and in our RCRA section 3007 authority to obtain information pertaining to materials that may become solid or hazardous wastes. Because a one-time notification is adequate to give the Regional Administrator notice about persons who are exporting for reuse, additional notifications are not necessary each time CRTs are exported for this purpose.

E. Universal Waste

In our June 12, 2002 notice, the Agency proposed a conditional exclusion from the definition of solid waste for used CRTs and CRT glass being recycled. However, we also solicited comment on the alternative approach of adding these materials to the universal waste rule. In particular, we requested comment on whether various universal waste requirements would be appropriate or burdensome for glass processors, or collectors who send used CRTs or CRT glass to these processors. The universal waste requirements in question were employee training, notification of universal waste management activities, and tracking of shipments sent and received. After evaluating all comments, the Agency has decided to retain the proposed conditional exclusion from the definition of solid waste for used CRTs and processed CRT glass, instead of adding these materials to the universal waste rule. Significant comments, our responses, and the rationale for the final rule are explained below.

Response to Comments

Some states and many industry commenters (such as those from the electronics industry) supported the proposed conditional exclusion and did not want EPA to add used CRTs to the universal waste rule. These commenters agreed with the Agency that used CRTs, when managed under the proposed conditions, resemble commodities more than wastes. They argued that adding CRTs to the universal waste scheme would harm the developing infrastructure for electronics recycling by imposing greater burdens and reducing flexibility. According to these commenters, classifying CRTs as hazardous waste would create a "stigma" that would make retailers or collectors reluctant to participate in recycling programs. One state said that adding used CRTs to the universal waste rule would make virtually any business with computers or televisions a potential hazardous waste generator, with negative implications for program implementation and enforcement.

They also believed that the universal waste requirements mentioned above were unnecessary for used CRTs because these materials pose minimal environmental risks. A few commenters feared that glass processors could be classified as "destination facilities" which could possibly need a RCRA storage permit, thereby frustrating CRT recycling goals. Finally, they questioned whether processed glass met the criteria for addition to the universal waste rule because it is not "widely generated."

On the other hand, other commenters, including several states, supported these requirements and suggested that EPA add used CRTs to the universal waste rule. These commenters generally noted that CRTs fit the regulatory criteria for universal waste at 40 CFR part 273, and cited the familiarity of stakeholders with this rule. Some of these commenters argued that keeping CRTs within the universe of hazardous waste would ensure better oversight by regulatory authorities than would a conditional exclusion from the definition of solid waste.

One commenter pointed to the significant amounts of lead contained in many CRTs, and disputed the Agency's assertion that leaded glass from CRTs resembled a commodity more than a waste. This commenter believed that the universal waste rule would ensure more responsible management of such a potentially harmful substance. In particular, this commenter urged imposing the requirements in the universal waste rule for employee training, release response, packaging, labeling, notification, and accumulation time limits. Some states were also concerned about speculative accumulation, and supported the one-year accumulation limit for universal waste. Others preferred the universal waste requirements because 40 CFR 273.17 and 273.37 require universal waste handlers to contain all releases.

According to several commenters, the streamlined requirements of the universal waste rule would also encourage recycling. One commenter believed that adding CRTs to the universal waste rule would facilitate improved voluntary management of CRTs from households or CESQGs, since the universal waste rule specifically allows wastes from these sources to be managed as universal wastes.

After considering these comments, EPA has decided to finalize the proposed conditional exclusion from the definition of solid waste for CRTs and CRT glass being recycled. We agree with the commenters who pointed out that intact or broken CRTs largely fit the regulatory criteria for universal wastes (see 40 CFR 273.81). For example, they are frequently generated in a wide variety of settings and are present in significant volumes in the municipal wastestream. Commenters are also correct that stakeholders are familiar with the universal waste scheme, although they are also quite familiar with the concept of conditional exclusions. However, we disagree with the commenter who implied that the presence of lead in CRT glass prevents this material from being commodity-like. As discussed elsewhere in this notice, there are demonstrated markets for CRTs and CRT glass, and it is generally the presence of lead that contributes to its value to glass manufacturers and smelters. An exclusion is more suitable for materials that resemble commodities more than wastes, especially if conditions are promulgated to ensure that they will be stored and handled as objects of value. In support of our decision, we note that many of the provisions of the conditional exclusion are similar to the provisions suggested by commenters, and recommended by the CSI for CRTs sent for recycling. For example, the packaging and labeling requirements for CRTs are nearly identical. In addition, we are also imposing notice and consent requirements for CRTs exported for recycling, as would be required under the universal waste rule.

Although some commenters believed that regulating CRTs sent for recycling under the universal waste program would ensure greater regulatory oversight, materials destined for the types of recycling addressed in today's rule do not need as much regulatory oversight as other waste materials because, when handled consistently with the specified conditions, they are commodity-like. Furthermore, the requirements of the universal waste rule for employee training, notification of waste management activities, and tracking of shipments are not necessary as a matter of federal law for these materials, when they are not being sent for disposal. The packaging and labeling conditions for broken CRTs that are promulgated today will ensure that the possibility of releases to the environment is very low. In addition, intact CRTs sent for recycling also pose a minimal risk of releases while being transported, since the glass is unlikely to be released unless the vacuum is broken. Lead from CRTs is therefore not readily available to the environment as long as the CRTs are intact. Similarly, we note that under today's rule, the speculative accumulation requirements of 40 CFR 261.1(c)(8) apply to used CRTs (whether broken or intact) and processed CRT glass. These requirements will be as effective in preventing extended accumulation periods as the accumulation limits of 40 CFR 273.15 and 273.35. In addition, processed CRT glass sent for many kinds of recycling is commodity-like. This material fits the criteria for the variance from the definition of solid waste for "partially reclaimed" materials under 40 CFR 260.30(c) and 261.31(c) (see the discussion of this issue in the preamble to our proposal at 67 FR 40514). This variance is specifically designed for commodity-like materials. We agree with the commenter who noted that processed glass does not actually fit the regulatory criteria for the universal waste rule (because it is not widely generated by different types of facilities) and that glass processors might technically be considered destination facilities under the universal waste rule (because they are recyclers).

Under the universal waste approach, CRTs destined for recycling would still be classified as hazardous wastes, although subject to reduced regulation. We agree with those commenters who argued that in the case of CRTs, this classification could discourage recycling. We are concerned that nonprofit organizations might refuse to help collect used CRTs because of this hazardous waste classification. Without their participation, CRT recycling would be greatly inhibited.

A few commenters also believed that adding CRTs to the universal waste rule

would alleviate the need for our proposed distinctions between used and unused or intact and broken CRTs. The Agency does not agree with these commenters. Adding used CRTs to the universal waste rule would not eliminate the need for these distinctions. Unused, intact computers and televisions are often returned to the manufacturer, or they may be sold or donated for use. Long-standing rules define unused materials as products rather than wastes, and products would not be subject to the universal waste rule. Similarly, even if intact and broken CRTs were added to the universal waste rule, the same universal waste requirements would not be appropriate for both categories of materials, since there is a greater possibility of releases from broken CRTs.

It is true that 40 CFR 273.17 and 273.37 require universal waste handlers to contain all releases. Under a conditional exclusion, on the other hand, if a person failed to respond to a release, EPA or the State could take action, including an enforcement action, which is a reactive rather than preventive measure. However, in the case of CRTs and CRT glass, the possibility of immediate environmental harm from a release is expected to be sufficiently low to be outweighed by the benefits from fostering increased recycling.

Some commenters urged us to adopt the universal waste approach because, unlike the conditional exclusion approach, it does not require use of the hazardous waste manifest for materials sent to disposal. Existing universal waste rules are intended to promote safer disposal of waste generated by households and small quantity generators, who are currently exempt from Subtitle C regulation. These commenters wanted this benefit for CRTs sent to disposal; one commenter stated that having similar requirements for recycling and disposal reduces complications for enforcement authorities by eliminating the need to discern the waste handler's intent. Other commenters, however, argued that used CRTs should be fully regulated when sent for disposal, and that such full regulation was necessary to protect human health and the environment.

Even though requiring no manifest for CRTs could simplify the regulations applicable to CRTs, we believe that today's conditional exclusion will foster the equally important goal of collecting CRTs, conserving resources, and minimizing negative impacts on the environment. We anticipate that it will lead to increased recycling and less disposal of CRTs, including those from households and CESQGs, because municipalities and other entities can consolidate CRTs from all sources more easily than if some CRTs were classified as hazardous wastes. In addition, as described earlier in this notice, the Agency and many states are engaged in several efforts to increase the rate of CRT and electronics recycling, including electronics from households and CESQGs. We believe that these efforts, as well as many others at the state and local level, will ultimately bring about a considerable improvement in the rate of voluntary electronics recycling.

With respect to disposal, materials sent to landfills or incinerators under the universal waste rule need not be accompanied by a hazardous waste manifest. Under our proposed conditional exclusion, the manifest would have to accompany CRTs sent for disposal. A few states said the universal waste rule was therefore less stringent (in this respect) than a conditional exclusion. These states were therefore concerned that if a state had already added CRTs to its universal waste program, it would have to amend its rules and seek authorization from EPA to remain equivalent to the federal program. This conclusion is incorrect; the Agency has concluded that adding CRTs to a state universal waste program is permissible under state authorization rules. As commenters pointed out, the universal waste rule is in other respects more stringent than today's conditional exclusion. In addition, the Agency's longstanding position is that under a state universal waste program, individual wastes and management standards are not subject to the authorization revision provisions in 40 CFR 271.21, since the state is already authorized for the universal waste regulations and the regulation of hazardous wastes (see the preamble to the universal waste rule at 60 FR 25537, May 11, 1995). Therefore, states are free to add CRTs to their universal waste programs without seeking authorization from EPA.

F. Definitions

Several commenters suggested changes to some of EPA's proposed definitions. The following is a summary of these suggested changes, with our responses.

"Cathode Ray Tube"

The Agency's proposed definition of "cathode ray tube" was a "vacuum tube, composed primarily of glass, which is the video display component of a television or computer monitor." Some commenters said that our proposed definition did not make clear whether we intended to include such devices as scanning equipment, multichannel analyzers, medical, automotive, oscilloscope, military, aircraft, and appliance CRTs. These commenters apparently believed that these types of CRTs did not fall within the definition of a television or computer monitor. One commenter said that the use of the term "video display" was misleading, since that phrase is associated with television monitors. This commenter suggested that "video or visual display component" would be a better definition. Another commenter suggested that EPA confine the regulatory definition to color CRTs, since monochrome CRTs generally do not exhibit the toxicity characteristic for lead.

The Agency agrees with those commenters who desired a more general definition that would encompass various types of CRTs; we believe that such a definition would provide more clarity to the regulated community and would better reflect the intent of our proposal (see 67 FR 40509). We also agree with the commenter who said that "video or visual display component" would be a more precise definition. For these reasons, we are changing our proposed definition of "cathode ray tube" in 40 CFR 260.10 to read as follows: "cathode ray tube means a vacuum tube, composed primarily of glass, which is the video or visual display component of an electronic device". This definition would encompass all the different types of CRTs mentioned by the commenters.

The Agency does not agree with the commenter who suggested that the definition of "cathode ray tube" be limited to color CRTs, since we are not certain that all color CRTs exhibit the toxicity characteristic for lead, or that no monochrome CRTs exhibit this characteristic. For this reason, we are not revising our proposed definition to include a reference to color or monochrome CRTs. If CRTs do not exhibit the toxicity characteristic for lead, they are not regulated under any of the hazardous waste regulations, including the exclusion promulgated today.

"Intact" and "Broken" CRTs

In our proposal, EPA had defined an "intact" CRT as one remaining within the monitor whose vacuum has not been released. A "broken" CRT, on the other hand, was defined as "glass removed from the monitor after the vacuum has been released". Some commenters pointed out that our proposed

definitions did not take into account two categories of CRTs: those removed from a monitor without release of the vacuum (i.e., "bare" CRTs) or CRTs remaining within the monitor after being inadvertently broken. One commenter believed that intact CRTs removed from the monitor were commodity-like, and should therefore be completely excluded from the definition of solid waste, especially since they presented very little potential for environmental releases. However, another commenter suggested that intact CRTs removed from the monitor should be treated the same as broken CRTs. Some commenters stated that the proposed rule did not address broken CRTs remaining within a monitor because of inadvertent breaking of the glass.

Another commenter pointed out that his company considered CRTs with released vacuum tubes to be intact because they have not been mechanically altered so as to increase the potential release of heavy metals.

After reviewing the comments, the Agency agrees that its proposed definitions did not adequately address at least one category of CRTs. With respect to intact CRTs that are removed from the monitor with the vacuum still unbroken, we understand that these materials must normally be packaged before being shipped for repair or reuse. It would therefore be unnecessary and redundant to subject these materials to the same conditions as broken CRTs sent for recycling. They resemble products more than wastes, and should not be considered solid wastes, unless disposed. In today's rule, therefore, we are clarifying the status of these materials by including them within the definition of "intact CRT," and we are revising that definition to read: "an intact CRT means a CRT whose vacuum has not been released."

However, the Agency is not changing the definition of "broken CRT" to specifically address inadvertently broken CRTs, since such breakage is accidental and does not occur routinely. If some CRTs within a shipment of intact CRTs are accidentally broken, such occurrences are most appropriately addressed on a case-by-case basis by the appropriate regulatory authorities.

One commenter suggested that the definition of "broken CRT" should refer to glass removed from any "housing" or "casing," rather than glass removed from a "monitor." The Agency agrees that the language suggested by the commenter is more descriptive. The same commenter noted that our proposed definition assumed that CRT vacuums are released before the CRT is removed from the monitor, whereas in actuality the CRT is sometimes removed from the monitor, after which the vacuum is released. EPA agrees with the commenter that our intent was not to draw distinctions based on the timing of the vacuum release. We have therefore revised our proposed definition of "broken CRT" to read: "glass removed from its housing or casing whose vacuum has been released."

One commenter noted that EPA did not present data showing that a CRT is not reusable as a product after the vacuum has been released and the glass removed. A few commenters suggested that EPA revise its definition of "broken CRT" to refer to CRTs that were no longer reusable, or to specify that CRTs become wastes when they will no longer be used for the purpose for which they were manufactured. In response to these comments, we note that the Agency specifically requested comment in the preamble to our proposed rule about whether it was possible to repair and reuse a CRT after the vacuum was released. No commenters submitted information or explanations about how this phenomenon might occur. With respect to broken CRTs, a released vacuum facilitates glass breakage and makes subsequent environmental releases more likely, even if these materials have not been substantially altered mechanically. We also believe that it would be much more difficult to implement the definition if regulators or the regulated community were required to ascertain whether a computer, television, or other electronic device could be used again. Such a determination would require considerably more technical expertise than merely examining a CRT to see if the vacuum had been released. Therefore, under today's rule, a CRT will still be considered broken if the vacuum is released.

One commenter suggested that we should change the definitions of "intact" and "broken" CRTs in proposed 40 CFR 260.10 to read "used, intact CRTs" and "used, broken CRTs" (presumably to be consistent with the language in our proposed exclusions). EPA agrees and has added this language to the definitions in today's final rule.

A few commenters objected to the Agency's regulatory distinctions between "unused" and "used" or "intact" and "broken" CRTs. These commenters believed that most CRTs in all of these categories should be treated the same (presumably because the environmental risks were similar).

Although classifying all CRTs in the same regulatory category would undoubtedly lead to simplified program implementation, EPA does not believe that eliminating our proposed distinctions is desirable. Intact CRTs present very little risk of releases, unless they are accumulated for long periods of time; therefore, subjecting them to the same conditions as broken CRTs is not appropriate.

"CRT Processing"

EPA received several comments on the proposed definition of "CRT processing." Specifically, the proposed regulation stated that CRT processing meant conducting all of the following activities: (1) Receiving broken or intact CRTs; (2) intentionally breaking intact CRTs, or further breaking or separating broken CRTs; (3) sorting or otherwise managing glass removed from CRT monitors; and (4) cleaning coatings off the glass removed from CRTs. Some commenters believed that it was not necessary to perform all of these activities in order to be considered a CRT processor. In particular, commenters pointed out that some CRT recyclers do not clean coatings from CRT glass, and that there is an increased market for glass with the coating still on it. These commenters recommended that the definition of "CRT processing" be revised to specify that performing the first three activities listed above, or cleaning coatings from glass removed from CRTs, should be sufficient to classify a person or facility as a CRT processor.

EPA agrees with these commenters. As one commenter stated, coatings do not have to be removed from CRT glass sent to a smelter. We are therefore revising our proposed definition of "CRT processing" to mean conducting all of the following activities: (1) Receiving broken or intact CRTs; and (2) intentionally breaking intact CRTs or further breaking or separating broken CRTs; and (3) sorting or otherwise managing glass removed from CRT monitors. Since any CRT recycler cleaning coatings from CRT glass would necessarily be performing the first three activities, we believe it is unnecessary to refer to such cleaning in the regulations. This revised definition will be more consistent with the current activities of CRT recyclers.

"Processed CRT Glass"

In our proposal, we did not include a definition of "processed CRT glass." One commenter noted that if EPA revised its definition of "CRT processing" to remove the reference to coating, the Agency should then promulgate a definition of "processed CRT glass" that would ensure that only CRT glass with the coatings removed

would be subject to the requirements of proposed 40 CFR 261.39(c) (i.e., no packaging or labeling for the processed glass). This commenter believed that only glass with the coating removed could properly be considered commodity-like. EPA disagrees with this suggestion, because we believe that whether CRT glass is coated or uncoated has little to do with whether the glass resembles a commodity. As stated above, CRT glass sent to smelters does not need to have coatings removed, and we believe that such materials are commodity-like. We believe that the destination of the glass is a more reliable indicator of its nature as a commodity than its coated or uncoated condition.

"CRT Glass Manufacturing"

Finally, one commenter pointed out that our proposed definition of "CRT glass manufacturing facility" could cause confusion because 40 CFR 260.10 defines a "facility" as "land, etc. used for treating, storing, and disposing of hazardous waste," which is not true of CRT glass manufacturers. The Agency agrees with this commenter that the use of the word "facility" could be misinterpreted and has changed the definition in today's rule to read: "CRT glass manufacturer means an operation or part of an operation that uses a furnace to manufacture CRT glass."

G. Disposal

In the preamble to our proposed rule, EPA solicited comment on whether to allow CRTs sent for disposal in hazardous waste facilities (i.e., landfills or incinerators) to comply with streamlined packaging and labeling requirements similar to the ones we proposed for broken CRTs sent for recycling, rather than comply with the full Subtitle C requirements, including use of the hazardous waste manifest.

Some commenters said that disposal of CRTs should be subject to streamlined requirements similar to those applicable to broken CRTs sent for recycling. These commenters generally believed that CRTs presented very low environmental risks, even in landfills. They cited what they believed to be the benefits of simplified program implementation (presumably including facilitation of inspections and enforcement) if CRTs sent for recycling and disposal were subject to the same regulatory requirements. Other commenters supported the application of the full Subtitle C requirements to CRTs sent for disposal. These commenters believed that CRTs sent for disposal presented greater environmental risks; they also supported this approach because they believed it would encourage recycling.

After evaluating these comments, the Agency has concluded that the arguments for streamlining requirements for CRTs sent for disposal do not appear to be justified. As noted by some commenters, the volume of these materials will increase in future years because of evolving computer and television technology. We have not conducted a separate analysis of disposal issues as part of this rulemaking. In addition, we wish to encourage the environmentally sound recycling of this rapidly growing wastestream to conserve resources and raw materials, and we do not want to promulgate regulations that are inconsistent with this policy. For this reason, we are not promulgating streamlined packaging and labeling requirements for CRTs sent for disposal.

H. Enforcement

Under today's rule, CRTs and CRT glass destined for recycling and CRTs exported for reuse are excluded from RCRA Subtitle C regulation if certain conditions are met. Persons that handle CRTs and CRT glass that are subject to this exclusion will be responsible for maintaining the exclusion by ensuring that all of the conditions are met. If the CRTs are not managed as specified by these conditions, they are not excluded. The CRTs would then be considered hazardous waste (if they exhibit a hazardous waste characteristic) for Subtitle C purposes from the time they were "generated", i.e., from the time the decision was made to dispose of them or to release the vacuum for recycling, rather than to send them to facilities where they may be reused.

Persons taking advantage of the exclusion that fail to meet one or more of its conditions may be subject to enforcement action and the CRTs may be considered to be hazardous waste from the point of their generation. EPA could choose to bring an enforcement action under RCRA Section 3008(a) for all violations of the hazardous waste requirements occurring from the time a decision was made to dispose of the CRTs or to release the vacuum for recycling, through the time they are finally disposed of or reclaimed.

EPA believes that this approach, which treats CRTs exhibiting a hazardous waste characteristic that do not conform to the conditions of the exclusion as hazardous waste from their point of generation, provides all handlers with an incentive to handle the CRTs consistent with the conditions. It also encourages each person to take appropriate steps to ensure that CRTs are safely handled and legitimately reused or recycled by others in the management chain.

Persons managing CRTs before they become wastes are not considered generators and are not subject to RCRA requirements. For example, charitable organizations, municipalities, retailers, or manufacturers who collect intact CRTS are not generators when they send CRTs to facilities that decide whether they will be reused, recycled, or disposed.

V. State Authority

A. Applicability of Rules in Authorized States

Under section 3006 of RCRA, EPA may authorize a qualified state to administer and enforce a hazardous waste program within the state in lieu of the federal program, and to issue and enforce permits in the state. A state may receive authorization by following the approval process described in 40 CFR 271.21 (see 40 CFR part 271 for the overall standards and requirements for authorization). EPA continues to have independent authority to bring enforcement actions under RCRA Sections 3007, 3008, 3013, and 7003. An authorized state also continues to have independent authority to bring enforcement actions under state law.

After a state receives initial authorization, new federal requirements promulgated under RCRA authority existing prior to the 1984 Hazardous and Solid Waste Amendments (HSWA) do not apply in that state until the state adopts and receives authorization for equivalent state requirements. In contrast, under RCRA Section 3006(g) (42 U.S.C. 6926(g)), new federal requirements and prohibitions promulgated pursuant to HSWA provisions take effect in authorized states at the same time that they take effect in unauthorized states. As such, EPA carries out HSWA requirements and prohibitions in authorized states, including the issuance of new permits implementing those requirements, until EPA authorizes the state to do so.

Authorized states are required to modify their programs only when EPA enacts federal requirements that are more stringent or broader in scope than existing federal requirements. RCRA Section 3009 allows the states to impose standards more stringent than those in the federal program (see also 40 CFR 271.1(i)). Therefore, authorized states are not required to adopt federal regulations, both HSWA and non-HSWA, that are considered less stringent than previous federal regulations.

B. Effect on State Authorization

Today's rule will have a different effect on authorized state programs, depending on how the state is currently regulating CRTs. In the proposal to today's rule, EPA clarified its views on how the current RCRA regulations most appropriately applied to CRTs sent for recycling (see 67 FR 40508 at 40511, June 12, 2002), and we proposed to revise the regulations to clarify any confusion and to set a clear federal floor. In the case of used CRTs going for recycling, EPA at the time encouraged states to implement approaches consistent with the proposal. Today's final rule modifies the proposal in three principal respects: (1) Speculative accumulation requirements for used, intact CRTs; (2) one-time notification requirement for used CRTs exported for reuse; and (3) notice and consent requirements for CRTs exported for recycling. These requirements are more stringent than the approach that EPA, in the proposed preamble, recommended that states adopt under the current regulations. Therefore, states that adopted the approach recommended in the proposed rule must amend their programs so that they are no less stringent than the federal approach. States currently regulating CRTs as hazardous waste, including under the universal waste rule, would not have to amend their programs, since their programs are more stringent than the federal requirements.

The limitations on speculative accumulation for intact CRTs are issued under RCRA authority, and therefore will not go into effect (in states not currently managing intact CRTs as hazardous waste) until states have adopted today's rule. The one-time notification for intact CRTs exported for reuse and notice and consent requirements for CRTs exported for recycling are implemented under HSWA authority (section 3017 of RCRA, which governs notice and consent) and therefore go into effect six months after the publication date of this rule. The Agency is adding the rule to Table 1 in 40 CFR 271.1(j), which identifies the federal program requirements that are promulgated pursuant to the statutory authority that was added by HSWA.

C. Interstate Transport

Because some states may choose to regulate CRTs or processed CRT glass under the universal waste or other hazardous waste rules, there will probably be cases when used CRTs or processed CRT glass will be transported to and from states with different regulations governing these wastes.

First, a waste which is subject to an exclusion from the definition of solid waste in the state where it is generated may be sent to a state where it is subject to the hazardous waste regulations. In this scenario, for the portion of the trip through the originating state, and any other states where the waste is excluded, neither a hazardous waste transporter with an EPA identification number per 40 CFR 263.11 nor a manifest would be required. However, for the portion of the trip through the receiving state, and any other states that do not consider the waste to be excluded, the transporter must have a manifest, except as provided by the universal waste rules, and must move the waste in compliance with 40 CFR Part 263. In order for the final transporter and the receiving facility to fulfill the requirements concerning the manifest (40 CFR 263.20, 263.21, 263.22; 264.71, 264.72, 264.76 or 265.71, 265.72, and 265.76), the initiating facility should complete a manifest and forward it to the first transporter to travel in a state where the waste is not excluded. The receiving facility must then sign the manifest and send a copy to the initiating facility.

Second, CRTs or processed CRT glass generated in a state which regulates them as hazardous waste may be sent to a state where they are excluded. In this scenario, the material must be moved by a hazardous waste transporter, while the material is in the generator's state or any other states where it is not excluded, except as provided by the universal waste rules. The initiating facility would complete a manifest and give copies to the transporter as required under 40 CFR 262.23(a). Transportation within the receiving state and any other states that exclude the material would not require a manifest and need not be transported by a hazardous waste transporter. However, it is the initiating facility's responsibility to ensure that the manifest is forwarded to the receiving facility by the transporter and sent back to the initiating facility by the receiving facility (see 40 CFR 262.23 and 262.42).

VI. Statutory and Executive Order Reviews

A. Executive Order 12866: Regulatory Planning and Review

Under Executive Order 12866 (58 FR 51735, October 4, 1993), federal agencies must determine whether this regulatory action is "significant" and therefore subject to review by the Office of Management and Budget (OMB) and to the requirements of the Executive Order. The Order defines "significant regulatory action" as one that is likely to result in a rule that may: (1) Have an annual effect on the economy of $100 million or more or adversely affect in a material way the economy, a sector of the economy, productivity, competition, jobs, the environment, public health or safety, or state, local, or tribal governments or communities; (2) create serious inconsistency or otherwise interfere with an action taken or planned by another agency; (3) materially alter the budgetary impact of entitlements, grants, user fees, or loan programs or the rights and obligations of recipients; or (4) raise novel legal or policy issues arising out of legal mandates, the President's priorities, or the principles set forth in the Executive Order.

Pursuant to the terms of Executive Order 12866, the Agency has determined that today's rule is a significant regulatory action because it contains novel policy issues. As such, this action was submitted to OMB for review. Changes made in response to OMB suggestions or recommendations are documented in the docket to today's rule.

To estimate the cost savings, incremental costs, economic impacts and benefits from this rule to affected regulated entities, we completed an economic analysis for the rulemaking. Copies of this analysis have been placed in the RCRA docket for public review (see "Economic Analysis of Cathode Ray Tube Management, Final Rulemaking," March 19, 2004).

1. Methodology

To estimate the cost savings, incremental costs, economic impacts and benefits of this rule, the Agency estimated both the affected volume of cathode ray tubes (CRTs) and regulated entities. The Agency has evaluated two baseline (pre-regulatory) scenarios: (1) A scenario which models a distribution of affected monitors as if all affected entities followed standard Subtitle C regulations, and (2) a scenario which models a high percentage of CRTs being discarded untreated in municipal solid waste landfills. This latter scenario is being analyzed to evaluate the possible real-world effect of this rule on affected entities.

The Agency then modeled a post-regulatory scenario that simulates management of CRTs after the regulation promulgated today is implemented. In our economic analysis, we have calculated administrative, storage, transportation and disposal/recovery costs for both baselines and the post-regulatory scenarios and estimated the net cost savings and economic

impacts for each combination of the two baselines and the post-regulatory scenario. The first baseline and post-regulatory scenario is the pairing that we are using to meet our administrative requirements following this section.

2. Results

a. Volume

We have estimated the affected volume of CRTs (including both previously regulated and diverted volumes of monitors) under the post-regulatory scenario to be 54,000 tons. We believe that approximately 10,000 tons of CRTs would be diverted from export or hazardous waste landfill to CRT glass manufacturing under the post-regulatory alternative.

b. Cost/Economic Impact

We estimate that the rule will save CRT handlers $5.0 million per year compared to the scenario which assumed that all affected entities followed the standard Subtitle C regulations. This cost savings comes from reduced administrative, transportation and disposal/management cost.

To estimate the economic impact of the rule on CRT handlers, the Agency evaluated the cost savings or incremental costs as a percentage of firm sales. In virtually all cases, economic impacts are cost savings of less than one percent of firm sales. Under the first scenario, the average savings for a previously regulated small quantity generator is $520 per year; for a previously regulated large quantity generator, the average savings is $1,091 per year.

c. Benefits

EPA has evaluated the qualitative benefits and to a lesser extent, the quantitative benefits of the rule for CRTs. Some of the benefits resulting from today's rule include conservation of landfill capacity, increase in resource efficiency, growth of a recycling infrastructure for CRTs, and possible reduction of lead emissions to the environment from CRT recycling. EPA estimates that approximately 3,690 tons or 545,000 cubic feet of CRTs per year would be redirected away from landfills towards recycling under today's rule. In addition, as mentioned above, the use of processed CRT glass benefits the manufacturer in several ways, such as improving heat transfer and melting characteristics in the furnaces, lowering energy consumption, and maintaining or improving the quality of the final product. This rule may facilitate the growth and development of the CRT glass processing industry by reducing regulatory barriers to the establishment of new glass processing firms. Finally, this rule will encourage reuse and recycling by diverting CRTs from municipal landfills and waste-to-energy facilities.

B. Paperwork Reduction Act

The Office of Management and Budget (OMB) has approved the information collection requirements contained in this rule under the provisions of the *Paperwork Reduction Act,* 44 U.S.C. 3501 *et seq.* and has assigned OMB control number 2050–0053.

The information requirements established for this action, and identified in the Information Collection Request (ICR) supporting today's rule, are largely self-implementing, except for the notice and consent requirements for CRTs exported for recycling. This process will ensure that: (i) Regulated entities managing CRTs are held accountable to the applicable requirements; (ii) state inspectors can verify compliance when needed; and (iii) CRTs exported for recycling or reuse are actually handled as commodities abroad.

EPA has carefully considered the burden imposed upon the regulated community by the regulations. EPA is confident that those activities required of respondents are necessary and, to the extent possible, has attempted to minimize the burden imposed. EPA believes strongly that if the minimum requirements specified under the regulations are not met, neither the facilities nor EPA can ensure that used CRTs are being managed in a manner protective of human health and the environment.

For the requirements applicable to CRTs, the aggregate annual burden to respondents over the three-year period covered by this ICR is estimated at 5,400 hours, with a cost of approximately $269,100. Average annual burden hours per respondent are estimated to be between 3.4 and 4.1 hours (the latter figure is for respondents who are exporters). There are an estimated 3,775 respondents. However, this represents a reduction in burden to respondents of approximately 17,306 hours, or $878,034. The estimated operation and maintenance costs are $100 (including the cost of postage and envelopes). There are no start-up costs and no costs for purchases of services. Administrative costs to the Agency are estimated to be 371 hours per year, or $11,173. Burden means the total time, effort, or financial resources expended by persons to generate, maintain, retain, disclose, or provide information to or for a federal agency. This includes the time needed to review instructions; develop, acquire, install, and utilize technology and systems for the purposes of collecting, validating, and verifying information, processing and maintaining information, and disclosing and providing information; adjust the existing ways to comply with any previously applicable instructions and requirements; train personnel to be able to respond to a collection of information; search data sources; complete and review the collection of information; and transmit or otherwise disclose the information.

An Agency may not conduct or sponsor, and a person is not required to respond to, a collection of information unless it displays a currently valid OMB control number. The OMB control numbers for EPA's regulations are listed in 40 CFR Part 9. In addition, EPA is amending the table in 40 CFR Part 9 of currently approved OMB control numbers for various regulations to list the regulatory citations for the information requirements contained in this final rule.

C. Regulatory Flexibility Act

The Regulatory Flexibility Act (RFA), as amended by the Small Business Regulatory Enforcement Fairness Act of 1996 (SBREFA), 5 U.S.C. 601 *et seq.,* generally requires an agency to prepare a regulatory flexibility analysis of any rule subject to notice and comment rulemaking requirements under the Administrative Procedure Act or any other statute, unless the agency certifies that the rule will not have a significant economic impact on a substantial number of small entities. Small entities include small businesses, small organizations, and small governmental jurisdictions.

For purposes of assessing the impacts of today's rule on small entities, small entity is defined as: (1) A small business that is defined by the Small Business Administration by category of business using the North American Industrial Classification System (NAICS) and codified at 13 CFR 121.201; (2) a small governmental jurisdiction that is a government of a city, county, town, school district or special district with a population of less than 50,000; and (3) a small organization that is any not-for-profit enterprise which is independently owned and operated and is not dominant in its field.

After considering the economic impacts of today's rule on small entities, I hereby certify that this action will not have a significant adverse impact on a substantial number of small entities. In determining whether a rule has a significant economic impact on a

substantial number of small entities, the impact of concern is any significant adverse economic impact on small entities, since the primary purpose of the regulatory flexibility analyses is to identify and address regulatory alternatives "which minimize any significant economic impact of the rule on small entities." 5 U.S.C. 603 and 604. Thus, an agency may certify that a rule will not have a significant economic impact on a substantial number of small entities if the rule relieves regulatory burden, or otherwise has a positive effect on all of the small entities subject to the rule.

The small entity analysis conducted for today's rule indicates that streamlining requirements for CRTs would generally result in savings to affected entities compared to baseline requirements. Under the full compliance scenario, the rule is not expected to result in a net cost to any affected entity.

D. Unfunded Mandates Reform Act

Title II of the Unfunded Mandates Reform Act of 1995 (UMRA), Public Law 104–4, establishes requirements for federal agencies to assess the effects of their regulatory actions on state, local, and tribal governments and the private sector. Under section 202 of the UMRA, EPA generally must prepare a written statement, including a cost-benefit analysis, for the proposed and final rules with "federal mandates" that may result in expenditures by state, local, and tribal governments, in the aggregate, or to the private sector, of $100 million or more in any one year. Before promulgating a rule for which a written statement is needed, Section 205 of the UMRA requires federal agencies to identify and consider a reasonable number of regulatory alternatives and adopt the least costly, most cost-effective or least burdensome alternative that achieves the objectives of the rule. The provisions of section 205 do not apply when they are inconsistent with applicable law. Moreover, section 205 allows EPA to adopt an alternative other than the least costly, most cost-effective, or least burdensome alternative if the Administrator publishes with the final rule an explanation why that alternative was not adopted.

This final rule does not include a federal mandate that may result in expenditures of $100 million of more to state, local, or tribal governments in the aggregate, because the UMRA generally excludes from the definition of "federal intergovernmental mandate" duties that arise from participation in a voluntary federal program. States are not legally required to have or maintain a RCRA authorized program. Therefore, today's final rule is not subject to the requirements of Sections 202 or 205 of UMRA. In addition, this final rule contains no regulatory requirements that might significantly or uniquely affect small governments under Section 203 of UMRA. Therefore we have determined that today's rule is not subject to the requirements of sections 202, 203, or 205 of UMRA.

E. Executive Order 13132: Federalism

Executive Order 13132, entitled "Federalism" (64 FR 43255, August 10, 1999), requires EPA to develop an accountable process to ensure meaningful and timely input by State and local officials in the development of regulatory policies that have federalism implications. "Policies that have federalism implications" is defined in the Executive Order to include regulations that have "substantial direct effects on the states, on the relationship between the national government and the states, or on the distribution of power and responsibilities among the various levels of government." This rule does not have federalism implications. It streamlines RCRA management requirements for CRTs and CRT glass being recycled, and will affect primarily those persons who are engaged in CRT recycling. It will not have substantial direct effects on the states, on the relationship between the national government and the States, or on the distribution of power and responsibilities among the various levels of government, as specified in Executive Order 13132.

Although Section 6 of Executive Order 13132 does not apply to this rule, EPA consulted with representatives of the Association of State and Territorial Solid Waste Management Officials (ASTSWMO) in developing this rule prior to finalization.

F. Executive Order 13175: Consultation and Coordination With Indian Tribal Governments

Executive Order 13175, entitled "Consultation and Coordination with Indian Tribal Governments" (65 FR 67249, November 6, 2000), requires EPA to develop an accountable process to ensure "meaningful and timely input by tribal officials in the development of regulatory policies that have tribal implications." This final rule does not have tribal implications, as specified in Executive Order 13175. It does not impose any new requirements on tribal officials nor does it impose substantial direct compliance costs on them. This rule does not create a mandate for tribal governments, nor does it impose any enforceable duties on these entities. Thus, Executive Order 13175 does not apply to this rule.

G. Executive Order 13045: Protection of Children From Environmental Health and Safety Risk

"Protection of Children From Environmental Health Risks and Safety Risks" (62 FR 19885, April 23, 1997) applies to any rule that EPA determines (1) is "economically significant" as defined under Executive Order 12866, and (2) concerns an environmental health or safety risk that EPA has reason to believe may have a disproportionate effect on children. If the regulatory action meets both criteria, the Agency must evaluate the environmental health or safety effects of the planned rule on children and explain why the planned regulation is preferable to other potential effective and reasonably feasible alternatives considered by the Agency.

This rule is not subject to Executive Order 13045 because it is not an economically significant rule as defined by Executive Order 12866 and because it does not concern an environmental health or safety risk that the Agency has reason to believe may have a disproportionate effect on children.

H. Executive Order 13211

This rule is not a "significant energy action" as defined in Executive Order 13211, "Actions Concerning Regulations That Significantly Affect Energy Supply, Distribution, or Use" (66 FR 28355, May 22, 2001) because it is not likely to have a significant adverse effect on the supply, distribution, or use of energy. Today's rule streamlines hazardous waste management requirements for used cathode ray tubes. By encouraging reuse and recycling, the rule may save energy costs associated with manufacturing new materials.

I. National Technology Transfer and Advancement Act of 1995

Section 12(d) of the National Technology Transfer and Advancement Act of 1995 ("NTTAA"), Public Law 104–113, section 12(d) (15 U.S.C. 272 note) directs EPA to use voluntary consensus standards in its regulatory activities unless to do so would be inconsistent with applicable law or otherwise impractical. Voluntary consensus standards are technical standards (e.g., materials specifications, test methods, sampling procedures, and business practices) that are developed or adopted by voluntary consensus standards bodies. The NTTAA directs EPA to provide Congress, though OMB, explanations when the Agency decides

not to use available and applicable voluntary consensus standards. This rule does not establish technical standards. Therefore, EPA did not consider the use of any voluntary consensus standards.

J. Environmental Justice

Executive Order 12898, "Federal Actions to Address Environmental Justice in Minority Populations and Low-Income Populations" (February 11, 1994) is designed to address the environmental and human health conditions of minority and low-income populations. EPA is committed to addressing environmental justice concerns and has assumed a leadership role in environmental justice initiatives to enhance environmental quality for all citizens of the United States. The Agency's goals are to ensure that no segment of the population, regardless of race, color, national origin, income, or net worth bears disproportionately high and adverse human health and environmental impacts as a result of EPA's policies, programs, and activities. In response to Executive Order 12898, EPA's Office of Solid Waste and Emergency Response (OSWER) formed an Environmental Justice Task Force to analyze the array of environmental justice issues specific to waste programs and to develop an overall strategy to identify and address these issues (OSWER Directive No. 9200.3–17). To address this goal, EPA conducted a qualitative analysis of the environmental justice issues under this rule. Potential environmental justice impacts are identified consistent with the EPA's Environmental Justice Strategy and the OSWER Environmental Justice Action Agenda.

Today's rule would streamline hazardous waste management requirements for used cathode ray tubes sent for recycling. Facilities that would be affected by today's rule include those generating hazardous waste computers and televisions sent for recycling. Also affected would be facilities which recycle these materials. Disposal facilities themselves would not be affected by today's rule.

The wide distribution of affected facilities throughout the United States does not suggest any distributional pattern around communities of concern. Any building in any area could be affected by today's rule. Specific impacts on low income or minority communities, therefore, are undetermined. The Agency believes that emissions during transportation would not be a major contributor to communities of concern through which used CRTs may be transported. Any such material broken during transport would be contained in the required packaging. Overall, no disproportional impacts to minority or low income communities are expected.

K. Congressional Review Act

The Congressional Review Act, 5 U.S.C. 801 *et seq.*, as added by the Small Business Regulatory Enforcement Fairness Act of 1996, generally provides that before a rule may take effect, the agency promulgating the rule must submit a rule report, which includes a copy of the rule, to each House of the Congress and to the Comptroller General of the United States. EPA will submit a report containing this rule and other required information to the U.S. Senate, the U.S. House of Representatives, and the Comptroller General of the United States prior to publication of the rule in the **Federal Register.** A major rule cannot take effect until 60 days after it is published in the **Federal Register.** This action is not a "major rule" as defined by 5 U.S.C. 804(2). This rule will be effective January 29, 2007.

List of Subjects

40 CFR Part 9

Environmental protection, Reporting and recordkeeping requirements.

40 CFR Part 260

Environmental protection, Administrative practice and procedure, Confidential business information, Hazardous waste, Reporting and recordkeeping requirements.

40 CFR Part 261

Environmental protection, Hazardous waste, Recycling, Reporting and recordkeeping requirements.

40 CFR Part 271

Administrative practice and procedure, Confidential business information, Hazardous materials transportation, Hazardous waste, Indians-lands, Intergovernmental relations, Penalties, Reporting and recordkeeping requirements, Water pollution control, Water supply.

Dated: July 19, 2006.

Stephen L. Johnson,

Administrator.

■ For the reasons set out in the preamble, title 40, chapter I of the Code of Federal Regulations is amended as follows:

PART 9—[AMENDED]

■ 1. The authority citation for part 9 continues to read as follows:

Authority: 7 U.S.C. 135 *et seq.*, 136–136y; 15 U.S.C. 2001, 2003, 2005, 2006, 2601–2671; 21 U.S.C. 331j, 346a, 348; 31 U.S.C. 9701; 33 U.S.C. 1251 *et seq.*, 1311, 1313d, 1314, 1318, 1321, 1326, 1330, 1342, 1344, 1345 (d) and (e), 1361; E.O. 11735, 38 FR 21243, 3 CFR, 1971–1975 Comp. p. 973; 42 U.S.C. 241, 242b, 243, 246, 300f, 300g, 300g–1, 300g–2, 300g–3, 300g–4, 300g–5, 300g–6, 300j–1, 300j–2, 300j–3, 300j–4, 300j–9, 1857 *et seq.*, 6901–6992k, 7401–7671q, 7542, 9601–9657, 11023, 11048.

■ 2. In § 9.1 the table is amended by adding new entries in numerical order under the indicated heading to read as follows:

§ 9.1 OMB approvals under the Paperwork Reduction Act.

* * * * *

40 CFR citation	OMB control No.
Identification and Listing of Hazardous Waste	
261.39	2050–0053
261.40	2050–0053
261.41	2050–0053

PART 260—HAZARDOUS WASTE MANAGEMENT SYSTEM: GENERAL

■ 3. The authority citation for part 260 continues to read as follows:

Authority: 42 U.S.C. 6905, 6912(a), 6921–6927, 6930, 6934, 6935, 6937, 6938, 6939, and 6974.

Subpart B—Definitions

■ 4. Section 260.10 is amended by adding in alphabetical order the definitions of "Cathode ray tube," "CRT collector," "CRT glass manufacturer," and "CRT processing", to read as follows:

§ 260.10 Definitions.

* * * * *

Cathode ray tube or CRT means a vacuum tube, composed primarily of glass, which is the visual or video display component of an electronic device. A used, intact CRT means a CRT whose vacuum has not been released. A used, broken CRT means glass removed from its housing or casing whose vacuum has been released.

* * * * *

CRT collector means a person who receives used, intact CRTs for recycling, repair, resale, or donation.

CRT glass manufacturer means an operation or part of an operation that uses a furnace to manufacture CRT glass.

CRT processing means conducting all of the following activities:

(1) Receiving broken or intact CRTs; and

(2) Intentionally breaking intact CRTs or further breaking or separating broken CRTs; and

(3) Sorting or otherwise managing glass removed from CRT monitors.

* * * * *

PART 261—IDENTIFICATION AND LISTING OF HAZARDOUS WASTE

■ 5. The authority citation for part 261 continues to read as follows:

Authority: 42 U.S.C. 6905, 6912(a), 6921, 6922, 6924(y), and 6938.

Subpart A—General

■ 6. Section 261.4 is amended by adding a new paragraph (a)(22), to read as follows:

§ 261.4 Exclusions.

(a) * * *

(22) Used cathode ray tubes (CRTs)

(i) Used, intact CRTs as defined in § 260.10 of this chapter are not solid wastes within the United States unless they are disposed, or unless they are speculatively accumulated as defined in § 261.1(c)(8) by CRT collectors or glass processors.

(ii) Used, intact CRTs as defined in § 260.10 of this chapter are not solid wastes when exported for recycling provided that they meet the requirements of § 261.40.

(iii) Used, broken CRTs as defined in § 260.10 of this chapter are not solid wastes provided that they meet the requirements of § 261.39.

(iv) Glass removed from CRTs is not a solid waste provided that it meets the requirements of § 261.39(c).

* * * * *

■ 7. Part 261 is amended by adding subpart E to read as follows:

Subpart E—Exclusions/Exemptions

Sec.

261.39 Conditional Exclusion for Used, Broken Cathode Ray Tubes (CRTs) and Processed CRT Glass Undergoing Recycling.
261.40 Conditional Exclusion for Used, Intact Cathode Ray Tubes (CRTs) Exported for Recycling.
261.41 Notification and Recordkeeping for Used, Intact Cathode Ray Tubes (CRTs) Exported for Reuse.

Subpart E—Exclusions/Exemptions

§ 261.39 Conditional Exclusion for Used, Broken Cathode Ray Tubes (CRTs) and Processed CRT Glass Undergoing Recycling.

Used, broken CRTs are not solid wastes if they meet the following conditions:

(a) *Prior to processing:* These materials are not solid wastes if they are destined for recycling and if they meet the following requirements:

(1) *Storage.* The broken CRTs must be either:

(i) Stored in a building with a roof, floor, and walls, or

(ii) Placed in a container (*i.e.*, a package or a vehicle) that is constructed, filled, and closed to minimize releases to the environment of CRT glass (including fine solid materials).

(2) *Labeling.* Each container in which the used, broken CRT is contained must be labeled or marked clearly with one of the following phrases: "Used cathode ray tube(s)-contains leaded glass " or "Leaded glass from televisions or computers." It must also be labeled: "Do not mix with other glass materials."

(3) *Transportation.* The used, broken CRTs must be transported in a container meeting the requirements of paragraphs (a)(1)(ii) and (2) of this section.

(4) *Speculative accumulation and use constituting disposal.* The used, broken CRTs are subject to the limitations on speculative accumulation as defined in paragraph (c)(8) of this section. If they are used in a manner constituting disposal, they must comply with the applicable requirements of part 266, subpart C instead of the requirements of this section.

(5) *Exports.* In addition to the applicable conditions specified in paragraphs (a)(1)–(4) of this section, exporters of used, broken CRTs must comply with the following requirements:

(i) Notify EPA of an intended export before the CRTs are scheduled to leave the United States. A complete notification should be submitted sixty (60) days before the initial shipment is intended to be shipped off-site. This notification may cover export activities extending over a twelve (12) month or lesser period. The notification must be in writing, signed by the exporter, and include the following information:

(A) Name, mailing address, telephone number and EPA ID number (if applicable) of the exporter of the CRTs.

(B) The estimated frequency or rate at which the CRTs are to be exported and the period of time over which they are to be exported.

(C) The estimated total quantity of CRTs specified in kilograms.

(D) All points of entry to and departure from each foreign country through which the CRTs will pass.

(E) A description of the means by which each shipment of the CRTs will be transported (*e.g.*, mode of transportation vehicle (air, highway, rail, water, etc.), type(s) of container (drums, boxes, tanks, etc.)).

(F) The name and address of the recycler and any alternate recycler.

(G) A description of the manner in which the CRTs will be recycled in the foreign country that will be receiving the CRTs.

(H) The name of any transit country through which the CRTs will be sent and a description of the approximate length of time the CRTs will remain in such country and the nature of their handling while there.

(ii) Notifications submitted by mail should be sent to the following mailing address: Office of Enforcement and Compliance Assurance, Office of Federal Activities, International Compliance Assurance Division, (Mail Code 2254A), Environmental Protection Agency, 1200 Pennsylvania Ave., NW., Washington, DC 20460. Hand-delivered notifications should be sent to: Office of Enforcement and Compliance Assurance, Office of Federal Activities, International Compliance Assurance Division, (Mail Code 2254A), Environmental Protection Agency, Ariel Rios Bldg., Room 6144, 1200 Pennsylvania Ave., NW., Washington, DC. In both cases, the following shall be prominently displayed on the front of the envelope: "Attention: Notification of Intent to Export CRTs."

(iii) Upon request by EPA, the exporter shall furnish to EPA any additional information which a receiving country requests in order to respond to a notification.

(iv) EPA will provide a complete notification to the receiving country and any transit countries. A notification is complete when EPA receives a notification which EPA determines satisfies the requirements of paragraph (a)(5)(i) of this section. Where a claim of confidentiality is asserted with respect to any notification information required by paragraph (a)(5)(i) of this section, EPA may find the notification not complete until any such claim is resolved in accordance with 40 CFR 260.2.

(v) The export of CRTs is prohibited unless the receiving country consents to the intended export. When the receiving country consents in writing to the receipt of the CRTs, EPA will forward an Acknowledgment of Consent to Export CRTs to the exporter. Where the receiving country objects to receipt of

the CRTs or withdraws a prior consent, EPA will notify the exporter in writing. EPA will also notify the exporter of any responses from transit countries.

(vi) When the conditions specified on the original notification change, the exporter must provide EPA with a written renotification of the change, except for changes to the telephone number in paragraph (a)(5)(i)(A) of this section and decreases in the quantity indicated pursuant to paragraph (a)(5)(i)(C) of this section. The shipment cannot take place until consent of the receiving country to the changes has been obtained (except for changes to information about points of entry and departure and transit countries pursuant to paragraphs (a)(5)(i)(D) and (a)(5)(i)(H) of this section) and the exporter of CRTs receives from EPA a copy of the Acknowledgment of Consent to Export CRTs reflecting the receiving country's consent to the changes.

(vii) A copy of the Acknowledgment of Consent to Export CRTs must accompany the shipment of CRTs. The shipment must conform to the terms of the Acknowledgment.

(viii) If a shipment of CRTs cannot be delivered for any reason to the recycler or the alternate recycler, the exporter of CRTs must renotify EPA of a change in the conditions of the original notification to allow shipment to a new recycler in accordance with paragraph (a)(5)(vi) of this section and obtain another Acknowledgment of Consent to Export CRTs.

(ix) Exporters must keep copies of notifications and Acknowledgments of Consent to Export CRTs for a period of three years following receipt of the Acknowledgment.

(b) *Requirements for used CRT processing:* Used, broken CRTs undergoing CRT processing as defined in § 260.10 of this chapter are not solid wastes if they meet the following requirements:

(1) *Storage.* Used, broken CRTs undergoing processing are subject to the requirement of paragraph (a)(4) of this section.

(2) *Processing.*

(i) All activities specified in paragraphs (2) and (3) of the definition of "CRT processing" in § 260.10 of this chapter must be performed within a building with a roof, floor, and walls; and

(ii) No activities may be performed that use temperatures high enough to volatilize lead from CRTs.

(c) *Processed CRT glass sent to CRT glass making or lead smelting:* Glass from used CRTs that is destined for recycling at a CRT glass manufacturer or a lead smelter after processing is not a solid waste unless it is speculatively accumulated as defined in § 261.1(c)(8).

(d) *Use constituting disposal:* Glass from used CRTs that is used in a manner constituting disposal must comply with the requirements of 40 CFR part 266, subpart C instead of the requirements of this section.

§ 261.40 Conditional Exclusion for Used, Intact Cathode Ray Tubes (CRTs) Exported for Recycling.

Used, intact CRTs exported for recycling are not solid wastes if they meet the notice and consent conditions of § 261.39(a)(5), and if they are not speculatively accumulated as defined in § 261.1(c)(8).

§ 261.41 Notification and Recordkeeping for Used, Intact Cathode Ray Tubes (CRTs) Exported for Reuse.

(a) Persons who export used, intact CRTs for reuse must send a one-time notification to the Regional Administrator. The notification must include a statement that the notifier plans to export used, intact CRTs for reuse, the notifier's name, address, and EPA ID number (if applicable) and the name and phone number of a contact person.

(b) Persons who export used, intact CRTs for reuse must keep copies of normal business records, such as contracts, demonstrating that each shipment of exported CRTs will be reused. This documentation must be retained for a period of at least three years from the date the CRTs were exported.

■ 8. Section 261.38 of subpart D is moved to subpart E.

PART 271—REQUIREMENTS FOR AUTHORIZATION OF STATE HAZARDOUS WASTE PROGRAMS

■ 9. The authority citation for part 271 continues to read as follows:

Authority: 42 U.S.C. 6905, 6912(a), and 6926.

■ 10. Section 271.1(j) is amended by adding the following entries to Table 1 in chronological order by date of publication in the **Federal Register**, to read as follows:

§ 271.1 Purpose and scope.

* * * * *

(j) * * *

TABLE 1.—REGULATIONS IMPLEMENTING THE HAZARDOUS AND SOLID WASTE AMENDMENTS OF 1984

Promulgation date	Title of regulation	**Federal Register** reference	Effective date
*	* * * *	*	*
July 28, 2006	Final Rule for Cathode Ray Tubes	[Insert FR page numbers] ..	Jan. 29, 2007.
*	* * * *	*	*

[FR Doc. 06–6490 Filed 7–27–06; 8:45 am]
BILLING CODE 6560–50–P



Federal Register

Friday,
July 14, 2006

Part III

Environmental Protection Agency

40 CFR Parts 260, 261 et al.
Hazardous Waste and Used Oil; Corrections to Errors in the Code of Federal Regulations; Final Rule

ENVIRONMENTAL PROTECTION AGENCY

40 CFR Parts 260, 261, 262, 264, 265, 266, 267, 268, 270, 271, 273 and 279

[FRL–8188–2]

Hazardous Waste and Used Oil; Corrections to Errors in the Code of Federal Regulations

AGENCY: Environmental Protection Agency.

ACTION: Final rule.

SUMMARY: The Environmental Protection Agency (EPA) is correcting errors in the hazardous waste and used oil regulations, as a result of printing omissions, typographical errors, misspellings, citations to paragraphs and other references that have been deleted or moved to new locations without correcting the citations, and similar mistakes appearing in numerous final rules published in the **Federal Register**. This final rule does not create new regulatory requirements.

DATES: *Effective Date:* This final rule is effective on July 14, 2006.

FOR FURTHER INFORMATION CONTACT: Kathleen Rafferty, USEPA Headquarters, Ariel Rios Building, 1200 Pennsylvania Avenue, NW., Mailcode 5303P, Washington, DC 20460; phone number: (703) 308–0589; e-mail: *rafferty.kathy@epa.gov*.

SUPPLEMENTARY INFORMATION:

I. Does This Rule Create New Federal Requirements?

This rule does not create new regulatory requirements; rather, the rule corrects typographical errors, misspellings, punctuation mistakes, missing words, nomenclature errors, incorrect citations, and similar technical mistakes made in numerous final rules published in the **Federal Register**, and corrects printing omissions and other printing errors in the **Federal Register** and Code of Federal Regulations, in order to improve the clarity of the regulations. The application, implementation, and enforcement of the regulations addressed in this rule are not changed in any way.

II. Why Is This Correction Issued as a Final Rule?

Section 553 of the Administrative Procedures Act (APA), 5 U.S.C. 553(b), requires agencies to provide prior notice and opportunity for public comment before issuing a final rule. However, an agency may issue a rule without providing notice and an opportunity for public comment if it finds that notice and public comment procedures are impracticable, unnecessary, or contrary to the public interest (*see* 5 U.S.C. 553(b)(3)(B)). EPA has determined that there is good cause for making this action final without prior proposal and opportunity for public comment because these corrections to the Code of Federal Regulations do not change the regulatory requirements for the hazardous waste management program, and therefore comment is unnecessary. This action corrects typographical and printing errors, incorrect citations resulting primarily from a failure to identify and make conforming changes to internal references when obsolete requirements are removed and subsequent paragraphs are redesignated, and similar mistakes. For these reasons, EPA believes that there is good cause under 5 U.S.C. 553(b)(3) for issuing these corrections as a final rule, and that it is in the public interest to make the corrections to the CFR immediately effective, without going through notice and comment procedures.

III. What Does This Rule Do and Why Are the Corrections Necessary?

This rule corrects approximately 500 errors in the 40 CFR hazardous waste and used oil regulations. As discussed in Section I. above, these errors resulted from such mistakes as typographical and printing errors, and incorrect citations often resulting from EPA's failure to make conforming changes to internal references when, for example, removing obsolete requirements and making associated redesignations of paragraphs; this action also replaces references to DOT regulations that have been superceded (and are thus no longer in the CFR) with the verbatim language of the superceded DOT regulations without changing the implementation and enforcement of the regulations in any way. EPA believes that the errors cause confusion and that the corrections will facilitate understanding of the hazardous waste and used oil regulations.

In developing this rule, EPA accumulated a lengthy list of suggested "technical" corrections, including a number from EPA regions and the States who implement these regulations. Today's action represents approximately 85 percent of the suggested technical corrections received. EPA will continue to examine the remaining 15 percent for a subsequent technical corrections rule.

The 40 CFR sections where corrections are being made are listed below, organized by part. For a number of these, where the correction is not so obvious (e.g., is not a simple misspelling), a description of the change and an explanation are provided. As can be seen by these descriptions, none of the corrections in today's notice changes the original substance or meaning of these sections.

A. Corrections to 40 CFR Part 260 (Hazardous Waste Management System: General)

1. EPA is amending the following sections in 40 CFR part 260 in order to correct typographical errors and incorrect citations: Section 260.10 definitions of "Designated facility," "Incompatible waste," "Personnel or facility personnel," "Universal waste," and "Used oil;" and §§ 260.22, 260.40, and 260.41.

2. *40 CFR 260.40 and 260.41:* EPA is making a conforming change to § 260.40(a) and to the introductory language in § 260.41 by revising the reference "§ 261.6(a)(2)(iv)" to read "§ 261.6(a)(2)(iii)." When §§ 260.40 and 260.41 were first added (50 FR 662 and 663, January 4, 1985), § 260.6 was revised (50 FR 665, January 4, 1985) such that paragraph (a)(2)(iii) was reserved for used oil, paragraph (a)(2)(iv) referred to precious metals, and paragraph (a)(2)(v) referred to spent lead-acid batteries. Subsequently, in the used oil regulations (57 FR 41612, September 10, 1992), § 261.6(a)(2) paragraph (iii) was deleted, and paragraphs (iv) and (v) were redesignated as paragraphs (iii) and (iv), but the conforming changes were not made to §§ 260.40 and 260.41, by redesignating § 261.6(a)(2)(iv) to § 261.6(a)(2)(iii), to keep the reference to precious metals. Today's rule makes this conforming correction. EPA also notes that the reference in § 260.41 to subpart F of part 266 correctly addresses precious metals recovery (it is subpart G of part 266 that addresses spent lead-acid batteries reclamation).

B. Corrections to Part 261 (Identification and Listing of Hazardous Waste)

1. EPA is amending the following sections of 40 CFR part 261 in order to correct typographical and spelling errors, incorrect citations, and printing errors: Sections 261.2, 261.3, 261.4, 261.6, 261.21, 261.24, 261.31, 261.32, 261.33, 261.38, Appendix VII (F002, F038, F039, K001, and K073 entries), and Appendix VIII.

2. *40 CFR 261.21(a)(3) and 261.21(a)(4):* When EPA first promulgated the ignitability characteristic for hazardous waste identification, the Agency incorporated, by reference, U.S. Department of Transportation (DOT) regulations (contained in Title 49 of the CFR) that defined an ignitable compressed gas and

an oxidizer. In 1990, DOT revised and recodified its regulations governing transportation of hazardous materials, including the sections of 49 CFR referenced by 40 CFR 261.21.[1] The referenced DOT regulations were both revised and moved within 49 CFR; as a result, the hazardous characteristic definitions at 40 CFR 261.21(a)(3) and 261.21(a)(4) now refer to nonexistent or irrelevant sections of the DOT regulations.

Since these original DOT regulations are still required under RCRA, EPA is replacing the obsolete references to the DOT regulations contained in the definitions for an ignitable compressed gas and an oxidizer, 40 CFR 261.21(a)(3) and 261.21(a)(4), respectively, with the actual language from the referenced sections of the DOT regulations that was published in Title 49 of the CFR at the time of the finalization of the RCRA regulations (1980). Because it can be difficult to obtain copies of the CFR from 1980, this revision will make it easier for the regulated community to find and apply the definitions of ignitable compressed gas and oxidizer for the purposes of 261.21. The implementation and enforcement of the ignitability characteristic will not change in any way. The Agency is simply publishing the original definitions to ease the burden on the regulated community.

3. *40 CFR 261.31(a):* This section was amended June 29, 1995 (60 CFR 33913), by removing footnote 1 from the table (referring to a temporary stay of the effective date of regulations listing certain wood preserving wastes as hazardous wastes). The Office of **Federal Register**, by mistake, also removed the footnote designated by an asterisk (*) which said "*(I,T) should be used to specify mixtures containing ignitable and toxic constituents." Today's notice restores and clarifies the footnote to read "*(I,T) should be used to specify mixtures that are ignitable and contain toxic constituents."

4. *40 CFR 261.33(e) and 261.33(f):* The Tables in §§ 261.33(e) and 261.33(f) describe P-listed waste and U-listed waste, respectively. The wastes listed in these Tables are currently organized alphabetically, by substance. In order to simplify the use of the Tables in §§ 231.33(e) and 261.33(f), this rule adds a list of the same wastes organized numerically, by Hazardous Waste Number, to the end of each Table. The Table in § 261.33(e) will now have an alphabetical list of P-listed wastes followed by a numerical list of P-listed wastes, and the Table in § 261.33(f) will now have an alphabetical list of U-listed wastes followed by a numerical list of U-listed wastes. The wastes listed in these Tables are not being changed, except to correct typographical errors. This revision is included to make the Tables in §§ 261.33(e) and 261.33 (f) easier to use and does not substantively change the regulations governing P-listed or U-listed wastes.

C. Corrections to Part 262 (Standards Applicable to Generators of Hazardous Waste)

1. EPA is amending the following sections in 40 CFR part 262 in order to correct typographical errors and incorrect citations, and to update EPA addresses and the list of OECD countries: Sections 262.34, 262.53, 262.56, 262.58, 262.70, 262.81, 262.82, 262.83, 262.84, 262.87, 262.90, and the introductory paragraph to the part 262 Appendix.

2. *40 CFR 262.53(b), 262.56(b), 262.83(b)(1)(i), 262.83(b)(2)(i), 262.84(e), and 262.87(a):* These sections are all being amended by updating the mailing and hand delivery addresses for delivery of the various export notifications, reports and tracking documents to EPA.

3. *40 CFR 262.58(a)(1):* This section is being amended to update the list of designated OECD Member countries by adding the Czech Republic, Hungary, Poland, the Slovak Republic, and South Korea to accurately reflect the current membership.

4. *40 CFR 262.81(k):* This section is being amended by updating the address for the EPA RCRA Docket.

D. Corrections to Part 264 (Standards for Owners and Operators of Hazardous Waste Treatment, Storage, and Disposal Facilities

1. EPA is amending the following sections of 40 CFR part 264 in order to correct typographical and spelling errors, incorrect citations, and printing errors: Sections 264.1, 264.4, 264.13, 264.17, 264.18, 264.97, 264.98, 264.99, 264.101, 264.111, 264.112, 264.115, 264.116, 264.118, 264.119, 264.140, 264.142, 264.143, 264.145, 264.147, 264.151, 264.175, 264.193, 264.221, 264.223, 264.226, 264.251, 264.252, 264.259, 264.280, 264.283, 264.301, 264.302, 264.304, 264.314, 264.317, 264.344, 264.552, 264.553, 264.554, 264.555, 264.573, 264.600, 264.601, 264.1030, 264.1033, 264.1034, 264.1035, 264.1050, 264.1058, 264.1064, 264.1080, 264.1090, 264.1101, 264.1102, and Tables 1 and 2 of Appendix I.

2. *40 CFR 264.112(b)(8) and 264.140(d)(1):* On October 22, 1998 (63 FR 56710), EPA issued a final rule establishing new requirements related to closure and post-closure care at land disposal facilities. Today's rule corrects two typographical errors that appeared in the October 22, 1998 final rule. Sections 264.112(b)(8) and 264.140(d)(1)of that rule referred to § 264.110(d), when they should have referred to § 264.110(c). This error is evidenced by the fact that § 264.110(d) does not exist. In addition, the preamble of the final rule correctly refers to § 264.110(c) in the text under Table 1 (63 FR 56714). Finally, the corresponding provision in §§ 265.112(b)(8) and 265.140(d)(1) correctly refers to § 265.110(d), which is analogous to § 264.110(c). Thus, this final rule corrects the typographical errors in §§ 264.112(b)(8) and 264.140(d)(1) by changing the incorrect reference "§ 264.110(d)" to read "§ 264.110(c)."

3. *40 CFR 264.221(e)(2)(i)(B), 264.301(e)(2)(i)(B), 264.314(f)(2), 265.221(d)(2)(i)(B), 265.301(d)(2)(i)(B), and 265.314(g)(2):* These sections in 40 CFR parts 264 and 265 all refer to "underground source of drinking water (as that term is defined in § 144.3 of this chapter)." Today's correction replaces the citation "§ 144.3 of this chapter" in each of these sections with "40 CFR 270.2" since both citations contain identical definitions for "underground source of drinking water," but the former is in the Underground Injection Control Program rules and the latter is in the Hazardous Waste Permit Program rules which the user is more likely to have readily available since parts 264 and 265 are the associated Hazardous Waste Facility rules. Today's correction also adds quotes around "underground source of drinking water" to make it clear that this is the term that is defined.

4. *40 CFR 264.573 and 265.443:* Sections 264.572 and 265.442 each provide two options for drip pads: Synthetic liners, in paragraph (a) of both sections; and other low permeability material, in paragraph (b) of both sections. But the design and operating requirements for synthetic liners in paragraphs 264.573(b) and 265.443(b), incorrectly refer to paragraphs 264.572(b) and 265.442(b), respectively; and the design and operating requirements for other low permeability material in paragraphs 264.573(a)(4)(i) and 265.443(a)(4)(i) incorrectly refer to §§ 264.572(a) and 265.442(a), respectively. This mistake was in the original **Federal Register** notice (57 FR 61503, December 24, 1992). Today's action corrects these four references by changing (a) to (b) and (b) to (a) as indicated.

[1] 55 FR 52402.

5. *40 CFR 264.1090(c):* EPA is amending this paragraph to correct a typographical error and to remove a duplicate sentence; no other changes are being made.

6. *40 CFR 264.1101(b)(3)(iii) and 265.1101(b)(3)(iii):* These paragraphs refer to §§ 264.193(d)(1) and 265.193(d)(1), respectively, for the requirements for external liner systems for tanks, but these referenced paragraphs merely provide that a liner external to a tank is an option for meeting secondary containment. The actual requirements for external liner systems for tanks are found in §§ 264.193(e)(1) and 265.193(e)(1), respectively. This mistake was in the original **Federal Register** notice (57 FR 37266, August 18, 1992). Today's action provides the correct paragraphs for the requirements.

7. *Table 1 of Appendix I to 40 CFR Part 264:* EPA is amending Table 1 in order to add the unit of measure codes for "Pounds," "Short tons," "Kilograms," and "Tons."

E. Corrections to Part 265 (Interim Status Standards for Owners and Operators of Hazardous Waste Treatment, Storage, and Disposal Facilities

1. EPA is amending the following sections of 40 CFR part 265 in order to correct typographical and spelling errors, incorrect citations, and printing errors: Sections 265.1, 265.12, 265.14, 265.16, 265.19, 265.56, 265.90, 265.110, 265.111, 265.112, 265.113, 265.117, 265.119, 265.140, 265.142, 265.145, 265.147, 265.174, 265.193, 265.194, 265.197, 265.201, 265.221, 265.223, 265.224, 265.228, 265.229, 265.255, 265.259, 265.280, 265.281, 265.301, 265.302, 265.303, 265.312, 265.314, 265.316, 265.405, 265.441, 265.443, 265.445, 265.1033, 265.1035, 265.1063, 265.1080, 265.1085, 265.1087, 265.1090, 265.1100, 265.1101, Tables 1 and 2 of Appendix I, Appendix V, and Appendix VI.

2. *40 CFR 265.147(b)(1)(i) and (ii):* Because of a printing error, 40 CFR 265.147(a)(1)(i) and (ii), and 265.147(b)(1)(i) and (ii) were omitted from the July 1, 1989, 1990 and 1991 CFRs, although they were included in earlier editions of the **Federal Register** and CFRs. A September 23, 1991 (56 FR 47912) correction to the CFR published in the **Federal Register** corrected the omission of § 265.147(a)(1)(i) and (ii) from those CFRs, but did not mention the omission of § 265.147(b)(1)(i) and (ii) from the CFR. This correction is being made to be sure the subparagraphs in 265.147(b)(1) are in the next edition of the CFR.

3. *40 CFR 265.174:* The Burden Reduction Rule (71 FR 16910, April 4, 2006) inadvertently lifted the phrase "and the containment system" from § 264.174 and inserted it into § 265.174. The intent of the Burden Reduction Rule in revising §§ 264.174 and 265.174 was to provide a procedure for Performance Track member facilities to revise their required inspection frequency for container/container areas. At the same time, the Burden Reduction Rule sought to make conforming changes to these sections. Before the Burden Reduction Rule, these two sections, except for the phrase "and the containment system," were identical in meaning (although they used different language).

Section 264.175 contains requirements and specifications for a containment system for the Part 264 container storage areas. There are no requirements for a containment system for Part 265 container storage areas (§ 265.175 does not exist; it is reserved). To simplify, clarify, and avoid confusion, the Burden Reduction Rule attempted to conform these two sections by using the same language in new § 265.174 as in new § 264.174 for the comparable parts; but in the process, the erroneous reference "and the containment system" was retained. Today's notice corrects this error.

4. *40 CFR 265.221:* The April 4, 2006 final rule (71 FR 16911) amended 40 CFR 265.221 (a). In the process, the words "above and" were inadvertently added, such that the paragraph was amended to read, "The owner or operator of each new surface impoundment unit* * * *must install two or more liners, and a leachate collection and removal system above and between the liners* * * *." Table 8 in the preamble (71 FR 16876, April 4, 2006) incorrectly indicated that the existing language in § 265.22 (a) included the words "above and," and the Table indicated that no change was being made here. In actuality, the words "above and" were not in the existing language and EPA indeed had no intent to change this part of the paragraph. As a practical matter, it is impossible to have a "leachate" collection and removal system above a liner in a surface impoundment since the liquid waste itself is there, not leachate.

5. *40 CFR 265.229:* The January 29, 1992 final rule (57 FR 3462) amended 40 CFR 265.228 by redesignating paragraphs (b)(2) and (b)(3) as paragraphs (b)(3) and (b)(4) respectively, and by adding a new paragraph (b)(2). However, instructions for amending § 265.228 were erroneously also applied to § 265.229 (which was not amended by the January 29, 1992 rule), thus resulting in the redesignation of § 265.229(b)(2) and (b)(3) as § 265.229(b)(3) and (b)(4) and the addition of a new § 265.229(b)(2), repeating the paragraph added at § 265.228(b)(2). This error is being corrected by removing 40 CFR 265.229(b)(2), redesignating 40 CFR 265.229(b)(3) and (b)(4) as 40 CFR 265.229(b)(2) and (b)(3), and removing the reference to "57 FR 3493, Jan. 29, 1992" from the **Federal Register** listing at the end of 40 CFR 265.229.

6. *40 CFR 265.1100(d):* Section 265.1100 lists a number of criteria that enable a containment building to not be classified as land disposal under RCRA 3004(k), i.e., that prevent or control releases to the environment. The operable verbs used in this list are: "to prevent" (paragraph (a)), "to withstand" (paragraph (b)), "to prevent" (paragraph (c)(1)), "to minimize" (paragraph (c)(2)), "to prevent" (paragraph (c)(3)), and "to ensure containment and prevent" (paragraph (e)). Yet in paragraph (d), EPA, by mistake, used the word "permit" instead of "prevent," in saying: "Has controls as needed to permit fugitive dust emissions." As further evidence EPA meant "prevent," the comparable paragraph in § 264.1100(d) says: "Has controls sufficient to prevent fugitive dust emissions* * * *." Further, the accompanying design and operating standards in § 265.1101(a)(2)(i) and (c)(1)(iv) require that all containment buildings "provide an effective barrier against fugitive dust emissions," and "control fugitive dust emissions" with "no visible emissions." This mistake was in the original **Federal Register** notice (57 FR 37268, August 18, 1992). Today's action corrects this mistake by changing "permit" to "prevent" in § 265.1100, paragraph (d).

7. *Table 1 of Appendix I to 40 CFR Part 265:* EPA is amending Table 1 in order to add the unit of measure codes for "Pounds," "Short tons," "Kilograms," and "Tons."

F. Corrections to Part 266 (Standards for the Management of Specific Hazardous Wastes and Specific Types of Hazardous Waste Management Facilities)

1. EPA is amending the following sections of 40 CFR part 266 in order to correct typographical and spelling errors, incorrect citations, and printing errors: Sections 266.70, 266.80, 266.100, 266.102, 266.103, 266.106, 266.109, Title of Subpart N, and Appendices III, IV, V, VI, VIII, IX and XIII.

2. *40 CFR 266.103(c)(1)(i) and (ix):* These provisions were initially

introduced into the Code of Federal Regulations by a final rule published on February 21, 1991 (56 FR 7134), with an amendment to § 266.103(c)(1)(ix) published on July 17, 1991 (56 FR 32688). An August 27, 1991 final rule (56 FR 42504) amended paragraphs (c)(1) and (c)(3)(i), but a printing error by the Office of the Federal Register resulted in the removal of 40 CFR 266.103(c)(1)(i) through (xiii) and 40 CFR 266.103(c)(3)(ii) and (iii) from the 1992 edition of 40 CFR. A September 30, 1992 final rule (57 FR 44999) reinstated these paragraphs and clarified that they were regarded by EPA to have been in effect continuously in the form published in the 1991 CFR and as subsequently amended by an August 25, 1992 final rule (57 FR 38558). However, in reinstating these paragraphs, errors were introduced in the text at § 266.103(c)(1)(i) and (ix). Today's notice is correcting the errors by reinstating the language at § 266.103(c)(1)(i), as introduced by the February 21, 1991 (56 FR 7134) final rule, and the language at § 266.103(c)(1)(ix), as introduced by the February 21, 1991 final rule (56 FR 7134) and amended by the July 17, 1991 final rule (56 FR 32688).

3. *40 CFR 266.106(d)(1):* The August 25, 1992 final rule (57 *FR* 38558), which amended 40 CFR 266.106(d)(1), introduced an error into the Federal code by including the duplicate phrase "dispersion modeling to predict the maximum annual average off-site ground level concentration for each." Today's action corrects the error by removing the duplicate phrase.

G. Corrections to Part 267 (Standards for Owners and Operators of Hazardous Waste Facilities Operating Under a Standardized Permit)

1. EPA is amending 40 CFR part 267 in order to correct the nomenclature in § 267.147.

H. Corrections to Part 268 (Land Disposal Restrictions)

1. EPA is amending the following sections of 40 CFR part 268 in order to correct typographical and spelling errors, incorrect citations, and printing errors: Sections 268.2, 268.4, 268.6, 268.7, 268.14, 268.40, 268.42, 268.44, 268.45, 268.48 Table, 268.49, 268.50, and Appendix VIII.

2. *40 CFR 268.7(b)(4)(ii), (d), (d)(2), and (d)(3):* All these paragraphs incorrectly cite § 261.3(e), which is now "reserved," for debris excluded from the definition of hazardous waste. The exclusion for debris is located in § 261.3(f). This error can be traced to a January 9, 1992 **Federal Register** (57 FR 1013) where it was proposed to place this requirement in § 261.3(e), but in the August 18, 1992 **Federal Register** (57 FR 37264) it was placed in § 261.3(f). It was also the August 18, 1992 final rule that erroneously added six references to § 261.3(e) instead of § 261.3(f). Today's action corrects these citations.

3. *40 CFR 268.7(d)(1) and (d)(1)(i) through (iii):* The August 18, 1992 final rule (57 FR 37194) added 40 CFR 268.7(d)(1) and (d)(1)(i) through (iii) to the Federal code. On January 3, 1995 (60 *FR* 244–245), EPA amended § 268.7(d), introductory text, and (d)(1), but in doing so, erroneously added the duplicate phrase "or State authorized to implement part 268 requirements" in paragraph (d)(1). In addition, the Office of the Federal Register, by mistake, removed paragraphs (d)(1)(i) through (iii). This notice corrects these errors by removing the duplicate phrase at 40 CFR 268.7(d)(1) and reinstating paragraphs (d)(1)(i) through (iii) of 40 CFR 268.7.

I. Corrections to Part 270 (EPA Administered Permit Programs: The Hazardous Waste Permit Program)

EPA is amending the following sections of 40 CFR part 270 in order to correct typographical and spelling errors, and incorrect citations: Sections 270.1, 270.2, 270.10, 270.11, 270.13, 270.14, 270.17, 270.18, 270.20, 270.25, 270.26, 270.33, 270.41, 270.42, 270.42 Appendix I, 270.51, 270.70 and 270.72.

J. Corrections to Part 271 (Requirements for Authorization of State Hazardous Waste Program)

1. EPA is correcting typographical and spelling errors in the following sections of 40 CFR part 271: Sections 271.1, 271.21, and 271.23.

2. *40 CFR 271.21(g)(1)(i):* Today's action restores language that the CFR mistakenly changed between the 1996 and 1997 CFRs, by revising "The State has received an extension of the program modification deadline * * * and has made dils to revise its program * * *" to read "The State has received an extension of the program modification deadline * * * and has made diligent efforts to revise its program * * *."

K. Corrections to Part 273 (Standards for Universal Waste Management)

EPA is amending the following sections of 40 CFR part 273 in order to correct typographical and spelling errors: Sections 273.9, 273.13, 273.14, 273.34 and 273.61.

L. Corrections to Part 279 (Standards for the Management of Used Oil)

EPA is amending the following sections of 40 CFR part 279 in order to correct typographical and spelling errors, and incorrect citations: §§ 279.1, 279.10, 279.11, 279.43, 279.44, 279.45, 279.52, 279.55, 279.56, 279.57, 279.59, 279.63, 279.64, and 279.70.

IV. Statutory and Executive Order Reviews

This final rule corrects errors introduced into the CFR by numerous previous rules and does not create any new regulatory requirements. Therefore, this rule complies with applicable executive orders and statutory provisions as follows.

1. *Executive Order 12866: Regulatory Planning Review*—Because this rule corrects errors in the CFR and does not create any new regulatory requirements, EPA has determined that this rule is not a "significant regulatory action" under the terms of Executive Order 12866 (58 FR 51735, October 4, 1993) and is therefore not subject to review by the Office of Management and Budget (OMB).

2. *Paperwork Reduction Act*—This rule does not impose an information collection burden under the provisions of the Paperwork Reduction Act of 1995 (44 U.S.C. 3501 *et seq.*).

3. *Regulatory Flexibility Act*—This rule corrects errors in the CFR and does not impose new burdens on small entities. Accordingly, I certify that this action will not have a significant economic impact on a substantial number of small entities under the Regulatory Flexibility Act (5 U.S.C. 601 *et seq.*).

4. *Unfunded Mandates Reform Act*—Because this rule only corrects errors in the CFR, it does not contain any unfunded mandate or significantly or uniquely affect small governments, as described in the Unfunded Mandates Reform Act of 1995 (Pub. L. 104–4).

5. *Executive Order 13132: Federalism*—Executive Order 13132 (64 FR 43255, August 10, 1999) does not apply to this rule because it will not have federalism implications (i.e., substantial direct effects on the States, on the relationship between the Federal government and the States, or on the distribution of power and responsibilities among the various levels of government).

6. *Executive Order 13175: Consultation and Coordination with Indian Tribal Governments*—Executive Order 13175 (65 FR 67249, November 6, 2000) does not apply to this rule because it will not have tribal

implications (i.e., substantial direct effects on one or more Indian tribes, or on the relationship between the Federal government and Indian tribes, or on the distribution of power and responsibilities between the Federal government and Indian tribes).

7. *Executive Order 13045: Protection of Children from Environmental Health and Safety Risks*—This rule is not subject to Executive Order 13045 (62 FR 19885, April 23, 1997), because it is not economically significant and it is not based on environmental health or safety risks.

8. *Executive Order 13211: Actions that Significantly Affect Energy Supply, Distribution, or Use*—This rule is not subject to Executive Order 13211 (66 FR 28355, May 22, 2001) because it is not a significant regulatory action under Executive Order 12866.

9. *National Technology Transfer Advancement Act*—The requirements of section 12(d) of the National Technology Transfer and Advancement Act of 1995 (15 U.S.C. 272 note) do not apply because this rule only corrects errors in the CFR and does not involve technical standards.

10. *Executive Order 12988*—As required by section 3 of Executive Order 12988 (61 FR 4729, February 7, 1996), EPA has taken the necessary steps in this action to eliminate drafting errors and ambiguity, minimize potential litigation, and provide a clear legal standard for affected conduct.

11. *Congressional Review Act*—EPA will submit a report containing this rule and other information required by the Congressional Review Act (5 U.S.C. 801 *et seq.*, as amended) to the U.S. Senate, the U.S. House of Representatives, and the Comptroller General of the United States prior to publication in the **Federal Register.** A major rule cannot take effect until 60 days after it is published in the **Federal Register.** This action is not a "major rule" as defined by 5 U.S.C. 804(2). This action is effective July 14, 2006.

List of Subjects

40 CFR Part 260

Environmental protection, Administrative practice and procedure, Confidential business information, Hazardous waste, Reporting and recordkeeping requirements.

40 CFR Part 261

Environmental protection, Hazardous waste, Recycling, Reporting and recordkeeping requirements.

40 CFR Part 262

Environmental protection, Exports, Hazardous materials transportation, Hazardous waste, Imports, Labeling, Packaging and containers, Reporting and recordkeeping requirements.

40 CFR Parts 264 and 265

Environmental protection, Air pollution control, Hazardous waste, Insurance, Packaging and containers, Reporting and recordkeeping requirements, Security measures, Surety bonds.

40 CFR Part 266

Hazardous waste, Recyclable materials, Boilers and industrial furnaces, Low-level mixed waste.

40 CFR Part 267

Standardized permits, Financial test.

40 CFR Part 268

Environmental protection, Hazardous materials, Reporting and recordkeeping requirements.

40 CFR Part 270

Environmental protection, Administrative practice and procedure, Confidential business information, Hazardous materials transportation, Hazardous waste, Reporting and recordkeeping requirements, Water pollution control, Water supply.

40 CFR Part 271

Environmental protection, Administrative practice and procedure, Confidential business information, Hazardous materials transportation, Hazardous waste, Indian lands, Intergovernmental relations, Penalties, Reporting and recordkeeping requirements, Water pollution control, Water supply.

40 CFR Part 273

Environmental protection, Hazardous materials transportation, Hazardous waste.

40 CFR Part 279

Environmental protection, Petroleum, Recycling, Reporting and recordkeeping requirements.

Dated: June 16, 2006.

Susan Parker Bodine,

Assistant Administrator for Office of Solid Waste and Emergency Response.

■ For the reasons set out in the preamble, 40 CFR Parts 260, 261, 262, 264, 265, 266, 267 268, 270, 271, 273, and 279 are amended as follows:

PART 260—HAZARDOUS WASTE MANAGEMENT SYSTEM: GENERAL

■ 1. The authority citation for part 260 continues to read as follows:

Authority: 42 U.S.C. 6905, 6912(a), 6921–6927, 6930, 6934, 6935, 6937, 6938, 6939, and 6974.

§ 260.10 [Amended]

■ 2. Amend § 260.10 as follows:
■ a. In the definition of "*Incompatible waste,*" revise the parenthetical phrase "(See part 265, appendix V, of this chapter for examples.)" to read "(See appendix V of parts 264 and 265 of this chapter for examples.)";
■ b. In the definition of "*Personnel or facility personnel,*" remove the comma after the word "work";
■ c. In the definition of "*Universal waste,*" remove the section symbol "§" in front of "273";
■ d. In the definition of "*Used oil,*" revise "in contaminated" to read "is contaminated".

§ 260.22 [Amended]

■ 3. Amend § 260.22 as follows:
■ a. In paragraph (a)(1), revise "actutely" to read "acutely";
■ b. In paragraph (d)(1)(ii), revise "hazrdous" to read "hazardous".

§ 260.40 [Amended]

■ 4. In § 260.40, amend paragraph (a) by revising the citation "§ 261.6(a)(2)(iv)" to read "§ 261.6(a)(2)(iii)".

§ 260.41 [Amended]

■ 5. Amend the § 260.41 introductory text by revising the citation "§ 261.6(a)(2)(iv)" to read "§ 261.6(a)(2)(iii)".

PART 261—IDENTIFICATION AND LISTING OF HAZARDOUS WASTE

■ 6. The authority citation for Part 261 continues to read as follows:

Authority: 42 U.S.C. 6905, 6912(a), 6921, 6922, 6924(y), and 6938.

§ 261.2 [Amended]

■ 7. Amend § 261.2 (c)(1)(i) by revising the reference to "Table I" to read "Table 1"(*i.e.*, revise the letter "I" to be the number "1").

§ 261.3 [Amended]

■ 8. Amend § 261.3(a)(2)(i) by revising the reference to "table I" to read "Table 1" (*i.e.*, revise the letter "I" to be the number "1").

§ 261.4 [Amended]

■ 9. Amend § 261.4 as follows: a. In paragraph (a)(20)(v), revise "inparagraph" by inserting a space to read "in paragraph";
■ b. In paragraph (b)(6)(i)(B), revise "exlcusively" to read "exclusively";
■ c. In paragraph (b)(6)(ii) introductory text, revise "Specific waste" to read "Specific wastes";

■ d. In paragraph (b)(6)(ii)(D), revise "crome" to read "chrome";
■ e. In paragraph (b)(6)(ii)(F), revise "sludes" to read "sludges", and revise the word "chrometan" to read "chrome tan";
■ f. In paragraph (b)(9), revise "and wood product" to read "and wood products";
■ g. In paragraph (e)(2)(vi), revise the citation "(e)(v)(C)" to read "(e)(2)(v)(C)";
■ h. In paragraph (e)(3)(i) first sentence, revise "treatabilty" to read "treatability".

§ 261.6 [Amended]

■ 10. Amend § 261.6 as follows:
■ a. In paragraph (a)(2)(i), remove the parenthetical phrase "(subpart C)" and add "(40 CFR part 266, subpart C)" in its place;
■ b. In paragraph (a)(2)(ii), remove the parenthetical phrase "(subpart H)" and add "(40 CFR part 266, subpart H)" in its place;
■ c. In paragraph (a)(2)(iii), remove the parenthetical phrase "(subpart F)" and add "(40 CFR part 266, subpart F)" in its place;
■ d. In paragraph (a)(2)(iv), remove the parenthetical phrase "(subpart G)" and add "(40 CFR part 266, subpart G)" in its palce;
■ e. In paragraph (a)(2)(v), remove the parenthetical phrase "(subpart O)" and add "(40 CFR part 266, subpart O)" in its place;
■ f. In paragraph (c)(2), revise the word "rcycled" to read "recycled".

§ 261.21 [Amended]

■ 11. In § 261.21, revise paragraphs (a)(3) and (a)(4) and add notes 1 through 4 to the end of the section to read as follows:

§ 261.21 Characteristic of ignitability.

(a) * * *

(3) It is an ignitable compressed gas.

(i) The term "compressed gas" shall designate any material or mixture having in the container an absolute pressure exceeding 40 p.s.i. at 70 °F or, regardless of the pressure at 70 °F, having an absolute pressure exceeding 104 p.s.i. at 130 °F; or any liquid flammable material having a vapor pressure exceeding 40 p.s.i. absolute at 100 °F as determined by ASTM Test D–323.

(ii) A compressed gas shall be characterized as ignitable if any one of the following occurs:

(A) Either a mixture of 13 percent or less (by volume) with air forms a flammable mixture or the flammable range with air is wider than 12 percent regardless of the lower limit. These limits shall be determined at atmospheric temperature and pressure. The method of sampling and test procedure shall be acceptable to the Bureau of Explosives and approved by the director, Pipeline and Hazardous Materials Technology, U.S. Department of Transportation (see Note 2).

(B) Using the Bureau of Explosives' Flame Projection Apparatus (see Note 1), the flame projects more than 18 inches beyond the ignition source with valve opened fully, or, the flame flashes back and burns at the valve with any degree of valve opening.

(C) Using the Bureau of Explosives' Open Drum Apparatus (see Note 1), there is any significant propagation of flame away from the ignition source.

(D) Using the Bureau of Explosives' Closed Drum Apparatus (see Note 1), there is any explosion of the vapor-air mixture in the drum.

(4) It is an oxidizer. An oxidizer for the purpose of this subchapter is a substance such as a chlorate, permanganate, inorganic peroxide, or a nitrate, that yields oxygen readily to stimulate the combustion of organic matter (see Note 4).

(i) An organic compound containing the bivalent -O-O- structure and which may be considered a derivative of hydrogen peroxide where one or more of the hydrogen atoms have been replaced by organic radicals must be classed as an organic peroxide unless:

(A) The material meets the definition of a Class A explosive or a Class B explosive, as defined in § 261.23(a)(8), in which case it must be classed as an explosive,

(B) The material is forbidden to be offered for transportation according to 49 CFR 172.101 and 49 CFR 173.21,

(C) It is determined that the predominant hazard of the material containing an organic peroxide is other than that of an organic peroxide, or

(D) According to data on file with the Pipeline and Hazardous Materials Safety Administration in the U.S. Department of Transportation (see Note 3), it has been determined that the material does not present a hazard in transportation.

* * * * *

Note 1: A description of the Bureau of Explosives' Flame Projection Apparatus, Open Drum Apparatus, Closed Drum Apparatus, and method of tests may be procured from the Bureau of Explosives.

Note 2: As part of a U.S. Department of Transportation (DOT) reorganization, the Office of Hazardous Materials Technology (OHMT), which was the office listed in the 1980 publication of 49 CFR 173.300 for the purposes of approving sampling and test procedures for a flammable gas, ceased operations on February 20, 2005. OHMT programs have moved to the Pipeline and Hazardous Materials Safety Administration (PHMSA) in the DOT.

Note 3: As part of a U.S. Department of Transportation (DOT) reorganization, the Research and Special Programs Administration (RSPA), which was the office listed in the 1980 publication of 49 CFR 173.151a for the purposes of determining that a material does not present a hazard in transport, ceased operations on February 20, 2005. RSPA programs have moved to the Pipeline and Hazardous Materials Safety Administration (PHMSA) in the DOT.

Note 4: The DOT regulatory definition of an oxidizer was contained in § 173.151 of 49 CFR, and the definition of an organic peroxide was contained in paragraph 173.151a. An organic peroxide is a type of oxidizer.

§ 261.24 [Amended]

■ 12. In § 261.24, amend paragraph (b) by revising the reference to "Table I" to read "Table 1" (i.e., replace the letter "I" with the number "1").

§ 261.31 [Amended]

■ 13. In § 261.31(a), amend the Table by adding a footnote at the bottom to read as follows: "*(I,T) should be used to specify mixtures that are ignitable and contain toxic constituents.".

§ 261.32 [Amended]

■ 14. In § 261.32, amend the Table entries for "K107" and "K069" as follows:
■ a. In the second column of the row beginning "K107", amend "1,1-dimethyl-hydrazine" by deleting the hyphen to read "1,1-dimethylhydrazine";
■ b. In the second column of the row beginning "K069", add a closing parenthesis after the word "Register".

§ 261.33 [Amended]

■ 15. Amend § 261.33 as follows:
■ a. In paragraph (e), revise the phrase "are subject to be the" to read "are subject to the";
■ b. In paragraph (e), amend the bracketed Comment by adding a sentence at the end, within the brackets, to read as set forth below;
■ c. In the Table in paragraph (e), in the third column of the row beginning "P045", in the substance "2-Butanone, 3,3-dimethyl-l-(methylthio)-,O-[methylamino)carbonyl]oxime", add an opening parenthesis to revise "[methylamino)" to read "[(methylamino)";
■ d. In the Table in paragraph (e), in the third column of the row beginning "P194", in the substance "Ethanimidothioc acid, 2-(dimethylamino)-N-[[(methylamino) carbonyl]oxy]-2-oxo-, methyl ester,"

revise "Ethanimidothioc" to read "Ethanimidothioic";

■ e. In the Table in paragraph (e), in the third column of the second row beginning "P074", revise "Nickel cynaide" to read "Nickel cyanide".

■ f. Add entries to the end of the Table in paragraph (e) to read as set forth below:

■ g. Amend paragraph (f) by revising "manfacturing" to read "manufacturing".

■ h. In paragraph (f), amend the bracketed Comment by adding a sentence to the end, within the brackets, to read as set forth below.

■ i. In the table to paragraph (f), in the entry with "Paraldehyde" in the third column, revise the first column "2" to read "U182";

■ j. In the table of paragrah (f), in the third column of the second row beginning "U216", revise "Thallium chloride Tlcl" to read "thallium chloride TlCl";

■ k. In the table of paragraph (f), add an entry just above the entry for "U227" (in column 1), "79–00–5" (in column 2), and "1,1,2-Trichloroethane" (in column 3) to read as set forth below.

■ l. Add entries to the end of the Table in paragraph (f) as follows:

§ 261.33 Discarded commercial chemical products, off-specification species, container residues, and spill residues thereof.

* * * * *

■ (e) * * *

[*Comment:* * * * Wastes are first listed in alphabetical order by substance and then listed again in numerical order by Hazardous Waste Number.]

* * * * *

NUMERICAL LIST

Hazardous waste No.	Chemical abstracts No.	Substance
P001	[1] 81–81–2	2H-1-Benzopyran-2-one, 4-hydroxy-3-(3-oxo-1-phenylbutyl)-, & salts, when present at concentrations greater than 0.3%
P001	[1] 81–81–2	Warfarin, & salts, when present at concentrations greater than 0.3%
P002	591–08–2	Acetamide, -(aminothioxomethyl)-
P002	591–08–2	1-Acetyl-2-thiourea
P003	107–02–8	Acrolein
P003	107–02–8	2-Propenal
P004	309–00–2	Aldrin
P004	309–00–2	1,4,5,8-Dimethanonaphthalene, 1,2,3,4,10,10-hexa-chloro-1,4,4a,5,8,8a,-hexahydro-, (1alpha,4alpha,4abeta,5alpha,8alpha,8abeta)-
P005	107–18–6	Allyl alcohol
P005	107–18–6	2-Propen-1-ol
P006	20859–73–8	Aluminum phosphide (R,T)
P007	2763–96–4	5-(Aminomethyl)-3-isoxazolol
P007	2763–96–4	3(2H)-Isoxazolone, 5-(aminomethyl)-
P008	504–24–5	4-Aminopyridine
P008	504–24–5	4-Pyridinamine
P009	131–74–8	Ammonium picrate (R)
P009	131–74–8	Phenol, 2,4,6-trinitro-, ammonium salt (R)
P010	7778–39–4	Arsenic acid H_3AsO_4
P011	1303–28–2	Arsenic oxide As_2O_5
P011	1303–28–2	Arsenic pentoxide
P012	1327–53–3	Arsenic oxide As_2O_3
P012	1327–53–3	Arsenic trioxide
P013	542–62–1	Barium cyanide
P014	108–98–5	Benzenethiol
P014	108–98–5	Thiophenol
P015	7440–41–7	Beryllium powder
P016	542–88–1	Dichloromethyl ether
P016	542–88–1	Methane, oxybis[chloro-
P017	598–31–2	Bromoacetone
P017	598–31–2	2-Propanone, 1-bromo-
P018	357–57–3	Brucine
P018	357–57–3	Strychnidin-10-one, 2,3-dimethoxy-
P020	88–85–7	Dinoseb
P020	88–85–7	Phenol, 2-(1-methylpropyl)-4,6-dinitro-
P021	592–01–8	Calcium cyanide
P021	592–01–8	Calcium cyanide $Ca(CN)_2$
P022	75–15–0	Carbon disulfide
P023	107–20–0	Acetaldehyde, chloro-
P023	107–20–0	Chloroacetaldehyde
P024	106–47–8	Benzenamine, 4-chloro-
P024	106–47–8	p-Chloroaniline
P026	5344–82–1	1-(o-Chlorophenyl)thiourea
P026	5344–82–1	Thiourea, (2-chlorophenyl)-
P027	542–76–7	3-Chloropropionitrile
P027	542–76–7	Propanenitrile, 3-chloro-
P028	100–44–7	Benzene, (chloromethyl)-
P028	100–44–7	Benzyl chloride
P029	544–92–3	Copper cyanide
P029	544–92–3	Copper cyanide Cu(CN)
P030	.....	Cyanides (soluble cyanide salts), not otherwise specified
P031	460–19–5	Cyanogen

NUMERICAL LIST—Continued

Hazardous waste No.	Chemical abstracts No.	Substance
P031	460–19–5	Ethanedinitrile
P033	506–77–4	Cyanogen chloride
P033	506–77–4	Cyanogen chloride (CN)Cl
P034	131–89–5	2-Cyclohexyl-4,6-dinitrophenol
P034	131–89–5	Phenol, 2-cyclohexyl-4,6-dinitro-
P036	696–28–6	Arsonous dichloride, phenyl-
P036	696–28–6	Dichlorophenylarsine
P037	60–57–1	Dieldrin
P037	60–57–1	2,7:3,6-Dimethanonaphth[2,3-b]oxirene, 3,4,5,6,9,9-hexachloro-1a,2,2a,3,6,6a,7,7a-octahydro-, (1aalpha,2beta,2aalpha,3beta,6beta,6aalpha,7beta, 7aalpha)-
P038	692–42–2	Arsine, diethyl-
P038	692–42–2	Diethylarsine
P039	298–04–4	Disulfoton
P039	298–04–4	Phosphorodithioic acid, O,O-diethyl S-[2-(ethylthio)ethyl] ester
P040	297–97–2	O,O-Diethyl O-pyrazinyl phosphorothioate
P040	297–97–2	Phosphorothioic acid, O,O-diethyl O-pyrazinyl ester
P041	311–45–5	Diethyl-p-nitrophenyl phosphate
P041	311–45–5	Phosphoric acid, diethyl 4-nitrophenyl ester
P042	51–43–4	1,2-Benzenediol, 4-[1-hydroxy-2-(methylamino)ethyl]-, (R)-
P042	51–43–4	Epinephrine
P043	55–91–4	Diisopropylfluorophosphate (DFP)
P043	55–91–4	Phosphorofluoridic acid, bis(1-methylethyl) ester
P044	60–51–5	Dimethoate
P044	60–51–5	Phosphorodithioic acid, O,O-dimethyl S-[2-(methyl amino)-2-oxoethyl] ester
P045	39196–18–4	2-Butanone, 3,3-dimethyl-1-(methylthio)-, O-[(methylamino)carbonyl] oxime
P045	39196–18–4	Thiofanox
P046	122–09–8	Benzeneethanamine, alpha,alpha-dimethyl-
P046	122–09–8	alpha,alpha-Dimethylphenethylamine
P047	[1] 534–52–1	4,6-Dinitro-o-cresol, & salts
P047	[1] 534–52–1	Phenol, 2-methyl-4,6-dinitro-, & salts
P048	51–28–5	2,4-Dinitrophenol
P048	51–28–5	Phenol, 2,4-dinitro-
P049	541–53–7	Dithiobiuret
P049	541–53–7	Thioimidodicarbonic diamide $[(H_2 N)C(S)]_2 NH$
P050	115–29–7	Endosulfan
P050	115–29–7	6,9-Methano-2,4,3-benzodioxathiepin, 6,7,8,9,10,10-hexachloro-1,5,5a,6,9,9a-hexahydro-, 3-oxide
P051	[1] 72–20–8	2,7:3,6-Dimethanonaphth [2,3-b]oxirene, 3,4,5,6,9,9-hexachloro-1a,2,2a,3,6,6a,7,7a-octahydro-, (1aalpha,2beta,2abeta,3alpha,6alpha,6abeta,7beta, 7aalpha)-, & metabolites
P051	72–20–8	Endrin
P051	72–20–8	Endrin, & metabolites
P054	151–56–4	Aziridine
P054	151–56–4	Ethyleneimine
P056	7782–41–4	Fluorine
P057	640–19–7	Acetamide, 2-fluoro-
P057	640–19–7	Fluoroacetamide
P058	62–74–8	Acetic acid, fluoro-, sodium salt
P058	62–74–8	Fluoroacetic acid, sodium salt
P059	76–44–8	Heptachlor
P059	76–44–8	4,7-Methano-1H-indene, 1,4,5,6,7,8,8-heptachloro-3a,4,7,7a-tetrahydro-
P060	465–73–6	1,4,5,8-Dimethanonaphthalene, 1,2,3,4,10,10-hexa-chloro-1,4,4a,5,8,8a-hexahydro-, (1alpha,4alpha,4abeta,5beta,8beta,8abeta)-
P060	465–73–6	Isodrin
P062	757–58–4	Hexaethyl tetraphosphate
P062	757–58–4	Tetraphosphoric acid, hexaethyl ester
P063	74–90–8	Hydrocyanic acid
P063	74–90–8	Hydrogen cyanide
P064	624–83–9	Methane, isocyanato-
P064	624–83–9	Methyl isocyanate
P065	628–86–4	Fulminic acid, mercury(2+) salt (R,T)
P065	628–86–4	Mercury fulminate (R,T)
P066	16752–77–5	Ethanimidothioic acid, N-[[(methylamino)carbonyl]oxy]-, methyl ester
P066	16752–77–5	Methomyl
P067	75–55–8	Aziridine, 2-methyl-
P067	75–55–8	1,2-Propylenimine
P068	60–34–4	Hydrazine, methyl-
P068	60–34–4	Methyl hydrazine
P069	75–86–5	2-Methyllactonitrile
P069	75–86–5	Propanenitrile, 2-hydroxy-2-methyl-
P070	116–06–3	Aldicarb
P070	116–06–3	Propanal, 2-methyl-2-(methylthio)-, O-[(methylamino)carbonyl]oxime
P071	298–00–0	Methyl parathion

NUMERICAL LIST—Continued

Hazardous waste No.	Chemical abstracts No.	Substance
P071	298–00–0	Phosphorothioic acid, O,O,-dimethyl O-(4-nitrophenyl) ester
P072	86–88–4	alpha-Naphthylthiourea
P072	86–88–4	Thiourea, 1-naphthalenyl-
P073	13463–39–3	Nickel carbonyl
P073	13463–39–3	Nickel carbonyl $Ni(CO)_4$, (T-4)-
P074	557–19–7	Nickel cyanide
P074	557–19–7	Nickel cyanide $Ni(CN)_2$
P075	[1] 54–11–5	Nicotine, & salts
P075	[1] 54–11–5	Pyridine, 3-(1-methyl-2-pyrrolidinyl)-, (S)-, & salts
P076	10102–43–9	Nitric oxide
P076	10102–43–9	Nitrogen oxide NO
P077	100–01–6	Benzenamine, 4-nitro-
P077	100–01–6	p-Nitroaniline
P078	10102–44–0	Nitrogen dioxide
P078	10102–44–0	Nitrogen oxide NO_2
P081	55–63–0	Nitroglycerine (R)
P081	55–63–0	1,2,3-Propanetriol, trinitrate (R)
P082	62–75–9	Methanamine, -methyl-N-nitroso-
P082	62–75–9	N-Nitrosodimethylamine
P084	4549–40–0	N-Nitrosomethylvinylamine
P084	4549–40–0	Vinylamine, -methyl-N-nitroso-
P085	152–16–9	Diphosphoramide, octamethyl-
P085	152–16–9	Octamethylpyrophosphoramide
P087	20816–12–0	Osmium oxide OsO_4, (T-4)-
P087	20816–12–0	Osmium tetroxide
P088	145–73–3	Endothall
P088	145–73–3	7-Oxabicyclo[2.2.1]heptane-2,3-dicarboxylic acid
P089	56–38–2	Parathion
P089	56–38–2	Phosphorothioic acid, O,O-diethyl O-(4-nitrophenyl) ester
P092	62–38–4	Mercury, (acetato-O)phenyl-
P092	62–38–4	Phenylmercury acetate
P093	103–85–5	Phenylthiourea
P093	103–85–5	Thiourea, phenyl-
P094	298–02–2	Phorate
P094	298–02–2	Phosphorodithioic acid, O,O-diethyl S-[(ethylthio)methyl] ester
P095	75–44–5	Carbonic dichloride
P095	75–44–5	Phosgene
P096	7803–51–2	Hydrogen phosphide
P096	7803–51–2	Phosphine
P097	52–85–7	Famphur
P097	52–85–7	Phosphorothioic acid, O-[4-[(dimethylamino)sulfonyl]phenyl] O,O-dimethyl ester
P098	151–50–8	Potassium cyanide
P098	151–50–8	Potassium cyanide K(CN)
P099	506–61–6	Argentate(1-), bis(cyano-C)-, potassium
P099	506–61–6	Potassium silver cyanide
P101	107–12–0	Ethyl cyanide
P101	107–12–0	Propanenitrile
P102	107–19–7	Propargyl alcohol
P102	107–19–7	2-Propyn-1-ol
P103	630–10–4	Selenourea
P104	506–64–9	Silver cyanide
P104	506–64–9	Silver cyanide Ag(CN)
P105	26628–22–8	Sodium azide
P106	143–33–9	Sodium cyanide
P106	143–33–9	Sodium cyanide Na(CN)
P108	[1] 157–24–9	Strychnidin-10-one, & salts
P108	[1] 157–24–9	Strychnine, & salts
P109	3689–24–5	Tetraethyldithiopyrophosphate
P109	3689–24–5	Thiodiphosphoric acid, tetraethyl ester
P110	78–00–2	Plumbane, tetraethyl-
P110	78–00–2	Tetraethyl lead
P111	107–49–3	Diphosphoric acid, tetraethyl ester
P111	107–49–3	Tetraethyl pyrophosphate
P112	509–14–8	Methane, tetranitro-(R)
P112	509–14–8	Tetranitromethane (R)
P113	1314–32–5	Thallic oxide
P113	1314–32–5	Thallium oxide $Tl_2 O_3$
P114	12039–52–0	Selenious acid, dithallium(1+) salt
P114	12039–52–0	Tetraethyldithiopyrophosphate
P115	7446–18–6	Thiodiphosphoric acid, tetraethyl ester
P115	7446–18–6	Plumbane, tetraethyl-

NUMERICAL LIST—Continued

Hazardous waste No.	Chemical abstracts No.	Substance
P116	79–19–6	Tetraethyl lead
P116	79–19–6	Thiosemicarbazide
P118	75–70–7	Methanethiol, trichloro-
P118	75–70–7	Trichloromethanethiol
P119	7803–55–6	Ammonium vanadate
P119	7803–55–6	Vanadic acid, ammonium salt
P120	1314–62–1	Vanadium oxide V_2O_5
P120	1314–62–1	Vanadium pentoxide
P121	557–21–1	Zinc cyanide
P121	557–21–1	Zinc cyanide $Zn(CN)_2$
P122	1314–84–7	Zinc phosphide $Zn_3 P_2$, when present at concentrations greater than 10% (R,T)
P123	8001–35–2	Toxaphene
P127	1563–66–2	7-Benzofuranol, 2,3-dihydro-2,2-dimethyl-, methylcarbamate.
P127	1563–66–2	Carbofuran
P128	315–8–4	Mexacarbate
P128	315–18–4	Phenol, 4-(dimethylamino)-3,5-dimethyl-, methylcarbamate (ester)
P185	26419–73–8	1,3-Dithiolane-2-carboxaldehyde, 2,4-dimethyl-, O-[(methylamino)-carbonyl]oxime.
P185	26419–73–8	Tirpate
P188	57–64–7	Benzoic acid, 2-hydroxy-, compd. with (3aS-cis)-1,2,3,3a,8,8a-hexahydro-1,3a,8-trimethylpyrrolo[2,3-b]indol-5-yl methylcarbamate ester (1:1)
P188	57–64–7	Physostigmine salicylate
P189	55285–14–8	Carbamic acid, [(dibutylamino)-thio]methyl-, 2,3-dihydro-2,2-dimethyl-7-benzofuranyl ester
P189	55285–14–8	Carbosulfan
P190	1129–41–5	Carbamic acid, methyl-, 3-methylphenyl ester
P190	1129–41–5	Metolcarb
P191	644–64–4	Carbamic acid, dimethyl-, 1-[(dimethyl-amino)carbonyl]-5-methyl-1H-pyrazol-3-yl ester
P191	644–64–4	Dimetilan
P192	119–38–0	Carbamic acid, dimethyl-, 3-methyl-1-(1-methylethyl)-1H-pyrazol-5-yl ester
P192	119–38–0	Isolan
P194	23135–22–0	Ethanimidthioic acid, 2-(dimethylamino)-N-[[(methylamino) carbonyl]oxy]-2-oxo-, methyl ester
P194	23135–22–0	Oxamyl
P196	15339–36–3	Manganese, bis(dimethylcarbamodithioato-S,S′)-,
P196	15339–36–3	Manganese dimethyldithiocarbamate
P197	17702–57–7	Formparanate
P197	17702–57–7	Methanimidamide, N,N-dimethyl-N′-[2-methyl-4-[[(methylamino)carbonyl]oxy]phenyl]-
P198	23422–53–9	Formetanate hydrochloride
P198	23422–53–9	Methanimidamide, N,N-dimethyl-N′-[3-[[(methylamino)-carbonyl]oxy]phenyl]-monohydrochloride
P199	2032–65–7	Methiocarb
P199	2032–65–7	Phenol, (3,5-dimethyl-4-(methylthio)-, methylcarbamate
P201	2631–37–0	Phenol, 3-methyl-5-(1-methylethyl)-, methyl carbamate
P201	2631–37–0	Promecarb
P202	64–00–6	m-Cumenyl methylcarbamate
P202	64–00–6	3-Isopropylphenyl N-methylcarbamate
P202	64–00–6	Phenol, 3-(1-methylethyl)-, methyl carbamate
P203	1646–88–4	Aldicarb sulfone
P203	1646–88–4	Propanal, 2-methyl-2-(methyl-sulfonyl)-, O-[(methylamino)carbonyl] oxime
P204	57–47–6	Physostigmine
P204	57–47–6	Pyrrolo[2,3-b]indol-5-ol, 1,2,3,3a,8,8a-hexahydro-1,3a,8-trimethyl-, methylcarbamate (ester), (3aS-cis)-
P205	137–30–4	Zinc, bis(dimethylcarbamodithioato-S,S′)-,
P205	137–30–4	Ziram

[1] CAS Number given for parent compound only.

* * * * *

(f) * * *

[*Comment:* * * * Wastes are first listed in alphabetical order by substance and then listed again in numerical order by Hazardous Waste Number.]

NUMERICAL LIST

Hazardous Waste No.	Chemical abstracts No.	Substance
*	*	* * * * * *
U226	71–55–6	1,1,1-Trichloroethane
*	*	* * * * * *
U001	75–07–0	Acetaldehyde (I)
U001	75–07–0	Ethanal (I)
U002	67–64–1	Acetone (I)
U002	67–64–1	2-Propanone (I)

NUMERICAL LIST—Continued

Hazardous Waste No.	Chemical abstracts No.	Substance
U003	75–05–8	Acetonitrile (I,T)
U004	98–86–2	Acetophenone
U004	98–86–2	Ethanone, 1-phenyl-
U005	53–96–3	Acetamide, -9H-fluoren-2-yl-
U005	53–96–3	2-Acetylaminofluorene
U006	75–36–5	Acetyl chloride (C,R,T)
U007	79–06–1	Acrylamide
U007	79–06–1	2-Propenamide
U008	79–10–7	Acrylic acid (I)
U008	79–10–7	2-Propenoic acid (I)
U009	107–13–1	Acrylonitrile
U009	107–13–1	2-Propenenitrile
U010	50–07–7	Azirino[2′,3′:3,4]pyrrolo[1,2-a]indole-4,7-dione, 6-amino-8-[[(aminocarbonyl)oxy]methyl]-1,1a,2,8,8a,8b-hexahydro-8a-methoxy-5-methyl-, [1aS-(1aalpha, 8beta,8aalpha,8balpha)]-
U010	50–07–7	Mitomycin C
U011	61–82–5	Amitrole
U011	61–82–5	1H-1,2,4-Triazol-3-amine
U012	62–53–3	Aniline (I,T)
U012	62–53–3	Benzenamine (I,T)
U014	492–80–8	Auramine
U014	492–80–8	Benzenamine, 4,4′-carbonimidoylbis[N,N-dimethyl-
U015	115–02–6	Azaserine
U015	115–02–6	L-Serine, diazoacetate (ester)
U016	225–51–4	Benz[c]acridine
U017	98–87–3	Benzal chloride
U017	98–87–3	Benzene, (dichloromethyl)-
U018	56–55–3	Benz[a]anthracene
U019	71–43–2	Benzene (I,T)
U020	98–09–9	Benzenesulfonic acid chloride (C,R)
U020	98–09–9	Benzenesulfonyl chloride (C,R)
U021	92–87–5	Benzidine
U021	92–87–5	[1,1′-Biphenyl]-4,4′-diamine
U022	50–32–8	Benzo[a]pyrene
U023	98–07–7	Benzene, (trichloromethyl)-
U023	98–07–7	Benzotrichloride (C,R,T)
U024	111–91–1	Dichloromethoxy ethane
U024	111–91–1	Ethane, 1,1′-[methylenebis(oxy)]bis[2-chloro-
U025	111–44–4	Dichloroethyl ether
U025	111–44–4	Ethane, 1,1′-oxybis[2-chloro-
U026	494–03–1	Chlornaphazin
U026	494–03–1	Naphthalenamine, N,N′-bis(2-chloroethyl)-
U027	108–60–1	Dichloroisopropyl ether
U027	108–60–1	Propane, 2,2′-oxybis[2-chloro-
U028	117–81–7	1,2-Benzenedicarboxylic acid, bis(2-ethylhexyl) ester
U028	117–81–7	Diethylhexyl phthalate
U029	74–83–9	Methane, bromo-
U029	74–83–9	Methyl bromide
U030	101–55–3	Benzene, 1-bromo-4-phenoxy-
U030	101–55–3	4-Bromophenyl phenyl ether
U031	71–36–3	1-Butanol (I)
U031	71–36–3	n-Butyl alcohol (I)
U032	13765–19–0	Calcium chromate
U032	13765–19–0	Chromic acid H_2CrO_4, calcium salt
U033	353–50–4	Carbonic difluoride
U033	353–50–4	Carbon oxyfluoride (R,T)
U034	75–87–6	Acetaldehyde, trichloro-
U034	75–87–6	Chloral
U035	305–03–3	Benzenebutanoic acid, 4-[bis(2-chloroethyl)amino]-
U035	305–03–3	Chlorambucil
U036	57–74–9	Chlordane, alpha & gamma isomers
U036	57–74–9	4,7-Methano-1H-indene, 1,2,4,5,6,7,8,8-octachloro-2,3,3a,4,7,7a-hexahydro-
U037	108–90–7	Benzene, chloro-
U037	108–90–7	Chlorobenzene
U038	510–15–6	Benzeneacetic acid, 4-chloro-alpha-(4-chlorophenyl)-alpha-hydroxy-, ethyl ester
U038	510–15–6	Chlorobenzilate
U039	59–50–7	p-Chloro-m-cresol
U039	59–50–7	Phenol, 4-chloro-3-methyl-
U041	106–89–8	Epichlorohydrin
U041	106–89–8	Oxirane, (chloromethyl)-
U042	110–75–8	2-Chloroethyl vinyl ether
U042	110–75–8	Ethene, (2-chloroethoxy)-

NUMERICAL LIST—Continued

Hazardous Waste No.	Chemical abstracts No.	Substance
U043	75–01–4	Ethene, chloro-
U043	75–01–4	Vinyl chloride
U044	67–66–3	Chloroform
U044	67–66–3	Methane, trichloro-
U045	74–87–3	Methane, chloro- (I,T)
U045	74–87–3	Methyl chloride (I,T)
U046	107–30–2	Chloromethyl methyl ether
U046	107–30–2	Methane, chloromethoxy-
U047	91–58–7	beta-Chloronaphthalene
U047	91–58–7	Naphthalene, 2-chloro-
U048	95–57–8	o-Chlorophenol
U048	95–57–8	Phenol, 2-chloro-
U049	3165–93–3	Benzenamine, 4-chloro-2-methyl-, hydrochloride
U049	3165–93–3	4-Chloro-o-toluidine, hydrochloride
U050	218–01–9	Chrysene
U051		Creosote
U052	1319–77–3	Cresol (Cresylic acid)
U052	1319–77–3	Phenol, methyl-
U053	4170–30–3	2-Butenal
U053	4170–30–3	Crotonaldehyde
U055	98–82–8	Benzene, (1-methylethyl)-(I)
U055	98–82–8	Cumene (I)
U056	110–82–7	Benzene, hexahydro-(I)
U056	110–82–7	Cyclohexane (I)
U057	108–94–1	Cyclohexanone (I)
U058	50–18–0	Cyclophosphamide
U058	50–18–0	2H-1,3,2-Oxazaphosphorin-2-amine, N,N-bis(2-chloroethyl)tetrahydro-, 2-oxide
U059	20830–81–3	Daunomycin
U059	20830–81–3	5,12-Naphthacenedione, 8-acetyl-10-[(3-amino-2,3,6-trideoxy)-alpha-L-lyxo-hexopyranosyl)oxy]-7,8,9,10-tetrahydro-6,8,11-trihydroxy-1-methoxy-, (8S-cis)-
U060	72–54–8	Benzene, 1,1′-(2,2-dichloroethylidene)bis[4-chloro-
U060	72–54–8	DDD
U061	50–29–3	Benzene, 1,1′-(2,2,2-trichloroethylidene)bis[4-chloro-
U061	50–29–3	DDT
U062	2303–16–4	Carbamothioic acid, bis(1-methylethyl)-, S-(2,3-di chloro-2-propenyl) ester
U062	2303–16–4	Diallate
U063	53–70–3	Dibenz[a,h]anthracene
U064	189–55–9	Benzo[rst]pentaphene
U064	189–55–9	Dibenzo[a,i]pyrene
U066	96–12–8	1,2-Dibromo-3-chloropropane
U066	96–12–8	Propane, 1,2-dibromo-3-chloro-
U067	106–93–4	Ethane, 1,2-dibromo-
U067	106–93–4	Ethylene dibromide
U068	74–95–3	Methane, dibromo-
U068	74–95–3	Methylene bromide
U069	84–74–2	1,2-Benzenedicarboxylic acid, dibutyl ester
U069	84–74–2	Dibutyl phthalate
U070	95–50–1	Benzene, 1,2-dichloro-
U070	95–50–1	o-Dichlorobenzene
U071	541–73–1	Benzene, 1,3-dichloro-
U071	541–73–1	m-Dichlorobenzene
U072	106–46–7	Benzene, 1,4-dichloro-
U072	106–46–7	p-Dichlorobenzene
U073	91–94–1	[1,1′-Biphenyl]-4,4′-diamine, 3,3′-dichloro-
U073	91–94–1	3,3′-Dichlorobenzidine
U074	764–41–0	2-Butene, 1,4-dichloro-(I,T)
U074	764–41–0	1,4-Dichloro-2-butene (I,T)
U075	75–71–8	Dichlorodifluoromethane
U075	75–71–8	Methane, dichlorodifluoro-
U076	75–34–3	Ethane, 1,1-dichloro-
U076	75–34–3	Ethylidene dichloride
U077	107–06–2	Ethane, 1,2-dichloro-
U077	107–06–2	Ethylene dichloride
U078	75–35–4	1,1-Dichloroethylene
U078	75–35–4	Ethene, 1,1-dichloro-
U079	156–60–5	1,2-Dichloroethylene
U079	156–60–5	Ethene, 1,2-dichloro-, (E)-
U080	75–09–2	Methane, dichloro-
U080	75–09–2	Methylene chloride
U081	120–83–2	2,4-Dichlorophenol

NUMERICAL LIST—Continued

Hazardous Waste No.	Chemical abstracts No.	Substance
U081	120–83–2	Phenol, 2,4-dichloro-
U082	87–65–0	2,6-Dichlorophenol
U082	87–65–0	Phenol, 2,6-dichloro-
U083	78–87–5	Propane, 1,2-dichloro-
U083	78–87–5	Propylene dichloride
U084	542–75–6	1,3-Dichloropropene
U084	542–75–6	1-Propene, 1,3-dichloro-
U085	1464–53–5	2,2′-Bioxirane
U085	1464–53–5	1,2:3,4-Diepoxybutane (I,T)
U086	1615–80–1	N,N′-Diethylhydrazine
U086	1615–80–1	Hydrazine, 1,2-diethyl-
U087	3288–58–2	O,O-Diethyl S-methyl dithiophosphate
U087	3288–58–2	Phosphorodithioic acid, O,O-diethyl S-methyl ester
U088	84–66–2	1,2-Benzenedicarboxylic acid, diethyl ester
U088	84–66–2	Diethyl phthalate
U089	56–53–1	Diethylstilbesterol
U089	56–53–1	Phenol, 4,4′-(1,2-diethyl-1,2-ethenediyl)bis-, (E)-
U090	94–58–6	1,3-Benzodioxole, 5-propyl-
U090	94–58–6	Dihydrosafrole
U091	119–90–4	[1,1′-Biphenyl]-4,4′-diamine, 3,3′-dimethoxy-
U091	119–90–4	3,3′-Dimethoxybenzidine
U092	124–40–3	Dimethylamine (I)
U092	124–40–3	Methanamine, -methyl-(I)
U093	60–11–7	Benzenamine, N,N-dimethyl-4-(phenylazo)-
U093	60–11–7	p-Dimethylaminoazobenzene
U094	57–97–6	Benz[a]anthracene, 7,12-dimethyl-
U094	57–97–6	7,12-Dimethylbenz[a]anthracene
U095	119–93–7	[1,1′-Biphenyl]-4,4′-diamine, 3,3′-dimethyl-
U095	119–93–7	3,3′-Dimethylbenzidine
U096	80–15–9	alpha,alpha-Dimethylbenzylhydroperoxide (R)
U096	80–15–9	Hydroperoxide, 1-methyl-1-phenylethyl-(R)
U097	79–44–7	Carbamic chloride, dimethyl-
U097	79–44–7	Dimethylcarbamoyl chloride
U098	57–14–7	1,1-Dimethylhydrazine
U098	57–14–7	Hydrazine, 1,1-dimethyl-
U099	540–73–8	1,2-Dimethylhydrazine
U099	540–73–8	Hydrazine, 1,2-dimethyl-
U101	105–67–9	2,4-Dimethylphenol
U101	105–67–9	Phenol, 2,4-dimethyl-
U102	131–11–3	1,2-Benzenedicarboxylic acid, dimethyl ester
U102	131–11–3	Dimethyl phthalate
U103	77–78–1	Dimethyl sulfate
U103	77–78–1	Sulfuric acid, dimethyl ester
U105	121–14–2	Benzene, 1-methyl-2,4-dinitro-
U105	121–14–2	2,4-Dinitrotoluene
U106	606–20–2	Benzene, 2-methyl-1,3-dinitro-
U106	606–20–2	2,6-Dinitrotoluene
U107	117–84–0	1,2-Benzenedicarboxylic acid, dioctyl ester
U107	117–84–0	Di-n-octyl phthalate
U108	123–91–1	1,4-Diethyleneoxide
U108	123–91–1	1,4-Dioxane
U109	122–66–7	1,2-Diphenylhydrazine
U109	122–66–7	Hydrazine, 1,2-diphenyl-
U110	142–84–7	Dipropylamine (I)
U110	142–84–7	1-Propanamine, N-propyl-(I)
U111	621–64–7	Di-n-propylnitrosamine
U111	621–64–7	1-Propanamine, N-nitroso-N-propyl-
U112	141–78–6	Acetic acid ethyl ester (I)
U112	141–78–6	Ethyl acetate (I)
U113	140–88–5	Ethyl acrylate (I)
U113	140–88–5	2-Propenoic acid, ethyl ester (I)
U114	[1]111–54–6	Carbamodithioic acid, 1,2-ethanediylbis-, salts & esters
U114	[1]111–54–6	Ethylenebisdithiocarbamic acid, salts & esters
U115	75–21–8	Ethylene oxide (I,T)
U115	75–21–8	Oxirane (I,T)
U116	96–45–7	Ethylenethiourea
U116	96–45–7	2-Imidazolidinethione
U117	60–29–7	Ethane, 1,1′-oxybis-(I)
U117	60–29–7	Ethyl ether (I)
U118	97–63–2	Ethyl methacrylate
U118	97–63–2	2-Propenoic acid, 2-methyl-, ethyl ester

NUMERICAL LIST—Continued

Hazardous Waste No.	Chemical abstracts No.	Substance
U119	62–50–0	Ethyl methanesulfonate
U119	62–50–0	Methanesulfonic acid, ethyl ester
U120	206–44–0	Fluoranthene
U121	75–69–4	Methane, trichlorofluoro-
U121	75–69–4	Trichloromonofluoromethane
U122	50–00–0	Formaldehyde
U123	64–18–6	Formic acid (C,T)
U124	110–00–9	Furan (I)
U124	110–00–9	Furfuran (I)
U125	98–01–1	2-Furancarboxaldehyde (I)
U125	98–01–1	Furfural (I)
U126	765–34–4	Glycidylaldehyde
U126	765–34–4	Oxiranecarboxyaldehyde
U127	118–74–1	Benzene, hexachloro-
U127	118–74–1	Hexachlorobenzene
U128	87–68–3	1,3-Butadiene, 1,1,2,3,4,4-hexachloro-
U128	87–68–3	Hexachlorobutadiene
U129	58–89–9	Cyclohexane, 1,2,3,4,5,6-hexachloro-, (1alpha,2alpha,3beta,4alpha,5alpha,6beta)-
U129	58–89–9	Lindane
U130	77–47–4	1,3-Cyclopentadiene, 1,2,3,4,5,5-hexachloro-
U130	77–47–4	Hexachlorocyclopentadiene
U131	67–72–1	Ethane, hexachloro-
U131	67–72–1	Hexachloroethane
U132	70–30–4	Hexachlorophene
U132	70–30–4	Phenol, 2,2′-methylenebis[3,4,6-trichloro-
U133	302–01–2	Hydrazine (R,T)
U134	7664–39–3	Hydrofluoric acid (C,T)
U134	7664–39–3	Hydrogen fluoride (C,T)
U135	7783–06–4	Hydrogen sulfide
U135	7783–06–4	Hydrogen sulfide H_2S
U136	75–60–5	Arsinic acid, dimethyl-
U136	75–60–5	Cacodylic acid
U137	193–39–5	Indeno[1,2,3-cd]pyrene
U138	74–88–4	Methane, iodo-
U138	74–88–4	Methyl iodide
U140	78–83–1	Isobutyl alcohol (I,T)
U140	78–83–1	1-Propanol, 2-methyl- (I,T)
U141	120–58–1	1,3-Benzodioxole, 5-(1-propenyl)-
U141	120–58–1	Isosafrole
U142	143–50–0	Kepone
U142	143–50–0	1,3,4-Metheno-2H-cyclobuta[cd]pentalen-2-one, 1,1a,3,3a,4,5,5,5a,5b,6-decachlorooctahydro-
U143	303–34–4	2-Butenoic acid, 2-methyl-, 7-[[2,3-dihydroxy-2-(1-methoxyethyl)-3-methyl-1-oxobutoxy]methyl]-2,3,5,7a-tetrahydro-1H-pyrrolizin-1-yl ester, [1S-[1alpha(Z),7(2S*,3R*),7aalpha]]-
U143	303–34–4	Lasiocarpine
U144	301–04–2	Acetic acid, lead(2+) salt
U144	301–04–2	Lead acetate
U145	7446–27–7	Lead phosphate
U145	7446–27–7	Phosphoric acid, lead(2+) salt (2:3)
U146	1335–32–6	Lead, bis(acetato-O)tetrahydroxytri-
U146	1335–32–6	Lead subacetate
U147	108–31–6	2,5-Furandione
U147	108–31–6	Maleic anhydride
U148	123–33–1	Maleic hydrazide
U148	123–33–1	3,6-Pyridazinedione, 1,2-dihydro-
U149	109–77–3	Malononitrile
U149	109–77–3	Propanedinitrile
U150	148–82–3	Melphalan
U150	148–82–3	L-Phenylalanine, 4-[bis(2-chloroethyl)amino]-
U151	7439–97–6	Mercury
U152	126–98–7	Methacrylonitrile (I,T)
U152	126–98–7	2-Propenenitrile, 2-methyl- (I,T)
U153	74–93–1	Methanethiol (I,T)
U153	74–93–1	Thiomethanol (I,T)
U154	67–56–1	Methanol (I)
U154	67–56–1	Methyl alcohol (I)
U155	91–80–5	1,2-Ethanediamine, N,N-dimethyl-N′-2-pyridinyl-N′-(2-thienylmethyl)-
U155	91–80–5	Methapyrilene
U156	79–22–1	Carbonochloridic acid, methyl ester (I,T)
U156	79–22–1	Methyl chlorocarbonate (I,T)
U157	56–49–5	Benz[j]aceanthrylene, 1,2-dihydro-3-methyl-
U157	56–49–5	3-Methylcholanthrene

NUMERICAL LIST—Continued

Hazardous Waste No.	Chemical abstracts No.	Substance
U158	101–14–4	Benzenamine, 4,4′-methylenebis[2-chloro-
U158	101–14–4	4,4′-Methylenebis(2-chloroaniline)
U159	78–93–3	2-Butanone (I,T)
U159	78–93–3	Methyl ethyl ketone (MEK) (I,T)
U160	1338–23–4	2-Butanone, peroxide (R,T)
U160	1338–23–4	Methyl ethyl ketone peroxide (R,T)
U161	108–10–1	Methyl isobutyl ketone (I)
U161	108–10–1	4-Methyl-2-pentanone (I)
U161	108–10–1	Pentanol, 4-methyl-
U162	80–62–6	Methyl methacrylate (I,T)
U162	80–62–6	2-Propenoic acid, 2-methyl-, methyl ester (I,T)
U163	70–25–7	Guanidine, -methyl-N′-nitro-N-nitroso-
U163	70–25–7	MNNG
U164	56–04–2	Methylthiouracil
U164	56–04–2	4(1H)-Pyrimidinone, 2,3-dihydro-6-methyl-2-thioxo-
U165	91–20–3	Naphthalene
U166	130–15–4	1,4-Naphthalenedione
U166	130–15–4	1,4-Naphthoquinone
U167	134–32–7	1-Naphthalenamine
U167	134–32–7	alpha-Naphthylamine
U168	91–59–8	2-Naphthalenamine
U168	91–59–8	beta-Naphthylamine
U169	98–95–3	Benzene, nitro-
U169	98–95–3	Nitrobenzene (I,T)
U170	100–02–7	p-Nitrophenol
U170	100–02–7	Phenol, 4-nitro-
U171	79–46–9	2-Nitropropane (I,T)
U171	79–46–9	Propane, 2-nitro- (I,T)
U172	924–16–3	1-Butanamine, N-butyl-N-nitroso-
U172	924–16–3	N-Nitrosodi-n-butylamine
U173	1116–54–7	Ethanol, 2,2′-(nitrosoimino)bis-
U173	1116–54–7	N-Nitrosodiethanolamine
U174	55–18–5	Ethanamine, -ethyl-N-nitroso-
U174	55–18–5	N-Nitrosodiethylamine
U176	759–73–9	N-Nitroso-N-ethylurea
U176	759–73–9	Urea, N-ethyl-N-nitroso-
U177	684–93–5	N-Nitroso-N-methylurea
U177	684–93–5	Urea, N-methyl-N-nitroso-
U178	615–53–2	Carbamic acid, methylnitroso-, ethyl ester
U178	615–53–2	N-Nitroso-N-methylurethane
U179	100–75–4	N-Nitrosopiperidine
U179	100–75–4	Piperidine, 1-nitroso-
U180	930–55–2	N-Nitrosopyrrolidine
U180	930–55–2	Pyrrolidine, 1-nitroso-
U181	99–55–8	Benzenamine, 2-methyl-5-nitro-
U181	99–55–8	5-Nitro-o-toluidine
U182	123–63–7	1,3,5-Trioxane, 2,4,6-trimethyl-
U182	123–63–7	Paraldehyde
U183	608–93–5	Benzene, pentachloro-
U183	608–93–5	Pentachlorobenzene
U184	76–01–7	Ethane, pentachloro-
U184	76–01–7	Pentachloroethane
U185	82–68–8	Benzene, pentachloronitro-
U185	82–68–8	Pentachloronitrobenzene (PCNB)
U186	504–60–9	1-Methylbutadiene (I)
U186	504–60–9	1,3-Pentadiene (I)
U187	62–44–2	Acetamide, -(4-ethoxyphenyl)-
U187	62–44–2	Phenacetin
U188	108–95–2	Phenol
U189	1314–80–3	Phosphorus sulfide (R)
U189	1314–80–3	Sulfur phosphide (R)
U190	85–44–9	1,3-Isobenzofurandione
U190	85–44–9	Phthalic anhydride
U191	109–06–8	2-Picoline
U191	109–06–8	Pyridine, 2-methyl-
U192	23950–58–5	Benzamide, 3,5-dichloro-N-(1,1-dimethyl-2-propynyl)-
U192	23950–58–5	Pronamide
U193	1120–71–4	1,2-Oxathiolane, 2,2-dioxide
U193	1120–71–4	1,3-Propane sultone
U194	107–10–8	1-Propanamine (I,T)
U194	107–10–8	n-Propylamine (I,T)

NUMERICAL LIST—Continued

Hazardous Waste No.	Chemical abstracts No.	Substance
U196	110–86–1	Pyridine
U197	106–51–4	p-Benzoquinone
U197	106–51–4	2,5-Cyclohexadiene-1,4-dione
U200	50–55–5	Reserpine
U200	50–55–5	Yohimban-16-carboxylic acid, 11,17-dimethoxy-18-[(3,4,5-trimethoxybenzoyl)oxy]-, methyl ester,(3beta,16beta,17alpha,18beta,20alpha)-
U201	108–46–3	1,3-Benzenediol
U201	108–46–3	Resorcinol
U202	181–07–2	1,2-Benzisothiazol-3(2H)-one, 1,1-dioxide, & salts
U202	181–07–2	Saccharin, & salts
U203	94–59–7	1,3-Benzodioxole, 5-(2-propenyl)-
U203	94–59–7	Safrole
U204	7783–00–8	Selenious acid
U204	7783–00–8	Selenium dioxide
U205	7488–56–4	Selenium sulfide
U205	7488–56–4	Selenium sulfide SeS_2 (R,T)
U206	18883–66–4	Glucopyranose, 2-deoxy-2-(3-methyl-3-nitrosoureido)-, D-
U206	18883–66–4	D-Glucose, 2-deoxy-2-[[(methylnitrosoamino)-carbonyl]amino]-
U206	18883–66–4	Streptozotocin
U207	95–94–3	Benzene, 1,2,4,5-tetrachloro-
U207	95–94–3	1,2,4,5-Tetrachlorobenzene
U208	630–20–6	Ethane, 1,1,1,2-tetrachloro-
U208	630–20–6	1,1,1,2-Tetrachloroethane
U209	79–34–5	Ethane, 1,1,2,2-tetrachloro-
U209	79–34–5	1,1,2,2-Tetrachloroethane
U210	127–18–4	Ethene, tetrachloro-
U210	127–18–4	Tetrachloroethylene
U211	56–23–5	Carbon tetrachloride
U211	56–23–5	Methane, tetrachloro-
U213	109–99–9	Furan, tetrahydro-(I)
U213	109–99–9	Tetrahydrofuran (I)
U214	563–68–8	Acetic acid, thallium(1+) salt
U214	563–68–8	Thallium(I) acetate
U215	6533–73–9	Carbonic acid, dithallium(1+) salt
U215	6533–73–9	Thallium(I) carbonate
U216	7791–12–0	Thallium(I) chloride
U216	7791–12–0	Thallium chloride TlCl
U217	10102–45–1	Nitric acid, thallium(1+) salt
U217	10102–45–1	Thallium(I) nitrate
U218	62–55–5	Ethanethioamide
U218	62–55–5	Thioacetamide
U219	62–56–6	Thiourea
U220	108–88–3	Benzene, methyl-
U220	108–88–3	Toluene
U221	25376–45–8	Benzenediamine, ar-methyl-
U221	25376–45–8	Toluenediamine
U222	636–21–5	Benzenamine, 2-methyl-, hydrochloride
U222	636–21–5	o-Toluidine hydrochloride
U223	26471–62–5	Benzene, 1,3-diisocyanatomethyl- (R,T)
U223	26471–62–5	Toluene diisocyanate (R,T)
U225	75–25–2	Bromoform
U225	75–25–2	Methane, tribromo-
U226	71–55–6	Ethane, 1,1,1-trichloro-
U226	71–55–6	Methyl chloroform
U226	71–55–6	1,1,1-Trichloroethane
U227	79–00–5	Ethane, 1,1,2-trichloro-
U227	79–00–5	1,1,2-Trichloroethane
U228	79–01–6	Ethene, trichloro-
U228	79–01–6	Trichloroethylene
U234	99–35–4	Benzene, 1,3,5-trinitro-
U234	99–35–4	1,3,5-Trinitrobenzene (R,T)
U235	126–72–7	1-Propanol, 2,3-dibromo-, phosphate (3:1)
U235	126–72–7	Tris(2,3-dibromopropyl) phosphate
U236	72–57–1	2,7-Naphthalenedisulfonic acid, 3,3′-[(3,3′-dimethyl[1,1′-biphenyl]-4,4′-diyl)bis(azo)bis[5-amino-4-hydroxy]-, tetrasodium salt
U236	72–57–1	Trypan blue
U237	66–75–1	2,4-(1H,3H)-Pyrimidinedione, 5-[bis(2-chloroethyl)amino]-
U237	66–75–1	Uracil mustard
U238	51–79–6	Carbamic acid, ethyl ester
U238	51–79–6	Ethyl carbamate (urethane)
U239	1330–20–7	Benzene, dimethyl- (I,T)

NUMERICAL LIST—Continued

Hazardous Waste No.	Chemical abstracts No.	Substance
U239	1330–20–7	Xylene (I)
U240	[1] 94–75–7	Acetic acid, (2,4-dichlorophenoxy)-, salts & esters
U240	[1] 94–75–7	2,4-D, salts & esters
U243	1888–71–7	Hexachloropropene
U243	1888–71–7	1-Propene, 1,1,2,3,3,3-hexachloro-
U244	137–26–8	Thioperoxydicarbonic diamide $[(H_2N)C(S)]_2 S_2$, tetramethyl-
U244	137–26–8	Thiram
U246	506–68–3	Cyanogen bromide (CN)Br
U247	72–43–5	Benzene, 1,1′-(2,2,2-trichloroethylidene)bis[4- methoxy-
U247	72–43–5	Methoxychlor
U248	[1] 81–81–2	2H-1-Benzopyran-2-one, 4-hydroxy-3-(3-oxo-1-phenyl-butyl)-, & salts, when present at concentrations of 0.3% or less
U248	[1] 81–81–2	Warfarin, & salts, when present at concentrations of 0.3% or less
U249	1314–84–7	Zinc phosphide $Zn_3 P_2$, when present at concentrations of 10% or less
U271	17804–35–2	Benomyl
U271	17804–35–2	Carbamic acid, [1-[(butylamino)carbonyl]-1H-benzimidazol-2-yl]-, methyl ester
U278	22781–23–3	Bendiocarb
U278	22781–23–3	1,3-Benzodioxol-4-ol, 2,2-dimethyl-, methyl carbamate
U279	63–25–2	Carbaryl
U279	63–25–2	1-Naphthalenol, methylcarbamate
U280	101–27–9	Barban
U280	101–27–9	Carbamic acid, (3-chlorophenyl)-, 4-chloro-2-butynyl ester
U328	95–53–4	Benzenamine, 2-methyl-
U328	95–53–4	o-Toluidine
U353	106–49–0	Benzenamine, 4-methyl-
U353	106–49–0	p-Toluidine
U359	110–80–5	Ethanol, 2-ethoxy-
U359	110–80–5	Ethylene glycol monoethyl ether
U364	22961–82–6	Bendiocarb phenol
U364	22961–82–6	1,3-Benzodioxol-4-ol, 2,2-dimethyl-,
U367	1563–38–8	7-Benzofuranol, 2,3-dihydro-2,2-dimethyl-
U367	1563–38–8	Carbofuran phenol
U372	10605–21–7	Carbamic acid, 1H-benzimidazol-2-yl, methyl ester
U372	10605–21–7	Carbendazim
U373	122–42–9	Carbamic acid, phenyl-, 1-methylethyl ester
U373	122–42–9	Propham
U387	52888–80–9	Carbamothioic acid, dipropyl-, S-(phenylmethyl) ester
U387	52888–80–9	Prosulfocarb
U389	2303–17–5	Carbamothioic acid, bis(1-methylethyl)-, S-(2,3,3-trichloro-2-propenyl) ester
U389	2303–17–5	Triallate
U394	30558–43–1	A2213
U394	30558–43–1	Ethanimidothioic acid, 2-(dimethylamino)-N-hydroxy-2-oxo-, methyl ester
U395	5952–26–1	Diethylene glycol, dicarbamate
U395	5952–26–1	Ethanol, 2,2′-oxybis-, dicarbamate
U404	121–44–8	Ethanamine, N,N-diethyl-
U404	121–44–8	Triethylamine
U409	23564–05–8	Carbamic acid, [1,2-phenylenebis (iminocarbonothioyl)]bis-, dimethyl ester
U409	23564–05–8	Thiophanate-methyl
U410	59669–26–0	Ethanimidothioic acid, N,N′-[thiobis[(methylimino)carbonyloxy]]bis-, dimethyl ester
U410	59669–26–0	Thiodicarb
U411	114–26–1	Phenol, 2-(1-methylethoxy)-, methylcarbamate
U411	114–26–1	Propoxur
See F027	93–76–5	Acetic acid, (2,4,5-trichlorophenoxy)-
See F027	87–86–5	Pentachlorophenol
See F027	87–86–5	Phenol, pentachloro-
See F027	58–90–2	Phenol, 2,3,4,6-tetrachloro-
See F027	95–95–4	Phenol, 2,4,5-trichloro-
See F027	88–06–2	Phenol, 2,4,6-trichloro-
See F027	93–72–1	Propanoic acid, 2-(2,4,5-trichlorophenoxy)-
See F027	93–72–1	Silvex (2,4,5-TP)
See F027	93–76–5	2,4,5-T
See F027	58–90–2	2,3,4,6-Tetrachlorophenol
See F027	95–95–4	2,4,5-Trichlorophenol
See F027	88–06–2	2,4,6-Trichlorophenol

[1] CAS Number given for parent compound only.

§ 261.38 [Amended]

■ 16–21. Amend § 261.38 as follows:

■ a. In Table 1 to § 261.38, revise the column one subheading "Halogenated Organic:" to read "Halogenated Organics:"; and under "Halogenated

Organics:", insert a closing bracket "]" after the chemical name "Dichloromethoxy ethane [Bis(2-chloroethoxy)methane".

■ b. Amend the certification statement in paragraph (c)(1)(i)(C)(*4*) by revising the citation "40 CFR 261.28(c)(10)" to read "40 CFR 261.38(c)(10)".

Appendix VII to Part 261—[Amended]

■ 22–23. In Part 261 Appendix VII, amend the entries for "F002", "F038", "F039", "K001", and "K073" as follows:

■ a. In the second column of the "F002" row, revise "trichfluoroethane" to read "trifluoroethane";

■ b. In the second column of the "F038" row, add a comma between "benzo(a)pyrene" and "chrysene" to read "benzo(a)pyrene, chrysene";

■ c. In the second column of the "F039" row, revise the citation "40 CFR 268.43(a)" to read "40 CFR 268.43";

■ d. In the second column of the "K001" row, revise "cresosote" to read "creosote";

■ e. In the second column of the "K073" row, revise "hexacholroethane" to read "hexachloroethane".

Appendix VIII to Part 261—[Amended]

■ 24. Amend Part 261 Appendix VIII by amending the entries for "Allyl chloride", "Benzidine", § 1,2-Dichloroethylene", "Lasiocarpine", and "Nitrosamines, N.O.S." to read as follows:

■ a. In the third column of the "Allyl chloride" row, revise "107–18–6" to read "107–05–1";

■ b. In the second column of the "Benzidine" row, amend "-4,4^1-" by changing the superscript "1" to the symbol "'" to read, "-4,4'-";

■ c. In the second column of the "1,2-Dichloroethylene" row, revise "-dichlrol-" to read "-dichloro-";

■ d. In the third and fourth columns of the "Lasiocarpine" row, revise "303–34–1" to read "303–34–4"; and revise "4143" to read "U143";

■ e. In the third column of the "Nitrosamines, N.O.S." row, revise "35576–91–1D" to read "35576–91–1".

PART 262—STANDARDS APPLICABLE TO GENERATORS OF HAZARDOUS WASTE

■ 25. The authority citation for part 262 continues to read as follows:

Authority: 42 U.S.C. 6906, 6912, 6922–6925, 6937, and 6938.

§ 262.34 [Amended]

■ 26. Amend § 262.34(a)(1)(iv) by removing the beginning phrase "The waste is placed in containment buildings" and adding in its place the phrase "In containment buildings".

■ 27. Section 262.53 is amended by revising paragraph (b) to read as follows:

§ 262.53 Notification of Intent to Export.

* * * * *

(b) Notifications submitted by mail should be sent to the following mailing address: Office of Enforcement and Compliance Assurance, Office of Federal Activities, International Compliance Assurance Division (2254A), Environmental Protection Agency, 1200 Pennsylvania Ave., NW., Washington, DC 20460. Hand-delivered notifications should be sent to: Office of Enforcement and Compliance Assurance, Office of Federal Activities, International Compliance Assurance Division, Environmental Protection Agency, Ariel Rios Bldg., Room 6144, 12th St. and Pennsylvania Ave., NW., Washington, DC 20004. In both cases, the following shall be prominently displayed on the front of the envelope: "Attention: Notification of Intent to Export.".

* * * * *

■ 28. Section 262.56 is amended by revising paragraph (b) to read as follows:

§ 262.56 Annual Reports.

* * * * *

(b) Annual reports submitted by mail should be sent to the following mailing address: Office of Enforcement and Compliance Assurance, Office of Federal Activities, International Compliance Assurance Division (2254A), Environmental Protection Agency, 1200 Pennsylvania Ave., NW., Washington, DC 20460. Hand-delivered reports should be sent to: Office of Enforcement and Compliance Assurance, Office of Federal Activities, International Compliance Assurance Division, Environmental Protection Agency, Ariel Rios Bldg., Room 6144, 12th St. and Pennsylvania Ave., NW., Washington, DC 20004.

■ 29. Section 262.58 is amended by revising paragraph (a)(1) to read as follows:

§ 262.58 International Agreements.

(a) * * *

(1) For the purposes of subpart H, the designated OECD Member countries consist of Australia, Austria, Belgium, the Czech Republic, Denmark, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Japan, Luxembourg, the Netherlands, New Zealand, Norway, Poland, Portugal, the Slovak Republic, South Korea, Spain, Sweden, Switzerland, Turkey, the United Kingdom, and the United States.

* * * * *

§ 262.70 [Amended]

■ 30. Amend § 262.70 by revising the word "consisent" to read "consistent".

§ 262.81 [Amended]

■ 31. In § 262.81, amend paragraph (k) by revising "RCRA Information Center (RIC), 1235 Jefferson-Davis Highway, first floor, Arlington, VA 22203" to read "RCRA Docket, EPA/DC, EPA West, Room B102, 1301 Constitution Ave., NW., Washington, DC 20460".

§ 262.82 [Amended]

■ 32. In § 262.82, amend paragraph (a)(1)(ii) by revising the phrase "Green-list waste" to read "Green-list wastes".

■ 33. Amend § 262.83 as follows:

■ a. Amend paragraph (b)(1)(i) by revising "Office of Compliance, Enforcement Planning, Targeting and Data Division (2222A)" to read "Office of Federal Activities, International Compliance Assurance Division (2254A)".

■ b. Revise paragraph (b)(2)(i) to read as follows:

§ 262.83 Notification and consent.

* * * * *

(b) * * *

(2) * * *

(i) The notifier must provide EPA the information identified in paragraph (e) of this section in English, at least 10 days in advance of commencing shipment to a pre-approved facility. The notification should indicate that the recovery facility is pre-approved, and may apply to a single specific shipment or to multiple shipments as described in paragraph (b)(1)(i) of this section. This information must be sent to the Office of Enforcement and Compliance Assurance, Office of Federal Activities, International Compliance Assurance Division (2254A), Environmental Protection Agency, 1200 Pennsylvania Ave., NW., Washington, DC 20460, with the words "Attention: OECD Export Notification—Pre-approved Facility" prominently displayed on the envelope.

* * * * *

■ 34–35. Section 262.84 is amended by revising paragraph (e) to read as follows:

§ 262.84 Tracking document.

* * * * *

(e) Within three working days of the receipt of imports subject to this Subpart, the owner or operator of the U.S. recovery facility must send signed copies of the tracking document to the notifier, to the Office of Enforcement and Compliance Assurance, Office of Federal Activities, International Compliance Assurance Division (2254A), Environmental Protection

Agency, 1200 Pennsylvania Ave., NW., Washington, DC 20460, and to the competent authorities of the exporting and transit countries.

§ 262.87 [Amended]

■ 36. Amend § 262.87 as follows:
■ a. In paragraph (a) revise "Office of Compliance, Enforcement Planning, Targeting and Data Division (2222A)", to read, "Office of Federal Activities, International Compliance Assurance Division (2254A)";
■ b. Amend paragraph (a)(5) introductory text by inserting a space in "100kg" and "1000kg" to read "100 kg" and "1000 kg".

§ 262.90 [Amended]

■ 37.–38. Amend § 262.90 in paragraph (c)(2)(vii) by revising "newpaper" to read "newspaper"; and in paragraph (d)(2) by revising "directed.This" by adding a space after the period to read "directed. This".

PART 264—STANDARDS FOR OWNERS AND OPERATORS OF HAZARDOUS WASTE TREATMENT, STORAGE, AND DISPOSAL FACILITIES

■ 39.–40. The authority citation for Part 264 continues to read as follows:

Authority: 42 U.S.C. 6905, 6912(a), 6924 and 6925.

§ 264.1 [Amended]

■ 41. In § 264.1, amend paragraph (g)(2) by revising "subparts C, D, F, or G" to read "subparts C, F, G, or H".

§ 264.4 [Amended]

■ 42. Amend § 264.4 by revising "purusant" to read "pursuant".

§ 264.13 [Amended]

■ 43. In § 264.13, amend paragraph (b)(7)(iii)(B) by revising the semicolon at the end of the subsection into a colon.

§ 264.17 [Amended]

■ 44. In § 264.17, amend paragraph (b) introductory text by revising the word "reactons" to read "reactions".

§ 264.18 [Amended]

■ 45. In § 264.18, amend paragraph (a)(2)(iii) by revising "Quarternary" to read "Quaternary"; and amend paragraph (b)(2)(iii) by revising "exeeded" to read "exceeded".

§ 264.97 [Amended]

■ 46. Amend § 264.97 as follows:
■ a. In paragraph (a)(1) introductory text, revise "background water" to read "background ground water";
■ b. In paragraph (a)(1)(i), revise "background quality" to read "background ground-water quality";
■ c. In paragraph (i)(5), revise "tha can be" to read "that can be".

§ 264.98 [Amended]

■ 47. Amend § 264.98 as follows:
■ a. In paragraph (a)(2), revise "persistance" to read "persistence";
■ b. In paragraph (g)(4)(i), revise "concentration or any" to read "concentration of any".

§ 264.99 [Amended]

■ 48. In § 264.99, amend paragraph (h)(2) introductory text, by revising the citation "§ 264.98(h)(5)" to read "§ 264.98(g)(5)".

§ 264.101 [Amended]

■ 49. In § 264.101, amend paragraph (d) by revising the phrase "This does not apply" to read "This section does not apply".

§ 264.111 [Amended]

■ 50. In § 264.111, amend paragraph (c) by revising the word "subpart" to read "part".

§ 264.112 [Amended]

■ 51. In § 264.112, amend paragraph (b)(8) by revising the citation "264.110(d)" to read "264.110(c)".

§ 264.115 [Amended]

■ 52. Amend § 264.115 by eliminating the second period at the end of the first sentence.

§ 264.116 [Amended]

■ 53. Amend § 264.116 by revising "landfills cells" to read "landfill cells".

§ 264.118 [Amended]

■ 54. In § 264.118, amend paragraph (c) by revising the citation "§ 264.188(b)(3)" to read "§ 264.118(b)(3)".

§ 264.119 [Amended]

■ 55. In § 264.119, amend paragraph (b)(1)(ii) by revising the citation "40 CFR subpart G" to read "40 CFR part 264, subpart G".

§ 264.140 [Amended]

■ 56. In § 264.140, amend paragraph (d)(1) by revising the citation "§ 264.110(d)" to read "§ 264.110(c)".

§ 264.142 [Amended]

■ 57. In § 264.142, amend paragraph (b)(2) by revising "mutliplying" to read "multiplying".

§ 264.143 [Amended]

■ 58. Amend § 264.143 as follows:
■ a. In paragraph (b)(7), revise "then the penal sum" to read "than the penal sum";
■ b. In paragraph (b)(8), revise "as evidence by" to read "as evidenced by";
■ c. In paragraph (e)(5), revise "signficantly" to read "significantly".

§ 264.145 [Amended]

■ 59. Amend § 264.145 as follows:
■ a. In paragraph (a)(3)(i), revise "anniversay" to read "anniversary";
■ b. In paragraph (d)(6), revise "issued in a amount" to read "issued in an amount";
■ c. In paragraph (f)(11) introductory text, revise "for this section" to read "of this section"; and revise "the direct of higher-tier" to read "the direct or higher-tier".

§ 264.147 [Amended]

■ 60. In § 264.147, amend paragraph (h)(1) by revising "letter or credit" to read "letter of credit".

§ 264.151 [Amended]

■ 61. Amend § 264.151 as follows:
■ a. In paragraph (b), in the section "Corporate Surety(ies)," remove the bracket (]) after "State of incorporation";
■ b. In paragraph (f) introductory paragraph, revise the second occurrence of the citation "265.143(e)" to read "265.145(e)";
■ c. In paragraph (g), in the fifth paragraph of the LETTER FROM CHIEF FINANCIAL OFFICER, revise ""nonsudden" of" to read ""nonsudden" or";
■ d. In paragraph (g), in Item 3. of the LETTER FROM CHIEF FINANCIAL OFFICER, revise "subpart H or 40 CFR" to read "subpart H of 40 CFR";
■ e. In paragraph (g), in Part A, ALTERNATIVE I item *3., revise "Current $" to read "Current liabilities $";
■ f. In paragraph (g), in Part B, ALTERNATIVE I item 10., insert an asterisk (*) before "10.";
■ g. In paragraph (g), in Part B, ALTERNATIVE I item 15., remove the comma after the word "If";
■ h. In paragraph (g), in Part B, ALTERNATIVE II item *7., remove the underline before the "$";
■ i.–j. In paragraph (h)(2), under the section GUARANTEE FOR LIABILITY COVERAGE, in the second sentence, revise "or which guarantor" to read "of which guarantor"; and revise the phrase "[either 264.141(h)]" to read "[either 264.141(h) or 265.141(h)]";
■ k. In paragraph (h)(2), under the section RECITALS, item 13.(a), under the subsection CERTIFICATION OF VALID CLAIM, insert a closing bracket (]) after "[Principal's";

■ l. In paragraph (h)(2), under the section RECITALS, item 14, last line, revise "Signature of witness of notary" to read "Signature of witness or notary";
■ m. In paragraph (i), following item 2.(e), after "[Title]" revise "Authorized Representive" to read "Authorized Representative";
■ n. In paragraph (j), item 2.(d), revise "corportation" to read "corporation";
■ o. In paragraph (k), in the section IRREVOCABLE STANDBY LETTER OF CREDIT, delete the opening quotation mark before "(1)" before the subsection CERTIFICATE OF VALID CLAIM, and insert a closing bracket (]) at the end of the phrase after (2) to read "Grantor's facility or group of facilities.]";
■ p. In paragraph (k), in the section CERTIFICATE OF VALID CLAIM, in the paragraph following (2), revise "[date] at least one year later]" to read "[date at least one year later]";
■ q. In paragraph (l), revise the citations "§ 264.147(h) or § 265.147(h)" to read "§ 264.147(i) or § 265.147(i)";
■ r. In paragraph (l), in the subsection CERTIFICATION OF VALID CLAIM, in the introductory paragraph, revise "accidential" to read "accidental";
■ s. In paragraph (m)(1), in the CERTIFICATION OF VALID CLAIM Section 8.(c), revise both instances of "depositary" to read "depository";
■ t.–u. In paragraph (n)(1), under STANDBY TRUST AGREEMENT, in Section 3.(c)(1), revise "employee or" to read "employee of";
■ v. In paragraph (n)(1), Section 3.(e)(3), insert the word "by" after "Property loaned" to read "Property loaned by";
■ w. In paragraph (n)(1), Section 12., third sentence, replace the semicolon after "the appointment" with a comma;
■ x. In paragraph (n)(1), Section 16., second sentence, revise "reasonable" to read "reasonably".

§ 264.175 [Amended]

■ 62. In § 264.175, amend paragraph (b)(1) by revising "underly" to read "underlie".

§ 264.193 [Amended]

■ 63. Amend § 264.193 as follows:
■ a. In the third sentence of the NOTE following paragraph (c)(4), revise "subject" to read "subject";
■ b. In paragraph (d)(4), insert a period at the end of the sentence;
■ c. In paragraph (e)(2)(ii), replace the colon with a semicolon;
■ d. In paragraph (e)(2)(iii), replace the colon with a semicolon;
■ e. In paragraph (e)(2)(v)(A), revise the citation "§ 262.21" to read "§ 261.21";
■ f. In paragraph (e)(2)(v)(B), revise the citation "§ 262.21" to read "§ 261.23", and replace the period after the word "vapor" with a semicolon and add the word "and";
■ g. In paragraph (e)(3)(i), replace the period at the end with a semicolon;
■ h. In paragraph (e)(3)(ii), replace the colon with a semicolon;
■ i. In paragraph (g)(1)(iii), replace the comma after the word "water" with a semi-colon;
■ j. In paragraph (g)(1)(iv), insert a period at the end of the paragraph;
■ k. In paragraph (g)(2)(i)(A), replace the period with a comma.

§ 264.221 [Amended]

■ 64. Amend § 264.221 as follows:
■ a. In paragraph (c)(1)(i)(B), revise "1x10/$^{-7}$/ cm/sec" to read "1x10^{-7} cm/sec";
■ b. In paragraph (c)(2)(ii), revise "1x10/$^{-1}$/ cm/sec" to read "1x10^{-1} cm/sec" and revise "3x10/$^{-4}$/ m^2sec" to read "3x10^{-4} m^2/sec";
■ c. In paragraph (e)(1), revise "EP toxicity characteristics in" to read "toxicity characteristic in";
■ d. In paragraph (e)(2)(i)(B), revise the citation "§ 144.3 of this chapter" to read "40 CFR 270.2"; and add quotation marks around "underground source of drinking water".
■ e. In paragraph (e)(2)(i)(C), revise "requrements" to read "requirements".

§ 264.223 [Amended]

■ 65. In § 264.223, amend paragraph (b)(1) by revising "exceedence" to read "exceedance".

§ 264.226 [Amended]

■ 66. In § 264.226, amend paragraph (a)(2) by revising "inperfections" to read "imperfections".

§ 264.251 [Amended]

■ 67. In § 264.251, amend paragraph (a)(2)(i)(A) by revising "resistent" to read "resistant".

§ 264.252 [Amended]

■ 68. Amend § 264.252 as follows:
■ a. In paragraph (a), revise "surface impoundment units" to read "waste pile units";
■ b. In paragraph (b), remove the comma after the citation "§ 264.254(c)".

§ 264.259 [Amended]

■ 69. In § 264.259, amend paragraph (b) by removing the comma between the word "and" and "F027".

§ 264.280 [Amended]

■ 70. Amend § 264.280 as follows:
■ a. In paragraph (c)(7), revise "expect that" to read "except that";
■ b. In paragraph (d), introductory text, revise "closure of post-closure" to read "closure or post-closure".

§ 264.283 [Amended]

■ 71. In § 264.283, amend paragraph (a) by removing the comma between the word "and" and "F027".

§ 264.301 [Amended]

■ 72. Amend § 264.301 as follows:
■ a. In paragraph (c)(2), revise "paragraphs (3)(c)(iii) and (iv)" to read "paragraphs (c)(3)(iii) and (iv)";
■ b. In paragraph (e)(2)(i)(B), revise the citation "§ 144.3 of this chapter" to read "40 CFR 270.2"; and add quotation marks around "underground source of drinking water".

§ 264.302 [Amended]

■ 73. Amend § 264.302 as follows:
■ a. In paragraph (a), revise "surface impoundment units" to read "landfill units";
■ b. In paragraph (b), remove the comma after the citation "§ 264.303(c)".

§ 264.304 [Amended]

■ 74. In § 264.304, amend paragraph (b)(1) by revising "exceedence" to read "exceedance".

§ 264.314 [Amended]

■ 75. In § 264.314, amend paragraph (e)(2) by revising the citation "§ 144.3 of this chapter" to read "40 CFR 270.2"; and by adding quotation marks around "underground source of drinking water".

§ 264.317 [Amended]

■ 76. In § 264.317, amend paragraph (a) introductory text by revising "in a landfills" to read "in a landfill".

§ 264.344 [Amended]

■ 77. In § 264.344, amend paragraph (b) by revising "new wastes may be be based" to read "new wastes may be based".

§ 264.552 [Amended]

■ 78. Amend § 264.552 as follows:
■ a. In paragraph (e)(4)(iii), replace the colon at the end of the paragraph with a period;
■ b. In paragraph (e)(4)(iv)(F), revise the citation "40 CFR 260.11(11)" to read "40 CFR 260.11(a)(11)";
■ c. In paragraph (e)(6)(iii)(E), revise "Hydrological" to read "Hydrogeological".

§ 264.553 [Amended]

■ 79. In § 264.553, amend paragraph (e) introductory text by revising "the Administrator" to read "the Regional Administrator".

§ 264.554 [Amended]

■ 80. In § 264.554, amend paragraph (a) introductory text by revising "Director

in according" to read "Director according".

§ 264.555 [Amended]

■ 81. In § 264.555, amend paragraph (e)(6) by revising the word "miminal" to read "minimal".

§ 264.573 [Amended]

■ 82. Amend § 264.573 as follows:
■ a. In paragraph (a)(1), revise "non-earthern" to read "non-earthen"; and replace the colon at the end of the paragraph with a semicolon;
■ b. In paragraph (a)(4)(i), revise both occurrences of "1x10^{-7}" to read "1x10^{-7}"; and revise the citations "§ 264.572(a) instead of § 264.572(b)" to read "§ 264.572(b) instead of § 264.572(a)";
■ c. In paragraph (a)(5), revise "perations" to read "operations";
■ d. In paragraph (b) introductory text, revise the citations "§ 264.572(b) instead of § 264.572(a)" to read "§ 264.572(a) instead of § 264. 572(b)";
■ e. In paragraph (m)(2) and in paragraph (m)(3) twice, revise "clean up" to read "cleanup".

§ 264.600 [Amended]

■ 83. Amend § 264.600 by revising "miscellanenous" to read "miscellaneous"; and by revising "provide" to read "provides".

§ 264.601 [Amended]

■ 84. Amend § 264.601 as follows:
■ a. In paragraph (a) introductory text, revise "heath" to read "health";
■ b. In paragraph (b)(11), revise "constitutents" to read "constituents";
■ c. In paragraph (c)(4), revise "metorologic" to read "meteorologic".

§ 264.1030 [Amended]

■ 85. Amend § 264.1030(c) by revising "owner and operator receives" to read "owner and operator receive"; and revise "owner and operator is subject" to read "owner and operator are subject".

§ 264.1033 [Amended]

■ 86. In § 264.1033, amend paragraph (f)(2)(vii)(B) by replacing the period after the word "regular" with a comma.

§ 264.1034 [Amended]

■ 87. In § 264.1034, amend paragraph (b)(2) by removing the "(6)" in front of the phrase "The detection".

§ 264.1035 [Amended]

■ 88. Amend § 264.1035 as follows:
■ a. In paragraph (c)(4)(i), replace the period after the first instance of "760 °C" with a comma;
■ b. In paragraph (c)(4)(ii), insert a comma after the word "greater".

§ 264.1050 [Amended]

■ 89. In § 264.1050, amend paragraph (f) by revising the citation "§ 264,1064(g)(6)" to read "§ 264.1064(g)(6)".

§ 264.1058 [Amended]

■ 90. In § 264.1058, amend paragraph (c)(1) by replacing the period after the second occurrence of the word "detected" with a comma.

§ 264.1064 [Amended]

■ 91. In § 264.1064, amend paragraph (c)(3) by removing the second section symbol (§) in the citation "§§ 264.1057(c)".

§ 264.1080 [Amended]

■ 92. Amend § 264.1080 as follows:
■ a. In paragraph (a), revise "subparts I, J, or K" to read "subpart "I, J, or K";
■ b. In paragraph (c), last sentence, revise "owner and operator is subject" to read "owner and operator are subject".

§ 264.1090 [Amended]

■ 93. In § 264.1090, amend paragraph (c) by removing the third sentence.

§ 264.1101 [Amended]

■ 94. Amend § 264.1101 as follows:
■ a. In paragraph (b)(3)(iii), revise the citation "§ 264.193(d)(1)" to read "§ 264.193(e)(1)";
■ b. In paragraph (c)(3) introductory text, revise "hazardous waste, must repair" to read "hazardous waste, the owner or operator must repair";
■ c. In paragraph (c)(3)(i), revise "lead" to read "led";
■ d. In paragraph (d) introductory text, revise "For containment buildings that contain areas both" to read "For a containment building that contains both areas".

§ 264.1102 [Amended]

■ 95. In § 264.1102, amend paragraph (a) by removing the comma after "etc.".

■ 96. Amend Appendix I to Part 264 as follows:
■ a. In Table 1, add unit of measure codes for "Pounds", "Short tons", "Kilograms", and "Tons" at the end of the table to read as set forth below; and
■ b. In Table 2 at Section 2.(d), revise the line "T75 Tricking filter" to read "T75 Trickling filter".

Appendix I to Part 264—Recordkeeping Instructions.

TABLE 1

Unit of measure	Code[1]

TABLE 1—Continued

Unit of measure	Code[1]
* * * * *	
Pounds	P
Short tons	T
Kilograms	K
Tons	M

[1] Single digit symbols are used here for data processing purposes.

* * * * *

PART 265—INTERIM STATUS STANDARDS FOR OWNERS AND OPERATORS OF HAZARDOUS WASTE TREATMENT, STORAGE, AND DISPOSAL FACILITIES

■ 97. The authority citation for part 265 is revised to read as follows:

Authority: 42 U.S.C. 6905, 6906, 6912, 6922, 6923, 6924, 6925, 6935, 6936, and 6937.

§ 265.1 [Amended]

■ 98. Amend § 265.1 as follows:
■ a. In paragraph (c)(4)(i) remove the phrase, "As stated in paragraph (c)(2) of this section,";
■ b. In paragraph (c)(6), revise "subparts C, D, F, or G" to read "subparts C, F, G, or H".

§ 265.12 [Amended]

■ 99. In § 265.12, amend paragraph (a)(1) by revising "of the date of the waste" to read "of the date the waste".

§ 265.14 [Amended]

■ 100. In § 265.14, amend paragraph (b)(1) by revising "guards of facility personnel" to read "guards or facility personnel".

§ 265.16 [Amended]

■ 101. In § 265.16, amend paragraph (b) by revising "successfuly" to read "successfully".

§ 265.19 [Amended]

■ 102. In § 265.19, amend paragraph (c)(2) last sentence, by revising "264.254(c)(1)" to read "264.251(c)(1)".

§ 265.56 [Amended]

■ 103. In § 265.56, amend paragraph (b) by revising "a real" to read "areal" (one word).

§ 265.90 [Amended]

■ 104. In § 265.90, amend paragraph (d) introductory text by removing the comma after the phrase "he may".

§ 265.110 [Amended]

■ 105. In § 265.110, amend paragraph (b)(4) by revising "building" to read "buildings".

§ 265.111 [Amended]

■ 106. In § 265.111, amend paragraph (c) by revising the citation "264.1102" to read "265.1102".

§ 265.112 [Amended]

■ 107. Amend § 265.112 as follows:
■ a. In paragraph (b)(5), revise "partial and final closure period" to read "partial and final closure periods";
■ b. In paragraph (d)(4), in the next to last sentence, revise the citation "§§ with 265.111" to read "§§ 265.111"; revise "part, §§ 265.197" to read "part, and §§ 265.197"; and revise the citation "264.1102" to read "265.1102".

§ 265.113 [Amended]

■ 108. Amend § 265.113 as follows:
■ a. In paragraph (b) introductory text, revise "extenstion" to read "extension";
■ b. In paragraph (e)(4), revise "oonstituents" to read "constituents".

§ 265.117 [Amended]

■ 109. In § 265.117, amend paragraph (b) introductory text by revising "Administator" to read "Administrator".

§ 265.119 [Amended]

■ 110. In § 265.119, amend paragraph (b)(1)(ii) by revising the citation "40 CFR subpart G" to read "40 CFR part 265, subpart G".

§ 265.140 [Amended]

■ 111. Amend § 265.140 as follows:
■ a. In paragraph (b) introductory text, revise the citation "265.146" to read "265.145";
■ b. In paragraph (b)(2), revise the citation "§ 264.197" to read "§ 265.197".

§ 265.142 [Amended]

■ 112. In § 265.142, amend paragraph (a) by removing "265.178" from the list of sections.

§ 265.145 [Amended]

■ 113. Amend § 265.145 as follows:
■ a. In paragraph (e)(11), first sentence, revise "for this section" to read "of this section";
■ b. In paragraph (e)(11), second sentence, revise "direct of higher-tier" to read "direct or higher-tier";
■ c. In paragraph (e)(11), third sentence, revise the citation "(f)(1) through (9)" to read "(e)(1) through (9)";
■ d. In paragraph (e)(11), fifth sentence, revise the citation "(f)(3)" to read "(e)(3)".

§ 265.147 [Amended]

■ 114. Amend § 265.147 as follows:
■ a. Amend paragraph (a)(1)(i) in the next to last sentence by revising "or Regional Administrator if facilities" to read "or Regional Administrators if the facilities".
■ b. Amend paragraph (b)(1) by adding paragraphs (i) and (ii) to read as follows:

§ 265.147 Liability requirements.

* * * * *

(b) * * *

(1) * * *

(i) Each insurance policy must be amended by attachment of the Hazardous Waste Facility Liability Endorsement or evidenced by a Certificate of Liability Insurance. The wording of the endorsement must be identical to the wording specified in § 264.151(i). The wording of the certificate of insurance must be identical to the wording specified in § 264.151(j). The owner or operator must submit a signed duplicate original of the endorsement or the certificate of insurance to the Regional Administrator, or Regional Administrators if the facilities are located in more than one Region. If requested by a Regional Administrator, the owner or operator must provide a signed duplicate original of the insurance policy.

(ii) Each insurance policy must be issued by an insurer which, at a minimum, is licensed to transact the business of insurance, or eligible to provide insurance as an excess or surplus lines insurer, in one or more States.

* * * * *

§ 265.174 [Amended]

■ 115.–116. Amend § 265.174, by deleting the phrase "and the containment system".

§ 265.193 [Amended]

■ 117. Amend § 265.193 as follows:
■ a. In paragraph (e)(2)(v)(A), revise the citation "§ 262.21" to read "§ 261.21";
■ b. In paragraph (e)(2)(v)(B), revise the citation "§ 262.21" to read "§ 261.23";
■ c. In paragraph (i)(2), in the last sentence, revise "tanks surfaces" to read "tank surfaces".

§ 265.194 [Amended]

■ 118. In § 265.194, amend paragraphs (b)(1) and (b)(2) by inserting a period after "e.g" in both paragraphs, and in paragraph (b)(1), by revising "discount" to read "disconnect".

§ 265.197 [Amended]

■ 119. In § 265.197, amend paragraph (b) by inserting a period after the closing parenthesis of the citation "(265.310)".

§ 265.201 [Amended]

■ 120. In § 265.201, amend paragraph (c) introductory text, by revising "hazardous in tanks" to read "hazardous waste in tanks".

§ 265.221 [Amended]

■ 121. Amend § 265.221 as follows:
■ a. In paragraph (a), revise "leachate collection and removal system above and between the liners" to read "leachate collection and removal system between the liners";
■ b. In paragraph (d)(2)(i)(A), revise "in leaking?" to read "is leaking"; revise "soil it is not" to read "soil is not"; and revise "the owner of operator" to read "the owner or operator";
■ c. In paragraph (d)(2)(i)(B), revise the citation "§ 144.3 of this chapter" to read "40 CFR 270.2"; and add quotation marks around "underground source of drinking water".

§ 265.224 [Amended]

■ 122–123. In § 265.224, amend paragraph (b)(1) by revising "exceedence" to read "exceedance".

§ 265.228 [Amended]

■ 124. Amend § 265.228 as follows:
■ a. In paragraph (a)(2)(iii)(D), revise "Accomodate" to read "Accommodate";
■ b. In paragraph (b)(2), revise the citation "§§ 265.221(c)(2)(iv)" to read "§§ 264.221(c)(2)(iv)".

§ 265.229 [Amended]

■ 125. Amend § 265.229 by removing paragraph (b)(2) and redesignate paragraphs (b)(3) and (b)(4) as paragraphs (b)(2) and (b)(3), respectively.

§ 265.255 [Amended]

■ 126. Amend § 265.255 in paragraph (b) by revising "surface impoundment units" to read "waste pile units".

§ 265.259 [Amended]

■ 127. In § 265.259, amend paragraph (b)(1) by revising "exceedence" to read "exceedance".

§ 265.280 [Amended]

■ 128. In § 265.280, amend paragraph (a)(4) by revising "gowth" to read "growth".

§ 265.281 [Amended]

■ 129. In § 265.281, amend paragraph (a)(1) by revising the citation "§ 265.21" to read "§ 261.21".

§ 265.301 [Amended]

■ 130. Amend § 265.301 as follows:
■ a. In paragraph (a), revise "in accordance with § 264.301(d), (e), or (f)

of this chapter" to read "in accordance with § 264.301(c), unless exempted under § 264.301(d), (e), or (f) of this chapter";

■ b. In paragraph (d)(1), revise "such waste does not" to read "such wastes do not"; revise the citation "§ 261.4" to read "§ 261.24"; and revise "Hazardous Waste Number" to read "Hazardous Waste Numbers";

■ c. In paragraph (d)(2)(i)(B), revise the citation "§ 144.3 of this chapter" to read "40 CFR 270.2"; and add quotation marks around "underground source of drinking water".

§ 265.302 [Amended]

■ 131. In § 265.302, amend paragraph (b) by revising "surface impoundment units" to read "landfill units".

§ 265.303 [Amended]

■ 132. In § 265.303, amend paragraph (b)(1) by revising "exceedence" to read "exceedance".

§ 265.312 [Amended]

■ 133. In § 265.312, amend paragraph (a)(1) by revising "dissolution or material" to read "dissolution of material".

§ 265.314 [Amended]

■ 134. Amend § 265.314 as follows:

■ a. In paragraph (e)(1)(ii), revise "polysobutylene" to read "polyisobutylene";

■ b. In paragraph (f)(2), revise the citation "§ 144.3 of this chapter" to read "40 CFR 270.2"; and add quotation marks around "underground source of drinking water".

§ 265.316 [Amended]

■ 135. Amend § 265.316 as follows:

■ a. In the introductory text, revise "landfull" to read "landfill";

■ b. In paragraph (c), revise "container's" to read "containers";

■ c. In paragraph (d), revise "§ 260.10(a)" to read "§ 260.10".

§ 265.405 [Amended]

■ 136. In § 265.405, amend paragraph (a)(1) by revising the citation "§ 261.21 or 261.23 or this chapter" to read "§§ 261.21 or 261.23 of this chapter".

§ 265.441 [Amended]

■ 137. In § 265.441, amend paragraph (c) by revising "state Director" to read "State Director".

§ 265.443 [Amended]

■ 138. Amend § 265.443 as follows:

■ a. In paragraph (a)(4)(i), revise the citation "§ 265.442(a) instead of § 265.442(b)" to read "§ 265.442(b) instead of § 265.442(a)";

■ b. In paragraph (b) introductory text, revise the citation "§ 265.442(b) instead of § 265.442(a)" to read "§ 265.442(a) instead of § 265. 442(b)".

§ 265.445 [Amended]

■ 139. In § 265.445, amend paragraph (b) by revising "post/closure care" to read "post-closure care".

§ 265.1033 [Amended]

■ 140. In § 265.1033, amend paragraph (f)(2)(ii) by replacing the period with a comma after "±0.5 °C".

§ 265.1035 [Amended]

■ 141. Amend § 265.1035 as follows:

■ a. In paragraph (b)(2) introductory text, replace the period with a comma after the citation "§ 265.1032";

■ b. In paragraph (b)(2)(i), revise "annual throughput end operating hours" to read "annual throughput and operating hours";

■ c. In paragraph (c)(4)(i), replace the period with a comma after the first occurrence of "760 °C".

§ 265.1063 [Amended]

■ 142. In § 265.1063, amend paragraph (b)(4)(ii) by replacing the period in "10.000" with a comma.

§ 265.1080 [Amended]

■ 143. In § 265.1080, amend paragraph (a) by revising the citation "subparts I, J, or K" to read "subpart I, J, or K".

§ 265.1085 [Amended]

■ 144. In § 265.1085, amend paragraph (h)(3) introductory text, by revising "under either or the following" to read "under either of the following".

§ 265.1087 [Amended]

■ 145. In § 265.1087, amend paragraph (b) by designating the text following the paragraph heading "General requirements" as paragraph (b)(1).

§ 265.1090 [Amended]

■ 146. In § 265.1090, amend paragraph (f)(1) by revising the citation "§ 265.1084(c)(2)(i)" to read "§ 265.1083(c)(2)(i)".

§ 265.1100 [Amended]

■ 147. In § 265.1100, amend paragraph (d) by revising "permit" to read "prevent".

"265.1101 [Amended]

■ 148. Amend § 265.1101 as follows:

■ a. In paragraph (b)(3)(i)(B), revise "trasmissivity" to read "transmissivity";

■ b. In paragraph (b)(3)(iii), revise the citation "§ 265.193(d)(1)" to read "§ 265.193(e)(1)";

■ c. In paragraph (c)(3) introductory text, revise "hazardous waste, must repair" to read "hazardous waste, the owner or operator must repair";

■ d. In paragraph (d) introductory text, revise "For containment" to read "For a containment".

■ 149. Amend Appendix I to part 265 as follows:

■ a. In Table 1, add unit of measure codes for "Pounds," "Short tons," "Kilograms," and "Tons" at the end of the table to read as set forth below;

■ b. In Table 2, Section 2.(d), revise "T75 Tricking filter" to read "T75 Trickling filter";

■ c. In Table 2, Section 4., revise the heading "Miscellaneous (Subpart X)" to read "Miscellaneous";

■ d. In Table, 2, Section 4., revise "X99 Other Subpart X (specify)" to read "X99 Other (specify)".

Appendix I to Part 265—Recordkeeping Instructions

* * * * *

TABLE 1

Unit of measure	Code[1]
* * * * *	
Pounds	P
Short tons	T
Kilograms	K
Tons	M

[1] Single digit symbols are used here for data processing purposes.

* * * * *

Appendix V to Part 265—[Amended]

■ 150. In the table in Appendix V to Part 265, under the Group 1–A column, revise the phrase "Akaline caustic liquids" to read "Alkaline caustic liquids"; and revise "Lime sludge and other corrosive alkalines" to read "Lime sludge and other corrosive alkalies".

Appendix VI to Part 265—[Amended]

■ 151. Amend Appendix VI to part 265 as follows:

■ a. In the entry "Dichlorvos (DDVP)", revise the CAS No. "62737" to read "62–73–7";

■ b. In the entry "Ethylene thiourea (2-imidazolidinethione)" revise the CAS No. "9–64–" to read "96–45–7";

■ c. In the entry "Neopentyl glycol (dimethylolpropane)" revise "dimethylolpropane" to read "dimethylpropane";

■ d. In the entry "1,3-Propane sulfone", revise "sulfone" to read "sultone".

PART 266—STANDARDS FOR THE MANAGEMENT OF SPECIFIC HAZARDOUS WASTES AND SPECIFIC TYPES OF HAZARDOUS WASTE MANAGEMENT FACILITIES

■ 152. The authority citation for part 266 continues to read as follows:

Authority: 42 U.S.C. 1006, 2002(a), 3001–3009, 3014, 6905, 6906, 6912, 6921, 6922, 6924–6927, 6934, and 6937.

§ 266.70 [Amended]

■ 153. In § 266.70, amend paragraph (a) by revising "paladium, irridium" to read "palladium, iridium".

§ 266.80 [Amended]

■ 154. In § 266.80, amend the Table in paragraph (a) by inserting, in the third column, a comma after "(except for § 262.11)" in all four instances.

§ 266.100 [Amended]

■ 155. Amend § 266.100 as follows:
■ a. In paragraph (b)(2)(iv), revise "§ 266.212" to read § 266.112";
■ b. In paragraph (d)(3)(i)(A), revise "appendix IX" to read "appendix XI";
■ c. In paragraph (g) introductory text, revise "paladium, irridium" to read "palladium, iridium".

§ 266.102 [Amended]

■ 156. Amend § 266.102 as follows:
■ a. In paragraph (a)(2)(vi), revise "(Corrective Action)" to read "(Releases from Solid Waste Management Units)";
■ b. In paragraph (e)(3)(i)(E), revise the citation "§ 266.111(b)" to read "§ 266. 105(a)";
■ c. In paragraph (e)(5)(i)(C), revise "chorline" to read "chlorine"; and revise "feestocks" to read "feedstocks";
■ d. In paragraph (e)(6)(ii)(B)(2), revise "of preceding" to read "of the preceding";
■ e. In paragraph (e)(8)(iii), revise "values" to read "valves".

■ 157. Amend § 266.103 as follows:
■ a. In paragraph (a)(4)(vii), revise the citation "265.147–265.151" to read "265.147–265.150";
■ b. In paragraph (b)(2)(v)(B)(2), revise "meterological" to read "meteorological";
■ c. In paragraph (b)(5)(ii)(A), revise "on a hourly" to read "on an hourly";
■ d. In paragraph (b)(6)(viii)(A), revise "Ageny" to read "Agency";
■ e. In paragraph (c)(1)(ii)(A)(2), revise "feedsteams" to read "feedstreams";
■ f. In paragraph (c)(1)(ix)(A), revise "ration" to read "ratio";
■ g. In paragraph (c)(4)(iv)(C)(1), revise "on a hourly" to read "on an hourly";
■ h. In paragraph (g)(1)(i), revise "on a hourly" to read "on an hourly".
■ i. Revise paragraphs (c)(1)(i) and (c)(1)(ix) introductory text to read as follows:

§ 266.103 Interim status standards for burners.

* * * * *

(c) * * *

(1) * * *

(i) Feed rate of total hazardous waste and (unless complying with the Tier I or adjusted Tier I metals feed rate screening limits under § 266.106(b) or (e)), pumpable hazardous waste;

* * * * *

(ix) For systems using wet scrubbers, including wet ionizing scrubbers (unless complying with the Tier I or Adjusted Tier I metals feed rate screening limits under § 266.106(b) or (e) and the total chlorine and chloride feed rate screening limits under § 266.107(b)(1) or (e)):

* * * * *

§ 266.106 [Amended]

■ 158–159. In § 266.106, amend paragraph (d)(1) by deleting the second appearance of the phrase "dispersion modeling to predict the maximum annual average off-site ground level concentration for each".

§ 266.109 [Amended]

■ 160. Amend § 266.109 as follows:
■ a. In paragraph (a)(2)(ii), revise "constitutent" to read "constituent" in both instances;
■ b. In paragraph (b) introductory text in the paragraph heading, revise "*particular*" to read "*particulate*".

Subpart N—Conditional Exemption for Low-Level Mixed Waste Storage, Treatment, Transportation and Disposal.

■ 161. Amend Part 266 by revising the subpart heading to read as set forth above.

Appendix III to Part 266—[Amended]

■ 162. Amend Part 266, Appendix III column headings by revising "$C1_2$" to read "Cl_2" three times, and by revising "HC1" to read "HCl" three times (i.e., revise the "1" (one) to be a lower-case letter L in all six cases).

Appendix IV to Part 266—[Amended]

■ 163. Amend Part 266, Appendix IV as follows:
■ a. Revise the entry "Maleic Anyhdride" to read "Maleic Anhydride";
■ b. Revise the entry "2.4.5-Trichlorophenol" to read "2,4,5-Trichlorophenol".

Appendix V to Part 266—[Amended]

■ 164. Amend Part 266, Appendix V as follows:
■ a. Revise the third column heading "Unit risk (m3/μg)" to read "Unit risk ($m^3/\mu g$)";
■ b. Revise the fourth column heading "RsD (μg/m3)" to read "RsD ($\mu g/m^3$)";
■ c. Revise the entry "Benxene" to read "Benzene";
■ d. Revise the entry "Hexachlorodibenxo-p-dioxin (1,2 Mixture)" to read "Hexachlorodibenzo-p-dioxin (1,2 Mixture)".

Appendix VI to Part 266—[Amended]

■ 165. Amend Part 266, Appendix VI by revising the first column heading "Flow rate (m3/s)" to read "Flow rate (m^3/s)".

Appendix VIII to Part 266—[Amended]

■ 166. Amend Part 266, Appendix VIII in the "Semivolatiles" column, by revising "Plychlorinated" to read "Polychlorinated".

Appendix IX to Part 266—[Amended]

■ 167. Amend Part 266, Appendix IX as follows:
■ a. In the Table of Contents at 4.0, revise "Estimating Toxicity Equipment or" to read "Estimating the Toxicity Equivalence of";
■ b. In the Table of Contents at 9.2, revise "Cl," to read "Cl_2";
■ c. In the Table of Contents at 10.4, revise "Overviev" to read "Overview";
■ d. In Section 2.1.2.9, revise "The PA test" to read "The RA test";
■ e. In Section 2.1.2.10, revise "determination of 0^2" to read "determination of O_2)";
■ f. In Table 2.1–1 footnote 1, revise "of twice the permit limit" to read "or twice the permit limit";
■ g. In Section 2.1.4.6, revise "the PA test" to read "the RA test";
■ h. In Section 2.2.10, first sentence, revise "used In conjunction" to read "used in conjunction";
■ i. In the section 4.0 title, revise "DIBENCO-" to read "DIBENZO-";
■ j. In Section 5.0 at Step 6, footnote 5 first sentence, remove the comma after the phrase "urban and rural areas";
■ k. In Section 5.0 at Table 5.0–5, for distance 10.00, revise the Generic source #1 value "9.4" in the second column to read "29.4";
■ l. In Section 5.0 at Step 7(B), second sentence, insert a closing parenthesis after "(identified in Step 7(A)" to read "(identified in Step 7(A))";
■ m. In Section 5.0 at the Table in Step 10(D)1., replace the comma in column heading ">0,5 – 2.5" with a period to read ">0.5–2.5";
■ n. In Section 5.0 at the Table below Table 5.0–6, revise the column heading

"$C^a(\mu g/m^3)$" to read "$C_a(\mu g/m^3)$"; and revise "$C_{A(>G/M3)}$" to read "$C_a(\mu g/m^3)$";
■ o. In Section 6.2, first paragraph second sentence, revise "Within These" to read "Within these";
■ p. In Section 7.1, second paragraph second sentence, revise "Mulitple" to read "Multiple";
■ q. In Section 7.2, at the last paragraph, revise "This, if" to read "Thus, if";
■ r. In Section 8.0, second paragraph, revise "chorine" to read "chlorine";
■ s. In Section 9.2, in the first sentence, revise the formula "Cl2" to read "Cl_2";
■ t. In Section 10.3, last sentence of next to last paragraph, replace the period in the phrase "To avoid this expense." with a comma;
■ u. In Section 10.5(2), fourth bullet, in the sentence starting "Three of the first five tests", replace the period in "hazardous wastes. and in" with a comma.

Appendix XIII to Part 266—[Amended]

■ 168. Amend Part 266, Appendix XIII at item number 14 by revising "levels or mercury" to read "levels of mercury".

PART 267—STANDARDS FOR OWNERS AND OPERATORS OF HAZARDOUS WASTE FACILITIES OPERATING UNDER A STANDARDIZED PERMIT

■ 169. The authority citation for part 267 continues to read as follows:

Authority: 42 U.S.C. 6902, 6912(a), 6924–6926, and 6930.

§ 267.147 [Amended]

■ 170. In § 267.147, amend paragraph (f)(2)(i)(A) by revising "test for facilities regulated under § 267 and also § 264 or § 265" to read "test for facilities regulated under part 267 and also part 264 or part 265".

PART 268—LAND DISPOSAL RESTRICTIONS

■ 171. The authority citation for part 268 continues to read as follows:

Authority: 42 U.S.C. 6905, 6912(a), 6921, and 6924.

§ 268.2 [Amended]

■ 172. In § 268.2, amend paragraph (g) by revising "A manufactured" to read "a manufactured"; "Any material" to read "any material"; "Process residuals" to read "process residuals"; and "and Intact" to read "and intact".

§ 268.4 [Amended]

■ 173. In § 268.4, amend paragraph (a)(3) introductory text by revising the citation "of part 264 or part 264" to read "of part 264 or part 265".

§ 268.6 [Amended]

■ 174. In § 268.6, amend paragraph (c)(5) introductory text by revising "section meet" to read "section meets".

■ 175. Amend § 268.7 as follows:
■ a. In paragraph (a)(1), insert a closing parenthesis at the end of the sentence that starts "(Alternatively, the generator" and in the second to last sentence, revise "solids contaminated" to read "soils contaminated";
■ b. In paragraph (a)(3)(ii), second sentence, insert the word "column" after the phrase "information in", and insert a closing quotation mark after the citation "268.7(a)(3)";
■ c. In paragraph (a)(4), at entry 8 of the Table, amend "[is subject to/complies with" by inserting a closing bracket ("]") at the end of the phrase;
■ d. In paragraph (b)(3)(ii) at entry 5 of the Table, insert a closing quotation mark after the citation "268.49(c)";
■ e. In paragraph (b)(4)(ii), revise the citation "§ 261.3(e)" to read "§ 261.3(f)";
■ f. In paragraph (c)(2), remove the closing parenthesis from "Leaching Procedure)";
■ g. In paragraph (d) introductory text, revise the citation "§ 261.3(e)" to read "§ 261.3(f)";
■ h. Revise paragraph (d)(1) to read as set forth below;
■ i. In paragraph (d)(2), revise the citation "§ 261.2(e)(1)" to read "§ 261.3(f)(1)";
■ j. In paragraph (d)(3), revise the citation "§ 261.3(e)(1)" to read "§ 261.3(f)(1)".

§ 268.7 Testing, tracking, and recordkeeping requirements for generators, treaters, and disposal facilities.

* * * * *

(d) * * *

(1) A one-time notification, including the following information, must be submitted to the EPA Regional hazardous waste management division director (or his designated representative) or State authorized to implement part 268 requirements:

(i) The name and address of the Subtitle D facility receiving the treated debris;

(ii) A description of the hazardous debris as initially generated, including the applicable EPA Hazardous Waste Number(s); and

(iii) For debris excluded under § 261.3(f)(1) of this chapter, the technology from Table 1, § 268.45, used to treat the debris.

* * * * *

§ 268.14 [Amended]

■ 176. In § 268.14, amend paragraphs (b) and (c) by revising "not withstanding" to read "notwithstanding" in both instances.

§ 268.40 [Amended]

■ 177.–178. Amend § 268.40 as follows:
■ a. In paragraph (g), revise "as definded" to read "as defined".
■ b. Amend the table TREATMENT STANDARDS FOR HAZARDOUS WASTES as follows:
■ 1. At the column heading "Wastewaters", revise "Concentration in mg/L[3]" to read "Concentration[3] in mg/L";
■ 2. At the column heading "Nonwastewaters", revise "Concentration in mg/kg[5]" to read "Concentration[5] in mg/kg";
■ 3. At the entry "K047", in the waste description column, revise "water form TNT" to read "water from TNT";
■ 4. At the entries "K049" and "K051", revise the CAS number for "Chrysene" from "2218–01–9" to read "218–01–9";
■ 5. At the entry "K088", revise the common name "Bemz(a)anthracene" to read "Benz(a)anthracene"; and revise the common name "Indeno(1,2,3,-c,d)pyrene" to read "Indeno(1,2,3-cd)pyrene";
■ 6. At the entry "K111", revise the CAS number for "2,4-Dinitrotoluene" from "121–1–2" to read "121–14–2";
■ 7. At the entry "K114", in the waste description column, revise the common name "dinitrotolune" to read "dinitrotoluene";
■ 8. At the entry "K156", revise the CAS number for "Acetophenone" from "96–86–2" to read "98–86–2"; and revise the CAS number for "Triethylamine" from "101–44–8" to read "121–44–8";
■ 9. At the entry "U202" "Acetone" following "U001", revise "U202" to read "U002";
■ 10. At the entry "U134", revise the CAS number "16984–48–8" to read "7664–39–3";
■ 11. At the entry "U137", revise in the waste description and in the common name columns "Indeno(1,2,3-c,d)pyrene" to read "Indeno(1,2,3-cd)pyrene" in both instances.

§ 268.42 [Amended]

■ 179. In § 268.42, Table 1, amend the entry for Technology code "SSTRP" in the second column as follows:
■ a. In the first sentence, revise "as well as, temperature and pressure ranges have" to read "as well as temperature and pressure ranges, have";
■ b. In the second sentence, insert a comma after the phrase "parameters of the unit"; remove the comma in the phrase "such as, the number"; and replace the period at the end of "the internal column design." with a comma;
■ c. In the third sentence, revise "Thus, resulting" to read "thus resulting".

§ 268.44 [Amended]

■ 180. In § 268.44, amend paragraph (c), last sentence of the certification statement, by revising "I am aware that these are" to read "I am aware that there are".

§ 268.45 [Amended]

■ 181. Amend § 268.45, Table 1, as follows:
■ a. At item B.1., first column, revise "biodegration" to read "biodegradation";
■ b. At item B.2.a., first column, revise "electolytic" to read "electrolytic"; and under number (8), revise "permanganates" to read "permanganates".

§ 268.48 [Amended]

■ 182. Amend § 268.48 Table, UNIVERSAL TREATMENT STANDARDS, as follows:
■ a. At the column heading "Wastewater standard", revise "Concentration in mg/l[2]" to read "Concentration[2] in mg/l";
■ b. At the column heading "Nonwastewater standard", revise "Concentration in mg/kg[3]" to read "Concentration[3] in mg/kg".
■ c. At entry "1,2,3,4,6,7,8-Heptachlorodibenzofluran (1,2,3,4,6,7,8-HpCDF)" revise CAS number "67562–39–5" to read "67562–39–4";
■ d. Revise the next entry "1,2,3,4,6,7,8-Heptachlorodibenzofluran (1,2,3,4,7,8,9-HpCDF)" (CAS number 55673–89–7) to read "1,2,3,4,7,8,9–Heptachlorodibenzofluran (1,2,3,4,7,8,9–HpCDF)".

§ 268.49 [Amended]

■ 183. In § 268.49, amend paragraph (d) by revising "flouride" to read "fluoride".

§ 268.50 [Amended]

■ 184. Amend § 268.50 as follows:
■ a. In paragraph (c), revise "A owner/operator" to read "An owner/operator";
■ b. In paragraph (g), revise "requirements in this do not" to read "requirements in this section do not".

Appendix VIII to Part 268—[Amended]

■ 185. Amend Part 268, Appendix VIII, by removing the second instances of the entries for "K011" "Nonwastewater" and for "K011" "Wastewater".

PART 270—EPA ADMINISTERED PERMIT PROGRAMS: THE HAZARDOUS WASTE PERMIT PROGRAM

■ 186. The authority citation for part 270 continues to read as follows:

Authority: 42 U.S.C. 6905, 6912, 6924, 6925, 6927, 6939, and 6974.

§ 270.1 [Amended]

■ 187. Amend § 270.1 as follows:
■ a. In the table in paragraph (a)(2), after 3001 revise "Indentification" to read "Identification";
■ b. In paragraph (b) introductory text, revise "analagous" to read "analogous";
■ c. In paragraph (c)(1)(iii), revise "it they" to read "if they?";
■ d. In paragraph (c)(3)(i) introductory text, revise "obtain an RCRA" to read "obtain a RCRA".

§ 270.2 [Amended]

■ 188. Amend § 270.2 as follows:
■ a. In the definition of "*On-site*", revise "continguous" to read "contiguous";
■ b. In the definition of "*Publicly owned treatment works (POTW)*", revise "unsed" to read "used".

§ 270.10 [Amended]

■ 189. In § 270.10, amend paragraph (j) by revising "stores, treats, or dispose of" to read "stores, treats, or disposes".

§ 270.11 [Amended]

■ 190. Amend § 270.11 as follows:
■ a. In paragraph (d)(1), revise "paragraph (a) or (b) of this must" to read "paragraph (a) or (b) of this section must";
■ b. In paragraph (d)(2), certification statement, revise "upon information and belief" to read "to the best of my knowledge and belief".

§ 270.13 [Amended]

■ 191. In § 270.13, amend paragraph (k)(7) by revising "Sancturies" to read "Sanctuaries".

§ 270.14 [Amended]

■ 192. Amend § 270.14 as follows:
■ a. In paragraph (a), in next to the last sentence, revise "design drawings and specification" to read "design drawings and specifications";
■ b. In paragraph (b)(11)(ii)(B), revise "with 200 feet" to read "within 200 feet";
■ c. In paragraph (b)(19)(iii), revise "intermittant" to read "intermittent";
■ d. In paragraph (b)(21), revise "uner" to read "under".

§ 270.17 [Amended]

■ 193. In § 270.17, amend paragraph (f) by revising "detailed-plans" to read "detailed plans".

§ 270.18 [Amended]

■ 194. In § 270.18, amend paragraph (b) by revising the citation "§ 264.90(2)" to read "§ 264.90(b)(2)"; and amend paragraph (g) by revising "place" to read "placed".

§ 270.20 [Amended]

■ 195. In § 270.20, amend paragraph (i)(2) by revising "attentuative" to read "attenuative".

§ 270.26 [Amended]

■ 196.–197. In § 270.26, amend paragraph (c)(15) by revising "through(f) § 264.573" to read "through (f) of § 264.573".

§ 270.33 [Amended]

■ 198. In § 270.33, amend paragraph (b) introductory text by revising "An RCRA permit" to read "A RCRA permit".

§ 270.41 [Amended]

■ 199. In § 270.41, amend paragraph (c) by revising "environmental" to read "environment".

§ 270.42 [Amended]

■ 200. In § 270.42, amend paragraph (d)(2)(i) by revising "do no" to read "do not".

Appendix I to § 270.42—[Amended]

■ 201. Amend § 270.42 Appendix I as follows:
■ a. At item C.4, revise the modification class code (second column) "[1]2" to read "2";
■ b. At item C.6, revise the citation "264.98(j)" to read "264.98(h)";
■ c. At item C.7.a, revise the citation "264.98(h)(4)" to read "264.98(g)(4)";
■ d. At item C.7.b, revise the citation "264.99(k)" to read "264.99(j)";
■ e. At item C.8.a, revise the citation "264.99(i)(2)" to read "264.99(h)(2)";
■ f. At item F.2, amend by replacing the colon after "2" with a period;
■ g. At item F.4, revise "Storage of treatment" to read "Storage or treatment";
■ h. At item F.4.a., revise the modification class code "1" to read "[1]1";
■ i. At item G.1, amend by replacing the colon after "1" with a period;
■ j. At item H.6, revise the modification class code "*1" to read "[1]1";
■ k. At item J.7, revise the modification class code "*1" to read "[1]1";
■ l. At item L.9, revise "Changes Needed to meet Standards" to read "changes needed to meet standards".

§ 270.70 [Amended]

■ 202.–203. In § 270.70, amend paragraph (a) introductory text by revising "have an RCRA permit" to read "have a RCRA permit".

§ 270.72 [Amended]

■ 204. In § 270.72, amend paragraph (b)(2) by revising "inpoundments" to read "impoundments".

PART 271—REQUIREMENTS FOR AUTHORIZATION OF STATE HAZARDOUS WASTE PROGRAMS

■ 205. The authority citation for Part 271 continues to read as follows:

Authority: 42 U.S.C. 6905, 6912(a), and 6926.

§ 271.1 [Amended]

■ 206. Amend § 271.1 as follows:
■ a. In Table 1, at promulgation date of April 8, 1996, second column, revise "Wastesaters," to read "Wastewaters,"; and at promulgation date of July 15, 2002, second column, revise "Fertlizers" to read "Fertilizers";
■ b. In Table 2, at the fourteenth item under effective date of Nov. 8, 1984, second column, revise "envirorment" to read "environment"; and at effective date of Sept. 1, 1985, second column, revise "mininization" to read "minimization".

§ 271.21 [Amended]

■ 207. Amend § 271.21 as follows:
■ a. In paragraph (f), remove the phrase "speciflines";
■ b. In paragraph (g)(1)(i), revise "dils" to read "diligent efforts".

§ 271.23 [Amended]

■ 208. Amend § 271.23 as follows:
■ a. In paragraph (a)(1), revise "relevent" to read "relevant";
■ b. In paragraph (b)(1), revise "with drawal" to read "withdrawal";
■ c. In paragraph (b)(5), revise "makng" to read "making".

PART 273—STANDARDS FOR UNIVERSAL WASTE MANAGEMENT

■ 209. The authority citation for Part 273 continues to read as follows:

Authority: 42 U.S.C. 6922, 6923, 6924, 6925, 6930, and 6937.

§ 273.9 [Amended]

■ 210. In § 273.9, amend the definition of "*Universal Waste*" as follows:
■ a. Revise "hazardous waste" to read "hazardous wastes";
■ b. In paragraph (1), insert a semicolon after the citation "§ 273.2";
■ c. In paragraph (2), insert a semicolon after the citation "§ 273.3";

§ 273.13 [Amended]

■ 211. In § 273.13, amend paragraph (b) introductory text by revising "prevent releases" to read "prevents releases".

§ 273.14 [Amended]

■ 212. Amend § 273.14, in paragraph (a), by adding closing quotation marks after the phrase "Universal Waste—Battery(ies),".

§ 273.34 [Amended]

■ 213. In § 273.34, amend paragraph (a) by revising "clearly with the any one" to read "clearly with any one".

PART 279—STANDARDS FOR THE MANAGEMENT OF USED OIL

■ 214–215. The authority citation for Part 279 continues to read as follows:

Authority: Sections 1006, 2002(a), 3001 through 3007, 3010, 3014, and 7004 of the Solid Waste Disposal Act, as amended (42 U.S.C. 6905, 6912(a), 6921 through 6927, 6930, 6934, and 6974); and sections 101(37) and 114(c) of CERCLA (42 U.S.C. 9601(37) and 9614(c)).

§ 279.1 [Amended]

■ 216. In § 279.1, amend the definition of "Petroleum refining facility" by revising "kerosine" to read "kerosene".

§ 279.10 [Amended]

■ 217. In § 279.10, amend paragraph (b)(2) introductory text by revising "solely exhibits" to read "solely exhibit"; and by revising "hazardous waste characteristic" to read "hazardous waste characteristics".

§ 279.11 [Amended]

■ 218. Amend § 279.11 as follows:
■ a. In the first sentence, delete "in the specification"; and in the second sentence, revise "not to exceed any specification" to read "not to exceed any allowable level";
■ b. In Table 1, revise the title of the table to read "TABLE 1—USED OIL NOT EXCEEDING ANY ALLOWABLE LEVEL SHOWN BELOW IS NOT SUBJECT TO THIS PART WHEN BURNED FOR ENERGY RECOVERY[1]", and in the first footnote, revise "The specification does not" to read "The allowable levels do not".

§ 279.43 [Amended]

■ 219. Amend § 279.43 as follows:
■ a. In paragraph (c)(3)(i), insert a comma after the citation "49 CFR 171.15";
■ b. In paragraph (c)(5), revise "used oil discharged" to read "used oil discharge".

§ 279.44 [Amended]

■ 220. Amend § 279.44 as follows:
■ a. In paragraph (a), revise "being transporter" to read "being transported";
■ b. In paragraph (c)(2), revise "if the CFC are" to read "if the CFCs are".

§ 279.45 [Amended]

■ 221. Amend § 279.45 in paragraph (a) by revising "subpart F of this chapter" to read "subpart F of this part".

§ 279.52 [Amended]

■ 222. Amend § 279.52 as follows:
■ a. In paragraphs (a) and (b), revise "processors and re-refiners" to read "processing and re-refining" in both instances;
■ b. In paragraph (b)(1)(ii), revise "release or used oil" to read "release of used oil";
■ c. In paragraph (b)(6)(ii), revise "a real extent" to read "areal extent"; revise "facility records of manifests" to read "facility records or manifests"; and revise "analysts" to read "analyses";
■ d. In paragraph (b)(6)(iii), revise "from water of chemical" to read "from water or chemical".

§ 279.55 [Amended]

■ 223. Amend § 279.55 as follows:
■ a. In paragraph (a) introductory text, revise "At at minimum" to read "At a minimum";
■ b. In paragraph (b)(2)(i)(B), revise the citation "§ 260.20 and 260.21" to read "§§ 260.20 and 260.21".

§ 279.56 [Amended]

■ 224. Amend § 279.56 in paragraph (a)(2), by revising "processor/re-refining" to read "processor/re-refiner".

§ 279.57 [Amended]

■ 225. In § 279.57, amend paragraph (a)(2)(ii) by revising "an specified" to read "as specified".

§ 279.59 [Amended]

■ 226. Amend § 279.59 by revising "or re-fining of" to read "or re-refining of".

§ 279.63 [Amended]

■ 227. In § 279.63, amend paragraph (b)(3) by revising "processor/refiner" to read "processor/re-refiner".

§ 279.64 [Amended]

■ 228. In § 279.64, amend paragraph (e) heading by revising the word "existing" to read "new".

§ 279.70 [Amended]

■ 229. In § 279.70, amend paragraph (b)(1) by revising the word "incidently" to read "incidentally".

[FR Doc. 06–5601 Filed 7–13–06; 8:45 am]
BILLING CODE 6560–50–P

the objection arises after the comment period allowed for in the proposal. Filing a petition for reconsideration by the Administrator of this final rule does not affect the finality of this rule for the purposes of judicial review nor does it extend the time within which a petition for judicial review may be filed, and shall not postpone the effectiveness of such rule or action. This action may not be challenged later in proceedings to enforce its requirements. (See section 307(b)(2).)

List of Subjects in 40 CFR Part 62

Environmental protection, Administrative practices and procedures, Air pollution control, Intergovernmental relations, Reporting and recordkeeping requirements, Solid Waste Incinerators, Waste treatment and disposal.

Dated: March 27, 2007.

Robert W. Varney,

Regional Administrator, EPA New England.

■ 40 CFR part 62 is amended as follows:

PART 62—[AMENDED]

■ 1. The authority citation for part 62 continues to read as follows:

Authority: 42 U.S.C. 7401 *et seq.*

Subpart OO—Rhode Island

■ 2. Subpart OO is amended by adding a new § 62.9995 and a new undesignated center heading to read as follows:

Air Emissions From Existing Other Solid Waste Incineration Units

§ 62. 9995 Identification of Plan-Negative Declaration.

On November 5, 2006, the Rhode Island Department of Environmental Management submitted a letter certifying that there are no existing other solid waste incineration units in the state subject to the emission guidelines under part 60, subpart EEEE of this chapter.

[FR Doc. E7–6460 Filed 4–5–07; 8:45 am]
BILLING CODE 6560–50–P

ENVIRONMENTAL PROTECTION AGENCY

40 CFR Part 261

[EPA–R05–RCRA–2007–0213; SW–FRL–8294–8]

Hazardous Waste Management System; Identification and Listing of Hazardous Waste Final Exclusion

AGENCY: Environmental Protection Agency (EPA).

ACTION: Final rule.

SUMMARY: The EPA (also, "the Agency" or "we" in this preamble) is granting a petition to exclude (or "delist") wastewater treatment plant sludges from conversion coating on aluminum generated by AutoAlliance International, Inc. (AAI), a Ford/Mazda joint venture company in Flat Rock, Michigan, from the list of hazardous wastes.

Today's action conditionally excludes the petitioned waste from the requirements of hazardous waste regulations under the Resource Conservation and Recovery Act (RCRA) when disposed of in a lined Subtitle D landfill which is permitted, licensed, or registered by a State to manage industrial solid waste. The exclusion was proposed on March 7, 2002 as part of an expedited process to evaluate this waste under a pilot project developed with the Michigan Department of Environmental Quality (MDEQ). The rule also imposes testing conditions for waste generated in the future to ensure that this waste continues to qualify for delisting.

DATES: This rule is effective on April 6, 2007.

ADDRESSES: EPA has established an electronic docket for this action under Docket ID No. EPA–R05–RCRA–2007–0213. The electronic docket contains all relevant documents created after this action was proposed as well as a selection of pertinent documents from the original paper docket for the proposed rule, Docket ID No. R5–MIECOS–01. Certain other material, such as copyrighted material, is not placed on the Internet and will be publicly available only in hard copy form. All documents in the electronic docket are listed on the *http://www.regulations.gov* Web site. Publicly available materials from Docket ID No. EPA–R05–RCRA–2007–0213 are available either electronically through *http://www.regulations.gov* or in hard copy. Materials from the original paper docket, Docket ID No. R5–MIECOS–01, are also available in hard copy. You can view and copy materials from both dockets at the Records Center, 7th floor, U.S. EPA Region 5, 77 West Jackson Blvd., Chicago, Illinois 60604. This facility is open from 8:30 a.m. to 4 p.m., Monday through Friday, excluding legal holidays. We recommend you telephone Todd Ramaly at (312) 353–9317 before visiting the Region 5 office.

FOR FURTHER INFORMATION CONTACT: Todd Ramaly, Waste, Pesticides, and Toxics Division, (Mail Code: DU–7J), EPA Region 5, 77 W. Jackson Blvd., Chicago, IL 60604; *telephone number:* (312) 353–9317; *fax number:* (312) 353–4788; *e-mail address: ramaly.todd@epa.gov.*

SUPPLEMENTARY INFORMATION: The information in this section is organized as follows:

I. Background
A. What is a delisting petition?
B. What regulations allow a waste to be delisted?
C. What waste did AAI petition to delist?
II. The Expedited Process for Delisting
A. Why was the expedited process developed for this waste?
B. What is the expedited process to delist F019?
III. EPA's Evaluation of This Petition
A. What information was submitted in support of this petition?
B. How did EPA evaluate the information submitted?
IV. Public Comments Received on the Proposed Exclusion
A. Who submitted comments on the proposed rule?
B. Comments received and responses from EPA
V. Final Rule Granting This Petition
A. What decision is EPA finalizing?
B. What are the terms of this exclusion?
C. When is the delisting effective?
D. How does this action affect the states?
VI. Statutory and Executive Order Reviews

I. Background

A. What is a delisting petition?

A delisting petition is a request from a generator to exclude waste from the list of hazardous wastes under RCRA regulations. In a delisting petition, the petitioner must show that waste generated at a particular facility does not meet any of the criteria for which EPA listed the waste as set forth in Title 40 Code of Federal Regulations (40 CFR) 261.11 and the background document for the waste. In addition, a petitioner must demonstrate that the waste does not exhibit any of the hazardous waste characteristics (that is, ignitability, reactivity, corrosivity, and toxicity) and must present sufficient information for us to decide whether factors other than those for which the waste was listed warrant retaining it as a hazardous waste. See 40 CFR 260.22, 42 United States Code (U.S.C.) 6921(f) and the background documents for a listed waste.

Generators remain obligated under RCRA to confirm that their waste remains nonhazardous based on the hazardous waste characteristics even if EPA has "delisted" the wastes and to ensure that future generated wastes meet the conditions set.

B. What regulations allow a waste to be delisted?

Under 40 CFR 260.20, 260.22, and 42 U.S.C. 6921(f), facilities may petition the EPA to remove their wastes from hazardous waste control by excluding them from the lists of hazardous wastes contained in 40 CFR 261.31 and 261.32. Specifically, 40 CFR 260.20 allows any person to petition the Administrator to modify or revoke any provision of parts 260 through 266, 268, and 273 of 40 CFR. 40 CFR 260.22 provides a generator the opportunity to petition the Administrator to exclude a waste from the lists of hazardous wastes on a "generator specific" basis.

C. What waste did AAI petition to delist?

AAI petitioned to exclude wastewater treatment sludges resulting from a zinc phosphating conversion coating process on car and truck bodies, which have aluminum components. When treated, the wastewater from the conversion coating on aluminum results in a listed waste, F019. The wastewater from the phosphating process entering the wastewater treatment plant combines with wastewaters from other operations at the plant including cleaning and rinsing operations, electrocoating processes, vehicle leak testing, and floor scrubbing. Wastewaters include alkaline cleaners, surfactants, organic detergents, rinse conditioners from cleaning operations and overflows and rinse water from electrocoating. All sludge from the treatment of this wastewater is regulated as RCRA hazardous waste F019.

II. The Expedited Process for Delisting

A. Why was the expedited process developed for this waste?

Automobile manufacturers are adding aluminum components to automobile and light truck bodies. When aluminum is conversion coated in a zinc phosphating process in automobile assembly plants, the resulting wastewater treatment sludge must be managed as EPA hazardous waste F019. F019 wastes generated at other auto assembly plants using the same zinc phosphating and wastewater treatment processes have been shown to be nonhazardous.

This similarity of manufacturing processes and the resultant wastes provides an opportunity for the automobile industry to be more efficient in submitting delisting petitions and for EPA to be more efficient in evaluating them. Efficiency may be gained and time saved by using a standardized approach for gathering, submitting and evaluating data. Therefore, EPA, in conjunction with MDEQ, developed a pilot project to expedite the delisting process. This approach to making delisting determinations for this group of facilities is efficient while still being consistent with current laws and regulations and protective of human health and the environment.

By removing regulatory controls under RCRA, EPA is facilitating the use of aluminum in cars. EPA believes that incorporating aluminum in cars will be advantageous to the environment since lighter cars are capable of achieving better fuel economy.

B. What is the expedited process to delist F019?

The expedited process to delist F019 is an approach developed through a Memorandum of Understanding (MOU) with MDEQ for gathering and evaluating data in support of multiple petitions from automobile assembly plants. The expedited delisting process is applicable to wastes generated by automobile and light truck assembly plants in the State of Michigan which use a similar manufacturing process and generate similar F019 waste.

Based on available historical data and other information, the expedited process identified 70 constituents which might be of concern in the waste and provides that the F019 sludge generated by automobile assembly plants may be delisted if the levels of the 70 constituents do not exceed the allowable levels established for each constituent in this rulemaking. The maximum annual quantity of waste generated by any single facility that may be covered by an expedited delisting is 3,000 cubic yards. Delisting levels were also proposed for smaller quantities of 1,000 and 2,000 cubic yards.

III. EPA's Evaluation of This Petition

A. What information was submitted in support of this petition?

AAI submitted certification that its process was the same as the process described in the MOU between Region 5 and MDEQ. See 67 FR 10341, March 7, 2002. The facility also asserted that its waste does not meet the criteria for which F019 waste was listed and there are no other factors that might cause the waste to be hazardous.

To support its exclusion demonstration, AAI collected six samples representing waste generated over six discreet one-week periods. AAI stored six roll-off boxes of sludge generated weekly from May 6 through June 16, 2005. Composite and grab samples were collected from each of the six roll-off boxes on June 25, 2005. Each sample was analyzed for: (1) Total analyses of 69 constituents of concern; (2) Toxicity Characteristic Leaching Procedure (TCLP), SW–846 Method 1311, analyses of 69 constituents of concern; (3) oil and grease; and (4) leachable metals using the Extraction Procedure for Oily Wastes (OWEP), SW–846 Method 1330A, in lieu of Method 1311 if a sample contained more than 1% oil and grease. In addition, the pH of each sample was measured and a determination was made that the waste was not ignitable, corrosive or reactive (see 40 CFR 261.21–261.23). Although the expedited delisting project originally required analysis of 70 constituents, analysis of acrylamide required extreme methods to achieve a detection level at the level of concern and no acrylamide was detected in any sample analyzed by the original facilities participating in the expedited delisting project. Thus, the Agency decided it would not be appropriate to require analysis for acrylamide. Also, AAI was not required to analyze for total sulfide and total cyanide as long as they provided the narrative determination of reactivity required in 40 CFR Part 261.23. With the exception of the minor changes described above, all sampling and analyses were done in accordance with the sampling and analysis plan, which is an appendix to the MOU and is available in the docket for this rule.

The maximum values of constituents detected in any sample of the waste (in milligrams per kilogram—mg/kg) and in a TCLP or OWEP analysis of that waste (in milligrams per liter—mg/L) are summarized in the following table. The data submitted included the appropriate quality assurance and quality control (QA/QC) information validated by a third party.

Constituent detected	Maximum observed concentration		Maximum allowable concentration		GW (µg/L)
	Total (mg/kg)	TCLP (mg/L)	Total (mg/kg)	TCLP*(mg/L)	
Volatile Organic Compounds					
acetone	8.6	0.43	NA	228	3,750
formaldehyde	4.6	0.23	689	84.2	1,380
Semivolatile Organic Compounds					
bis(2-ethylhexyl)phthalate	4.9	<0.005	NA	0.0896	1.47
di-n-octyl phthalate	3.3	<0.002	NA	0.112	1.3
o-cresol	<1.5	0.0011	NA	114	1,875
p-cresol	<1.5	0.005	NA	11.4	188
Metals					
barium	208	<0.35	NA	100	2,000
chromium	58	<0.17	NA	4.95	100
lead	9.7	<0.2	NA	5	15
mercury	<0.1	0.0007	8.92	0.2	2
nickel	1,850	12.8	NA	90.5	750
tin	184	19.6	NA	721	22,500
zinc	13,300	0.45	NA	898	11,300

*Or OWEP as applicable.
< Not detected at the specified concentration.
NA not applicable.

B. How did EPA evaluate the information submitted?

EPA compared the analytical results submitted by AAI to the maximum allowable levels set forth in the proposed rule (67 FR 10341, March 7, 2002). The maximum allowable levels for constituents detected in the waste or a TCLP extract of the waste are summarized in the table above, along with the observed levels. The table also includes the maximum allowable levels in groundwater at a potential receptor well (in micrograms per liter—µg/L), as evaluated by the Delisting Risk Assessment Software (DRAS). These levels are the more conservative of either the Safe Drinking Water Act Maximum Contaminant Level (MCL) or the health-based value calculated by DRAS based on the target cancer risk level of 10^{-6}. For arsenic, the target cancer risk was set at 10^{-4} in consideration of the MCL and the potential for natural occurrence. The maximum allowable groundwater concentration and delisting level for arsenic correspond to a drinking water concentration less than one half the current MCL of 10 µg/L.

EPA also used the DRAS program to estimate the aggregate cancer risk and hazard index for constituents detected in the waste. The aggregate cancer risk is the cumulative total of all individual constituent cancer risks. The hazard index is a similar cumulative total of non-cancer effects. The target aggregate cancer risk is 1×10^{-5} and the target hazard index is one. The wastewater treatment plant sludge at AAI met both of these criteria based on maximum observed values.

IV. Public Comments Received on the Proposed Exclusion

A. Who submitted comments on the proposed rule?

The EPA received public comments on the proposed notice published on March 7, 2002 from Alliance of Automobile Manufacturers, Honda of America Mfg., Inc., Alcoa Inc., and The Aluminum Association. All commenters were supportive of the proposal and suggested expanding the project and revising the listing.

B. Comments Received and Responses From EPA

(1) *Comment:* EPA should revise the F019 listing to specify that wastewater treatment sludges from zinc phosphating operations are not within the scope of the listing. Data gathered as a result of the Expedited Delisting Project, together with the available historical data, should provide enough data to fully characterize this waste and to justify a revision of the listing.

EPA Response: On January 18, 2007 (72 FR 2219), the Agency proposed to amend the F019 listing to exempt the wastewater treatment sludge generated from zinc phosphating, when zinc phosphating is used in the automobile assembly process and provided the waste is disposed in a landfill unit subject to certain liner design criteria.

(2) *Comment:* EPA should issue an interpretive rule clarifying that zinc phosphating operations are outside the scope of the F019 listing.

EPA Response: See response to comment (1) above.

(3) *Comment:* Automobile assembly facilities outside of Michigan would like to take advantage of the precedent set by this expedited delisting project to delist F019 generated by similar operations in other states and regions.

EPA Response: The Agency believes that the expedited delisting procedures and requirements set forth in this proposal are appropriate for similar automotive assembly facilities outside the State of Michigan, subject to the discretion of the regulatory agency (state or region).

(4) *Comment:* Alternatives to landfilling like recycling should be allowed within the petition process.

EPA Response: The risk assessment model currently used by the Agency cannot predict the risks from exposure to waste that are managed through recycling. EPA's conditional delisting policy is that in order to reduce the uncertainty caused by potential unrestricted use or management of delisted waste, delistings apply only to wastes managed in the type of unit (*e.g.*, "a landfill") modeled in the delisting risk assessment. EPA recognizes that several recent rulemakings related to RCRA-listed hazardous wastes have proposed conditional exemptions from the regulatory definition of "solid waste" when such wastes, by virtue of their being recycled, are treated more as commodities than as wastes. For example, see 68 FR 61588, October 28,

2005. The Agency is not aware of any recycling or reclamation of F019 sludges; therefore, EPA believes that current market conditions do not support the recycling of F019 waste for the purposes of recovering the metal content of such waste. EPA has requested comment on whether this understanding is accurate and whether recycling of F019 waste is economically feasible under today's market conditions. See 72 FR 2224, January 18, 2007. If recycling of F019 wastes becomes economically feasible or beneficial in the future, the Agency will consider its options for how to address this, including through a subsequent rulemaking, such as the ongoing rulemaking related to the definition of solid waste.

(5) *Comment:* Analytical methods should be specified in the pre-approved common sampling plan instead of requiring each participant to submit a site-specific list of methods.

EPA Response: Allowing the petitioner to choose an analytical method which meets the data quality objectives specific to the delisting petition provides flexibility. Data quality objectives will vary depending on the allowable levels that are a function of the volume of petitioned waste. The Agency believes that the flexibility of performance based methods results in better data.

(6) *Comment:* Detection limits should not be required prior to sampling since they cannot be adequately predicted without a way to estimate matrix effects.

EPA Response: Although matrix effects cannot be assessed in advance of laboratory analysis, a laboratory should be able to provide estimated detection levels and reporting levels which are lower than, or at least equal to, the allowable delisting level for each constituent.

(7) *Comment:* Since the process generating the sludge is extremely stable, verification sampling should be conducted on an annual, instead of quarterly, basis. The requirement that any process change is promptly reported and the exclusion suspended until EPA gives written approval that the delisting can continue is an adequate safeguard justifying the decrease in sample event frequency.

EPA Response: Verification data submitted in conjunction with past delistings of this waste have shown significant variation on a quarterly basis over longer periods of time. Annual sampling would not detect such variations. Once enough verification data are collected to support a statistical analysis, a change in the frequency of verification sampling and/or sampling parameters may be considered.

(8) *Comment:* The final **Federal Register** should make it clear that assembly plants that manufacture light trucks are also eligible for the project.

EPA Response: Today's notice specifically defines eligible facilities as inclusive of manufacturers of light trucks.

(9) *Comment:* The table of maximum allowable levels in the March 7, 2002 proposed rule contains errors in the columns for vinyl chloride.

EPA Response: A missing space or tab in the table caused the error. The maximum allowable concentrations proposed for 2,000 cubic yards of waste should have been 115 mg/kg total and 0.00234 mg/L TCLP.

V. Final Rule Granting This Petition

A. What decision is EPA finalizing?

Today the EPA is finalizing an exclusion to conditionally delist an annual volume of 2,000 cubic yards of wastewater treatment plant sludges generated at AAI from conversion coating on aluminum.

On March 7, 2002, EPA proposed to exclude or delist this wastewater treatment sludge from the list of hazardous wastes in 40 CFR 261.31 and accepted public comment on the proposed rule (67 FR 10341). EPA considered all comments received, and we believe that this waste should be excluded from hazardous waste control.

After EPA proposed the exclusion for AAI in 2002, the Agency promulgated the Methods Innovation Rule (MIR)(70 FR 34538, June 14, 2005). The MIR reformed RCRA-related testing and monitoring by restricting requirements to use the methods found in "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods," also known as "SW–846," to those situations where the method is the only one capable of measuring the property (*i.e.*, it is used to measure a method-defined parameter). In addition, the MIR revised several conditional delistings to specifically mention method-defined parameters incorporated by reference at § 260.11 consistent with the Office of Federal Register's revised format for incorporation by reference. Therefore, EPA is including a specific reference to SW–846 Methods 1311, 1330A, and 9071B (method-defined parameters) for the generation of the leachate extract in the quarterly verification testing requirement for the AAI delisting. SW–846 Method 1311 must be used for generation of the leachate extract used in the testing of the delisting levels if oil and grease comprise less than 1% of the waste. SW–846 Method 1330A must be used for generation of the leaching extract if oil and grease comprise 1% or more of the waste. SW–846 Method 9071B must be used for determination of oil and grease. SW–846 Methods 1311, 1330A, and 9071B are incorporated by reference in 40 CFR 260.11.

B. What are the terms of this exclusion?

AAI must dispose of the waste in a lined Subtitle D landfill which is permitted, licensed, or registered by a state to manage industrial solid waste. AAI must obtain and analyze on a quarterly basis a representative sample of the waste. AAI must verify that the concentrations of the constituents of concern do not exceed the allowable levels set forth in this exclusion. The list of constituents for verification is a subset of those initially tested for and is based on the occurrence of constituents at the majority of facilities participating in the expedited process to delist F019 and the concentrations detected relative to the allowable levels.

This exclusion applies only to a maximum annual volume of 2,000 cubic yards and is effective only if all conditions contained in this rule are satisfied.

C. When is the delisting effective?

This rule is effective April 6, 2007. The Hazardous and Solid Waste Amendments of 1984 amended section 3010 of RCRA to allow rules to become effective in less than six months when the regulated community does not need the six-month period to come into compliance. This rule reduces rather than increases the existing requirements and, therefore, is effective immediately upon publication under the Administrative Procedure Act, pursuant to 5 U.S.C. 553(d).

D. How does this action affect the states?

Today's exclusion is being issued under the federal RCRA delisting program. Therefore, only states subject to federal RCRA delisting provisions would be affected. This exclusion is not effective in states that have received authorization to make their own delisting decisions. Also, the exclusion may not be effective in states having a dual system that includes federal RCRA requirements and their own requirements. EPA allows states to impose their own regulatory requirements that are more stringent than EPA's, under section 3009 of RCRA. These more stringent requirements may include a provision that prohibits a federally issued

exclusion from taking effect in the state. Because a dual system (that is, both federal (RCRA) and state (non-RCRA) programs) may regulate a petitioner's waste, we urge petitioners to contact the state regulatory authority to establish the status of their wastes under the state law. If a participating facility transports the petitioned waste to or manages the waste in any state with delisting authorization, it must obtain a delisting from that state before it can manage the waste as nonhazardous in the state.

VI. Statutory and Executive Order Reviews

Under Executive Order 12866, "Regulatory Planning and Review" (58 FR 51735, October 4, 1993), this rule is not of general applicability and therefore is not a regulatory action subject to review by the Office of Management and Budget (OMB). This rule does not impose an information collection burden under the provisions of the Paperwork Reduction Act of 1995 (44 U.S.C. 3501 *et seq.*) because it applies to a particular facility only. Because this rule is of particular applicability relating to a particular facility, it is not subject to the regulatory flexibility provisions of the Regulatory Flexibility Act (5 U.S.C. 601 *et seq.*), or to sections 202, 204, and 205 of the Unfunded Mandates Reform Act of 1995 (UMRA) (Pub. L. 104–4). Because this rule will affect only a particular facility, it will not significantly or uniquely affect small governments, as specified in section 203 of UMRA.

Because this rule will affect only a particular facility, this final rule does not have federalism implications. It will not have substantial direct effects on the States, on the relationship between the national government and the States, or on the distribution of power and responsibilities among the various levels of government, as specified in Executive Order 13132, "Federalism," (64 FR 43255, August 10, 1999). Thus, Executive Order 13132 does not apply to this rule. Similarly, because this rule will affect only a particular facility, this final rule does not have tribal implications, as specified in Executive Order 13175, "Consultation and Coordination with Indian Tribal Governments" (65 FR 67249, November 9, 2000). Thus, Executive Order 13175 does not apply to this rule.

This rule also is not subject to Executive Order 13045,"Protection of Children from Environmental Health Risks and Safety Risks" (62 FR 19885, April 23, 1997), because it is not economically significant as defined in Executive Order 12866, and because the Agency does not have reason to believe the environmental health or safety risks addressed by this action present a disproportionate risk to children. The basis for this belief is that the Agency used the DRAS program, which considers health and safety risks to infants and children, to calculate the maximum allowable concentrations for this rule.

This rule is not subject to Executive Order 13211, "Actions Concerning Regulations That Significantly Affect Energy Supply, Distribution, or Use" (66 FR 28355 (May 22, 2001)), because it is not a significant regulatory action under Executive Order 12866.

This rule does not involve technical standards; thus, the requirements of section 12(d) of the National Technology Transfer and Advancement Act of 1995 (15 U.S.C. 272 note) do not apply.

The Congressional Review Act, 5 U.S.C. 801 *et seq.*, as added by the Small Business Regulatory Enforcement Fairness Act of 1996, generally provides that before a rule may take effect, the agency promulgating the rule must submit a rule report which includes a copy of the rule to each House of the Congress and to the Comptroller General of the United States. Section 804 exempts from section 801 the following types of rules: (1) Rules of particular applicability; (2) rules relating to agency management or personnel; and (3) rules of agency organization, procedure, or practice that do not substantially affect the rights or obligations of non-agency parties 5 U.S.C. 804(3). EPA is not required to submit a rule report regarding today's action under section 801 because this is a rule of particular applicability.

List of Subjects in 40 CFR Part 261

Environmental protection, Hazardous waste, Recycling, and Reporting and recordkeeping requirements.

Authority: Sec. 3001(f) RCRA, 42 U.S.C. 6921(f).

Dated: March 19, 2007.

Margaret M. Guerriero,

Director, Waste, Pesticides and Toxics Division.

■ For the reasons set out in the preamble, 40 CFR part 261 is amended as follows:

PART 261—IDENTIFICATION AND LISTING OF HAZARDOUS WASTE

■ 1. The authority citation for part 261 continues to read as follows:

Authority: 42 U.S.C. 6905, 6912(a), 6921, 6922, and 6938.

■ 2. In Table 1 of Appendix IX of part 261 the following wastestream is added in alphabetical order to read as follows:

Appendix IX to Part 261—Wastes Excluded Under §§ 260.20 and 260.22

TABLE 1.—WASTES EXCLUDED FROM NON-SPECIFIC SOURCES

Facility/address	Waste description
* * * * * * *	
AutoAlliance International Inc., Flat Rock, Michigan.	Wastewater treatment sludges, F019, that are generated by AutoAlliance International, Inc. (AAI) at Flat Rock, Michigan at a maximum annual rate of 2,000 cubic yards per year. The sludges must be disposed of in a lined landfill with leachate collection which is licensed, permitted, or otherwise authorized to accept the delisted wastewater treatment sludges in accordance with 40 CFR part 258. The exclusion becomes effective as of April 6, 2007. 1. Delisting Levels: (A) The concentrations in a leachate extract of the waste measured in any sample must not exceed the following levels (mg/L): arsenic—0.3; cadmium—0.5; chromium—4.95; lead—5; nickel—90.5; selenium—1; tin—721; zinc—898; p-cresol—11.4; and formaldehyde—84.2. (B) The total concentration measured in any sample must not exceed the following levels (mg/kg): mercury—8.92; and formaldehyde—689.

TABLE 1.—WASTES EXCLUDED FROM NON-SPECIFIC SOURCES—Continued

Facility/address	Waste description
	2. Quarterly Verification Testing: To verify that the waste does not exceed the specified delisting levels, AAI must collect and analyze one representative sample of the waste on a quarterly basis. Sample collection and analyses, including quality control procedures, must be performed using appropriate methods. SW–846 Method 1311 must be used for generation of the leachate extract used in the testing of the delisting levels if oil and grease comprise less than 1% of the waste. SW–846 Method 1330A must be used for generation of the leaching extract if oil and grease comprise 1% or more of the waste. SW–846 Method 9071B must be used for determination of oil and grease. SW–846 Methods 1311, 1330A, and 9071B are incorporated by reference in 40 CFR 260.11. 3. Changes in Operating Conditions: AAI must notify the EPA in writing if the manufacturing process, the chemicals used in the manufacturing process, the treatment process, or the chemicals used in the treatment process change significantly. AAI must handle wastes generated after the process change as hazardous until it has demonstrated that the wastes continue to meet the delisting levels and that no new hazardous constituents listed in Appendix VIII of part 261 have been introduced and it has received written approval from EPA. 4. Data Submittals: AAI must submit the data obtained through verification testing or as required by other conditions of this rule to both U.S. EPA Region 5, 77 W. Jackson Blvd., Chicago, IL 60604 and MDEQ, Waste and Hazardous Materials Division, Hazardous Waste Section, at P.O. Box 30241, Lansing, Michigan 48909. The quarterly verification data and certification of proper disposal must be submitted annually upon the anniversary of the effective date of this exclusion. AAI must compile, summarize and maintain on site for a minimum of five years records of operating conditions and analytical data. AAI must make these records available for inspection. A signed copy of the certification statement in 40 CFR 260.22(i)(12) must accompany all data. 5. Reopener Language: (a) If, anytime after disposal of the delisted waste AAI possesses or is otherwise made aware of any data (including but not limited to leachate data or groundwater monitoring data) relevant to the delisted waste indicating that any constituent is at a level in the leachate higher than the specified delisting level, or is in the groundwater at a concentration higher than the maximum allowable groundwater concentration in paragraph (e), then AAI must report such data, in writing, to the Regional Administrator within 10 days of first possessing or being made aware of that data. (b) Based on the information described in paragraph (a) and any other information received from any source, the Regional Administrator will make a preliminary determination as to whether the reported information requires Agency action to protect human health or the environment. Further action may include suspending, or revoking the exclusion, or other appropriate response necessary to protect human health and the environment. (c) If the Regional Administrator determines that the reported information does require Agency action, the Regional Administrator will inform AAI in writing of the actions the Regional Administrator believes are necessary to protect human health and the environment. The notice shall include a statement of the proposed action and a statement providing AAI with an opportunity to present information as to why the proposed Agency action is not necessary or to suggest an alternative action. AAI shall have 30 days from the date of the Regional Administrator's notice to present the information. (d) If after 30 days AAI presents no further information, the Regional Administrator will issue a final written determination describing the Agency actions that are necessary to protect human health or the environment. Any required action described in the Regional Administrator's determination shall become effective immediately, unless the Regional Administrator provides otherwise. (e) Maximum Allowable Groundwater Concentrations (μg/L): arsenic—5; cadmium—5; chromium—100; lead—15; nickel—750; selenium—50; tin—22,500; zinc—11,300; p-cresol—188; and formaldehyde—1,380.

* * * * * * *

[FR Doc. 07–1650 Filed 4–5–07; 8:45 am]
BILLING CODE 6560–50–P

DEPARTMENT OF TRANSPORTATION

Surface Transportation Board

49 CFR Part 1002

[STB Ex Parte No. 542 (Sub-No. 14)]

Regulations Governing Fees for Services Performed in Connection With Licensing and Related Services—2007 Update

AGENCY: Surface Transportation Board.
ACTION: Final Rule.

SUMMARY: The Board adopts its 2007 User Fee Update and revises its fee schedule to recover the costs associated with the January 2007 Government salary increases and to reflect changes in overhead costs to the Board.

EFFECTIVE DATE: These rules are effective May 6, 2007.

FOR FURTHER INFORMATION CONTACT: David T. Groves, (202) 245–0327, or Anne Quinlan, (202) 245–0309. [TDD for the hearing impaired: 1–800–877–8339.]

SUPPLEMENTARY INFORMATION: The Board's regulations at 49 CFR 1002.3 require that the Board's user fee schedule be updated annually. The regulation at 49 CFR 1002.3(a) provides that the entire fee schedule or selected fees can be modified more than once a year, if necessary. Fees are revised based on the cost study formula set forth at 49 CFR 1002.3(d).

Because Board employees received a salary increase of 2.64% in January 2007, the Board is updating its user fees to recover the increased personnel costs. With certain exceptions, all fees, including those adopted or amended in *Regulations Governing Fees for Services Performed in Connection With Licensing and Related Services—2002 New Fees,* STB Ex Parte No. 542 (Sub-No. 4) (STB served Mar. 29, 2004) will also be updated based on the cost formula contained in 49 CFR 1002.3(d). In addition, changes to the overhead costs borne by the Board are reflected in the revised fee schedule.

The fee increases adopted here result from the mechanical application of the update formula in 49 CFR 1002.3(d), which was adopted through notice and comment procedures in *Regulations Governing Fees for Services—1987 Update,* 4 I.C.C.2d 137 (1987). No new fees are being proposed in this proceeding. Therefore, the Board finds

[FR Doc. E6–22413 Filed 12–29–06; 8:45 am]
BILLING CODE 6560–50–P

ENVIRONMENTAL PROTECTION AGENCY

40 CFR Part 261

[SW–FRL–8264–7]

Hazardous Waste Management System; Identification and Listing of Hazardous Waste; Final Exclusion

AGENCY: Environmental Protection Agency.

ACTION: Final Rule.

SUMMARY: Environmental Protection Agency (EPA) is granting a petition submitted by General Motors Corporation-Arlington Truck Assembly Plant (GM-Arlington) to exclude (or delist) a wastewater treatment plant (WWTP) sludge generated by GM-Arlington in Arlington, TX from the lists of hazardous wastes. This final rule responds to the petition submitted by GM-Arlington to delist F019 WWTP sludge generated from the facility's waste water treatment plant.

After careful analysis and use of the Delisting Risk Assessment Software (DRAS), EPA has concluded the petitioned waste is not hazardous waste. This exclusion applies to 3,000 cubic yards per year of the F019 WWTP sludge. Accordingly, this final rule excludes the petitioned waste from the requirements of hazardous waste regulations under the Resource Conservation and Recovery Act (RCRA) when it is disposed in a Subtitle D Landfill.

EFFECTIVE DATE: January 3, 2007.

ADDRESSES: The public docket for this final rule is located at the Environmental Protection Agency Region 6, 1445 Ross Avenue, Dallas, Texas 75202, and is available for viewing in EPA Freedom of Information Act review room on the 7th floor from 9 a.m. to 4 p.m., Monday through Friday, excluding Federal holidays. Call (214) 665–6444 for appointments. The reference number for this docket is "F–05–TXDEL–GM-Arlington.". The public may copy material from any regulatory docket at no cost for the first 100 pages and at a cost of $0.15 per page for additional copies.

FOR FURTHER INFORMATION CONTACT: Ben Banipal, Section Chief of the Corrective Action and Waste Minimization Section, Multimedia Planning and Permitting Division (6PD–C), Environmental Protection Agency Region 6, 1445 Ross Avenue, Dallas, Texas 75202. For technical information concerning this notice, contact Youngmoo Kim, Environmental Protection Agency Region 6, 1445 Ross Avenue, (6PD–C), Dallas, Texas 75202, at (214) 665–6788, or *kim.youngmoo@epa.gov.*

SUPPLEMENTARY INFORMATION: The information in this section is organized as follows:

I. Overview Information
  A. What action is EPA finalizing?
  B. Why is EPA approving this action?
  C. What are the limits of this exclusion?
  D. How will GM-Arlington manage the waste if it is delisted?
  E. When is the final delisting exclusion effective?
  F. How does this final rule affect states?
II. Background
  A. What is a delisting?
  B. What regulations allow facilities to delist a waste?
  C. What information must the generator supply?
III. EPA's Evaluation of the Waste Information and Data
  A. What waste did GM-Arlington petition EPA to delist?
  B. How much waste did GM-Arlington propose to delist?
  C. How did GM-Arlington sample and analyze the waste data in this petition?
IV. Public Comments Received on the proposed exclusion
  A. Who submitted comments on the proposed rule?
  B. What were the comments and what are EPA's responses to them?
V. Statutory and Executive Order Reviews

I. Overview Information

A. What action is EPA finalizing?

After evaluating the petition, EPA proposed, on July 19, 2005, to exclude the waste water treatment plant sludge from the lists of hazardous waste under 40 CFR 261.31 and 261.32 (see 70 FR 41358). EPA is finalizing the decision to grant GM-Arlington's delisting petition to have its waste water treatment sludge managed and disposed as non-hazardous waste provided certain verification and monitoring conditions are met.

B. Why is EPA approving this action?

GM-Arlington's petition requests a delisting from the F019 waste listing under 40 CFR 260.20 and 260.22. GM-Arlington does not believe that the petitioned waste meets the criteria for which EPA listed it. GM-Arlington also believes no additional constituents or factors could cause the waste to be hazardous. EPA's review of this petition included consideration of the original listing criteria and the additional factors required by the Hazardous and Solid Waste Amendments of 1984. See section 3001(f) of RCRA, 42 U.S.C. 6921(f), and 40 CFR 260.22 (d)(1)–(4) (hereinafter all sectional references are to 40 CFR unless otherwise indicated). In making the final delisting determination, EPA evaluated the petitioned waste against the listing criteria and factors cited in § 261.11(a)(2) and (a)(3). Based on this review, EPA agrees with the petitioner that the waste is nonhazardous with respect to the original listing criteria. If EPA had found, based on this review, that the waste remained hazardous based on the factors for which the waste as originally listed, EPA would have proposed to deny the petition. EPA evaluated the waste with respect to other factors or criteria to assess whether there is a reasonable basis to believe that such additional factors could cause the waste to be hazardous. EPA considered whether the waste is acutely toxic, the concentration of the constituents in the waste, their tendency to migrate and to bioaccumulate, their persistence in the environment once released from the waste, plausible and specific types of management of the petitioned waste, the quantities of waste generated, and waste variability. EPA believes that the petitioned waste does not meet the listing criteria and thus should not be a listed waste. EPA's final decision to delist waste from GM-Arlington's facility is based on the information submitted in support of this rule, including descriptions of the wastes and analytical data from the Arlington, Texas facility.

C. What are the limits of this exclusion?

This exclusion applies to the waste described in the petition only if the requirements described in 40 CFR Part 261, Appendix IX, Table 1 and the conditions contained herein are satisfied.

D. How will GM-Arlington manage the waste if it is delisted?

The WWTP sludge from GM-Arlington will be disposed of in a RCRA Subtitle D landfill.

E. When is the final delisting exclusion effective?

This rule is effective January 3, 2007. The Hazardous and Solid Waste Amendments of 1984 amended Section 3010 of RCRA, 42 U.S.C. 6930(b)(1), allows rules to become effective less than six months after the rule is published when the regulated community does not need the six-month period to come into compliance. That is the case here because this rule reduces, rather than increases, the existing requirements for persons generating hazardous waste. This reduction in existing requirements also provides a

basis for making this rule effective immediately, upon publication, under the Administrative Procedure Act, pursuant to 5 U.S.C. 553(d).

F. How does this final rule affect states?

Because EPA is issuing this exclusion under the Federal RCRA delisting program, only states subject to Federal RCRA delisting provisions would be affected. This would exclude states which have received authorization from EPA to make their own delisting decisions.

EPA allows states to impose their own non-RCRA regulatory requirements that are more stringent than EPA's, under section 3009 of RCRA, 42 U.S.C. 6929. These more stringent requirements may include a provision that prohibits a Federally issued exclusion from taking effect in the state. Because a dual system (that is, both Federal (RCRA) and State (non-RCRA) programs) may regulate a petitioner's waste, EPA urges petitioners to contact the State regulatory authority to establish the status of their wastes under the State law.

EPA has also authorized some states (for example, Louisiana, Oklahoma, Georgia, and Illinois) to administer a RCRA delisting program in place of the Federal program; that is, to make state delisting decisions. Therefore, this exclusion does not apply in those authorized states unless that state makes the rule part of its authorized program. If GM-Arlington transports the petitioned waste to or manages the waste in any state with delisting authorization, GM-Arlington must obtain delisting authorization from that state before it can manage the waste as nonhazardous in the state.

II. Background

A. What is a delisting petition?

A delisting petition is a request from a generator to EPA, or another agency with jurisdiction, to exclude or delist from the RCRA list of hazardous waste, certain wastes the generator believes should not be considered hazardous under RCRA.

B. What regulations allow facilities to delist a waste?

Under §§ 260.20 and 260.22, facilities may petition EPA to remove their wastes from hazardous waste regulation by excluding them from the lists of hazardous wastes contained in §§ 261.31 and 261.32. Specifically, § 260.20 allows any person to petition the Administrator to modify or revoke any provision of 40 CFR Parts 260 through 265 and 268. Section 260.22 provides generators the opportunity to petition the Administrator to exclude a waste from a particular generating facility from the hazardous waste lists.

C. What information must the generator supply?

Petitioners must provide sufficient information to EPA to allow EPA to determine that the waste to be excluded does not meet any of the criteria under which the waste was listed as a hazardous waste. In addition, the Administrator must determine, where he/she has a reasonable basis to believe that factors (including additional constituents) other than those for which the waste was listed could cause the waste to be a hazardous waste and that such factors do not warrant retaining the waste as a hazardous waste.

III. EPA's Evaluation of the Waste Information and Data

A. What waste did GM-Arlington petition EPA to delist?

On September 14, 2004, GM-Arlington petitioned EPA to exclude from the lists of hazardous wastes contained in §§ 261.31, WWTP sludge (F019) generated from its facility located in Arlington, Texas. The waste falls under the classification of listed waste pursuant to § 261.31.

B. How much waste did GM-Arlington propose to delist?

Specifically, in its petition, GM-Arlington requested that EPA grant a standard exclusion for 3,000 cubic yards per year of the WWTP sludge.

C. How did GM-Arlington sample and analyze the waste data in this petition?

To support its petition, GM-Arlington submitted:

(1) Historical information on waste generation and management practices;

(2) background information and Memorandum of Understanding for the Michigan ECOS project;

(3) analytical results from six samples for total concentrations of COCs; and

(4) analytical results from six samples for Toxicity Characteristic Leaching Procedure(TCLP) extract values.

IV. Public Comments Received on the Proposed Exclusion

A. Who submitted comments on the proposed rule?

Comments were submitted by General Motors Worldwide Facilities Group Environmental Services to correct information contained in the proposed rule and comments in support of granting the petition were submitted by the Alliance of Automobile Manufacturers.

B. What were the comments and what are EPA's responses to them?

1. Waste Disposal in Subtitle D Landfill and Other Authorized States

Comment: GM requests that EPA clarify that GM, at its discretion, has the option to dispose of the waste in any Subtitle D landfill and is not bound to use the site Waste Management landfill. GM also requests that EPA clarify that an authorized state may accept EPA's decision or make their own determinations based upon their own review process. This comment was also supported by the Alliance of Automobile Manufacturers.

Response: EPA does not limit the disposal of the F019 to a specific Subtitle D landfill. EPA states, in the exclusion language on page 41366 of the proposed rule in Table 1, (2)(B), that GM-Arlington can manage and dispose of the nonhazardous WWTP sludge according to all applicable solid waste regulations. GM provided in its petition specific reference to the Waste Management, East Oak Landfill, 3201 Mostley Road, Oklahoma City, OK 73141 as a disposal site for this waste. Since this disposal site is cited in the GM delisting petition and Oklahoma Department of Environmental Quality (ODEQ) is authorized for delisting, GM should consult with ODEQ regarding waste disposal and meet ODEQ requirements. EPA's delisting authority does not apply in Oklahoma. If GM decides to dispose the waste in another Subtitle D landfill in a state not authorized for delisting, GM must notify EPA by a letter regarding the disposal site which meets all applicable Subtitle D solid waste regulations in accordance with the notification requirements in paragraph (7) of the exclusion.

2. Acrylamide

*Comment: In Section III B. of the preamble, EPA states "Acrylamide was a major compound of concern for other nationwide GM plants' petitions * * *" GM requests that EPA qualify this statement to accurately reflect that the issues previously experienced regarding acrylamide were due to complex modeling and analytical issues and not tangible environmental issues.*

Response: Acrylamide is not a compound of concern (COC) for the waste at GM-Arlington, because it is not detected in the waste.

3. Corrections

Multiple pH Testing

Comment: EPA incorrectly states that Multiple pH testing was performed on the waste.

Response: Multiple pH is incorrectly stated in Section III C.(5) of the preamble. No multiple pH testing was performed.

Table 1 Correction

Comment: GM requests that EPA revise Table 1, Analytical Results/ Maximum Allowable Concentrations to correct an error; tetracholoethane to tetrachloroethylene.

Response: We acknowledge the typographical error of tetrachoroethylene. However, EPA does not republish supporting tables from the proposed rule. Tetrachloroethylene will not be included in Table 1 because it is a non-detected compound and is not a COC.

Comment: GM requests that EPA Region VI incorporate the same risk level used by EPA Region V for arsenic. EPA should correct the cadmium concentration to 0.36 mg/l. GM is unable to recreate the levels presented for both the inorganic and organic constituents because EPA has yet to make available to the public a current and corrected version of the DRAS model.

Response:

- The maximum TCLP concentration of arsenic is below detection limit and is not a COC for GM-Arlington's delisting exclusion.
- The delisting level for cadmium is 0.36 mg/l and has been corrected in the final exclusion language.
- EPA Region 6 used DRAS Version 2.0 to evaluate risk from disposal of the GM-Arlington wastes. The maximum concentration levels we proposed for the GM-Arlington rule are based on the delisting process. We will provide GM with this Version of the DRAS on CD. The model is run at a risk level of 1×10^{-5} and a hazard quotient of 0.1. EPA Regions 5 and 6 currently use different risk level thresholds for calculating waste concentrations, Region 6 risk assessors feel confident that using the risk level and hazard quotient in this manner provide protective results for all Region 6 petitioners.

Web Link for Accessing DRAS

Comment: The web link referenced in the preamble to access the DRAS model is incorrect. GM suggests that EPA correct this link as follows: http://www.epa.gov/region6/6pd/rcra_c/pd-o/dras/dras.htm.

Response: We acknowledge the web link: *http://www.epa.gov/region6/6pd/rcra_c/pd-o/dras/dras.htm* is incorrect. The link to the risk assessment page of the Delisting Program Webpage is sometimes broken when updates to the web page are made. The DRAS can be accessed by using the Region 6 hazardous waste delisting program page as a point of entry. That web link is currently: *http://www.epa.gov/arkansas/6pd/rcra_c/pd-o/delist.htm.* The DRAS will be associated with the "risk assessment" link.

4. Data Submittal/Changes in Operating Conditions

Comment: GM requests that EPA clarify the preamble language to match the language in condition (4) Changes in Operating Conditions, in Table 1. The condition requires EPA approval, when and if, there is a significant change in the waste that may or could result in a significant change in composition of the waste. This comment is also supported by the Alliance of Automobile Manufacturers.

Response: As stated above, we do not republish preamble language. As GM states, the language found in the exclusion language of Appendix IX to Part 261—Waste Excluded Under §§ 260.20 and 260.22. Table 1—Waste Excluded From Non-Specific Sources, explains what GM must do in cases where operating conditions change. Any changes which affect waste composition, waste volume, and toxicants' concentration levels above health-based safe criteria require notification of EPA whether it is a process or an equipment change in operation.

5. Table 1 Delisting Levels

Comment: GM requests that EPA reevaluate the list of constituents of concern identified in the proposed conditions for the delisting. GM requests that 51 chemicals be removed from the list of constituents with corresponding delisting levels. There also 5 chemicals that were detected but the TCLP results were not within 2 orders of magnitude of the DRAS exit level. GM requests that these five chemicals be removed also. This comment is also supported by the Alliance of Automobile Manufacturers.

Response: The undetected constituents will be removed from Table 1. EPA Region 6 lists all detected constituents with a corresponding delisting concentration level in its exclusions. If the concentrations ever exceed the delisting limit, they would go unmonitored because testing was not required for the verification and annual testing. The following sixteen (16) chemicals will remain in the final rule as COCs: (1) Acetone; (2) Ethyl Benzene; (3) n-Butyl Alcohol; (4) Toluene; (5) Bis(2-Ethylhexyl) Phthalate; (6) p-Cresol; (7) Naphthalene; (8) Barium; (9) Cadmium; (10) Chromium; (11) Cobalt; (12) Lead; (13) Nickel; (14) Silver; (15) Tin; and (16) Zinc.

6. Verification Testing

Comment: The verification testing requirements as described in the preamble and proposed conditions for delisting are confusing and inconsistent with other delisting conditions for similar waste streams. This comment is also supported by the Alliance of Automobile Manufacturers.

Response: Delistings are site-specific rule makings. The verification and sampling requirements for a petition will vary and be structured under consideration of the site specific conditions.

Initial Verification Sampling and Quarterly Sampling

Comment: GM believes eight samples required for the initial sampling schedule is overly rigorous and requests that EPA remove the initial sampling verification requirement. GM proposes that it will manage the waste as hazardous until it has performed verification testing of one sample analyzed for ten constituents. Provided that the delisting levels are not exceeded, then GM may manage the waste as nonhazardous. This is consistent with the delisting petition issued in Region 5 for similar facilities. GM-Arlington will be at a competitive disadvantage, if it were to have to manage its wastes differently from those included in the Region 5 petition. This comment is also supported by the Alliance of Automobile Manufacturers.

Response: Sixteen data points are necessary to perform statistical analysis on the data received. GM proposes in its comment to perform only one sample. One sample cannot be a statistical pool. EPA proposed, during the verification period, that 18 samples would be collected. The verification requirements of eight (8) initial samples, 6 samples over the next three quarters, in addition to the 6 samples initially provided was proposed so that enough data would be collected to complete statistical analysis of the data provided. The EPA has considered the comments made by GM and the requirement of eight initial samples will be reduced to two. The number of samples for the quarterly sampling will remain the same, two each quarter for the first year. EPA will not evaluate the data using a statistical approach; we will use the highest concentration of each chemical to evaluate the petition. The Verification Testing Language has been revised to represent the following: (1) Two samples taken in the first 30 days after the exclusion is issued; (2) The report

provided to EPA thirty days after the samples are taken, which is 60 days after the exclusion has been issued—Management of the waste as non-hazardous may begin after the EPA reviews and approves the data; (3) GM must then perform subsequent verification by collecting and analyzing two samples for each sampling event for the next three quarters of the first year. Quarterly reports are due to EPA within 30 days of the sampling event; and (4) After completion of the Initial and Subsequent testing and notification by letter from EPA, GM will be required to collect one sample annually, and provide EPA with the results from the annual verification test within 30 days of the sampling event.

Initial Sludge Management

Comment: GM requests that the Arlington, TX facility be allowed to manage its sludge as non-hazardous upon completion of the first successful verification sampling event.

Response: As stated above, EPA Region 6 will allow GM to manage its waste as non-hazardous if the sludge meets the delisting levels after the initial verification testing.

Retesting

Comment: GM supports the delisting conditions of Table 1, condition 2(c) which allows GM-Arlington to collect one additional sample and perform expedited analysis to verify an exceedance of a delisting level.

Response: While in such limited testing scenarios EPA does not expect a petitioned waste to fail the delisting levels, there are instances where anomalous results may be reported. EPA will allow a petitioner to retest to confirm or disprove an anomalous result.

Reduced Verification Requirements

Comment: GM supports EPA's approach to allow GM to end the quarterly sampling requirement after one year of successfully demonstrating that the waste meets the delisting levels.

Response: Annual sampling is required after one year of quarterly sampling as it states in Table 1 Condition (3)(C)(ii).

Analytical Quality Control Information

Comment: GM requests clarification as to what information will satisfy the requirement in Condition (3)(A)(iii) regarding analytical quality control information.

Response: EPA expects that analytical quality control information and the sample analysis include the data from an equipment blank, quality of distilled water or extraction solvent, duplicates for precision measurement, a spike to measure % recovery for accuracy to define the closeness of the true values of measured data.

7. Data Submittals/Certification Statement

Comment: GM requests that EPA allow GM to replace the certification language proposed with the certification language in 40 CFR 260.22(i)(12), consistent with other delisting petitions granted by EPA for similar waste streams. This comment is also supported by the Alliance of Automobile Manufacturers.

Response: The certification language included in the proposed exclusion is consistent with the language in all EPA Region 6 conditional exclusions. No change to this language will be made.

Other Comments and Changes in the EPA Proposed Rule for GM

1. Page 41360, III A. There is a typographical error "Felist". This should be "Delist".

2. Page 41360. Arsenic should be deleted from Table 1, since its concentration is below the detection limit.

3. Page 41362. The web link to access the DRAS model should be corrected.

4. Page 41362. The middle column states "Using the risk level(carcinogenic risk of 10–5 and non-cancer hazard index of 1.0) * * *" We use a hazard quotient for individual chemical is 0.1, assuming average number of chemicals on site is 10. Therefore, the wording of hazard index of 1.0 should be changed to hazard *quotient of 0.1* because we are talking about the risk level of each chemical. Hazard index means the summation of quotients from individual non-carcinogenic compounds.

5. Page 41366. For Table 1 the number of delisting sixty-six (66) constituents will be reduced to sixteen (16) chemicals by eliminating undetected chemicals.

V. Statutory and Executive Order Reviews

Under Executive Order 12866, "Regulatory Planning and Review " (58 FR 51735, October 4, 1993), this rule is not of general applicability and therefore is not a regulatory action subject to review by the Office of Management and Budget (OMB). This rule does not impose an information collection burden under the provisions of the Paperwork Reduction Act of 1995 (44 U.S.C. 3501 *et seq.*) because it applies to a particular facility only. Because this rule is of particular applicability relating to a particular facility, it is not subject to the regulatory flexibility provisions of the Regulatory Flexibility Act (5 U.S.C. 601 *et seq.*), or to sections 202, 204, and 205 of the Unfunded Mandates Reform Act of 1995 (UMRA) (Pub. L. 104–4). Because this rule will affect only a particular facility, it will not significantly or uniquely affect small governments, as specified in section 203 of UMRA. Because this rule will affect only a particular facility, this final rule does not have federalism implications. It will not have substantial direct effects on the States, on the relationship between the national government and the States, or on the distribution of power and responsibilities among the various levels of government, as specified in Executive Order 13132, "Federalism", (64 FR 43255, August 10, 1999). Thus, Executive Order 13132 does not apply to this rule. Similarly, because this rule will affect only a particular facility, this final rule does not have tribal implications, as specified in Executive Order 13175, "Consultation and Coordination with Indian Tribal Governments" (65 FR 67249, November 9, 2000). Thus, Executive Order 13175 does not apply to this rule. This rule also is not subject to Executive Order 13045, "Protection of Children from Environmental Health Risks and Safety Risks" (62 FR 19885, April 23, 1997), because it is not economically significant as defined in Executive Order 12866, and because the Agency does not have reason to believe the environmental health or safety risks addressed by this action present a disproportionate risk to children. The basis for this belief is that the Agency used the DRAS program, which considers health and safety risks to infants and children, to calculate the maximum allowable concentrations for this rule. This rule is not subject to Executive Order 13211, "Actions Concerning Regulations That Significantly Affect Energy Supply, Distribution, or Use" (66 FR 28355 (May 22, 2001)), because it is not a significant regulatory action under Executive Order 12866. This rule does not involve technical standards; thus, the requirements of section 12(d) of the National Technology Transfer and Advancement Act of 1995 (15 U.S.C. 272 note) do not apply. As required by section 3 of Executive Order 12988, "Civil Justice Reform", (61 FR 4729, February 7, 1996), in issuing this rule, EPA has taken the necessary steps to eliminate drafting errors and ambiguity, minimize potential litigation, and provide a clear legal standard for affected conduct. The Congressional

Review Act, 5 U.S.C. 801 *et seq.*, as added by the Small Business Regulatory Enforcement Fairness Act of 1996, generally provides that before a rule may take effect, the agency promulgating the rule must submit a rule report which includes a copy of the rule to each House of the Congress and to the Comptroller General of the United States. Section 804 exempts from section 801 the following types of rules: (1) Rules of particular applicability; (2) rules relating to agency management or personnel; and (3) rules of agency organization, procedure, or practice that do not substantially affect the rights or obligations of non-agency parties 5 U.S.C. 804(3). EPA is not required to submit a rule report regarding today's action under section 801 because this is a rule of particular applicability.

List of Subjects in 40 CFR Part 261

Environmental protection, Hazardous waste, Recycling, Reporting and recordkeeping requirements.

Authority: Sec. 3001(f) RCRA, 42 U.S.C. 6921(f)

Dated: December 20, 2006.

Carl E. Edlund,

Director Multimedia Planning and Permitting Division Region 6.

■ For the reasons set out in the preamble, 40 CFR part 261 is amended as follows:

PART 261—IDENTIFICATION AND LISTING OF HAZARDOUS WASTE

■ 1. The authority citation for Part 261 continues to read as follows:

Authority: 42 U.S.C. 6905, 6912(a), 6921, 6922, and 6938.

■ 2. In Table 1 of Appendix IX of Part 261 add the following waste stream in alphabetical order by facility to read as follows:

Appendix IX to Part 261—Waste Excluded Under §§ 260.20 and 260.22.

TABLE 1.—WASTE EXCLUDED FROM NON-SPECIFIC SOURCES

Facility	Address	Waste description
*	*	* * * * *
General Motors	Arlington, TX	Wastewater Treatment Sludge (WWTP) (EPA Hazardous Waste No. F019) generated at a maximum annual rate of 3,000 cubic yards per calendar year after January 3, 2007 and disposed in a Subtitle D landfill. For the exclusion to be valid, GM-Arlington must implement a verification testing program that meets the following paragraphs: (1) *Delisting Levels:* All leachable concentrations for those constituents must not exceed the following levels (mg/l for TCLP). (i) Inorganic Constituents: Barium-100; Cadmium-0.36; Chromium-5 (3.71) ; Cobalt-18.02; Lead-5; Nickel-67.8; Silver-5; Tin-540; Zinc-673. (ii) Organic Constituents: Acetone-171; Ethylbenzene-31.9; N-Butyl Alcohol-171; Toluene-45.6; Bis(2-Ethylhexyl) Phthalate-0.27; p-Cresol-8.55; Naphthalene-3.11. (2) *Waste Management:* (A) GM-Arlington must manage as hazardous all WWTP sludge generated, until it has completed initial verification testing described in paragraph (3)(A) and (B), as appropriate, and valid analyses show that paragraph(1) is satisfied. (B) Levels of constituents measured in the samples of the WWTP sludge that do not exceed the levels set forth in paragraph (1) are non-hazardous. GM-Arlington can manage and dispose of the non-hazardous WWTP sludge according to all applicable solid waste regulations. (C) If constituent levels in a sample exceed any of the delisting levels set in paragraph (1), GM-Arlington can collect one additional sample and perform expedited analyses to verify if the constituent exceeds the delisting level. If this sample confirms the exceedance, GM-Arlington must, from that point forward, treat the waste as hazardous until it is demonstrated that the waste again meets the levels in paragraph (1). GM-Arlington must manage and dispose of the waste generated under Subtitle C of RCRA from the time it becomes aware of any exceedance. (D) Upon completion of the Verification Testing described in paragraph 3(A) and (B), as appropriate, and the transmittal of the results to EPA, and if the testing results meet the requirements of paragraph (1), GM-Arlington may proceed to manage its WWTP sludge as non-hazardous waste. If subsequent Verification Testing indicates an exceedance of the Delisting Levels in paragraph (1), GM-Arlington must manage the WWTP sludge as a hazardous waste until two consecutive quarterly testing samples show levels below the Delisting Levels in paragraph (1). (3) *Verification Testing Requirements:* GM-Arlington must perform sample collection and analyses, including quality control procedures, according to appropriate methods such as those found in SW–846 or other reliable sources (with the exception of analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11, which must be used without substitution) for all constituents listed in paragraph (1). If EPA judges the process to be effective under the operating conditions used during the initial verification testing, GM-Arlington may replace the testing required in paragraph (3)(A) with the testing required in paragraph (3)(B). GM-Arlington Plant must continue to test as specified in paragraph (3)(A) until and unless notified by EPA in writing that testing in paragraph (3)(A) may be replaced by paragraph (3)(B). (A) *Initial Verification Testing:* After EPA grants the final exclusion, GM-Arlington must do the following: (i) Within 30 days of this exclusion becoming final, collect two (2) samples, before disposal, of the WWTP sludge. (ii) The samples are to be analyzed and compared against the Delisting Levels in paragraph (1). (iii) Within 60 days of the exclusion becoming final, GM-Arlington must report to EPA the initial verification analytical test data for the WWTP sludge, including analytical quality control information for the first thirty (30) days of operation after this exclusion becomes final. If levels of constituents measured in these samples of the WWTP sludge do not exceed the levels set forth in paragraph (1), GM-Arlington can manage and dispose of the WWTP sludge according to all applicable solid waste regulations.

TABLE 1.—WASTE EXCLUDED FROM NON-SPECIFIC SOURCES—Continued

Facility	Address	Waste description

(B) *Subsequent Verification Testing:* Following written notification by EPA, GM-Arlington may substitute the testing conditions in paragraph (3)(B) for paragraph (3)(A). GM-Arlington must continue to monitor operating conditions, and analyze two representative samples of the WWTP sludge for the next three quarters of operation during the first year of waste generation. The samples must represent the waste generated during the quarter. Quarterly reports are due to EPA, thirty days after the samples are taken.

After the first year of analytical sampling, verification sampling can be performed on a single annual sample of the WWTP sludge. The results are to be compared to the delisting levels in paragraph (1).

(C) *Termination of Testing:*

(i) After the first year of quarterly testing, if the delisting levels in paragraph (1) are being met, GM-Arlington may then request that EPA not require quarterly testing.

(ii) Following cancellation of the quarterly testing by EPA letter, GM-Arlington must continue to test one representative sample for all constituents listed in paragraph (1) annually. Results must be provided to EPA within 30 days of the testing.

(4) *Changes in Operating Conditions:* If GM-Arlington significantly changes the process described in its petition or starts any process that generates the waste that may or could significantly affect the composition or type of waste generated as established under paragraph (1) (by illustration, but not limitation, changes in equipment or operating conditions of the treatment process), it must notify EPA in writing; it may no longer handle the wastes generated from the new process as nonhazardous until the wastes meet the delisting levels set in paragraph (1) and it has received written approval to do so from EPA.

(5) *Data Submittals:* GM-Arlington must submit the information described below. If GM-Arlington fails to submit the required data within the specified time or maintain the required records on-site for the specified time, EPA, at its discretion, will consider this sufficient basis to reopen the exclusion as described in paragraph 6. GM-Arlington must:

(A) Submit the data obtained through paragraph(3) to the Section Chief, Region 6 Corrective Action and Waste Minimization Section, EPA, 1445 Ross Avenue, Dallas, Texas 75202–2733, Mail Code, (6PD–C) within the time specified.

(B) Compile records of operating conditions and analytical data from paragraph (3), summarized, and maintained on-site for a minimum of five years.

(C) Furnish these records and data when EPA or the State of Texas requests them for inspection.

(D) Send along with all data a signed copy of the following certification statement, to attest to the truth and accuracy of the data submitted:

"Under civil and criminal penalty of law for the making or submission of false or fraudulent statements or representations (pursuant to the applicable provisions of the Federal Code, which include, but may not be limited to, 18 U.S.C. 1001 and 42 U.S.C. 6928), I certify that the information contained in or accompanying this document is true, accurate and complete.

As to the (those) identified section(s) of this document for which I cannot personally verify its (their) truth and accuracy, I certify as the company official having supervisory responsibility for the persons who, acting under my direct instructions, made the verification that this information is true, accurate and complete.

If any of this information is determined by EPA in its sole discretion to be false, inaccurate or incomplete, and upon conveyance of this fact to the company, I recognize and agree that this exclusion of waste will be void as if it never had effect or to the extent directed by EPA and that the company will be liable for any actions taken in contravention of the company's RCRA and CERCLA obligations premised upon the company's reliance on the void exclusion."

(6) *Re-opener;*

(A) If, anytime after disposal of the delisted waste, GM-Arlington possesses or is otherwise made aware of any environmental data (including but not limited to leachate data or groundwater monitoring data) or any other data relevant to the delisted waste indicating that any constituent identified for the delisting verification testing is at a level higher than the delisting level allowed by EPA in granting the petition, then the facility must report the data, in writing, to EPA within 10 days of first possessing or being made aware of that data.

(B) If either the quarterly or annual testing of the waste does not meet the delisting requirements in paragraph 1, GM-Arlington must report the data, in writing, to EPA within 10 days of first possessing or being made aware of that data.

(C) If GM-Arlington fails to submit the information described in paragraphs (5), (6)(A) or (6)(B) or if any other information is received from any source, EPA will make a preliminary determination as to whether the reported information requires action to protect human health and/or the environment. Further action may include suspending, or revoking the exclusion, or other appropriate response necessary to protect human health and the environment.

(D) If EPA determines that the reported information requires action, EPA will notify the facility in writing of the actions it believes are necessary to protect human health and the environment. The notice shall include a statement of the proposed action and a statement providing the facility with an opportunity to present information explaining why the proposed EPA action is not necessary. The facility shall have 10 days from the date of EPA's notice to present such information.

TABLE 1.—WASTE EXCLUDED FROM NON-SPECIFIC SOURCES—Continued

Facility	Address	Waste description
		(E) Following the receipt of information from the facility described in paragraph (6)(D) or (if no information is presented under paragraph (6)(D)) the initial receipt of information described in paragraphs (5), (6)(A) or (6)(B), EPA will issue a final written determination describing the actions that are necessary to protect human health and/or the environment. Any required action described in EPA's determination shall become effective immediately, unless EPA provides otherwise. (7) *Notification Requirements:* GM-Arlington must do the following before transporting the delisted waste. Failure to provide this notification will result in a violation of the delisting petition and a possible revocation of the decision. (A) Provide a one-time written notification to any state Regulatory Agency to which or through which it will transport the delisted waste described above for disposal, 60 days before beginning such activities. (B) Update the one-time written notification if it ships the delisted waste into a different disposal facility. (C) Failure to provide this notification will result in a violation of the delisting variance and a possible revocation of the decision.
*	*	* * * * * *

[FR Doc. E6–22434 Filed 12–29–06; 8:45 am]
BILLING CODE 6560–50–P

and public procedure is impracticable, unnecessary or contrary to the public interest. This determination must be supported by a brief statement. 5 U.S.C. 808(2). As stated previously, EPA had made such a good cause finding, including the reasons therefore, and established an effective date of May 16, 2006. EPA will submit a report containing this rule and other required information to the U.S. Senate, the U.S. House of Representatives, and the Comptroller General of the United States prior to publication of the rule in the **Federal Register**. This correction to 40 CFR part 52 for Minnesota is not a "major rule" as defined by 5 U.S.C. 804(2).

List of Subjects in 40 CFR Part 52

Environmental protection, Air pollution control, Carbon monoxide, Intergovernmental relations, Lead, Nitrogen dioxide, Ozone, Particulate matter, Reporting and recordkeeping requirements, Sulfur oxides, Volatile organic compounds.

Dated: May 5, 2006.

Norman Niedergang,

Acting Regional Administrator, Region 5.

■ For the reasons stated in the preamble, part 52, title 40, chapter I of the Code of the Federal Regulations is amended as follows:

PART 52—[AMENDED]

■ 1. The authority citation for part 52 continues to read as follows:

Authority: 42 U.S.C. 7401 *et seq.*

§ 52.2587 [Redesignated]

■ 2. Section 52.2587 is redesignated as § 52.2589.

[FR Doc. 06–4551 Filed 5–15–06; 8:45 am]

BILLING CODE 6560–50–P

ENVIRONMENTAL PROTECTION AGENCY

40 CFR Part 261

[SW–FRL–8169–5]

Hazardous Waste Management System; Identification and Listing of Hazardous Waste; Final Exclusion

AGENCY: Environmental Protection Agency.

ACTION: Final rule.

SUMMARY: Environmental Protection Agency (EPA) is granting a petition submitted by Bayer Material Science LLC (Bayer) to exclude (or delist) a certain solid waste generated by its Baytown, TX plant from the lists of hazardous wastes. This final rule responds to the petition submitted by Bayer to delist K027, K104, K111, and K112 spent carbon generated from the facility's waste water treatment plant.

After careful analysis and use of the Delisting Risk Assessment Software (DRAS), EPA has concluded the petitioned waste is not hazardous waste. This exclusion applies to 7,728 cubic yards per year of the spent carbon.

DATES: *Effective Date:* May 16, 2006.

ADDRESSES: The public docket for this final rule is located at the EPA Region 6, 1445 Ross Avenue, Dallas, Texas 75202, and is available for viewing in EPA's Freedom of Information Act review room on the 7th floor from 9 a.m. to 4 p.m., Monday through Friday, excluding Federal holidays. Call (214) 665–6444 for appointments. The reference number for this docket is [R6–TXDEL–FY06–Bayer–Spent Carbon]. The public may copy material from any regulatory docket at no cost for the first 100 pages and at a cost of $0.15 per page for additional copies.

FOR FURTHER INFORMATION CONTACT: Ben Banipal, Section Chief of the Corrective Action and Waste Minimization Section, Multimedia Planning and Permitting Division (6PD–C), EPA Region 6, 1445 Ross Avenue, Dallas, Texas 75202. For technical information concerning this notice, contact Michelle Peace, EPA Region 6, 1445 Ross Avenue, (6PD–C), Dallas, Texas 75202, at (214) 665–7430, or *peace.michelle@epa.gov.*

SUPPLEMENTARY INFORMATION: The information in this section is organized as follows:

I. Overview Information
- A. What Action Is EPA Finalizing?
- B. Why Is EPA Approving This Action?
- C. What Are the Limits of This exclusion?
- D. How Will Bayer Manage the Waste, If It Is Delisted?
- E. When Is the Final Delisting Exclusion Effective?
- F. How Does this Final Rule Affect States?

II. Background
- A. What Is a Delisting?
- B. What Regulations Allow Facilities To Delist a Waste?
- C. What Information Must the Generator Supply?

III. EPA's Evaluation of the Waste Information and Data
- A. What Waste Did Bayer Petition EPA To Delist?
- B. How Much Waste Did Bayer Propose To Delist?
- C. How Did Bayer Sample and Analyze the Waste Data in This Petition?

IV. Public Comments Received on the Proposed Exclusion
- Who Submitted Comments on the Proposed Rule?

V. Statutory and Executive Order Reviews

I. Overview Information

A. What Action Is EPA Finalizing?

After evaluating the petition, EPA proposed, on February 14, 2006, to exclude the waste from the lists of hazardous waste under 40 CFR 261.31 and 261.32 (see 71 FR 7704). EPA is finalizing the decision to grant Bayer's delisting petition to have its spent carbon generated from treating waste waters at the plant subject to certain continued verification and monitoring conditions.

B. Why Is EPA Approving This Action?

Bayer's petition requests a delisting from the K027, K104, K111, and K112, waste listings under 40 CFR 260.20 and 260.22. Bayer does not believe that the petitioned waste meets the criteria for which EPA listed it. Bayer also believes no additional constituents or factors could cause the waste to be hazardous. EPA's review of this petition included consideration of the original listing criteria and the additional factors required by the Hazardous and Solid Waste Amendments of 1984. See section 3001(f) of RCRA, 42 U.S.C. 6921(f), and 40 CFR 260.22(d)(1)–(4) (hereinafter all sectional references are to 40 CFR unless otherwise indicated). In making the final delisting determination, EPA evaluated the petitioned waste against the listing criteria and factors cited in § 261.11(a)(2) and (a)(3). Based on this review, EPA agrees with the petitioner that the waste is nonhazardous with respect to the original listing criteria. If EPA had found, based on this review, that the waste remained hazardous based on the factors for which the waste was originally listed, EPA would have proposed to deny the petition. EPA evaluated the waste with respect to other factors or criteria to assess whether there is a reasonable basis to believe that such additional factors could cause the waste to be hazardous. EPA considered whether the waste is acutely toxic, the concentration of the constituents in the waste, their tendency to migrate and to bioaccumulate, their persistence in the environment once released from the waste, plausible and specific types of management of the petitioned waste, the quantities of waste generated, and waste variability. EPA believes that the petitioned waste does not meet the listing criteria and thus should not be a listed waste. EPA's final decision to delist waste from Bayer's facility is based on the information submitted in support of this rule, including descriptions of the wastes and analytical data from the Baytown, TX facility.

C. What Are the Limits of This Exclusion?

This exclusion applies to the waste described in the petition only if the requirements described in 40 CFR part 261, appendix IX, Table 2 and the conditions contained herein are satisfied.

D. How Will Bayer Manage the Waste, If It Is Delisted?

Bayer will dispose of the spent carbon in a Subtitle D landfill.

E. When Is the Final Delisting Exclusion Effective?

This rule is effective May 16, 2006. The Hazardous and Solid Waste Amendments of 1984 amended section 3010 of RCRA, 42 U.S.C. 6930(b)(1), allows rules to become effective less than six months after the rule is published when the regulated community does not need the six-month period to come into compliance. That is the case here because this rule reduces, rather than increases, the existing requirements for persons generating hazardous waste. This reduction in existing requirements also provides a basis for making this rule effective immediately, upon publication, under the Administrative Procedure Act, pursuant to 5 U.S.C. 553(d).

F. How Does This Final Rule Affect States?

Because EPA is issuing this exclusion under the Federal RCRA delisting program, only states subject to Federal RCRA delisting provisions would be affected. This would exclude states which have received authorization from EPA to make their own delisting decisions.

EPA allows states to impose their own non-RCRA regulatory requirements that are more stringent than EPA's requirements, under section 3009 of RCRA, 42 U.S.C. 6929. These more stringent requirements may include a provision that prohibits a Federally issued exclusion from taking effect in the state. Because a dual system (that is, both Federal (RCRA) and State (non-RCRA) programs) may regulate a petitioner's waste, EPA urges petitioners to contact the State regulatory authority to establish the status of their wastes under the State law.

EPA has also authorized some states (for example, Louisiana, Oklahoma, Georgia, and Illinois) to administer a RCRA delisting program in place of the Federal program; that is, to make state delisting decisions. Therefore, this exclusion does not apply in those authorized states unless that state makes the rule part of its authorized program. If Bayer transports the petitioned waste to or manages the waste in any state with delisting authorization, Bayer must obtain delisting authorization from that state before it can manage the waste as nonhazardous in the state.

II. Background

A. What Is a Delisting Petition?

A delisting petition is a request from a generator to EPA, or another agency with jurisdiction, to exclude or delist from the RCRA list of hazardous waste, certain wastes the generator believes should not be considered hazardous under RCRA.

B. What Regulations Allow Facilities To Delist a Waste?

Under §§ 260.20 and 260.22, facilities may petition EPA to remove their wastes from hazardous waste regulation by excluding them from the lists of hazardous wastes contained in §§ 261.31 and 261.32. Specifically, § 260.20 allows any person to petition the Administrator to modify or revoke any provision of 40 CFR parts 260 through 265 and 268. Section 260.22 provides generators the opportunity to petition the Administrator to exclude a waste from a particular generating facility from the hazardous waste lists.

C. What Information Must the Generator Supply?

Petitioners must provide sufficient information to EPA to allow EPA to determine that the waste to be excluded does not meet any of the criteria under which the waste was listed as a hazardous waste. In addition, the Administrator or his delegate must determine, where he/she has a reasonable basis to believe that factors (including additional constituents) other than those for which the waste was listed could cause the waste to be a hazardous waste and that such factors do not warrant retaining the waste as a hazardous waste.

III. EPA's Evaluation of the Waste Information and Data

A. What Waste Did Bayer Petition EPA to Delist?

On September 26, 2003, Bayer petitioned EPA to exclude from the lists of hazardous waste contained in § 261.32, spent carbon generated from its facility located in Baytown, Texas. The waste falls under the classification of a listed waste under § 261.30.

B. How Much Waste Did Bayer Propose to Delist?

Specifically, in its petition, Bayer requested that EPA grant a conditional exclusion for 7,728 cubic yards per year of the spent carbon.

C. How Did Bayer Sample and Analyze the Waste Data in This Petition?

To support its petition, Bayer submitted:

(1) Analytical results of the toxicity characteristic leaching procedure (TCLP) and total constituent analysis for volatile and semivolatile organics, pesticides, herbicides, dioxins/furans, PCBs and metals for six spent carbon samples;

(2) Analytical results from multiple pH leaching of metals; and

(3) Descriptions of the waste water treatment process and carbon regeneration process.

IV. Public Comments Received on the Proposed Exclusion

Who Submitted Comments on the Proposed Rule?

There were no comments submitted on the proposed rule.

V. Statutory and Executive Order Reviews

Under Executive Order 12866, "Regulatory Planning and Review " (58 FR 51735, October 4, 1993), this rule is not of general applicability and therefore is not a regulatory action subject to review by the Office of Management and Budget (OMB). This rule does not impose an information collection burden under the provisions of the Paperwork Reduction Act of 1995 (44 U.S.C. 3501 *et seq.*) because it applies to a particular facility only. Because this rule is of particular applicability relating to a particular facility, it is not subject to the regulatory flexibility provisions of the Regulatory Flexibility Act (5 U.S.C. 601 *et seq.*), or to sections 202, 204, and 205 of the Unfunded Mandates Reform Act of 1995 (UMRA) (Pub. L. 104–4). Because this rule will affect only a particular facility, it will not significantly or uniquely affect small governments, as specified in section 203 of UMRA. Because this rule will affect only a particular facility, this final rule does not have federalism implications. It will not have substantial direct effects on the States, on the relationship between the national government and the States, or on the distribution of power and responsibilities among the various levels of government, as specified in Executive Order 13132, "Federalism" (64 FR 43255, August 10, 1999). Thus, Executive Order 13132 does not apply to this rule. Similarly, because this rule will affect only a particular facility, this final rule does not have tribal

implications, as specified in Executive Order 13175, "Consultation and Coordination with Indian Tribal Governments" (65 FR 67249, November 9, 2000). Thus, Executive Order 13175 does not apply to this rule. This rule also is not subject to Executive Order 13045, "Protection of Children from Environmental Health Risks and Safety Risks" (62 FR 19885, April 23, 1997), because it is not economically significant as defined in Executive Order 12866, and because the Agency does not have reason to believe the environmental health or safety risks addressed by this action present a disproportionate risk to children. The basis for this belief is that the Agency used the DRAS program, which considers health and safety risks to infants and children, to calculate the maximum allowable concentrations for this rule. This rule is not subject to Executive Order 13211, "Actions Concerning Regulations That Significantly Affect Energy Supply, Distribution, or Use" (66 FR 28355 (May 22, 2001)), because it is not a significant regulatory action under Executive Order 12866. This rule does not involve technical standards; thus, the requirements of section 12(d) of the National Technology Transfer and Advancement Act of 1995 (15 U.S.C. 272 note) do not apply. As required by section 3 of Executive Order 12988, "Civil Justice Reform", (61 FR 4729, February 7, 1996), in issuing this rule, EPA has taken the necessary steps to eliminate drafting errors and ambiguity, minimize potential litigation, and provide a clear legal standard for affected conduct. The Congressional Review Act, 5 U.S.C. 801 *et seq.*, as added by the Small Business Regulatory Enforcement Fairness Act of 1996, generally provides that before a rule may take effect, the agency promulgating the rule must submit a rule report which includes a copy of the rule to each House of the Congress and to the Comptroller General of the United States. Section 804 exempts from section 801 the following types of rules: (1) Rules of particular applicability; (2) rules relating to agency management or personnel; and (3) rules of agency organization, procedure, or practice that do not substantially affect the rights or obligations of non-agency parties, 5 U.S.C. 804(3). EPA is not required to submit a rule report regarding today's action under section 801 because this is a rule of particular applicability.

List of Subjects in 40 CFR Part 261

Environmental protection, Hazardous waste, Recycling, Reporting and recordkeeping requirements.

Dated: May 3, 2006.

Carl E. Edlund,

P.E., Director, Multimedia Planning and Permitting Division, Region 6.

■ For the reasons set out in the preamble, 40 CFR part 261 is to be amended as follows:

PART 261—IDENTIFICATION AND LISTING OF HAZARDOUS WASTE

■ 1. The authority citation for part 261 continues to read as follows:

Authority: 42 U.S.C. 6905, 6912(a), 6921, 6922, and 6938.

■ 2. In Table 2 of Appendix IX of part 261 add the following waste stream in alphabetical order by facility to read as follows:

Appendix IX to Part 261—Waste Excluded Under §§ 260.20 and 260.22

TABLE 2.—WASTE EXCLUDED FROM SPECIFIC SOURCES

Facility	Address	Waste description
*	*	* * * * *
Bayer Material Science LLC ...	Baytown, TX ...	Spent Carbon (EPA Hazardous Waste Nos. K027, K104, K111, and K112) generated at a maximum rate of 7,728 cubic yards per calendar year after May 16, 2006. For the exclusion to be valid, Bayer must implement a verification testing program that meets the following Paragraphs: (1) Delisting Levels: All concentrations for those constituents must not exceed the maximum allowable concentrations in mg/l specified in this paragraph. Spent Carbon Leachable Concentrations (mg/l): Antimony–0.251; Arsenic–0.385, Barium–8.93; Beryllium–0.953; Cadmium–0.687; Chromium–5.0; Cobalt–2.75; Copper–128.0; Cyanide–1.65; Lead–5.0; Mercury–0.0294; Nickel–3.45; Selenium–0.266; Tin–2.75; Vanadium–2.58; Zinc–34.2; Aldrin–0.0000482; Acetophenone–87.1; Aniline–2.82; Benzene–0.554; Bis(2-ethylhexyl)phthalate–0.342; Benzyl alcohol–261; Butylbenzylphthalate–3.54; Chloroform–0.297; Di-n-octyl phthalate–0.00427; 2,4-Dinitrotoluene–0.0249; 2,6-Dinitrotoluene–0.0249 Diphenylamine–1.43; 1,4-Dioxane–14.6; Di-n-butylphthalate–2.02; Kepone–0.000373; 2-Nitrophenol–87.9; N-Nitrodiphenylamine–3.28; Phenol–52.2; 2,4-Toluenediamine–0.00502; Toluene diisocyanate–0.001. (2) Waste Holding and Handling: (A) Waste classification as non-hazardous can not begin until compliance with the limits set in paragraph (1) for spent carbon has occurred for two consecutive quarterly sampling events and the reports have been approved by EPA. (B) If constituent levels in any sample taken by Bayer exceed any of the delisting levels set in paragraph (1) for the spent carbon, Bayer must do the following: (i) notify EPA in accordance with paragraph (6) and (ii) manage and dispose the spent carbon as hazardous waste generated under Subtitle C of RCRA. (3) Testing Requirements: Upon this exclusion becoming final, Bayer must perform quarterly analytical testing by sampling and analyzing the spent carbon as follows: (A) Quarterly Testing: (i) Collect two representative composite samples of the spent carbon at quarterly intervals after EPA grants the final exclusion. The first composite samples may be taken at any time after EPA grants the final approval. Sampling should be performed in accordance with the sampling plan approved by EPA in support of the exclusion.

TABLE 2.—WASTE EXCLUDED FROM SPECIFIC SOURCES—Continued

Facility	Address	Waste description
		(ii) Analyze the samples for all constituents listed in paragraph (1). Any composite sample taken that exceeds the delisting levels listed in paragraph (1) for the spent carbon must be disposed as hazardous waste in accordance with the applicable hazardous waste requirements. (iii) Within thirty (30) days after taking its first quarterly sample, Bayer will report its first quarterly analytical test data to EPA. If levels of constituents measured in the samples of the spent carbon do not exceed the levels set forth in paragraph (1) of this exclusion for two consecutive quarters, Bayer can manage and dispose the non-hazardous spent carbon according to all applicable solid waste regulations. (B) Annual Testing: (i) If Bayer completes the quarterly testing specified in paragraph (3) above and no sample contains a constituent at a level which exceeds the limits set forth in paragraph (1), Bayer can begin annual testing as follows: Bayer must test two representative composite samples of the spent carbon for all constituents listed in paragraph (1) at least once per calendar year. (ii) The samples for the annual testing shall be a representative composite sample according to appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. Methods must meet Performance Based Measurement System Criteria in which the Data Quality Objectives are to demonstrate that samples of the Bayer spent carbon are representative for all constituents listed in paragraph (1). (iii) The samples for the annual testing taken for the second and subsequent annual testing events shall be taken within the same calendar month as the first annual sample taken. (iv) The annual testing report must include the total amount of waste in cubic yards disposed during the calendar year. (4) Changes in Operating Conditions: If Bayer significantly changes the process described in its petition or starts any process that generates the waste that may or could affect the composition or type of waste generated (by illustration, but not limitation, changes in equipment or operating conditions of the treatment process), it must notify EPA in writing and it may no longer handle the wastes generated from the new process as non-hazardous until the wastes meet the delisting levels set in paragraph (1) and it has received written approval to do so from EPA. Bayer must submit a modification to the petition complete with full sampling and analysis for circumstances where the waste volume changes and/or additional waste codes are added to the waste stream. (5) Data Submittals: Bayer must submit the information described below. If Bayer fails to submit the required data within the specified time or maintain the required records on-site for the specified time, EPA, at its discretion, will consider this sufficient basis to reopen the exclusion as described in paragraph (6). Bayer must: (A) Submit the data obtained through paragraph 3 to the Chief, Corrective Action and Waste Minimization Section, Multimedia Planning and Permitting Division, U. S. Environmental Protection Agency Region 6, 1445 Ross Ave., Dallas, Texas, 75202, within the time specified. All supporting data can be submitted on CD–ROM or some comparable electronic media. (B) Compile records of analytical data from paragraph (3), summarized, and maintained on-site for a minimum of five years. (C) Furnish these records and data when either EPA or the State of Texas requests them for inspection. (D) Send along with all data a signed copy of the following certification statement, to attest to the truth and accuracy of the data submitted: "Under civil and criminal penalty of law for the making or submission of false or fraudulent statements or representations (pursuant to the applicable provisions of the Federal Code, which include, but may not be limited to, 18 U.S.C. 1001 and 42 U.S.C. 6928), I certify that the information contained in or accompanying this document is true, accurate and complete. As to the (those) identified section(s) of this document for which I cannot personally verify its (their) truth and accuracy, I certify as the company official having supervisory responsibility for the persons who, acting under my direct instructions, made the verification that this information is true, accurate and complete. If any of this information is determined by EPA in its sole discretion to be false, inaccurate or incomplete, and upon conveyance of this fact to the company, I recognize and agree that this exclusion of waste will be void as if it never had effect or to the extent directed by EPA and that the company will be liable for any actions taken in contravention of the company's RCRA and CERCLA obligations premised upon the company's reliance on the void exclusion." (6) Reopener:

TABLE 2.—WASTE EXCLUDED FROM SPECIFIC SOURCES—Continued

Facility	Address	Waste description
		(A) If, anytime after disposal of the delisted waste Bayer possesses or is otherwise made aware of any environmental data (including but not limited to leachate data or ground water monitoring data) or any other data relevant to the delisted waste indicating that any constituent identified for the delisting verification testing is at a level higher than the delisting level allowed by EPA in granting the petition, then the facility must report the data, in writing, to EPA within 10 days of first possessing or being made aware of that data. (B) If either the quarterly or annual testing of the waste does not meet the delisting requirements in paragraph 1, Bayer must report the data, in writing, to EPA within 10 days of first possessing or being made aware of that data. (C) If Bayer fails to submit the information described in paragraphs (5),(6)(A) or (6)(B) or if any other information is received from any source, EPA will make a preliminary determination as to whether the reported information requires action to protect human health and/or the environment. Further action may include suspending, or revoking the exclusion, or other appropriate response necessary to protect human health and the environment. (D) If EPA determines that the reported information requires action, EPA will notify the facility in writing of the actions it believes are necessary to protect human health and the environment. The notice shall include a statement of the proposed action and a statement providing the facility with an opportunity to present information explaining why the proposed EPA action is not necessary. The facility shall have 10 days from the date of EPA's notice to present such information. (E) Following the receipt of information from the facility described in paragraph (6)(D) or (if no information is presented under paragraph (6)(D)) the initial receipt of information described in paragraphs (5), (6)(A) or (6)(B), EPA will issue a final written determination describing the actions that are necessary to protect human health and/or the environment. Any required action described in EPA's determination shall become effective immediately, unless EPA provides otherwise.

* * * * * * *

[FR Doc. 06–4514 Filed 5–15–06; 8:45 am]
BILLING CODE 6560–50–P

DEPARTMENT OF TRANSPORTATION

National Highway Traffic Safety Administration

49 CFR Part 578

[Docket No. NHTSA–05–24109; Notice 2]

RIN 2127–AJ83

Civil Penalties

AGENCY: National Highway Traffic Safety Administration (NHTSA), DOT.

ACTION: Final rule.

SUMMARY: This document amends NHTSA's regulation on civil penalties by increasing the maximum civil penalties for violations of the National Traffic and Motor Vehicle Safety Act, as amended (Vehicle Safety Act). This action is taken pursuant to the Federal Civil Monetary Penalty Inflation Adjustment Act of 1990, as amended by the Debt Collection Improvement Act of 1996, which requires NHTSA to review and, as warranted, adjust penalties based on inflation at least every four years. In addition, this document codifies amendments to the penalty provisions of the Vehicle Safety Act by the Safe, Accountable, Flexible, Efficient Transportation Equity Act—A Legacy for Users (SAFETEA–LU) and makes a technical correction to the text of the agency's penalty regulation.

DATES: This rule is effective on June 15, 2006.

FOR FURTHER INFORMATION CONTACT: Michael Kido, Office of Chief Counsel, NHTSA, telephone (202) 366–5263, facsimile (202) 366–3820, 400 Seventh Street, SW., Washington, DC 20590.

SUPPLEMENTARY INFORMATION: This rule amends NHTSA's regulations on civil penalties under the Vehicle Safety Act, 49 U.S.C. Chapter 301. As explained below, it makes four changes to 49 CFR Part 578 *Civil and Criminal Penalties.* These changes were proposed and explained in our March 9, 2006 Notice of Proposed Rulemaking ("NPRM") at 71 FR 12156. There were no comments on that notice.

First, this rule adjusts for inflation the maximum available penalties codified at 49 CFR 578.6(a). In order to preserve the remedial impact of civil penalties and to foster compliance with the law, the Federal Civil Monetary Penalty Inflation Adjustment Act of 1990 (28 U.S.C. 2461 Notes, Pub. L. 101–410), as amended by the Debt Collection Improvement Act of 1996, (Pub. L. 104–134) (referred to collectively as the "Adjustment Act" or, in context, the "Act"), requires us and other Federal agencies to regularly adjust civil penalties for inflation. Under the Adjustment Act, following an initial adjustment that was capped by the Act, these agencies must make further adjustments, as warranted, to the amounts of penalties in statutes they administer at least once every four years.

NHTSA is adjusting the maximum penalty for a single violation of the Vehicle Safety Act. The agency last published a rule stating the maximum civil penalty for a single violation or a single violation per day under 49 U.S.C. Chapter 301 on November 14, 2000, 65 FR 68108. This rule incorporated amendments to 49 U.S.C. 30165(a) in the Transportation Recall Enhancement, Accountability, and Documentation (TREAD) Act. Pub. L. 106–414, 114 Stat. 1800. In the TREAD Act, Congress set the maximum penalty for a single violation of the Vehicle Safety Act or a regulation thereunder at $5,000. The TREAD Act also set the maximum penalty for a violation of 49 U.S.C. 30166 or a regulation thereunder at $5,000 per violation per day. The agency codified these amounts at 49 CFR 578.6(a)(1) and (a)(2), respectively. In today's rule, NHTSA is adjusting these amounts from $5,000 to $6,000 based on the Adjustment Act, for the reasons set forth in the NPRM.

Additionally, the agency is adjusting the maximum penalty amounts for a related series of violations of the Vehicle Safety Act or a regulation thereunder and for a related series of

Federal Register

Tuesday,
June 14, 2005

Part II

Environmental Protection Agency

40 CFR Parts 63, 268, et al.
Waste Management System; Testing and Monitoring Activities; Final Rule: Methods Innovation Rule and SW–846 Final Update IIIB; Final Rule

ENVIRONMENTAL PROTECTION AGENCY

40 CFR Parts 63, 258, 260, 261, 264, 265, 266, 268, 270, 271, and 279

[RCRA–2002–0025; FRL–7916–1]

RIN 2050–AE41

Waste Management System; Testing and Monitoring Activities; Final Rule: Methods Innovation Rule and SW–846 Final Update IIIB

AGENCY: Environmental Protection Agency (EPA).

ACTION: Final rule.

SUMMARY: The Environmental Protection Agency is amending a variety of testing and monitoring requirements in the Resource Conservation and Recovery Act (RCRA) hazardous and non-hazardous solid waste regulations and for certain Clean Air Act (CAA) regulations that relate to hazardous waste combustors. These amendments allow more flexibility when conducting RCRA-related sampling and analysis by removing from the regulations a requirement to use the methods found in "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods," also known as "SW–846," in conducting various testing and monitoring and by limiting required uses of an SW–846 method to circumstances where the method is the only one capable of measuring the particular property (*i.e.*, the method is used to measure a required method-defined parameter). This action is an important step forward in implementing the use of a performance-based approach, which is part of the Agency's efforts toward Innovating for Better Environmental Results. Additionally, the Agency is making certain other clarifications and technical amendments. These changes should make it easier and more cost effective to comply with the affected regulations, without compromising human health or environmental protection.

DATES: This final rule is effective on July 14, 2005. The incorporation by reference of certain publications listed in the rule is approved by the Director of the Federal Register as of July 14, 2005.

ADDRESSES: EPA has established a docket for this action under Docket ID No. RCRA–2002–0025. All documents in the docket are listed in the EDOCKET index at *http://www.epa.gov/edocket*. Although listed in the index, some information is not publicly available, *i.e.*, CBI or other information for which disclosure is restricted by statute. Certain other material, such as copyrighted material, is not placed on the Internet and will be publicly available only in hard copy form. Publicly available docket materials are available either electronically in EDOCKET or in hard copy at the OSWER RCRA Docket, EPA/DC, EPA West, Room B102, 1301 Constitution Ave., NW., Washington, DC. The Public Reading Room is open from 8:30 a.m. to 4:30 p.m., Monday through Friday, excluding legal holidays. The telephone number for the Public Reading Room is (202) 566–1744. This Docket Facility is open from 8:30 a.m. to 4:30 p.m., Monday through Friday, excluding legal holidays. The Docket telephone number is (202) 566–0270.

FOR FURTHER INFORMATION CONTACT: For information on this rulemaking, contact Kim Kirkland at: Office of Solid Waste (5307W), U. S. Environmental Protection Agency, 1200 Pennsylvania Avenue, SW., Washington, DC 20460–0002, (703) 308–8855, e-mail address: *kirkland.kim@epa.gov*.

SUPPLEMENTARY INFORMATION:

I. General Information

A. Does This Action Apply to Me?

You may be covered by this action if you conduct waste sampling and analysis for Resource Conservation and Recovery Act (RCRA)-or National Emission Standards for Hazardous Air Pollutants (NESHAP)-related activities. Covered entities include anyone who generates, treats, stores, or disposes of hazardous or nonhazardous solid waste and is subject to RCRA subtitle C or D sampling and analysis requirements; and entities subject to NESHAP final standards for hazardous waste combustors (40 CFR part 63, subpart EEE). All types of industries, governments, and organizations may have entities that generate or manage RCRA-regulated hazardous and nonhazardous solid wastes and may be subject to RCRA-related sampling and analysis requirements.

To determine whether your facility, company, business organization, etc., is covered by this action, you should carefully examine the applicability criteria in part 63 and in parts 258 through 299 of the Code of Federal Regulations. If you have questions regarding the applicability of this action to a particular entity, consult your regulatory authority.

B. How Do I Obtain Copies of SW–846?

The Third Edition of SW–846, as amended by Final Updates I, II, IIA, IIB, III, IIIA, and IIIB will be available in pdf format on the Internet at *http://www.epa.gov/SW–846*. A paper copy of Final Update IIIB is also located in the docket for this rule (see section I.A above). Table 1 below provides sources for both paper and electronic copies of the Third Edition of SW–846 and all of its updates.

TABLE 1.—SOURCES FOR SW–846, THIRD EDITION, AND ITS UPDATES

Source	Available portions of SW–846
Superintendent of Documents, U.S. Government Printing Office (GPO), Washington, DC 20402, phone (202) 512–1800, toll free (866) 512–1800, fax orders (202) 512–2250, and online: *http://bookstore.gpo.gov*.	—Paper copies of the SW–846, Third Edition, basic manual and of certain updates, including Final Updates, I, II, IIA, IIB, III, and IIIB and Draft Update IVA. The subscriber must integrate the updates.
National Technical Information Service (NTIS), 5285 Port Royal Road, Springfield, VA 22161, (703) 605–6000 or (800) 553–6847.	—Paper copy of an integrated version of SW–846, Third Edition, as amended by Final Updates, I, II, IIA, IIB, III, and IIIA. —Individual paper copies of the SW–846, Third Edition, basic manual and of certain updates, including Final Updates I, II, IIA, IIB, III, IIIA, and IIIB and Draft Updates IVA and IVB. —CD-ROM of integrated version of SW-846, Third Edition, as amended by Final Updates I, II, IIA, IIB, and III (pdf and WordPerfect electronic copies). —CD-ROM of Draft Update IVA (pdf and WordPerfect electronic copies).
Internet: *http://www.epa.gov/SW-846*	—Integrated version of SW-846, Third Edition, as amended by Final Updates I, II, IIA, IIB, III, IIIA, and IIB (pdf electronic copy). —Draft Update IVA (pdf electronic copy). —Draft Update IVB (pdf electronic copy).

C. What Is the Legal Authority for This Action?

We are promulgating the part 258, 260, 261, 264–266, 268, 270, 271, and 279 regulations under the authority of sections 1006, 2002(a), 3001–3007, 3010, 3013–3018, and 7004 of the Solid Waste Disposal Act, as amended by the Resource Conservation and Recovery Act of 1976, as amended. We are promulgating the part 63 regulation under the authority of sections 112 and 114 of the Clean Air Act.

D. How Is the Rest of This Preamble Organized?

II. Summary of Today's Rule
III. Background and Purpose of Action To Reform RCRA-Related Testing and Monitoring
A. Public Comments Regarding How to Determine if a Method Is Appropriate
B. Public Comments Regarding Other Approaches
C. Public Comments Regarding Impacts From Removal of Required Uses of SW–846 Methods
IV. Regulatory Revisions Involving Removal of SW–846 Requirements
V. Editorial Corrections to SW–846 References in the RCRA Testing and Monitoring Regulations
VI. Action to Withdraw the Reactivity Interim Guidance from SW–846 Chapter Seven and Remove Required SW–846 Reactivity Analyses and Threshold Levels from Conditional Delistings
VII. Clarifications to Corrosivity and Ignitability Hazardous Waste Characteristics
A. Revision to § 261.22(a)(2) to Clarify that SW–846 Method 1110A Is the SW–846 Standardized Version of the NACE Standard Specified for Corrosivity Characteristic Testing
B. Revisions to § 261.21(a)(1) to Remove an Unnecessary Referral to Method Equivalency Petitions; and an Explanation regarding the Decision to Not Revise the Regulation to Include the Updated ASTM Standards and References to Methods 1010A and 1020B as Proposed
VIII. Availability of Final Update IIIB and Status of Final Update IV to SW–846
IX. Addition of Method 25A to §§ 264.1034(c)(1)(ii) and (iv) and 265.1034(c)(1)(ii) and (iv)
X. Removal of Requirements from § 63.1208(b)(8)(i) and (ii) in the NESHAP Standards to Demonstrate Feedstream Analytes Are Not Present at Certain Levels
XI. Status of the RCRA Waste Sampling Draft Technical Guidance
XII. State Authorization Procedures
A. Applicability of Federal Rules in Authorized States
B. Authorization of States for Today's Rule
C. Abbreviated Authorization Procedures
XIII. Statutory and Executive Order Reviews
A. Executive Order 12866: Regulatory Planning and Review
B. Paperwork Reduction Act
C. Regulatory Flexibility Act
D. Unfunded Mandates Reform Act
E. Executive Order 13132: Federalism
F. Executive Order 13175: Consultation and Coordination With Indian Tribal Governments
G. Executive Order 13045: Protection of Children From Environmental Health Risks and Safety Risks
H. Executive Order 13211: Actions That Significantly Affect Energy Supply, Distribution, or Use
I. National Technology Transfer and Advancement Act
J. Executive Order 12898: Federal Actions to Address Environmental Justice in Minority Populations and Low-Income Populations
K. Congressional Review Act

II. Summary of Today's Rule

On October 30, 2002 (67 FR 66251–66301), the Environmental Protection Agency (EPA) proposed to amend the testing and monitoring requirements under the hazardous and nonhazardous solid waste regulations, and a testing requirement under the Clean Air Act (CAA) in the National Emission Standards for Hazardous Air Pollutants (NESHAP) for hazardous waste combustors. EPA is finalizing those regulatory revisions at this time. Some of the public comments are summarized and addressed in the sections to follow, and a background document containing our responses to all public comments can be found in the docket to this rule, RCRA–2002–0025. After consideration of all comments and for the reasons summarized in today's rule, we are finalizing the following actions:

1. Reforming RCRA-related testing and monitoring by restricting requirements to use SW–846 to only those situations where the method is the only one capable of measuring the property (*i.e.*, it is used to measure a method-defined parameter). This will allow more flexibility in RCRA-related sampling and analysis by removing unnecessary required uses of SW–846.

2. Withdrawing the cyanide and sulfide reactivity guidance from sections 7.3.3 and 7.3.4 of SW–846 Chapter Seven and withdrawing required uses of reactive cyanide and sulfide methods and threshold levels from conditional delistings.

3. Amending the regulations for the ignitability and corrosivity hazardous waste characteristics. As part of this, we are clarifying in § 261.22(a)(2) that SW–846 Method 1110A, "Corrosivity Toward Steel," is the "standardized" (as described in § 261.22(a)(2)) SW–846 method that is required to be used to determine the characteristic of corrosivity for steel. We are also removing the unnecessary reference to equivalency petitions in the ignitability characteristic at § 261.21(a)(1). However, regarding the methods required for the determination of flash point under the characteristic of ignitability, the Agency decided not to replace the standard test methods ASTM D 3278–78 and D 93–79 with the latest versions of those methods.

4. Incorporating by reference Update IIIB to SW–846, which includes the revised Chapter Seven, and eleven revised methods, including method revisions to remove a requirement to use the SW–846 Chapter Nine, "Sampling Plan."

5. Adding Method 25A as an analytical option to analyses conducted in support of air emission standards for process vents and/or equipment leaks at treatment, storage, and disposal facilities.

6. Removing a requirement to demonstrate that feedstream analytes are not present at levels above the 80% upper confidence limit above the mean for sources subject to NESHAP: Final Standards for Hazardous Waste Combustors.

7. Removing from the regulations unnecessary references to SW–846, which do not affect the intent of the RCRA regulation.

This rule does not add any additional requirements to the regulations. Instead, this rule removes the requirement to use SW–846, and it clarifies what the Agency believes should be considered during the selection of other appropriate methods. Our purpose for the regulatory revisions is to make it easier and more cost effective to comply with the RCRA regulations by allowing more flexibility in method selection and use. If you prefer, where you find that a specific SW–846 method yields data that is suitably effective for demonstrating compliance in the particular matrix being analyzed, you can still use the SW–846 methods.

III. Background and Purpose of Action to Reform RCRA-Related Testing and Monitoring

Typically, the hazardous and nonhazardous solid waste RCRA regulations for testing and monitoring activities or the permits or waste analysis plans of facilities regulated by RCRA specify the analytes of concern to be determined in a matrix of concern at a particular regulatory level of concern. Additionally, some recently promulgated regulations specify the confidence level of concern. Most of the RCRA regulations leave the how (*i.e.*, which test method to use) up to the regulated community. Some RCRA regulations, however, specify the use of methods from the EPA publication

"Test Methods for Evaluating Solid Waste, Physical/Chemical Methods," also known as "SW–846."

Initially, EPA issued SW–846 in 1980 soon after the first RCRA regulations were published. At that time, we intended that SW–846 serve two roles. First, the Agency intended that it serve as a guidance manual of generally appropriate and reliable analytical methods for RCRA-related testing and monitoring. Second, we intended that it serve as a readily-available source of those few analytical methods which were required in order to comply with the RCRA regulations. Since that time, EPA published regulations that required the use of SW–846 methods in general. Subsequently, members of the regulated public made it clear to EPA that they would like the opportunity to use other reliable methods, and EPA also decided that some of the SW–846 requirements were not necessary.

The regulatory requirement to use SW–846 in general (e.g., as in the delisting regulations at § 260.22 prior to this final rule) did not identify specific SW–846 methods. Rather, this requirement typically included the regulation of many different analytes which could be determined by many different methods. Almost every update to SW–846 includes at least one method that may be applicable to one or more of these general analytical requirements. Therefore, whenever SW–846 was updated to revise or add methods, EPA had to incorporate by reference all of the new and revised methods into the RCRA regulations as part of a rulemaking. EPA issued the updates as a proposed rule, requested public comment, and then promulgated the update in a final rule. This lengthy process delayed the timely use of the new analytical technologies.

On October 30, 2002 (67 FR 66251–66301), EPA proposed to remove from the regulations a requirement to use a method found in SW–846, except when that method is the only one capable of measuring the particular property. At that time, we described our reasons for wanting to remove this requirement from the regulations, including the Agency's desire to fully implement a performance-based measurement system (PBMS) in the RCRA program. Specifically, we noted that such a change would: (1) Allow the regulated community more flexibility in method use during RCRA-required testing; (2) stimulate the development and timely use of innovative and more cost-effective monitoring technologies and approaches in the RCRA program; (3) allow more efficient and timely releases of SW–846 methods by decoupling most of the methods from required uses in the RCRA regulations; and (4) make the RCRA program more effective by focusing on measurement objectives rather than on measurement technologies. As noted, the Agency proposed to restrict the requirement to use a specific SW–846 method to only those situations where its particular procedure is the only one that is capable of measuring the property (*i.e.*, a method-defined parameter, or MDP). For example, to determine whether the levels of hazardous constituents in a particular waste stream are equal to or greater than the toxicity characteristic (TC) levels specified in § 261.24, waste generators must test their waste using SW–846 Method 1311, the "Toxicity Characteristic Leaching Procedure," or "TCLP." If levels in the waste are greater than or equal to the TC levels, the waste is a hazardous waste and is subject to the RCRA hazardous waste regulations. This is the only reliable method for determining whether TC levels are met. Thus, testing of any material to determine whether it meets the Toxicity Characteristic levels must be done using the TCLP. EPA describes the measurement obtained from the TCLP, as well as from certain other methods, as a required "method-defined parameter."

We requested public comment on the proposed revisions to the RCRA regulations, although not to the method-defined parameters, and received comments on the proposed action from over 20 different commenters, which included representatives of Federal Government agencies, State Government agencies, industry, waste generation and management entities, and analytical laboratories. The majority (86%) of the commenters generally supported, with comment, the MIR action and EPA's efforts to allow more flexibility in method selection when conducting RCRA-related sampling and analysis. Regarding the positive comments, one commenter, a state agency representative, applauded EPA for recognizing that regulating does not have to be prescriptive. Another commenter, a representative of analytical laboratories, believed that the additional flexibility will result in data quality improvements. Two representatives of waste generation or management entities concurred with EPA that the majority of the MIR revisions should make it easier and more cost effective to comply with RCRA-related regulations.

For the most part, the negative public comments may have reflected a misunderstanding of certain important aspects and premises of the MIR, which we are clarifying in our responses to those comments. With respect to other negative comments, the Agency expects that the discussion below will further clarify the purposes and premises of the MIR, and will clarify options for dealing with the inherent flexibility of this approach. Also, the Agency will continue to provide training on the concepts of this rule to further clarify its intent and support its implementation. You will find a background document containing our complete responses to all relevant public comments in the docket to this rule, docket number RCRA–2002–0025, at the location listed above under ADDRESSES. Some of the public comments are also addressed within this preamble to the final rule.

Based on our review of the public comments regarding the October 30, 2002 proposed rule, we are proceeding with publication of this final rule, which finalizes the proposed revisions to the RCRA regulations. That is, this rule removes unnecessary required uses of SW–846 in general and it removes any unnecessary required uses of specific SW–846 methods. Other reliable methods can now be used by the regulated public for compliance with the affected regulations. This action also encourages the timely use of new and innovative methods outside of SW–846 in that, for most sampling and analysis scenarios, it will not be necessary to submit an equivalency petition when using a non-SW–846 method. However, some regulations will still require use of a specific SW–846 method when that method is for determination of a RCRA-required method-defined parameter (MDP); in those cases, a regulated entity has to submit an equivalency petition and receive approval of that petition from the Agency before an alternative method can be used.

This final rule will allow the Agency to make final updates to SW–846 available in a more timely manner. For example, soon after publication of this document, we will announce the availability of Final Update IV (see section VIII of this document). The methods of Final Update IV did not have to go through the rulemaking process because, with publication of this final rule, SW–846 is no longer required in general by any existing RCRA regulation and none of the new or revised methods in Update IV are specifically required by any RCRA regulation for the analysis of method-defined parameters (MDPs). However, we did solicit and consider public comments on the methods through Federal Register notices, see 63 FR 25430–25438, May 8, 1998 (Draft

Update IVA), and 65 FR 70678–70681, November 27, 2000 (Draft Update IVB).

A. Public Comments Regarding How To Determine if a Method Is Appropriate

In section III.A of the preamble to the October 30, 2002 proposed rule, we discussed our proposed revisions to remove the requirement to use SW–846 methods by adding regulatory language allowing the use of appropriate methods such as those found in SW–846 or other reliable sources. In the preamble of the proposed rule, we provided guidance on how to determine if a method is appropriate for its analytical purpose. Specifically, we mentioned that such a method might be one published by EPA in a different manual or regulation or published by another government agency, a voluntary standards setting organization, or other well-known sources. We also proposed to retain mention of the SW–846 methods in the regulations as guidance and as examples of methods that could be appropriate.

In the proposed rule preamble, we gave two primary considerations in selecting an appropriate method, which together serve as our general definition of an appropriate method. As done in the preamble to the proposed rule, the text to follow explains each of these concepts and identifies other guidance that may be helpful to the regulated community.

1. Appropriate methods are reliable and accepted as such in the scientific community.

2. Appropriate methods generate effective data.

Regarding the first consideration, we noted that methods which are reliable and accepted in the scientific community might include those published by the Agency or other government entities using techniques that have documented reliability. SW–846 methods, for example, are reviewed by a technical workgroup composed of national expert-level chemists who provide peer input and determine whether method reliability is sufficiently documented. The technical reliability and acceptance of other methods published by other governmental or non-governmental organizations may also be documented, especially if the methods are subjected to some form of objective scientific review. For instance, to qualify for recognition as having developed a voluntary consensus standard (*e.g.*, analytical method) under the National Technology Transfer & Advancement Act of 1995 (NTTAA), an organization must produce standards by consensus, observe the principles of openness and balance of interests, and provide due process, including an appeals process.

Regarding the second consideration in the identification of appropriate methods—generation of effective data—we described in the preamble to the proposed rule examples of tools that might be used in this determination. *This consideration is project-specific* and therefore the tools and criteria will be different for each analytical effort. As stated in the proposed rule preamble, effective data are data of sufficiently known and appropriate quality to be used in making project-specific decisions. An example of such a decision is whether a particular waste is hazardous because a constituent of concern is present above a level of concern. Before sampling and analysis begins, project planners should identify why the analysis is being done, how the data will be used, and how "good" the data has to be (*e.g.*, the quality objectives for the project as established through a systematic planning process). Effective data meet the quality objectives set by the project planners for the specific project. The quality objectives should be rationally and systematically identified during the planning of the project and development of the project-specific Quality Assurance Project Plan (QAPP), Waste Analysis Plan (WAP), Sampling and Analysis Plan (SAP), or other appropriate systematic planning document. Sampling and analysis documentation should be sufficient to confirm that the data are effective and that the selected method is appropriate.

Quality objectives generally refer to the necessary quality of the overall decision to be made or, in other words, the tolerable error (*i.e.*, acceptable level of uncertainty for the decision). For example, a quality objective for waste analysis may be that one must demonstrate that an analyte is not present above the reported level at the 80 percent upper confidence around the mean, and that the method could have detected the presence of the analyte at that level and confidence limit. A quality objective may be specified in a regulation, a permit, a corrective action agreement, or other regulatory or enforcement document. Sometimes you must consider a quality objective regulatory specification when selecting an appropriate method. For example, the RCRA comparable fuels' provisions include quality objectives in lieu of naming the use of specific methods (see 63 FR 33781, June 19, 1998). You can find guidance on the development of formal data quality objectives (DQOs) in EPA's "Guidance for the Data Quality Objectives Process" (EPA QA/G–4) found at EPA's Quality Staff's Web site (*http://www.epa.gov/quality/*), in Chapter One, "Quality Control," of SW–846, and in ASTM D 5792, "Standard Practice for Generation of Environmental Data Related to Waste Management Activities: Development of Data Quality Objectives." You may also use other scientifically valid systematic planning processes for developing quality objectives based on specific project needs.

In the project planning document, you should identify the types of quality control (QC) concepts (*e.g.*, spike recovery analyses, blanks, etc.) you will use to determine if you meet your objectives. For example, selection of an appropriate method is sometimes demonstrated by adequate recovery of spiked or surrogate analytes and reproducible results, or through successful analysis of a standard reference material of a matrix-type analogous to that of the actual sample matrix. The method may not be appropriate for its intended use if your data show inadequate recovery of an analyte at a level that impairs a decision regarding whether the analyte is present at or below its regulatory level. Such a method would not generate effective data. Based on your QC data, you should determine whether the method generates results that are sufficiently sensitive, unbiased, and precise to demonstrate compliance with the subject regulation.

However, you should not just focus on controlling or documenting analytical quality, because regulatory decisions are also susceptible to error due to sampling procedures. If the contaminant variability is not properly addressed during the planning and collection of samples, an incorrect decision could be reached even though the method performed well in terms of laboratory quality control. No matter how accurate or precise the laboratory analysis, the data will provide misleading information if excessive error is introduced by improper sampling procedures. Guidance on identifying the necessary quality control procedures and on minimizing the potential for both analytical and sampling error can be found at the EPA Quality Staff's Web site (*http://www.epa.gov/quality/*) or in Chapters One, Two, and Nine of SW–846. In addition, guidance on determining and demonstrating the appropriateness of a selected measurement method for a particular application may be found in ASTM D 6956–03, "Standard Guide for Demonstrating and Assessing Whether a Chemical Analytical Measurement

System Provides Analytical Results Consistent with Their Intended Use."

Finally, EPA noted in the proposed rule preamble that you should identify appropriate methods for a specific project *before* sampling and analysis begins. As the regulated entity, you are ultimately responsible for compliance with a particular regulation. Therefore, you should not rely on the laboratory or other project participant to select an appropriate method. We recommend that you consult with your regulating authority during identification of performance goals and the selection of appropriate methods.

We requested and received public comment on the above considerations and on the proposal to allow the use of appropriate methods such as those found in SW–846 or other reliable sources. One supportive commenter believed the Agency had provided sufficient guidance in the preamble to the proposed rule on how to identify appropriate methods. As discussed below, a few commenters requested additional guidance regarding the selection of appropriate methods or had questions regarding the approach.

One commenter requested that an appropriate method definition be codified in the regulations. The Agency believes that codification of an appropriate method definition would be both very difficult and contrary to the intent and purpose of this rule, given the project-specific nature of "appropriate method selection" and the wide variety of data collection objectives that may be encountered. In the paragraphs above, the Agency has provided the key generic considerations for appropriate method selection, which together serve as our general definition for an appropriate method, and identified guidance sources, in the hope that this information will assist readers of this rule during the selection of appropriate methods, regardless of whether the methods are from SW–846 or other sources. In addition, since publication of the proposed rule, ASTM International published D 6956–03, "Standard Guide for Demonstrating and Assessing Whether a Chemical Analytical Measurement System Provides Analytical Results Consistent with Their Intended Use." This guidance document is not required by any EPA program, but may be useful to the regulated community during the selection of appropriate methods and during the evaluation of analytical results. The document can be obtained from ASTM by visiting its Web site at *http://www.ASTM.org* or by writing to: ASTM International, 100 Barr Harbor Drive, P.O. Box C700, West Conshohocken, PA 19418–2959. EPA also plans to continue to provide training to affected entities on the concepts of this rule and to support its implementation. When using any appropriate method, you should be able to determine the analyte of concern (e.g., the regulated constituent to be measured), in the matrix of concern (e.g., the physical substance which might contain the regulated constituent), at the level of concern (e.g., the regulated level of or the action level for the analyte).

One commenter was concerned that the regulated public might use other methods that do not meet the QC criteria in the SW–846 methods. The Agency does not believe that this should be a concern. The performance data and QC criteria given in the SW–846 methods are only examples, and are not requirements for analysis. The SW–846 example criteria may not be appropriate for every analytical purpose. Establishing QC criteria is a project planning issue and not a method issue. Methods should be adapted into standard operating procedures (SOPs) to meet QC criteria from systematic planning documents, not the other way around. Some analytical applications may require more or less stringent QC criteria than that given as examples in the SW–846 methods, and it would be contrary to promoting a PBMS approach if all analyses using any methods are expected to conform to the example criteria published in SW–846 methods. Sometimes, even when using an SW–846 method, it may not be necessary to fully meet its example performance criteria because project-specific quality objectives may not require evaluation of the same performance indicators or the criteria may not be appropriate to the specific application. In keeping with a PBMS approach and the goals of this rule, performance criteria should be determined on a project-specific basis during the planning stage.

Another commenter was concerned that some regulated entities might use methods that were not originally developed for environmental purposes, and thus data validity may be suspect. Provided that the method is appropriate based on the factors discussed above and in the proposed rule preamble, we do not believe that this should be a concern. If the data are suspect or otherwise not of sufficient quality for their intended use, then the method is not appropriate, regardless of its source, and thus the data are not acceptable for demonstrating compliance. Regardless of the original purpose or source of a method, it can be an appropriate method if it generates effective data, *e.g.*, the data quality objectives and performance criteria are met. Even an SW–846 method may not be appropriate for a particular application if it does not generate effective data. In addition, the application of method technologies from other disciplines promotes the use of innovative approaches and technologies, which may benefit RCRA-related analyses. Finally, many of the analytical techniques used today in environmental analyses were initially developed for other purposes.

One commenter agreed with EPA's approach to appropriate method selection, but had comments regarding the data quality objectives approach. The commenter believed that the DQO approach can be expensive and is not usually used during small analytical projects. In response, the Agency notes that, when data are being used in decision making involving two clearly alternative conditions (*e.g.*, compliance vs. noncompliance with a regulatory standard), the Agency's recommended systematic planning tool is the DQO process. While there is no regulatory obligation to use the DQO process, it is the recommended planning approach for many EPA data collection activities. However, the DQO process may be too complicated for some projects and is not the only way to generate quality data through systematic planning. It is presented here in the MIR only as an example of an approach involving systematic planning. However, at a minimum, the Agency recommends that some form of systematic planning be implemented for every data collection effort in order to generate effective data, and notes that such systematic planning should also involve consideration of cost. Systematic planning is a common sense approach, designed to ensure that the level of detail in planning is commensurate with the importance and intended use of the work and the available resources.

One commenter supported EPA's proposed flexibility, but thought that EPA should continue to use SW–846 as the primary vehicle for making recommendations regarding procedures that will meet minimum quality objectives for RCRA analyses. Thus, one would not be required to use SW–846 methods, but could choose to use them and be confident that they are appropriate sampling and analysis procedures, provided that they can be demonstrated to meet project quality objectives. Another commenter believed that it would be unrealistic for a regulated entity to agree to the use of other methods if EPA has not approved them. The commenter believed that such approval would guarantee

acceptance of the data, provided that the method was properly followed.

First, it should be noted that there are no "PBMS methods." PBMS is a regulatory approach where what has to be accomplished is specified, rather than how the monitoring is to be conducted. Under such a system, regulated entities are permitted to employ any method that is technically adequate to accomplish the compliance demonstration. Regarding EPA's approval of PBMS, EPA has already stated its objective to employ the performance approach in its regulatory and other monitoring programs to the extent feasible. On October 6, 1997 (62 FR 52098–52100), EPA published in the **Federal Register** its intent to adopt PBMS agency-wide. Subsequently, on May 8, 1998 (63 FR 25430–25438), EPA published in the **Federal Register** a notice of intent and request for comment regarding its plans to reform implementation of RCRA-related monitoring by formally adopting PBMS and by removing unnecessary required uses of methods from the RCRA regulations (part of PBMS).

EPA also believes that method selection should be a project-specific decision and therefore cannot recommend or approve any methods—even SW–846 methods—as always being appropriate for any given application. For that very reason, with this rule, EPA removed the requirement to use SW–846 methods, except when the methods are the only ones capable of measuring a particular property. Relying on the fact that a method is contained in SW–846 does not guarantee that the method will always generate effective data under any situation. If the SW–846 method is not an appropriate method for its intended application, following it exactly could generate erroneous data and could fail to demonstrate compliance with the RCRA requirements.

Second, EPA does not agree with the recommendation that it categorically state that any method is always an effective means of demonstrating compliance (with the exception of methods for the analysis of method-defined parameters) since the Agency has no way of knowing that a particular method is going to yield valid data in all potential situations and it goes counter to the performance approach which requires that regulated entities demonstrate compliance using data of known and documented quality. The Agency believes that it is up to the individual regulated entity to decide which methods are appropriate to use for any given compliance demonstration and that this determination should be initiated during the project planning stage. When considering method selection, the analytical performance indicators are key to the specific project goals that should be considered. Examples of analytical performance indicators that might be addressed include method sensitivity and selectivity, precision, bias, and reproducibility. The data user may even choose to revise method selection if additional information gathered during the project indicate that the initial selection was not appropriate. Therefore, method selection is a project-specific activity implemented by the regulated entity, and EPA's only concern is that the generated data be effective for its purpose, regardless of the method selection. The Agency does recommend that a regulated entity seek assistance from its regulating authority should the regulated entity have concerns regarding the use of any particular method. EPA also notes that guidance regarding demonstrating the performance of a given analytical method can be found in EPA-published guidance documents (some of which are listed above) and documents published by other Agencies (*e.g.*, ASTM).

One commenter was concerned regarding how method performance would be demonstrated under PBMS. The commenter claimed that implementation of a PBMS approach is very difficult and that, for it to work, there must be a "reference method" to be used as a benchmark against which to measure other methods.

EPA notes that the RCRA program does not use reference methods. Many different methods produce effective data for a particular project, which are not necessarily "equivalent," but all could be "applicable." For example, there are many analytical methodologies that can be used in analyzing a particular metal species (*e.g.*, ICAP, AA). In selecting a particular method for metal analysis, the analyst will consider analytical costs, accuracy and sensitivity needed, freedom from potential interferences, amount of sample required for an analysis, reagents to be used, and other factors in the overall process to select a method that will yield effective data at the lowest cost to the user. These factors should be considered when evaluating any method, including those published in SW–846, and the user needs to conduct the appropriate verifications to demonstrate the appropriateness of any method that is selected against its intended application. There are a number of approaches that can be used to demonstrate that a method is valid for a particular use. These include: use of appropriate reference standards, analysis of spiked samples, comparison of results to results generated using a method that employs a fundamentally different measurement process and would not be subject to the same potential interferences, etc. For further guidance in demonstrating method validity, see the previously cited ASTM document D 6956–03, "Standard Guide for Demonstrating and Assessing Whether a Chemical Analytical Measurement System Provides Analytical Results Consistent with their Intended Use."

B. Public Comments Regarding Other Approaches

As explained in section III.B of the proposed rule preamble, EPA considered several approaches to promoting "method use" flexibility in the RCRA regulations. We selected the "appropriate method" approach because it is universally applicable to the subject RCRA regulations. It also requires only minimal revisions to the regulations for implementation.

In addition, the option to use "appropriate methods" is not new to the RCRA regulations. For example, use of the TCLP, SW–846 Method 1311, is required for determining whether a waste is hazardous for the toxicity characteristic (the TC). It generates an extract (the leachate) which is subject to a determinative analysis for comparison with the TC regulatory limits. However, the TCLP procedure does not require specific analytical methods for the leachate determinative analysis, nor does it specify the use of even SW–846 methods in general for such analysis of the leachate. It allows method flexibility similar to that proposed by this rule by stating in section 7.2.14: "The TCLP extract shall be prepared and analyzed according to appropriate analytical methods."

Nevertheless, in the proposed rule preamble, the Agency requested the public's opinion on two alternative approaches that we considered during development of this rulemaking.

1. As a variation to the "appropriate method" approach described above, should we remove mention of SW–846 methods as examples of potentially appropriate methods from the subject regulations?

2. In lieu of the "appropriate method" approach, should we instead add specific measures of required measurement system performance or data quality objectives to each regulation, such as done in the comparable fuel rulemaking, and not mention or require the use of an appropriate method (including any SW–846 methods)? In the proposed MIR, we did not select this approach because it

might require significant regulatory changes with difficult to quantify impacts.

Most of the commenters preferred that EPA retain mention of SW–846 in the regulations as examples of potentially appropriate methods. However, some of these commenters appeared to believe that, by mentioning SW–846 methods as examples, it meant that such methods will always be appropriate for every data collection effort addressed by the regulation, and thus the performance of other candidate methods should be compared with the performance of the similar SW–846 method. One commenter wanted the Agency to legally recognize that the SW–846 methods are appropriate methods under the RCRA regulations.

The Agency strongly disagrees with commenters that SW–846 methods should be identified as always appropriate. As explained in section III.A of this rule, the determination of an appropriate method should be made on a project-specific basis and involves consideration of various project-specific objectives and criteria. As noted, an appropriate method might be one published by EPA in a different manual from SW–846 or might be a method published by a different government agency, a voluntary standards setting organization, or other well-known scientific sources. Whether a method is contained in SW–846 is not a primary criterion for determining if a method is appropriate. For example, there is a common misconception that the different SW–846 methods for sample extraction all have the same extraction efficiency, which is not the case at all, since the methods were intended to be appropriate for different applications. Methods found in other publications may be more appropriate based on the project-specific considerations.

Regarding the addition of performance criteria to the regulations, a few commenters did prefer that such criteria be added to the regulations. However, these commenters did not provide suggestions regarding how to best resolve those instances when such an approach might result in requiring use of methods which are more accurate or sensitive than necessary (with the result that monitoring costs may increase unnecessarily) or in other cases would not yield data of a sufficient quality to definitively determine if a facility is in compliance with a regulatory or permit level. Given these impact issues and the project-specific nature of what determines an appropriate method, it would be contrary to the purpose of this rulemaking and very difficult to develop and implement performance criteria and definitions that would be universally applicable. EPA therefore decided against adding criteria at this time to all of the regulations. We strongly believe that the appropriate method determination should be made on a project-specific basis by those familiar with the purpose of the analysis and should not be dictated by regulatory definition. EPA believes that generic performance criteria assigned by EPA would not assure consistent application of PBMS, but rather might discourage a PBMS application and flexibility in method selection and use. However, to further evaluate this issue, the Agency's Forum on Environmental Measurements (FEM) has formed an Action Team to address issues related to implementation of the performance approach. It is anticipated that the Action Team will address issues related to data quality and data quality documentation for use by all Agency programs.

In conclusion, as a result of consideration of all comments, we decided to not add performance criteria to the regulations. In addition, unlike the proposal, we decided to not include any references to SW–846 or "using appropriate methods such as those found in * * * SW–846" in the regulatory provisions because those references to SW–846 were unnecessary and, based on public comment, the regulated community may continue to believe that SW–846 methods will always be most appropriate.

C. Public Comments Regarding Impacts From Removal of Required Uses of SW–846 Methods

In the preamble to the proposed rule, we summarized the expected impacts on the regulated entities and the states, and requested public comment on the assumptions made in the analysis. We also requested public comment on the impact of this rule and how we might promote its successful implementation. The paragraphs to follow summarize our impact assumptions and provide our responses to some of the public comments regarding these topics.

As a result of this final rule, you can use any appropriate analytical test method in demonstrating compliance with the RCRA regulations, except for those regulatory provisions involving method-defined parameters. We believe that this action will not significantly or adversely impact the regulated community or other potentially affected parties because the Agency is not adding any additional regulatory requirements to the RCRA regulations, but rather is clarifying and expanding the flexibility that regulated entities have had in selecting appropriate methods to employ to demonstrate compliance whether or not such methods were described in SW–846. By making it clear that one may use any appropriate method, regulated entities may be able to cut the cost of compliance monitoring by using less expensive methods. Regulated entities may continue to use SW–846 methods to demonstrate compliance when it is appropriate to do so, and thus experience no impact from this rulemaking. EPA will also continue to publish and update SW–846 methods and ensure their scientific soundness by following peer review guidelines and requesting public comment on the methods through Federal Register notices.

Thus, as we noted in section III.C of the proposed rule preamble, the primary impact of this rule will be better analytical results (*e.g.*, due to paying better attention to method performance). The Agency also anticipates a tendency toward lower costs during compliance with the affected RCRA regulations because project planners may identify methods that are potentially less costly to use. Meanwhile, EPA also will continue to provide training and utilize our pool of Agency technical experts to serve the public by answering questions regarding the use of test methods during RCRA-related compliance activities.

Also, a demonstration that another method is appropriate is already allowed within RCRA-related sampling and analysis and will not involve much more than what regulated entities already should be doing. For example, as the regulated entity, you should already be setting method performance goals in your Quality Assurance Project Plan (QAPP), Sampling and Analysis Plan (SAP), or other systematic planning document and then evaluating compliance with those goals based on data quality indicators, including when using SW–846 methods.

Regarding public concerns about the comparability of data generated by different methods for the same purpose, we noted in the proposed rule preamble that this practice is not new because some regulations already allow the use of more than one method. We also do not believe that this should be a concern, provided that any alternative method is also an appropriate method as defined above. Specifically, if both methods generate effective data and meet the data quality objectives of the project, then results from both methods will be acceptable for demonstrating compliance. In addition, for situations where trends or comparability are to be

determined, measurement quality objectives should be selected for use in selecting methods to be used that will ensure that, for whatever desired level of difference one desires to determine, the data will be suitable for the purpose. This has always been EPA's approach in comparing data by different methods, and it is not affected or changed by this rule.

Some commenters preferred a more prescriptive approach in the regulations because method-specific requirements remove the burden of method-selection as it is believed that this translates into lower costs and greater agreement between permit writers and other project participants who may not have method-selection expertise. Because of consequences of this approach, the Agency believes it is undesirable. A major problem with the prescriptive-or mandated-methods approach is that it can lead to data of poor quality which can result in an incorrect assessment of compliance. Another problem is that the regulated community may not systematically plan their data collection efforts and thus not fully understand their project-specific goals. Method-selection decisions should be project specific and thus, specific methods should not be required in the regulations.

Some commenters also expressed concern regarding the impact of this rule on existing RCRA permits. RCRA permits are typically effective up to ten years. This rule will only effect new or reissued permits, and only to allow more flexibility in method selection. Therefore, RCRA permits will not be adversely impacted by this action.

Finally, this rule does not add new information collection or reporting requirements for regulated entities. Section 260.22(i) (reporting requirements for petitions to exclude wastes) and §§ 264.13(b) and 265.13(b) (reporting requirements for owners and operators of hazardous waste management facilities) provide sufficient reporting requirements to cover RCRA-related testing and analysis documentation regarding the use of other appropriate methods.

One commenter agreed, regarding impact of the rule, that the MIR will greatly benefit those situations where repeated analyses are needed, such as for a RCRA corrective action or for a WAP for a hazardous waste treatment, storage, or disposal facility (TSDF). However, the commenter also believed that smaller entities involved in waste analyses, such as small quantity generators (SQGs) will probably not benefit from the MIR. For the reasons given above, EPA believes that the impact of this rule will not be significant for any generator, including small quantity generators (SQGs), largely because the flexibility of method selection will provide better analytical results at a lower cost. Project planners and laboratories used by SQGs will identify methods that are potentially less costly and yet provide effective data. EPA believes that the regulated community will choose appropriate methods based on cost and data quality advantages, and therefore all regulated entities, including SQGs, could benefit from this rule.

One other commenter believed that if PBMS is adopted, prior approval by the State or other regulator of the method should be mandatory. The commenter argued that State reviewers are more familiar with SW–846 methods and data indicators and that a state's unfamiliarity with other methods might mean the State may not perform a timely review of the data.

As explained in the previous section, EPA believes that method approval prior to use would be contrary to the intent and philosophy of the performance concept and would negate the positive impacts of this rule. However, as also noted, the regulated community can consult with their regulating authority during the identification of performance goals and the selection of appropriate methods. EPA appreciates the commenter's concern regarding potentially negative impacts on the timely review of data. It is true some delay in data review may occur if the reviewer is not familiar with the procedure. Nevertheless, review of data should not be a new step in the process since effected entities should already be reviewing data indicators from the SW–846 methods during RCRA-related sampling and analysis. Once the reviewer and user become more familiar with a new method, less time will be needed to perform an equally thorough review. In the end, we believe the benefits of modifying the rules will far outweigh these potential impacts on data review time through the improvement of data effectiveness and a decrease in other costs. To help mitigate any potential negative impacts, we will continue to provide training and our staff are available to assist you during all stages of the process.

Some commenters expressed a concern that this action will impose an additional resource burden on States. In response, we note that the regulatory changes in this rule are equivalent to or less stringent than the existing Federal regulations which they amend. Therefore, authorized States are not required to adopt and seek authorization for this rulemaking within their programs. If a State believes that adoption may be too burdensome on their resources, then they need not adopt the revised regulations. Nevertheless, we encourage the adoption of these or similar revisions by authorized States in order to promote the national adoption of the performance approach in environmental regulations, permits, and monitoring. In addition, if States choose to adopt these revisions, the impact should not be significant since they already conduct method selection and data quality reviews to determine compliance with their testing and monitoring regulations.

Some commenters expressed a need for communication and training to assist in implementation of the MIR. We agree and the Agency plans to continue to provide education and training to States, EPA Regions, and the regulated community regarding the implementation of this rule, through such mechanisms as workshops, fact sheets, and Internet training modules. Over the past seven years, OSW has offered program-specific training (e.g., "Analytical Strategy for the RCRA Program: A Performance-Based Approach") for EPA Headquarters, Regional, and State personnel involved in RCRA activities that include sampling and analysis. The Agency plans to expand its performance approach training program and offer other courses on the evaluation of data and permit writing from a PBMS and effective data standpoint. These communication and training efforts will help ensure consistency in implementation of this and other Agency performance-based rules by the States, Regions, and regulated community and help limit any associated costs.

IV. Regulatory Revisions Involving Removal of SW–846 Requirements

In section IV of the proposed rule preamble, EPA listed and discussed each of the proposed regulatory revisions which removed the requirement to use SW–846 methods and stated that appropriate methods may be used. We requested public comment on these individual regulatory section revisions (e.g., comments regarding any impacts on implementation of each affected regulation that we may have overlooked) and in general did not receive any significant negative comments regarding the removal of the SW–846 requirements from any of the regulations. We are therefore finalizing the removal of the requirement to use SW–846 in those regulatory sections.

In addition, we are finalizing revisions to three conditional delistings in part 261, appendix IX, which were not included in the proposed rule, but which, like those delistings that were included in the proposal, unnecessarily require the use of SW–846 methods. We announced our intent to revise these delistings in a memorandum to the facilities and to the relevant EPA Regional offices. We gave the entities three weeks to comment on the revisions. One of the affected companies did not respond to the memorandum, while the other two companies responded, but did not have comments regarding the revisions.

Therefore, we decided to proceed with finalizing the revisions to these three delistings. The revisions to the conditional delistings are very similar to the other conditional delistings. We did not receive negative comments regarding the general removal of required uses of SW–846 in any of the conditional delistings listed in the proposed rule. We believe that these revisions are fully consistent with EPA's original intent to make such changes to any conditional delisting, or other regulations, which unnecessarily required the use of SW–846 methods for analyses other than for required MDPs.

The additional conditional delistings revised by this final rule are found in Table 1 of appendix IX of part 261 and address delisted wastes at the following facilities:

—Bekaert Corp., Dyersburg, TN
—OxyVinyls, L.P., Deer Park, TX
—Tokusen USA, Inc., Conway, AR

In addition, since publication of the proposed MIR, the Office of Federal Register (OFR) revised its format for incorporation by reference. Specifically, the OFR requires that the MDP methods incorporated by reference at § 260.11 be specifically mentioned in the relevant sections of the regulations, and not just include referrals to § 260.11. Therefore, in the conditional exclusion listings of part 261, appendix IX, we included a listing of the method-defined parameter methods to replace our proposed language stating that the methods listed in § 260.11 must be used without substitution when required. Those methods must be used as applicable to the particular delisting.

Finally regarding the conditional delistings, we are taking this opportunity to make several editorial corrections to Tables 1, 2 and 3 of appendix IX of part 261, which in no way substantially change or remove any requirements. We are removing repeats of the Bekaert Corp., Dyersburg, TN, conditional delisting from Tables 2 and 3 of appendix IX of part 261 because those entries were added to the tables in error. The Bekaert Corp. conditional delisting is for an F006 waste, which is from a non-specific source, and therefore the delisting only belongs in Table 1, which lists wastes excluded from non-specific sources (i.e., "F" coded listed wastes). Tables 2 and 3 of appendix IX of part 261 are meant to only list the conditional delistings of wastes excluded from specific sources (Table 2, i.e., "K" coded listed wastes) or from commercial chemical products, off-specification species, container residues, and soil residues thereof (Table 3, i.e., "P" and "U" coded listed wastes). Similarly, we are removing the OxyVinyls, Dear Park, TX, delisting from Table 1 and adding it to Table 2 of appendix IX. This is necessary because the OxyVinyls' delisting addresses K017, K019, and K020 wastes and was incorrectly placed in Table 1. Since these are changes that do not affect the implementation of the regulations, or add new or remove existing regulatory requirements, the Agency is providing notice of the changes without opportunity for comment.

Table 2 lists the regulatory revisions finalized by this rule to remove the requirement to use SW–846 methods and allow the flexibility to use other appropriate methods. As noted in the previous section of this preamble, the proposed references to "using appropriate methods such as those found in * * * SW–846" is not being included in the final regulation because the Agency decided that those references to SW–846 were unnecessary and because the regulated community may continue to believe that SW–846 methods will always be most appropriate. Finally, we corrected our proposed revision to § 261.35(b)(2)(iii)(B) by adding the relevant data from Table 1 of Method 8290 to the regulatory text so that Method 8290 (which contained the table but is not an MDP method) no longer has to be incorporated by reference. In the proposed rule, § 261.35(b)(2)(iii)(B) read as follows: "Not detected means at or below the lower method calibration limit (MCL) in SW–846 Method 8290, Table 1. Other appropriate methods from other reliable sources may be used provided that these criteria are met." In the final rule, we copied the relevant data from Table 1 directly into § 261.35(b)(2)(iii)(B) and so it is no longer necessary to mention Method 8290.

TABLE 2.—REVISIONS TO RCRA REGULATIONS TO REMOVE REQUIRED USES OF SW–846 METHODS

Regulation	Affected topic or program
§ 260.22(d)(1)(i)	Petitions to exclude waste from a particular facility.
Appendix IX to part 261	Wastes excluded under §§ 260.20 and 260.22.
§§ 261.35(b)(2)(iii)(A) and (B)	Deletion of certain waste codes following equipment cleaning.
§ 261.38(c)(7)	Comparable/syngas fuel exclusion.
§§ 264.1034(d)(1)(iii), 264.1063(d)(2), 265.1034(d)(1)(iii), and 265.1063(d)(2).	Air emission standards for process vents and equipment leaks.
§§ 265.1084(a)(3)(iii) and (b)(3)(iii), and 265.1084(a)(3)(ii)(C), (b)(3)(ii)(C), and (c)(3)(i).	Air emission control requirements for tanks, surface impoundments, and containers.
§§ 266.100(d)(1)(ii) and (g)(2), and 266.102(b)(1)	Hazardous wastes burned in boilers and industrial furnaces (BIFs).
§ 266.106(a)	Control of metal emissions at BIFs.
§§ 266.112(b)(1) and (b)(2)(i)	Residues from burning of wastes in BIFs.
Appendix IX, part 266	Methods Manual for BIF regulations.
§§ 270.19(c)(1)(iii) and (iv), 270.22(a)(2)(ii)(B), 270.62(b)(2)(i)(C) and (D), 270.66(c)(2)(i) and (ii).	Part B information and trial burn plan requirements for incinerators and BIFs.

This rule also revises the incorporation by reference of SW–846 in § 260.11 so that the paragraph only includes SW–846 methods that are required for method-defined parameters. Therefore, for each section where we removed the requirement to use only SW–846 methods, we also removed the SW–846 incorporation by reference.

Prior to this rule, all methods of SW–846 were incorporated by reference at § 260.11 "when used" within the RCRA regulations. All of SW–846 had to be incorporated by reference because some RCRA regulations required in general the SW–846 methods, *e.g.*, the delisting regulations at § 260.22(d)(1)(i). The required methods had to be incorporated by reference because their full text is too lengthy for publishing directly in the regulations and the methods are readily available to the public in the SW–846 manual. As a result of this rule, we are limiting the requirement to use SW–846 methods to when the methods analyze required method-defined parameters. Therefore, we revised § 260.11 to remove the incorporation by reference of all SW–846 methods, except those SW–846 methods that may be required for the analyses of method-defined parameters. Those methods will remain incorporated by reference when used for method-defined parameters and required by the RCRA regulations.

It is important to note that, while a method is listed in § 260.11 because it is used for analysis of a method-defined parameter, it also may be used for non-mandatory purposes. In those cases where the method is required by a specific regulation and is listed in 260.11, it is a method-defined parameter. For example, Method 9010C, "Total and Amenable Cyanide: Distillation," and Method 9012B, "Total and Amenable Cyanide (Automated Colorimetric, with Off-line Distillation)" are required under § 268.44, the universal treatment standards of the land disposal restrictions regulations, and are listed in § 260.11 as required by § 268.44. In that case, the methods cannot be substituted. However, in other circumstances, these two methods may be used when they are not required by their regulations (*e.g.*, during delistings) and in those cases they will only be considered appropriate methods and not MDPs. It is the application of a method in a regulation that determines whether a method is being used to analyze a required method-defined parameter—not simply whether the method is listed in § 260.11.

The SW–846 methods that remain as incorporated by reference in § 260.11 are listed in Table 3. The final list is different from that proposed in that Methods 3542 ("Extraction of Semivolatile Analytes Collected Using Method 0010 (Modified Method 5 Sampling Train)") and 5041A ("Analysis for Desorption of Sorbent Cartridges from Volatile Organic Sampling Train (VOST)") are no longer included. The methods were removed because they are currently not used as method-defined parameters under the RCRA program.

TABLE 3.—SW–846 METHODS TO REMAIN IN § 260.11

SW–846 method	Chapter location	Method title
0010	Ten	Modified Method 5 Sampling Train.
0011	Ten	Sampling for Selected Aldehyde and Ketone Emissions from Stationary Sources.
0020	Ten	Source Assessment Sampling System (SASS).
0023A	Ten	Sampling Method for Polychlorinated Dibenzo-p-Dioxins and Polychlorinated Dibenzofuran Emissions from Stationary Sources.
0030	Ten	Volatile Organic Sampling Train.
0031	Ten	Sampling Method for Volatile Organic Compounds (SMVOC).
0040	Ten	Sampling of Principal Organic Hazardous Constituents from Combustion Sources Using Tedlar® Bags.
0050	Ten	Isokinetic HCl/Cl_2 Emission Sampling Train.
0051	Ten	Midget Impinger HCl/Cl_2 Emission Sampling Train.
0060	Ten	Determination of Metals in Stack Emissions.
0061	Ten	Determination of Hexavalent Chromium Emissions from Stationary Sources.
1010A	Eight	Pensky-Martens Closed-Cup Method for Determining Ignitability.
1020B	Eight	Setaflash Closed-Cup Method for Determining Ignitability.
1110A	Eight	Corrosivity Toward Steel.
1310B	Eight	Extraction Procedure (EP) and Structural Integrity Test.
1311	Eight	Toxicity Characteristic Leaching Procedure.
1312	Six	Synthetic Precipitation Leaching Procedure.
1320	Six	Multiple Extraction Procedure.
1330A	Six	Extraction Procedure for Oily Wastes.
9010C	Five	Total and Amenable Cyanide: Distillation.
9012B	Five	Total and Amenable Cyanide (Automated Colorimetric, with Off-line Distillation).
9040C	Eight	pH Electrometric Measurement.
9045D	Six	Soil and Waste pH.
9060A	Five	Total Organic Carbon (TOC).
9070A	Five	n-Hexane Extractable Material (HEM) for Aqueous Samples.
9071B	Five	n-Hexane Extractable Material (HEM) for Sludge, Sediment, and Solid Samples.
9095B	Six	Paint Filter Liquids Test.

Please note that we are not adding any new methods to § 260.11—each method listed in Table 3 is already a part of SW–846 and was incorporated by reference during previous rulemakings. For each method retained as incorporated by reference, we are listing in § 260.11 the promulgated version of the method which was last incorporated by reference and thus which must be used during regulatory compliance.

In addition, since proposal of this rule, the Office of Federal Register (OFR) has revised the format of incorporation by reference sections within the Federal regulations, for instance, to include information regarding those regulatory sections or parts that specify use of the methods. We revised § 260.11(a) to reflect this new format.

V. Editorial Corrections to SW–846 References in the RCRA Testing and Monitoring Regulations

In section V of the preamble to the proposed rule, the Agency proposed to correct inaccurate references to SW–846 (some of which are logical outgrowths to the revision to § 260.11), and to clarify method selection flexibility in the RCRA regulations. We did not receive any negative comments regarding that

section of the proposed rule and thus are finalizing the editorial corrections, as proposed.

In addition, we are correcting certain regulations so that they include the appropriate suffix of the SW–846 MDP method required by them. As a result of these corrections, the method number in the regulation includes the suffix and matches the respective method number and suffix listed in § 260.11.

Table 4 lists and summarizes the editorial corrections to the RCRA regulations made by this final rule.

TABLE 4.—CORRECTIONS, CLARIFICATIONS OR REMOVALS

Regulation	Text correction, clarification, or removal
§ 258.28(c)(1)—Liquids restrictions	Correction to add "incorporated by reference in § 260.11" after "Paint Filter Liquids Test," and addition of the suffix "B" to the method number "9095."
Appendix I to part 258—Constituents for detection monitoring	Removal of footnote 1 to the table, which contains unnecessary references to SW–846.
Appendix II to part 258—List of inorganic and organic hazardous constituents.	Clarification regarding the use of other appropriate methods by removing the "Suggested Methods" and "PQLs (µg/L)" columns, removing footnotes 1, 5 and 6 and revising and renumbering the remaining footnotes, as appropriate.
§ 260.21(d)—Petitions for equivalent methods	Clarification that equivalent methods will be added to § 260.11, instead of just added to SW–846.
§ 260.22(d)(1)(i)—Petitions to amend part 261 to exclude a waste produced at a particular facility.	Removal of unnecessary reference to SW–846.
§§ 261.3(a)(2)(v), 279.10(b)(1)(ii), 279.44(c), 279.53(c), and 279.63(c)—Rebuttable presumption for used oil.	Removal of unnecessary references to SW–846.
§ 261.22(a)(1)—Characteristic of corrosivity	Addition of the suffix "C" to method number "9040."
Appendix I to part 261—Representative sampling methods	Removal of unnecessary references to SW–846.
Appendix II to part 261—Method 1311 Toxicity Characteristic Leaching Procedure (TCLP).	Removal of text in Appendix II to part 261; appendix reserved.
Appendix III to part 261—Chemical analysis test methods	Removal of text in Appendix III to part 261; appendix reserved.
§§ 264.190(a) and 265.190(a)—Applicability	Addition of the suffix "B" to method number "9095."
§ 264.314(c) and § 265.314(d)—Special requirements for bulk and containerized liquids.	Addition of the suffix "B" to method number "9095."
§§ 264.1034(f) and 265.1034(f)—Test methods and procedures.	Clarification that direct measurement is allowed to resolve disagreements regarding concentration estimates, and removal of unnecessary references to SW–846.
Appendix IX to part 264—Ground-water monitoring list	Clarification regarding the use of other appropriate methods by removing the "Suggested Methods" and "PQLs (µg/L)" columns and removing footnotes 1, 5 and 6 and revising and renumbering the subsequent footnotes, as appropriate.
§ 265.1081—Definitions	Correction to SW–846 reference in definition of "waste stabilization process."
Appendix IX to part 266—Methods manual for compliance with BIF regulations.	Corrections to reflect removal of SW–846 methods from the BIF Methods Manual on June 13, 1997 and clarification in existing guidance regarding use of other appropriate methods and SW–846.
§ 268.40(b) and table—Applicability of treatment standards	Addition of the suffix "B" to method number "1310," addition of the suffix "C" to method number "9010," and addition of the suffix "B" to method number "9012."
§ 268.44, table—Variance from a treatment standard	Addition of the suffix "C" to method number "9010" and the addition of the suffix "B" to method number "9012."
§ 268.48, table—Universal treatment standards	Addition of the suffix "C" to method number "9010" and addition of the suffix "B" to method number "9012."
Appendix IX to part 268—Extraction Procedure (EP) Toxicity Test Method and Structural Integrity Test (Method 1310).	Addition of the suffix "B" to method number "1310."

VI. Action To Withdraw the Reactivity Interim Guidance From SW–846 Chapter Seven and Remove Required SW–846 Reactivity Analyses and Threshold Levels From Conditional Delistings

In section VI of the preamble to the proposed rule, the Agency proposed to withdraw the reactivity interim threshold levels and reactive cyanide and sulfide methods from Chapter Seven of SW–846 and from certain conditional delistings found in appendix IX to 40 CFR part 261. EPA proposed these actions based on conclusions it reached and announced in an April 21, 1998 memorandum, a copy of which is available in the docket to this rulemaking, in which EPA addressed concerns about the effectiveness of the reactivity analysis procedures (see the proposed rule preamble for details regarding the content of this memo and its history). (See the April 21, 1998 memorandum at *http://www.epa.gov/SW–846/* for detailed information regarding NEIC's concerns and EPA's conclusions.) EPA consequently withdrew the July 1985 guidance through the aforementioned April 21, 1998 memorandum. To summarize, EPA concluded that the guidance had the following significant problems:

(1) The test conditions evaluate a single pH condition and not the range of pH conditions (2 to 12.5) specified in the reactivity regulation;

(2) The test conditions do not adequately recover the analyte and thus the tests predict low percentages of analyte releases in the waste;

(3) The mismanagement scenario and test conditions are not correctly scaled between each other; and

(4) The mismanagement scenario of an open pit is not the only exposure of concern and may not represent a plausible worst case scenario.

EPA received comments from eleven different commenters regarding this topic. You will find a background document containing our complete responses to all relevant public comments in the docket to this rule, docket number RCRA–2002–0025, at the location listed above under ADDRESSES. Three commenters supported the removal of the reactivity test procedures, stating that they believed

the test and guidance is flawed and that appropriate waste classifications can be made in the absence of guidance. On the other hand, three other commenters opposed the removal of the reactivity test procedures. One of these commenters stated that there are a number of concerns about the technical reasons for removal of the procedures, and believed that these warrant reconsideration of the proposed deletion of the guidance. In reviewing these concerns, the Agency found that the commenter may be misreading the Agency's basis for deletion of the guidance from SW–846. The commenter was concerned both about the impact of certain pH testing conditions and the use of Henry's Law in the guidance. However, these topics were not the reasons for withdrawing the guidance from SW–846. The Agency will investigate the commenter's concerns regarding pH testing conditions and Henry's Law as it develops revised guidance. Another one of the commenters asserted that the narrative criteria alone can be used for classification of high concentration cyanide wastes, but that additional guidance is needed for classifying lower level cyanide-bearing wastes. The other commenter understood the difficulties associated with the reactivity method guidance, but believed that the regulated community needed something other than the "honor system" to classify these reactive wastes.

The remaining five commenters had general concerns about making the reactivity characteristic determinations, but did not specifically support or oppose deletion of the tests or threshold levels. Four commenters out of the total of eleven commenters requested that EPA replace the deleted tests with other method guidance.

In response to all comments, the Agency is currently reviewing several test methods for possible inclusion in SW–846 as methods for characterizing cyanide-bearing wastes. However, the Agency still believes it inappropriate to retain the reactive cyanide and reactive sulfide methods in SW–846 for the reasons presented in the proposed rule preamble and listed above. Regarding the characteristic of reactivity, regulated parties have always been responsible for complying with the regulation at § 261.23—Characteristic of reactivity, which does not require any particular test methods for the characterization. Therefore, generators and other persons can use other appropriate methods or process knowledge in determining whether a particular waste is hazardous due to its reactivity.

VII. Clarifications to Corrosivity and Ignitability Hazardous Waste Characteristics

In sections VII.A and VII.B of the preamble to the proposed rule, the Agency proposed revisions to the corrosivity characteristic and the ignitability characteristic testing requirements. The proposed revisions included changes to references to ASTM standards and SW–846 methods. We considered these revisions to be non-substantive updates of the methods presently used in the regulations and we believed the revisions would not affect which wastes are determined to be hazardous based on the characteristics. We requested public comment on each of the proposed revisions. Significant comments and our responses are provided below.

A. Revision to § 261.22(a)(2) To Clarify That SW–846 Method 1110A Is the SW–846 Standardized Version of the NACE Standard Specified for Corrosivity Characteristic Testing

In section VII.A of the preamble to the proposed rule, EPA addressed proposed revisions to the corrosivity characteristic testing requirements, which included a clarification to § 261.22(a)(2). Section 261.22(a)(2) defines the hazardous waste characteristic of corrosivity for a liquid which corrodes steel. The required test method is identified as "the test method specified in NACE * * * Standard TM–01–69 as standardized in * * * SW–846 * * *" As explained in the May 19, 1980 regulations (see 45 FR 33084) which added § 261.22 to the RCRA regulations, EPA standardized the NACE Standard TM–01–69 in SW–846. As also explained in the background document to the corrosivity characteristic of the 1980 regulations, NACE Standard TM–01–69 describes a simple immersion test to determine the rate of corrosion. However, the procedure described in the background document, in fact, was not completely standardized because it was designed to test the suitability of metals for a variety of uses. As a result, a comment was submitted at that time which expressed concern with the incomplete standardization of the NACE Standard which allowed variation in test conditions. EPA agreed and, in response to the comment, put a standardized version of the method in SW–846 so that the procedure more clearly defined the appropriate test conditions. At the time, we did not specify which test method of SW–846 included the standardized version of the NACE method. This SW–846 method has always been Method 1110 (now Method 1110A as of Update IIIB), "Corrosivity Toward Steel." Therefore, in the proposed MIR, we proposed adding the number of this method to § 261.22(a)(2) for clarification of which SW–846 test method is the standardized version of NACE. This revision to § 261.22(a)(2) does not represent a change to the characteristic.

Three commenters addressed this section of the proposed MIR. Two of these commenters explicitly supported the clarification in § 261.22(a)(2) that SW–846 Method 1110A, "Corrosivity Toward Steel," is the standardized version of the NACE Standard TM–01–69. The other commenter did not comment on the proposed revision, but instead requested that EPA address a unrelated concern regarding the content of Method 1110A. None of the commenters disagreed with the Agency statement that the revisions were non-substantive.

Regarding SW–846 Method 1110A, the commenter believed that the method significantly differed from the corresponding Department of Transportation (DOT) corrosivity method. Specifically, Method 1110A suggests that a 24-hour test duration be used, while the DOT method indicates use of a longer test period. The commenter requested that EPA either clarify this difference or amend the regulations to allow the use of DOT's comparable corrosivity characteristic procedure, as set out in 49 CFR 173.137(c)(2), as an alternative test method for corrosivity under the hazardous waste regulations.

First, EPA notes that the test duration time in Method 1110A was not addressed or proposed for revision by the MIR. The MIR only proposed to clarify that Method 1110A is "the test method * * * standardized * * * in SW–846" for the corrosivity characteristic determination. The commenter does not appear to disagree with the proposed clarification. Because the Agency did not take comment, or even raise an issue, with the test duration time, we believe it inappropriate to address this provision in this final rule. Nevertheless, the Agency plans to evaluate the commenter's concerns to determine if future regulatory changes are warranted.

Therefore, in response to the comments submitted, the Agency is finalizing the regulatory revision whereby Method 1110A will be specified in § 261.22(a)(2). It is not necessary to also reference the NACE Standard TM–01–69 in the regulatory text. The NACE method was used to

initially develop Method 1110A and the two methods are not identical.

B. Revisions to § 261.21(a)(1) To Remove an Unnecessary Referral to Method Equivalency Petitions; and an Explanation Regarding the Decision To Not Revise the Regulation To Include the Updated ASTM Standards and References to Methods 1010A and 1020B as Proposed

In section VII.B of the preamble to the proposed rule, the Agency addressed proposed revisions to the ignitability characteristic testing requirements in § 261.21(a)(1). Section 261.21(a)(1) of the RCRA regulations defines the hazardous waste characteristic of ignitability as a liquid which has a flash point less than 60 °C (140 °F) as determined by the use of ASTM Standard D 93–79 or D 93–80 (Pensky-Martens Closed Cup Tester) or ASTM Standard D 3278–78 (Setaflash Closed Cup Tester). Since publication of the regulation, the ASTM Standard has been revised. However, before proposing to replace the ASTM Standard now in the regulation with the newer versions D 93–99c and D 3278–96, EPA compared the newer versions of the test protocol with the older versions of the protocol and found only non-substantive differences. Therefore, EPA proposed and requested comment on replacing the older versions of the ASTM Standard in § 261.21(a)(1) with the more recent versions. In addition, although ASTM Standard D 93–00 is newer than D 93–99c, EPA proposed that D 93–99c replace D 93–80 because EPA found that D 93–00 differed in a possibly substantial manner from D 93–80 and, if it were to be specified instead of D 93–99c, characteristic results may be significantly affected. Specifically, we found that the D 93–00 version specifies different sample container volumes for different sample types. It requires that all matrices, except residual fuel oil, be collected in containers not more than 85% or less than 50% full. This revision may significantly affect the characteristic results, since the potential to lose flammable volatile constituents will be greater from sample containers that may now have as much as 50% headspace. The Agency requested comment on this evaluation.

Finally, the Agency proposed to revise § 261.21(a)(1) to clarify that the ASTM standards for ignitability characteristic determinations are used and referenced by SW–846 Methods 1010A and 1020B. The Agency believed these revisions to § 261.21(a)(1) to be non-substantive and that the changes would not affect which wastes are determined to be hazardous based on the characteristic.

Five commenters addressed this section of the proposed MIR. Two commenters supported EPA's proposal to update the references to ASTM standards in § 261.21(a)(1). Two other commenters had general concerns about the ignitability characteristic and the ASTM standards, but did not appear to specifically support or oppose the replacements. Only one commenter commented on revising § 261.21(a)(1) to clarify that the ASTM standards for the ignitability characteristic are used and referenced by SW–846 Methods 1010A and 1020B. The commenter supported the regulatory revision.

Regarding ASTM Standards D 93–99c and D 93–00, the two commenters that supported updating the references agreed with EPA that D 93–99c and D 93–00 could yield different results and therefore, different conclusions as to whether or not a waste would be identified as hazardous. The two commenters that disagreed with the Agency's conclusion regarding D 93–00 maintained that the potential to lose volatile compounds also existed in the 1999 version. One of these commenters noted that an even newer version than D 93–00 was now available from ASTM, namely D 93–02. The commenter recommended that the Agency study that standard for any significant differences.

The Agency has considered all of the comments and decided to retain the existing ASTM regulatory standards and not replace them with the newer versions at this time. The Agency agrees with the commenter who suggested that EPA further study and review the new versions of the ASTM standards. Both newer versions of D 93 require that certain ASTM sampling procedures be used, which are unnecessarily prescriptive and often inapplicable to hazardous waste collection. The newer version of D 93 may also promote potential problems with requirements for sampling and automated test equipment. As a result, the Agency believes that a more detailed evaluation is warranted. In addition, the Agency believes that, although the newer versions of D 93 allows for automated test equipment, including the use of an electric igniter which may save time, a rigorous comparison of the electrical igniter versus the flame igniter should be conducted.

In addition, the Agency decided to not finalize the addition of references to Methods 1010A and 1020B in the regulations as proposed, but rather Methods 1010A and 1020B were revised as part of Final Update IIIB (final today as part of this rule, see section VIII), whereby all method text was replaced with direct references to the ASTM standards listed in § 261.21(a)(1).

Finally, as proposed regarding § 261.21(a)(1), we are removing that portion of the last sentence which refers to the equivalent test method demonstration. This information is adequately addressed in §§ 260.20 and 260.21. It is not necessary to repeat the information regarding method equivalency petitions in each section of a RCRA regulation which requires use of a specific test method(s). Also, this revision is consistent with similar sections on testing in part 261 and other parts of the RCRA regulations.

VIII. Availability of Final Update IIIB and Status of Final Update IV to SW–846

SW–846 is a guidance document that changes over time as new information and data are developed. On October 30, 2002, we proposed to revise several methods and chapters of SW–846 and release these revisions as Update IIIB to the Third Edition of SW–846. To date, EPA has finalized Updates I, II, IIA, IIB, III, and IIIA to the Third Edition of the SW–846 manual. On May 8, 1998 (see 63 FR 25430) and on November 27, 2000 (see 65 FR 70678), we also announced the availability of Draft Update IVA and IVB, respectively, which we published for guidance purposes only.

As part of this rule, we are finalizing Update IIIB. The Methods Team Web site at *http://www.epa.gov/SW–846* has been revised to remove Proposed Update IIIB and include an integrated electronic version of SW–846 which incorporates the final version of that update. In the near future after publication of this rule, Draft Updates IVA and IVB will be replaced by Final Update IV and its availability will be announced by a Federal Register notice.

The revised methods of Update IIIB are used for method-defined parameters and thus, any required uses of those methods will remain in the RCRA regulations. Therefore, we revised § 260.11 to include the Update IIIB methods.

In the proposed rule preamble, we also requested comments on certain parts of the Update IIIB methods and chapters. We did not consider comments on the other sections or parts of the methods or chapters because those portions were not proposed for revision. Most of the comments concerned the removal of the reactivity guidance methods from Chapter Seven and updating the ASTM standards. Those comments are addressed in previous sections of this preamble. The

Agency received a few other comments regarding the documents contained in Proposed Update IIIB. The docket to this rule (RCRA–2002–0025) contains a background document with our responses to all the comments submitted. The responses also identify any revisions made to the methods due to the comments.

Table 5 provides a listing of the four chapters and eleven methods in Final Update IIIB. The method numbers in the table reflect the appropriate method revision letter suffix (*e.g.*, A, B, C, etc.). These suffixes were not always reflected in the RCRA regulations themselves, e.g., the regulations cited the method number without a suffix. The relevant regulations revised by today's rule do reflect the latest suffix. Accordingly, this final rule identifies the latest promulgated version of the methods that remain as incorporated by reference at § 260.11 in the RCRA regulations. During compliance with those regulations, the regulated community must only use the latest promulgated revision of the methods as indicated in § 260.11, *i.e.*, the regulated community must only use the version of the method cited by § 260.11.

TABLE 5.—FINAL UPDATE IIIB METHODS AND CHAPTERS

Chapters or method number	Method or chapter title
Chapter Five	Miscellaneous Test Methods.
Chapter Six	Properties.
Chapter Seven	Characteristics Introduction and Regulatory Definitions.
Chapter Eight	Methods for Determining Characteristics.
1010A	(Referral to) Pensky-Martens Closed Cup Method for Determining Ignitability.
1020B	(Referral to) Setaflash Closed Cup Method for Determining Ignitability.
1110A	Corrosivity Toward Steel.
1310B	Extraction Procedure (EP) Toxicity Test Method and Structural Integrity Test.
9010C	Total and Amenable Cyanide: Distillation.
9012B	Total and Amenable Cyanide (Automated Colorimetric, with Off-line Distillation).
9040C	pH Electrometric Measurement.
9045D	Soil and Waste pH.
9060A	Total Organic Carbon.
9070A	n-Hexane Extractable Material (HEM) for Aqueous Samples.
9095B	Paint Filter Liquids Test.

Note: A suffix of "A" in the method number indicates revision one (the method has been revised once). A suffix of "B" in the method number indicates revision two (the method has been revised twice). A suffix of "C" in the method number indicates revision three (the method has been revised three times).

IX. Addition of Method 25A to §§ 264.1034(c)(1)(ii) and (iv) and 265.1034(c)(1)(ii) and (iv)

In section IX of the preamble to the proposed rule, the Agency proposed to revise §§ 264.1034(c)(1)(ii) and (iv) and §§ 265.1034(c)(1)(ii) and (iv) to allow the use of Method 25A, as well as Method 18, during analyses in support of air emission standards for process vents and/or equipment leaks at hazardous waste management facilities. All comments supported these revisions and therefore we finalized these changes, as proposed.

X. Removal of Requirements From §§ 63.1208(b)(8)(i) and (ii) in the NESHAP Standards To Demonstrate Feedstream Analytes Are Not Present at Certain Levels

In section X of the preamble to the proposed rule, the Agency proposed to remove the requirements for analytical DQOs (*e.g.*, 80% upper confidence limit) for feedstream analyses found in §§ 63.1208(b)(8)(i) and (ii) that were previously promulgated in the National Emission Standards for Hazardous Air Pollutants (NESHAP) for Hazardous Waste Combustors on September 30, 1999. All comments supported these revisions and therefore we are finalizing these changes, as proposed.

XI. Status of the RCRA Waste Sampling Draft Technical Guidance

In section XI of the preamble to the proposed rule, we announced the availability of a stand-alone sampling guidance document entitled, "RCRA Waste Sampling Draft Technical Guidance." We intended to replace the original sampling guidance version of Chapter Nine found in EPA publication SW–846 with this new document. We requested comment on the guidance. The Agency received a number of comments which are still under review and consideration. This additional review of the document will help us improve the guidance and ensure that it is most useful in its final form. Therefore, we are not at this time issuing a final version of the sampling guidance. Once we complete our review and evaluation of the comments, we will revise the document as appropriate and announce its availability in the Federal Register.

XII. State Authorization Procedures

A. Applicability of Federal Rules in Authorized States

Under section 3006 of RCRA, EPA may authorize qualified states to administer the RCRA hazardous waste program within the state. Following authorization, the state requirements authorized by EPA apply in lieu of equivalent Federal requirements and become Federally enforceable as requirements of RCRA. EPA maintains independent authority to bring enforcement actions under RCRA sections 3007, 3008, 3013, and 7003. Authorized states also have independent authority to bring enforcement actions under state law. A state may receive authorization by following the approval process described in 40 CFR part 271. 40 CFR part 271 also describes the overall standards and requirements for authorization.

After a state receives initial authorization, new regulatory requirements promulgated under the authority in the RCRA statute which existed prior to the 1984 Hazardous and Solid Waste Amendments (HSWA) do not apply in that state until the state adopts equivalent state requirements. The state must adopt such requirements to maintain authorization.

In contrast, under RCRA section 3006(g) (*i.e.*, 42 U.S.C. 6926(g)), new Federal requirements and prohibitions imposed pursuant to HSWA provisions take effect in authorized states at the same time that they take effect in unauthorized states. Although authorized states are still required to

update their hazardous waste programs to remain equivalent to the Federal program, EPA carries out HSWA requirements and prohibitions in authorized states, including the issuance of new permits implementing those requirements, until EPA authorizes the state to do so.

Finally, authorized states are required to modify their programs only when EPA promulgates Federal requirements that are more stringent or broader in scope than existing Federal requirements. RCRA section 3009 allows the states to impose standards more stringent than those in the Federal program. See also § 271.1(i). Therefore, authorized states are not required to adopt Federal regulations, both HSWA and non-HSWA, that are considered less stringent.

B. Authorization of States for Today's Rule

Today's rule affects many aspects of the RCRA Program and is promulgated pursuant to both HSWA and non-HSWA statutory authority. Therefore, the Agency added the rule to Table 1 in § 271.1(j), which identifies Federal regulations that are promulgated pursuant to the statutory authority that was added by HSWA. States may apply for final authorization for the HSWA provisions, as discussed in the following section of this preamble.

Today's rule language provides standards that are equivalent to or less stringent than the existing provisions in the Federal regulations which they would amend. Therefore, States would not be required to adopt and seek authorization for this rulemaking. EPA would implement this rulemaking only in those states which are not authorized for the RCRA Program, and will implement provisions promulgated pursuant to HSWA only in those states which have not received authorization for the HSWA provision that would be amended. In authorized States, the changes will not be applicable until and unless the State revises its program to adopt the revisions.

(Note: Procedures and deadlines for State program revisions are set forth in § 271.21.)

This rule will provide significant benefits to EPA, the states, and the regulated community, without compromising human health or environmental protection. Therefore, EPA strongly encourages authorized states to amend their programs and seek authorization for today's rule.

C. Abbreviated Authorization Procedures

EPA consider's today's rule to be a minor rulemaking and is adding it to the list of minor or routine rulemakings in Table 1 to § 271.21. Placement in this table will enable states to use the abbreviated procedures located in § 271.21(h) when they seek authorization for today's changes. These abbreviated procedures were established in the HWIR-media rulemaking (see 63 FR 65927, November 30, 1998).

XIII. Statutory and Executive Order Reviews

A. Executive Order 12866: Regulatory Planning and Review

Under Executive Order 12866 (58 FR 51735, October 4, 1993), we must determine whether a regulatory action is "significant," and therefore subject to Office of Management and Budget (OMB) review and the requirements of the Executive Order. The order defines a "significant regulatory action" as one that is likely to result in a rule that may:

(1) Have an annual effect on the economy of $100 million or more, adversely affect in a material way the economy, a sector of the economy, productivity, competition, jobs, the environment, public health or safety, or State, local, or tribal governments or communities;

(2) Create a serious inconsistency or otherwise interfere with an action taken or planned by another agency;

(3) Materially alter the budgetary impact of entitlements, grants, user fees, or loan programs or the rights and obligations of recipients thereof; or

(4) Raise novel legal or policy issues arising out of legal mandates, the President's priorities, or the principles set forth in this Executive Order.

OMB determined that this rule is not a "significant regulatory action" under the terms of Executive Order 12866 and is therefore not subject to OMB review and the requirements of the Executive Order.

B. Paperwork Reduction Act

This action does not impose any new information collection burden. There are no additional reporting, notification, or recordkeeping provisions associated with today's rule. However, the Office of Management and Budget (OMB) previously approved the information collection requirements contained in some of the existing regulations being revised by this rule, under the provisions of the Paperwork Reduction Act, 44 U.S.C. 3501 *et seq.*, and assigned OMB control numbers for those information collection requirements, as follows:

—40 CFR 258.28: OMB control number 2050–0122
—40 CFR 260.21 and 260.22: OMB control number 2050–0053
—40 CFR 261.3: OMB control number 2050–0085
—40 CFR 261.35: OMB control number 2050—0115
—40 CFR 264.1034, 264.1063, 265.1034, and 265.1063: OMB control number 2050–0050
—40 CFR 266.100, 266.102, 266.106, 266.112, Appendix IX to part 63, and 270.22: OMB control number 2050–0073
—40 CFR 270.19: OMB control number 2050–0009
—40 CFR 270.62: OMB control numbers 2050–0009 and 2050–0149
—40 CFR 270.66: OMB control numbers 2050–0073 and 2050–0149
—40 CFR 279.10, 279.44, 279.53 and 279.63: OMB control number 2050–0124

Copies of the ICR document(s) may be obtained from Sandy Farmer, by mail at the Office of Environmental Information, Collection Strategies Division; U.S. Environmental Protection Agency (2822); 1200 Pennsylvania Ave., NW., Washington, DC 20460, by email at *farmer.sandy@epa.gov*, or by calling (202) 260–2740. A copy may also be downloaded off the Internet at *http://www.epa.gov/icr*. Include the ICR and/or OMB number in any correspondence.

Burden means the total time, effort, or financial resources expended by persons to generate, maintain, retain, or disclose or provide information to or for a Federal agency. This includes the time needed to review instructions; develop, acquire, install, and utilize technology and systems for the purposes of collecting, validating, and verifying information, processing and maintaining information, and disclosing and providing information; adjust the existing ways to comply with any previously applicable instructions and requirements; train personnel to be able to respond to a collection of information; search data sources; complete and review the collection of information; and transmit or otherwise disclose the information.

An Agency may not conduct or sponsor, and a person is not required to respond to a collection of information, unless it displays a currently valid OMB control number. The OMB control numbers for EPA's regulations are listed in 40 CFR part 9 and 48 CFR chapter 15.

C. Regulatory Flexibility Act

The Regulatory Flexibility Act generally requires an agency to prepare

a regulatory flexibility analysis of any rule subject to notice and comment rulemaking requirements under the Administrative Procedure Act or any other statute, unless the agency certifies that the rule will not have a significant economic impact on a substantial number of small entities. Small entities include small businesses, small organizations, and small governmental jurisdictions.

For purposes of assessing the impacts of today's rule on small entities, small entity is defined as: (1) A small business that is independently owned and operated and not dominant in its field as defined by Small Business Administration (SBA) regulations under Section 3 of the Small Business Act for SIC; (2) a small governmental jurisdiction that is a government of a city, county, town, school district or special district with a population of less than 50,000; and (3) a small organization that is any not-for-profit enterprise which is independently owned and operated and is not dominant in its field.

After considering the economic impacts of today's final rule on small entities, I certify that this action will not have a significant economic impact on a substantial number of small entities. In determining whether a rule has a significant economic impact on a substantial number of small entities, the impact of concern is any significant adverse economic impact on small entities, since the primary purpose of the regulatory flexibility analyses is to identify and address regulatory alternatives "which minimize any significant economic impact of the rule on small entities." 5 U.S.C. sections 603 and 604. Thus, an agency may certify that a rule will not have a significant economic impact on a substantial number of small entities if the rule relieves regulatory burden, or otherwise has a positive economic effect on all of the small entities subject to the rule. Today's rule is specifically intended to reduce economic burden for all entities. The action will provide greater flexibility and utility to all affected entities, including small entities, by providing an increase in choices of appropriate analytical methods for RCRA applications. It does not create any new regulatory requirements or require any new reports beyond those now required by the revised regulations. In addition, its revisions need not be adopted by regulated entities. If the methods are appropriate, such entities can continue to use the methods previously specified in the regulations before today instead of choosing the option to use other appropriate methods from other reliable sources. We have therefore concluded that today's final rule will relieve regulatory burden for small entities.

D. Unfunded Mandates Reform Act

Title II of the Unfunded Mandates Reform Act of 1995 (UMRA or the Act), Pubic Law 104–4, establishes requirements for Federal agencies to assess the effects of their regulatory actions on State, local, and tribal governments and the private sector. Under section 202 of UMRA, EPA generally must prepare a written statement, including a cost-benefit analysis, for proposed rules and final rules with Federal mandates that may result in estimated costs to State, local, and tribal governments in the aggregate, or to the private sector, of $100 million or more in any one year. When such a statement is needed, section 205 of the Act generally requires EPA to identify and consider a reasonable number of regulatory alternatives. Under section 205, EPA must adopt the least costly, most cost-effective or least burdensome alternative that achieves the objectives of the rule, unless the Administrator explains in the final rule why that alternative was not adopted. The provisions of section 205 do not apply when they are inconsistent with applicable law. Before EPA establishes regulatory requirements that may significantly or uniquely affect small governments, including tribal governments, it must develop under section 203 of the Act a small government agency plan. The plan must provide for notifying potentially affected small governments, giving them meaningful and timely input in the development of EPA regulatory proposals with significant Federal intergovernmental mandates, and informing, educating, and advising them on compliance with the regulatory requirements.

First, this rule does not contain a Federal mandate. The rule imposes no enforceable duty on any State, local or tribal governments. This rule contains no regulatory requirements that might significantly or uniquely affect small governments. This is due to the fact that this rule does not add any new regulatory requirements and States need not adopt its revisions. This rule only revises certain regulatory sections to remove the requirement to use SW–846 methods and allow the use of other appropriate methods—that is, clarify allowed flexibility in method selection for meeting RCRA-related testing and monitoring requirements. Under RCRA, regardless of the method used—the one previously specified in the regulation before today or another appropriate method—regulated entities should be demonstrating that the method is appropriate for its intended use. This rule also does not propose new monitoring or information collection requirements. The additional flexibility allowed by this rule should result in improved data quality at reduced cost. Thus, today's rule is not subject to the requirements of sections 202, 203 and 205 of UMRA.

E. Executive Order 13132: Federalism

Executive Order 13132, entitled "Federalism" (64 FR 43255, August 10, 1999), requires EPA to develop an accountable process to ensure "meaningful and timely input by State and local officials in the development of regulatory policies that have federalism implications." "Policies that have federalism implications" is defined in the Executive Order to include regulations that have "substantial direct effects on the States, on the relationship between the National Government and the States, or on the distribution of power and responsibilities among the various levels of government."

This final rule does not have federalism implications. It will not have substantial direct effects on the States, on the relationship between the National Government and the States, or on the distribution of power and responsibilities among the various levels of government, as specified in Executive Order 13132. As explained above, today's rule does not impose new requirements on the States and its regulatory changes need not be adopted by the States. Thus, Executive Order 13132 does not apply to this rule. Because these changes are equivalent to or less stringent than the existing Federal program, States would not be required to adopt and seek authorization for them.

F. Executive Order 13175: Consultation and Coordination With Indian Tribal Governments

Executive Order 13175 (65 FR 67249) entitled, "Consultation and Coordination With Indian Tribal Governments" requires EPA to develop an accountable process to ensure "meaningful and timely input by tribal officials in the development of regulatory policies that have tribal implications. "Policies that have tribal implications" are defined in the Executive Order to include regulations that have "substantial direct effects on one or more Indian tribes, or on the distribution of power and responsibilities between the Federal Government and Indian tribes."

Today's rule does not have tribal implications. It will not have substantial direct effects on tribal governments, on the relationship between the Federal Government and Indian tribes, or on the distribution of power and responsibilities between the Federal Government and Indian tribes, as specified in Executive Order 13175. For many of the same reasons described above under unfunded mandates, the requirements of the Executive Order do not apply to this rulemaking. As stated above, this rule does not propose any new regulatory requirements and Indian tribal governments need not adopt it. It does not impose any direct compliance costs on tribal governments.

G. Executive Order 13045: Protection of Children From Environmental Health Risks and Safety Risks

Executive Order 13045, "Protection of Children From Environmental Health Risks and Safety Risks" (62 FR 19885, April 23, 1997) applies to any rule that: (1) Is determined to be "economically significant" as defined under Executive Order 12866, and (2) concerns an environmental health or safety risk that EPA has reason to believe may have a disproportionate effect on children. If the regulatory action meets both criteria, the Agency must evaluate the environmental health or safety effects of the planned rule on children, and explain why the planned regulation is preferable to other potentially effective and reasonably feasible alternatives considered by the Agency.

This rule is not subject to the Executive Order because it is not economically significant as defined in Executive Order 12866. Also, EPA interprets Executive Order 13045 as applying only to those regulatory actions that are based on health or safety risks, such that the analysis required under section 5–501 of the Order has the potential to influence the regulation. This rule is not subject to Executive Order 13045 because it does not establish an environmental standard intended to mitigate health or safety risks. The action discussed in today's rule is intended to provide increased flexibility in the use of methods for RCRA-related testing and monitoring, and thus is not subject to Executive Order 13045.

H. Executive Order 13211: Actions That Significantly Affect Energy Supply, Distribution, or Use

This rule is not a "significant energy action" as defined in Executive Order 13211, "Actions Concerning Regulations that Significantly Affect Energy Supply, Distribution, or Use" (66 FR 28355, May 22, 2001) because it is not likely to have a significant adverse effect on the supply, distribution, or use of energy. Further, we have concluded that this rule is not likely to have any adverse energy effects.

I. National Technology Transfer and Advancement Act

Section 12(d) of the National Technology Transfer and Advancement Act of 1995 ("NTTAA"), Public Law No. 104–113, section 12(d) (15 U.S.C. 272 note) directs EPA to use voluntary consensus standards in its regulatory activities unless to do so would be inconsistent with applicable law or otherwise impractical. Voluntary consensus standards are technical standards (*e.g.*, materials specifications, test methods, sampling procedures, and business practices) that are developed or adopted by voluntary consensus standards bodies. The NTTAA directs us to provide Congress, through OMB, explanations when the Agency decides not to use available and applicable voluntary consensus standards.

This rule increases flexibility in the use of methods for RCRA-related testing and monitoring and does not itself identify or require the use of new methods or other technical standards. In fact, this rule, may increase the use of available voluntary consensus standards for some RCRA applications, provided that such methods are appropriate for the regulatory application.

J. Executive Order 12898: Federal Actions To Address Environmental Justice in Minority Populations and Low-Income Populations

Executive Order 12898, "Federal Actions to Address Environmental Justice in Minority Populations and Low-Income Populations," February 11, 1994, requires that regulatory actions be accompanied by an environmental justice analysis. This analysis must look at potentially disproportionate impacts the action may have on minority and/or low-income communities.

The Agency has determined that the action does not raise environmental justice concerns. The impact of this rule will be to provide increased flexibility in the choice of appropriate analytical methods for RCRA applications. The Agency is not aware of any disproportionate impacts that such flexibility may have on minority and/or low-income communities.

K. Congressional Review Act

The Congressional Review Act, 5 U.S.C. 801 *et seq.*, as added by the Small Business Regulatory Enforcement Fairness Act of 1996, generally provides that before a rule may take effect, the agency promulgating the rule must submit a rule report, which includes a copy of the rule, to each House of the Congress and to the Comptroller General of the United States. EPA will submit a report containing this rule and other required information to the U.S. Senate, the U.S. House of Representatives, and the Comptroller General of the United States prior to publication of the rule in the Federal Register. A major rule cannot take effect until 60 days after it is published in the **Federal Register**. This action is not a "major rule" as defined by 5 U.S.C. 804(2). This rule will be effective July 14, 2005.

List of Subjects

40 CFR Part 63

Environmental protection, Air pollution control, Hazardous substances, Reporting and recordkeeping requirements.

40 CFR Part 258

Environmental protection, Incorporation by reference, Reporting and recordkeeping requirements, Waste treatment and disposal, Water pollution control.

40 CFR Part 260

Environmental protection, Administrative practice and procedure, Confidential business information, Hazardous waste, Incorporation by reference, Reporting and recordkeeping requirements.

40 CFR Part 261

Environmental protection, Comparable fuels, syngas fuels, Excluded hazardous waste, Incorporation by reference, Reporting and recordkeeping requirements.

40 CFR Part 264

Environmental protection, Air pollution control, Hazardous waste, Incorporation by reference, Insurance, Packaging and containers, Reporting and recordkeeping requirements, Security measures, Surety bonds.

40 CFR Part 265

Environmental protection, Air pollution control, Hazardous waste, Incorporation by reference, Insurance, Packaging and containers, Reporting and recordkeeping requirements, Security measures, Surety bonds, Water supply.

40 CFR Part 266

Environmental protection, Energy, Hazardous waste, Incorporation by reference, Recycling, Reporting and recordkeeping requirements.

40 CFR Part 268

Environmental protection, Hazardous waste, Incorporation by reference, Reporting and recordkeeping requirements.

40 CFR Part 270

Environmental protection, Administrative practice and procedure, Confidential business information, Hazardous materials transportation, Hazardous waste, Reporting and recordkeeping requirements, Water pollution control, Water supply.

40 CFR Part 271

Environmental protection, Administrative practice and procedure, Confidential business information, Hazardous materials transportation, Hazardous waste, Indians-lands, Intergovernmental relations, Penalties, Reporting and recordkeeping requirements, Water pollution control, Water supply.

40 CFR Part 279

Environmental protection, Petroleum, Recycling, Reporting and recordkeeping requirements.

Dated: May 16, 2005.

Stephen L. Johnson,

Administrator.

■ For the reasons set out in the preamble, EPA amends title 40, chapter I, of the Code of Federal Regulations as follows:

PART 63—NATIONAL EMISSION STANDARDS FOR HAZARDOUS AIR POLLUTANTS FOR SOURCE CATEGORIES

■ 1. The authority citation for part 63 continues to read as follows:

Authority: 42 U.S.C. 7401 *et seq.*

Subpart EEE—National Emission Standards for Hazardous Air Pollutants From Hazardous Waste Combustors

■ 2. Section 63.1208 is amended by revising paragraph (b)(8) to read as follows:

§ 63.1208 What are the test methods?

* * * * *

(b) * * *

(8) *Feedstream analytical methods.* You may use any reliable analytical method to determine feedstream concentrations of metals, chlorine, and other constituents. It is your responsibility to ensure that the sampling and analysis procedures are unbiased, precise, and that the results are representative of the feedstream.

* * * * *

PART 258—CRITERIA FOR MUNICIPAL SOLID WASTE LANDFILLS

■ 3. The authority citation for part 258 continues to read as follows:

Authority: 33 U.S.C. 1345(d) and (e); 42 U.S.C 6902(a), 6907, 6912(a), 6944, 6945(c), and 6949a(c).

Subpart C—Operating Criteria

■ 4. Section 258.28 is amended by revising paragraph (c)(1) to read as follows:

§ 258.28 Liquids restrictions.

* * * * *

(c) * * *

(1) Liquid waste means any waste material that is determined to contain "free liquids" as defined by Method 9095B (Paint Filter Liquids Test), included in "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods" (EPA Publication SW–846) which is incorporated by reference. A suffix of "B" in the method number indicates revision two (the method has been revised twice). Method 9095B is dated November 2004. This incorporation by reference was approved by the Director of the Federal Register pursuant to 5 U.S.C. 552(a) and 1 CFR part 51. This material is incorporated as it exists on the date of approval and a notice of any change in this material will be published in the Federal Register. A copy may be inspected at the Library, U.S. Environmental Protection Agency, 1200 Pennsylvania Ave., NW. (3403T), Washington, DC 20460, *libraryhq@epa.gov;* or at the National Archives and Records Administration (NARA). For information on the availability of this material at NARA, call 202–741–6030, or go to: *http://www.archives.gov/federal_register/code_of_federal_regulations/ibr_locations.html.*

* * * * *

■ 5. Appendix I to part 258 is revised to read as follows:

Appendix I to Part 258—Constituents for Detection Monitoring

Common name[1]	CAS RN[2]
Inorganic Constituents:	
(1) Antimony	(Total)
(2) Arsenic	(Total)
(3) Barium	(Total)
(4) Beryllium	(Total)
(5) Cadmium	(Total)
(6) Chromium	(Total)
(7) Cobalt	(Total)
(8) Copper	(Total)
(9) Lead	(Total)
(10) Nickel	(Total)
(11) Selenium	(Total)
(12) Silver	(Total)
(13) Thallium	(Total)
(14) Vanadium	(Total)
(15) Zinc	(Total)
Organic Constituents:	
(16) Acetone	67–64–1
(17) Acrylonitrile 1	107–13–1
(18) Benzene	71–43–2
(19) Bromochloromethane	74–97–5
(20) Bromodichloromethane	75–27–4
(21) Bromoform; Tribromomethane	75–25–2
(22) Carbon disulfide	75–15–0
(23) Carbon tetrachloride	56–23–5

Common name[1]	CAS RN[2]
(24) Chlorobenzene	108–90–7
(25) Chloroethane; Ethyl chloride	75–00–3
(26) Chloroform; Trichloromethane	67–66–3
(27) Dibromochloromethane; Chlorodibromomethane	124–48–1
(28) 1,2-Dibromo-3-chloropropane; DBCP	96–12–8
(29) 1,2-Dibromoethane; Ethylene dibromide; EDB	106–93–4
(30) o-Dichlorobenzene; 1,2-Dichlorobenzene	95–50–1
(31) p-Dichlorobenzene; 1,4-Dichlorobenzene	106–46–7
(32) trans-1, 4-Dichloro-2-butene	110–57–6
(33) 1,1-Dichlorethane; Ethylidene chloride	75–34–3
(34) 1,2-Dichlorethane; Ethylene dichloride	107–06–2
(35) 1,1-Dichloroethylene; 1,1-Dichloroethene; Vinylidene chloride	75–35–4
(36) cis-1,2-Dichloroethylene; cis-1,2-Dichloroethene	156–59–2
(37) trans-1, 2-Dichloroethylene; trans-1,2-Dichloroethene	156–60–5
(38) 1,2-Dichloropropane; Propylene dichloride	78–87–5
(39) cis-1,3-Dichloropropene	10061–01–5
(40) trans-1,3-Dichloropropene	10061–02–6
(41) Ethylbenzene	100–41–4
(42) 2-Hexanone; Methyl butyl ketone	591–78–6
(43) Methyl bromide; Bromomethane	74–83–9
(44) Methyl chloride; Chloromethane	74–87–3
(45) Methylene bromide; Dibromomethane	74–95–3
(46) Methylene chloride; Dichloromethane	75–09–2
(47) Methyl ethyl ketone; MEK; 2-Butanone	78–93–3
(48) Methyl iodide; Idomethane	74–88–4
(49) 4-Methyl-2-pentanone; Methyl isobutyl ketone	108–10–1
(50) Styrene	100–42–5
(51) 1,1,1,2-Tetrachloroethane	630–20–6
(52) 1,1,2,2-Tetrachloroethane	79–34–5
(53) Tetrachloroethylene; Tetrachloroethene; Perchloroethylene	127–18–4
(54) Toluene	108–88–3
(55) 1,1,1-Trichloroethane; Methylchloroform	71–55–6
(56) 1,1,2-Trichloroethane	79–00–5
(57) Trichloroethylene; Trichloroethene	79–01–6
(58) Trichlorofluoromethane; CFC–11	75–69–4
(59) 1,2,3-Trichloropropane	96–18–4
(60) Vinyl acetate	108–05–4
(61) Vinyl chloride	75–01–4
(62) Xylenes	1330–20–7

[1] Common names are those widely used in government regulations, scientific publications, and commerce; synonyms exist for many chemicals.

[2] Chemical Abstract Service registry number. Where "Total" is entered, all species in the ground water that contain this element are included.

■ 6. Appendix II to part 258 is revised to read as follows:

Appendix II to Part 258—List of Hazardous Inorganic and Organic Constituents

Common name[1]	CAS RN[2]	Chemical abstracts service index name[3]
Acenaphthene	83–32–9	Acenaphthylene, 1,2-dihydro-
Acenaphthylene	208–96–8	Acenaphthylene
Acetone	67–64–1	2-Propanone
Acetonitrile; Methyl cyanide	75–05–8	Acetonitrile
Acetophenone	98–86–2	Ethanone, 1-phenyl-
2-Acetylaminofluorene; 2-AAF	53–96–3	Acetamide, N–9H-fluoren-2-yl-
Acrolein	107–02–8	2-Propenal
Acrylonitrile	107–13–1	2-Propenenitrile
Aldrin	309–00–2	1,4:5,8-Dimethanonaphthalene, 1,2,3,4,10,10-hexachloro-1,4,4a,5,8,8a-hexahydro-(1,4,4a,5,8,8a)-
Allyl chloride	107–05–1	1-Propene, 3-chloro-
4-Aminobiphenyl	92–67–1	[1,1′-Biphenyl]- 4-amine
Anthracene	120–12–7	Anthracene
Antimony	(Total)	Antimony
Arsenic	(Total)	Arsenic
Barium	(Total)	Barium
Benzene	71–43–2	Benzene
Benzo[a]anthracene; Benzanthracene	56–55–3	Benz[a]anthracene
Benzo[b]fluoranthene	205–99–2	Benz[e]acephenanthrylene
Benzo[k]fluoranthene	207–08–9	Benzo[k]fluoranthene
Benzo[ghi]perylene	191–24–2	Benzo[ghi]perylene
Benzo[a]pyrene	50–32–8	Benzo[a]pyrene
Benzyl alcohol	100–51–6	Benzenemethanol

Common name[1]	CAS RN[2]	Chemical abstracts service index name[3]
Beryllium	(Total)	Beryllium
alpha-BHC	319–84–6	Cyclohexane, 1,2,3,4,5,6-hexachloro-,(1α,2α,3β,4α,5β,6β)-
beta-BHC	319–85–7	Cyclohexane, 1,2,3,4,5,6-hexachloro-,(1α,2β,3α,4β,5α,6β)-
delta-BHC	319–86–8	Cyclohexane, 1,2,3,4,5,6-hexachloro-,(1α,2α,3α,4β,5α,6β)-
gamma-BHC; Lindane	58–89–9	Cyclohexane, 1,2,3,4,5,6- hexachloro-,(1α,2α, 3β, 4α,5α,6β)-
Bis(2-chloroethoxy)methane	111–91–1	Ethane, 1,1′-[methylenebis (oxy)]bis [2-chloro-
Bis(2-chloroethyl)ether; Dichloroethyl ether	111–44–4	Ethane, 1,1′-oxybis[2-chloro-
Bis(2-chloro-1-methylethyl) ether; 2,2′-Dichlorodiisopropyl ether; DCIP, See footnote 4.	108–60–1	Propane, 2,2′-oxybis[1-chloro-
Bis(2-ethylhexyl) phthalate	117–81–7	1,2-Benzenedicarboxylic acid, bis(2-ethylhexyl)ester
Bromochloromethane; Chlorobromethane	74–97–5	Methane, bromochloro-
Bromodichloromethane; Dibromochloromethane	75–27–4	Methane, bromodichloro-
Bromoform; Tribromomethane	75–25–2	Methane, tribromo-
4-Bromophenyl phenyl ether	101–55–3	Benzene, 1-bromo-4-phenoxy-
Butyl benzyl phthalate; Benzyl butyl phthalate	85–68–7	1,2-Benzenedicarboxylic acid, butyl phenylmethyl ester
Cadmium	(Total)	Cadmium
Carbon disulfide	75–15–0	Carbon disulfide
Carbon tetrachloride	56–23–5	Methane, tetrachloro-
Chlordane	See footnote 5	4,7-Methano-1H-indene, 1,2,4,5,6,7,8,8-octachloro-2,3,3a,4,7,7a-hexahydro-
p-Chloroaniline	106–47–8	Benzenamine, 4-chloro-
Chlorobenzene	108–90–7	Benzene, chloro-
Chlorobenzilate	510–15–6	Benzeneacetic acid, 4-chloro--(4-chlorophenyl)--hydroxy-, ethyl ester.
p-Chloro-m-cresol; 4-Chloro-3-methylphenol	59–50–7	Phenol, 4-chloro-3-methyl-
Chloroethane; Ethyl chloride	75–00–3	Ethane, chloro-
Chloroform; Trichloromethane	67–66–3	Methane, trichloro-
2-Chloronaphthalene	91–58–7	Naphthalene, 2-chloro-
2-Chlorophenol	95–57–8	Phenol, 2-chloro-
4-Chlorophenyl phenyl ether	7005–72–3	Benzene, 1-chloro-4-phenoxy-
Chloroprene	126–99–8	1,3-Butadiene, 2-chloro-
Chromium	(Total)	Chromium
Chrysene	218–01–9	Chrysene
Cobalt	(Total)	Cobalt
Copper	(Total)	Copper
m-Cresol; 3-Methylphenol	108–39–4	Phenol, 3-methyl-
o-Cresol; 2-Methylphenol	95–48–7	Phenol, 2-methyl-
p-Cresol; 4-Methylphenol	106–44–5	Phenol, 4-methyl-
Cyanide	57–12–5	Cyanide
2,4-D; 2,4-Dichlorophenoxyacetic acid	94–75–7	Acetic acid, (2,4-dichlorophenoxy)-
4,4′-DDD	72–54–8	Benzene 1,1′-(2,2-dichloroethylidene) bis[4-chloro-
4,4′-DDE	72–55–9	Benzene, 1,1′-(dichloroethenylidene) bis[4-chloro-
4,4′-DDT	50–29–3	Benzene, 1,1′-(2,2,2-trichloroethylidene) bis[4-chloro-
Diallate	2303–16–4	Carbamothioic acid, bis(1-methylethyl)-, S- (2,3-dichloro-2-propenyl) ester.
Dibenz[a,h]anthracene	53–70–3	Dibenz[a,h]anthracene
Dibenzofuran	132–64–9	Dibenzofuran
Dibromochloromethane; Chlorodibromomethane	124–48–1	Methane, dibromochloro-
1,2-Dibromo-3-chloropropane; DBCP	96–12–8	Propane, 1,2-dibromo-3-chloro-
1,2-Dibromoethane; Ethylene dibromide; EDB	106–93–4	Ethane, 1,2-dibromo-
Di-n-butyl phthalate	84–74–2	1,2-Benzenedicarboxylic acid, dibutyl ester
o-Dichlorobenzene; 1,2-Dichlorobenzene	95–50–1	Benzene, 1,2-dichloro-
m-Dichlorobenzene; 1,3-Dichlorobenzene	541–73–1	Benzene, 1,3-dichloro-
p-Dichlorobenzene; 1,4-Dichlorobenzene	106–46–7	Benzene, 1,4-dichloro-
3,3′-Dichlorobenzidine	91–94–1	[1,1′-Biphenyl]-4,4′-diamine, 3,3′-dichloro-
trans-1,4-Dichloro-2-butene	110–57–6	2-Butene, 1,4-dichloro-, (E)-
Dichlorodifluoromethane; CFC 12	75–71–8	Methane, dichlorodifluoro-
1,1-Dichloroethane; Ethylidene chloride	75–34–3	Ethane, 1,1-dichloro-
1,2-Dichloroethane; Ethylene dichloride	107–06–2	Ethane, 1,2-dichloro-
1,1-Dichloroethylene; 1,1-Dichloroethene; Vinylidene chloride cis-1,2-Dichloroethylene; cis-1,2-Dichloroethene.	75–35–4 156–59–2	Ethene, 1,1-dichloro- Ethene, 1,2-dichloro-(Z)-
trans-1,2-Dichloroethylene; trans-1,2-Dichloroethene	156–60–5	Ethene, 1,2-dichloro-, (E)-
2,4-Dichlorophenol	120–83–2	Phenol, 2,4-dichloro-
2,6-Dichlorophenol	87–65–0	Phenol, 2,6-dichloro-
1,2-Dichloropropane	78–87–5	Propane, 1,2-dichloro-
1,3-Dichloropropane; Trimethylene dichloride	142–28–9	Propane, 1,3-dichloro-
2,2-Dichloropropane; Isopropylidene chloride	594–20–7	Propane, 2,2-dichloro-
1,1-Dichloropropene	563–58–6	1-Propene, 1,1-dichloro-
cis-1,3-Dichloropropene	10061–01–5	1-Propene, 1,3-dichloro-, (Z)-
trans-1,3-Dichloropropene	10061–02–6	1-Propene, 1,3-dichloro-, (E)-
Dieldrin	60–57–1	2,7:3,6-Dimethanonaphth [2,3-b]oxirene, 3,4,5,6,9,9-hexachloro-1a,2,2a,3,6,6a,7,7a-octahydro-, (1aα,2β,2aα,3β,6β,6aα,7β,7aα)-

Common name[1]	CAS RN[2]	Chemical abstracts service index name[3]
Diethyl phthalate	84–66–2	1,2-Benzenedicarboxylic acid, diethyl ester
O,O-Diethyl O–2-pyrazinyl phosphorothioate; Thionazin	297–97–2	Phosphorothioic acid, O,O-diethyl O-pyrazinyl ester.
Dimethoate	60–51–5	Phosphorodithioic acid, O,O-dimethyl S-[2-(methylamino)-2-oxoethyl] ester
p-(Dimethylamino)azobenzene	60–11–7	Benzenamine, N,N-dimethyl-4-(phenylazo)-
7,12-Dimethylbenz[a]anthracene	57–97–6	Benz[a]anthracene, 7,12-dimethyl-
3,3′-Dimethylbenzidine	119–93–7	[1,1′-Biphenyl]-4,4′-diamine, 3,3′-dimethyl-
alpha, &alpha-Dimethylphenethylamine	122–09–8	Benzeneethanamine,αα-dimethyl
2,4-Dimethylphenol; m-Xylenol	105–67–9	Phenol, 2,4-dimethyl-
Dimethyl phthalate	131–11–3	1,2-Benzenedicarboxylic acid, dimethyl ester
m-Dinitrobenzene	99–65–0	Benzene, 1,3-dinitro-
4,6-Dinitro-o-cresol; 4,6-Dinitro-2-methylphenol	534–52–1	Phenol, 2-methyl-4,6-dinitro-
2,4-Dinitrophenol	51–28–5	Phenol, 2,4-dinitro-
2,4-Dinitrotoluene	121–14–2	Benzene, 1-methyl-2,4-dinitro-
2,6-Dinitrotoluene	606–20–2	Benzene, 2-methyl-1,3-dinitro-
Dinoseb; DNBP; 2-sec-Butyl-4,6-dinitrophenol	88–85–7	Phenol, 2-(1-methylpropyl)-4,6-dinitro-
Di-n-octyl phthalate	117–84–0	1,2-Benzenedicarboxylic acid, dioctyl ester
Diphenylamine	122–39–4	Benzenamine, N-phenyl-
Disulfoton	298–04–4	Phosphorodithioic acid, O,O-diethyl S-[2-(ethylthio)ethyl] ester
Endosulfan I	959–98–8	6,9-Methano-2,4,3-benzodiox-athiepin, 6,7,8,9,10,10-hexachloro-1,5,5a,6,9,9a-hexahydro-, 3-oxide,
Endosulfan II	33213–65–9	6,9-Methano-2,4,3-benzodioxathiepin, 6,7,8,9,10,10-hexachloro- 1,5,5a,6,9,9a-hexahydro-, 3-oxide, (3α,5aα, 6β,9β, 9aα)-
Endosulfan sulfate	1031–07–8	6,9-Methano-2,4,3-benzodioxathiepin, 6,7,8,9,10,10-hexachloro-1,5,5a,6,9,9a-hexahydro-, 3,3-dioxide
Endrin	72–20–8	2,7:3,6-Dimethanonaphth[2,3-b]oxirene, 3,4,5,6,9,9-hexachloro-1a,2,2a,3,6,6a,7,7a-octahydro-, (1aα, 2β,2aβ, 3α,6α,6aβ,7β,7aα)-
Endrin aldehyde	7421–93–4	1,2,4-Methenocyclo-penta[cd]pentalene-5-carboxaldehyde,2,2a,3,3,4,7-hexachlorodecahydro-(1α,2β,2aβ,4β,4aβ,5β,6aβ,6bβ,7R*)-
Ethylbenzene	100–41–4	Benzene, ethyl-
Ethyl methacrylate	97–63–2	2-Propenoic acid, 2-methyl-, ethyl ester
Ethyl methanesulfonate	62–50–0	Methanesulfonic acid, ethyl ester
Famphur	52–85–7	Phosphorothioic acid, O-[4-[(dimethylamino)sulfonyl]phenyl]-O,O-dimethyl ester
Fluoranthene	206–44–0	Fluoranthene
Fluorene	86–73–7	9H-Fluorene
Heptachlor	76–44–8	4,7-Methano-1H-indene,1,4,5,6,7,8,8-heptachloro-3a,4,7,7a-tetrahydro-
Heptachlor epoxide	1024–57–3	2,5-Methano-2H-indeno[1,2-b]oxirene, 2,3,4,5,6,7,7-heptachlor-1a,1b,5,5a,6,6a,-hexahydr-,(1aα,1bβ, 2α,5α,5aβ,6β,6aα)
Hexachlorobenzene	118–74–1	Benzene, hexachloro-
Hexachlorobutadiene	87–68–3	1,3-Butadiene, 1,1,2,3,4,4-hexachloro-
Hexachlorocyclopentadiene	77–47–4	1,3-Cyclopentadiene, 1,2,3,4,5,5-hexachloro-
Hexachloroethane	67–72–1	Ethane, hexachloro-
Hexachloropropene	1888–71–7	1-Propene, 1,1,2,3,3,3-hexachloro-
2-Hexanone; Methyl butyl ketone	591–78–6	2-Hexanone
Indeno(1,2,3-cd)pyrene	193–39–5	Indeno[1,2,3-cd]pyrene
Isobutyl alcohol	78–83–1	1-Propanol, 2-methyl-
Isodrin	465–73–6	1,4,5,8-Dimethanonaphthalene,1,2,3,4,1 0,10-hexachloro-1,4,4a,5,8,8a hexahydro-(1α, 4α, 4aβ,5β,8β,8aβ)-
Isophorone	78–59–1	2-Cyclohexen-1-one, 3,5,5-trimethyl-
Isosafrole	120–58–1	1,3-Benzodioxole, 5-(1-propenyl)-
Kepone	143–50–0	1,3,4-Metheno-2H-cyclobuta-[cd]pentalen-2-one, 1,1a,3,3a,4,5,5,5a,5b,6-decachlorooctahydro-
Lead	(Total)	Lead
Mercury	(Total)	Mercury
Methacrylonitrile	126–98–7	2-Propenenitrile, 2-methyl-
Methapyrilene	91–80–5	1,2,Ethanediamine, N,N-dimethyl-N′-2-pyridinyl-N′-(2-thienylmethyl)-
Methoxychlor	72–43–5	Benzene, 1,1′-(2,2,2,trichloroethylidene)bis [4-methoxy-
Methyl bromide; Bromomethane	74–83–9	Methane, bromo-
Methyl chloride; Chloromethane	74–87–3	Methane, chloro-
3-Methylcholanthrene	56–49–5	Benz[j]aceanthrylene, 1,2-dihydro-3-methyl-
Methyl ethyl ketone; MEK; 2-Butanone	78–93–3	2-Butanone
Methyl iodide; Iodomethane	74–88–4	Methane, iodo-
Methyl methacrylate	80–62–6	2-Propenoic acid, 2-methyl-, methyl ester
Methyl methanesulfonate	66–27–3	Methanesulfonic acid, methyl ester
2-Methylnaphthalene	91–57–6	Naphthalene, 2-methyl-
Methyl parathion; Parathion methyl	298–00–0	Phosphorothioic acid, O,O-dimethyl

Common name [1]	CAS RN [2]	Chemical abstracts service index name [3]
4-Methyl-2-pentanone; Methyl isobutyl ketone	108–10–1	2-Pentanone, 4-methyl-
Methylene bromide; Dibromomethane	74–95–3	Methane, dibromo-
Methylene chloride; Dichloromethane	75–09–2	Methane, dichloro-
Naphthalene	91–20–3	Naphthalene
1,4-Naphthoquinone	130–15–4	1,4-Naphthalenedione
1-Naphthylamine	134–32–7	1-Naphthalenamine
2-Naphthylamine	91–59–8	2-Naphthalenamine
Nickel	(Total)	Nickel
o-Nitroaniline; 2-Nitroaniline	88–74–4	Benzenamine, 2-nitro-
m-Nitroaniline; 3-Nitroaniline	99–09–2	Benzenamine, 3-nitro-
p-Nitroaniline; 4-Nitroaniline	100–01–6	Benzenamine, 4-nitro-
Nitrobenzene	98–95–3	Benzene, nitro-
o-Nitrophenol; 2-Nitrophenol	88–75–5	Phenol, 2-nitro-
p-Nitrophenol; 4-Nitrophenol	100–02–7	Phenol, 4-nitro-
N-Nitrosodi-n-butylamine	924–16–3	1-Butanamine, N-butyl-N-nitroso-
N-Nitrosodiethylamine	55–18–5	Ethanamine, N-ethyl-N-nitroso-
N-Nitrosodimethylamine	62–75–9	Methanamine, N-methyl-N-nitroso-
N-Nitrosodiphenylamine	86–30–6	Benzenamine, N-nitroso-N-phenyl-
N-Nitrosodipropylamine; N-Nitroso-N-dipropylamine; Di-n-propylnitrosamine.	621–64–7	1-Propanamine, N-nitroso-N-propyl-
N-Nitrosomethylethalamine	10595–95–6	Ethanamine, N-methyl-N-nitroso-
N-Nitrosopiperidine	100–75–4	Piperidine, 1-nitroso-
N-Nitrosopyrrolidine	930–55–2	Pyrrolidine, 1-nitroso-
5-Nitro-o-toluidine	99–55–8	Benzenamine, 2-methyl-5-nitro-
Parathion	56–38–2	Phosphorothioic acid, O,O-diethyl-O-(4-nitrophenyl) ester
Pentachlorobenzene	608–93–5	Benzene, pentachloro-
Pentachloronitrobenzene	82–68–8	Benzene, pentachloronitro-
Pentachlorophenol	87–86–5	Phenol, pentachloro-
Phenacetin	62–44–2	Acetamide, N-(4-ethoxyphenyl)
Phenanthrene	85–01–8	Phenanthrene
Phenol	108–95–2	Phenol
p-Phenylenediamine	106–50–3	1,4-Benzenediamine
Phorate	298–02–2	Phosphorodithioic acid, O,O-diethyl S- [(ethylthio)methyl] ester
Polychlorinated biphenyls; PCBs	See footnote 6	1,1'-Biphenyl, chloro derivatives
Pronamide	23950–58–5	Benzamide, 3,5-dichloro-N-(1,1-dimethyl-2-propynyl)-
Propionitrile; Ethyl cyanide	107–12–0	Propanenitrile
Pyrene	129–00–0	Pyrene
Safrole	94–59–7	1,3-Benzodioxole, 5-(2- propenyl)-
Selenium	(Total)	Selenium
Silver	(Total)	Silver
Silvex; 2,4,5-TP	93–72–1	Propanoic acid, 2-(2,4,5- trichlorophenoxy)-
Styrene	100–42–5	Benzene, ethenyl-
Sulfide	18496–25–8	Sulfide
2,4,5-T; 2,4,5-Trichlorophenoxyacetic acid	93–76–5	Acetic acid, (2,4,5- trichlorophenoxy)-
2,3,7,8-TCDD; 2,3,7,8-Tetrachlorodibenzo- p-dioxin	1746–01–6	Dibenzo[b,e][1,4]dioxin, 2,3,7,8-tetrachloro-
1,2,4,5-Tetrachlorobenzene	95–94–3	Benzene, 1,2,4,5-tetrachloro-
1,1,1,2-Tetrachloroethane	630–20–6	Ethane, 1,1,1,2-tetrachloro-
1,1,2,2-Tetrachloroethane	79–34–5	Ethane, 1,1,2,2-tetrachloro-
Tetrachloroethylene; Tetrachloroethene; Perchloroethylene	127–18–4	Ethene, tetrachloro-
2,3,4,6-Tetrachlorophenol	58–90–2	Phenol, 2,3,4,6-tetrachloro-
Thallium	(Total)	Thallium
Tin	(Total)	Tin
Toluene	108–88–3	Benzene, methyl-
o-Toluidine	95–53–4	Benzenamine, 2-methyl-
Toxaphene	See footnote 7	Toxaphene
1,2,4-Trichlorobenzene	120–82–1	Benzene, 1,2,4-trichloro-
1,1,1-Trichloroethane; Methylchloroform	71–55–6	Ethane, 1,1,1-trichloro-
1,1,2-Trichloroethane	79–00–5	Ethane, 1,1,2-trichloro-
Trichloroethylene; Trichloroethene	79–01–6	Ethene, trichloro-
Trichlorofluoromethane; CFC–11	75–69–4	Methane, trichlorofluoro-
2,4,5-Trichlorophenol	95–95–4	Phenol, 2,4,5-trichloro-
2,4,6-Trichlorophenol	88–06–2	Phenol, 2,4,6-trichloro-
1,2,3-Trichloropropane	96–18–4	Propane, 1,2,3-trichloro-
O,O,O-Triethyl phosphorothioate	126–68–1	Phosphorothioic acid, O,O,O-triethyl ester
sym-Trinitrobenzene	99–35–4	Benzene, 1,3,5-trinitro-
Vanadium	(Total)	Vanadium
Vinyl acetate	108–05–4	Acetic acid, ethenyl ester
Vinyl chloride; Chloroethene	75–01–4	Ethene, chloro-
Xylene (total)	See footnote 8	Benzene, dimethyl-
Zinc	(Total)	Zinc

[1] Common names are those widely used in government regulations, scientific publications, and commerce; synonyms exist for many chemicals.

[2] Chemical Abstracts Service registry number. Where "Total" is entered, all species in the ground water that contain this element are included.
[3] CAS index names are those used in the 9th Cumulative Index.
[4] This substance is often called bis(2-chloroisopropyl) ether, the name Chemical Abstracts Service applies to its noncommercial isomer, propane, 2,2'-oxybis[2-chloro-(CAS RN 39638-32-9).
[5] Chlordane: This entry includes alpha-chlordane (CAS RN 5103-71-9), beta-chlordane (CAS RN 5103-74-2), gamma-chlordane (CAS RN 5566-34-7), and constituents of chlordane (CAS RN 57-74-9 and CAS RN 12789-03-6).
[6] Polychlorinated biphenyls (CAS RN 1336-36-3); this category contains congener chemicals, including constituents of Aroclor-1016 (CAS RN 12674-11-2), Aroclor-1221 (CAS RN 11104-28-2), Aroclor-1232 (CAS RN 11141-16-5), Aroclor-1242 (CAS RN 53469-21-9), Aroclor-1248 (CAS RN 12672-29-6), Aroclor-1254 (CAS RN 11097-69-1), and Aroclor-1260 (CAS RN 11096-82-5).
[7] Toxaphene: This entry includes congener chemicals contained in technical toxaphene (CAS RN 8001-35-2), i.e., chlorinated camphene.
[8] Xylene (total): This entry includes o-xylene (CAS RN 96-47-6), m-xylene (CAS RN 108-38-3), p-xylene (CAS RN 106-42-3), and unspecified xylenes (dimethylbenzenes) (CAS RN 1330-20-7).

PART 260—HAZARDOUS WASTE MANAGEMENT SYSTEM: GENERAL

■ 7. The authority citation for part 260 continues to read as follows:

Authority: 42 U.S.C. 6905, 6912(a), 6921–6927, 6930, 6934, 6935, 6937, 6938, 6939, and 6974.

Subpart B—Definitions

■ 8. Section 260.11 is revised to read as follows:

§ 260.11 References.

(a) When used in parts 260 through 270 of this chapter, the following publications are incorporated by reference. These incorporations by reference were approved by the Director of the Federal Register pursuant to 5 U.S.C. 552(a) and 1 CFR part 51. These materials are incorporated as they exist on the date of approval and a notice of any change in these materials will be published in the **Federal Register**. Copies may be inspected at the Library, U.S. Environmental Protection Agency, 1200 Pennsylvania Ave., NW. (3403T), Washington, DC 20460, *libraryhq@epa.gov;* or at the National Archives and Records Administration (NARA). For information on the availability of this material at NARA, call 202–741–6030, or go to: *http://www.archives.gov/federal_register/code_of_federal_regulations/ibr_locations.html.*

(b) The following materials are available for purchase from the American Society for Testing and Materials, 100 Barr Harbor Drive, P.O. Box C700, West Conshohocken, PA 19428–2959.

(1) ASTM D–93–79 or D–93–80, "Standard Test Methods for Flash Point by Pensky-Martens Closed Cup Tester," IBR approved for § 261.21.

(2) ASTM D–1946–82, "Standard Method for Analysis of Reformed Gas by Gas Chromatography," IBR approved for §§ 264.1033, 265.1033.

(3) ASTM D 2267–88, "Standard Test Method for Aromatics in Light Naphthas and Aviation Gasolines by Gas Chromatography," IBR approved for § 264.1063.

(4) ASTM D 2382–83, "Standard Test Method for Heat of Combustion of Hydrocarbon Fuels by Bomb Calorimeter (High-Precision Method)," IBR approved for §§ 264.1033, 265.1033.

(5) ASTM D 2879–92, "Standard Test Method for Vapor Pressure—Temperature Relationship and Initial Decomposition Temperature of Liquids by Isoteniscope," IBR approved for § 265.1084.

(6) ASTM D–3278–78, "Standard Test Methods for Flash Point for Liquids by Setaflash Closed Tester," IBR approved for § 261.21(a).

(7) ASTM E 168–88, "Standard Practices for General Techniques of Infrared Quantitative Analysis," IBR approved for § 264.1063.

(8) ASTM E 169–87, "Standard Practices for General Techniques of Ultraviolet-Visible Quantitative Analysis," IBR approved for § 264.1063.

(9) ASTM E 260–85, "Standard Practice for Packed Column Gas Chromatography," IBR approved for § 264.1063.

(10) ASTM E 926–88, "Standard Test Methods for Preparing Refuse-Derived Fuel (RDF) Samples for Analyses of Metals," Test Method C—Bomb, Acid Digestion Method.

(c) The following materials are available for purchase from the National Technical Information Service, 5285 Port Royal Road, Springfield, VA 22161; or for purchase from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402, (202) 512–1800.

(1) "APTI Course 415: Control of Gaseous Emissions," EPA Publication EPA–450/2–81–005, December 1981, IBR approved for §§ 264.1035, 265.1035, 270.24, 270.25.

(2) Method 1664, Revision A, n-Hexane Extractable Material (HEM; Oil and Grease) and Silica Gel Treated n-Hexane Extractable Material (SGT–HEM; Non-polar Material) by Extraction and Gravimetry, PB99–121949, IBR approved for part 261, appendix IX.

(3) The following methods as published in the test methods compendium known as "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods," EPA Publication SW–846, Third Edition. A suffix of "A" in the method number indicates revision one (the method has been revised once). A suffix of "B" in the method number indicates revision two (the method has been revised twice). A suffix of "C" in the method number indicates revision three (the method has been revised three times). A suffix of "D" in the method number indicates revision four (the method has been revised four times).

(i) Method 0010, dated September 1986 and in the Basic Manual, IBR approved for part 261, appendix IX.

(ii) Method 0020, dated September 1986 and in the Basic Manual, IBR approved for part 261, appendix IX.

(iii) Method 0030, dated September 1986 and in the Basic Manual, IBR approved for part 261, appendix IX.

(iv) Method 1320, dated September 1986 and in the Basic Manual, IBR approved for part 261, appendix IX.

(v) Method 1311, dated September 1992 and in Update I, IBR approved for part 261, appendix IX, and §§ 261.24, 268.7, 268.40.

(vi) Method 1330A, dated September 1992 and in Update I, IBR approved for part 261, appendix IX.

(vii) Method 1312 dated September 1994 and in Update II, IBR approved for part 261, appendix IX.

(viii) Method 0011, dated December 1996 and in Update III, IBR approved for part 261, appendix IX, and part 266, appendix IX.

(ix) Method 0023A, dated December 1996 and in Update III, IBR approved for part 261, appendix IX, part 266, appendix IX, and § 266.104.

(x) Method 0031, dated December 1996 and in Update III, IBR approved for part 261, appendix IX.

(xi) Method 0040, dated December 1996 and in Update III, IBR approved for part 261, appendix IX.

(xii) Method 0050, dated December 1996 and in Update III, IBR approved for part 261, appendix IX, part 266, appendix IX, and § 266.107.

(xiii) Method 0051, dated December 1996 and in Update III, IBR approved for part 261, appendix IX, part 266, appendix IX, and § 266.107.

(xiv) Method 0060, dated December 1996 and in Update III, IBR approved for part 261, appendix IX, § 266.106, and part 266, appendix IX.

(xv) Method 0061, dated December 1996 and in Update III, IBR approved for part 261, appendix IX, § 266.106, and part 266, appendix IX.

(xvi) Method 9071B, dated April 1998 and in Update IIIA, IBR approved for part 261, appendix IX.

(xvii) Method 1010A, dated November 2004 and in Update IIIB, IBR approved for part 261, appendix IX.

(xviii) Method 1020B, dated November 2004 and in Update IIIB, IBR approved for part 261, appendix IX.

(xix) Method 1110A, dated November 2004 and in Update IIIB, IBR approved for § 261.22 and part 261, appendix IX.

(xx) Method 1310B, dated November 2004 and in Update IIIB, IBR approved for part 261, appendix IX.

(xxi) Method 9010C, dated November 2004 and in Update IIIB, IBR approved for part

261, appendix IX and §§ 268.40, 268.44, 268.48.

(xxii) Method 9012B, dated November 2004 and in Update IIIB, IBR approved for part 261, appendix IX and §§ 268.40, 268.44, 268.48.

(xxiii) Method 9040C, dated November 2004 and in Update IIIB, IBR approved for part 261, appendix IX and § 261.22.

(xxiv) Method 9045D, dated November 2004 and in Update IIIB, IBR approved for part 261, appendix IX.

(xxv) Method 9060A, dated November 2004 and in Update IIIB, IBR approved for part 261, appendix IX, and §§ 264.1034, 264.1063, 265.1034, 265.1063.

(xxvi) Method 9070A, dated November 2004 and in Update IIIB, IBR approved for part 261, appendix IX.

(xxvii) Method 9095B, dated November 2004 and in Update IIIB, IBR approved, part 261, appendix IX, and §§ 264.190, 264.314, 265.190, 265.314, 265.1081, 268.32.

(d) The following materials are available for purchase from the National Fire Protection Association, 1 Batterymarch Park, P.O. Box 9101, Quincy, MA 02269–9101.

(1) "Flammable and Combustible Liquids Code" (1977 or 1981), IBR approved for §§ 264.198, 265.198.

(2) [Reserved]

(e) The following materials are available for purchase from the American Petroleum Institute, 1220 L Street, Northwest, Washington, DC 20005.

(1) API Publication 2517, Third Edition, February 1989, "Evaporative Loss from External Floating-Roof Tanks," IBR approved for § 265.1084.

(2) [Reserved]

(f) The following materials are available for purchase from the Environmental Protection Agency, Research Triangle Park, NC.

(1) "Screening Procedures for Estimating the Air Quality Impact of Stationary Sources, Revised", October 1992, EPA Publication No. EPA–450/R–92–019, IBR approved for part 266, appendix IX.

(2) [Reserved]

(g) The following materials are available for purchase from the Organisation for Economic Co-operation and Development, Environment Direcorate, 2 rue Andre Pascal, 75775 Paris Cedex 16, France.

(1) OECD Green List of Wastes (revised May 1994), Amber List of Wastes and Red List of Wastes (both revised May 1993) as set forth in Appendix 3, Appendix 4 and Appendix 5, respectively, to the OECD Council Decision C(92)39/FINAL (Concerning the Control of Transfrontier Movements of Wastes Destined for Recovery Operations), IBR approved for 262.89 of this chapter.

(2) [Reserved]

Subpart C—Rulemaking Petitions

■ 9. Section 260.21 is amended by revising paragraph (d) to read as follows:

§ 260.21 Petitions for equivalent testing or analytical methods.

* * * * *

(d) If the Administrator amends the regulations to permit use of a new testing method, the method will be incorporated by reference in § 260.11 and added to "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods," EPA Publication SW–846, U.S. Environmental Protection Agency, Office of Solid Waste, Washington, DC 20460.

■ 10. Section 260.22 is amended by revising paragraph (d)(1)(i) to read as follows:

§ 260.22 Petitions to amend part 261 to exclude a waste produced at a particular facility.

* * * * *

(d) * * *

(1) * * *

(i) Does not contain the constituent or constituents (as defined in Appendix VII of part 261 of this chapter) that caused the Administrator to list the waste; or

* * * * *

PART 261—IDENTIFICATION AND LISTING OF HAZARDOUS WASTE

■ 11. The authority citation for part 261 continues to read as follows:

Authority: 42 U.S.C. 6905, 6912(a), 6921, 6922, 6924(y), and 6938.

Subpart A—General

■ 12. Section 261.3 is amended by revising paragraph (a)(2)(v) introductory text to read as follows:

§ 261.3 Definition of hazardous waste.

(a) * * *

(2) * * *

(v) *Rebuttable presumption for used oil.* Used oil containing more than 1000 ppm total halogens is presumed to be a hazardous waste because it has been mixed with halogenated hazardous waste listed in subpart D of part 261 of this chapter. Persons may rebut this presumption by demonstrating that the used oil does not contain hazardous waste (for example, to show that the used oil does not contain significant concentrations of halogenated hazardous constituents listed in appendix VIII of part 261 of this chapter).

* * * * *

Subpart C—Characteristics of Hazardous Waste

■ 13. Section 261.21 is amended by revising paragraph (a)(1) to read as follows:

§ 261.21 Characteristic of ignitability.

(a) * * *

(1) It is a liquid, other than an aqueous solution containing less than 24 percent alcohol by volume and has flash point less than 60 °C (140 °F), as determined by a Pensky-Martens Closed Cup Tester, using the test method specified in ASTM Standard D 93–79 or D 93–80 (incorporated by reference, see § 260.11), or a Setaflash Closed Cup Tester, using the test method specified in ASTM Standard D 3278–78 (incorporated by reference, see § 260.11).

* * * * *

■ 14. Section 261.22 is amended by revising paragraphs (a)(1) and (2) to read as follows:

§ 261.22 Characteristic of corrosivity.

(a) * * *

(1) It is aqueous and has a pH less than or equal to 2 or greater than or equal to 12.5, as determined by a pH meter using Method 9040C in "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods," EPA Publication SW–846, as incorporated by reference in § 260.11 of this chapter.

(2) It is a liquid and corrodes steel (SAE 1020) at a rate greater than 6.35 mm (0.250 inch) per year at a test temperature of 55 °C (130 °F) as determined by Method 1110A in "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods," EPA Publication SW–846, and as incorporated by reference in § 260.11 of this chapter.

* * * * *

Subpart D—Lists of Hazardous Wastes

■ 15. Section 261.35 is amended by revising paragraphs (b)(2)(iii)(A) and (B) to read as follows:

§ 261.35 Deletion of certain hazardous waste codes following equipment cleaning and replacement.

* * * * *

(b) * * *

(2) * * *

(iii) * * *

(A) Rinses must be tested by using an appropriate method.

(B) "Not detected" means at or below the following lower method calibration limits (MCLs): The 2,3,7,8-TCDD-based MCL—0.01 parts per trillion (ppt), sample weight of 1000 g, IS spiking

level of 1 ppt, final extraction volume of 10–50 µL. For other congeners—multiply the values by 1 for TCDF/PeCDD/PeCDF, by 2.5 for HxCDD/HxCDF/HpCDD/HpCDF, and by 5 for OCDD/OCDF.

* * * * *

■ 16. Section 261.38 is amended by revising paragraph (c)(7) introductory text to read as follows:

§ 261.38 Comparable/Syngas Fuel Exclusion.

* * * * *

(c) * * *

(7) *Waste analysis plans.* The generator of a comparable/syngas fuel shall develop and follow a written waste analysis plan which describes the procedures for sampling and analysis of the hazardous waste to be excluded. The plan shall be followed and retained at the facility excluding the waste.

* * * * *

■ 17. Appendix I to part 261 is amended by revising paragraphs four and five to read as follows:

Appendix I to Part 261—Representative Sampling Methods

* * * * *

Containerized liquid waste—"COLIWASA."

Liquid waste in pits, ponds, lagoons, and similar reservoirs.—"Pond Sampler."

* * * * *

Appendices II and III to Part 261 [Removed and Reserved]

■ 18. Part 261 is amended by removing and reserving Appendices II and III.

■ 19. Appendix IX to part 261 is amended in Table 1:

■ a. In the entry for "Aptus, Inc, Coffeyville, Kansas," under the "Waste description" column, by revising paragraphs (2), (3), and (4);

■ b. In the entry for "Arkansas Department of Pollution Control and Ecology, Vertac Superfund site, Jacksonville, Arkansas," under the "Waste description" column, by revising the introductory text of paragraph (1) and by revising paragraph (3)(C);

■ c. In the entry for "Bekaert Corp., Dyersburg, TN," under the "Waste description" column, by revising paragraph (4)(B);

■ d. In the entry for "Bethlehem Steel Corporation, Sparrows Point, Maryland," under the "Waste description" column, by revising the introductory text of paragraph (1);

■ e. In the entry for "BMW Manufacturing Corporation, Greer, South Carolina," under the "Waste description" column, by revising the introductory text of paragraph (2);

■ f. In the entry for "DuraTherm, Incorporated, San Leon, Texas," under the "Waste description" column, by revising the introductory text of paragraph (3);

■ g. In the entry for "Eastman Chemical Company, Longview, Texas," under the "Waste description" column, by revising the introductory text of paragraph (3);

■ h. In the entry for "Envirite of Pennsylvania (formerly Envirite Corporation), York, Pennsylvania," under the "Waste description" column, by revising paragraph (2);

■ i. In the entry for "Geological Reclamation Operations and Waste Systems, Inc., Morrisville, PA," under the "Waste description" column, by revising the introductory text of paragraph (1);

■ j. In the entry for "McDonnell Douglas Corporation, Tulsa, Oklahoma," under the "Waste description" column, by revising paragraph (3);

■ k. In the entry for "Occidental Chemical, Ingleside, Texas," under the "Waste description" column, by revising the introductory text of paragraph (3);

■ l. By removing the entry for "OxyVinyls, L.P., Deer Park, TX;"

■ m. In the entry for "Rhodia, Houston, Texas," under the "Waste description" column, by revising the introductory text of paragraph (3);

■ n. In the entry for "Syntex Agribusiness, Springfield, MO," under the "Waste description" column, by revising paragraphs (2), (3), (4), (5), and (6);

■ o. In the entry for "Texas Eastman, Longview, Texas," under the "Waste description" column, by revising paragraph 3;

■ p. In the entry for "Tokusen USA, Inc., Conway, AR," under the "Waste description" column, by revising paragraph (2)(C), the introductory text of paragraph (3), and paragraphs (3)(A)(ii), (3)(B), and (3)(C)(ii);

■ q. In the entry for "Tyco Printed Circuit Group, Melbourne Division, Melbourne, Florida," under the "Waste description" column, by revising the introductory text of paragraph (1).

The revisions read as follows:

Appendix IX to Part 261—Wastes Excluded Under §§ 260.20 and 260.22

TABLE 1.—WASTES EXCLUDED FROM NON-SPECIFIC SOURCES

Facility	Address	Waste description
*	*	*
Aptus, Inc	Coffeyville, Kansas	(1) * * *

TABLE 1.—WASTES EXCLUDED FROM NON-SPECIFIC SOURCES—Continued

Facility	Address	Waste description
		(2) A minimum of four grab samples must be taken from each hopper (or other container) of kiln residue generated during each 24-hour run; all grabs collected during a given 24-hour run must then be composited to form one composite sample. A minimum of four grab samples must also be taken from each hopper (or other container) of spray dryer/baghouse residue generated during each 24-hour run; all grabs collected during a given 24-hour run must then be composited to form one composite sample. Prior to the disposal of the residues from each 24-hour run, a TCLP leachate test must be performed on these composite samples and the leachate analyzed for the TC toxic metals, nickel, and cyanide. If arsenic, chromium, lead or silver TC leachate test results exceed 1.6 ppm, barium levels exceed 32 ppm, cadmium or selenium levels exceed 0.3 ppm, mercury levels exceed 0.07 ppm, nickel levels exceed 10 ppm, or cyanide levels exceed 6.5 ppm, the wastes must be retreated to achieve these levels or must be disposed in accordance with subtitle C of RCRA. Analyses must be performed according to appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. (3) Aptus must generate, prior to the disposal of the residues, verification data from each 24 hour run for each treatment residue (i.e., kiln residue, spray dryer/baghouse residue) to demonstrate that the maximum allowable treatment residue concentrations listed below are not exceeded. Samples must be collected as specified in Condition (2). Analyses must be performed according to appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. Any residues which exceed any of the levels listed below must be retreated or must be disposed of as hazardous. Kiln residue and spray dryer/baghouse residue must not exceed the following levels: Aldrin—0.015 ppm, Benzene—9.7 ppm, Benzo(a)pyrene—0.43 ppm, Benzo(b)fluoranthene)—1.8 ppm, Chlordane—0.37 ppm, Chloroform—5.4 ppm, Chrysene—170 ppm, Dibenz(a,h)anthracene—0.083 ppm, 1,2-Dichloroethane—4.1 ppm, Dichloromethane—2.4 ppm, 2,4-Dichlorophenol—480 ppm, Dichlorvos—260 ppm, Disulfaton—23 ppm, Endosulfan I—310 ppm, Fluorene—120 ppm, Indeno(1,2,3,cd)-pyrene—330 ppm, Methyl parathion—210 ppm, Nitrosodiphenylamine—130 ppm, Phenanthrene—150 ppm, Polychlorinated biphenyls—0.31 ppm, Tetrachlorethylene—59 ppm, 2,4,5-TP (silvex)—110 ppm, 2,4,6-Trichlorophenol—3.9 ppm. (4) Aptus must generate, prior to disposal of residues, verification data from each 24-hour run for each treatment residue (i.e., kiln residue, spray dryer/baghouse residue) to demonstrate that the residues do not contain tetra-, penta-, or hexachlorodibenzo-p-dioxins or furans at levels of regulatory concern. Samples must be collected as specified in Condition (2). The TCDD equivalent levels for the solid residues must be less than 5 ppt. Any residues with detected dioxins or furans in excess of this level must be retreated or must be disposed of as acutely hazardous. For tetra- and penta-chlorinated dioxin and furan homologs, the maximum practical quantitation limit must not exceed 15 ppt for the solid residues. For hexachlorinated dioxin and furan homologs, the maximum practical quantitation limit must not exceed 37 ppt for the solid residues. * * * * *
Arkansas Department of Pollution Control and Ecology.	Vertac Superfund site, Jacksonville, Arkansas.	* * * * *

TABLE 1.—WASTES EXCLUDED FROM NON-SPECIFIC SOURCES—Continued

Facility	Address	Waste description
		(1) *Testing:* Sample collection and analyses (including quality control (QC) procedures) must be performed according to appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. * * * * * (3) * * * (C) *Chlorinated dioxins and furans:* 2,3,7,8-Tetrachlorodibenzo-p-dioxin equivalents, 4 x 10^{-7} ppm. The petitioned by-product must be analyzed for the tetra-, penta-, hexa-, and heptachlorodibenzo-p-dioxins, and the tetra-, penta-, hexa-, and heptachlorodibenzofurans to determine the 2, 3, 7, 8-tetra-chlorodibenzo-p-dioxin equivalent concentration. The analysis must be conducted using a measurement system that achieves practical quantitation limits of 15 parts per trillion (ppt) for the tetra- and penta-homologs, and 37 ppt for the hexa- and hepta-homologs. * * * * *
* * *	*	* * * * *
Bekaert Corp.	Dyersburg, TN	* * * * * (4) * * * (A) * * * (B) The sample for the annual testing shall be a representative composite sample for all constituents listed in paragraph (1).
Bethlehem Steel Corporation	Sparrows Point, Maryland	* * * * * (1) *Testing:* Sample collection and analyses (including quality control (QC) procedures) must be performed using appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. If EPA judges the stabilization process to be effective under the conditions used during the initial verification testing, BSC may replace the testing required in Condition (1)(A) with the testing required in Condition (1)(B). BSC must continue to test as specified in Condition (1)(A) until and unless notified by EPA in writing that testing in Condition (1)(A) may be replaced by Condition (1)(B) (to the extent directed by EPA). * * * * *
BMW Manufacturing Corporation	Greer, South Carolina	* * * * * (2) *Verification Testing Requirements:* Sample collection and analyses, including quality control procedures, must be performed using appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. Methods must meet Performance Based Measurement System Criteria in which the Data Quality Objectives are to demonstrate that representative samples of the BMW Sludge meet the delisting levels in Condition (1). * * * * *
* * *	*	* * * * *
DuraTherm, Incorporated	San Leon, Texas	* * * * *

TABLE 1.—WASTES EXCLUDED FROM NON-SPECIFIC SOURCES—Continued

Facility	Address	Waste description
		(3) *Verification Testing Requirements:* DuraTherm must perform sample collection and analyses, including quality control procedures, using appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. If EPA judges the process to be effective under the operating conditions used during the initial verification testing, DuraTherm may replace the testing required in Paragraph (3)(A) with the testing required in Paragraph (3)(B). DuraTherm must continue to test as specified in Paragraph (3)(A) until and unless notified by EPA in writing that testing in Paragraph (3)(A) may be replaced by Paragraph (3)(B).
		* * * * *
Eastman Chemical Company	Longview, Texas	* * * * *
		(3) *Verification Testing Requirements:* Eastman must perform sample collection and analyses, including quality control procedures, using appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. After completion of the initial verification period, Eastman may replace the testing required in Condition (3)(A) with the testing required in Condition (3)(B). Eastman must continue to test as specified in Condition (3)(A) until and unless notified by EPA in writing that testing in Condition (3)(A) may be replaced by Condition (3)(B).
		* * * * *
* * *	* * *	* * * * *
Envirite of Pennsylvania (formerly Envirite Corporation).	York, Pennsylvania	* * * * *
		(2) Each batch of treatment residue must be tested for leachable cyanide.If the leachable cyanide levels (using the EP Toxicity test without acetic acid adjustment) exceed 1.26 ppm, the waste must be re-treated or managed and disposed as a hazardous waste under 40 CFR Parts 262 to 265 and the permitting standards of 40 CFR Part 270.
		* * * * *
* * *	* * *	* * * * *
Geological Reclamation Operations and Systems, Inc.	Morrisville, Pennsylvania	* * * * *
		(1) *Testing:* Sample collection and analyses, including quality control (QC) procedures, must be performed using appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B.
		* * * * *
* * *	* * *	* * * * *
McDonnell Douglas Corporation	Tulsa, Oklahoma	* * * * *

TABLE 1.—WASTES EXCLUDED FROM NON-SPECIFIC SOURCES—Continued

Facility	Address	Waste description
		(3) *Verification Testing Requirements:* Sample collection and analyses, including quality control procedures, must be performed using appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. McDonnell Douglas must stabilize the previously unstabilized waste from the bottom portion of the northwest lagoon of the surface impoundment (which was closed as a landfill) using fly ash, kiln dust or similar accepted materials in batches of 500 cubic yards or less. McDonnell Douglas must analyze one composite sample from each batch of 500 cubic yards or less. A minimum of four grab samples must be taken from each waste pile (or other designated holding area) of stabilized waste generated from each batch run. Each composited batch sample must be analyzed, prior to disposal of the waste in the batch represented by that sample, for constituents listed in Condition (1). There are no verification testing requirements for the stabilized wastes in the upper portions of the northwest lagoon, the entire northeast lagoon, and the entire south lagoon of the surface impoundments which were closed as a landfill.
* * *	* * *	* * * * *
Occidental Chemical	Ingleside, Texas	* * * * *
		(3) *Verification Testing Requirements:* Sample collection and analyses, including quality control procedures, must be performed using appropriate methods. As applicable to the method-defined parameters of concern, any analyses requiring use of SW–846 methods incorporated by reference in 40 CFR 260.11 must use those methods without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. If EPA judges the incineration process to be effective under the operating conditions used during the initial verification testing, Occidental Chemical may replace the testing required in Condition (3)(A) with the testing required in Condition (3)(B). Occidental Chemical must continue to test as specified in Condition (3)(A) until and unless notified by EPA in writing that testing in Condition (3)(A) may be replaced by Condition (3)(B).
* * *	* * *	* * * * *
Rhodia	Houston, Texas	* * * * * *
		(3) *Verification Testing Requirements:* Rhodia must perform sample collection and analyses, including quality control procedures, using appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. If EPA judges the process to be effective under the operating conditions used during the initial verification testing, Rhodia may replace the testing required in Condition (3)(A) with the testing required in Condition (3)(B). Rhodia must continue to test as specified in Condition (3)(A) until and unless notified by EPA in writing that testing in Condition (3)(A) may be replaced by Condition (3)(B).
* * *	* * *	* * * * *
Syntex Agribusiness	Springfield, MO	* * * * *

TABLE 1.—WASTES EXCLUDED FROM NON-SPECIFIC SOURCES—Continued

Facility	Address	Waste description
		(2) Four grab samples of wastewater must be composited from the volume of filtered wastewater collected after each eight hour run and, prior to disposal the composite samples must be analyzed for the EP toxic metals, nickel, and cyanide. If arsenic, chromium, lead, and silver EP leachate test results exceed 0.61 ppm; barium levels exceed 12 ppm; cadmium and selenium levels exceed 0.12 ppm; mercury levels exceed 0.02 ppm; nickel levels exceed 6.1 ppm; or cyanide levels exceed 2.4 ppm, the wastewater must be retreated to achieve these levels or must be disposed in accordance with all applicable hazardous waste regulations. Analyses must be performed using appropriate methods. As applicable to the method- defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. (3) One grab sample must be taken from each drum of kiln and cyclone ash generated during each eight-hour run; all grabs collected during a given eight-hour run must then be composited to form one composite sample. A composite sample of four grab samples of the separator sludge must be collected at the end of each eight-hour run. Prior to the disposal of the residues from each eight-hour run, an EP leachate test must be performed on these composite samples and the leachate analyzed for the EP toxic metals, nickel, and cyanide (using a distilled water extraction for the cyanide extraction) to demonstrate that the following maximum allowable treatment residue concentrations listed below are not exceeded. Analyses must be performed using appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. Any residues which exceed any of the levels listed below must be retreated to achieve these levels or must be disposed in accordance with all applicable hazardous waste regulations. Maximum Allowable Solids Treatment Residue EP Leachate Concentrations (mg/L) Arsenic—1.6, Barium—32, Cadmium—0.32, Chromium—1.6, Lead—1.6, Mercury—0.065, Nickel—16, Selenium—0.32, Silver—1.6, Cyanide—6.5. (4) If Syntex stabilizes any of the kiln and cyclone ash or separator sludge, a Portland cement-type stabilization process must be used and Syntex must collect a composite sample of four grab samples from each batch of stabilized waste. An MEP leachate test must be performed on these composite samples and the leachate analyzed for the EP toxic metals, nickel, and cyanide (using a distilled water extraction for the cyanide leachate analysis) to demonstrate that the maximum allowable treatment residue concentrations listed in condition (3) are not exceeded during any run of the MEP extraction. Analyses must be performed using appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. Any residues which exceed any of the levels listed in Condition (3) must be retreated to achieve these levels or must be disposed in accordance with all applicable hazardous waste regulations. (If the residues are stabilized, the analyses required in this condition supercede the analyses required in Condition (3).)

TABLE 1.—WASTES EXCLUDED FROM NON-SPECIFIC SOURCES—Continued

Facility	Address	Waste description
		(5) Syntex must generate, prior to disposal of residues, verification data from each eight hour run from each treatment residue (i.e., kiln and cyclone ash, separator sludge, and filtered wastewater) to demonstrate that the maximum allowable treatment residue concentrations listed below are not exceeded. Samples must be collected as specified in Conditions (2) and (3). Analyses must be performed using appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. Any solid or liquid residues which exceed any of the levels listed below must be retreated to achieve these levels or must be disposed in accordance with Subtitle C of RCRA. Maximum Allowable Wastewater Concentrations (ppm): Benz(a)anthracene—1×10^{-7}, Benzo(a)pyrene—4×10^{-4}, Chloroform—0.07, Chrysene—0.002, Dibenz(a,h)anthracene—9×10^{-6}, 1,2-Dichloroethane—0.06, Dichloromethane—0.06, Indeno(1,2,3-cd)pyrene—0.002, Polychlorinated biphenyls—1×10^{-4}, 1,2,4,5-Tetrachlorobenzene—0.13, 2,3,4,6-Tetrachlorophenol—12, Toluene—120, Trichloroethylene—0.04, 2,4,5-Trichlorophenol—49, 2,4,6-Trichlorophenol—0.02, Maximum Allowable Solid Treatment Residue. Concentrations (ppm); Benz(a)anthracene—1.1, Benzo(a)pyrene—0.43, benzo(b)fluoranthene—1.8, Chloroform—5.4, Chrysene—170, Dibenz(a,h)anthracene—0.083, Dichloromethane—2.4, 1,2-Dichloroethane—4.1, Indeno(1,2,3-cd)pyrene—330, Polychlorinated biphenyls—0.31, 1,2,4,5-Tetrachlorobenzene—720, Trichloroethylene—6.6, 2,4,6-Trichlorophenol—3.9. (6) Syntex must generate, prior to disposal of residues, verification data from each eight-hour run for each treatment residue (i.e., kiln and cyclone ash, separator sludge, and filtered wastewater) to demonstrate that the residues do not contain tetra-, penta-, or hexachlorodibenzo-p-dioxins or furans at levels of regulatory concern. Samples must be collected as specified in Conditions (2) and (3). The TCDD equivalent levels for wastewaters must be less than 2 ppq and less than 5 ppt for the solid treatment residues. Any residues with detected dioxins or furans in excess of these levels must be retreated or must be disposed as acutely hazardous. For this analysis, Syntex must use appropriate methods. For tetra- and pentachloronated dioxin and furan homologs, the maximum practical quantitation limit must not exceed 15 ppt for solids and 120 ppq for wastewaters. For hexachlorinated homologs, the maximum practical quantitation limit must not exceed 37 ppt for solids and 300 ppq for wastewaters. * * * * *
* * *	*	* * * * *
Texas Eastman	Longview, Texas	* * * * * (3) *Verification Testing Requirements:* Sample collection and analyses, including quality control procedures, must be performed using appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. If EPA judges the incineration process to be effective under the operating conditions used during the initial verification testing described in Condition Texas Eastman may replace the testing required in Condition (4) with the testing required in Condition (5) below. Texas Eastman must, however, continue to test as specified in Condition (4) until notified by EPA in writing that testing in Condition (4) may be replaced by the testing described in Condition (5). * * * * *
Tokusen USA, Inc.	Conway, AR	* * * * * (2) * * * (B) * * *

TABLE 1.—WASTES EXCLUDED FROM NON-SPECIFIC SOURCES—Continued

Facility	Address	Waste description
		(C) If constituent levels in a sample exceed any of the delisting levels set in Paragraph (1), Tokusen must retreat the batches of waste used to generate the representative sample until it meets the levels. Tokusen must repeat the analyses of the treated waste. (D) * * * (3) *Verification Testing Requirements:* Tokusen must perform sample collection and analyses, including quality control procedures, using appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. If EPA judges the process to be effective under the operating conditions used during the initial verification testing, Tokusen may replace the testing required in Paragraph (3)(A) with the testing required in Paragraph (3)(B). Tokusen must continue to test as specified in Paragraph (3)(A) until and unless notified by EPA in writing that testing in Paragraph (3)(A) may be replaced by Paragraph (3)(B). (A) * * * (i) * * * * * * * * (ii) Make two composites of representative grab samples collected. * * * * * (B) *Subsequent Verification Testing:* Following written notification by EPA, Tokusen may substitute the testing conditions in (3)(B) for (3)(A). Tokusen must continue to monitor operating conditions, and analyze representative samples each quarter of operation during the first year of waste generation, using appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. The samples must represent the waste generated during the quarter. (C) * * * (i) * * * (ii) Following cancellation of the quarterly testing, Tokusen must continue to test a representative composite sample for all constituents listed in Paragraph (1) annually (by twelve months after final exclusion), using appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. * * * * *
*	*	* * * * *
Tyco Printed Circuit Group, Melbourne Division.	Melbourne, Florida	* * * * * (1) *Verification Testing Requirements:* Sample collection and analyses, including quality control procedures must be performed using appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CDFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. Methods must meet Performance Based Measurement System Criteria in which the Data Quality Objectives are to demonstrate that representative samples of the Tyco Sludge meet the delisting levels in Condition (3). * * * * *

TABLE 1.—WASTES EXCLUDED FROM NON-SPECIFIC SOURCES—Continued

Facility	Address	Waste description
*	* *	* * *

■ 20. Appendix IX to part 261 is amended in Table 2:

■ a. By removing the entry for "Bekaert Corp., Dyersburg, TN";

■ b. In the entry for "Bethlehem Steel Corp., Steelton, PA," under the "Waste description" column, by revising paragraphs (1) and (2);

■ c. In the entry for "Bethlehem Steel Corp., Johnston, PA," under the "Waste description" column, by revising paragraphs (1) and (2);

■ d. In the entry for "BF Goodrich Intermediates Company, Inc., Calvert City, Kentucky," under the "Waste description" column, by revising the introductory paragraph and by revising paragraphs (1)(B) and (3);

■ e. In the entry for "CF&I Steel Corporation, Pueblo, Colorado," under the "Waste description" column, by revising paragraphs (1) and (2);

■ f. In the entry for "Chaparral Steel Midlothian L.P., Midlothian, Texas," under the "Waste description" column, by revising paragraph (1) and the introductory text of paragraph (3);

■ g. In the entry for "Conversion Systems, Inc., Horsham, Pennsylvania," under the "Waste description" column, by revising the introductory text of paragraph (1);

■ h. In the entry for "DOE–RL, Richland, Washington," under the "Waste description" column, by revising the introductory text of paragraph (1) and by revising paragraph (3);

■ i. In the entry for "Envirite of Pennsylvania (formerly Envirite Corporation), York, Pennsylvania," under the "Waste description" column, by revising paragraph (2);

■ j. In the entry for "Heritage Environmental Services, LLC, at the Nucor Steel Facility, Crawfordsville, Indiana," under the "Waste Description" column, by revising paragraph (2);

■ k. In the entry for "Marathon Oil Co., Texas City, TX," under the "Waste description" column, by revising the introductory text of paragraph (1);

■ l. In the entry for "Occidental Chemical Corp, Muscle Shoals Plant, Sheffield, Alabama," under the "Waste description" column, by revising the introductory paragraph and by revising paragraphs (1)(A) and (3);

■ m. In the entry for "Occidental Chemical Corporation, Delaware City, Delaware," under the "Waste description" column, by revising the introductory paragraph and by revising paragraph (1)(A), the introductory text of paragraph (2) and by revising paragraph (3);

■ n. In the entry for "Oxy Vinyls, Deer Park, Texas," under the "Waste description" column, by revising the introductory text of paragraph (3);

■ o. By adding the entry for "OxyVinyls, L.P., Deer Park, TX," after the entry for "Oxy Vinyls, Deer Park, Texas;"

■ p. In the entry for "Roanoke Electric Steel Corp., Roanoke, VA," under the "Waste description" column, by revising paragraphs (1)(A), (1)(B), and (2);

■ q. In the entry for "USX Steel Corporation, USS Division, Southworks Plant, Gary Works, Chicago, Illinois," under the "Waste description" column, by revising the introductory text of paragraph (1) and by revising paragraphs (1)(A) and (2).

The revisions read as follows:

Appendix IX to Part 261—Wastes Excluded Under §§ 260.20 and 260.22

* * * * *

TABLE 2.—WASTES EXCLUDED FROM SPECIFIC SOURCES

Facility	Address	Waste description
*	* *	* * *
Bethlehem Steel Corp	Steelton, PA	* * * * *

(1) *Testing:*

(A) *Initial Testing:* During the first four weeks of operation of the full-scale treatment system, Bethlehem must collect representative grab samples of each treated batch of the CSEAFD and composite the grab samples daily. The daily composites, prior to disposal, must be analyzed for the EP leachate concentrations of all the EP toxic metals, nickel and cyanide (using distilled water in the cyanide extractions). Analyses must be performed using appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. Bethlehem must report the analytical test data obtained during this initial period no later than 90 days after the treatment of the first full-scale batch.

TABLE 2.—WASTES EXCLUDED FROM SPECIFIC SOURCES—Continued

Facility	Address	Waste description
		(B) *Subsequent Testing:* Bethlehem must collect representative grab samples from every treated batch of CSEAFD generated daily and composite all of the grab samples to produce a weekly composite sample. Bethlehem then must analyze each weekly composite sample for the EP leachate concentrations of all the EP toxic metals and nickel. Analyses must be performed using appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. The analytical data, including all quality control information, must be compiled and maintained on site for a minimum of three years. These data must be furnished upon request and made available for inspection by any employee or representative of EPA or the State of Pennsylvania. (2) *Delisting Levels:* If the EP extract concentrations resulting from the testing in condition (1)(A) or (1)(B) for chromium, lead, arsenic, or silver exceeds 0.315 mg/l; for barium exceeds 6.3 mg/l; for cadmium or selenium exceed 0.063 mg/l; for mercury exceeds 0.0126 mg/l; for nickel exceeds 3.15 mg/l; or for cyanide exceeds 4.42 mg/l, the waste must either be re-treated or managed and disposed in accordance with subtitle C of RCRA.
Bethlehem Steel Corp	Johnstown, PA	* * * * * (1) *Testing:* (A) *Initial Testing:* During the first four weeks of operation of the full-scale treatment system, Bethlehem must collect representative grab samples of each treated batch of the CSEAFD and composite the grab samples daily. The daily composites, prior to disposal, must be analyzed for the EP leachate concentrations of all the EP toxic metals, nickel, and cyanide (using distilled water in the cyanide extractions). Analyses must be performed using appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. Bethlehem must report the analytical test data obtained during this initial period no later than 90 days after the treatment of the first full-scale batch. (B) *Subsequent Testing:* Bethlehem must collect representative grab samples from every treated batch of CSEAFD generated daily and composite all of the grab samples to produce a weekly composite sample. Bethlehem then must analyze each weekly composite sample for the EP leachate concentrations of all the EP toxic metals and nickel. Analyses must be performed using appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. The analytical data, including all quality control information, must be compiled and maintained on site for a minimum of three years. These data must be furnished upon request and made available for inspection by any employee or representative of EPA or the State of Pennsylvania. (2) *Delisting Levels:* If the EP extract concentrations resulting from the testing in condition (1)(A) or (1)(B) for chromium, lead, arsenic, or silver exceed 0.315 mg/l; for barium exceeds 6.3 mg/l; for cadmium or selenium exceed 0.063 mg/l; for mercury exceeds 0.0126 mg/l; for nickel exceeds 3.15 mg/l; or for cyanide exceeds 4.42 mg/l, the waste must either be retreated until it meets these levels or managed and disposed in accordance with subtitle C of RCRA. * * * * *

TABLE 2.—WASTES EXCLUDED FROM SPECIFIC SOURCES—Continued

Facility	Address	Waste description
BF Goodrich Intermediates Company, Inc.	Calvert City, Kentucky	Brine purification muds and saturator insolubles (EPA Hazardous Waste No. K071) after August 18, 1989. This exclusion is conditional upon the collection and submission of data obtained from BFG's full-scale treatment system because BFG's original data was based on data presented by another petitioner using an identical treatment process. To ensure that hazardous constituents are not present in the waste at levels of regulatory concern once the full-scale treatment facility is in operation, BFG must implement a testing program. All sampling and analyses (including quality control procedures) must be performed using appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. This testing program must meet the following conditions for the exclusion to be valid: (1) * * * (B) Collect representative grab samples from every batch of treated mercury brine purification muds and treated saturator insolubles on a daily basis and composite the grab samples to produce two separate weekly composite samples (one of the treated mercury brine muds and one of the treated saturator insolubles). Prior to disposal of the treated batches, two weekly composite samples must be analyzed for the EP leachate concentrations of all the EP toxic metals (except mercury), nickel, and cyanide (using distilled water in the cyanide extractions). BFG must report the analytical test data, including all quality control data, obtained during this initial period no later than 90 days after the treatment of the first full-scale batch. (2) * * * (3) If, under condition (1) or (2), the EP leachate concentrations for chromium, lead, arsenic, or silver exceed 0.316 mg/l; for barium exceeds 6.31 mg/l; for cadmium or selenium exceed 0.063 mg/l; for mercury exceeds 0.0126 mg/l, for nickel exceeds 3.16 mg/l; or for cyanide exceeds 4.42 mg/l, the waste must either be retreated until it meets these levels or managed and disposed of in accordance with subtitle C of RCRA.
		* * * * * * * * * *
CF&I Steel Corporation	Pueblo, Colorado	(1) *Testing:* (A) *Initial Testing:* During the first four weeks of operation of the full-scale treatment system, CF&I must collect representative grab samples of each treated batch of the CSEAFD and composite the grab samples daily. The daily composites, prior to disposal, must be analyzed for the EP leachate concentrations of all the EP toxic metals, nickel, and cyanide (using distilled water in the cyanide extractions). Analyses must be performed using appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. CF&I must report the analytical test data obtained during this initial period no later than 90 days after the treatment of the first full-scale batch.

TABLE 2.—WASTES EXCLUDED FROM SPECIFIC SOURCES—Continued

Facility	Address	Waste description
		(B) *Subsequent Testing:* CF&I must collect representative grab samples from every treated batch of CSEAFD generated daily and composite all of the grab samples to produce a weekly composite sample. CF&I then must analyze each weekly composite sample for the EP leachate concentrations of all of the EP toxic metals and nickel. Analyses must be performed using appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. The analytical data, including all quality control information, must be compiled and maintained on site for a minimum of three years. These data must be furnished upon request and made available for inspection by any employee or representative of EPA or the State of Colorado. (2) *Delisting levels:* If the EP extract concentrations determined in conditions (1)(A) or (1)(B) for chromium, lead, arsenic, or silver exceed 0.315 mg/l; for barium exceeds 6.3 mg/l; for cadmium or selenium exceed 0.063 mg/l; for mercury exceeds 0.0126 mg/l; for nickel exceeds 3.15 mg/l; or for cyanide exceeds 4.42 mg/l, the waste must either be re-treated or managed and disposed in accordance with Subtitle C of RCRA.
Chaparral Steel Midlothian, L.P.	Midlothian, Texas	* * * * * (1) *Delisting Levels:* All concentrations for the constituent total lead in the approximately 2,500 cubic yards (500,000 gallons) per calender year of raw leachate from Landfill No. 3, storm water from the baghouse area, and other K061 wastewaters that is transferred from the storage tank to nonhazardous management must not exceed 0.69 mg/l (ppm). Constituents must be measured in the waste by appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. * * * * * (3) *Verification Testing Requirements:* Sample collection and analyses, including quality control procedures, must be performed using appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. Chaparral Steel must analyze one composite sample from each batch of untreated wastewater transferred from the hazardous waste storage tank to non-hazardous waste management. Each composited batch sample must be analyzed, prior to non-hazardous management of the waste in the batch represented by that sample, for the constituent lead as listed in Condition (1). Chaparral may treat the waste as specified in Condition (2). If EPA judges the treatment process to be effective during the operating conditions used during the initial verification testing, Chaparral Steel may replace the testing requirement in Condition (3)(A) with the testing requirement in Condition (3)(B). Chaparral must continue to test as specified in (3)(A) until and unless notified by EPA or designated authority that testing in Condition (3)(A) may be replaced by Condition (3)(B). * * * * *
Conversion Systems, Inc.	Horsham, Pennsylvania	* * * * *

TABLE 2.—WASTES EXCLUDED FROM SPECIFIC SOURCES—Continued

Facility	Address	Waste description
		(1) *Verification Testing Requirements:* Sample collection and analyses, including quality control procedures, must be performed using appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. * * * * *
DOE–RL	Richland, Washington	* * * * * (1) *Testing:* Sample collection and analyses (including quality control (QC) procedures) must be performed using appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. If EPA judges the treatment process to be effective under the operating conditions used during the initial verification testing, DOE may replace the testing required in Condition (1)(A) with the testing required in Condition (1)(B). DOE must continue to test as specified in Condition (1)(A) until notified by EPA in writing that testing in Condition (1)(A) may be replaced by Condition (1)(B). * * * * * (2) * * * (3) *Delisting Levels:* All total constituent concentrations in the waste samples must be measured using appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. All total constituent concentrations must be equal to or less than the following levels (ppm): Inorganic Constituents, Ammonium—10.0, Antimony—0.06, Arsenic—0.5, Barium—20.0, Beryllium—0.04, Cadmium—0.05, Chromium—1.0, Cyanide—2.0, Fluoride—40.0, Lead—0.15, Mercury—0.02, Nickel—1.0, Selenium—0.5, Silver—2.0, Vanadium—2.0, Zinc—100.0, Organic Constituents, Acetone—40.0, Benzene—0.05, Benzyl alcohol—100.0, 1-Butyl alcohol—40.0, Carbon tetrachloride—0.05, Chlorobenzene—1.0, Chloroform—0.1, Cresol—20.0, 1,4-Dichlorobenzene—0.75, 1,2-Dichloroethane—0.05, 1,1-Dichloroethylene—0.07, Di-n-octyl phthalate—7.0, Hexachloroethane—0.06, Methyl ethyl ketone—200.0, Methyl isobutyl ketone—30.0, Naphthalene—10.0, Tetrachloroethylene—0.05, Toluene—10.0, Tributyl phosphate—0.2, 1,1,1-Trichloroethane—2.0, 1,1,2-Trichloroethane—0.05, Trichloroethylene—0.05, Vinyl Chloride—0.02. * * * * *
* *	* *	* * * * *
Envirite of Pennsylvania (formerly Envirite Corporation).	York, Pennsylvania	* * * * * (2) Each batch of treatment residue (formerly must be tested for leachable cyanide. If the leachable cyanide levels Corporation) (using the EP Toxicity test without acetic acid adjustment) exceed 1.26 ppm, the waste must be re-treated or managed and disposed as a hazardous waste under 40 CFR Parts 262 to 265 and the permitting standards of 40 CFR Part 270. * * * * *
* *	* *	* * * * *
Heritage Environmental Services, LLC, at the Nucor Steel facility.	Crawfordsville, Indiana	* * * * *

TABLE 2.—WASTES EXCLUDED FROM SPECIFIC SOURCES—Continued

Facility	Address	Waste description
		(2) *Verification Testing:* On a monthly basis, Heritage or Nucor must analyze two samples of the waste using the TCLP, SW–846 Method 1311, with an extraction fluid of pH 12 ± 0.05 standard units and for the mercury determinative analysis of the leachate using an appropriate method. The constituent concentrations measured must be less than the delisting levels established in Paragraph (1). * * * * *
Marathon Oil Co	Texas City, TX	* * * * * (1) *Testing:* Sample collection and analyses (including quality control (QC) procedures) must be performed using appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. If EPA judges the treatment process to be effective under the operating conditions used during the initial verification testing, Marathon may replace the testing required in Condition (1)(A) with the testing required in Condition (1)(B). Marathon must continue to test as specified in Condition (1)(A), including testing for organics in Conditions (3)(B) and (3)(C), until and unless notified by EPA in writing that testing in Condition (1)(A) may be replaced by Condition (1)(B), or that testing for organics may be terminated as described in (1)(C) (to the extent directed by EPA). * * * * *
Occidental Chemical Corp., Muscle Shoals Plant.	Sheffield, Alabama	Retorted wastewater treatment sludge from the mercury cell process in chlorine production (EPA Hazardous Plant Waste No. K106) after September 19, 1989. This exclusion is conditional upon the submission of data obtained from Occidental's full-scale retort treatment system because Occidental's original data were based on a pilot-scale retort system. To ensure that hazardous constituents are not present in the waste at levels of regulatory concern once the full-scale treatment facility is in operation, Occidental must implement a testing program. All sampling and analyses (including quality control procedures) must be performed using appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. This testing program must meet the following conditions for the exclusion to be valid: (1) * * * (A) Collect representative grab samples from every batch of retorted material and composite the grab samples to produce a weekly composite sample. The weekly composite samples, prior to disposal or recycling, must be analyzed for the EP leachate concentrations of all the EP toxic metals (except mercury), nickel, and cyanide (using distilled water in the cyanide extractions). Occidental must report the analytical test data, including all quality control data, obtained during this initial period no later than 90 days after the treatment of the first full-scale batch. * * * * * (2) * * * (3) If, under condition (1) or (2), the EP leachate concentrations for chromium, lead, arsenic, or silver exceed 1.616 mg/l; for barium exceeds 32.3 mg/l; for cadmium or selenium exceed 0.323 mg/l; for mercury exceeds 0.065 mg/l, for nickel exceeds 16.15 mg/l; or for cyanide exceeds 22.61 mg/l, the waste must either be retreated until it meets these levels or managed and disposed of in accordance with subtitle C of RCRA. * * * * *

TABLE 2.—WASTES EXCLUDED FROM SPECIFIC SOURCES—Continued

Facility	Address	Waste description
Occidental Chemical Corporation	Delaware City, Delaware	Sodium chloride treatment muds (NaCl-TM), sodium chloride saturator cleanings (NaCl-SC), and potassium chloride treatment muds (KCl-TM) (all classified as EPA Hazardous Waste No. K071) generated at a maximum combined rate (for all three wastes) of 1,018 tons per year. This exclusion was published on April 29, 1991 and is conditioned upon the collection of data from Occidental's full-scale brine treatment system because Occidental's request for exclusion was based on data from a laboratory-scale brine treatment process. To ensure that hazardous constituents are not present in the waste at levels of regulatory concern once the full-scale treatment system is in operation, Occidental must implement a testing program for the petitioned waste. All sampling and analyses (including quality control (QC) procedures) must be performed using appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. This testing program must meet the following conditions for the exclusion to be valid: (1) * * * (A) Collect representative grab samples from each batch of the three treated wastestreams (sodium chloride saturator cleanings (NaCl-SC), sodium chloride treatment muds (NaCl-TM) and potassium chloride treatment muds (KCl-TM)) on an as generated basis and composite the samples to produce three separate weekly composite samples (of each type of K071 waste). The three weekly composite samples, prior to disposal, must be analyzed for the EP leachate concentrations of all the EP toxic metals (except mercury), nickel, and cyanide (using distilled water in the cyanide extractions). Occidental must report the waste volumes produced and the analytical test data, including all quality control data, obtained during this initial period, no later than 90 days after the treatment of the first full-scale batch. * * * (2) *Subsequent Testing:* After the first four weeks of full-scale treatment operations, Occidental must do the following; all sampling and analyses (including quality control procedures) must be performed using appropriate methods, and as applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B: * * * (3) If, under conditions (1) or (2), the EP leachate concentrations for chromium, lead, arsenic, or silver exceed 0.77 mg/l; for barium exceeds 15.5 mg/l; for cadmium or selenium exceed 0.16 mg/l; for mercury exceeds 0.031 mg/l, or for nickel or total cyanide exceed 10.9 mg/l, the waste must either be retreated or managed and disposed of in accordance with all applicable hazardous waste regulations. * * * * *
*	*	* * * * *
OxyVinyls	Deer Park, Texas	* * * * * (3) *Verification Testing Requirements:* Sample collection and analyses, including quality control procedures, must be performed using appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. If EPA judges the incineration process to be effective under the operating conditions used during the initial verification testing, OxyVinyls may replace the testing required in Condition (3)(A) with the testing required in Condition (3)(B). OxyVinyls must continue to test as specified in Condition (3)(A) until and unless notified by EPA in writing that testing in Condition (3)(A) may be replaced by Condition (3)(B).

TABLE 2.—WASTES EXCLUDED FROM SPECIFIC SOURCES—Continued

Facility	Address	Waste description
		* * * * *
OxyVinyls, L.P.	Deer Park, TX	Incinerator Offgas Scrubber Water (EPA Hazardous Waste Nos. K017, K019 and K020) generated at a maximum annual rate of 919,990 cubic yards per calendar year after April 22, 2004, and disposed in accordance with the TPDES permit. For the exclusion to be valid, OxyVinyls must implement a testing program that meets the following Paragraphs: (1) *Delisting Levels:* All total concentrations for those constituents must not exceed the following levels (mg/kg) in the incinerator offgas scrubber water. Incinerator offgas treatment scrubber water (i) Inorganic Constituents Antimony—0.0204; Arsenic—0.385; Barium—2.92; Beryllium—0.166; Cadmium—0.0225; Chromium—5.0; Cobalt—13.14; Copper—418.00; Lead—5.0; Nickel—1.13; Mercury—0.0111; Vanadium—0.838; Zinc—2.61 (ii) Organic Constituents Acetone—1.46; Bromoform—0.481; Bromomethane—8.2; Bromodichloromethane—0.0719; Chloroform—0.683; Dibromochloromethane—0.057; Iodomethane—0.19; Methylene Chloride—0.029; 2,3,7,8—TCDD equivalents as TEQ—0.0000926 (2) *Waste Management:* (A) OxyVinyls must manage as hazardous all incinerator offgas treatment scrubber water generated, until it has completed initial verification testing described in Paragraphs (3)(A) and (B), as appropriate, and valid analyses show that paragraph (1) is satisfied. (B) Levels of constituents measured in the samples of the incinerator offgas treatment scrubber water that do not exceed the levels set forth in Paragraph (1) are non-hazardous. OxyVinyls can manage and dispose the non-hazardous incinerator offgas treatment scrubber water according to all applicable solid waste regulations. (C) If constituent levels in a sample exceed any of the delisting levels set in Paragraph (1), OxyVinyls must collect one additional sample and perform the expedited analyses to confirm if the constituent exceeds the delisting level. If this sample confirms the exceedance, OxyVinyls must, from that point forward, treat the waste as hazardous until it is demonstrated that the waste again meets the levels set in Paragraph (1). OxyVinyls must notify EPA of the exceedance and resampling analytical results prior to disposing of the waste. (D) If the waste exceeds the levels in paragraph (1) OxyVinyls must manage and dispose of the waste generated under Subtitle C of RCRA from the time that it becomes aware of any exceedance. (E) Upon completion of the Verification Testing described in Paragraphs 3(A) and (B) as appropriate and the transmittal of the results to EPA, and if the testing results meet the requirements of Paragraph (1), OxyVinyls may proceed to manage its incinerator offgas treatment scrubber water as non-hazardous waste. If subsequent verification testing indicates an exceedance of the Delisting Levels in Paragraph (1), OxyVinyls must manage the incinerator offgas treatment scrubber water as a hazardous waste until two consecutive quarterly testing samples show levels below the Delisting Levels. (3) *Verification Testing Requirements:* OxyVinyls must perform sample collection and analyses, including quality control procedures, using appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. If EPA judges the process to be effective under the operating conditions used during the initial verification testing, OxyVinlys may replace the testing required in Paragraph (3)(A) with the testing required in Paragraph (3)(B). OxyVinyls must continue to test as specified in Paragraph (3)(A) until and unless notified by EPA in writing that testing in Paragraph (3)(A) may be replaced by Paragraph (3)(B).

TABLE 2.—WASTES EXCLUDED FROM SPECIFIC SOURCES—Continued

Facility	Address	Waste description
		(A) *Initial Verification Testing:* After EPA grants the final exclusion, OxyVinyls must do the following: (i) Within 60 days of this exclusion becoming final, collect four samples, before disposal, of the incinerator offgas treatment scrubber water. (ii) The samples are to be analyzed and compared against the delisting levels in Paragraph (1) (iii). Within sixty (60) days after the exclusion becomes final, OxyVinyls will report initial verification analytical test data, including analytical quality control information for the first sixty (30) days of operation after this exclusion becomes final of the incinerator offgas treatment scrubber water. If levels of constituents measured in the samples of the incinerator offgas treatment scrubber water that do not exceed the levels set forth in Paragraph (1) and are also non-hazardous in two consecutive quarters after the first thirty (30) days of operation after this exclusion, OxyVinyls can manage and dispose of the incinerator offgas treatment scrubber water according to all applicable solid water regulations after reporting the analytical results to EPA. (B) *Subsequent Verification Testing:* Following written notification by EPA, OxyVinyls may substitute the testing conditions in Paragraph (3)(B) for (3)(A). OxyVinyls must continue to monitor operating conditions, and analyze representative samples of each quarter of operation during the first year of waste generation. The samples must represent the waste generated during the quarter. After the first year of analytical sampling verification sampling can be performed on a single annual composite sample of the incinerator offgas treatment scrubber water. The results are to be compared to the delisting levels in Condition (1). (C) *Termination of Testing:* (i) After the first year of quarterly testing, if the Delisting Levels in Paragraph (1) are being met, OxyVinyls may then request that EPA stop requiring quarterly testing. After EPA notifies OxyVinyls in writing, the company may end quarterly testing. (ii) Following cancellation of the quarterly testing, OxyVinyls must continue to test a representative sample for all constituents listed in Paragraph (1) annually. (4) *Changes in Operating Conditions:* If OxyVinyls significantly changes the process described in its petition or starts any processes that generate(s) the waste that may or could significantly affect the composition or type of waste generated as established under Paragraph (1) (by illustration, but not limitation, changes in equipment or operating conditions of the treatment process), it must notify EPA in writing; OxyVinyls may no longer handle the wastes generated from the new process as nonhazardous until the wastes meet the delisting levels set in Paragraph (1) and it has received written approval to do so from EPA. (5) *Data Submittals:* OxyVinyls must submit the information described below. If OxyVinyls fails to submit the required data within the specified time or maintain the required records on-site for the specified time, EPA, at its discretion, will consider this sufficient basis to reopen the exclusion as described in Paragraph 6. OxyVinyls must: (A) Submit the data obtained through Paragraph 3 to the Section Chief, EPA Region 6 Corrective Action and Waste Minimization Section, 1445 Ross Avenue, Dallas, Texas 75202–2733, Mail Code, (6PD–C) within the time specified. (B) Compile records of operating conditions and analytical data from Paragraph (3), summarized, and maintained on-site for a minimum of five years. (C) Finish these records and data when EPA or the State of Texas request them for inspection.

TABLE 2.—WASTES EXCLUDED FROM SPECIFIC SOURCES—Continued

Facility	Address	Waste description
		(D) Send along with all data a signed copy of the following certification statement, to attest to the truth and accuracy of the data submitted: Under civil and criminal penalty of law for the making or submission of false or fraudulent statements or representations (pursuant to the applicable provisions of the Federal Code, which include, but may not be limited to, 18 U.S.C. 1001 and 42 U.S.C. 6928), I certify that the information contained in or accompanying this document is true, accurate and complete. As to the (those) identified section(s) of this document for which I cannot personally verify its (their) truth and accuracy, I certify as the company official having supervisory responsibility for the persons who, acting under my direct instructions, made the verification that this information is true, accurate and complete. If any of this information is determined by EPA in its sole discretion to be false, inaccurate or incomplete, and upon conveyance of this fact to the company, I recognize and agree that this exclusion of waste will be void as if its never had effect or to the extent directed by EPA and that the company will be liable for any actions taken in contravention of the company's RCRA and CERCLA obligations premised upon the company's reliance on the void exclusion. (6) *Reopener:* (A) If, anytime after disposal of the delisted waste OxyVinyls possesses or is otherwise made aware of any environmental data (including but not limited to leachate data or groundwater monitoring data) or any other data relevant to the delisted waste indicating that any constituent identified for the delisting verification testing is at a level higher than the delisting level allowed by the Regional Administrator or his delegate in granting the petition, then the facility must report the data, in writing, to the Regional Administrator or his delegate within 10 days of first possessing or being made aware of that data. (B) If the annual testing of the waste does not meet the delisting requirements in Paragraph 1, OxyVinyls must report the data, in writing, to the Regional Administrator or his delegate within 10 days of first possessing or being made aware of that data. (C) If OxyVinyls fails to submit the information described in paragraphs (5), (6)(A) or (6)(B) or if any other information is received from any source, the Regional Administrator or his delegate will make a preliminary determination as to whether the reported information requires EPA action to protect human health or the environment. Further action may include suspending, or revoking the exclusion, or other appropriate response necessary to protect human health and environment. (D) If the Regional Administrator or his delegate determines that the reported information does require action by EPA's Regional Administrator or his delegate will notify the facility in writing of the actions the Regional Administrator or his delegate believes are necessary to protect human health and the environment. The notice shall include a statement of the proposed action and a statement providing the facility with an opportunity to present information as to why the proposed EPA action is not necessary. The facility shall have 10 days from the date of the Regional Administrator or his delegate's notice to present such information. (E) Following the receipt of information from the facility described in paragraph (6)(D) or (of no information is presented under paragraph (6)(D)) the initial receipt of information described in paragraphs (5), (6)(A) or (6)(B), the Regional Administrator or his delegate will issue a final written determination describing EPA actions that are necessary to protect human health or the environment. Any require action described in the Regional Administrator or his delegate's determination shall become effective immediately, unless the Regional Administrator or his delegate provides otherwise. (7) *Notification Requirements:* OxyVinyls must do the following before transporting the delisted waste. Failure to provide this notification will result in a violation of the delisting petition and a possible revocation of the decision. (A) Provide a one-time written notification to any State Regulatory Agency to which or through which it will transport the delisted waste described above for disposal, 60 days before beginning such activities. (B) Update the one-time written notification if it ships the delisted waste into a different disposal facility. (C) Failure to provide this notification will result in a violation of the delisting variance and a possible revocation of the decision.

TABLE 2.—WASTES EXCLUDED FROM SPECIFIC SOURCES—Continued

Facility	Address	Waste description
*	*	*
Roanoke Electric Steel Corp	Roanoke, VA	* * * * *
		(1) * * *
		(A) *Initial Testing:* During the first four weeks of operation of the full-scale treatment system, Roanoke must collect representative grab samples of each treated batch of the CSEAFD and composite the grab samples daily. The daily composites, prior to disposal, must be analyzed for the EP leachate concentrations of all the EP toxic metals, nickel and cyanide (using distilled water in the cyanide extractions). Analyses must be performed using appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. Roanoke must report the analytical test data obtained during this initial period no later than 90 days after the treatment of the first full-scale batch.
		(B) *Subsequent Testing:* Roanoke must collect representative grab samples from every treated batch of CSEAFD generated daily and composite all of the grab samples to produce a weekly composite sample. Roanoke then must analyze each weekly composite sample for all of the EP toxic metals and nickel. Analyses must be performed using appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051,0060,0061, 1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B. The analytical data, including all quality control information, must be compiled and maintained on site for a minimum of three years. These data must be furnished upon request and made available for inspection for any employee or representative of EPA or the State of Virginia.
		(2) *Delisting levels:* If the EP extract concentrations for chromium, lead, arsenic, or silver exceed 0.315 mg/l; for barium exceeds 6.3 mg/l; for cadmium or selenium exceed 0.063 mg/l; for mercury exceeds 0.0126 mg/l, for nickel exceeds 3.15 mg/l, or for cyanide exceeds 1.26 mg/l, the waste must either be re-treated or managed and disposed in accordance with subtitle C of RCRA.
		* * * * *
*	*	*
USX Steel Corporation, USS Division, Southworks Plant, Gary Works.	Chicago, Illinois	
		(1) *Testing:* Sample collection and analyses (including quality control (QC) procedures) must be performed using appropriate methods. As applicable to the method-defined parameters of concern, analyses requiring the use of SW–846 methods incorporated by reference in 40 CFR 260.11 must be used without substitution. As applicable, the SW–846 methods might include Methods 0010, 0011, 0020, 0023A, 0030, 0031, 0040, 0050, 0051, 0060, 0061,1010A, 1020B, 1110A, 1310B, 1311, 1312, 1320, 1330A, 9010C, 9012B, 9040C, 9045D, 9060A, 9070A (uses EPA Method 1664, Rev. A), 9071B, and 9095B.
		(A) *Initial Testing:* During the first four weeks of operation of the full-scale treatment system, USX must collect representative grab samples of each treated batch of the CSEAFD and composite the grab samples daily. The daily composites, prior to disposal, must be analyzed for the EP leachate concentrations of all the EP toxic metals, nickel, and cyanide (using distilled water in the cyanide extractions). USX must report the analytical test data, including quality control information, obtained during this initial period no later than 90 days after the treatment of the first full-scale batch. * * *

TABLE 2.—WASTES EXCLUDED FROM SPECIFIC SOURCES—Continued

Facility	Address	Waste description
		(2) *Delisting levels:* If the EP extract concentrations for chromium, lead, arsenic, or silver exceed 0.315 mg/l; for barium exceeds 6.3 mg/l; for cadmium or selenium exceed 0.063 mg/l; for mercury exceeds 0.0126 mg/l; for nickel exceeds 3.15 mg/l; or for cyanide exceeds 4.42 mg/l, the waste must either be re-treated until it meets these levels or managed and disposed in accordance with subtitle C of RCRA.

* * * * *

Appendix IX to Part 261 [Amended]

■ 21. Appendix IX to part 261 is amended in Table 3 by removing the entry for "Bekaert Corp., Dyersburg, TN".

PART 264—STANDARDS FOR OWNERS AND OPERATORS OF HAZARDOUS WASTE TREATMENT, STORAGE, AND DISPOSAL FACILITIES

■ 22. The authority citation for part 264 continues to read as follows:

Authority: 42 U.S.C. 6905, 6912(a), 6924, 6925, 6927, 6928(h), and 6974.

Subpart J—Tank Systems

■ 23. Section 264.190 is amended by revising paragraph (a) to read as follows:

§ 264.190 Applicability.

* * * * *

(a) Tank systems that are used to store or treat hazardous waste which contains no free liquids and are situated inside a building with an impermeable floor are exempted from the requirements in § 264.193. To demonstrate the absence or presence of free liquids in the stored/treated waste, the following test must be used: Method 9095B (Paint Filter Liquids Test) as described in "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods," EPA Publication SW–846, as incorporated by reference in § 260.11 of this chapter.

* * * * *

Subpart N—Landfills

■ 24. Section 264.314 is amended by revising paragraph (c) to read as follows:

§ 264.314 Special requirements for bulk and containerized liquids.

* * * * *

(c) To demonstrate the absence or presence of free liquids in either a containerized or a bulk waste, the following test must be used: Method 9095B (Paint Filter Liquids Test) as described in "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods," EPA Publication SW–846, as incorporated by reference in § 260.11 of this chapter.

* * * * *

Subpart AA—Air Emission Standards for Process Vents

■ 25. Section 264.1034 is amended by revising paragraphs (c)(1)(ii), (c)(1)(iv), (d)(1)(iii) and (f) to read as follows:

§ 264.1034 Test methods and procedures.

* * * * *

(c) * * *

(1) * * *

(ii) Method 18 or Method 25A in 40 CFR part 60, appendix A, for organic content. If Method 25A is used, the organic HAP used as the calibration gas must be the single organic HAP representing the largest percent by volume of the emissions. The use of Method 25A is acceptable if the response from the high-level calibration gas is at least 20 times the standard deviation of the response from the zero calibration gas when the instrument is zeroed on the most sensitive scale.

* * * * *

(iv) Total organic mass flow rates shall be determined by the following equation:

(A) For sources utilizing Method 18.

$$E_h = Q_{2sd}\left\{\sum_{i=1}^{n} C_i MW_i\right\}[0.0416]\left[10^{-6}\right]$$

Where:

E_h = Total organic mass flow rate, kg/h;

Q_{2sd} = Volumetric flow rate of gases entering or exiting control device, as determined by Method 2, dscm/h;

n = Number of organic compounds in the vent gas;

C_i = Organic concentration in ppm, dry basis, of compound i in the vent gas, as determined by Method 18;

MW_i = Molecular weight of organic compound i in the vent gas, kg/kg-mol;

0.0416 = Conversion factor for molar volume, kg-mol/m3 (@ 293 K and 760 mm Hg);

10^{-6} = Conversion from ppm

(B) For sources utilizing Method 25A.

$E_h = (Q)(C)(MW)(0.0416)(10^{-6})$

Where:

E_h = Total organic mass flow rate, kg/h;

Q = Volumetric flow rate of gases entering or exiting control device, as determined by Method 2, dscm/h;

C = Organic concentration in ppm, dry basis, as determined by Method 25A;

MW = Molecular weight of propane, 44;

0.0416 = Conversion factor for molar volume, kg-mol/m3 (@ 293 K and 760 mm Hg);

10^{-6} = Conversion from ppm.

* * * * *

(d) * * *

(1) * * *

(iii) Each sample shall be analyzed and the total organic concentration of the sample shall be computed using Method 9060A (incorporated by reference under 40 CFR 260.11) of "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods," EPA Publication SW–846, or analyzed for its individual organic constituents.

* * * * *

(f) When an owner or operator and the Regional Administrator do not agree on whether a distillation, fractionation, thin-film evaporation, solvent extraction, or air or steam stripping operation manages a hazardous waste with organic concentrations of at least 10 ppmw based on knowledge of the waste, the dispute may be resolved by using direct measurement as specified at paragraph (d)(1) of this section.

Subpart BB—Air Emission Standards for Equipment Leaks

■ 26. Section 264.1063 is amended by revising paragraph (d)(2) to read as follows:

§ 264.1063 Test methods and procedures.

* * * * *

(d) * * *

(2) Method 9060A (incorporated by reference under 40 CFR 260.11) of "Test Methods for Evaluating Solid Waste,"

EPA Publication SW–846, for computing total organic concentration of the sample, or analyzed for its individual organic constituents; or

* * * * *

Subpart EE—Hazardous Waste Munitions and Explosives Storage

Appendix IX to Part 264—Ground-Water Monitoring List

■ 27. Appendix IX to part 264 is revised as follows:

GROUND-WATER MONITORING LIST

Common name[1]	CAS RN[2]	Chemical abstracts service index name[3]
Acenaphthene	83–32–9	Acenaphthylene, 1,2-dihydro-
Acenaphthylene	208–96–8	Acenaphthylene
Acetone	67–64–1	2-Propanone
Acetophenone	98–86–2	Ethanone, 1-phenyl-
Acetonitrile; Methyl cyanide	75–05–8	Acetonitrile
2-Acetylaminofluorene; 2-AAF	53–96–3	Acetamide, N–9H-fluoren-2-yl-
Acrolein	107–02–8	2-Propenal
Acrylonitrile	107–13–1	2-Propenenitrile
Aldrin	309–00–2	1,4:5,8-Dimethanonaphthalene, 1,2,3,4,10,10-hexachloro-1,4,4a,5,8,8a-hexahydro-(1α,4α,4aβ,5α,8α,8aβ)-
Allyl chloride	107–05–1	1-Propene, 3-chloro-
4-Aminobiphenyl	92–67–1	[1,1'-Biphenyl]-4-amine
Aniline	62–53–3	Benzenamine
Anthracene	120–12–7	Anthracene
Antimony	(Total)	Antimony
Aramite	140–57–8	Sulfurous acid, 2-chloroethyl 2-[4-(1,1-dimethylethyl) phenoxy]-1-methylethyl ester
Arsenic	(Total)	Arsenic
Barium	(Total)	Barium
Benzene	71–43–2	Benzene
Benzo[a]anthracene; Benzanthracene	56–55–3	Benz[a]anthracene
Benzo[b]fluoranthene	205–99–2	Benz[e]acephenanthrylene
Benzo[k]fluoranthene	207–08–9	Benzo[k]fluoranthene
Benzo[ghi]perylene	191–24–2	Benzo[ghi]perylene
Benzo[a]pyrene	50–32–8	Benzo[a]pyrene
Benzyl alcohol	100–51–6	Benzenemethanol
Beryllium	(Total)	Beryllium
alpha-BHC	319–84–6	Cyclohexane, 1,2,3,4,5,6-hexachloro-,(1α,2α,3β,4β,5β,6β)-
beta-BHC	319–85–7	Cyclohexane, 1,2,3,4,5,6-hexachloro-,(1α,2β,3α,4β,5α,6β)-
delta-BHC	319–86–8	Cyclohexane, 1,2,3,4,5,6-hexachloro-,(1α,2α,3α,4β,5α,6β)-
gamma-BHC; Lindane	58–89–9	Cyclohexane, 1,2,3,4,5,6-hexachloro-,(1α,2α,3β,4α,5α,6β)-
Bis(2-chloroethoxy)methane	111–91–1	Ethane, 1,1'-[methylenebis(oxy)]bis [2-chloro-
Bis(2-chloroethyl)ether	111–44–4	Ethane, 1,1'-oxybis[2-chloro-
Bis(2-chloro-1-methylethyl) ether; 2,2'-Dichlorodiisopropyl ether.	108–60–1	Propane, 2,2'-oxybis[1-chloro-
Bis(2-ethylhexyl) phthalate	117–81–7	1,2-Benzenedicarboxylic acid, bis(2-ethylhexyl)ester
Bromodichloromethane	75–27–4	Methane, bromodichloro-
Bromoform; Tribromomethane	75–25–2	Methane, tribromo-
4-Bromophenyl phenyl ether	101–55–3	Benzene, 1-bromo-4-phenoxy-
Butyl benzyl phthalate; Benzyl butyl phthalate	85–68–7	1,2-Benzenedicarboxylic acid, butyl phenylmethyl ester
Cadmium	(Total)	Cadmium
Carbon disulfide	75–15–0	Carbon disulfide
Carbon tetrachloride	56–23–5	Methane, tetrachloro-
Chlordane	57–74–9	4,7-Methano-1H-indene, 1,2,4,5,6,7,8,8-octachloro-2,3,3a,4,7,7a -hexahydro-
p-Chloroaniline	106–47–8	Benzenamine, 4-chloro-
Chlorobenzene	108–90–7	Benzene, chloro-
Chlorobenzilate	510–15–6	Benzeneacetic acid, 4-chloro-α-(4-chlorophenyl)-α-hydroxy-, ethyl ester
p-Chloro-m-cresol	59–50–7	Phenol, 4-chloro-3-methyl-
Chloroethane; Ethyl chloride	75–00–3	Ethane, chloro-
Chloroform	67–66–3	Methane, trichloro-
2-Chloronaphthalene	91–58–7	Naphthalene, 2-chloro-
2-Chlorophenol	95–57–8	Phenol, 2-chloro-
4-Chlorophenyl phenyl ether	7005–72–3	Benzene, 1-chloro-4-phenoxy-
Chloroprene	126–99–8	1,3-Butadiene,2-chloro-
Chromium	(Total)	Chromium
Chrysene	218–01–9	Chrysene
Cobalt	(Total)	Cobalt
Copper	(Total)	Copper
m-Cresol	108–39–4	Phenol, 3-methyl-
o-Cresol	95–48–7	Phenol, 2-methyl-
p-Cresol	106–44–5	Phenol, 4-methyl-
Cyanide	57–12–5	Cyanide
2,4-D; 2,4-Dichlorophenoxyacetic acids	94–75–7	Acetic acid, (2,4-dichlorophenoxy)-

GROUND-WATER MONITORING LIST—Continued

Common name[1]	CAS RN[2]	Chemical abstracts service index name[3]
4,4′-DDD	72–54–8	Benzene 1,1′-(2,2-dichloroethylidene) bis[4-chloro-
4,4′-DDE	72–55–9	Benzene, 1,1′-(dichloroethenylidene) bis[4-chloro-
4,4′-DDT	50–29–3	Benzene, 1,1′-(2,2,2-trichloroethylidene) bis[4-chloro-
Diallate	2303–16–4	Carbamothioic acid, bis(1-methylethyl)- , S- (2,3-dichloro-2-propenyl) ester
Dibenz[a,h]anthracene	53–70–3	Dibenz[a,h]anthracene
Dibenzofuran	132–64–9	Dibenzofuran
Dibromochloromethane; Chlorodibromomethane	124–48–1	Methane, dibromochloro-
1,2-Dibromo-3-chloropropane; DBCP	96–12–8	Propane, 1,2-dibromo-3-chloro-
1,2-Dibromoethane; Ethylene dibromide	106–93–4	Ethane, 1,2-dibromo-
Di-n-butyl phthalate	84–74–2	1,2-Benzenedicarboxylic acid, dibutyl ester
o-Dichlorobenzene	95–50–1	Benzene, 1,2-dichloro-
m-Dichlorobenzene	541–73–1	Benzene, 1,3-dichloro-
p-Dichlorobenzene	106–46–7	Benzene, 1,4-dichloro-
3,3′-Dichlorobenzidine	91–94–1	[1,1′-Biphenyl]-4,4′-diamine, 3,3′-dichloro-
trans-1,4-Dichloro-2-butene	110–57–6	2-Butene, 1,4-dichloro-, (E)-
Dichlorodifluoromethane	75–71–8	Methane, dichlorodifluoro-
1,1-Dichloroethane	75–34–3	Ethane, 1,1-dichloro-
1,2-Dichloroethane; Ethylene dichloride	107–06–2	Ethane, 1,2-dichloro-
1,1-Dichloroethylene; Vinylidene chloride	75–35–4	Ethene, 1,1-dichloro-
trans-1,2-Dichloroethylene	156–60–5	Ethene, 1,2-dichloro-, (E)-
2,4-Dichlorophenol	120–83–2	Phenol, 2,4-dichloro-
2,6-Dichlorophenol	87–65–0	Phenol, 2,6-dichloro-
1,2-Dichloropropane	78–87–5	Propane, 1,2-dichloro-
cis-1,3-Dichloropropene	10061–01–5	1-Propene, 1,3-dichloro-, (Z)-
trans-1,3-Dichloropropene	10061–02–6	1-Propene, 1,3-dichloro-, (E)-
Dieldrin	60–57–1	2,7:3,6-Dimethanonaphth [2,3-b]oxirene, 3,4,5,6,9,9-hexachloro-1a,2,2a,3,6,6a,7,7a-octahydro-, (1aα,2β,2aα,3β,6β,,6aα,7β,7aα)-
Diethyl phthalate	84–66–2	1,2-Benzenedicarboxylic acid, diethyl ester
O,O-Diethyl O-2-pyrazinyl phosphorothioate; Thionazin	297–97–2	Phosphorothioic acid, O,O-diethyl O-pyrazinyl ester
Dimethoate	60–51–5	Phosphorodithioic acid, O,O-dimethyl S-[2-(methylamino)-2-oxoethyl] ester
p-(Dimethylamino)azobenzene	60–11–7	Benzenamine, N,N-dimethyl-4-(phenylazo)-
7,12-Dimethylbenz[a]anthracene	57–97–6	Benz[a]anthracene, 7,12-dimethyl-
3,3′-Dimethylbenzidine	119–93–7	[1,1′-Biphenyl]-4,4′-diamine, 3,3′-dimethyl-
alpha, alpha-Dimethylphenethylamine	122–09–8	Benzeneethanamine, α,α-dimethyl-
2,4-Dimethylphenol	105–67–9	Phenol, 2,4-dimethyl-
Dimethyl phthalate	131–11–3	1,2-Benzenedicarboxylic acid, dimethyl ester
m-Dinitrobenzene	99–65–0	Benzene, 1,3-dinitro-
4,6-Dinitro-o-cresol	534–52–1	Phenol, 2-methyl-4,6-dinitro-
2,4-Dinitrophenol	51–28–5	Phenol, 2,4-dinitro-
2,4-Dinitrotoluene	121–14–2	Benzene, 1-methyl-2,4-dinitro-
2,6-Dinitrotoluene	606–20–2	Benzene, 2-methyl-1,3-dinitro-
Dinoseb; DNBP; 2-sec-Butyl-4,6-dinitrophenol	88–85–7	Phenol, 2-(1-methylpropyl)-4,6-dinitro-
Di-n-octyl phthalate	117–84–0	1,2-Benzenedicarboxylic acid, dioctyl ester
1,4-Dioxane	123–91–1	1,4-Dioxane
Diphenylamine	122–39–4	Benzenamine, N-phenyl-
Disulfoton	298–04–4	Phosphorodithioic acid, O,O-diethyl S-[2-(ethylthio)ethyl]ester
Endosulfan I	959–98–8	6,9-Methano-2,4,3- benzodioxathiepin, 6,7,8,9,10,10-hexachloro-1,5,5a,6,9,9a-hexahydro-, 3-oxide,(3α,5aβ,6α,9α,9aβ)-
Endosulfan II	33213–65–9	6,9-Methano-2,4,3- benzodioxathiepin, 6,7,8,9,10,10-hexachloro-1,5,5a,6,9,9a-hexahydro-, 3-oxide, (3α,5aα,6β,9β,9aα)-
Endosulfan sulfate	1031–07–8	6,9-Methano-2,4,3- benzodioxathiepin, 6,7,8,9,10,10-hexachloro-1,5,5a,6,9,9a-hexahydro-, 3,3-dioxide
Endrin	72–20–8	2,7:3,6-Dimethanonaphth[2,3-b]oxirene, 3,4,5,6,9,9-hexachloro-,1a,2,2a,3,6,6a,7,7a-octahydro-, (1aα,2β,2aβ,3α,6α,6aβ,7β, 7aα)-
Endrin aldehyde	7421–93–4	1,2,4- Methenocyclopenta[cd] pentalene-5-carboxaldehyde, 2,2a,3,3,4,7-hexachlorodecahydro-,(1α,2β,2aβ,4β,4aβ, 5β,6aβ,6bβ,7R*)-
Ethylbenzene	100–41–4	Benzene, ethyl-
Ethyl methacrylate	97–63–2	2-Propenoic acid, 2-methyl-, ethyl ester
Ethyl methanesulfonate	62–50–0	Methanesulfonic acid, ethyl ester
Famphur	52–85–7	Phosphorothioic acid, O-[4-[(dimethylamino)sulfonyl]phenyl]-O,O-dimethyl ester
Fluoranthene	206–44–0	Fluoranthene
Fluorene	86–73–7	9H-Fluorene
Heptachlor	76–44–8	4,7-Methano-1H-indene, 1,4,5,6,7,8,8-heptachloro-3a,4,7,7a-tetrahydro-

GROUND-WATER MONITORING LIST—Continued

Common name[1]	CAS RN[2]	Chemical abstracts service index name[3]
Heptachlor epoxide	1024–57–3	2,5-Methano-2H-indeno[1,2-b] oxirene, 2,3,4,5,6,7,7-heptachloro-1a,1b,5,5a,6,6a,-hexahydro-, (1aα,1bβ,2α,5α,5aβ,6β,6aα)
Hexachlorobenzene	118–74–1	Benzene, hexachloro-
Hexachlorobutadiene	87–68–3	1,3-Butadiene, 1,1,2,3,4,4-hexachloro-
Hexachlorocyclopentadiene	77–47–4	1,3-Cyclopentadiene, 1,2,3,4,5,5-hexachloro-
Hexachloroethane	67–72–1	Ethane, hexachloro-
Hexachlorophene	70–30–4	Phenol, 2,2'-methylenebis[3,4,6-trichloro-
Hexachloropropene	1888–71–7	1-Propene, 1,1,2,3,3,3-hexachloro-
2-Hexanone	591–78–6	2-Hexanone
Indeno(1,2,3-cd)pyrene	193–39–5	Indeno[1,2,3-cd]pyrene
Isobutyl alcohol	78–83–1	1-Propanol, 2-methyl-
Isodrin	465–73–6	1,4,5,8-Dimethanonaphthalene,1,2,3,4,1 0,10-hexachloro-1,4,4a,5,8,8a hexahydro-(1α, 4α, 4aβ, 5β, 8β, 8aβ)-
Isophorone	78–59–1	2-Cyclohexen-1-one, 3,5,5-trimethyl-
Isosafrole	120–58–1	1,3-Benzodioxole, 5-(1-propenyl)-
Kepone	143–50–0	1,3,4-Metheno-2H-cyclobuta-[cd]pentalen-2-one, 1,1a,3,3a,4,5,5,5a,5b,6-decachlorooctahydro-
Lead	(Total)	Lead
Mercury	(Total)	Mercury
Methacrylonitrile	126–98–7	2-Propenenitrile, 2-methyl-
Methapyrilene	91–80–5	1,2,Ethanediamine,N,N-dimethyl-N'-2-pyridinyl-N'-(2-thienylmethyl)-
Methoxychlor	72–43–5	Benzene, 1,1'-(2,2,2,trichloroethylidene)bis [4-methoxy-
Methyl bromide; Bromomethane	74–83–9	Methane, bromo-
Methyl chloride; Chloromethane	74–87–3	Methane, chloro-
3-Methylcholanthrene	56–49–5	Benz[j]aceanthrylene, 1,2-dihydro-3-methyl-
Methylene bromide; Dibromomethane	74–95–3	Methane, dibromo-
Methylene chloride; Dichloromethane	75–09–2	Methane, dichloro-
Methyl ethyl ketone; MEK;	78–93–3	2-Butanone
Methyl iodide; Iodomethane	74–88–4	Methane, iodo-
Methyl methacrylate	80–62–6	2-Propenoic acid, 2-methyl-, methyl ester
Methyl methanesulfonate	66–27–3	Methanesulfonic acid, methyl ester
2-Methylnaphthalene	91–57–6	Naphthalene, 2-methyl-
Methyl parathion; Parathion methyl	298–00–0	Phosphorothioic acid, O,O-dimethyl O=(4-nitrophenyl) ester
4-Methyl-2-pentanone; Methyl isobutyl ketone	108–10–1	2-Pentanone, 4-methyl-
Naphthalene	91–20–3	Naphthalene
1,4-Naphthoquinone	130–15–4	1,4-Naphthalenedione
1-Naphthylamine	134–32–7	1-Naphthalenamine
2-Naphthylamine	91–59–8	2-Naphthalenamine
Nickel	(Total)	Nickel
o-Nitroaniline	88–74–4	Benzenamine, 2-nitro-
m-Nitroaniline	99–09–2	Benzenamine, 3-nitro-
p-Nitroaniline	100–01–6	Benzenamine, 4-nitro-
Nitrobenzene	98–95–3	Benzene, nitro-
o-Nitrophenol	88–75–5	Phenol, 2-nitro-
p-Nitrophenol	100–02–7	Phenol, 4-nitro-
4-Nitroquinoline 1-oxide	56–57–5	Quinoline, 4-nitro, 1-oxide
N-Nitrosodi-n-butylamine	924–16–3	1-Butanamine, N-butyl-N-nitroso-
N-Nitrosodiethylamine	55–18–5	Ethanamine, N-ethyl-N-nitroso-
N-Nitrosodimethylamine	62–75–9	Methanamine, N-methyl-N-nitroso-
N-Nitrosodiphenylamine	86–30–6	Benzenamine, N-nitroso-N-phenyl-
N-Nitrosodipropylamine;Di-n-propylnitrosamine	621–64–7	1-Propanamine, N-nitroso-N-propyl-
N-Nitrosomethylethalamine	10595–95–6	Ethanamine, N-methyl-N-nitroso-
N-Nitrosomorpholine	59–89–2	Morpholine, 4-nitroso-
N-Nitrosopiperidine	100–75–4	Piperidine, 1-nitroso-
N-Nitrosopyrrolidine	930–55–2	Pyrrolidine, 1-nitroso-
5-Nitro-o-toluidine	99–55–8	Benzenamine, 2-methyl-5-nitro-
Parathion	56–38–2	Phosphorothioic acid, O,O-diethyl-O-(4-nitrophenyl) ester
Polychlorinated biphenyls; PCBs	See footnote 4	1,1'-Biphenyl, chloro derivatives
Polychlorinated dibenzo-p-dioxins; PCDDs	See footnote 5	Dibenzo[b,e][1,4]dioxin, chloro derivatives
Polychlorinated dibenzofurans; PCDFs	See footnote 6	Dibenzofuran, chloro derivatives
Pentachlorobenzene	608–93–5	Benzene, pentachloro-
Pentachloroethane	76–01–7	Ethane, pentachloro-
Pentachloronitrobenzene	82–68–8	Benzene, pentachloronitro-
Pentachlorophenol	87–86–5	Phenol, pentachloro-
Phenacetin	62–44–2	Acetamide, N-(4-ethoxyphenyl)
Phenanthrene	85–01–8	Phenanthrene
Phenol	108–95–2	Phenol
p-Phenylenediamine	106–50–3	1,4-Benzenediamine
Phorate	298–02–2	Phosphorodithioic acid, O,O-diethyl S- [(ethylthio)methyl] ester

GROUND-WATER MONITORING LIST—Continued

Common name[1]	CAS RN[2]	Chemical abstracts service index name[3]
2-Picoline	109–06–8	Pyridine, 2-methyl-
Pronamide	23950–58–5	Benzamide, 3,5-dichloro-N-(1,1-dimethyl-2-propynyl)-
Propionitrile; Ethyl cyanide	107–12–0	Propanenitrile
Pyrene	129–00–0	Pyrene
Pyridine	110–86–1	Pyridine
Safrole	94–59–7	1,3-Benzodioxole, 5-(2-propenyl)-
Selenium	(Total)	Selenium
Silver	(Total)	Silver
Silvex; 2,4,5-TP	93–72–1	Propanoic acid, 2-(2,4,5- trichlorophenoxy)-
Styrene	100–42–5	Benzene, ethenyl-
Sulfide	18496–25–8	Sulfide
2,4,5-T; 2,4,5-Trichlorophenoxyacetic acid	93–76–5	Acetic acid, (2,4,5-trichlorophenoxy)-
2,3,7,8-TCDD; 2,3,7,8-Tetrachlorodibenzo-p-dioxin	1746–01–6	Dibenzo[b,e][1,4]dioxin, 2,3,7,8-tetrachloro-
1,2,4,5-Tetrachlorobenzene	95–94–3	Benzene, 1,2,4,5-tetrachloro-
1,1,1,2-Tetrachloroethane	630–20–6	Ethane, 1,1,1,2-tetrachloro-
1,1,2,2-Tetrachloroethane	79–34–5	Ethane, 1,1,2,2-tetrachloro-
Tetrachloroethylene; Perchloroethylene; Tetrachloroethene	127–18–4	Ethene, tetrachloro-
2,3,4,6-Tetrachlorophenol	58–90–2	Phenol, 2,3,4,6-tetrachloro-
Tetraethyl dithiopyrophosphate; Sulfotepp	3689–24–5	Thiodiphosphoric acid ([(HO)$_2$ P(S)]$_2$ O), tetraethyl ester
Thallium	(Total)	Thallium
Tin	(Total)	Tin
Toluene	108–88–3	Benzene, methyl-
o-Toluidine	95–53–4	Benzenamine, 2-methyl-
Toxaphene	8001–35–2	Toxaphene
1,2,4-Trichlorobenzene	120–82–1	Benzene, 1,2,4-trichloro-
1,1,1-Trichloroethane; Methylchloroform	71–55–6	Ethane, 1,1,1-trichloro-
1,1,2-Trichloroethane	79–00–5	Ethane, 1,1,2-trichloro-
Trichloroethylene; Trichloroethene	79–01–6	Ethene, trichloro-
Trichlorofluoromethane	75–69–4	Methane, trichlorofluoro-
2,4,5-Trichlorophenol	95–95–4	Phenol, 2,4,5-trichloro-
2,4,6-Trichlorophenol	88–06–2	Phenol, 2,4,6-trichloro-
1,2,3-Trichloropropane	96–18–4	Propane, 1,2,3-trichloro-
O,O,O-Triethyl phosphorothioate	126–68–1	Phosphorothioic acid, O,O,O-triethyl ester
sym-Trinitrobenzene	99–35–4	Benzene, 1,3,5-trinitro-
Vanadium	(Total)	Vanadium
Vinyl acetate	108–05–4	Acetic acid, ethenyl ester
Vinyl chloride	75–01–4	Ethene, chloro-
Xylene (total)	1330–20–7	Benzene, dimethyl-
Zinc	(Total)	Zinc

[1] Common names are those widely used in government regulations, scientific publications, and commerce; synonyms exist for many chemicals.

[2] Chemical Abstracts Service registry number. Where "Total" is entered, all species in the ground water that contain this element are included.

[3] CAS index names are those used in the 9th Cumulative Index.

[4] Polychlorinated biphenyls (CAS RN 1336–36–3); this category contains congener chemicals, including constituents of Aroclor-1016 (CAS RN 12674–11–2), Aroclor-1221 (CAS RN 11104–28–2), Aroclor-1232 (CAS RN 11141–16–5), Aroclor-1242 (CAS RN 53469–21–9), Aroclor-1248 (CAS RN 12672–29–6), Aroclor-1254 (CAS RN 11097–69–1), and Aroclor-1260 (CAS RN 11096–82–5).

[5] This category contains congener chemicals, including tetrachlorodibenzo-p-dioxins (see also 2,3,7,8-TCDD), pentachlorodibenzo-p-dioxins, and hexachlorodibenzo-p-dioxins.

[6] This category contains congener chemicals, including tetrachlorodibenzofurans, pentachlorodibenzofurans, and hexachlorodibenzofurans.

PART 265—INTERIM STATUS STANDARDS FOR OWNERS AND OPERATORS OF HAZARDOUS WASTE TREATMENT, STORAGE, AND DISPOSAL FACILITIES

■ 28. The authority citation for part 265 continues to read as follows:

Authority: 42 U.S.C. 6905, 6906, 6912, 6922, 6923, 6924, 6925, 6935, 6936 and 6937, unless otherwise noted.

Subpart J—Tank Systems

■ 29. Section 265.190 is amended by revising paragraph (a) to read as follows:

§ 265.190 Applicability.

* * * * *

(a) Tank systems that are used to store or treat hazardous waste which contains no free liquids and are situated inside a building with an impermeable floor are exempted from the requirements in § 265.193. To demonstrate the absence or presence of free liquids in the stored/treated waste, the following test must be used: Method 9095B (Paint Filter Liquids Test) as described in "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods," EPA Publication SW–846, as incorporated by reference in § 260.11 of this chapter.

* * * * *

Subpart N—Landfills

■ 30. Section 265.314 is amended by revising paragraph (d) to read as follows:

§ 265.314 Special requirements for bulk and containerized liquids.

* * * * *

(d) To demonstrate the absence or presence of free liquids in either a containerized or a bulk waste, the following test must be used: Method 9095B (Paint Filter Liquids Test) as described in "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods," EPA Publication SW–846, as incorporated by reference in § 260.11 of this chapter.

* * * * *

Subpart AA—Air Emission Standards for Process Vents

■ 31. Section 265.1034 is amended by revising paragraphs (c)(1)(ii), (c)(1)(iv), (d)(1)(iii) and (f) to read as follows:

§ 265.1034 Test methods and procedures.

* * * * *

(c) * * *

(1) * * *

(ii) Method 18 or Method 25A in 40 CFR part 60, appendix A, for organic content. If Method 25A is used, the organic HAP used as the calibration gas must be the single organic HAP representing the largest percent by volume of the emissions. The use of Method 25A is acceptable if the response from the high-level calibration gas is at least 20 times the standard deviation of the response from the zero calibration gas when the instrument is zeroed on the most sensitive scale.

* * * * *

(iv) Total organic mass flow rates shall be determined by the following equation:

(A) For sources utilizing Method 18.

$$E_h = Q_{2sd}\left\{\sum_{i=1}^{n} C_i MW_i\right\}[0.0416][10^{-6}]$$

Where:

E_h = Total organic mass flow rate, kg/h;

Q_{2sd} = Volumetric flow rate of gases entering or exiting control device, as determined by Method 2, dscm/h;

n = Number of organic compounds in the vent gas;

C_i = Organic concentration in ppm, dry basis, of compound i in the vent gas, as determined by Method 18;

MW_i = Molecular weight of organic compound i in the vent gas, kg/kg-mol;

0.0416 = Conversion factor for molar volume, kg-mol/m3 (@ 293 K and 760 mm Hg);

10^{-6} = Conversion from ppm

(B) For sources utilizing Method 25A.

$E_h = (Q)(C)(MW)(0.0416)(10^{-6})$

Where:

E_h = Total organic mass flow rate, kg/h;

Q = Volumetric flow rate of gases entering or exiting control device, as determined by Method 2, dscm/h;

C = Organic concentration in ppm, dry basis, as determined by Method 25A;

MW = Molecular weight of propane, 44;

0.0416 = Conversion factor for molar volume, kg-mol/m3 (@ 293 K and 760 mm Hg);

10^{-6} = Conversion from ppm.

* * * * *

(d) * * *

(1) * * *

(iii) Each sample shall be analyzed and the total organic concentration of the sample shall be computed using Method 9060A (incorporated by reference under § 260.11 of this chapter) of "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods," EPA Publication SW–846; or analyzed for its individual organic constituents.

* * * * *

(f) When an owner or operator and the Regional Administrator do not agree on whether a distillation, fractionation, thin-film evaporation, solvent extraction, or air or steam stripping operation manages a hazardous waste with organic concentrations of at least 10 ppmw based on knowledge of the waste, the dispute may be resolved using direct measurement as specified at paragraph (d)(1) of this section.

Subpart BB—Air Emission Standards for Equipment Leaks

■ 32. Section 265.1063 is amended by revising paragraph (d)(2) to read as follows:

§ 265.1063 Test methods and procedures.

* * * * *

(d) * * *

(2) Method 9060A (incorporated by reference under § 260.11 of this chapter) of "Test Methods for Evaluating Solid Waste," EPA Publication SW–846 or analyzed for its individual organic constituents; or

* * * * *

Subpart CC—Air Emission Standards for Tanks, Surface Impoundments, and Containers

■ 33. Section 265.1081 is amended by revising the definition "Waste stabilization process" to read as follows:

§ 265.1081 Definitions.

* * * * *

Waste stabilization process means any physical or chemical process used to either reduce the mobility of hazardous constituents in a hazardous waste or eliminate free liquids as determined by Test Method 9095B (Paint Filter Liquids Test) in "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods," EPA Publication SW–846, as incorporated by reference in § 260.11. A waste stabilization process includes mixing the hazardous waste with binders or other materials, and curing the resulting hazardous waste and binder mixture. Other synonymous terms used to refer to this process are "waste fixation" or "waste solidification." This does not include the adding of absorbent materials to the surface of a waste, without mixing, agitation, or subsequent curing, to absorb free liquid.

■ 34. Section 265.1084 is amended by revising paragraphs (a)(3)(ii)(C), (a)(3)(iii), (b)(3)(ii)(C), (b)(3)(iii), and (c)(3)(i) to read as follows:

§ 265.1084 Waste determination procedures.

(a) * * *

(3) * * *

(ii) * * *

(C) All samples shall be collected and handled in accordance with written procedures prepared by the owner or operator and documented in a site sampling plan. This plan shall describe the procedure by which representative samples of the hazardous waste stream are collected such that a minimum loss of organics occurs throughout the sample collection and handling process, and by which sample integrity is maintained. A copy of the written sampling plan shall be maintained on-site in the facility operating records. An example of acceptable sample collection and handling procedures for a total volatile organic constituent concentration may be found in Method 25D in 40 CFR part 60, appendix A.

* * * * *

(iii) *Analysis.* Each collected sample shall be prepared and analyzed in accordance with Method 25D in 40 CFR part 60, appendix A for the total concentration of volatile organic constituents, or using one or more methods when the individual organic compound concentrations are identified and summed and the summed waste concentration accounts for and reflects all organic compounds in the waste with Henry's law constant values at least 0.1 mole-fraction-in-the-gas-phase/mole-fraction-in-the-liquid-phase (0.1 Y/X) [which can also be expressed as 1.8×10^{-6} atmospheres/gram-mole/m^3] at 25 degrees Celsius. At the owner or operator's discretion, the owner or operator may adjust test data obtained by any appropriate method to discount any contribution to the total volatile organic concentration that is a result of including a compound with a Henry's law constant value of less than 0.1 Y/X at 25 degrees Celsius. To adjust these data, the measured concentration of each individual chemical constituent contained in the waste is multiplied by the appropriate constituent-specific adjustment factor (f_{m25D}). If the owner or operator elects to adjust test data, the adjustment must be made to all individual chemical constituents with a Henry's law constant value greater than

or equal to 0.1 Y/X at 25 degrees Celsius contained in the waste. Constituent-specific adjustment factors (f_{m25D}) can be obtained by contacting the Waste and Chemical Processes Group, Office of Air Quality Planning and Standards, Research Triangle Park, NC 27711. Other test methods may be used if they meet the requirements in paragraph (a)(3)(iii)(A) or (B) of this section and provided the requirement to reflect all organic compounds in the waste with Henry's law constant values greater than or equal to 0.1 Y/X [which can also be expressed as 1.8×10^{-6} atmospheres/gram-mole/m^3] at 25 degrees Celsius, is met.

(A) Any EPA standard method that has been validated in accordance with "Alternative Validation Procedure for EPA Waste and Wastewater Methods," 40 CFR part 63, appendix D.

(B) Any other analysis method that has been validated in accordance with the procedures specified in Section 5.1 or Section 5.3, and the corresponding calculations in Section 6.1 or Section 6.3, of Method 301 in 40 CFR part 63, appendix A. The data are acceptable if they meet the criteria specified in Section 6.1.5 or Section 6.3.3 of Method 301. If correction is required under section 6.3.3 of Method 301, the data are acceptable if the correction factor is within the range 0.7 to 1.30. Other sections of Method 301 are not required.

* * * * *

(b) * * *

(3) * * *

(ii) * * *

(C) All samples shall be collected and handled in accordance with written procedures prepared by the owner or operator and documented in a site sampling plan. This plan shall describe the procedure by which representative samples of the hazardous waste stream are collected such that a minimum loss of organics occurs throughout the sample collection and handling process, and by which sample integrity is maintained. A copy of the written sampling plan shall be maintained on-site in the facility operating records. An example of acceptable sample collection and handling procedures for a total volatile organic constituent concentration may be found in Method 25D in 40 CFR part 60, appendix A.

* * * * *

(iii) *Analysis.* Each collected sample shall be prepared and analyzed in accordance with Method 25D in 40 CFR part 60, appendix A for the total concentration of volatile organic constituents, or using one or more methods when the individual organic compound concentrations are identified and summed and the summed waste concentration accounts for and reflects all organic compounds in the waste with Henry's law constant values at least 0.1 mole-fraction-in-the-gas-phase/mole-fraction-in-the-liquid-phase (0.1 Y/X) [which can also be expressed as 1.8×10^{-6} atmospheres/gram-mole/m^3] at 25 degrees Celsius. When the owner or operator is making a waste determination for a treated hazardous waste that is to be compared to an average VO concentration at the point of waste origination or the point of waste entry to the treatment system to determine if the conditions of § 264.1082(c)(2)(i) through (c)(2)(vi) of this chapter, or § 265.1083(c)(2)(i) through (c)(2)(vi) of this subpart are met, then the waste samples shall be prepared and analyzed using the same method or methods as were used in making the initial waste determinations at the point of waste origination or at the point of entry to the treatment system. At the owner or operator's discretion, the owner or operator may adjust test data obtained by any appropriate method to discount any contribution to the total volatile organic concentration that is a result of including a compound with a Henry's law constant value less than 0.1 Y/X at 25 degrees Celsius. To adjust these data, the measured concentration of each individual chemical constituent in the waste is multiplied by the appropriate constituent-specific adjustment factor (f_{m25D}). If the owner or operator elects to adjust test data, the adjustment must be made to all individual chemical constituents with a Henry's law constant value greater than or equal to 0.1 Y/X at 25 degrees Celsius contained in the waste. Constituent-specific adjustment factors (f_{m25D}) can be obtained by contacting the Waste and Chemical Processes Group, Office of Air Quality Planning and Standards, Research Triangle Park, NC 27711. Other test methods may be used if they meet the requirements in paragraph (a)(3)(iii)(A) or (B) of this section and provided the requirement to reflect all organic compounds in the waste with Henry's law constant values greater than or equal to 0.1 Y/X [which can also be expressed as 1.8×10^{-6} atmospheres/gram-mole/m^3] at 25 degrees Celsius, is met.

(A) Any EPA standard method that has been validated in accordance with "Alternative Validation Procedure for EPA Waste and Wastewater Methods," 40 CFR part 63, appendix D.

(B) Any other analysis method that has been validated in accordance with the procedures specified in Section 5.1 or Section 5.3, and the corresponding calculations in Section 6.1 or Section 6.3, of Method 301 in 40 CFR part 63, appendix A. The data are acceptable if they meet the criteria specified in Section 6.1.5 or Section 6.3.3 of Method 301. If correction is required under section 6.3.3 of Method 301, the data are acceptable if the correction factor is within the range 0.7 to 1.30. Other sections of Method 301 are not required.

* * * * *

(c) * * *

(3) * * *

(i) Sampling. A sufficient number of samples shall be collected to be representative of the waste contained in the tank. All samples shall be collected and handled in accordance with written procedures prepared by the owner or operator and documented in a site sampling plan. This plan shall describe the procedure by which representative samples of the hazardous waste are collected such that a minimum loss of organics occurs throughout the sample collection and handling process and by which sample integrity is maintained. A copy of the written sampling plan shall be maintained on-site in the facility operating records. An example of acceptable sample collection and handling procedures may be found in Method 25D in 40 CFR part 60, appendix A.

* * * * *

PART 266—STANDARDS FOR THE MANAGEMENT OF SPECIFIC HAZARDOUS WASTES AND SPECIFIC TYPES OF HAZARDOUS WASTE MANAGEMENT FACILITIES

■ 35. The authority citation for part 266 continues to read as follows:

Authority: 42 U.S.C. 1006, 2002(a), 3001–3009, 3014, 6905, 6906, 6912, 6922, 6924–6927, 6934 and 6937.

Subpart H—Hazardous Waste Burned in Boilers and Industrial Furnaces

■ 36. Section 266.100 is amended by revising paragraphs (d)(1)(ii) and (g)(2) to read as follows:

§ 266.100 Applicability.

* * * * *

(d) * * *

(1) * * *

(ii) Sample and analyze the hazardous waste and other feedstocks as necessary to comply with the requirements of this paragraph by using appropriate methods; and

* * * * *

(g) * * *

(2) Sample and analyze the hazardous waste as necessary to document that the waste contains economically significant

amounts of the metals and that the treatment recovers economically significant amounts of precious metal; and

* * * * *

■ 37. Section 266.102 is amended by revising paragraph (b)(1) to read as follows:

§ 266.102 Permit standards for burners.

* * * * *

(b) * * * (1) The owner or operator must provide an analysis of the hazardous waste that quantifies the concentration of any constituent identified in appendix VIII of part 261 of this chapter that may reasonably be expected to be in the waste. Such constituents must be identified and quantified if present, at levels detectable by using appropriate analytical procedures. The appendix VIII, part 261 constituents excluded from this analysis must be identified and the basis for their exclusion explained. This analysis will be used to provide all information required by this subpart and §§ 270.22 and 270.66 of this chapter and to enable the permit writer to prescribe such permit conditions as necessary to protect human health and the environment. Such analysis must be included as a portion of the part B permit application, or, for facilities operating under the interim status standards of this subpart, as a portion of the trial burn plan that may be submitted before the part B application under provisions of § 270.66(g) of this chapter as well as any other analysis required by the permit authority in preparing the permit. Owners and operators of boilers and industrial furnaces not operating under the interim status standards must provide the information required by §§ 270.22 or 270.66(c) of this chapter in the part B application to the greatest extent possible.

* * * * *

■ 38. Section 266.106 is amended by revising paragraph (a) to read as follows:

§ 266.106 Standards to control metals emissions.

(a) *General.* The owner or operator must comply with the metals standards provided by paragraphs (b), (c), (d), (e), or (f) of this section for each metal listed in paragraph (b) of this section that is present in the hazardous waste at detectable levels by using appropriate analytical procedures.

* * * * *

■ 39. Section 266.112 is amended by revising paragraph (b)(1) introductory text and paragraph (b)(2)(i) to read as follows:

§ 266.112 Regulation of residues.

* * * * *

(b) * * *

(1) *Comparison of waste-derived residue with normal residue.* The waste-derived residue must not contain appendix VIII, part 261 constituents (toxic constituents) that could reasonably be attributable to the hazardous waste at concentrations significantly higher than in residue generated without burning or processing of hazardous waste, using the following procedure. Toxic compounds that could reasonably be attributable to burning or processing the hazardous waste (constituents of concern) include toxic constituents in the hazardous waste, and the organic compounds listed in appendix VIII of this part that may be generated as products of incomplete combustion. For polychlorinated dibenzo-p-dioxins and polychlorinated dibenzo-furans, analyses must be performed to determine specific congeners and homologues, and the results converted to 2,3,7,8-TCDD equivalent values using the procedure specified in section 4.0 of appendix IX of this part.

* * * * *

(2) * * * (i) *Nonmetal constituents:* The concentration of each nonmetal toxic constituent of concern (specified in paragraph (b)(1) of this section) in the waste-derived residue must not exceed the health-based level specified in appendix VII of this part, or the level of detection, whichever is higher. If a health-based limit for a constituent of concern is not listed in appendix VII of this part, then a limit of 0.002 micrograms per kilogram or the level of detection (which must be determined by using appropriate analytical procedures), whichever is higher, must be used. The levels specified in appendix VII of this part (and the default level of 0.002 micrograms per kilogram or the level of detection for constituents as identified in Note 1 of appendix VII of this chapter) are administratively stayed under the condition, for those constituents specified in paragraph (b)(1) of this section, that the owner or operator complies with alternative levels defined as the land disposal restriction limits specified in § 268.43 of this chapter for F039 nonwastewaters. In complying with those alternative levels, if an owner or operator is unable to detect a constituent despite documenting use of best good-faith efforts as defined by applicable Agency guidance or standards, the owner or operator is deemed to be in compliance for that constituent. Until new guidance or standards are developed, the owner or operator may demonstrate such good-faith efforts by achieving a detection limit for the constituent that does not exceed an order of magnitude above the level provided by § 268.43 of this chapter for F039 nonwastewaters. In complying with the § 268.43 of this chapter F039 nonwastewater levels for polychlorinated dibenzo-p-dioxins and polychlorinated dibenzo-furans, analyses must be performed for total hexachlorodibenzo-p-dioxins, total hexachlorodibenzofurans, total pentachlorodibenzo-p-dioxins, total pentachlorodibenzofurans, total tetrachlorodibenzo-p-dioxins, and total tetrachlorodibenzofurans.

Note to this paragraph (b)(2)(i): The administrative stay, under the condition that the owner or operator complies with alternative levels defined as the land disposal restriction limits specified in § 268.43 of this chapter for F039 nonwastewaters, remains in effect until further administrative action is taken and notice is published in the Federal Register and the Code of Federal Regulations.

* * * * *

■ 40. Appendix IX of part 266 is amended to:

■ a. Revise sections 1.0 and 3.0,

■ b. Revise the first paragraph of section 4.0,

■ c. Revise paragraph (2) of section 10.3,

■ d. Revise the introductory text of the fifth bullet of paragraph (1) of section 10.5,

■ e. Revise the third dash text under the second bullet of paragraph (2) of section 10.5,

■ f. Revise the third and the introductory text of the fifth bullet of paragraph (5) of section 10.5,

■ g. Revise the introductory text of the fourth bullet of paragraph (1) of section 10.6,

■ h. Revise the third and the introductory text of the fourth bullet of paragraph (5) of section 10.6.

The revisions read as follows:

Appendix IX to Part 266—Methods Manual for Compliance With the BIF Regulations

* * * * *

Section 1.0 Introduction

This document presents required methods for demonstrating compliance with U.S. Environmental Protection Agency regulations for boilers and industrial furnaces (BIFs) burning hazardous waste (see 40 CFR part 266, subpart H). The methods included in this document are:

1. Performance Specifications for Continuous Emission Monitoring (CEM) of Carbon Monoxide, Oxygen, and Hydrocarbons in Stack Gases.

2. Procedures for Estimating the Toxicity Equivalency of Chlorinated Dibenzo-p-dioxin and Dibenzofuran Congeners.

3. Hazardous Waste Combustion Air Quality Screening Procedures (HWCAQSP).

4. Simplified Land Use Classification Procedure for Compliance with Tier I and Tier II Limits.

5. Statistical Methodology for Bevill Residue Determinations.

6. Procedures for Determining Default Values for Air Pollution Control System Removal Efficiencies.

7. Procedures for Determining Default Values for Partitioning of Metals, Ash, and Total Chloride/Chlorine.

8. Alternate Methodology for Implementing Metals Controls.

a. Sampling and analytical methods for multiple metals, hexavalent chromium, HCl and chlorine, polychlorinated dibenzo-p-dioxins and dibenzofurans, and aldehydes and ketones can be found in "Test Methods for Evaluating Solid Wastes, Physical/Chemical Methods" (EPA Publication SW–846). Additional methods referenced in subpart H of part 266 but not included in this document can be found in 40 CFR parts 60 and 61, and SW–846.

b. The CEM performance specifications of section 2.0, the relevant sampling Methods 0011, 0023A, 0050, 0051, 0060, and 0061 of SW–846, incorporated by reference in § 260.11, and the toxicity equivalency procedure for dioxins and furans of section 4.0 are required procedures for determining compliance with BIF regulations. For the determination of chloride from HCl/Cl_2 emission sampling train, you must use appropriate methods. For the determination of carbonyl compounds by high-performance liquid chromatography, you must use appropriate methods. The CEM performance specifications are interim. The finalized CEM performance specifications will be published in 40 CFR parts 60 and 61.

* * * * *

Section 3.0 Sampling and Analytical Methods

Note: The sampling and analytical methods to the BIF manual are published in "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods," EPA Publication SW–846.

Section 4.0 Procedure for Estimating the Toxicity Equivalency of Chlorinated Dibenzo-p-Dioxin and Dibenzofuran Congeners

PCDDs and PCDFs must be determined using whichever is the most recent version between of SW–846 Method 0023A (incorporated by reference, in § 260.11) as identified, or OAQPS Method 23 of appendix A to part 60. In this method, individual congeners or homologues [1] are measured and then summed to yield a total PCDD/PCDF value. No toxicity factors are specified in the method to compute risks from such emissions.

* * * * *

[1] The term "congener" refers to any one particular member of the same chemical family; e.g., there are 75 congeners of chlorinated dibenzo-p-dioxins. The term "homologue" refers to a group of structurally related chemicals that have the same degree of chlorination. For example, there are eight homologues of CDs, monochlorinated through octachlorinated. Dibenzo-p-dioxins and dibenzofurans that are chlorinated at the 2,3,7, and 8 positions are denoted as "2378" congeners, except when 2,3,7,8–TCDD is uniquely referred to: e.g., 1,2,3,7,8–PeCDF and 2,3,4,7,8–PeCDF are both referred to as "2378–PeCDFs."

* * * * *

Section 10.0 Alternative Methodology for Implementing Metals Controls

* * * * *

10.3 *Basis*

* * * * *

(2) The metal concentrations in the collected kiln dust can be accurately and representatively measured.

* * * * *

10.5 *Implementation Procedures*

* * * * *

(1) * * *

• Follow appropriate guidelines for preparing test plans and waste analysis plans for the following tests:

* * * * *

(2) * * *

—Follow appropriate sampling and analytical procedures such as those described in the waste analysis plan as they pertain to the condition and accessibility of the dust.

* * * * *

(5) * * *

• Follow the sampling, compositing, and analytical procedures described in this method and in other appropriate methods, as they pertain to the condition and accessibility of the kiln dust. * * *

• Samples must be collected at least once every 8 hours, and a daily composite must be prepared according to appropriate procedures.

* * * * *

10.6 *Precompliance Procedures*

* * * * *

(1) * * *

• Follow appropriate procedures for preparing waste analysis plans for the following tasks:

* * * * *

(5) * * *

• Follow the sampling, compositing, and analytical procedures described in this method and in other appropriate methods as they pertain to the condition and accessibility of the kiln dust.

• Samples must be collected at least once every 8 hours, and a daily composite must be prepared according to appropriate procedures.

* * * * *

PART 268—LAND DISPOSAL RESTRICTIONS

■ 41. The authority citation for part 268 continues to read as follows:

Authority: 42 U.S.C. 6905, 6912(a), 6921, and 6924.

Subpart D—Treatment Standards

■ 42. Section 268.40 is amended by revising paragraph (b) and footnote 7 of the table "Treatment Standards for Hazardous Wastes" to read as follows:

§ 268.40 Applicability of treatment standards.

* * * * *

(b) For wastewaters, compliance with concentration level standards is based on maximums for any one day, except for D004 through D011 wastes for which the previously promulgated treatment standards based on grab samples remain in effect. For all nonwastewaters, compliance with concentration level standards is based on grab sampling. For wastes covered by the waste extract standards, the test Method 1311, the Toxicity Characteristic Leaching Procedure found in "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods," EPA Publication SW–846, as incorporated by reference in § 260.11, must be used to measure compliance. An exception is made for D004 and D008, for which either of two test methods may be used: Method 1311, or Method 1310B, the Extraction Procedure Toxicity Test. For wastes covered by a technology standard, the wastes may be land disposed after being treated using that specified technology or an equivalent treatment technology approved by the Administrator under the procedures set forth in § 268.42(b).

* * * * *

Treatment Standards for Hazardous Wastes

* * * * *

[7] Both Cyanides (Total) and Cyanides (Amenable) for nonwastewaters are to be analyzed using Method 9010C or 9012B, found in "Test Methods' for Evaluating Solid Waste, Physical/Chemical Methods," EPA Publication SW–846, as incorporated by reference in 40 CFR 260.11, with a sample size of 10 grams and a distillation time of one hour and 15 minutes.

* * * * *

■ 43. Section 268.44 is amended by revising footnote 4 of the table "Wastes Excluded From the Treatment Standards Under § 268.40" to read as follows:

§ 268.44 Variance from a treatment standard.

* * * * *

Table—Wastes Excluded From the Treatment Standards Under § 268.40

* * * * *

[4]—Cyanide nonwastewaters are analyzed using SW–846 Method 9010C or 9012B, as incorporated by reference in § 260.11 of this

chapter; sample size 10 grams, distillation time, 1 hour and 15 minutes.

* * * * *

■ 44. Section 268.48 is amended by revising footnote 4 of the table "Universal Treatment Standards" to read as follows:

§ 268.48 Universal treatment standards.

* * * * *

Universal Treatment Standards

* * * * *

4 Both Cyanides (Total) and Cyanides (Amenable) for nonwastewaters are to be analyzed using Method 9010C or 9012B, found in "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods," EPA Publication SW–846, as incorporated by reference in 40 CFR 260.11, with a sample size of 10 grams and a distillation time of one hour and 15 minutes.

* * * * *

■ 45. Appendix IX to part 268 is revised as follows:

Appendix IX to Part 268—Extraction Procedure (EP) Toxicity Test Method and Structural Integrity Test (Method 1310B)

Note: The EP (Method 1310B) is published in "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods," EPA Publication SW–846, as incorporated by reference in § 260.11 of this chapter.

PART 270—EPA ADMINISTERED PERMIT PROGRAMS: THE HAZARDOUS WASTE PERMIT

■ 46. The authority citation for part 270 continues to read as follows:

Authority: 42 U.S.C. 6905, 6912, 6924, 6925, 6927, 6939, and 6974.

Subpart B—Permit Application

■ 47. Section 270.19 is amended by revising paragraphs (c)(1)(iii) and (iv) to read as follows:

§ 270.19 Specific part B information requirements for incinerators.

* * * * *

(c) * * *

(1) * * *

(iii) An identification of any hazardous organic constituents listed in part 261, appendix VIII, of this chapter, which are present in the waste to be burned, except that the applicant need not analyze for constituents listed in part 261, appendix VIII, of this chapter which would reasonably not be expected to be found in the waste. The constituents excluded from analysis must be identified and the basis for their exclusion stated. The waste analysis must rely on appropriate analytical techniques.

(iv) An approximate quantification of the hazardous constituents identified in the waste, within the precision produced by appropriate analytical methods.

* * * * *

■ 48. Section 270.22 is amended by revising paragraph (a)(2)(ii)(B) to read as follows:

§ 270.22 Specific part B information requirements for boilers and industrial furnaces burning hazardous waste.

* * * * *

(a) * * *

(2) * * *

(ii) * * *

(B) Results of analyses of each waste to be burned, documenting the concentrations of nonmetal compounds listed in appendix VIII of part 261 of this chapter, except for those constituents that would reasonably not be expected to be in the waste. The constituents excluded from analysis must be identified and the basis for their exclusion explained. The analysis must rely on appropriate analytical techniques.

* * * * *

Subpart F—Special Forms of Permits

■ 49. Section 270.62 is amended by revising paragraphs (b)(2)(i)(C) and (D) to read as follows:

§ 270.62 Hazardous waste incinerator permits.

* * * * *

(b) * * *

(2) * * *

(i) * * *

(C) An identification of any hazardous organic constituents listed in part 261, appendix VIII of this chapter, which are present in the waste to be burned, except that the applicant need not analyze for constituents listed in part 261, appendix VIII, of this chapter which would reasonably not be expected to be found in the waste. The constituents excluded from analysis must be identified, and the basis for the exclusion stated. The waste analysis must rely on appropriate analytical techniques.

(D) An approximate quantification of the hazardous constituents identified in the waste, within the precision produced by appropriate analytical methods.

* * * * *

■ 50. Section 270.66 is amended by revising paragraphs (c)(2)(i) and (ii) to read as follows:

§ 270.66 Permits for boilers and industrial furnaces burning hazardous waste.

* * * * *

(c) * * *

(2) * * *

(i) An identification of any hazardous organic constituents listed in appendix VIII, part 261, of this chapter that are present in the feed stream, except that the applicant need not analyze for constituents listed in appendix VIII that would reasonably not be expected to be found in the hazardous waste. The constituents excluded from analysis must be identified and the basis for this exclusion explained. The waste analysis must be conducted in accordance with appropriate analytical techniques.

(ii) An approximate quantification of the hazardous constituents identified in the hazardous waste, within the precision produced by appropriate analytical methods.

* * * * *

PART 271—REQUIREMENTS FOR AUTHORIZATION OF STATE HAZARDOUS WASTE PROGRAMS

■ 51. The authority citation for part 271 continues to read as follows:

Authority: 42 U.S.C. 6905, 6912(a) and 6926.

■ 52. Section 271.1(j) is amended by adding the following entries to Table 1 in chronological order by date of publication in the Federal Register, to read as follows:

§ 271.1 Purpose and scope.

* * * * *

(j) * * *

TABLE 1.—REGULATIONS IMPLEMENTING THE HAZARDOUS AND SOLID WASTE AMENDMENTS OF 1984

Promulgation date	Title of regulation	Federal Register reference	Effective date

TABLE 1.—REGULATIONS IMPLEMENTING THE HAZARDOUS AND SOLID WASTE AMENDMENTS OF 1984—Continued

Promulgation date	Title of regulation	Federal Register reference	Effective date
* * * * *	* * *		
July 14, 2005	Process Vent and Equipment Leak Organic Air Emission Standards for Owners and of Operators of Hazardous Waste Treatment, Storage, and Disposal Facilities.	[Insert FR page citation of publication date].	July 14, 2005.
July 14, 2005	Burning of Hazardous Waste in Boilers and Industrial Furnaces.	[Insert FR page citation of publication date].	July 14, 2005.
July 14, 2005	Air Emission Standards Tanks, Surface Impoundments, Containers.	[Insert FR page citation of publication date].	July 14, 2005.

* * * * *

■ 53. Section 271.21 is amended by adding the following entries to Table 1 in chronological order by date of publication in the Federal Register, to read as follows:

§ 271.21 Procedures for revision of State programs.

* * * * *

TABLE 1 TO § 271.21

Title of regulation	Promulgation date	Federal Register reference
* * * * * * *		
Office of Solid Waste Testing and Monitoring Activities, Methods Innovation Rule.	July 14, 2005	[Insert FR page citation of publication date].
Process Vent and Equipment Leak Organic Air Emission Standards for Owners and Operators of Hazardous Waste Treatment, Storage, and Disposal Facilities.	July 14, 2005	[Insert FR page citation of publication date].
Burning of hazardous waste in boilers and industrial furnaces	July 14, 2005	[Insert FR page citation of publication date].
Air Emissions Standards for Tanks, Surface Impoundments, and Containers.	July 14, 2005	[Insert FR page citation of publication date].

PART 279—STANDARDS FOR THE MANAGEMENT OF USED OIL

■ 54. The authority citation for part 279 continues to read as follows:

Authority: Sections 1006, 2002(a), 3001 through 3007, 3010, 3014, and 7004 of the Solid Waste Disposal Act, as amended (42 U.S.C. 6905, 6912(a), 6921 through 6927, 6930, 6934, and 6974); and sections 101(37) and 114(c) of CERCLA (42 U.S.C. 9601(37) and 9614(c)).

Subpart B—Applicability

■ 55. Section 279.10 is amended by revising paragraph (b)(1)(ii) introductory text to read as follows:

§ 279.10 Applicability.

* * * * *

(b) * * *

(1) * * *

(ii) *Rebuttable presumption for used oil.* Used oil containing more than 1,000 ppm total halogens is presumed to be a hazardous waste because it has been mixed with halogenated hazardous waste listed in subpart D of part 261 of this chapter. Persons may rebut this presumption by demonstrating that the used oil does not contain hazardous waste (for example, by showing that the used oil does not contain significant concentrations of halogenated hazardous constituents listed in appendix VIII of part 261 of this chapter).

* * * * *

Subpart E—Standards for Used Oil Transporter and Transfer Facilities

■ 56. Section 279.44 is amended by revising the introductory text of paragraph (c) to read as follows:

§ 279.44 Rebuttable presumption for used oil.

* * * * *

(c) If the used oil contains greater than or equal to 1,000 ppm total halogens, it is presumed to be a hazardous waste because it has been mixed with halogenated hazardous waste listed in subpart D of part 261 of this chapter. The owner or operator may rebut the presumption by demonstrating that the used oil does not contain hazardous waste (for example, by showing that the used oil does not contain significant concentrations of halogenated hazardous constituents listed in appendix VIII of part 261 of this chapter).

* * * * *

Subpart F—Standards for Used Oil Processors and Re-Refiners

■ 57. Section 279.53 is amended by revising paragraph (c) introductory text to read as follows:

§ 279.53 Rebuttable presumption for used oil.

* * * * *

(c) If the used oil contains greater than or equal to 1,000 ppm total halogens, it is presumed to be a hazardous waste because it has been mixed with halogenated hazardous waste listed in subpart D of part 261 of this chapter. The owner or operator may rebut the presumption by demonstrating that the used oil does not contain hazardous waste (for example, by showing that the used oil does not contain significant concentrations of halogenated hazardous constituents listed in appendix VIII of part 261 of this chapter).

* * * * *

Subpart G—Standards for Used Oil Burners Who Burn Off-Specification Used Oil for Energy Recovery

■ 58. Section 279.63 is amended by revising paragraph (c) introductory text to read as follows:

§ 279.63 Rebuttable presumption for used oil.

* * * * *

(c) If the used oil contains greater than or equal to 1,000 ppm total halogens, it is presumed to be a hazardous waste because it has been mixed with halogenated hazardous waste listed in subpart D of part 261 of this chapter. The owner or operator may rebut the presumption by demonstrating that the used oil does not contain hazardous waste (for example, by showing that the used oil does not contain significant concentrations of halogenated hazardous constituents listed in appendix VIII of part 261 of this chapter).

* * * * *

[FR Doc. 05–10197 Filed 6–13–05; 8:45 am]

BILLING CODE 6560–50–P

Federal Register

Wednesday,
October 12, 2005

Part II

Environmental Protection Agency

40 CFR Parts 9, 63, 260 et al.
National Emission Standards for Hazardous Air Pollutants: Final Standards for Hazardous Air Pollutants for Hazardous Waste Combustors (Phase I Final Replacement Standards and Phase II); Final Rule

ENVIRONMENTAL PROTECTION AGENCY

40 CFR Parts 9, 63, 260, 264, 265, 266, 270 and 271

[FRL–7971–8]

RIN 2050–AE01

National Emission Standards for Hazardous Air Pollutants: Final Standards for Hazardous Air Pollutants for Hazardous Waste Combustors (Phase I Final Replacement Standards and Phase II)

AGENCY: Environmental Protection Agency (EPA).

ACTION: Final rule.

SUMMARY: This action finalizes national emission standards (NESHAP) for hazardous air pollutants for hazardous waste combustors (HWCs): hazardous waste burning incinerators, cement kilns, lightweight aggregate kilns, industrial/commercial/institutional boilers and process heaters, and hydrochloric acid production furnaces. EPA has identified HWCs as major sources of hazardous air pollutant (HAP) emissions. These standards implement section 112(d) of the Clean Air Act (CAA) by requiring hazardous waste combustors to meet HAP emission standards reflecting the performance of the maximum achievable control technology (MACT).

The HAP emitted by HWCs include arsenic, beryllium, cadmium, chromium, dioxins and furans, hydrogen chloride and chlorine gas, lead, manganese, and mercury. Exposure to these substances has been demonstrated to cause adverse health effects such as irritation to the lung, skin, and mucus membranes, effects on the central nervous system, kidney damage, and cancer. The adverse health effects associated with exposure to these specific HAP are further described in the preamble. For many HAP, these findings have only been shown with concentrations higher than those typically in the ambient air.

This action also presents our decision regarding the February 28, 2002 petition for rulemaking submitted by the Cement Kiln Recycling Coalition, relating to EPA's implementation of the so-called omnibus permitting authority under section 3005(c) of the Resource Conservation and Recovery Act (RCRA). That section requires that each permit issued under RCRA contain such terms and conditions as permit writers determine to be necessary to protect human health and the environment. In that petition, the Cement Kiln Recycling Coalition requested that we repeal the existing site-specific risk assessment policy and technical guidance for hazardous waste combustors and that we promulgate the policy and guidance as rules in accordance with the Administrative Procedure Act if we continue to believe that site-specific risk assessments may be necessary.

DATES: The final rule is effective December 12, 2005. The incorporation by reference of Method 0023A into § 63.14 is approved by the Director of the Federal Register as of December 12, 2005.

ADDRESSES: The official public docket is the collection of materials that is available for public viewing at the Office of Air and Radiation Docket and Information Center (Air Docket) in the EPA Docket Center, Room B–102, 1301 Constitution Ave., NW., Washington, DC.

FOR FURTHER INFORMATION CONTACT: For more information concerning applicability and rule determinations, contact your State or local representative or appropriate EPA Regional Office representative. For information concerning rule development, contact Michael Galbraith, Waste Treatment Branch, Hazardous Waste Minimization and Management Division, (5302W), U.S. EPA, 1200 Pennsylvania Avenue, NW., Washington DC 20460, telephone number (703) 605–0567, fax number (703) 308–8433, electronic mail address *galbraith.michael@epa.gov.*

SUPPLEMENTARY INFORMATION:

Regulated Entities

The promulgation of the final rule would affect the following North American Industrial Classification System (NAICS) and Standard Industrial Classification (SIC) codes:

Category	NAICS code	SIC code	Examples of potentially regulated entities
Any industry that combusts hazardous waste as defined in the final rule.			
	562211	4953	Incinerator, hazardous waste
	327310	3241	Cement manufacturing, clinker production
	327992	3295	Ground or treated mineral and earth manufacturing
	325	28	Chemical Manufacturers
	324	29	Petroleum Refiners
	331	33	Primary Aluminum
	333	38	Photographic equipment and supplies
	488, 561, 562	49	Sanitary Services, N.E.C.
	421	50	Scrap and waste materials
	422	51	Chemical and Allied Products, N.E.C
	512, 541, 561, 812	73	Business Services, N.E.C.
	512, 514, 541, 711	89	Services, N.E.C.
	924	95	Air, Water and Solid Waste Management

This table is not intended to be exhaustive, but rather provides a guide for readers regarding entities likely to be regulated by this action. This table lists examples of the types of entities EPA is now aware could potentially be regulated by this action. Other types of entities not listed could also be affected. To determine whether your facility, company, business, organization, etc., is regulated by this action, you should examine the applicability criteria in Part II of this preamble. If you have any questions regarding the applicability of this action to a particular entity, consult the person listed in the preceding FOR FURTHER INFORMATION CONTACT section.

Abbreviations and Acronyms Used in This Document

acfm actual cubic feet per minute
Btu British thermal units
CAA Clean Air Act
CFR Code of Federal Regulations
DRE destruction and removal efficiency
dscf dry standard cubic foot
dscm dry standard cubic meter

EPA Environmental Protection Agency
FR Federal Register
gr/dscf grains per dry standard cubic foot
HAP hazardous air pollutant(s)
ICR Information Collection Request
kg/hr kilograms per hour
kW-hour kilo Watt hour
MACT Maximum Achievable Control Technology
mg/dscm milligrams per dry standard cubic meter
MMBtu million British thermal unit
ng/dscm nanograms per dry standard cubic meter
NESHAP national emission standards for HAP
ng nanograms
POHC principal organic hazardous constituent
ppmv parts per million by volume
ppmw parts per million by weight
Pub. L. Public Law
RCRA Resource Conservation and Recovery Act
SRE system removal efficiency
TEQ toxicity equivalence
µg/dscm micrograms per dry standard cubic meter
U.S.C. United States Code

Table of Contents

Part One: Background and Summary
I. What Is the Statutory Authority for this Standard?
II. What Is the Regulatory Development Background of the Source Categories in the Final Rule?
A. Phase I Source Categories
B. Phase II Source Categories
III. How Was the Final Rule Developed?
IV. What Is the Relationship Between the Final Rule and Other MACT Combustion Rules?
V. What Are the Health Effects Associated with Pollutants Emitted by Hazardous Waste Combustors?
Part Two: Summary of the Final Rule
I. What Source Categories and Subcategories Are Affected by the Final Rule?
II. What Are the Affected Sources and Emission Points?
III. What Pollutants Are Emitted and Controlled?
IV. Does the Final Rule Apply to Me?
V. What Are the Emission Limitations?
VI. What Are the Testing and Initial Compliance Requirements?
A. Compliance Dates
B. Testing Requirements
C. Initial Compliance Requirements
VII. What Are the Continuous Compliance Requirements?
VIII. What Are the Notification, Recordkeeping, and Reporting Requirements?
IX. What Is the Health-Based Compliance Alternative for Total Chlorine, and How Do I Demonstrate Eligibility?
A. Overview
B. HCl-Equivalent Emission Rates
C. Eligibility Demonstration
D. Assurance that the 1-Hour HCl-Equivalent Emission Rate Will Not Be Exceeded
E. Review and Approval of Eligibility Demonstrations
F. Testing Requirements
G. Monitoring Requirements
H. Relationship Among Emission Rates, Emission Rate Limits, and Feedrate Limits
I. Changes
X. Overview on Floor Methodologies
Part Three: What Are the Major Changes Since Proposal?
I. Database
A. Hazardous Burning Incinerators
B. Hazardous Waste Cement Kilns
C. Hazardous Waste Lightweight Aggregate Kilns
D. Liquid Fuel Boilers
E. HCl Production Furnaces
F. Total Chlorine Emissions Data Below 20 ppmv
II. Emission Limits
A. Incinerators
B. Hazardous Waste Burning Cement Kilns
C. Hazardous Waste Burning Lightweight Aggregate Kilns
D. Solid Fuel Boilers
E. Liquid Fuel Boilers
F. Hydrochloric Acid Production Furnaces
G. Dioxin/Furan Testing for Sources Not Subject to a Numerical Standard
III. Statistics and Variability
A. Using Statistical Imputation to Address Variability of Nondetect Values
B. Degrees of Freedom when Imputing a Standard Deviation Using the Universal Variability Factor for Particulate Matter Controlled by a Fabric Filter
IV. Compliance Assurance for Fabric Filters, Electrostatic Precipitators, and Ionizing Wet Scrubbers
V. Health-Based Compliance Alternative for Total Chlorine
Part Four: What Are the Responses to Major Comments?
I. Database
A. Revisions to the EPA's Hazardous Waste Combustor Data Base
B. Use of Data from Recently Upgraded Sources
C. Correction of Total Chlorine Data to Address Potential Bias in Stack Measurement Method
D. Mercury Data for Cement Kilns
E. Mercury Data for Lightweight Aggregate Kilns
F. Incinerator Database
II. Affected Sources
A. Area Source Boilers and Hydrochloric Acid Production Furnaces
B. Boilers Eligible for the RCRA Low Risk Waste Exemption
C. Mobile Incinerators
III. Floor Approaches
A. Variability
B. SRE/Feed Methdology
C. Air Pollution Control Technology Methodologies for the Particulate Matter Standard and for the Total Chlorine Standard for Hydrochloric Acid Production Furnaces
D. Format of Standards
E. Standards Can Be No Less Stringent Than the Interim Standards
F. How Can EPA's Approach to Assessing Variability and its Ranking Methodologies be Reasonable when they Result in Standards Higher than the Interim Standards?
IV. Use of Surrogates
A. Particulate Matter as Surrogate for Metal HAP
B. Carbon Monoxide/Hydrocarbons and DRE as Surrogates for Dioxin/Furan
C. Use of Carbon Monoxide and Total Hydrocarbons as Surrogate for Non-Dioxin Organic HAP
V. Additional Issues Relating to Variability and Statistics
A. Data Sets Containing Nondetects
B. Using Statistical Imputation to Address Variability of Nondetect Values
C. Analysis of Variance Procedures to Assess Subcategorization
VI. Emission Standards
A. Incinerators
B. Cement Kilns
C. Lightweight Aggregate Kilns
D. Liquid Fuel Boilers
E. General
VII. Health-Based Compliance Alternative for Total Chlorine
A. Authority for Health-Based Compliance Alternatives
B. Implementation of the Health-Based Standards
C. National Health-Based Standards for Cement Kilns.
VIII. Implementation and Compliance
A. Compliance Assurance Issues for both Fabric Filters and Electrostatic Precipitators (and Ionizing Wet Scrubbers)
B. Compliance Assurance Issues for Fabric Filters
C. Compliance Issues for Electrostatic Precipitators and Ionizing Wet Scrubbers
D. Fugitive Emissions
E. Notification of Intent to Comply and Compliance Progress Report
F. Startup, Shutdown, and Malfunction Plan
G. Public Notice of Test Plans
H. Using Method 23 Instead of Method 0023A
I. Extrapolating Feedrate Limits for Compliance with the Liquid Fuel Boiler Mercury and Semivolatile Metal Standards
J. Temporary Compliance with Alternative, Otherwise Applicable MACT Standards
K. Periodic DRE Testing and Limits on Minimum Combustion Chamber Temperature for Cement Kilns
L. One Time Dioxin and Furan Test for Sources Not Subject to a Numerical Limit for Dioxin and Furan
M. Miscellaneous Compliance Issues
IX. Site-Specific Risk Assessment under RCRA
A. What Is the Site-Specific Risk Assessment Policy?
B. Why Might SSRAs Continue To Be Necessary for Sources Complying With Phase 1 Replacement Standards and Phase 2 Standards?
C. What Changes Are EPA Finalizing With Respect To the Site-Specific Risk Assessment Policy?
D. How Will the New SSRA Regulatory Provisions Work?
E. What Were Commenters' Reactions to EPA's Proposed Decision Not to Provide National Criteria for Determining When an SSRA Is or Is Not Necessary?

F. What Are EPA's Responses to the Cement Kiln Recycling Coalition's Comments on the Proposal and What is EPA's Final Decision on CKRC's Petition?
X. Permitting
A. What is the Statutory Authority for the RCRA Requirements Discussed in this Section?
B. Did Commenters Express any Concerns Regarding the Current Permitting Requirements?
C. Are There Any Changes to the Proposed Class 1 Permit Modification Procedure?
D. What Permitting Approach Is EPA Finalizing for New Units?
E. What Other Permitting Requirements Were Discussed In the Proposal?
Part Five: What Are the CAA Delegation Clarifications and RCRA State Authorization Requirements?
I. Authority for this Rule.
II. CAA Delegation Authority.
III. Clarifications to CAA Delegation Provisions for Subpart EEE.
A. Alternatives to Requirements.
B. Alternatives to Test Methods.
C. Alternatives to Monitoring.
D. Alternatives to Recordkeeping and Reporting.
E. Other Delegation Provisions
IV. RCRA State Authorization and Amendments To the RCRA Regulations.
Part Six: Impacts of the Final Rule
I. What Are the Air Impacts?
II. What Are the Water and Solid Waste Impacts?
III. What Are the Energy Impacts?
IV. What Are the Control Costs?
V. What Are the Economic Impacts?
A. Market Exit Estimates
B. Waste Reallocations
VI. What Are the Social Costs and Benefits of the Final Rule?
A. Combustion Market Overview
B. Baseline Specification
C. Analytical Methodology and Findings—Social Cost Analysis
D. Analytical Methodology and Findings—Benefits Assessment
Part Seven: How Does the Final Rule Meet the RCRA Protectiveness Mandate?
I. Background
II. Evaluation of Protectiveness
Part Eight: Statutory and Executive Order Reviews
I. Executive Order 12866: Regulatory Planning and Review
II. Paperwork Reduction Act
III. Regulatory Flexibility Act
IV. Unfunded Mandates Reform Act of 1995
V. Executive Order 13132: Federalism
VI. Executive Order 13175: Consultation and Coordination with Indian Tribal Governments
VII. Executive Order 13045: Protection of Children from Environmental Health Risks and Safety Risks
VIII. Executive Order 13211: Actions Concerning Regulations that Significantly Affect Energy Supply, Distribution, or Use
IX. National Technology Transfer and Advancement Act
X. Executive Order 12898: Federal Actions to Address Environmental Justice in Minority Populations and Low-Income Populations
XI. Congressional Review

Part One: Background and Summary

I. What Is the Statutory Authority for This Standard?

Section 112 of the Clean Air Act requires that the EPA promulgate regulations requiring the control of HAP emissions from major and certain area sources. The control of HAP is achieved through promulgation of emission standards under sections 112(d) and (in a second round of standard setting) (f).

EPA's initial list of categories of major and area sources of HAP selected for regulation in accordance with section 112(c) of the Act was published in the **Federal Register** on July 16, 1992 (57 FR 31576). Hazardous waste incinerators, Portland cement plants, clay products manufacturing (including lightweight aggregate kilns), industrial/commercial/institutional boilers and process heaters, and hydrochloric acid production furnaces are among the listed 174 categories of sources. The listing was based on the Administrator's determination that these sources may reasonably be anticipated to emit one or more of the 186 listed HAP in quantities sufficient to designate them as major sources.

II. What Is the Regulatory Development Background of the Source Categories in the Final Rule?

Today's notice finalizes standards for controlling emissions of HAP from hazardous waste combustors: incinerators, cement kilns, lightweight aggregate kilns, boilers, process heaters[1], and hydrochloric acid production furnaces that burn hazardous waste. We call incinerators, cement kilns, and lightweight aggregate kilns Phase I sources because we have already promulgated standards for those source categories. We call boilers and hydrochloric acid production furnaces Phase II sources because we intended to promulgate MACT standards for those source categories after promulgating MACT standards for Phase I sources. The regulatory background of Phase I and Phase II source categories is discussed below.

A. Phase I Source Categories

Phase I combustor sources are regulated under the Resource Conservation and Recovery Act (RCRA), which establishes a "cradle-to-grave" regulatory structure overseeing the safe treatment, storage, and disposal of hazardous waste. We issued RCRA rules to control air emissions from hazardous waste burning incinerators in 1981, 40 CFR Parts 264 and 265, Subpart O, and from cement kilns and lightweight aggregate kilns that burn hazardous waste in 1991, 40 CFR Part 266, Subpart H. These rules rely generally on risk-based standards to assure control necessary to protect human health and the environment, the applicable RCRA standard. See RCRA section 3004 (a) and (q).

The Phase I source categories also are subject to standards under the Clean Air Act. We promulgated standards for Phase I sources on September 30, 1999 (64 FR 52828). This final rule is referred to in this preamble as the Phase I rule or 1999 final rule. These emission standards created a technology-based national cap for hazardous air pollutant emissions from the combustion of hazardous waste in these devices. The rule regulates emissions of numerous hazardous air pollutants: dioxin/furans, other toxic organics (through surrogates), mercury, other toxic metals (both directly and through a surrogate), and hydrogen chloride and chlorine gas. Where necessary, Section 3005(c)(3) of RCRA provides the authority to impose additional conditions on a source-by-source basis in a RCRA permit if necessary to protect human health and the environment.

A number of parties, representing interests of both industrial sources and of the environmental community, sought judicial review of the Phase I rule. On July 24, 2001, the United States Court of Appeals for the District of Columbia Circuit granted portions of the Sierra Club's petition for review and vacated the challenged portions of the standards. *Cement Kiln Recycling Coalition* v. *EPA*, 255 F. 3d 855 (D.C. Cir. 2001). The court held that EPA had not demonstrated that its calculation of MACT floors met the statutory requirement of being no less stringent than (1) the average emission limitation achieved by the best performing 12 percent of existing sources and, for new sources, (2) the emission control achieved in practice by the best controlled similar source for new sources. 255 F.3d at 861, 865–66. As a remedy, the court, after declining to rule on most of the issues presented in the industry petitions for review, vacated the "challenged regulations," stating that: "[W]e have chosen not to reach the bulk of industry petitioners' claims, and leaving the regulations in place during remand would ignore petitioners' potentially meritorious challenges." Id.

[1] A process heater meets the RCRA definition of a boiler. Therefore, process heaters that burn hazardous wastes are covered under subpart EEE as boilers, and are discussed as such in subsequent parts of the preamble.

at 872. Examples of the specific challenges the Court indicated might have merit were provisions relating to compliance during start up/shut down and malfunction events, including emergency safety vent openings, the dioxin/furan standard for lightweight aggregate kilns, and the semivolatile metal standard for cement kilns. *Id.* However, the Court stated, "[b]ecause this decision leaves EPA without standards regulating [hazardous waste combustor] emissions, EPA (or any of the parties to this proceeding) may file a motion to delay issuance of the mandate to request either that the current standards remain in place or that EPA be allowed reasonable time to develop interim standards." Id.

Acting on this invitation, all parties moved the Court jointly to stay the issuance of its mandate for four months to allow EPA time to develop interim standards, which would replace the vacated standards temporarily, until final standards consistent with the Court's mandate are promulgated. The interim standards were published on February 13, 2002 (67 FR 6792). EPA did not justify or characterize these standards as conforming to MACT, but rather as an interim measure to prevent adverse consequences that would result from the regulatory gap resulting from no standards being in place. Id. at 6793, 6795–96; see also 69 FR at 21217 (April 20, 2004). EPA also entered into a settlement agreement, enforceable by the Court of Appeals, to issue final standard conforming to the Court's mandate by June 14, 2005. That date has since been extended to September 14, 2005.

B. Phase II Source Categories

Phase II combustors—boilers and hydrochloric acid production furnaces—are also regulated under the Resource Conservation and Recovery Act (RCRA) pursuant to 40 CFR Part 266, Subpart H, and (for reasons discussed below) are also subject to the MACT standard setting process in section 112(d) of the CAA. We delayed promulgating MACT standards for these source categories pending reevaluation of the MACT standard-setting methodology following the Court's decision to vacate the standards for the Phase I source categories. We also have entered into a judicially enforceable consent decree with Sierra Club that requires EPA to promulgate MACT standards for the Phase II sources by June 14, 2005, since extended to September 14, 2005—the same date that (for independent reasons) is required for the replacement standards for Phase I sources.

III. How Was the Final Rule Developed?

We proposed standards for HWCs on April 20, 2004 (69 FR 21197). The public comment period closed on July 6, 2004. In addition, on February 4, 2005, we requested certain key commenters to comment by email on a limited number of issues arising from public comments on the proposed rule. The comment period for those issues closed on March 7, 2005.

We received approximately 100 public comment letters on the proposed rule and the subsequent direct request for comments. Comments were submitted by owner/operators of HWCs, trade associations, state regulatory agencies and their representatives, and environmental groups. Today's final rule reflects our consideration of all of the comments and additional information we received. Major public comments on the proposed rule along with our responses, are summarized in this preamble.

IV. What Is the Relationship Between the Final Rule and Other MACT Combustion Rules?

The amendments to the Subpart EEE, Part 63, standards for hazardous waste combustors apply to the source categories that are currently subject to that subpart—incinerators, cement kilns, and lightweight aggregate kilns that burn hazardous waste. Today's final rule, however, also amends Subpart EEE to establish MACT standards for the Phase II source categories—those boilers and hydrochloric acid production furnaces that burn hazardous waste.

Generally speaking, you are an affected source pursuant to Subpart EEE if you combust, or have previously combusted, hazardous waste in an incinerator, cement kiln, lightweight aggregate kiln, boiler, or hydrochloric acid production furnace. You continue to be an affected source until you cease burning hazardous waste and initiate closure requirements pursuant to RCRA. Affected sources do not include: (1) Sources exempt from regulation under 40 CFR part 266, subpart H, because the only hazardous waste they burn is listed under 40 CFR 266.100(c); (2) research, development, and demonstration sources exempt under § 63.1200(b); and (3) boilers exempt from regulation under 40 CFR part 266, subpart H, because they meet the definition of small quantity burner under 40 CFR 266.108. See § 63.1200(b).

If you never previously combusted hazardous waste, or have ceased burning hazardous waste and initiated RCRA closure requirements, you are not subject to Subpart EEE. Rather, EPA has promulgated separate MACT standards for sources that do not burn hazardous waste within the following source categories: commercial and industrial solid waste incinerators (40 CFR Part 60, Subparts CCCC and DDDD); Portland cement manufacturing facilities (40 CFR Part 63, Subpart LLL); industrial/commercial/institutional boilers and process heaters (40 CFR Part 63, Subpart DDDDD); and hydrochloric acid production facilities (40 CFR Part 63, Subpart NNNNN). In addition, EPA considered whether to establish MACT standards for lightweight aggregate manufacturing facilities that do not burn hazardous waste, and determined that they are not major sources of HAP emissions. Thus, EPA has not established MACT standards for lightweight aggregate manufacturing facilities that do not burn hazardous waste.

Note that non-stack emissions points are not regulated under Subpart EEE.[2] Emissions attributable to storage and handling of hazardous waste prior to combustion (i.e., emissions from tanks, containers, equipment, and process vents) would continue to be regulated pursuant to either RCRA Subpart AA, BB, and CC and/or an applicable MACT that applies to the before-mentioned material handling devices. Emissions unrelated to the hazardous waste operations may be regulated pursuant to other MACT rulemakings. For example, Portland cement manufacturing facilities that combust hazardous waste are subject to both Subpart EEE and Subpart LLL, and hydrochloric acid production facilities that combust hazardous waste may be subject to both Subpart EEE and Subpart NNNNN.[3] In these instances Subpart EEE controls HAP emissions from the cement kiln and hydrochloric acid production furnace stack, while Subparts LLL and NNNNN would control HAP emissions from other operations that are not directly related to the combustion of hazardous waste (e.g., clinker cooler emissions for cement production facilities, and hydrochloric acid product transportation and storage for hydrochloric acid production facilities).

Note that if you temporarily cease burning hazardous waste for any reason, you remain an affected source and are still subject to the applicable Subpart

[2] Note, however, that fugitive emissions attributable to the combustion of hazardous waste from the combustion device are regulated pursuant to Subpart EEE.

[3] Hydrochloric acid production furnaces that combust hazardous waste are also affected sources subject to Subpart NNNNN if they produce a liquid acid product that contains greater than 30% hydrochloric acid.

EEE requirements. However, even as an affected source, the emission standards or operating limits do not apply if: (1) Hazardous waste is not in the combustion chamber and you elect to comply with other MACT (or CAA section 129) standards that otherwise would be applicable if you were not burning hazardous waste, e.g., the nonhazardous waste burning Portland Cement Kiln MACT (Subpart LLL); or (2) you are in a startup, shutdown, or malfunction mode of operation.

V. What Are the Health Effects Associated With Pollutants Emitted by Hazardous Waste Combustors?

Today's final rule protects air quality and promotes the public health by reducing the emissions of some of the HAP listed in Section 112(b)(1) of the CAA. Emissions data collected in the development of this final rule show that metals, hydrogen chloride and chlorine gas, dioxins and furans, and other organic compounds are emitted from hazardous waste combustors. The HAP that would be controlled with this rule are associated with a variety of adverse health affects. These adverse health effects include chronic health disorders (e.g., irritation of the lung, skin, and mucus membranes and effects on the blood, digestive tract, kidneys, and central nervous system), and acute health disorders (e.g., lung irritation and congestion, alimentary effects such as nausea and vomiting, and effects on the central nervous system). Provided below are brief descriptions of risks associated with HAP that are emitted from hazardous waste combustors.

Antimony

Antimony occurs at very low levels in the environment, both in the soils and foods. Higher concentrations, however, are found at antimony processing sites, and in their hazardous wastes. The most common industrial use of antimony is as a fire retardant in the form of antimony trioxide. Chronic occupational exposure to antimony (generally antimony trioxide) is most commonly associated with "antimony pneumoconiosis," a condition involving fibrosis and scarring of the lung tissues. Studies have shown that antimony accumulates in the lung and is retained for long periods of time. Effects are not limited to the lungs, however, and myocardial effects (effects on the heart muscle) and related effects (e.g., increased blood pressure, altered EKG readings) are among the best-characterized human health effects associated with antimony exposure. Reproductive effects (increased incidence of spontaneous abortions and higher rates of premature deliveries) have been observed in female workers exposed in an antimony processing facilities. Similar effects on the heart, lungs, and reproductive system have been observed in laboratory animals.

EPA assessed the carcinogenicity of antimony and found the evidence for carcinogenicity to be weak, with conflicting evidence from inhalation studies with laboratory animals, equivocal data from the occupational studies, negative results from studies of oral exposures in laboratory animals, and little evidence of mutagenicity or genotoxicity.[4] As a consequence, EPA concluded that insufficient data are available to adequately characterize the carcinogenicity of antimony and, accordingly, the carcinogenicity of antimony cannot be determined based on available information. However, the International Agency for Research on Cancer in an earlier evaluation, concluded that antimony trioxide is "possibly carcinogenic to humans" (Group 2B).

Arsenic

Chronic (long-term) inhalation exposure to inorganic arsenic in humans is associated with irritation of the skin and mucous membranes. Human data suggest a relationship between inhalation exposure of women working at or living near metal smelters and an increased risk of reproductive effects, such as spontaneous abortions. Inorganic arsenic exposure in humans by the inhalation route has been shown to be strongly associated with lung cancer, while ingestion or inorganic arsenic in humans has been linked to a form of skin cancer and also to bladder, liver, and lung cancer. EPA has classified inorganic arsenic as a Group A, human carcinogen.

Beryllium

Chronic inhalation exposure of humans to high levels of beryllium has been reported to cause chronic beryllium disease (berylliosis), in which granulomatous (noncancerous) lesions develop in the lung. Inhalation exposure to high levels of beryllium has been demonstrated to cause lung cancer in rats and monkeys. Human studies are limited, but suggest a causal relationship between beryllium exposure and an increased risk of lung cancer. We have classified beryllium as a Group B1, probable human carcinogen, when inhaled; data are inadequate to determine whether beryllium is carcinogenic when ingested.

Cadmium

Chronic inhalation or oral exposure to cadmium leads to a build-up of cadmium in the kidneys that can cause kidney disease. Cadmium has been shown to be a developmental toxicant in animals, resulting in fetal malformations and other effects, but no conclusive evidence exists in humans. An association between cadmium exposure and an increased risk of lung cancer has been reported from human studies, but these studies are inconclusive due to confounding factors. Animal studies have demonstrated an increase in lung cancer from long-term inhalation exposure to cadmium. EPA has classified cadmium as a Group B1, probable carcinogen.

Chlorine gas

Chlorine is an irritant to the eyes, the upper respiratory tract, and lungs. Chronic exposure to chlorine gas in workers has resulted in respiratory effects including eye and throat irritation and airflow obstruction. No information is available on the carcinogenic effects of chlorine in humans from inhalation exposure. A National Toxicology Program (NTP) study showed no evidence of carcinogenic activity in male rats or male and female mice, and equivocal evidence in female rats, from ingestion of chlorinated water. The EPA has not classified chlorine for potential carcinogenicity. In the absence of specific scientific evidence to the contrary, it is the Agency's policy to classify noncarcinogenic effects as threshold effects. RfC development is the default approach for threshold (or nonlinear) effects.

Chromium

Chromium may be emitted in two forms, trivalent chromium (chromium III) or hexavalent chromium (chromium VI). The respiratory tract is the major target organ for chromium VI toxicity for inhalation exposures. Bronchitis, decreases pulmonary function, pneumonia, and other respiratory effects have been noted from chronic high does exposure in occupational settings due to chromium VI. Limited human studies suggest that chromium VI inhalation exposure may be associated with complications during pregnancy and childbirth, while animal studies have not reported reproductive effects from inhalation exposure to chromium VI. Human and animal studies have clearly established that inhaled chromium VI is

[4] See "Evaluating THe Carcinogenicity of Antimony," Rish Assessment Issue Paper (98–030/07–26–99), Superfund Technical Support Center, National Center for Environmental Assessment, July 26, 1999.

a carcinogen, resulting in an increased risk of lung cancer. EPA has classified chromium VI as a Group A, human carcinogen.

Chromium III is less toxic than chromium VI. The respiratory tract is also the major target organ for chromium III toxicity, similar to chromium VI. Chromium III is an essential element in humans, with a daily intake of 50 to 200 micrograms per day recommended for an adult. The body can detoxify some amount of chromium VI to chromium III. EPA has not classified chromium III with respect to carcinogenicity.

Cobalt

Cobalt is a relatively rare metal that is produced primarily as a by-product during refining of other metals, especially copper. Cobalt has been widely reported to cause respiratory effects in humans exposed by inhalation, including respiratory irritation, wheezing, asthma, and pneumonia. Cardiomyopathy (damage to the heart muscle) has also been reported, although this effect is better known from oral exposure. Other effects of oral exposure in humans are polycythemia (an abnormally high number of red blood cells) and the blocking of uptake of iodine by the thyroid. In addition, cobalt is a sensitizer in humans by any route of exposure. Sensitized individuals may react to inhalation of cobalt by developing asthma or to ingestion or dermal contact with cobalt by developing dermatitis. Cobalt is as a vital component of vitamin B_{12}, though there is no evidence that intake of cobalt is ever limiting in the human diet.

A number of epidemiological studies have found that exposures to cobalt are associated with an increased incidence of lung cancer in occupational settings. The International Agency for Research on Cancer (part of the World Health Organization) classifies cobalt and cobalt compounds as "possibly carcinogenic to humans" (Group 2B). The American Conference of Governmental Industrial Hygienists has classified cobalt as a confirmed animal carcinogen with unknown relevance to humans (category A3). An EPA assessment concludes that under EPA's cancer guidelines, cobalt would be considered likely to be carcinogenic to humans.[5]

Dioxins and Furans

Exposures to 2,3,7,8-tetrachlorodibenzo-p-dioxin (2,3,7,8–TCDD) and related compounds at levels 10 times or less above those modeled to approximate average background exposure have resulted in adverse non-cancer health effects in animals. This statement is based on assumptions about the toxic equivalent for these compounds, for which there is acknowledged uncertainty. These effects include changes in hormone systems, alterations in fetal development, reduced reproductive capacity, and immunosuppression. Effects that may be linked to dioxin and furan exposures at low dose in humans include changes in markers of early development and hormone levels. Dioxin and furan exposures are associated with altered liver function and lipid metabolism changes in activity of various liver enzymes, depression of the immune system, and endocrine and nervous system effects. EPA in its 1985 dioxin assessment classified 2,3,7,8–TCDD as a probable human carcinogen. The International Agency for Research on Cancer (IARC) concluded in 1997 that the overall weight of the evidence was sufficient to characterize 2,3,7,8–TCDD as a known human carcinogen.[6] In 2001 the U.S. Department of Health and Human Services National Toxicology Program in their 9th Report on Carcinogens classified 2,3,7,8–TCDD as a known human carcinogen.[7]

The chemical and environmental stability of dioxins and their tendency to accumulate in fat have resulted in their detection within many ecosystems. In the United States and elsewhere, accidental contamination of the environment by 2,3,7,8–TCDD has resulted in deaths in many species of wildlife and domestic animals.[8] High residues of this compound in fish have resulted in closing rivers to fishing. Laboratory studies with birds, mammals, aquatic organisms, and other species have demonstrated that exposure to 2,3,7,8–TCDD can result in acute and delayed mortality as well as carcinogenic, teratogenic, mutagenic, histopathologic, immunotoxic, and reproductive effects, depending on dose received, which varied widely in the experiments.[9]

Hydrogen chloride/hydrochloric acid

Hydrogen chloride, also called hydrochloric acid, is corrosive to the eyes, skin, and mucous membranes. Chronic (long-term) occupational exposure to hydrochloric acid has been reported to cause gastritis, bronchitis, and dermatitis in workers. Prolonged exposure to low concentrations may also cause dental discoloration and erosion. No information is available on the reproductive or developmental effects of hydrochloric acid in humans. In rats exposed to hydrochloric acid by inhalation, altered estrus cycles have been reported in females and increased fetal mortality and decreased fetal weight have been reported in offspring. EPA has not classified hydrochloric acid for carcinogenicity. In the absence of specific scientific evidence to the contrary, it is the Agency's policy to classify noncarcinogenic effects as threshold effects. RfC development is the default approach for threshold (or nonlinear) effects.

Lead

Lead can cause a variety of effects at low dose levels. Chronic exposure to high levels of lead in humans results in effects on the blood, central nervous system, blood pressure, and kidneys. Children are particularly sensitive to the chronic effects of lead, with slowed cognitive development, reduced growth and other effects reported. Reproductive effects, such as decreased sperm count in men and spontaneous abortions in women, have been associated with lead exposure. The developing fetus is at particular risk from maternal lead exposure, with low birth weight and slowed postnatal neurobehavioral development noted. Human studies are inconclusive regarding lead exposure and cancer, while animal studies have reported an increase in kidney cancer from lead exposure by the oral route. EPA has classified lead as a Group B2, probable human carcinogen.

Manganese

Health effects in humans have been associated with both deficiencies and excess intakes of manganese. Chronic exposure to low levels of manganese in the diet is considered to be nutritionally essential in humans, with a recommended daily allowance of 2 to 5 milligrams per day (mg/d). Chronic

[5] See "Derivation of a Provisional Carcinogenicity Assessment for Cobalt and Compounds," Risk Assessment Issue Paper (00–122/1–15–02), Superfund Technical Support Center, National Center for Environmental Assessment, January 15, 2002. This is a provisional EPA assessment that has been externally peer reviewed but has not yet been incorporated in IRIS.

[6] IARC (International Agency for Research on Cancer). (1997) IARC monographs on the evaluation of carcinogenic risks to humans. Vol. 69. Polychlorinated dibenzo-para-dioxins and polychlorinated dibenzofurans. Lyon, France.

[7] The U.S. Department of Health and Human Services, National Toxicology Program 9th Report on Carcinogens, Revised January 2001.

[8] This does not necessarily apply in regard to laboratory testing, which tend to use 2,3,7,8 TCDD as the test compound.

[9] Eisler, R. 1986. Dioxin hazards to fish, wildlife, and invertebrates: a synoptic review. U.S. Fish and Wildlife Service Biological Report. 85(1.8).

exposure to high levels of manganese by inhalation in humans results primarily in central nervous system effects. Visual reaction time, hand steadiness, and eye-hand coordination were affected in chronically-exposed workers. Impotence and loss of libido have been noted in male workers afflicted with manganism attributed to inhalation exposures. EPA has classified manganese in Group D, not classifiable as to carcinogenicity in humans.

Mercury

Mercury exists in three forms: elemental mercury, inorganic mercury compounds (primarily mercuric chloride), and organic mercury compounds (primarily methyl mercury). Each form exhibits different health effects. Various sources may release elemental or inorganic mercury; environmental methyl mercury is typically formed by biological processes after mercury has precipitated from the air.

Chronic exposure to elemental mercury in humans also affects the central nervous system, with effects such as increased excitability, irritability, excessive shyness, and tremors. The EPA has not classified elemental mercury with respect to cancer.

The major effect from chronic exposure to inorganic mercury is kidney damage. Reproductive and developmental animal studies have reported effects such as alterations in testicular tissue, increased embryo resorption rates, and abnormalities of development. Mercuric chloride (an inorganic mercury compound) exposure has been shown to result in forestomach, thyroid, and renal tumors in experimental animals. EPA has classified mercuric chloride as a Group C, possible human carcinogen.

Nickel

Nickel is an essential element in some animal species, and it has been suggested it may be essential for human nutrition. Nickel dermatitis, consisting of itching of the fingers, hand and forearms, is the most common effect in humans from chronic exposure to nickel. Respiratory effects have also been reported in humans from inhalation exposure to nickel. No information is available regarding the reproductive of developmental effects of nickel in humans, but animal studies have reported such effects, although a consistent dose-response relationship has not been seen. Nickel forms released from industrial boilers include soluble nickel compounds, nickel subsulfide, and nickel carbonyl. Human and animal studies have reported an increased risk of lung and nasal cancers from exposure to nickel refinery dusts and nickel subsulfide. Animal studies of soluble nickel compounds i.e., nickel carbonyl) have reported lung tumors. The EPA has classified nickel refinery subsulfide as a Group A, human carcinogen and nickel carbonyl as a Group B2, probable human carcinogen.

Organic HAP

Organic HAPs include halogenated and nonhalogenated organic classes of compounds such as polycyclic aromatic hydrocarbons (PAHs) and polychlorinated biphenyls (PCBs). Both PAHs and PCBs are classified as potential human carcinogens, and are considered toxic, persistent and bioaccumulative. Organic HAP also include compounds such as benzene, methane, propane, chlorinated alkanes and alkenes, phenols and chlorinated aromatics. Adverse health effects of HAPs include damage to the immune system, as well as neurological, reproductive, developmental, respiratory and other health problems.

Particulate Matter

Atmospheric particulate matter (PM) is composed of sulfate, nitrate, ammonium, and other ions, elemental carbon, particle-bound water, a wide variety of organic compounds, and a large number of elements contained in various compounds, some of which originate from crustal materials and others from combustion sources. Combustion sources are the primary origin of trace metals found in fine particles in the atmosphere. Ambient PM can be of primary or secondary origin.

Exposure to particles can lead to a variety of serious health effects. The largest particles do not get very far into the lungs, so they tend to cause fewer harmful health effects. Fine particles pose the greatest problems because they can get deep into the lungs. Scientific studies show links between these small particles and numerous adverse health effects. Epidemiological studies have shown a significant correlation between elevated PM levels and premature mortality. Other important effects associated with PM exposure include aggravation of respiratory and cardiovascular disease (as indicated by increased hospital admissions, emergency room visits, absences from school or work, and restricted activity days), lung disease, decreased lung function, asthma attacks, and certain cardiovascular problems. Individuals particularly sensitive to PM exposure include older adults and people with heart and lung disease.

This is only a partial summary of adverse health and environmental effects associated with exposure to PM. Further information is found in the 2004 Criteria Document for PM ("Air Quality Criteria for Particulate Matter," EPA/600/P–99/002bF) and the 2005 Staff Paper for PM (EPA, "Review of the National Ambient Air Quality Standards for Particulate Matter, Policy Assessment of Scientific and Technical Information: OAQPS Staff Paper," (June 2005)).

Selenium

Selenium is a naturally occurring substance that is toxic at high concentrations but is also a nutritionally essential element. Studies of humans chronically exposed to high levels of selenium in food and water have reported discoloration of the skin, pathological deformation and loss of nails, loss of hair, excessive tooth decay and discoloration, lack of mental alertness, and listlessness. The consumption of high levels of selenium by pigs, sheep, and cattle has been shown to interfere with normal fetal development and to produce birth defects. Results of human and animal studies suggest that supplementation with some forms of selenium may result in a reduced incidence of several tumor types. One selenium compound, selenium sulfide, is carcinogenic in animals exposed orally. We have classified elemental selenium as a Group D, not classifiable as to human carcinogenicity, and selenium sulfide as a Group B2, probable human carcinogen.

Part Two: Summary of the Final Rule

I. What Source Categories and Subcategories Are Affected by the Final Rule?

Today's rule promulgates standards for controlling emissions of HAP from hazardous waste combustors: incinerators, cement kilns, lightweight aggregate kilns, boilers, and hydrochloric acid production furnaces that burn hazardous waste. A description of each source category can be found in the proposed rule (see 69 FR at 21207–08).

Hazardous waste burning incinerators, cement kilns, and lightweight aggregate kilns are currently subject to 40 CFR part 63, subpart EEE, National Emission Standards for Hazardous Air Pollutants (NESHAP). Today's rule revises the emissions limits and certain compliance and monitoring provisions of subpart EEE for these

source categories. The definitions of hazardous waste incinerator, hazardous waste cement kiln, and hazardous waste lightweight aggregate kiln appear at 40 CFR 63.1201(a).

Boilers that burn hazardous waste are also affected sources under today's rule. The rule uses the RCRA definition of a boiler under 40 CFR 260.10 and includes industrial, commercial, and institutional boilers as well as thermal units known as process heaters. Hazardous waste burning boilers will continue to comply with the emission standards found under 40 CFR part 266, subpart H (i.e., the existing RCRA rules) until they demonstrate compliance with the requirements of 40 CFR part 63, subpart EEE, and, for permitted sources, subsequently remove these requirements from their RCRA permit.

Finally, hydrochloric acid production furnaces that burn hazardous waste are affected sources under today's rule. These furnaces are a type of halogen acid furnace included in the definition of "industrial furnace" defined at § 260.10. Hydrochloric acid production furnaces that burn hazardous waste will continue to comply with the emission standards found under 40 CFR part 266, subpart H, until they demonstrate compliance with 40 CFR part 63, subpart EEE, and, for permitted sources, subsequently remove these requirements from their RCRA permit.

II. What Are the Affected Sources and Emission Points?

Today's rule apply to each major and area source incinerator, cement kiln, lightweight aggregate kiln, boiler, and hydrochloric acid production furnace that burns hazardous waste.[10] We note that only major source boilers and hydrochloric acid production furnaces are subject to the full suite of subpart EEE emission standards.[11] The emissions limits apply to each emission point (e.g., stack) where gases from the combustion of hazardous waste are discharged or otherwise emitted into the atmosphere. For facilities that have multiple combustion gas discharge points, the emission limits generally apply to each emission point. A cement kiln, for example, could be configured to have dual stacks where the majority of combustion gases are discharged though the main stack and other combustion gases emitted through a separate stack, such as an alkali bypass stack. In that case, the emission standards would apply separately to each of these stacks.[12]

III. What Pollutants Are Emitted and Controlled?

Hazardous waste combustors emit dioxin/furans, sometimes at high levels depending on the design and operation of the emission control equipment, and, for incinerators, depending on whether a waste heat recovery boiler is used. All hazardous waste combustors can also emit high levels of other organic HAP if they are not designed, operated, and maintained to operate under good combustion conditions.

Hazardous waste combustors can also emit high levels of metal HAP, depending on the level of metals in the waste feed and the design and operation of air emissions control equipment. Hazardous waste burning hydrochloric acid production furnaces, however, generally feed and emit low levels of metal HAP.

All of these HAP metals (except for the volatile metal mercury) are emitted as a portion of the particulate matter emitted by these sources. Hazardous waste combustors can also emit high levels of particulate matter, except that hydrochloric acid production furnaces generally feed hazardous wastes with low ash content and consequently emit low levels of particulate matter. A majority of particulate matter emissions from hazardous waste combustors are in the form of fine particulate. Particulate emissions from incinerators and liquid fuel-fired boilers depend on the ash content of the hazardous waste feed and the design and operation of air emission control equipment. Particulate emissions from cement kilns and lightweight aggregate kilns are not significantly affected by the ash content of the hazardous waste fuel because uncontrolled particulate emissions are attributable primarily to fine raw material entrained in the combustion gas. Thus, particulate emissions from kilns depends on operating conditions that effect entrainment of raw material, and the design and operation of the emission control equipment.

IV. Does the Final Rule Apply to Me?

The final rule applies to you if you own or operate a hazardous waste combustor—an incinerator, cement kiln, lightweight aggregate kiln, boiler, or hydrochloric acid production facility that burns hazardous waste. The final rule does not apply to a source that meets the applicability requirements of § 63.1200(b) for reasons explained at 69 FR at 21212–13.

V. What Are the Emission Limitations?

You must meet the emission limits in Tables 1 and 2 of this preamble for your applicable source category and subcategory. Standards are corrected to 7 percent oxygen. As noted at proposal, we previously promulgated requirements for carbon monoxide, total hydrocarbon, and destruction and removal efficiency standards under subpart EEE for incinerators, cement kilns, and lightweight aggregate kilns. We view these standards as unaffected by the Court's vacature of the challenged regulations in its decision of July 24, 2001. We are therefore not re-promulgating and reopening consideration of these standards in today's final rule, but are summarizing these standards in Tables 1 and 2 for reader's convenience.[13] See 69 FR at 21221, 21248, 21261 and 21274.

Liquid fuel boilers equipped with dry air pollution control devices are subject to different dioxin/furan emission standards than liquid fuel boilers that are not equipped with dry air pollution control devices.[14] Liquid fuel boilers processing hazardous waste with a heating value less than 10,000 BTU/lb must comply with the emission concentration-based standards (expressed as mass of total HAP emissions per volume of stack gas emitted) for mercury, semivolatile metals, low volatile metals, and total chlorine. Liquid fuel boilers processing hazardous waste with heating values greater than 10,000 BTU/lb must comply with thermal emissions-based standards (expressed as mass of HAP emissions attributable to the hazardous waste per million BTU input from the hazardous waste) for those same pollutants. Low volatile metal standards for liquid fuel boilers apply only to emissions of chromium, whereas the low volatile metal standard for the other source categories applies to the combined emissions of chromium, arsenic, and beryllium. Semivolatile metal standards apply to the combined emissions of lead and cadmium.

For any of the source categories except hydrochloric acid production

[10] A major source emits or has the potential to emit 10 tons per year of any single hazardous air pollutant or 25 tons per year or greater of hazardous air pollutants in the aggregate. An area source is a source that is not a major source.

[11] See Part Four, Section II.A for a discussion of the standards that are applicable to area source boilers and hydrochloric acid production furnaces.

[12] We note that there is a provision that allows cement kilns with dual stacks to average emissions on a flow-weighted basis to demonstrate compliance with the metal and chlorine emission standards. See §§ 63.1204(e) and 63.1220(3).

[13] We are also republishing these standards, for reader's convenience only, in the new replacement standard section for these source categories. See § 63.1219, § 63.1220 and § 673.1219.

[14] Liquid fuel boilers equipped with a wet air pollution control device followed by a dry air pollution control device do not meet the definition of a dry air pollution device.

furnaces, you may elect to comply with an alternative to the total chlorine standard under which you would establish site-specific, health-based emission limits for hydrogen chloride and chlorine based on national exposure standards. This alternative chlorine standard is discussed in part two, section IX and part four, section VII.

Incinerators and liquid and solid fuel boilers may elect to comply with an alternative to the particulate matter standard that would limit emissions of all the semivolatile metal HAPs and low volatile metal HAPs. Under this alternative, the numerical emission limits for semivolatile metal and low volatile metal emission HAP are identical to the limitations included in Tables 1 and 2. However, for semivolatile metals, the alternative standard applies to the combined emissions of lead, cadmium, and selenium; for low volatile metals, the standard applies to the combined emissions of chromium, arsenic, beryllium, antimony, cobalt, manganese, and nickel. See § 63.1219(e).

TABLE 1.—SUMMARY OF EMISSION LIMITS FOR EXISTING SOURCES

	Incinerators	Cement kilns	Lightweight aggregate kilns	Solid fuel-fired boilers [1]	Liquid fuel-fired boilers [1]	Hydrochloric acid production furnaces [1]
Dioxin/Furans (ng TEQ/dscm).	0.20 or 0.40 and temperature control < 400°F at APCD inlet [6].	0.20 or 0.40 and temperature control < 400°F at APCD inlet.	0.20 or rapid quench below 400°F at kiln exit.	CO or HC and DRE standard as a surrogate.	0.40 for dry APCD sources; CO or HC and DRE standard as surrogate for others.	CO or HC and DRE standard as surrogate.
Mercury	130 µg/dscm	Hazardous waste feed restriction of 3.0 ppmw and 120 µg/dscm MTEC [11]; or 120 µg/dscm total emissions.	120 hazardous waste MTEC [11] feed restriction or 120 µg/dscm total emissions.	11 µg/dscm	4.2E-5lb/MMBtu [2, 5] or 19 µg/dscm [2]; depending on BTU content of hazardous waste [13].	Total chlorine standard as surrogate.
Particulate Matter	0.013 gr/dscf [8]	0.028 gr/dscf and 20% opacity [12].	0.025 gr/dscf	0.030 gr/dscf [8]	0.035 gr/dscf [8]	Total chlorine standard as surrogate.
Semivolatile Metals (lead + cadmium).	230 µg/dscm	7.6 E-4 lbs/MMBtu [5] and 330 µg/dscm [3].	3.0E-4 lb/MMBtu [5] and 250 µg/dscm [3].	180 µg/dscm	8.2 E–5 lb/MMBtu [2, 5] or 150 µg/dscm [2]; depending on BTU content of hazardous waste [13].	Total chlorine standard as surrogate.
Low Volatile Metals (arsenic + beryllium + chromium).	92 µg/dscm	2.1 E-5 lbs/MMBtu [5] and 56 µg/dscm [3].	9.5E-5 lb/MMBtu [5] and 110 µg/dscm [3].	380 µg/dscm	1.26E–4 lbMMBtu [4, 5] or 370 µg/dscm [4]; depending on BTU content of hazardous waste [13].	Total chlorine standard as surrogate.
Total Chlorine (hydrogen chloride + chlorine gas).	32 ppmv [7]	120 ppmv [7]	600 ppmv [7]	440 ppmv [7]	5.08E–2 lb/MMBtu [5, 7] or 31 ppmv [7]; depending on BTU content of hazardous waste [13].	150 ppmv or 99.923% system removal efficiency.
Carbon Monoxide (CO) or Hydrocarbons (HC).	100 ppmv CO [9] or 10 ppmv HC.	See Note # 10 below.	100 ppmv CO [9] or 20 ppmv HC.	(2) 100 ppmv CO [9] or 10 ppmv HC		
Destruction and Removal Efficiency.	99.99% for each principal organic hazardous pollutant. For sources burning hazardous wastes F020, F021, F022, F023, F026, or F027, however, 99.9999% for each principal organic hazardous pollutant.					

Notes:

[1] Particulate matter, semivolatile metal, low volatile metal, and total chlorine standards for solid and liquid fuel boilers apply only to major sources. Particulate matter, semivolatile and low volatile metal standards for hydrochloric acid production furnaces apply only to major sources, although area sources must still comply with the surrogate total chlorine standard to control mercury emissions.

[2] Standard is based on normal emissions data, and is therefore expressed as an annual average emission limitation.

[3] Sources must comply with both the thermal emissions and emission concentration standards.

[4] Low volatile metal standard for liquid fuel-fired boilers is for chromium only.

[5] Standards expressed as mass of pollutant contributed by hazardous waste per million BTU contributed by the hazardous waste.

[6] APCD means "air pollution control device".

[7] Sources may elect to comply with site-specific risk-based emission limits for hydrogen chloride and chlorine gas

[8] Sources may elect to comply with an alternative to the particulate matter standard.

[9] Sources that elect to comply with the CO standard must demonstrate compliance with the HC standard during the comprehensive performance test that demonstrates compliance with the destruction and removal efficiency requirement.

[10] Kilns without a bypass: 20 ppmv HC or 100 ppmv CO [9]. Kilns with a bypass/mid-kiln sampling system: 10 ppmv HC or 100 ppmv CO9 in the bypass duct, mid-kiln sampling system or bypass stack.

[11] MTEC means "maximum theoretical emission concentration", and is equivalent to the feed rate divided by gas flow rate

[12] The opacity standard does not apply to a source equipped with a bag leak detection system under 63.1206(c)(8) or a particulate matter detection system under 63.1206(c)(9).

[13] Emission concentration-based standards apply to sources processing hazardous waste with energy content less than 10,000 BTU/lb; thermal emission standards apply to sources processing hazardous waste with energy content greater than 10,000 btu/lb.

TABLE 2.—SUMMARY OF EMISSION LIMITS FOR NEW OR RECONSTRUCTED SOURCES

	Incinerators	Cement kilns	Lightweight aggregate kilns	Solid fuel boilers [1]	Liquid fuel boilers [1]	Hydrochloric acid production furnaces [1]
Dioxin/Furans (ng TEQ/dscm).	0.11 for dry APCD and/or WHB [5] sources; 0.20 for other sources.	0.20 or 0.40 and temperature control <400 °F at APCD inlet.	0.20 or rapid quench <400 °F at kiln exit.	CO or HC and DRE standard as a surrogate.	0.40 for sources with dry APCD; CO or HC and DRE standard as a surrogate for other sources.	CO or THC and DRE standard as a surrogate.
Mercury	8.1 µg/dscm	Hazardous waste feed restriction of 1.9 ppmw and 120 µg/dscm MTEC [10]; or 120 µg/dscm total emissions.	120 hazardous waste MTEC [10] feed restriction or 120 µg/dscm total emissions.	11 µg/dscm	1.2E–6 lb/MMBtu [2 4] or 6.8 µg/dscm [2]; depending on BTU content of hazardous waste [12].	TCI as surrogate.
Particulate matter (gr/dscf).	0.0015 [7]	0.0023 and 20% opacity [11].	0.0098	0.015 [7]	0.0087 [7]	TCI as surrogate.
Semivolatile Metals (lead + cadmium).	10 µg/dscm	6.2E–5 lb/MMBtu [4] and 180 µg/dscm.	3.7 E–5 lb/MMBtu [4] and 43 µg/dscm.	180 µg/dscm	6.2 E–6 lb/MMBtu [2 4] or 78 µg/dscm [2]; depending on BTU content of hazardous waste [12].	TCI as surrogate.
Low Volatile Metals (arsenic + beryllium + chromium).	23 µg/dscm	1.5E–5 lb/MMBtu [4] and 54 µg/dscm.	3..3E–5 lb/MMBtu [4] and 110 µg/dscm.	190 µg/dscm	1.41E–5lb/MMBtu [3 4] or 12 µg/dscm [3]; depending on BTU content of hazardous waste [12].	TCI as surrogate.
Total Chlorine (Hydrogen chloride + chlorine gas).	21 ppmv [6]	86 ppmv [6]	600 ppmv [6]	73 ppmv [6]	5.08E–2 lb/MMBtu [4 6] or 31 ppmv [6]; depending on BTU content of hazardous waste [12].	25 ppmv or 99.987% SRE.
Carbon monoxide (CO) or Hydrocarbons (HC).	100 ppmv CO [8] or 10 ppmv HC.	See note #9 below.	100 ppmv CO [8] or 20 ppmv HC.	100 ppmv CO [8] or 10 ppmv HC		
Destruction and Removal Efficiency.	99.99% for each principal organic hazardous pollutant. For sources burning hazardous wastes F020, F021, F022, F023, F026, or F027, however, 99.9999% for each principal organic hazardous pollutant.					

Notes:

[1] Particulate matter, semivolatile metal, low volatile metal, and total chlorine standards for solid and liquid fuel boilers apply only to major sources. Particulate matter, semivolatile and low volatile metal standards for hydrochloric acid production furnaces apply only to major sources, although area sources must still comply with the surrogate total chlorine standard to control mercury emissions.

[2] Standard is based on normal emissions data, and is therefore expressed as an annual average emission limitation.

[3] Low volatile metal standard for liquid fuel-fired boilers is for chromium only. Arsenic and beryllium are not included in the low volatile metal total for liquid fuel-fired boilers.

[4] Standards expressed as mass of pollutant contributed by hazardous waste per million BTU contributed by the hazardous waste.

[5] APCD means "air pollution control device", WHB means "waste heat boiler".

[6] Sources may elect to comply with risk-based emission limits for hydrogen chloride and chlorine gas.

[7] Sources may elect to comply with an alternative to the particulate matter standard.

[8] Sources that elect to comply with the CO standard must demonstrate compliance with the THC standard during the comprehensive performance test that demonstrates compliance with the destruction and removal efficiency requirement.

[9] Greenfield kilns without a bypass: 20 ppmv HC or 100 ppmv CO [8] and 50 ppmv HC. Greenfield kilns with a bypass/mid kiln sampling system: Main stack standard of 50 ppmv HC and 10 ppmv HC or 100 ppmv CO [8] in the bypass duct, mid-kiln sampling system or bypass stack. Greenfield kilns with a bypass/mid-kiln sampling system: 10 ppmv HC or 100 ppmv CO [8] in the bypass duct, mid-kiln sampling system or bypass stack; Non-greenfield kilns without a bypass: 20 ppmv HC or 100 ppmv CO [8]. A greenfield kiln is a kiln whose construction commenced after April 19, 1996 at a plant site where a cement kiln (whether burning hazardous waste or not) did not previously exist.

[10] MTEC means "maximum theoretical emission concentration", and is equivalent to the feed rate divided by gas flow rate.

[11] The opacity standard does not apply to a source equipped with a bag leak detection system under 63.1206(c)(8) or a particulate matter detection system under 63.1206(c)(9).

[12] Emission concentration-based standards apply to sources processing hazardous waste with energy content less than 10,000 BTU/lb; thermal emission standards apply to sources processing hazardous waste with energy content greater than 10,000 btu/lb.

VI. What Are the Testing and Initial Compliance Requirements?

The testing and initial compliance requirements we promulgate today for solid fuel boilers, liquid fuel boilers, and hydrochloric acid production furnaces are identical to those that are applicable to incinerators, cement kilns, and lightweight aggregate kilns at §§ 63.1206, 63.1207, and 63.1208. We note, however, that today's final rule revises some of these requirements as they apply to all or specific HWCs (*e.g.*, one-time dioxin/furan test for sources not subject to a numerical dioxin/furan standard; dioxin/furan stack test method; hydrogen chloride and chlorine stack test methods)

We also discuss compliance and testing dates for incinerators, cement kilns, and lightweight aggregate kilns as well. Even though we are not repromulgating the compliance and testing requirements for those source categories, those sources must demonstrate compliance with the replacement emission standards promulgated today.

A. Compliance Dates

The time-line for testing and initial compliance requirements is as follows:

1. The compliance date is October 14, 2008;[15]

2. You must submit a comprehensive performance test plan to the permitting authority for review and approval 12 months prior to commencing the test.

3. You must submit an eligibility demonstration for the health-based compliance alternative to the total chlorine emission standard 12 months before the compliance date if you elect to comply with § 63.1215;

4. You must place in the operating record a Documentation of Compliance by the compliance date identifying the operating parameter limits that, using available information, you have determined will ensure compliance with the emission standards;

5. For boilers and hydrochloric acid production furnaces, you must commence the initial comprehensive performance test within 6 months after the compliance date;

6. For incinerators, cement kilns, and lightweight aggregate kilns, you must commence the initial comprehensive performance test within 12 months after the compliance date;

7. You must complete the initial comprehensive performance test within 60 days of commencing the test; and

8. You must submit a Notification of Compliance within 90 days of completing the test documenting compliance with emission standards and continuous monitoring system requirements.

B. Testing Requirements

All hazardous waste combustors must commence the initial comprehensive performance test under the time lines discussed above. The purpose of the comprehensive performance test is to document compliance with the emission standards of the final rule and establish operating parameter limits to maintain compliance with those standards. You must also conduct periodic comprehensive performance testing every five years.

If your source is subject to a numerical dioxin/furan emission standard (i.e., incinerators, cement kilns, lightweight aggregate kilns that comply with the 0.2 ng TEQ/dscm standard, and liquid fuel boilers equipped with a dry air pollution control device), you must conduct a dioxin/furan confirmatory performance test no later than 2.5 years after each comprehensive performance test (i.e., midway between comprehensive performance tests). If your source is not subject to a numerical dioxin/furan emission standard (e.g., solid fuel boilers, lightweight aggregate kilns that comply with the 400 °F temperature limit at the kiln exit, liquid fuel boilers equipped with wet or no air pollution control system, and hydrochloric acid production furnaces), you must conduct a one-time dioxin/furan test to enable the Agency to evaluate the effectiveness of the carbon monoxide/hydrocarbon standard and the destruction and removal efficiency standard in controlling dioxin/furan emissions for those sources. Previous dioxin/furan emission tests may be used to meet this requirement if the combustor operated under the conditions required by the rule and if design and operation of the combustor has not changed since the test in a manner that could increase dioxin/furan emissions. The Agency will use those emissions data when reevaluating the MACT standards under CAA section 112(d)(6), when determining whether to develop residual risk standards for these sources pursuant to section 112(f)(2), and when determining whether the source's RCRA Permit is protective of human health and the environment.

You must use the following stack test methods to document compliance with the emission standards: (1) Method 29 for mercury, semivolatile metals, and low volatile metals; and (2) Method 26/26A, Methods 320 or 321, or ASTM D 6735–01 for hydrogen chloride and chlorine;[16] (3) either Method 0023A or Method 23 for dioxin/furans; and (4) either Method 5 or 5i for particulate matter.

C. Initial Compliance Requirements

The initial compliance requirements for solid fuel boilers, liquid fuel boilers, and hydrochloric acid production furnaces include:[17]

1. You must place in the operating record a Documentation of Compliance by the compliance date identifying the operating parameter limits that, using available information, you have determined will ensure compliance with the emission standards;

2. You must develop and comply with a startup, shutdown, and malfunction plan;

3. You must install an automatic waste feed cutoff system that links the operating parameter limits to the waste feed cutoff system;

4. You must control combustion system leaks;

5. You must establish and comply with an operator training and certification program;

6. You must establish and comply with an operation and maintenance plan;

7. If your source is equipped with a baghouse, you must install either a bag leak detection system or a particulate matter detection system;[18] and

8. If your source is equipped with an electrostatic precipitator or ionizing wet scrubber, you must either establish site-specific control device operating parameter limits which limits are linked to the automatic waste feed cutoff system, or install a particulate matter detection system and take corrective measures when the alarm level is exceeded.

VII. What Are the Continuous Compliance Requirements?

The continuous compliance requirements for solid fuel boilers, liquid fuel boilers, and hydrochloric acid production furnaces are identical to those applicable to incinerators, cement kilns, and lightweight aggregate kilns. See § 63.1209. We note, however, that today's final rule revises some of these requirements as they apply to all or specific HWCs (e.g., bag leak detection system requirements; optional particulate matter detection system requirements; compliance assurance for thermal emissions-based standards).

You must use carbon monoxide or hydrocarbon continuous emissions monitors (as well as an oxygen continuous emissions monitor to correct the carbon monoxide or hydrocarbon values to 7% oxygen) to ensure compliance with the carbon monoxide or hydrocarbon emission standards.

You must also establish limits (as applicable) on the feedrate of metals, chlorine, and ash, key combustor operating parameters, and key operating

[15] See 69 FR at 21313 for rationale. We received no adverse comments at proposal.

[16] Note that you may be required to use other test methods to document emissions of hydrogen chloride and chlorine if you elect to comply with the alternative, health-based emission limits for total chlorine under § 63.1215. See § 63.1208(b)(5).

[17] These same requirements currently apply to incinerators, cement kilns, and lightweight aggregate kilns.

[18] A major difference between a bag leak detection system and a particulate matter detection system is the way the alarm level is established. The alarm level for a bag leak detection system is established using concepts in the Agency's bag leak detection system guidance document while the alarm level for a particulate matter detection system is established based on the detector response during the comprehensive performance test. The ash feedrate limit for incinerators and boilers is waived if you use a particulate matter detection system but not if you use a bag leak detection system because the bag leak detection system alarm level may not provide reasonable assurance of continuous compliance with the particulate matter emission standard.

parameters of the air pollution control device based on operations during the comprehensive performance test. You must continuously monitor these parameters with a continuous monitoring system.

VIII. What Are the Notification, Recordkeeping, and Reporting Requirements?

The notification, recordkeeping, and reporting requirements that we promulgate today for solid fuel boilers, liquid fuel boilers, and hydrochloric acid production furnaces are identical to those that are applicable to incinerators, cement kilns, and lightweight aggregate kilns. See §§ 63.1210 and 63.1211. We note, however, that today's final rule revises some of these requirements as they apply to all or specific HWCs.

You must submit notifications including the following to the permitting authority in addition to those required by the NESHAP General Provisions, subpart A of 40 CFR part 63:

1. Notification of changes in design, operation, or maintenance (§ 63.1206(b)(5)(i));

2. Notification of performance test and continuous monitoring system evaluation, including the performance test plan and continuous monitoring system performance evaluation plan (§ 63.1207(e));

3. Notification of compliance, including results of performance tests and continuous monitoring system evaluations (§§ 63.1210(b), 63.1207(j); 63.1207(k), and 63.1207(l)); and

4. Various notifications if you request or elect to comply with alternative requirements at § 63.1210(a)(2).

You must submit the following reports to the permitting authority in addition to those required by the NESHAP General Provisions, subpart A of 40 CFR part 63:

1. Startup, shutdown, and malfunction plan, if you elect to comply with § 63.1206(c)(2)(ii)(B));

2. Excessive exceedances report (§ 63.1206(c)(3)(vi)); and

3. Emergency safety vent opening reports (§ 63.1206(c)(4)(iv)).

Finally, you must keep records documenting compliance with the requirements of Subpart EEE. Recordkeeping requirements are prescribed in § 63.1211(b), and include requirements under the NESHAP General Provisions, subpart A of 40 CFR

IX. What Is the Health-Based Compliance Alternative for Total Chlorine, and How Do I Demonstrate Eligibility?

A. Overview

The rule allows you to establish and comply with health-based compliance alternatives for total chlorine for hazardous waste combustors other than hydrochloric acid production furnaces in lieu of the MACT technology-based emission standards established under §§ 63.1216, 63.1217, 63.1219, 63.1220, and 63.1221. See § 63.1215. To identify and comply with the limits, you must:

(1) Identify a total chlorine emission rate for each on-site hazardous waste combustor. You may select total chlorine emission rates as you choose to demonstrate eligibility for the health-based limits, except the total chlorine emission rate limits for incinerators, cement kilns, and lightweight aggregate kilns cannot result in total chlorine emission concentrations exceeding the Interim Standards provided by §§ 63.1203, 63.1204, and 63.1205;[19]

(2) Calculate the HCl-equivalent emission rate for the total chlorine emission rates you select, considering long-term exposure and using Reference Concentrations (RfCs) as the health threshold metric. This emission rate is called the annual average HCl-equivalent emission rate;

(3) Perform an eligibility demonstration to determine if your annual average HCl-equivalent emission rate meets the national exposure standard (i.e., Hazard Index not exceeding 1.0 considering the maximum annual average ambient concentration of hydrogen chloride and chlorine at an off-site receptor location which concentrations are attributable to all on-site hazardous waste combustors) and thus is below the annual average HCl-equivalent emission rate limit;

(4) Calculate the HCl-equivalent emission rate for the total chlorine emission rates you select, considering short-term exposure and using acute Reference Exposure Levels (aRELs) as the health threshold metric. This emission rate is called the 1-hour average HCl-equivalent emission rate.

(5) Determine whether your 1-hour HCl-equivalent emission rate may exceed the national exposure standard (i.e., Hazard Index not exceeding 1.0 considering the maximum 1-hour average ambient concentration of hydrogen chloride and chlorine at an off-site receptor location which concentrations are attributable to all on-site hazardous waste combustors) and thus may exceed the 1-hour average HCl-equivalent emission rate limit when complying with the annual average HCl-equivalent emission rate limit, absent an hourly rolling average limit on the feedrate of total chlorine and chloride.

(6) Submit your eligibility demonstration, including your determination of whether the 1-hour average HCl-equivalent emission rate limit may be exceeded absent an hourly rolling average limit on the feedrate of total chlorine and chloride, for review and approval;

(7) Document during the comprehensive performance test the total chlorine system removal efficiency for each combustor and use this system removal efficiency to calculate chlorine feedrate limits. Also, document that total chlorine emissions during the test do not exceed the 1-hour average HCl-equivalent emission rate limit during any run of the test. In addition, establish operating limits on the emission control device based on operations during the comprehensive performance test; and

(8) Comply with the requirements for changes in the design, operation, or maintenance of the facility which could affect the HCl-equivalent emission rate limits or system removal efficiency for total chlorine, and changes in the vicinity of your facility over which you do not have control (e.g., new receptors locating proximate to the facility).

B. HCl-Equivalent Emission Rates

You must express total chlorine emission rates (lb/hr) from each on-site hazardous waste combustor, including hydrochloric acid production furnaces[20], as an annual average HCl-equivalent emission rate and a 1-hour average HCl-equivalent emission rate. See § 63.1215(b). The annual average HCl-equivalent emission rate equates chlorine emission rates to hydrogen chloride (HCl) emission rates using Reference Concentrations (RfCs) as the health risk metric for long-term exposure. The 1-hour average HCl-equivalent emission rate equates chlorine emission rates to HCl emission rates using 1-hour Reference Exposure

[19] Note that the final rule sunsets the Interim Standards on the compliance date of today's rule but codifies the Interim Standards for total chlorine under § 63.1215(b)(7).

[20] Although hydrochloric acid production furnaces are not eligible for the health-based total chlorine emission limits (because control of total chlorine is a surrogate for control of metal HAP), you must consider total chlorine emissions from hydrochloric acid production furnaces when demonstrating that total chlorine emissions from all on-site hazardous waste combustors will not exceed the Hazard Index limit of 1.0 at an off-site receptor location.

Levels (aRELs) as the health risk metric for acute exposure.

To calculate HCl-equivalent emission rates, you must apportion total chlorine emissions (ppmv) between chlorine and HCl using the volumetric ratio of chlorine to hydrogen chloride (Cl_2/HCl).

- To calculate the annual average HCl-equivalent emission rate (lb/hr) and the emission rate limit, you must use the historical average Cl_2/HCl volumetric ratio from all regulatory compliance tests and the gas flowrate (and other relevant parameters) from the most recent RCRA compliance test or MACT performance test.
- To calculate the 1-hour average HCl-equivalent emission rate (lb/hr) and emission rate limit, you must use the highest Cl_2/HCl volumetric ratio from all regulatory compliance tests and the gas flowrate from the most recent RCRA compliance test or MACT performance test.
- If you believe that the Cl_2/HCl volumetric ratio for one or more historical compliance tests is not representative of the current ratio, you may request that the permitting authority allow you to screen those ratios from the analysis of historical ratios.
- If the permitting authority believes that too few historical Cl_2/HCl ratios are available to establish a representative average ratio and a representative maximum ratio, the permitting authority may require you to conduct periodic testing to establish representative ratios.
- You must include the Cl_2/HCl volumetric ratio demonstrated during each performance test in your data base of historical Cl_2/HCl ratios to update the ratios for subsequent calculations of the annual average and 1-hour average HCl-equivalent emission rates (and emission rate limits).

C. Eligibility Demonstration

You must perform an eligibility demonstration to determine whether the total chlorine emission rates you select for each on-site hazardous waste combustor meet the national exposure standard (i.e., the Hazard Index of 1.0 cannot be exceeded at an off-site receptor location considering maximum annual average ambient concentrations attributable to all on-site hazardous waste combustors and the RfCs for HCl and chlorine) using either a look-up table analysis or a site-specific compliance demonstration.[21] Eligibility for the health-based total chlorine standard is determined by comparing the annual average HCl-equivalent emission rate for the total chlorine emission rate you select for each combustor to the annual average HCl-equivalent emission rate limit.

The annual average HCl-equivalent emission rate limit is the HCl-equivalent emission rate, determined by equating the toxicity of chlorine to HCl using RfCs as the health risk metric for long-term exposure, which ensures that maximum annual average ambient concentrations of HCl equivalents do not exceed a Hazard Index of 1.0, rounded to the nearest tenths decimal place (0.1) and considering all on-site hazardous waste combustors. See § 63.1215(b)(2).

Your facility is eligible for the health-based compliance alternatives for total chlorine if either: (1) The annual average HCl-equivalent emission rate for each on-site hazardous waste combustor is below the HCl-equivalent emission rate limit determined from the appropriate value for the emission rate limit in the applicable look-up table and the proration procedure for multiple combustors discussed below; or (2) the annual average HCl-equivalent emission rate for each on-site hazardous waste combustor is below the annual average HCl-equivalent emission rate limit you calculate based on a site-specific compliance demonstration.

1. Look-Up Table Analysis

Look-up tables for the eligibility demonstration are provided as Tables 1 and 2 to § 63.1215. Table 1 presents annual average HCl-equivalent emission rate limits for sources located in flat terrain. For purposes of this analysis, flat terrain is terrain that rises to a level not exceeding one half the stack height within a distance of 50 stack heights.

Table 2 presents annual average HCl-equivalent emission rate limits for sources located in simple elevated terrain. For purposes of this analysis, simple elevated terrain is terrain that rises to a level exceeding one half the stack height, but that does not exceed the stack height within a distance of 50 stack heights.

If your facility is not located in either flat or simple elevated terrain, you must conduct a site-specific compliance demonstration.

To determine the annual average HCl-equivalent emission rate limit for a source from the look-up table, you must use the stack height and stack diameter for your hazardous waste combustors and the distance between the stack and the property boundary. If any of these values for stack height, stack diameter, and distance to nearest property boundary do not match the exact values in the look-up table, you must use the next lowest table value. If you have more than one hazardous waste combustor on site, you must adjust the emission rate limits provided by the tables such that the sum of the ratios for all combustors of the adjusted emission rate limit to the emission rate limit provided by the table cannot exceed 1.0. See § 63.1215 (c)(3)(v).

2. Site-Specific Compliance Demonstration

You may use any scientifically-accepted peer-reviewed risk assessment methodology for your site-specific compliance demonstration to calculate an annual average HCl-equivalent emission rate limit for each on-site hazardous waste combustor. An example of one approach for performing the demonstration for air toxics can be found in the EPA's "Air Toxics Risk Assessment Reference Library, Volume 2, Site-Specific Risk Assessment Technical Resource Document," which may be obtained through the EPA's Air Toxics Web site at *http://www.epa.gov/ttn/atw*.

To determine the annual average HCl-equivalent emission rate limit for each on-site hazardous waste combustor, your site-specific compliance demonstration must, at a minimum: (1) estimate long-term inhalation exposures through the estimation of annual or multi-year average ambient concentrations; (2) estimate the inhalation exposure for the actual individual most exposed to the facility's emissions from hazardous waste combustors, considering locations where people reside and where people congregate for work, school, or recreation; (3) use site-specific, quality-assured data wherever possible; (4) use health-protective default assumptions wherever site-specific data are not available, and: (5) contain adequate documentation of the data and methods used for the assessment so that it is transparent and can be reproduced by an experienced risk assessor and emissions measurement expert.

To establish the annual average HCl-equivalent emission rate limit for each combustor, you may apportion as you elect among the combustors the annual average HCl-equivalent emission rate limit for the facility, which limit ensures that the RfC-based Hazard Index of 1.0 is not exceeded.

[21] The total chlorine emission rates (lb/hr) for incinerators, cement kilns, and lightweight aggregate kilns cannot result in total chlorine emission concentrations (ppmv) exceeding the Interim Standards provided by §§ 63.1203, 63.1204, and 63.1205. The final rule sunsets the Interim Standards on the compliance date of today's rule but codifies the Interim Standards for total chlorine under § 63.1215(b)(7).

D. Assurance That the 1-Hour HCl-Equivalent Emission Rate Will Not Be Exceeded

The long-term, RfC-based Hazard Index will always be higher than the short-term, aREL-based Hazard Index for a constant HCl-equivalent emission rate because the health threshold levels for short-term exposure are orders of magnitude higher than the health threshold levels for long-term exposure.[22] Even though maximum 1-hour average ambient concentrations are substantially higher than maximum annual average concentrations, the higher short-term ambient concentrations do not offset the much higher health threshold levels for short-term exposures. Thus, the long-term, RfC-based Hazard Index will always govern regarding whether a source can make an eligibility demonstration. Accordingly, eligibility for the health-based emission limits is based solely on whether a source can comply with the annual average HCl-equivalent emission rate limit.

Nonetheless, some sources may have highly variably chlorine feedrates (and corresponding highly variable HCl-equivalent emission rates) such that they may feed chlorine at very high levels for short periods of time and still remain in compliance with the chlorine feedrate limit established to ensure compliance with the annual average HCl-equivalent emission rate limit.[23] To ensure that the 1-hour HCl-equivalent emission rate limit will not be exceeded during these periods of peak emissions, you must establish a 1-hour average HCl-equivalent emission rate and 1-hour average HCl-equivalent emission rate limit for each combustor and consider site-specific factors including prescribed criteria to determine if the 1-hour average HCl-equivalent emission rate limit may be exceeded absent an hourly rolling average limit on chlorine feedrate. If the 1-hour average HCl-equivalent emission rate limit may be exceeded, you must establish an hourly rolling average feedrate limit on chlorine.

You must calculate the 1-hour average HCl-equivalent emission rate from the total chlorine emission rate you select for each source.

You must establish the 1-hour average HCl-equivalent emission rate limit for each affected source using either a look-up table analysis or site-specific analysis. Look-up tables are provided for 1-hour average HCl-equivalent emission rate limits as Table 3 and Table 4 to this section. Table 3 provides limits for facilities located in flat terrain. Table 4 provides limits for facilities located in simple elevated terrain. You must use the Tables to establish emission rate limits in the same manner as you use Tables 1 and 2 to establish annual average HCl-equivalent emission rate limits.

If you conduct a site-specific analysis to establish a 1-hour average HCl-equivalent emission rate limit, you must follow the risk assessment procedures you used to establish an annual average HCl-equivalent emission rate limit. The 1-hour HCl-equivalent emission rate limit, however, is the emission rate than ensures that the Hazard Index associated with maximum 1-hour average exposures is not greater than 1.0.

You must consider criteria including the following to determine if a source may exceed the 1-hour HCl-equivalent emission rate limit absent an hourly rolling average chlorine feedrate limit: (1) The ratio of the 1-hour average HCl-equivalent emission rate based on the total chlorine emission rate you select for each hazardous waste combustor to the 1-hour average HCl-equivalent emission rate limit for the combustor; and (2) the potential for the source to vary total chlorine and chloride feedrates substantially over the averaging period for the feedrate limit you establish to ensure compliance with the annual average HCl-equivalent emission rate limit.

If you determine that a source may exceed the 1-hour average HCl-equivalent emission rate limit, you must establish an hourly rolling average chlorine feedrate limit as discussed below in Section G.

You must include the following information in your eligibility demonstration to document your determination whether an hourly rolling average feedrate limit is needed to maintain compliance with the 1-hour HCl-equivalent emission rate limit: (1) Determination of the Cl2/HCl volumetric ratio established for 1-hour average HCl-equivalent emission rate determinations as provided by § 63.1215(b)(6)(ii); (2) determination of the 1-hour average HCl-equivalent emission rate calculated from the total chlorine emission rate you select for the combustor; (3) determination of the 1-hour average HCl-equivalent emission rate limit; (4) determination of the ratio of the 1-hour average HCl-equivalent emission rate to the 1-hour HCl-equivalent emission rate limit for the combustor; and (5) determination of the potential for the source to vary chlorine feedrates substantially over the averaging period for the long-term feedrate limit (*i.e.*, 12-hours, or up to annually) established to maintain compliance with the annual average HCl-equivalent emission rate limit.

E. Review and Approval of Eligibility Demonstrations

The permitting authority will review and approve your eligibility demonstration. Your eligibility demonstration must contain, at a minimum, the information listed in § 63.1215(d)(1).

1. Review and Approval for Existing Sources

If you operate an existing source, you must submit the eligibility demonstration to your permitting authority for review and approval not later than 12 months prior to the compliance date. You must also submit a separate copy of the eligibility demonstration to: U.S. EPA, Risk and Exposure Assessment Group, Emission Standards Division (C404–01), Attn: Group Leader, Research Triangle Park, North Carolina 27711, electronic mail address *REAG@epa.gov*.

Your permitting authority should notify you of approval or intent to disapprove your eligibility demonstration within 6 months after receipt of the original demonstration, and within 3 months after receipt of any supplemental information that you submit. A notice of intent to disapprove your eligibility demonstration will identify incomplete or inaccurate information or noncompliance with prescribed procedures and specify how much time you will have to submit additional information or to comply with the MACT total chlorine standards. If your eligibility demonstration is disapproved, the permitting authority may extend the compliance date of the total chlorine standard to allow you to make changes to the design or operation of the combustor or related systems as quickly as practicable to enable you to achieve compliance with the MACT standard for total chlorine.

If your permitting authority has not approved your eligibility demonstration by the compliance date, and has not issued a notice of intent to disapprove your demonstration, you may nonetheless begin complying, on the compliance date, with the annual average HCl-equivalent emission rate limits you present in your eligibility demonstration.

If your permitting authority issues a notice of intent to disapprove your eligibility demonstration after the

[22] USEPA, "Technical Support Document for HWC MACT Standards, Volume III: Selection of MACT Standards," September 2005, Section 24.2.

[23] See discussion below in Section F regarding the requirement to establish chlorine feedrate limits.

compliance date, the authority will identify the basis for that notice and specify how much time you will have to submit additional information or to comply with the MACT total chlorine standards. The permitting authority may extend the compliance date of the total chlorine standard to allow you to make changes to the design or operation of the combustor or related systems as quickly as practicable to enable you to achieve compliance with the MACT standard for total chlorine.

2. Review and Approval for New and Reconstructed Sources

The procedures for review and approval of eligibility demonstrations applicable to existing sources discussed above also apply to new or reconstructed sources, except that the date you must submit the eligibility demonstration is as discussed below.

If you operate a new or reconstructed source that starts up by April 12, 2007, or a solid fuel-fired boiler or liquid fuel-fired boiler that is an area source that increases its emissions or its potential to emit such that it becomes a major source of HAP before April 12, 2007, you must either: (1) Submit an eligibility demonstration for review and approval by April 12, 2006 and comply with the HCl-equivalent emission rate limits and operating requirements you establish in the eligibility demonstration; or (2) comply with the final total chlorine emission standards under §§ 63.1216, 63.1217, 63.1219, 63.1220, and 63.1221, by October 12, 2005, or upon startup, whichever is later, except for a standard that is more stringent than the standard proposed on April 20, 2004 for your source. If a final standard is more stringent than the proposed standard, you may comply with the proposed standard until October 14, 2008, after which you must comply with the final standard.

If you operate a new or reconstructed source that starts up on or after April 12, 2007, or a solid fuel-fired boiler or liquid fuel-fired boiler that is an area source that increases its emissions or its potential to emit such that it becomes a major source of HAP on or after April 12, 2007, you must comply with either of the following. You may submit an eligibility demonstration for review and approval 12 months prior to startup. Alternatively, you may comply with the final total chlorine emission standards under §§ 63.1216, 63.1217, 63.1219, 63.1220, and 63.1221 upon startup. If the final standard is more stringent than the standard proposed for your source on April 20, 2004, however, and if you start operations before October 14, 2008, you may comply with the proposed standard until October 14, 2008, after which you must comply with the final standard.

F. Testing Requirements

You must comply with the requirements for comprehensive performance testing under § 63.1207.

1. Test Methods for Stack Gas Containing Alkaline Particulate

If you operate a cement kiln or a combustor equipped with a dry acid gas scrubber, you must use EPA Method 320/321 or ASTM D 6735–01, or an equivalent method, to measure hydrogen chloride, and the back-half (caustic impingers) of Method 26/26A, or an equivalent method, to measure chlorine.

2. Test Methods for Stack Gas Containing High Levels of Bromine or Sulfur

If you operate an incinerator, boiler, or lightweight aggregate kiln and your feedstreams contain bromine or sulfur during the comprehensive performance test at the levels indicated below, you must use EPA Method 320/321 or ASTM D 6735'01, or an equivalent method, to measure hydrogen chloride, and Method 26/26A, or an equivalent method, to measure chlorine and hydrogen chloride combined. You must determine your chlorine emissions to be the higher of: (1) The value measured by Method 26/26A, or an equivalent method; or (2) the value calculated by the difference between the combined hydrogen chloride and chlorine levels measured by Method 26/26a, or an equivalent method, and the hydrogen chloride measurement from EPA Method 320/321 or ASTM D 6735–01, or an equivalent method.

These procedures apply if you feed during the comprehensive performance test bromine at a bromine/chlorine ratio in feedstreams greater than 5 percent by mass, or sulfur at a sulfur/chlorine ratio in feedstreams greater than 50 percent by mass.[24]

Finally, you should precondition the M26/26A filter for one hour prior to beginning the performance test to minimize the potential for a low bias caused by adsorption/absorption of hydrogen chloride on the filter.

G. Monitoring Requirements

You must establish and comply with limits on the same operating parameters that apply to sources complying with the MACT standard for total chlorine under § 63.1209(o), except that feedrate limits on total chlorine and chloride must be established as described below.

1. Feedrate Limit to Ensure Compliance with the Annual Average HCl-Equivalent Emission Rate Limit

For sources subject to the feedrate limit for total chlorine and chloride under § 63.1209(n)(4) to ensure compliance with the semivolatile metals standard, the feedrate limit (and averaging period) for total chlorine and chloride to ensure compliance with the annual average HCl-equivalent emission rate limit is the same as required by that paragraph. Thus, the chlorine feedrate limit is the average of the run averages during the comprehensive performance test, and is established as a 12-hour rolling average.

That chlorine feedrate limit cannot exceed the numerical value (i.e., not considering the averaging period) of the feedrate limit that ensures compliance with the annual average HCl-equivalent emission rate limit, however. Therefore, the numerical value of the total chlorine and chloride feedrate limit must not exceed the value you calculate as the annual average HCl-equivalent emission rate limit (lb/hr) divided by [1 − system removal efficiency]. You must calculate a total chlorine system removal efficiency for each test run of the comprehensive performance test as [1 − total chlorine emission rate (g/s)/ chlorine feedrate (g/s)], and calculate the average system removal efficiency of the test run averages. If your source does not control total chlorine, you must assume zero system removal efficiency. If emissions during the comprehensive performance test exceed the annual average HCl-equivalent emission rate limit, eligibility for the health-based emission limits is not affected. This is because the emission rate limit is an annual average limit. Compliance is based on a 12-hour rolling average chlorine feedrate limit (rather than an (up to) an annual averaging period) for sources subject to the 12-hour rolling average feedrate limit for total chlorine and chloride under § 63.1209(n)(4) to ensure compliance with the semivolatile metals standard given that the more stringent feedrate limit (i.e., the feedrate limit with the shorter averaging period) would apply.

For sources exempt from the feedrate limit for total chlorine and chloride under § 63.1209(n)(4) because they comply with § 63.1207(m)(2) (which allows compliance with the semivolatile metals emission standard absent emissions testing by assuming all metals fed are emitted), the feedrate limit for total chlorine and chloride to ensure

[24] USEPA, "Technical Support Document for HWC MACT Standards, Volume IV: Compliance with the HWC MACT Standards," September 2005, Chapter 15.1.2.

compliance with the annual average HCl-equivalent emission rate must be established as follows:

- You must establish an average period for the feedrate limit that does not exceed an annual rolling average;
- You must calculate a total chlorine system removal efficiency for each test run of the comprehensive performance test as [1 − total chlorine emission rate (g/s)/chlorine feedrate (g/s)], and calculate the average system removal efficiency of the test run averages. If your source is not equipped with a control system that consistently and reproducibly controls total emissions (e.g., wet or dry scrubber), you must assume zero system removal efficiency. If emissions during the comprehensive performance test exceed the annual average HCl-equivalent emission rate limit, eligibility for emission limits under this section is not affected. The emission rate limit is an annual average limit and compliance is based on an annual average feedrate limit on total chlorine and chloride (or a shorter averaging period if you so elect under paragraph (g)(2)(ii)(A) of this section); and
- You must calculate the feedrate limit for total chlorine and chloride as the annual average HCl-equivalent emission rate limit (lb/hr) divided by [1 − system removal efficiency] and comply with the feedrate limit on the averaging period you establish.

2. Feedrate Limit To Ensure Compliance With the 1-Hour Average HCl-Equivalent Emission Rate Limit

You must establish an hourly rolling average feedrate limit on total chlorine and chloride to ensure compliance with the 1-hour average HCl-equivalent emission rate limit unless you determine that the hourly rolling average feedrate limit is waived as discussed under Section D above. If required, you must calculate the hourly rolling average feedrate limit for total chlorine and chloride as the 1-hour average HCl-equivalent emission rate limit (lb/hr) divided by [1 − system removal efficiency] using the system removal efficiency demonstrated during the comprehensive performance test.

H. Relationship Among Emission Rates, Emission Rate Limits, and Feedrate Limits

We summarize here the relationship among: (1) the total chlorine emission rate you select in your eligibility demonstration; (2) the annual average and 1-hour average HCl-equivalent emission rates you present in your eligibility demonstration; (3) the annual average and 1-hour average emission rate limits you present in your eligibility demonstration; (4) performance test emission rates for total chlorine and HCl-equivalent emissions; and (5) long-term and hourly rolling average chlorine feedrate limits.

1. Total Chlorine Emission Rate, Annual Average HCl-Equivalent Emission Rate, and Annual Average HCl-Equivalent Emission Rate Limit

For the eligibility demonstration, you must select a total chlorine emission concentration (ppmv) for each combustor, determine the Cl_2/HCl volumetric ratio, calculate the annual average HCl-equivalent emission rate (lb/hr), and document that the emission rate does not exceed the annual average HCl-equivalent emission rate limit.

You select a total chlorine (*i.e.*, HCl and chlorine combined) emission concentration (ppmv) for each hazardous waste combustor expressed as chloride ($Cl^{(-)}$) equivalent. For incinerators, cement kilns, and lightweight aggregate kilns, this emission concentration cannot exceed the Interim Standards for total chlorine. You then determine the average Cl_2/HCl volumetric ratio considering all historical regulatory emissions tests and apportion total chlorine emissions between Cl_2 and HCl accordingly. You use these apportioned volumetric emissions to calculate the Cl_2 and HCl emission rates (lb/hr) using the average gas flowrate (and other relevant parameters) for the most recent RCRA compliance test or MACT performance test for total chlorine. Finally, you use these Cl_2 and HCl emission rates to calculate an annual average HCl-equivalent emission rate, which cannot exceed the annual average HCl-equivalent emission rate limit that you establish as discussed below.

To establish the annual average HCl-equivalent emission rate limit, you may either use Tables 1 or 2 in § 63.1215 to look-up the limit, or conduct a site-specific risk analysis. Under the site-specific risk analysis option, the annual average HCl-equivalent emission rate limit would be the highest emission rate that the risk assessment estimates would result in a Hazard Index not exceeding 1.0 for the actual individual most exposed to the facility's emissions considering off-site locations where people reside and where people congregate for work, school, or recreation.

If you have more than one on-site hazardous waste combustor, and if you use the look-up tables to establish the annual average HCl-equivalent emission rate limits, the sum of the ratios for all combustors of the annual average HCl-equivalent emission rate to the annual average HCl-equivalent emission rate limit cannot not exceed 1.0. This will ensure that the RfC-based Hazard Index of 1.0 is not exceeded, a principle criterion of the eligibility demonstration.

If you use site-specific risk analysis to demonstrate that a Hazard Index of 1.0 is not exceeded, you would generally identify for each combustor the maximum annual average HCl-equivalent emission rate that the risk assessment estimates would result in an RfC-based Hazard Index of 1.0 at any off-site receptor location (i.e., considering locations where people reside and where people congregate for work, school, or recreation.[25] This emission rate would be the annual average HCl-equivalent emission rate limit for each combustor.

2. 1-Hour Average HCl-Equivalent Emission Rate and Emission Rate Limit

As discussed in Section D above, you must determine in your eligibility demonstration whether the 1-hour HCl-equivalent emission rate limit may be exceeded absent an hourly rolling average chlorine feedrate limit. To make this determination, you must establish a 1-hour average HCl-equivalent emission rate and a 1-hour average HCl-equivalent emission rate limit.

You calculate the 1-hour average HCl-equivalent emission rate from the total chlorine emission rate, established as discussed above, using the equation in § 63.1215(b)(3).

You establish the 1-hour average HCl-equivalent emission rate limit by either using Tables 3 or 4 in § 63.1215 to look-up the limit, or conducting a site-specific risk analysis. Under the site-specific risk analysis option, the 1-hour average HCl-equivalent emission rate limit would be the highest emission rate that the risk assessment estimates would result in an aREL-based Hazard Index not exceeding 1.0 at any off-site receptor location (i.e., considering locations where people reside and where people congregate for work, school, or recreation).

3. Performance Test Emissions

During the comprehensive performance test, you must demonstrate a system removal efficiency for total chlorine as [1 − TCl emitted (lb/hr)/chlorine fed (lb/hr)]. During the test, however, the total chlorine emission rate you select for each combustor and the annual average HCl-equivalent

[25] Note again, however, that the total chlorine emission concentration (ppmv) is capped by the Interim Standards for incinerators, cement kilns, and lightweight aggregate kilns.

emission rate limit can exceed the levels you present in the eligibility demonstration. This is because those emission rates are annual average rates and need not be complied with over the duration of three runs of the performance test, which may be nominally only 3 hours.

The 1-hour average HCl-equivalent emission rate limit cannot be exceeded during any run of the comprehensive performance test, however. This limit is based on an aREL Hazard Index of 1.0; an exceedance of the limit over a test run with a nominal 1-hour duration would result in a Hazard Index of greater than 1.0.

4. Chlorine Feedrate Limits

To maintain compliance with the annual average HCl-equivalent emission rate limit, you must establish a long-term average chlorine feedrate limit. In addition, if you determine under § 63.1205(d)(3) that the 1-hour average HCl-equivalent emission rate may be exceeded (i.e., because your chlorine feedrate may vary substantially over the averaging period for the long-term chlorine feedrate limit), you must establish an hourly rolling average chlorine feedrate limit.

Long-Term Chlorine Feedrate Limit. The chlorine feedrate limit to maintain compliance with the annual average HCl-equivalent emission rate is either: (1) The chlorine feedrate during the comprehensive performance test if you demonstrate compliance with the semivolatile metals emission standard during the test (see § 63.1209(o)); or (2) if you comply with the semivolatile metals emission standard under § 63.1207(m)(2) by assuming all metals in the feed to the combustor are emitted, the HCl-equivalent emission rate limit divided by [1 − system removal efficiency] where you demonstrate the system removal efficiency during the comprehensive performance test.

If you establish the chlorine feedrate limit based on the feedrate during the performance test to demonstrate compliance with the semivolatile metals emission standard, the averaging period for the feedrate limit is a 12-hour rolling average. If you establish the chlorine feedrate limit based on the system removal efficiency during the performance test, the averaging period is up to an annual rolling average. See discussion in Part Four, Section VII.B of this preamble.

If you comply with the semivolatile metals emission standard under § 63.1207(m)(2), however, the long-term chlorine feedrate limit is based on the system removal efficiency during the comprehensive performance test rather than the feedrate during the performance test. This is because the averaging period for this chlorine feedrate limit (that ensures compliance with the annual average HCl-equivalent emission rate limit) is up to an annual rolling average. See § 63.1215(g)(2). Thus, the chlorine feedrate, and total chlorine emissions, can be higher than the limit during the relatively short duration of the comprehensive performance tests.

Hourly Rolling Average Chlorine Feedrate Limit. If you determine under § 63.1205(d)(3) that the 1-hour average HCl-equivalent emission rate limit may be exceeded, you must establish an hourly rolling average chlorine feedrate limit. That feedrate limit is established as the 1-hour HCl-equivalent emission rate limit divided by [1 − system removal efficiency]. The hourly rolling average chlorine feedrate limit is not established based on feedrates during the performance test because performance test feedrates may be substantially lower than the feedrate needed to ensure compliance with the 1-hour average HCl-equivalent emission rate. Note, however, that the hourly rolling average feedrate limit cannot be exceeded during any run of the comprehensive performance test. This chlorine feedrate limit is based on the 1-hour average HCl-equivalent emission rate limit, which is based on an aREL Hazard Index of 1.0. Thus, an exceedance of the hourly rolling average feedrate limit (and the 1-hour lHCl-equivalent emission rate limit) over a test run with a nominal 1-hour duration would result in a Hazard Index of greater than 1.0.

I. Changes

Your requirements will change in response to changes that affect the HCl-equivalent emission rate or HCl-equivalent emission rate limit for a source.

1. Changes Over Which You Have Control

Changes That Affect HCl-Equivalent Emission Rate Limits. If you plan to change the design, operation, or maintenance of the facility in a manner that would decrease the annual average or 1-hour average HCl-equivalent emission rate limit (*e.g.*, reduce the distance to the property line; reduce stack gas temperature; reduce stack height), prior to the change you must submit to the permitting authority a revised eligibility demonstration documenting the lower emission rate limits and calculations of reduced total chlorine and chloride feedrate limits.

If you plan to change the design, operation, or maintenance of the facility in a manner than would increase the annual average or 1-hour average HCl-equivalent emission rate limit, and you elect to increase your total chlorine and chloride feedrate limits, prior to the change you must submit to the permitting authority a revised eligibility demonstration documenting the increased emission rate limits and calculations of the increased feedrate limits prior to the change.

Changes That Affect System Removal Efficiency. If you plan to change the design, operation, or maintenance of the combustor in a manner than could decrease the system removal efficiency, you are subject to the requirements of § 63.1206(b)(5) for conducting a performance test to reestablish the combustor's system removal efficiency. You also must submit a revised eligibility demonstration documenting the lower system removal efficiency and the reduced feedrate limits on total chlorine and chloride.

If you plan to change the design, operation, or maintenance of the combustor in a manner than could increase the system removal efficiency, and you elect to document the increased system removal efficiency to establish higher feedrate limits on total chlorine and chloride, you are subject to the requirements of § 63.1206(b)(5) for conducting a performance test to reestablish the combustor's system removal efficiency. You must also submit a revised eligibility demonstration documenting the higher system removal efficiency and the increased feedrate limits on total chlorine and chloride.

2. Changes Over Which You Do Not Have Control

If you use site-specific risk assessment in lieu of the look-up tables to establish the HCl-equivalent emission rate limit, you must review the documentation you use in your eligibility demonstration every five years from the date of the comprehensive performance test and submit for review and approval with the comprehensive performance test plan either a certification that the information used in your eligibility demonstration has not changed in a manner that would decrease the annual average HCl-equivalent emission rate limit, or a revised eligibility demonstration. Examples of changes beyond your control that may decrease the annual average HCl-equivalent emission rate limit (or 1-hour average HCl-equivalent emission rate limit) are construction of residences at a location exposed to higher ambient

concentrations than evaluated during your previous risk analysis, or a reduction in the RfCs or aRELs.

If, in the interim between the dates of your comprehensive performance tests, you have reason to know of changes that would decrease the annual average HCl-equivalent emission rate limit, you must submit a revised eligibility demonstration as soon as practicable but not more frequently than annually.

If you determine that you cannot demonstrate compliance with a lower annual average HCl-equivalent emission rate limit (dictated by a change over which you do not have control) during the comprehensive performance test because you need additional time to complete changes to the design or operation of the source or related systems, you may request that the permitting authority grant you additional time to make those changes as quickly as practicable.

X. Overview on Floor Methodologies

The most contentious issue in the rulemaking involved methodologies for determining MACT floors, namely, which sources are best performing, and what is their level of performance. Superficially, these questions have a ready answer: the best performers are the lowest emitters as measured by compliance tests, and those tests fix their level of performance. But compliance tests are snapshots which do not fully capture sources' total operating variability. Since the standards must be met at all times, picking lowest compliance test data to set the standard results in standards best performing sources themselves would be unable to meet at all times.

To avoid this impermissible result, EPA selected approaches that reasonably estimate best performing sources' total variability. Certain types of variability can be quantified statistically, and EPA did so here (using standard statistical approaches) in all of the floor methodologies used in the rule. There are other components of variability, however, which cannot be fully quantified, but nonetheless must be accounted for in reasonably estimating best performing sources' performance over time. EPA selected ranking methodologies which best account for this total variability.

Where control of the feed of HAP is feasible and technically assessable (the case for HAP metals and for total chlorine), EPA used a methodology that ranked sources by their ability to best control both HAP feed and HAP emissions. This methodology thus assesses the efficiency of control of both the HAP inputs to a hazardous waste combustion unit, and the efficiency of control of the unit's outputs. This methodology reasonably selects the best performing (and for new sources, best controlled) sources, and reasonably assesses their level of performance. When HAP feed control is not feasible, notably where HAP is contributed by raw material and fossil fuel inputs, EPA determined best performers and their level of performance using a methodology that selects the lowest emitters using the best air pollution control technology. This methodology reasonably estimates the best performing sources' level of performance, and better accounts for total variability in emissions levels of the best performing sources.

EPA carefully examined approaches selecting lowest emitters as best performers. Examination of other test conditions from the same best performing sources shows, however, that this approach results in standards not achievable even by the best performers. Indeed, in order to meet such standards, even "best performing" sources (lowest emitting in individual tests) would have to add additional air pollution control technology. EPA views this result as an end run around the section 112(d)(2) beyond-the-floor process, because floor standards would force industry-wide technological changes without consideration of the factors (cost and energy in particular) which Congress mandated for consideration when establishing beyond-the-floor standards.

Part Three: What Are the Major Changes Since Proposal?

I. Database

A. Hazardous Burning Incinerators

Five incinerators have been removed from the database because they have initiated or completed RCRA closure.[26] Two incinerators have been added to the list of sources used to calculate the floor levels.[27] Emissions data from source 3015 has been excluded for purposes of calculating the particulate matter floor because the source was processing an atypical waste stream from a particulate matter compliance perspective. See part four, section I.F. We have excluded the most recent mercury and dioxin/furan emissions data from source 327, and have instead used data from an older test condition to represent this source's emissions because the source encountered problems with its carbon injection system during the most recent test. See part four, section I.F. Emissions data from source 3006 has been excluded for purposes of calculating the semivolatile metal standard because this source did not measure cadmium emissions during its emissions test. See part four, section I.F. We have added mercury emissions data from source 901 (DSSI) to the incinerator mercury database because this source (which is otherwise subject to standards for liquid fuel boilers) is burning a waste which is unlike that burned by any other liquid fuel boiler with respect to mercury concentration and waste provenance, but typical of waste burned by incinerators with respect to those factors. See part four, section VI.D.1. This change correspondingly affects the liquid fuel boiler standard by removing that data from the liquid fuel boiler database.

B. Hazardous Waste Cement Kilns

1. Use of Emissions Data From Ash Grove Cement Company

The emissions data from Ash Grove Cement Company, which operates a recently constructed preheater/precalciner kiln located in Chanute, Kansas, are considered when calculating MACT floors for new hazardous waste burning cement kilns. In the proposal, we did not consider their emissions data in the floor analyses for existing sources because Ash Grove Cement used the data to demonstrate compliance with the new source interim standards, and did not address the data for purposes of new source standards. See 69 FR at 21217 n. 35. Consistent with our position on use of post-1999 emissions data, we are including Ash Grove Cement's emissions data in the floor analyses for new sources. See also Part Four, Section I.B of the preamble.

2. Removal of Holcim's Emissions Data From EPA's HWC Data Base

Following cessation of hazardous waste operations in 2003, we are removing all emissions data from both wet process cement kilns at Holcim's Holly Hill, South Carolina, plant from our hazardous waste combustor data base. This is consistent with our approach in both this rule and the 1999 rule to base the standards only on performance of sources that actually are operating (i.e., burning hazardous waste). See also Part Four, Section I.A and 64 FR at 52844.

[26] See "Final Technical Support Document for HWC MACT Standards, Volume II: HWC Database" for a list of the sources that have initiated or completed RCRA closure.

[27] We noticed the data from these sources but did not include them in the MACT standard calculations at proposal. Note that inclusion of these sources did not affect any of the calculated MACT standards. See "Final Technical Support Document for HWC MACT Standards, Volume II: HWC Database" for more discussion.

3. Use of Mercury Data

As discussed below, we are using a commenter-submitted dataset as the basis of the mercury standards for existing and new cement kilns. This comprehensive dataset documents the day-to-day levels of mercury in hazardous waste fired to all cement kilns for a three year period covering 1999 to 2001. We have determined that the commenter-submitted data are more representative than data used at proposal. See Part Four, Section I.D of the preamble for our rationale.

C. Hazardous Waste Lightweight Aggregate Kilns

We are incorporating mercury data submitted by a commenter into the MACT floor analysis for existing and new lightweight aggregate kilns. These data document the day-to-day levels of mercury in hazardous waste fired to lightweight aggregate kilns located at Solite Corporation's Arvonia plant between October 2003 and June 2004. We have determined that the commenter-submitted data are more representative than the data used at proposal. See Part Four, Section I.E of the preamble for our rationale.

D. Liquid Fuel Boilers

In the proposed rule, we classified liquid fuel boilers as one category. The final rule classifies them into two for purposes of the mercury, semivolatile metals, chromium, and total chlorine standards: one for liquid fuel boilers burning lower heating value hazardous waste (hazardous waste with a heating value less than 10,000 Btu/lb), and another for liquid fuel boilers burning higher heating value hazardous waste (hazardous waste with a heating value of 10,000 Btu/lb or greater).

We also made other, minor changes to the data base because some sources have initiated closure, were misclassified as other sources in the proposed rule, or were inadvertently not considered in the floor calculations although the sources' test reports were in the docket at proposal.

E. HCl Production Furnaces

Six of the 17 hydrochloric acid production furnaces have ceased burning hazardous waste since proposal. Consequently, we do not use emissions data from these sources to establish the final standards. All six of these sources were equipped with waste heat recovery boilers and had relatively high dioxin/furan emissions. In addition, we reclassified source #2020 as a boiler based on comments received at proposal.

F. Total Chlorine Emissions Data Below 20 ppmv

We corrected all the total chlorine measurements in the data base that were below 20 ppmv to account for potential systemic negative biases in the Method 0050 data in response to comments on the proposed rule. See the discussion in Part Four, Section I.C.1 below.

To account for the bias, we corrected all total chlorine emissions data that were below 20 ppmv to 20 ppmv. We accounted for within-test condition emissions variability for the corrected data by imputing a standard deviation that is based on a regression analysis of run-to-run standard deviation versus emission concentration for all data above 20 ppmv. This approach of using a regression analysis to impute a standard deviation is similar to the approach we used to account for total variability (i.e., test-to-test and within test variability) of PM emissions for sources that use fabric filters.

II. Emission Limits

A. Incinerators

The changes in the incinerator standards for existing sources since proposal are:

Standard	Proposed limit	Final limit
Dioxin/Furans (ng TEQ/dscm)	Sources with dry air pollution control systems or waste heat boilers: 0.28; For others: 0.2 or 0.4 and temperature control at inlet of air pollution control device < 400 °F.	For all sources, 0.20 or 0.40 and temperature control < 400 °F at the air pollution control device inlet.
Particulate Matter (gr/dscf)	0.015	0.013.
Semivolatile Metals (µg/dscm)	59	230.
Low Volatile Metals (µg/dscm)	84	92.
Total Chlorine (ppmv)	1.5	32.
Alternative to the particulate matter standard: Combined emissions of lead, cadmium and selenium (µg/dscm).	59	230.
Alternative to the particulate matter standard: Combined emissions of arsenic, berrylium, chrome, antimony, cobalt, manganese, and nickel (µg/dscm).	84	92.

The changes in the incinerator standards for new sources since proposal are:

Standard	Proposed limit	Final limit
Particulate Matter (gr/dscf)	0.0007	0.0015
Mercury (µg/dscm)	8.0	8.1
Semivolatile Metals (µg/dscm)	6.5	10
Low Volatile Metals (µg/dscm)	8.9	23
Total Chlorine (ppmv)	0.18	21
Alternative to the particulate matter standard: Combined emissions of lead, cadmium and selenium (µg/dscm)	6.5	10
Alternative to the particulate matter standard: Combined emissions of arsenic, berrylium, chrome, antimony, cobalt, manganese, and nickel (µg/dscm)	8.9	23

Hazardous Waste Burning Cement Kilns

The changes in the standards for existing cement kiln since proposal are:

Standard	Proposed limit	Final limit
Mercury (µg/dscm)	64[1]	Both 3.0 ppmw[2] and either 120 µg/dscm (stack emissions) or 120 µg/dscm (expressed as a hazardous waste MTEC)[3].
Particulate matter	0.028 gr/dscf	0.028 gr/dscf *and* 20% opacity[4].
Semivolatile metals	4.0E–04 lb/MMBtu[5]	7.6E–04 lb/MMBtu[5] *and* 330 µg/dscm.
Low volatile metals	1.4E–05 lb/MMBtu[5]	2.1E–05 lb/MMBtu[5] *and* 56 µg/dscm.
Total chlorine (ppmv)[6]	110	120.

[1] The proposed mercury standard was an annual limit.
[2] Feed concentration of mercury in hazardous waste as-fired.
[3] HW MTEC means maximum theoretical emissions concentration of the hazardous waste and MTEC is defined at § 63.1201(a).
[4] The opacity standard does not apply to a source equipped with a bag leak detection system under § 63.1206(c)(8) or a particulate matter detection system under § 63.1206(c)(9).
[5] Standard is expressed as mass of pollutant stack emissions attributable to the hazardous waste per million British thermal unit heat input of the hazardous waste.
[6] Combined standard, reported as a chloride ($Cl^{(-)}$) equivalent.

The changes in the standards for new cement kilns since proposal are:

Standard	Proposed limit	Final limit
Mercury (µg/dscm)	35[1]	Both 1.9 ppmw[2] and either 120 µg/dscm (stack emissions) or 120 µg/dscm (expressed as a hazardous waste MTEC)[3].
Particulate matter	0.0058 gr/dscf	0.0023 gr/dscf and 20% opacity[4].
Semivolatile metals	6.2E–05 lb/MMBtu[5]	6.2E–05 lb/MMBtu[5] *and* 180 µg/dscm.
Low volatile metals	1.4E–05 lb/MMBtu[5]	1.5E–05 lb/MMBtu[5] *and* 54 µg/dscm.
Total chlorine (ppmv)[6]	78	86.

[1] The proposed mercury standard was an annual limit.
[2] Feed concentration of mercury in hazardous waste as-fired.
[3] HW MTEC means maximum theoretical emissions concentration of the hazardous waste and MTEC is defined at § 63.1201(a).
[4] The opacity standard does not apply to a source equipped with a bag leak detection system under § 63.1206(c)(8) or a particulate matter detection system under § 63.1206(c)(9).
[5] Standard is expressed as mass of pollutant stack emissions attributable to the hazardous waste per million British thermal unit heat input of the hazardous waste.
[6] Combined standard, reported as a chloride ($Cl^{(-)}$) equivalent.

C. Hazardous Waste Burning Lightweight Aggregate Kilns

The changes in the standards for existing lightweight aggregate kilns since proposal are:

Standard	Proposed limit	Final limit
Dioxins and furans (ng TEQ/dscm)	0.40	0.20 *or* rapid quench of the flue gas at the exit of the kiln to less than 400 °F.
Mercury (µg/dscm)	67[1]	120 µg/dscm (stack emissions) or 120 µg/dscm (expressed as a hazardous waste MTEC)[2].
Semivolatile metals	3.1E–04 lb/MMBtu[3] *and* 250 µg/dscm	3.0E–04 lb/MMBtu[3] *and* 250 µg/dscm.

[1] The proposed mercury standard was an annual limit.
[2] HW MTEC means maximum theoretical emissions concentration of the hazardous waste and MTEC is defined at § 63.1201(a).
[3] Standard is expressed as mass of pollutant stack emissions attributable to the hazardous waste per million British thermal unit heat input of the hazardous waste.

The changes in the standards for new lightweight aggregate kilns since proposal are:

Standard	Proposed limit	Final limit
Dioxins and furans (ng TEQ/dscm)	0.40	0.20 *or* rapid quench of the flue gas at the exit of the kiln to less than 400 °F.

Standard	Proposed limit	Final limit
Particulate matter	0.0099 gr/dscf	0.0098 gr/dscf.
Mercury (μg/dscm)	67[1]	120 μg/dscm (stack emissions) or 120 μg/dscm (expressed as a hazardous waste MTEC)[2].
Semivolatile metals	2.4E–05 lb/MMBtu[3] *and* 43 μg/dscm	3.7E–05 lb/MMBtu[3] *and* 43 μg/dscm.

[1] The proposed mercury standard was an annual limit.
[2] HW MTEC means maximum theoretical emissions concentration of the hazardous waste and MTEC is defined at § 63.1201(a).
[3] Standard is expressed as mass of pollutant stack emissions attributable to the hazardous waste per million British thermal unit heat input of the hazardous waste.

D. Solid Fuel Boilers

The changes in the solid fuel boiler standards for existing sources since proposal are:

Standard	Proposed limit	Final limit
Mercury (μg/dscm)	10	11
Semivolatile Metals (μg/dscm)	170	180
Low Volatile metals (μg/dscm)	210	380
Alternative to the particulate matter standard: Combined emissions of lead, cadmium and selenium (μg/dscm)	170	180
Alternative to the particulate matter standard: Combined emissions of arsenic, beryllium, chromium, antimony, cobalt, manganese, and nickel (μg/dscm)	210	380

The changes in the solid fuel boiler standards for new sources since proposal are:

Standard	Proposed limit	Final limit
Mercury (μg/dscm)	10	11
Semivolatile Metals (μg/dscm)	170	180
Low Volatile metals (μg/dscm)	210	380
Alternative to the particulate matter standard: Combined emissions of lead, cadmium and selenium (μg/dscm)	170	180

E. Liquid Fuel Boilers

We redefined the liquid fuel boiler subcategory into two separate boiler subcategories based on the heating value of the hazardous waste they burn: Those that burn waste below 10,000 Btu/lb, those that burn hazardous waste with a heating value of 10,000 Btu/lb or greater. See Part Four, Section VI.D.2 of today's preamble for a complete discussion.

The additional changes to the liquid fuel boiler standards for existing sources since proposal are:

Standard	Proposed limit	Final limit	
		HW Fuel < 10,000 Btu/lb	HW Fuel ≥ 10,000 Btu/lb
Mercury (lb/MM Btu)	3.7E–6	19 μg/dscm	4.2E–5
Particulate matter (gr/dscf)	0.032	0.035	
Semivolatile metals (lb/MM Btu)	1.1E–5	150 μg/dscm	8.2E–5
Chromium (lb/MM Btu)	1.1E–4	370 μg/dscm	1.3E–4
Total chlorine (Lb/MM Btu)	2.5E–2	31 ppmv	5.1E–2
Alternative to the particulate matter standard: Combined emissions of lead, cadmium and selenium (lb/MM Btu).	1.1E–5	150 μg/dscm	8.2E–5
Alternative to the particulate matter standard: Combined emissions of arsenic, beryllium, chromium, antimony, cobalt, manganese, and nickel (lb/MM Btu).	1.1E–4	370 μg/dscm	1.3E–4

The changes in the liquid fuel boiler standards for new sources since proposal are:

Standard	Proposed limit	Final limit	
		HW fuel < 10,000 Btu/lb	HW fuel > 10,000 Btu/lb
Dioxin and Furan, dry APCD (ng TEQ/dscm)	0.015 or temp control <400F for dry APCD.	0.40	
Mercury (lb/MM Btu)	3.8E–7	6.8 µg/dscm	1.2E–6
Particulate matter (gr/dscf)	0.0076	0.0087	
Semivolatile metals (lb/MM Btu)	4.3E–6	78 µg/dscm	6.2E–6
Chromium (lb/MM Btu)	3.6E–5	12 µg/dscm	1.4E–5
Total chlorine (lb/MM Btu)	7.2E–4	31 µg/dscm	5.1E–2
Alternative to the particulate matter standard: Combined emissions of lead, cadmium and selenium (lb/MM Btu).	4.3E–6	78 µg/dscm [1]	6.2E–6 [1]
Alternative to the particulate matter standard: Combined emissions of arsenic, beryllium, chromium, antimony, cobalt, manganese, and nickel (lb/MM Btu).	3.6E–5	12 µg/dscm [2]	1.4E–5 [2]

[1] New or reconstructed liquid fuel boilers that process residual oil or liquid feedstreams that are neither fossil fuel nor hazardous waste and that operate pursuant to the alternative to the particulate matter standard must comply with the alternative emission concentration standard of 4.7 µg/dscm, which is applicable to lead, cadmium and selenium emissions attributable to all feedstreams (hazardous and nonhazardous).

[2] New or reconstructed liquid fuel boilers that process residual oil or liquid feedstreams that are neither fossil fuel nor hazardous waste that operate pursuant to the alternative to the particulate matter standard must comply with the alternative emission concentration standard of 12 µg/dscm, which is applicable to arsenic, beryllium, chrome, antimony, cobalt, manganese, and nickel emissions attributable to all feedstreams (hazardous and nonhazardous).

F. Hydrochloric Acid Production Furnaces

The changes in the hydrochloric acid production furnace standards for existing sources since proposal are:

Standard	Proposed limit	Final limit
Dioxin and Furans	0.4 ng TEQ/dscm	Carbon Monoxide/Total Hydrocarbons and DRE standards as surrogates.
Total chlorine	14 ppmv or 99.9927% system removal efficiency	150 ppmv or 99.923% system removal efficiency.

The changes in the hydrochloric acid production furnace standards for new sources since proposal are:

Standard	Proposed limit	Final limit
Dioxin and Furans	0.4 ng TEQ/dscm	Carbon Monoxide/Total Hydrocarbons and DRE standards as surrogates
Total chlorine	1.2 ppmv or 99.9994% system removal efficiency	25 ppmv or 99.987% system removal efficiency

G. Dioxin/Furan Testing for Sources Not Subject to a Numerical Standard

Today's final rule requires that all sources not subject to a numerical dioxin and furan standard perform a one time test to determine their dioxin and furan emissions. See the discussion in Part Four, Section VII.L.

In the proposed rule, this requirement was limited to solid fuel boilers and those liquid fuel boilers with a wet or no air pollution control system. The final rule expands this requirement to include hydrochloric acid production furnaces and those lightweight aggregate kilns that elect to comply with the temperature limit at the kiln exit in lieu of the 0.20 ng TEQ/dscm dioxin/furan standard. Those sources are not subject to a numerical dioxin/furan standard under the final rule for reasons explained in Volume III of the Technical Support Document, Sections 12 and 15. We note that sources not subject to a numerical dioxin/furan emission standard are subject to the carbon monoxide or hydrocarbon standards and the DRE standard as surrogates.

We are making no changes to the implementation of this requirement. See the proposed rule at 69 FR at 21307 for more information.

III. Statistics and Variability

A. Using Statistical Imputation To Address Variability of Nondetect Values

In the final rule, we use a statistical approach to impute the value of nondetect emissions and feedrate measurements to avoid dampening of the variability of data sets when nondetect measurements are assumed to be present at the detection limit.

At proposal, we assumed that nondetects (i.e., HAP levels in stack emissions below the level of detection of the applicable analytic method) are invariably present at the detection limit. Commenters on the proposed rule stated, however, that assuming nondetects are present at the detection limit dampens emissions variability—a consideration necessary to reasonably ascertain sources' performance over time. This could have significant practical consequence for those data sets (such as the data base for liquid fuel boilers) dominated by nondetected values. We agree with these commenters, and instead of making the arbitrary assumption that all nondetected values are identical (which

in fact is highly unlikely), we are using a statistical methodology to impute the value of nondetect measurements.

The imputation approach assigns a value for each nondetect measurement in a data set within the possible range of values that results in maximizing the 99th percentile upper prediction limit for the data set. For example, the possible range of values for a measurement that is 100% nondetect is between zero and the detection limit.

On February 4, 2005 we distributed a direct request for comments on the imputation approach to major stakeholders. We respond to the comments we received in Part Four, Section IV.D of today's notice.

B. Degrees of Freedom When Imputing a Standard Deviation Using the Universal Variability Factor for Particulate Matter Controlled by a Fabric Filter

The use of the universal variability factor to impute a standard deviation for particulate emissions from sources controlled with a fabric filter takes advantage of the empirical observation that the standard deviation of particulate emissions from sources is positively correlated to the average particulate emissions of sources. Based on this observation, we use regression analysis to determine the best fitting curve to explain the relationship of average value to standard deviation.

In the final rule, we use the actual sample size, rather than an assumed sample size of nine used at proposal, to determine the degrees of freedom for the t-statistic to calculate the floor using the standard deviation imputed from the universal variability factor for particulate matter controlled by a fabric filter.

At proposal, we used eight degrees of freedom to identify the t-statistic to account for within-test condition variability (i.e., run-to-run variability) for standard deviations imputed from the universal variability factor regression.[28] This is because, on average, about three test conditions with nine individual test runs are associated with each source used to develop the regression curve.

A commenter states, however, that this approach can dramatically understate variability when imputing a standard deviation for a source with only three runs because the t-statistic is substantially higher for 2 degrees of freedom than 8 degrees of freedom.

We agree with the commenter. Moreover, using the actual number of runs to identify the t-statistic rather than assuming nine runs is appropriate given that the true test condition average is less certain for sources with only three runs, and thus there is less certainty in the imputed standard deviation. The higher t-statistic associated with a three-run data set reflects this uncertainty.

In addition, we include emissions data classified as "normal" in the regression analysis for the final rule. At proposal, we used only data classified as CT (i.e., highest compliance test condition in a test campaign) or IB (i.e., a compliance test condition that achieved lower emissions than another compliance test condition in the test campaign). We conclude that normal data (i.e., emissions data that were not used to establish operating limits and thus do not reflect variability in controllable operating parameters) should also be considered in the regression analysis because particulate matter emissions are relatively insensitive to baghouse inlet loading and operating conditions.[29] Including normal emissions in the analysis provides additional data to better quantify these devices' performance variability.

IV. Compliance Assurance for Fabric Filters, Electrostatic Precipitators, and Ionizing Wet Scrubbers

The final rule provides additional requirements to clarify how you determine the duration of periods of operation when the alarm set point has been exceeded for a bag leak detection system or a particulate matter detection system:

1. You must keep records of the date, time, and duration of each alarm, the time corrective action was initiated and completed, and a brief description of the cause of the alarm and the corrective action taken.

2. You must record the percent of the operating time during each 6-month period that the alarm sounds.

3. In calculating the operating time percentage, if inspection of the fabric filter, electrostatic precipitator, or ionizing wet scrubber demonstrates that no corrective action is required, no alarm time is counted.

4. If corrective action is required, each alarm shall be counted as a minimum of 1 hour.

The final rule also establishes revised procedures for establishing the alarm set point if you elect to use a particulate matter detector system in lieu of site-specific operating parameter limits for compliance assurance for sources equipped with electrostatic precipitators and ionizing wet scrubbers. The rule explicitly allows you to maximize controllable operating parameters during the comprehensive performance test to account for variability by, for example, detuning the APCD or spiking ash. To establish the alarm set-point, you may either establish the set-point as the average of the test condition run average detector responses during the comprehensive performance test or extrapolate the detector response after approximating the correlation between the detector response and particulate matter emission concentrations. You may extrapolate the detector response up to a response value that corresponds to 50% of the particulate matter emission standard or 125% of the highest particulate matter concentration used to develop the correlation, whichever is greater. To establish an approximate correlation of the detector response to particulate matter emission concentrations you should use as guidance Performance Specification-11 for PM CEMS (40 CFR Part 60, Appendix B), except that you need conduct only 5 runs to establish the initial correlation rather than a minimum of 15 runs required by PS–11.

The final rule also notes that an exceedance of a detector response that corresponds to the particulate matter emission standard is not evidence that the standard has been exceeded because the correlation is an approximate correlation used for the purpose of compliance assurance to determine when corrective measures must be taken. The correlation, however, does not meet the requirements of PS–11 for compliance monitoring.

In addition, if you elect to use a particulate matter detection system in lieu of site-specific control device operating parameter limits on the electronic control device, the ash feedrate limit for incinerators and boilers under § 63.1209(m)(3) is waived. The ash feedrate limit is waived because the particulate matter detection system continuously monitors relative particulate matter emissions and the alarm set point provides reasonable assurance that emissions will not exceed the standard.[30]

[28] USEPA, "Draft Technical Support Document for HWC MACT Standards, Volume III: Selection of MACT Standards," March 2004, p. 5–4.

[29] USEPA, "Technical Support Document for HWC MACT Standards, Volume III: Selection of MACT Standards," September 2005, Section 5.3. See also Part Four, Section III.C of this preamble.

[30] Note that if your incinerator or boiler is equipped with a fabric filter and you elect under § 63.1206(c)(8)(i) to use a particulate matter detection system in lieu of a bag leak detection system for compliance assurance, the ash feedrate limit is waived. The ash feedrate limit is not waived if you use a bag leak detection system, however, because the alarm level may not ensure compliance with the emission standard when you follow the

Finally, you must submit an excessive exceedance notification within 30 days of the date that the alarm set-point is exceeded more than 5 percent of the time during any 6-month block period of time, or within 30 days after the end of the 6-month block period, whichever is earlier. The proposed rule would have required you to submit that notification within 5 days of the end of the 6-month block period.

V. Health-Based Compliance Alternative for Total Chlorine

The final rule includes the following major changes to the proposed health-based compliance alternative for total chlorine:

(1) You must use 1-hour Reference Exposure Levels (aRELs) rather than 1-hour acute exposure guideline levels (AEGL–1), as the acute health risk threshold metric when calculating 1-hour HCl-equivalent emission rates;

(2) You must establish a long-term average chlorine feedrate limit (i.e., 12 hour rolling average or an (up to) annual rolling average) as the annual average HCl-equivalent emission rate limit divided by [1 − system removal efficiency]. You establish the total chlorine system removal efficiency during the comprehensive performance test. The proposed rule would have required you to establish the long-term average chlorine feedrate limit as the average of the test run averages of the comprehensive performance test.[31]

(3) At proposal, we requested comment on whether and how to establish a short-term chlorine feedrate limit to ensure that the acute exposure Hazard Index of 1.0 is not exceeded. See 69 FR at 21304. We conclude for the final rule that a 1-hour rolling average feedrate limit may be needed for some situations (i.e., if chlorine feedrates can vary substantially during the averaging period for the long-term feedrate limit and potentially result in an exceedance of the 1-hour average HCl-equivalent emission rate limit). Accordingly, although your eligibility for the health-based compliance alternatives is based on annual average HCl-equivalent emissions, you must determine considering prescribed criteria whether your 1-hour HCl-equivalent emission rate may exceed the national exposure standard (i.e., Hazard Index not exceeding 1.0 considering the maximum 1-hour average ambient concentration of hydrogen chloride and chlorine at an off-site receptor location[32]) and thus may exceed the 1-hour average HCl-equivalent emission rate limit absent an hourly rolling average limit on the feedrate of chlorine. If the acute exposure standard may be exceeded, you must establish an hourly rolling average chlorine feedrate limit as the 1-hour HCl-equivalent emission rate limit divided by [1 − system removal efficiency]. You establish the system removal efficiency during the comprehensive performance test.

(4) When calculating HCl-equivalent emission rates, rather than partitioning total chlorine emissions between chlorine and HCl (i.e., the Cl_2/HCl volumetric ratio) based on the comprehensive performance test as proposed, you must establish the Cl_2/HCl volumetric ratio used to calculate the annual average HCl-equivalent emission rate based on the historical average ratio from all regulatory compliance tests. You must establish the Cl_2/HCl volumetric used to calculate the 1-hour average HCl-equivalent emission rate as the highest of the historical ratios from all regulatory compliance tests. The rule allows you to exclude ratios from historical compliance tests where the emission data may not be representative of the current Cl_2/HCl ratio for reasons such as changes to the design or operation of the combustor or biases in measurement methods. The rule also explicitly allows the permitting authority to require periodic emissions testing to obtain a representative average and maximum ratio;

(5) The look-up table analysis has been refined by presenting annual average and 1-hour HCl-equivalent emission rate limits as a function of stack height, stack diameter, and distance to property line. In addition, separate look-up tables are presented for flat terrain and simple elevated terrain;

(6) The proposed rule required approval of the eligibility demonstration before you could comply with the alternative health-based emission limits for total chlorine. Under the final rule, if your permitting authority has not approved your eligibility demonstration by the compliance date, and has not issued a notice of intent to disapprove your demonstration, you may nonetheless begin complying, on the compliance date, with the annual average HCl-equivalent emission rate limits you present in your eligibility demonstration. In addition, if your permitting authority issues a notice of intent to disapprove your eligibility demonstration, the authority will identify the basis for that notice and specify how much time you will have to submit additional information or to comply with the MACT total chlorine standards. The permitting authority may extend the compliance date of the total chlorine standards to allow you to make changes to the design or operation of the combustor or related systems as quickly as practicable to enable you to achieve compliance with the MACT total chlorine standards;

(7) We have revised the approach for determining chlorine emissions if you feed bromine or sulfur during the comprehensive performance test at levels higher than those specified in § 63.1215(e)(3)(ii)(B). Under the final rule, you must use EPA Method 320/321 or ASTM D 6735'01, or an equivalent method, to measure hydrogen chloride, and Method 26/26A, or an equivalent method, to measure chlorine and hydrogen chloride. You must determine your chlorine emissions to be the higher of: (1) The value measured by Method 26/26A, or an equivalent method; or (2) the value calculated by difference between the combined hydrogen chloride and chlorine levels measured by Method 26/26a, or an equivalent method, and the hydrogen chloride measurement from EPA Method 320/321 or ASTM D 6735–01, or an equivalent method; and

(8) The proposed rule would have required you to conduct a new comprehensive performance test if you planned to make changes to the facility that would lower the annual average HCl-equivalent emission rate limit. Under the final rule, you would be required to conduct a performance test as a result of a planned change only for a change to the design, operation, or maintenance of the combustor that could affect the system removal efficiency for total chlorine if the change could reduce the system removal efficiency, or if the change would increase the system removal efficiency and you elect to increase the feedrate limits on total chlorine and chloride.

---

concepts in the Agency's guidance document on bag leak detection systems to establish the alarm level.

[31] Note that, as a practical matter, most sources must establish the chlorine feedrate limit as the average of the test run average feedrate limit during the comprehensive performance test to demonstrate compliance with the semivolatile emission standard. This is because chlorine feedrate is a compliance assurance parameter for the semivolatile metal emission standard. That feedrate limit is based on a 12-hour rolling average. To ensure compliance with the annual average HCl-equivalent emission rate limit, however, that feedrate limit cannot exceed the value calculated as the annual average HCl-equivalent emission rate limit divided by [1 − system removal efficiency], where you demonstrate the total chlorine system removal efficiency during the performance test.

[32] Under the site-specific risk assessment approach to demonstrate eligibility, you must consider locations where people reside and where people congregate for work, school, or recreation.

Part Four: What Are the Responses to Major Comments?

I. Database

A. Revisions to the EPA's Hazardous Waste Combustor Data Base

Comment: Several commenters identify sources which have ceased operations as a hazardous waste combustor and should be removed from EPA's data base.

Response: We agree with commenters that data and information from sources no longer burning hazardous waste should not be included in our hazardous waste combustor data base and should not be used to calculate the MACT standards. We consider any source that has initiated RCRA closure procedures and activities as a source that is no longer burning hazardous waste. This data handling decision is consistent with the approach we used in the 1999 final rule. See 64 FR at 52844. As we stated in that rule, ample emissions data remain to support calculating the MACT standards without using data from sources that no longer burn hazardous waste.

As a result, we removed the following former hazardous waste combustors from the data base: the Safety-Kleen incinerator in Clarence, New York, the Dow Chemical Company incinerators in Midland, Michigan, and LaPorte, Texas, the two Holcim wet process cement kilns in Holly Hill, South Carolina, the Dow Chemical Company liquid fuel-fired boiler in Freeport, Texas, the Union Carbide liquid fuel-fired boilers in Hahnville, Louisiana, and Texas City, Texas, and six Dow Chemical Company hydrochloric production furnaces in Freeport, Texas.

We are retaining, however, Solite Corporation's lightweight aggregate facility in Cascade, Virginia, in the data base. Even though the facility recently initiated RCRA closure procedures, this data handling decision differs from those listed in the preceding paragraph because Solite Corporation provided this new information in February 2005 while information on the other closures was reported or available to us in 2004. Because we cannot continually adjust our data base and still finalize this rulemaking by the court-ordered deadline, we stopped making revisions to the data base in late 2004. Additional facility changes after that date, like Solite Corporation's Cascade facility closure, simply could not be incorporated.

Comment: One commenter identifies a source in EPA's data base that should be classified as a boiler instead of a hydrochloric acid production furnace.

Response: We agree with the commenter. In today's rule, Dow Chemical Company's boiler F–2820, located in Freeport, Texas, is reclassified in our data base as a boiler. This source is identified as unit number 2020 in our data base.

B. Use of Data From Recently Upgraded Sources

Comment: Many commenters recommend that EPA remove from the data base (or not consider for standards-setting purposes) emissions data from sources that upgraded their emissions controls to comply with the promulgated emission standards of either the 1999 rule or the 2002 interim standards. Several commenters also state that any emissions data that were obtained or used to demonstrate compliance with the promulgated standards of 1999 or 2002 should not be used for standard-setting purposes by the Agency. That is, EPA must evaluate the source category as it existed at the beginning of the rule development process and not after emissions controls are later added to comply with the 1999 or 2002 standards. Several commenters also state that EPA is only partly correct in claiming that the interim standards are not MACT standards because the interim standards were established and considered to be MACT until the Court issued its opinion in July 2001. Until that time, sources proceeded to upgrade their facilities to achieve the standards promulgated in 1999. The rationale for these recommendations is threefold: (1) Use of the data unfairly ignores the MACT-driven reductions already achieved by some sources; (2) it is contrary to sound public policy to use data from upgraded facilities to "ratchet down" the MACT floors to a level more stringent because these sources would not have increased their level of performance but for the legal obligation to comply with the standards; and (3) EPA's reliance on *National Lime Ass'n v. EPA*, 233 F.3d 625, 640 (D.C. Cir. 2000), for the proposition that the motivation for a source's performance is legally irrelevant in developing MACT floor levels is misplaced because that case involved the initial MACT standard setting process, and not a subsequent rule.

One commenter agrees with EPA's proposed position and states that use of data from sources that have upgraded is not only appropriate, but also required by the Clean Air Act. This commenter states that the actual performance of sources that have upgraded their emissions equipment—to meet the 1999 standards or for any reason—is reflected only by the most recently generated emissions data for the source. Thus, the Clean Air Act requires EPA to use the most recently generated data available to it and precludes the Agency from using older, out-of-date performance data.

EPA also received several comments stating that the language of section 112(d)(3)(A) of the Clean Air Act informs how the Agency should consider emissions data from sources that conducted testing after that 1999 rule was promulgated. One commenter states that the only data which should not be used in calculating the MACT floors are from sources that are subject to lowest achievable emission rates (LAER). Thus, the commenter states, Congress considered the possibility of significant and recent upgrades, and concluded that EPA should use up-to-date data to reflect source's performance, but must exclude certain sources from the floor calculation if their upgrades were of a specific degree and were accomplished within a specific period of time. Another commenter states that Congress did not intend to pile technology upon technology as confirmed by section 112(d)(3)(A) that specifically excludes sources that implemented LAER from consideration when establishing section 112(d) standards. Thus, the commenter states, considering data from sources that have upgraded violates both the language and intent of the Clean Air Act. Another commenter states that, while Congress no doubt contemplated that EPA should use all available emissions information in setting initial MACT standards, neither the statute nor the legislative history suggest that follow-up MACT rulemakings require the use of data reflecting compliance efforts with previous MACT standards or interim standards.

Response: As proposed, EPA maintains its position on use of post-1999 emissions data. The statute indicates that EPA is to base MACT floors on performance of sources "for which the Administrator has emissions information." Section 112(d)(3)(A); *CKRC*, 255 F. 3d at 867. There can be no dispute that post-1999 performance data in EPA's possession fits this description. We also reiterate that the motivation for the control reflected in data available to us is irrelevant. See 69 FR at 21217–218. We further agree with those commenters who pointed out that Congress was explicit when it wanted certain emissions information (i.e., sources operating pursuant to a LAER standard) excluded from consideration in establishing floors. There is, of course, no such enumerated exception

for sources that have upgraded their performance for other reasons.

We also do not agree with those commenters arguing (with respect to the standards for the Phase 1 sources (incinerators, cement kilns, and lightweight aggregate kilns)) in effect that the present rulemaking involves revision of an existing MACT standard. If this were indeed a revision of a MACT standard under section 112(d)(6), then EPA would not redetermine floor levels. See 70 FR at 20008 (April 15, 2005). However, EPA has not to date promulgated valid MACT floors or valid MACT standards for these sources. The 1999 standards do not reflect MACT, as held by the *CKRC* court. The interim standards likewise do not reflect MACT, but were designed to prevent a regulatory gap and were described as such from their inception. 67 FR at 7693 (Feb. 13, 2002); see also *Joint Motion of all Parties for Stay of Issuance of Mandate* in case no. 99–1457 (October 19, 2001), pp. 11–12 ("The Parties emphasize that the contemplated interim rule is in the nature of a remedy. It would not respond to the Court's mandate regarding the need to demonstrate that EPA's methodology reasonably predicts the performance of the average of the best performing twelve percent of sources (or best-performing source). EPA intends to address those issues in a subsequent rule, which will necessarily require a longer time to develop, propose, and finalize.") EPA consequently believes that it is adopting in this rule the initial section 112(d) MACT standards for hazardous waste burning incinerators, cement kilns, and lightweight aggregate kilns, and that the floor levels for existing sources are based, as provided in section 112(d)(3), on performance of those sources for which EPA has "emissions information."

However, we disagree with the comment that we must make exclusive use of the most recent information from hazardous waste combustion sources. There is no such restriction in section 112(d)(3). EPA has exhaustively examined all of the data in its possession for all source categories covered by this rule, and determined (and documented) which data are suitable for evaluating sources' performance.

C. Correction of Total Chlorine Data to Address Potential Bias in Stack Measurement Method

Comment: Several commenters state that EPA's proposed total chlorine standards of 1.5 ppm for existing incinerators and 0.18 ppm for new incinerators are based on biased data of indeterminate quality and are unachievable. Commenters assert that Method 26A and its RCRA equivalent, SW 846 Method 0050, have a negative bias at concentrations below 20 ppmv when used on stacks controlled with wet scrubbers. Commenters cite two recurring situations when this bias is likely to occur: (1) hydrogen chloride dissolving in condensed moisture in the sampling train; and (2) hydrogen chloride reacting with alkaline compounds from the scrubber water that are collected on the filter ahead of the impingers.

Commenters are particularly concerned about the negative bias associated with stack gas containing substantial water vapor. Commenters note that EPA found in a controlled laboratory study by Steger[33] that the bias is between 17 and 29 percent at stack gas moisture content of 7 to 9 percent. This stack gas moisture is much less than the nominal 50% moisture contained in some hazardous waste combustor stacks according to the commenters. Commenters believe this is why EPA's Method 0050, which was used to gather most of the data in the HWC MACT data base, states in Section 1.2 that "this method is not acceptable for demonstrating compliance with HCl emission standards less than 20 ppm."

Moreover, commenters state that the procedures in Method 0050 to address the negative bias caused by condensed moisture were not followed for many RCRA compliance tests. The method uses an optional cyclone to collect moisture droplets, and requires a 45 minute purge of the cyclone and sampling train to recover hydrogen chloride from water collected by the cyclone and any condensed moisture in the train. The cyclone is not necessary if the stack gas does not contain water droplets. According to commenters, the cyclone and subsequent purge were often not used in the presence of water droplets because a potential low bias below 20 ppmv was irrelevant when demonstrating compliance with emission standards on the order of 100 ppmv. There was no need for the extra complexity and expense of using a cyclone and train purge given the purpose of the test. Although the data were acceptable for their intended purpose, commenters conclude that the data are not useful for establishing standards below 20 ppmv.

For these reasons, commenters suggest that EPA not consider total chlorine measurements below 20 ppmv when establishing the standards.

Response: For the reasons discussed below, we corrected all total chlorine measurements in our data base for all source categories that were below 20 ppmv to 20 ppmv to establish the total chlorine floors. Moreover, to address run-to-run variability given that all runs for several data sets are now corrected to 20 ppmv, we impute a run standard deviation based on a regression analysis of run standard deviation versus total chlorine concentration for sources with total chlorine measurements greater than 20 ppmv. This is the same approach we used to impute variability from sources using fabric filters when determining the particulate matter MACT floors.

Effect of Moisture Vapor. Commenters imply that stack gas with high levels of gas phase water vapor will inherently be problematic, particularly at emissions less than 20 ppmv. There is no basis for claiming that water vapor, per se, causes a bias in SW–846 Method 0050 or its equivalent, Method 26A. Condensed moisture (i.e., water droplets), however, can cause a bias because it can dissolve hydrogen chloride in the sampling train and prevent it from being captured in the impingers if the sampling train is not properly purged. Water droplets can potentially be present due to entrainment from the wet scrubber, condensation in cooler regions of the stack along the stack walls, and entrainment from condensed moisture dripping down the stack wall across the inlet duct opening.

Although Method 0050 addresses the water droplet issue by use of a cyclone and 45 minute purge, the Steger paper (Ibid.) concludes that a 45 minute purge is not adequate to evaporate all water collected by the cyclone in stacks with a total moisture content (vapor and condensed moisture) of 7 to 9%. At those moisture levels, Steger documented the negative bias that commenters reference. Steger's recommendation was to increase the heat input to the sample train by increasing the train and filter temperature from 120C (248F) to 200C (392F). We agree that increasing the probe and filter temperature will provide a better opportunity to evaporate any condensed moisture, but another solution to the problem is to require that the post-test purge be run long enough to evaporate all condensed moisture. That is the approach used by Method 26A, which EPA promulgated after Method 0050, and which sources must use to demonstrate compliance with the final standards. Method 26A uses an extended purge time rather than

[33] Steger, J.L., et al, "Laboratory Evaluation of Method 0050 for Hydrogen Chloride", Proc of 13th Annual Incineration Conference, Houston, TX, May 1994.

elevating the train temperature to address condensed moisture because that approach can be implemented by the stack tester at the site without using nonstandard equipment.

We attempted to quantify the level of condensed moisture in the Steger study and to compare it to the levels of condensed moisture that may be present in hazardous waste combustor stack gas. This would provide an indication if the bias that Steger quantified with a 45 minute purge might also be applicable to some hazardous waste combustors. We conclude that this comparison would be problematic, however, because: (1) given the limited information available in the Steger paper, it is difficult to quantify the level of condensed moisture in his gas samples; and (2) we cannot estimate the levels of condensed moisture in hazardous waste combustor stack gas because, even though condensed moisture may have been present during a test, method protocol is to report the saturation moisture level only (i.e., the amount of water vapor present), and not the total moisture content (i.e., both condensed and vapor phase moisture).

We can conclude, however, that, if hazardous waste combustor stack gas were to contain the levels of condensed moisture present in the gas that Steger tested, the 45 minute purge required by Method 0050 would not be sufficient to avoid a negative bias. We also conclude that this is potentially a practical issue and not merely a theoretical concern because, as commenters note, hazardous waste combustors that use wet scrubbers are often saturated with water vapor that will condense if the flue gas cools.

Data from Wet Stacks When a Cyclone Was Not Used. Commenters state that Method 0050 procedures for addressing water droplets (adequate or not, as discussed above) were not followed in many cases because a low bias below 20 ppmv was not relevant to demonstrating compliance with standards on the order of 100 ppmv. We do not know which data sets may be problematic because, as previously stated, the moisture concentration reported was often the saturation (vapor phase only) moisture level and not the total (vapor and liquid) moisture in the flue gas. We also have no documentation that a cyclone was used—even in situations where the moisture content was documented to be above the dew point. We therefore conclude that all data below 20 ppmv from sources controlled with a wet scrubber are suspect and should be corrected.

Potential Bias Due to Filter Affinity for Hydrogen Chloride. Studies by the American Society of Testing and Materials indicate that the filter used in the Method 0050 train (and the M26/26A trains) may adsorb/absorb hydrogen chloride and cause a negative bias at low emission levels. (See ASTM D6735–01, section 11.1.3 and "note 2" of section 14.2.3) This inherent affinity for hydrogen chloride can be satisfied by preconditioning the sampling train for one hour. None of the tests in our database were preconditioned in such a manner.

We are normally not concerned about this type of bias because we would expect the bias to apply to all sources equally (e.g., wet or dry gas) and for all subsequent compliance tests. In other words, we are ordinarily less concerned if a standard is based on biased data, as long as the means by which the standard was developed and the means of compliance would experience identical bias.

However, we did correct the wet gas measurements below 20 ppmv to address the potential low bias caused by condensed moisture. This correction would also correct for any potential bias caused by the filter's inherent affinity for hydrogen chloride. This results in a data set that is partially corrected for this issue—sources with wet stacks would be corrected for this potential bias while sources with dry stacks would not be corrected. To address this unacceptable mix of potentially biased and unbiased data (i.e., dry gas data biased due to affinity of filter for hydrogen chloride and wet gas data corrected for condensed moisture and affinity of filter for hydrogen chloride), we also correct total chlorine measurements from dry gas stacks (i.e., sources that do not use wet scrubbers).

Deposition of Alkaline Particulate on the Filter. Commenters are also concerned that hydrogen chloride may react with alkaline compounds from the scrubber water droplets that are collected on the filter ahead of the impingers. Commenters suggest this potential cause for a low bias at total chlorine levels below 20 ppmv is another reason not to use measurements below 20 ppmv to establish the standards.

Although alkaline particulate deposition on the method filter causing a negative bias is a much greater concern for sources that have stack gas containing high levels of alkaline particulate (e.g., cement kilns, sources equipped with dry scrubbers), we agree with commenters that this may be of concern for all sources equipped with wet scrubbers. Our approach to correct all data below 20 ppmv addresses this concern.

Decision Unique to Hazardous Waste Combustors. We note that the rationale for our decision to correct total chlorine data below 20 ppmv to account for the biases discussed above is unique to the hazardous waste combustor MACT rule. Some sources apparently did not follow Method 0050 procedures to minimize the low bias caused by condensed moisture for understandable reasons. Even if sources had followed Method 0050 procedures to minimize the bias (i.e., cyclone and 45 minute purge) there still may have been a substantial bias because of insufficient purge time, as Steger's work may indicate. We note that the total chlorine stack test method used by sources other than hazardous waste combustors—Method 26A—requires that the cyclone and sampling train be purged until all condensed moisture is evaporated. We believe it is necessary to correct our data below 20 ppmv data because of issues associated exclusively with Method 0050 and how it was used to demonstrate compliance with these sources.

Determining Variability for Data at 20 ppmv. Correcting those total chlorine data below 20 ppmv to 20 ppmv brings about a situation identical to the one we confronted with nondetect data. See Part Four, Section V.B. below. The MACT pool of best performing source(s) for some data sets is now comprised of largely the same values. This has the effect of understating the variability associated with these data.

To address this concern, we took an approach similar to the one we used to determine variability of PM emissions for sources equipped with a fabric filter. In that case, we performed a linear regression on the data, charting variability against emissions, and used the variability that resulted from the linear regression analysis as the variability for the sources average emissions. In this case, most or all of the incinerator and liquid fuel boiler sources in the MACT pool have average emissions at or near 20 ppmv. We therefore performed a linear regression on the total chlorine data charting average test condition results above 20 ppmv against the variability associated with that test condition. The variability associated with 20 ppmv was the variability we used for incinerator and liquid fuel boiler data sets affected by the 20 ppmv correction.

We also considered using the statistical imputation approach we used for nondetect values. See discussion in Section IV.B below. The statistical imputation approach for correcting data below 20 ppmv without dampening variability would involve imputing a value between the reported value and 20

ppmv because the "true" value of the biased data would lie in this interval. This approach would be problematic, however, given that many of the reported values were much lower than 20 ppmv; our statistical imputation approach would tend to overestimate the run to run variability. Consequently, we conclude that a regression analysis approach is more appropriate. A regression analysis is particularly pertinent in this situation because: (1) We consider data above 20 ppmv used to develop the regression to be unbiased; and (2) all the corrected data averages for which we are imputing a standard deviation from the regression curve are at or near 20 ppmv. Thus, any potential concern about downward extrapolation from the regression would be minimized.

We note that, although a regression analysis is appropriate to estimate run-to-run variability for the corrected total chlorine data, we could not use a linear regression analysis to address variability of nondetect values. To estimate a standard deviation from a regression analysis, we would need to know the test condition average emissions. This would not be feasible, however, because some or all of the run measurements for a test condition are nondetect. In addition, we are concerned that a regression analysis would not accurately estimate the standard deviation at low emission levels because we would have to extrapolate the regression downward to levels where we have few measured data (i.e., data other than nondetect). Moreover, the statistical imputation approach is more suitable for handling nondetects because the approach calculates the run-to-run variability by taking into account the percent nondetect for the emissions for each run.[34] A regression approach would be difficult to apply particularly in the case of test conditions containing partial nondetects or a mix of detect and nondetect values. Given these concerns with using a regression analysis to estimate the standard deviation of test conditions with runs that have one or more nondetect (or partial nondetect) measurements, we conclude that the statistical imputation approach best assures that the calculated floor levels account for run-to-run emissions variability.

Compliance with the Standards. The final standards are based on data that were corrected to address specific issues concerning these data. See the above discussion regarding stack gas moisture, filter affinity for hydrogen chloride, and alkaline compound reactions with hydrogen chloride in the sampling train.

Sources must demonstrate compliance using a stack test method that also addresses these issues. Sources with wet stacks must use Method 26A and follow those procedures regarding the use of a cyclone and the purging of the system whenever condensed moisture may be present in the sampling system.

Finally, all sources—those with either wet or dry gas—should precondition the sampling train for one hour prior to beginning the test to satisfy the filter's affinity for hydrogen chloride. The permitting authority will ensure that sources precondition the sample train (under authority of § 63.1209(g)(2)) when they review and approve the performance test plan.

D. Mercury Data for Cement Kilns

Comment: Several commenters state that EPA's data base of mercury emissions data (and associated feed concentrations of mercury in the hazardous waste) are unrepresentative and unsuitable for use in determining MACT standards for cement kilns. These comments are supported by an extensive amount of data submitted by the cement manufacturing industry including three years of data documenting day-to-day levels of mercury in hazardous waste fuels fired to all 14 hazardous waste burning cement kilns.[35] The commenters recommend that EPA use the commenter-submitted data as the basis for assessing cement kilns' performance for control of mercury because it is the most complete and representative data available to EPA.

Response: We agree that the commenter-submitted mercury data are more representative than those we used at proposal. First, these data represent a significantly larger and more comprehensive dataset compared to the one used to support the proposed mercury standard. The commenter-submitted data document the day-to-day levels of mercury in hazardous waste fired to all cement kilns for a three year period covering 1999 to 2001. In total, approximately 20,000 measurements of the concentration of mercury in hazardous waste are included in the dataset. When considered in whole, these data describe the performance (and variability thereof) of all cement kilns for the three year period because each measurement represents the mercury concentration in the burn tank used to fire the kiln over the course of a day's operation (or longer period).[36] In comparison, the data used to support the proposed floor level consisted of a much smaller dataset of approximately 50 test conditions representing a snapshot of performance somewhere in the range of normal operations, with each test condition representing a relatively short period of time (e.g., several hours).[37] As discussed at proposal, we were concerned regarding the representativeness of this smaller dataset. See 69 FR at 21251. In addition, the commenter-submitted dataset allows us to better evaluate the only mercury control technique used by existing hazardous waste burning cement kilns—controlling the feed concentration of mercury in the hazardous waste. The commenters have demonstrated convincingly that the mercury dataset used at proposal does not properly show the range of performance and variability in performance these cement kilns actually experience, while the significantly more robust dataset submitted by commenters does illustrate this variability. Thus, we conclude the larger commenter-submitted dataset is superior to EPA's smaller testing dataset.

We note that our MACT floor analysis of the commenter-submitted dataset to determine which sources are the best performers and to identify a mercury standard for cement kilns is discussed in the background document.[38] Additional discussion of issues related to the mercury standard for cement kilns is found in Part Four, Section VI.B of the preamble.

[34] For multi-constituent HAP (e.g. SVM) the emissions for a run could be comprised of fully detected values for some HAP and detection limits for other HAP that were nondetect.

[35] See docket item OAR–2004–0022–0049.

[36] Mercury is a volatile compound at the typical operating temperatures of the air pollution control devices used by cement kilns (i.e., baghouses and electrostatic precipitators). Most of the mercury exits the cement kiln system as volatile stack emissions, with a smaller fraction partitioning to the clinker product or cement kiln dust. Thus, in general, there is a proportional relationship between the mercury concentration in the hazardous waste and stack emissions of mercury (i.e., as the mercury concentration in hazardous waste increases (assuming mercury concentrations in other inputs such as raw materials and fossil fuels (coal) and other factors remain constant), emissions of mercury will correspondingly increase).

[37] EPA's dataset for mercury for cement kilns is not like the RCRA compliance test emission data for other HAPs where each source designs the compliance test such that the operating limits it establishes account for the variability it expects to encounter during its normal operations (e.g., semi- and low volatile metals). This is not necessarily true for mercury for cement kilns as shown in our analysis of our mercury dataset at proposal. See 69 FR at 21251.

[38] USEPA, "Technical Support Document for HWC MACT Standards, Volume III: Selection of MACT Standards," Sections 7.5.3 and 11.0, September 2005.

E. Mercury Data for Lightweight Aggregate Kilns

Comment: One commenter, an owner and operator of seven of the nine operating lightweight aggregate kilns, states that the mercury dataset used by EPA at proposal is a limited and unrepresentative snapshot of performance of their seven kilns. To support their position that the snapshot emissions data are unrepresentative, the commenter submitted eight months of data documenting levels of mercury in hazardous waste fuels fired to their lightweight aggregate kilns.[39]

Response: We agree with the commenter that their mercury data submission is more representative than those used at proposal. As discussed in a notice for public comment sent directly to certain commenters,[40] the commenter-submitted dataset documents the day-to-day levels of mercury in hazardous waste fuels fired to Solite Corporation's Arvonia kilns between October 2003 and June 2004. The dataset consists of over 310 measurements of the concentration in mercury in hazardous waste. Each measurement represents the mercury concentration of the burn tank used to fire the kiln over the course of a day's operation (or longer period). In comparison, the data used to support the proposed floor level consisted of a smaller dataset of 15 test conditions.

The nature of the mercury data submitted by the commenter is the same as we received for the cement kiln category discussed in the preceding section. For similar reasons, we accept the more comprehensive commenter-submitted dataset as one that better shows the range of performance and variability in performance for these lightweight aggregate kilns. One notable difference, however, is that the commenter submitted mercury data only for its company (representing seven of nine lightweight aggregate kilns). Thus, we received no data documenting day-to-day levels of the concentration of mercury in hazardous waste fuels for the other two lightweight aggregate kilns owned by a different company. For these two lightweight aggregate kilns, we continue to use available data available in our database.[41]

Comment: One commenter opposes the use of the commenter-submitted mercury data because EPA would be uncritically accepting a limited and select data set from a commenter with a direct interest in the outcome of its use. Instead, the commenter suggests EPA use its section 114 authority to obtain all data that are available, not just the data selected by that commenter.

Response: We disagree that we uncritically accepted the commenter-submitted mercury data. The reason the commenter submitted data collected between October 2003 and June 2004 is that the facility was, prior to October 2003, in the process of upgrading its on-site analysis equipment. One outcome of this laboratory upgrade was its capability to detect mercury in hazardous waste at lower concentrations. Prior to the upgrade, the facility's on-site laboratory was capable of detecting mercury in the hazardous waste at a concentration of approximately 2 ppmw, which is a level such that the vast majority of measurements would neither be detected nor useful for identifying best performers and their level of performance.[42] The June 4, 2004 cutoff date represents a practicable date that measurements could still be incorporated into the commenter's public comments to the proposed rule, which were submitted on July 6, 2004. Finally, the commenter provided all waste fuel measurements during this period and states reliably that no measurements made during this period were selectively excluded.[43]

We also reject the commenter's suggestion that we use our authority under section 114 of the Clean Air Act to obtain additional hazardous waste mercury concentration data from the facility. There is no obligation for us to gather more performance data, given that the statute indicates that we are to base floor levels on performance of sources "for which the Administrator has emissions information." Section 112(d)(3)(A); *CKRC*, 255 F. 3d at 867. In addition, given our concerns about the usefulness of measurements with high detection limits discussed above, the collection of additional data prior to the laboratory upgrade would not be productive. When balanced against the expenditure of significant resources, both in time and level of effort, to collect several more months of data, we conclude that obtaining additional mercury measurements is unnecessary because the available eight months of data—including over 310 individual measurements—represent a significant amount of data that we judge to be adequately reflective of the source's performance and variability in performance.

F. Incinerator Database

Comment: Commenters state that many of the top performers (e.g., 3011, 3015, 3022, 349) dilute emission concentrations in the stack by burning natural gas to initiate reactive waste (e.g., explosives, inorganic hydrides) or to decontaminate inert material. Commenters do not believe these units should be considered "representative" of the overall incinerator source category and should not be used to establish standards for incinerators combusting primarily organic wastes.

Response: Source 3022 has closed and has been removed from the database. Emission data from source #3015 (ICI explosives) has been excluded for purposes of calculating the particulate matter floor because the test report indicates this source was primarily feeding scrap metal, which we conclude to be an atypical waste stream from a particulate matter compliance perspective.[44]

The sources identified by the commenter are among the best performing sources in two instances. Source 3011 is the second ranked best performer for the particulate matter standard. This source is among the best performers for particulate matter because it uses a state-of-the art baghouse that is equipped with Teflon coated bags. There is no evidence to suggest that this source was diluting its particulate matter emissions. We acknowledge that we do not have ash feed data for the test conditions that were used in the particulate matter standard analysis. However, this source had the third and fourth highest metal feed control levels among all the sources used in the MACT analysis for the semivolatile and low volatile metal

[39] See docket items OAR–2004–0022–0270 and OAR–2004–0022–0333.

[40] See docket item OAR–2004–0022–0370.

[41] Unlike that is available for the commenter's kilns, we note that we have compliance test emissions data, which is designed to maximize operating parameters (e.g., HAP feedrates) that affect emissions, for the other two kilns. For additional discussion on how these data were analyzed in conjunction with the commenter-submitted data, see the document "Technical Support Document for HWC MACT Standards, Volume III: Selection of MACT Standards," Section 7.5.3 and 12.0, September 2005.

[42] A mercury concentration of 2 ppmw in the hazardous waste corresponds to a stack concentration of approximately 200 µg/dscm, which is well above the interim standard of 120 µg/dscm for mercury.

[43] See also docket items OAR–2004–0022–0233 and OAR–2004–0022–0367.

[44] We did not have ash feed data for source 3015. We acknowledge that ash feed control levels do not significantly affect particulate matter emissions from sources equipped with baghouses. However, in this instance, the particulate matter emissions from this source may not be representative because this source may not have been feeding any appreciable levels of ash given that scrap metal feeds generally would not contribute to the ash loading into the baghouse.

standards.[45] We therefore conclude that it is appropriate to include this source in the MACT analysis that determines the relevant best performers for particulate matter.

Source 349 is the eighth ranked (out of 11) best performer for the particulate matter standard. We acknowledge that the ash feed level for this source is lower than most incinerators equipped with baghouses. However, particulate matter emissions from sources equipped with baghouses are not significantly affected by the ash inlet loading to the baghouse.[46] This is further supported by the fact that this source is ranked eighth among the best performers. We conclude source 349 is a best performer not because of its relatively low ash feed level, but rather because it is equipped with a well designed and operated baghouse. It is therefore appropriate to include this source in the MACT analysis.

Comment: Commenters state that source 341 should not be considered in the MACT analysis because it is a small laboratory waste burner that processes only 900 lbs/hr of waste. Commenters claim that more than 80 percent of the waste profile is non-hazardous waste.

Response: We approached this comment by asking if it would be appropriate to create a separate subcategory for source 341. We conclude it is not necessary to subcategorize hazardous waste incinerators based on the size of combustion units. This is because the ranking factors used to identify the relevant best performing sources are normalized in order to remove the influence that combustion unit size would otherwise have when identifying best performing sources. See part 4 section III.D below. Air pollution control system types (a ranking factor for particulate matter) are generally sized to match the corresponding volumetric gas flow rate in order to achieve a given control efficiency. The size of the combustor therefore does not influence a source's ability to achieve a given control efficiency. System removal efficiency and hazardous waste feed control MTECs (ranking factors used by the SRE/Feed methodology as described in part 4 section III.B below) are also not influenced by the size of the combustor.[47]

Emission limitations are similarly normalized to remove the influence of combustion unit size by expressing the standards as emission concentration limits rather than as mass emission rate limits. See section III.D. This is illustrated in the following example. Assume there are two cement kilns side by side with similar designs, the only difference being one is twice the size of the other, producing twice as much clinker. They both have identical types of air pollution control systems (the larger source is equipped with a larger control device that is appropriately sized to accommodate the larger volumetric gas flow rates and achieves the same control efficiency as the smaller control device). If we were to assess performance based on HAP mass emission rates (e.g., pounds per hour), the smaller source would be the better performer because its mass emission rates would be half of the mass emission rate of the larger source, even though they both are achieving the same back-end control efficiency. Emission concentrations, on the other hand, are calculated by dividing the HAP mass emission rate (e.g., pounds per hour) by the volumetric gas flowrate (e.g., cubic feet per hour). In the above example, both sources would have identical HAP emission concentrations (the larger source has twice the mass emission rate, but twice the volumetric gas flow rate), accurately reflecting their identical control efficiency. Emission concentrations normalize the size of each source by accounting for volumetric gas flowate, which is directly tied to the amount of raw material each source processes (and subsequently the amount of product that is produced). This is a reason we point out that normalization eliminates the need to create subcategories based on unit size. See part four section III.D.

Further, it would be difficult to determine an appropriate minimum size cutoff in which to base such a subcategorization determination. Such a subcategorization scheme could also yield nonsensical floor results, as was the case when we assessed subcategorizing commercial incinerators and on-site incinerators.[48]

We have identified source 341 as the best performing source for particulate matter and low volatile metals. It is the single best performing source for these standards because it is equipped with a state-of-the-art baghouse.[49] This source, which simultaneously feeds hazardous and nonhazardous wastes, conducted several emission tests that reflected different modes of operation. The amount of nonhazardous waste that was processed in the combustion unit varied across test conditions. We could not ascertain the exact amount of hazardous waste processed in the test condition that was used in the MACT analysis for low volatile metals because the test report stated the wastes that were processed were a mixture of hazardous and nonhazardous wastes, although we estimate that at least 26% of the waste processed was nonhazardous.[50] We note that we are aware of several other incinerators that processed nonhazardous waste at levels greater than 26 percent during their emission tests. We therefore do not believe this to be atypical operation that warrants subcategoriztion.

Moreover, the fact that this source was feeding nonhazardous wastes does not result in atypically low hazardous waste low volatile metal feed control levels, as evidenced by the relative feed control ranking for this source of thirteenth among the 26 sources assessed in the MACT analysis. It also has the highest normalized hazardous waste feed control level among the best performing sources, and has the fifth best low volatile metal system removal efficiency among those same 26 sources. We repeat that this source is being identified as the best performing source primarily because it is equipped with a highly efficient baghouse, not because it is feeding low levels of HAP metals attributable to its hazardous waste.

Furthermore, this source is not the lowest emitting source in the database. There are two sources with similar, but slightly lower low volatile metal compliance test emissions (one commercial incinerator and one onsite, non-commercial incinerator). This provides further evidence that the

[45] We note that feed control levels are normalized based on each source's gas flowrate. The feed control levels used to assess performance are therefore appropriate indicators that directly address whether emissions of these pollutants are in fact being diluted by the combustion of natural gas.

[46] See USEPA, "Technical Support Document for the HWC MACT Standards, Vol I: Description of Source Categories," September 2005, Section 3.2.2, for further discussion.

[47] System removal efficiency is a measure of the amount of the pollutant that is removed from the flue combustion gas prior to being emitted and likewise is not influenced by the size of the combustor because back-end control systems are sized to achieve a given performance level. Hazardous waste feed control levels are normalized to remove the influence of combustor size by dividing each source's mass feed rate by its volumetric gas flowrate.

[48] See USEPA, "Technical Support Document for the HWC MACT Standards, Volume III: Selection of MACT Standards", September 2005, Section 4.3.2 for further discussion.

[49] See USEPA, "Final Technical Support Document for the HWC MACT Standards, Volume I: Description of Source Categories", September 2005, Section 3.2.1, for further discussion.

[50] See USEPA, "Final Technical Support Document for the HWC MACT Standards, Volume I: Description of Source Categories", September 2005, Section 2.1 for further discussion.

emissions from this source appropriately represent emissions of a relevant best performing source.

Regarding the particulate matter standard, source 341 does not have atypically low ash feed rates as compared to other sources equipped with baghouses. Out of the nine best performing particulate matter sources for which we have ash feed information, this source ranks fourth (a ranking of one is indicative of the lowest ash feed rate). Nonetheless, as previously discussed, particulate matter emissions from sources equipped with baghouses are not significantly affected by the ash inlet loading to the baghouse. We note that particulate matter emissions from the second and third best performing source are not significantly different from this source, providing further evidence that this source is representative of the range of emissions exhibited by other well designed and operating incinerators equipped with baghouses.[51]

Comment: Commenters state that sources 3018 and 3019 are identified as best performers for mercury emissions for incinerators. After evaluating the trial burn plans for these sources, the commenter believes the data should not be used to calculate the MACT floor because the spiking rate for mercury was extremely low for a compliance test. The ranking for feedrate is therefore unrepresentative. The commenter suggests that these test results should be characterized as "normal".

Response: We have verified that the emission tests performed for sources 3018 and 3019 reflect the upper range of mercury emissions that are not to be exceeded by these sources, and that their spiked mercury feed rates were back-calculated from a risk assessment. We therefore conclude that we properly characterized these emissions as compliance test emissions data because they reflect the emissions resulting from the upper bound of hazardous waste mercury feedrates from these sources.[52] Consequently, these data are properly included with the other data used to calculate floor standards for mercury for incinerators.

Comment: Commenters state the trial burn plan for sources 3018 and 3019 describes these units to be of similar design. Thus the difference in results between these two similar sources is indicative of additional variability above and beyond the run-to-run variability and should be assessed if the data are deemed usable at all.

Response: We conclude both of these sources are in fact unique sources that should be assessed as individual sources for purposes of the MACT analysis. Although these sources are of similar design, we do not believe they are identical, in part because: (1) The facility itself conducted separate emission tests for the two units (rather than trying to avail itself of the 'data in lieu' option, which could save it the expense of a second compliance test, the obvious inference being that the source or regulatory official regards the two units as different); and (2) discussions with facility representatives indicated these units are similar, but not identical.[53] As a result, it would be inappropriate to assess emissions variability by combining the emissions of these two sources into one test condition given they are not identical units.

Comment: Commenters state that emissions data from source 327 should not be used to calculate dioxin/furan and mercury floors because they claim the carbon injection system did not appear to function properly during the test.

Response: We agree with the commenters. We have determined that this source encountered problems with its carbon injection system during the emissions test from which the data were obtained and subsequently used in EPA's proposed MACT analysis. We have also verified that this source did not establish operating parameter limits for the carbon injection system as a result of this test.[54] We therefore have excluded this mercury and dioxin data from the MACT analysis, and have instead used emissions data from an older test condition to represent this source's emissions.

Comment: Commenters state that the emissions data from source 3006 were based on a miniburn to determine how close the unit was to achieving the interim MACT standards. The commenter questions whether these data should be used for purposes of calculating MACT standards.

Response: The fact that a source conducts a voluntary emissions test (e.g., a miniburn) to determine how close it is operating to upcoming emission standards does not necessarily lead us to conclude that the emission data are inappropriate for purposes of calculating MACT standards. However, since proposal, we have determined that this source did not measure cadmium emissions during this emissions test. As a result, we conclude the semivolatile metal emissions data from this source should not be used in the MACT standard calculation for semivolatile metals because the data do not represent the source's combined emissions of lead and cadmium.

II. Affected Sources

A. Area Source Boilers and Hydrochloric Acid Production Furnaces

Comment: Five commenters state that the area sources subject to the proposed rule are negligible contributors to 112(c)(6) HAP emissions and should not be subject to major source standards for 112(c)(6) HAP. Commenters note that requiring compliance with MACT for 112(c)(6) HAP and RCRA for other toxic pollutants is more complicated and burdensome for sources than complying only with RCRA. Although an area source can choose to become regulated as a major source in order to reduce some RCRA requirements, they would become subject to more onerous emissions limits under Subpart EEE and the other MACT requirements.

One of these commenters states that subjecting an area source to major source standards under 112(c)(6) sends a negative message to industry that EPA does not value emissions reduction and/or chemical substitution, or other methods used by area sources to achieve that status. EPA is no longer providing any incentive for sources to take such difficult yet environmentally beneficial steps to become an area source. Imposing Title V permitting requirements on an entire facility that operates as an area source of hazardous air pollutants (HAPs) will impose an unfair and undue burden on the facility.

Another of these commenters states that section 112(c)(6) requires in pertinent part that EPA list categories and subcategories of sources assuring that sources accounting for not less than 90% of the aggregate emissions of each pollutant (specified in 112(c)(6)) are subject to standards under Section 112(d)(2) or (d)(4). In 1998, EPA published a notice identifying the list of source categories accounting for the section 112(c)(6) HAP emissions and to be regulated under section 112(d) to meet the 90% requirement. (63 FR 17838) At the time, EPA acknowledged that MACT standards for a number of the source categories had not yet been promulgated, and stated that when the

[51] Source 341 particulate matter emissions, after accounting for variability, equated to 0.0015 gr/dscf. The second and third ranked particulate matter sources emissions, considering variability, equated to 0.0018 and 0.0023 gr/dscf, respectively.

[52] See February 11, 2005 memo to docket titled "October 20 Conference Call with Squibb Manufacturing regarding Source # 3018 and 3019".

[53] Also see February 11, 2005 memo to docket titled "October 20 Conference Call with Squibb Manufacturing regarding Source # 3018 and 3019".

[54] See July 15, 2005 memo to docket titled "Telephone Conversation with Utah DEQ Regarding 2001 Clean Harbor Emission Test."

regulations for each of those categories are developed, EPA will analyze the data specific to those sources and determine, under Section 112(d), in what manner requirements will be established. EPA also stated that:

"Some area categories may be negligible contributors to the 90% goal, and as such pose unwarranted burdens for subjecting to standards. These trivial source categories will be removed from the listing as they are evaluated since they will not contribute significantly to the 90% goal." (63 FR 17841)

The commenter believes the "two or fewer" area source boilers identified by EPA in the present rulemaking are "negligible contributors" to the 90% goal and therefore, should not be required to adopt the same MACT emission limitations and requirements as major sources of the 112(c)(6) pollutants. The commenter believes EPA's decision to subject area source boilers and hydrochloric acid production furnaces is incorrect, unsupported by the administrative record, and therefore arbitrary and capricious.

One commenter states that, if EPA regulates area sources, it should significantly reduce the administrative burden for area sources by: exempting them from Title V provisions for Subpart EEE requirements; exempting them from compliance with the General Provisions of 63 Subpart A; limiting them to a one-time comprehensive performance test; or limiting other applicable requirements.

Response: We continue to believe that boiler and hydrochloric acid furnace area sources warrant regulation under the major source MACT standards for mercury, dioxin/furan, carbon monoxide/hydrocarbons, and destruction and removal efficiency pursuant to section 112(c)(6).

As discussed at proposal (69 FR at 21212), section 112(c)(6) of the CAA requires EPA to list and promulgate section 112(d)(2) or (d)(4) standards (i.e., standards reflecting MACT) for categories and subcategories of sources emitting seven specific pollutants. Five of those listed pollutants are emitted by boilers and hydrochloric acid production furnaces: mercury, 2,3,7,8-tetrachlorodibenzofuran, 2,3,7,8-tetrachlorodibenzo-p-dioxin, polycyclic organic matter, and polychlorinated biphenyls.

As discussed below, EPA must assure that source categories accounting for not less than 90 percent of the aggregated emissions of each enumerated pollutant are subject to MACT standards (and of course is not prohibited from requiring more than 90 percent of aggregated emissions to be controlled by MACT standards). Congress singled out the pollutants in section 112(c)(6) as being of "'specific concern'" not just because of their toxicity but because of their propensity to cause substantial harm to human health and the environment via indirect exposure pathways (i.e., from the air through other media, such as water, soil, food uptake, etc.). Furthermore, these pollutants have exhibited special potential to bioaccumulate, causing pervasive environmental harm in biota and, ultimately, human health risks.

Section 112(c)(6) of the CAA requires EPA to list categories and subcategories of sources of seven specified pollutants to assure that sources accounting for not less than 90 percent of the aggregate emissions of each such pollutant are subject to standards under CAA section 112(d)(2) or 112(d)(4). In 1998, EPA issued the list of source categories pursuant to section 112(c)(6), and that list is published at 63 Fed. Reg. 17838, 17849, Table 2 (April 10, 1998).

In the 1998 listing, EPA identified the following three subcategories of the HWC source category that emit one or more of the seven section 112(c)(6) pollutants: (1) Hazardous waste incinerators—(emit mercury, dioxin, furans, polycyclic organic matter (POM) and polychlorinated biphenyls (PCBs)); (2) Portland cement manufacture: hazardous waste kilns—(emit mercury, dioxin, furans, and POM); and (3) lightweight aggregate kilns: hazardous waste kilns—(emit dioxin, furans, and mercury). These three subcategories are all subject to today's rule, which is issued pursuant to CAA section 112(d)(2). As explained below, the HWC NESHAP effectively controls emissions of the identified section 112(c)(6) pollutants from the identified subcategories. Accordingly, EPA considers the sources in these three subcategories as being "subject to standards" for purposes of section 112(c)(6).

Specifically, with regard to hazardous waste-burning incinerators, cement kilns, and lightweight aggregate kilns, EPA is adopting in this final rule MACT standards for mercury and dioxins/furans. EPA has already adopted MACT standards for control of POM and PCBs emitted by these sources in the 1999 rule, which standards were not reopened or reconsidered in this rulemaking. These standards are the CO/HC standards, which in combination with the Destruction Removal Efficiency (DRE) requirement, assure that these sources operate continuously under good combustion conditions which inhibit formation of POM and PCBs as combustion by-products, or destroy these HAP if they are present in the wastes being combusted.[55] See discussion in Part Four, Sections V.A and V.B of this preamble.

The HWC NESHAP also applies to hazardous waste-burning boilers and hydrochloric acid production furnaces. In particular, for these boilers and furnaces, this rule addresses emissions of dioxin/furan, mercury, POM and PCBs either through specific numeric standards for the identified HAP, or through standards for surrogate pollutants which control emissions of the identified HAP.

We estimate that approximately 620 pounds of mercury are emitted annually in aggregate from hazardous waste burning boilers in the United States.[56] Also, we estimate that hazardous waste burning boilers and hydrochloric acid production furnaces emit in aggregate approximately 2.3 and 0.2 grams TEQ per year of dioxin/furan, respectively. Controlling emissions of these HAP from area sources consequently reduces emissions of these HAP through application of MACT standards. We note that only major source boilers and hydrochloric acid furnaces are subject to the full suite of subpart EEE emission standards.[57] Section 112(c)(3) of the CAA requires us to subject area sources to the full suite of standards applicable to major sources if we find "a threat of adverse effects to human health or the environment" that warrants such action. We cannot make this finding for area source boilers and halogen acid production furnaces. 69 FR at 21212. Consequently, as proposed, area sources in these categories would be subject only to the MACT standards for mercury, dioxin/furan, and polycyclic

[55] Courts have repeatedly upheld EPA's authority under CAA section 112(d) to use a surrogate to regulate hazardous pollutants if it is reasonable to do so. See, e.g., *National Lime*, 233 F. 3d at 637 (holding that EPA properly used particulate matter as a surrogate for HAP metals).

[56] See USEPA "Technical Support Document for HWC MACT Standards, Volume V: Emission Estimates and Engineering Costs," September, 2005, Section 3.

[57] We note that as a practical matter, however, the same MACT standards apply to both major and area source HCl production furnaces. This is because major sources are subject to the following standards: CO/HC, DRE, and total chlorine. Because the CO/HC and DRE standards are surrogates to control dioxin/furan, and the total chlorine standard is a surrogate to control metal HAP, area sources are subject to the same standards that address dioxin/furan, polycyclic organic matter, polychlorinated biphenyls, and mercury. There is an enforcement difference between the requirements, however. For area sources, an exceedance of the total chlorine standard (or failure to ensure that compliance is maintained) relates to control of mercury only while for a major source, the same failure relates to control of mercury, other metal HAP, and HCl and chlorine.

organic matter and polychlorinated biphenyls (through the surrogate standards for carbon monoxide/hydrocarbons and destruction and removal efficiency) to control the HAP enumerated in section 112(c)(6). RCRA standards under Part 266, Subpart H for particulate matter, metals other than mercury, and hydrogen chloride and chlorine gas would continue to apply to these area sources unless an area source elects to comply with the major source standards in lieu of the RCRA standards. See § 266.100(b)(3) and the revisions to §§ 270.22 and 270.66.

Commenters refer to the "two or fewer" potential area source boilers we identified at proposal as "negligible contributors" and, therefore, conclude that these area sources should not be subject to major source standards for emission of these HAPs. Commenters did not quantify the amount of emissions from area sources, and did not even identify how many area sources are at issue. We do not know how many boilers and hydrochloric acid furnaces are area sources. We apparently underestimated the number given that four companies commented on the proposed rule saying that area sources should not be subject to major source standards for mercury, dioxin/furan, PCBs, and polycyclic organic matter, and one of those companies indicates it operates multiple area sources. Consequently, we continue to believe that area sources in these categories may have the potential to emit more than negligible levels of these HAP.

We also note that the major source standards are tailored to minimize the compliance burden for sources that emit low levels of HAP. Commenters raise concerns about applying the major source standards for HAP enumerated in section 112(c)(6) to liquid fuel boiler area sources. The emission standard compliance burden for liquid fuel boilers that have the potential to emit only low levels of mercury, dioxin/furan, and polycyclic organic matter is minimal. For example, sources that emit low levels of mercury because their feedstreams have low levels of mercury can elect to comply with the mercury emission standard by documenting that the mercury in feedstreams will not exceed the standard assuming zero removal by emission control equipment. We note that 75% of the liquid fuel boilers in our data base, and the two boilers cited by commenters, do not have emission control devices.

The compliance burden for the major source standards for dioxin/furan and for the surrogates to control other polycyclic organic matter—carbon monoxide/hydrocarbons and destruction and removal efficiency (DRE)—should also be minimal for area source liquid fuel boilers. The dioxin/furan standard applicable to the 90% of liquid fuel boilers with wet or no air pollution control equipment is compliance with the carbon monoxide/hydrocarbon standard and the DRE standard. Liquid fuel boilers already comply with these same standards under RCRA. The surrogate standards to control other polycyclic organic matter are also the carbon monoxide/hydrocarbon and DRE standards. Finally, we note that the DRE requirement under Subpart EEE is less burdensome than the DRE requirement under RCRA. Under Subpart EEE, a source needs to conduct a one-time only DRE test, provided that design and operation does not change in a manner than could adversely affect DRE. Under RCRA, the DRE test must be conducted each time the RCRA permit is renewed.

The incremental compliance burden associated with the other Subpart EEE major source requirements, such as the operations and maintenance plan, the startup, shutdown, and malfunction plan, operator training, and the automatic waste feed cutoff system should also be minimal for liquid fuel boilers without an emission control device. In addition, most of the requirements are either identical to or very similar to requirements under RCRA with which these area sources are already complying.[58]

B. Boilers Eligible for the RCRA Low Risk Waste Exemption

Comment: Several commenters state that EPA should exempt those boilers that qualify as Low Risk Waste Exemption (LRWE) burners under the RCRA Boiler and Industrial Furnace Rule at § 266.109 from the MACT particulate matter and destruction and removal efficiency (DRE) standards because EPA has not: (1) Made a demonstration that the data used to provide the exemption to low risk burners under RCRA is no longer valid; or (2) established in the affirmative that regulating these units will provide any benefit to human, health and the environment. Commenters believe that regulating LRWE units under Subpart EEE is unnecessary and inconsistent with RCRA subtitle C and more importantly, appears to be controlling LRWE units for control's sake.

Commenters also state that EPA has not properly addressed the requirements of CAA section 112(n)(7) regarding the inconsistency between the requirements for Low Risk Waste Exempt (LRWE) units under RCRA and those of Subpart EEE. The purported purpose of section 112(n)(7) is to allow EPA to avoid imposing additional emission limitations on a source category subcategory when such limitations would be unnecessary and duplicative.

In addition, commenters state that the costs associated with this MACT are much more than improved feed control or better back-end control. This proposed rule also requires substantial dollar investment in improved data acquisition, computer controls and recordkeeping systems, performance testing, training, development of plans, and other regulatory requirements.

Response: Boilers and hydrochloric acid production furnaces that currently qualify for the RCRA § 266.109 low risk waste exemption are not exempt from Subpart EEE under the final rule.

The Administrator does not have the authority under CAA section 112(d) to exempt sources that comply with RCRA § 266.109. Indeed, there is no necessary connection between the two provisions, since one is technology-based and the other is risk-based. CAA section 112(d)(2) requires the Administrator to establish technology-based emission standards, standards that require the maximum degree of reduction in emissions that is deemed achievable. Although section 112(d)(4) gives the Administrator the authority to establish health-based emission standards in lieu of the MACT standards for pollutants for which a health threshold has been established, we cannot use that authority to develop health-based standards for sources that comply with RCRA § 266.109 because those sources emit HAP for which a health threshold has not been established.

The final rule complies fully with CAA section 112(n)(7) by coordinating applicability of the RCRA and CAA requirements and precluding dual requirements. For example, RCRA requirements that are duplicative of MACT requirements will be removed from the RCRA operating permit when the permitting authority issues a certification of compliance after the source submits a Notification of Compliance.

We also note that the MACT standards are tailored to impose

[58] RCRA, 40 CFR Part 264 requirements that are similar to MACT requirements include: the general inspection requirements and personnel training requirements of Subpart B; the preparedness and prevention requirements of Subpart C, including design and operation of facility, testing and maintenance of equipment, and access to communications or alarm system; the contingency plan and emergency procedures requirements of Subpart D; and the operating requirements and monitoring and inspection requirements of Subpart O.

minimal burden on sources that have low emissions of HAP. The particulate matter emission standard and associated testing can be waived (similar to the § 266.109 exemption) for boilers that elect to document that emissions of total metal HAP do not exceed the limits provided by § 63.1206(b)(14). Hydrochloric acid production furnaces are not subject to a particulate matter emission standard.

The compliance burden with the destruction and removal efficiency (DRE) standard is also minimal given that it is a one-time test, provided that the source does not change its design or operation in a manner that would adversely affect DRE. In addition, the compliance burden for sources with low levels of metals in their feedstreams is minimal. Sources can document compliance with the metals emission standards by assuming all metals in the feed are emitted (i.e., by assuming zero system removal efficiency). Under this procedure, boilers burning relatively clean wastes are not required to conduct a performance test to document compliance with the metals emission standards.

Further, we note that the MACT standard to control organic HAP emissions other than dioxin/furan is the same as the RCRA standard—demonstrating good combustion conditions by complying with a carbon monoxide standard of 100 ppmv.

Finally, we note that the ancillary requirements under MACT (e.g., personnel training; operating and maintenance plan; startup, shutdown, and malfunction plan) should not pose substantially higher costs than similar requirements under RCRA. See response to comment in Section A above. To the extent that compliance costs increase, we have accounted for those costs in our estimates of the cost of the final rule.[59]

C. Mobile Incinerators

Comment: A mobile incinerator used as a directly-fired thermal desorption unit at a Superfund remediation site should not be an affected source under this rule.

Response: EPA is not determining or changing the applicability of any hazardous waste burning unit under today's rule. A combustion unit that treats hazardous waste and meets the definition of incinerator at 40 CFR 260.10 is an affected source under this rule. 40 CFR part 63 also defines a source as any building, structure, facility, or installation which emits or may emit any air pollutant. A mobile incinerator at a remediation site meets this definition.

Comment: One commenter states that a subcategory with different standards must be created for mobile incinerators, or the standards for incinerators must be calculated using actual emissions data from mobile units.

Response: EPA did not have any emissions data from mobile incinerators in the database for the proposed rule. That data base was developed over many years with ample opportunity for public comment. We developed a data base for incinerators to support the 1996 proposed rule (61 FR 17358) and noticed that data base for public comment on January 7, 1997 (64 FR 52828). We updated that data base in July 2002, and noticed the revised data base for public comment (67 FR 44452). We used that revised data base to support the proposed rule. We did not receive comments providing data for mobile incinerators as a result of either public notice.

One commenter on the proposed rule provided a summary of emissions data from one test at a mobile incinerator. The commenter suggested that the data support its view that its mobile incinerator is unique and that EPA should consider subcategorizing incinerators according to mobile incinerators versus other incinerators. We analyzed these data and conclude that the final standards are readily achievable by this source. Moreover, as explained elsewhere, EPA's approach to assess the need for subcategorization is to apply a statistical test to determine whether the emissions data are statistically different from the remaining group. Given that owners and operators of mobile incinerators have not provided emissions data prior to proposal, and that the commenter provides summarized data for only one mobile incinerator (which also indicate that the source can achieve the emission standards in the final rule); we are not compelled to gather additional information, particularly given our time constraints to promulgate the final rule under a court-ordered deadline.

Comment: In support of subcategorizing mobile incinerators, commenters state that mobile thermal treatment systems are substantially different from hazardous waste incinerators. They are much smaller in size, firing capacity rate, refractory lining, and operating temperatures. Most of them treat contaminated soil, so have very high particulate feedrate loading with high ash content, rapid kiln rotation rate, and counter-current flow design like cement kilns. This results in high particulate matter emissions. They operate only for a short duration at a site (usually less than 6 months), and have no flexibility with regard to their waste feed.

Response: We recognize that there is variability between various sources' with regard to size, capacity, operating temperatures etc., and so we applied a statistical test to assess the need of subcategorization, as has been discussed above. The emissions data provided by the commenter also indicate the source can achieve the final standards. The soil entrained in desorber off-gases of mobile incinerators has a relatively large particle size, and is very easy to capture with conventional particulate control systems (such as a fabric filter) used by the incinerators.

Comment: Since mobile incinerators are relocated from site to site, the new source standard should not apply based on the erection date of the mobile unit.

Response: We are not changing the applicability of a new or reconstructed source designation in this rulemaking. The relocation issue is addressed in the definition of "construction" in 40 CFR Section 63.2, which states: "Construction does not include the removal of all equipment comprising an *affected source* from an existing location and the reinstallation of such equipment at a new location * * *" (emphasis added). Therefore, the relocation of an existing Subpart EEE affected source, such as a mobile incinerator, would not result in that mobile incinerator becoming a "new" source. Keep in mind also that the relocation exemption only applies to affected sources. If a mobile incinerator is relocated from an R&D facility (where the unit is not an affected source per Table 1 to Section 63.1200) to a location where the mobile incinerator would become an affected source, the relocation exemption within the definition of "construction" would not apply and the mobile incinerator would be a "new" source. Also, with regard to leased sources, the owner/operator of the facility is responsible for all affected sources operating at his/her facility regardless of whether the sources are owned or leased. The owner or operator should obtain from the leasing company all relevant information pertaining to the affected source in order to be able to demonstrate that the affected source is operating in compliance with the appropriate standards.

III. Floor Approaches

In this section we discuss comments addressing methodologies used in this rule for determining MACT floors. We address comments relating both to

[59] USEPA "Technical Support Document for HWC MACT Standards, Volume V: Emission Estimates and Engineering Costs," September, 2005.

general, overarching issues and to the specific methodologies used in the rule. Our most important point is that the methodologies EPA selected reasonably estimate the performance of the best performing sources by best accounting for these sources' total variability.

A. Variability

1. Authority To Consider Emissions Variability

Comment: Many commenters concur with our approach to account for emissions variability while several commenters believe that our approach does not adequately account for emissions variability. See discussions on separate topics below. One commenter, however, states that use of variability factors (however derived) is inherently unlawful and arbitrary and capricious. The commenter notes that, because floors for existing sources must reflect the "average" emission level achieved by the relevant best performing sources, they cannot reflect any worse levels of performance from the best performers. Indeed, the argument is that the Clean Air Act already accounts for variability by requiring EPA to base existing source floors on the average emission level achieved by the best performing sources.

The commenter continues by stating that EPA has added variability factors both to each individual source's performance and to the collective performance of the alleged best performers, in each case purporting to find an emission level that the individual or group would meet ninety-nine times out of 100 future emission tests. Thus, EPA ignores sources' measured performance in favor of the theoretical worst performance that might ever be expected from them. By looking to the best performers' worst performance rather than their average performance, EPA would set weaker floors than the Clean Air Act allows.

In addition, the commenter notes that EPA's approach to account for emissions variability is arbitrary and capricious because EPA never explains why it chose the 99th percentile for its variability adjustments rather than some other percentile.

Finally, the commenter notes that EPA appears to indicate that its variability analysis would either be applied to variation between sources or would affect EPA's statistical analysis of the variation between sources. The commenter states that any attempt by EPA to add a variability factor to adjust for intersource variability is unlawful and arbitrary and capricious.

Response: Our response explains our approach to estimating best performing sources' variability and addresses the following issues: (1) Considering the variability in each source's performance is necessary to identify the best performing sources and their level of performance; (2) EPA reasonably considered variability in ranking sources to identify the best performers and in considering the range of best performing sources' performance over time to identify an emission level that the average of those sources can achieve; (3) considering variability at the 99th percentile level is reasonable; (4) considering intersource variability by pooling run-to-run variability is appropriate; and (5) compliance test conditions do not fully reflect all of best performing sources' performance variability.

a. *Variability Must Be Considered.* Variability in each source's performance must be considered at the outset in identifying the best performing sources. This is simply another way of saying that best performers are those that perform best over time (i.e. day-in, day-out), a reasonable approach. This approach not only reasonably reflects the statutory language, but also furthers the ultimate objective of section 112 which is to reduce risk from exposure to HAP. Since most of the risk from exposure to emissions from this source category is associated with chronic exposure to HAP (see Part 1 section VI above), assessing a source's performance over time by accounting for variability is reasonable and appropriate.

For similar reasons, variability must be considered in ascertaining these sources' level of performance. Floors for existing sources must reflect "the average emission limitation achieved by the best performing 12 percent" of sources, and for new sources, must reflect "the emission control that is achieved in practice by the best controlled source." Section 112 (d) (3). EPA construes these requirements as meaning achievable over time, since sources are required to achieve the standards at all times. This interpretation has strong support in the case law. See *Sierra Club* v. *EPA*, 167 F. 3d 658, 665 (D.C. Cir. 1999), stating that "EPA would be justified in setting the floors at a level that is a reasonable estimate of the performance of the 'best controlled similar unit' under the worst reasonably foreseeable circumstances. It is reasonable to suppose that if an emissions standard is as stringent as 'the emissions control that is achieved in practice' by a particular unit, then that particular unit will not violate the standard. This only results if 'achieved in practice' is interpreted to mean 'achieved under the worst foreseeable circumstances'; see also *National Lime Ass'n* v. *EPA*, 627 F. 2d 416, 431 n. 46 (D.C. Cir. 1980) (where a statute requires that a standard be 'achievable,' it must be achievable under "the most adverse circumstances which can reasonably be expected to recur");

The court has further indicated that EPA is to account for variability in assessing sources' performance for purposes of establishing floors, and stated that this assessment may require EPA to make reasonable estimates of performance of best performing sources. *CKRC*, 255 F. 3d at 865–66; *Mossville Environmental Action Now* v. *EPA*, 370 F. 3d 1232, 1242 (D.C. Cir. 2004)(maximum daily variability must be accounted for when establishing MACT floors).[60] Indeed, EPA's error in *CKRC* was not in estimating best performing sources' variability, but in using an unreasonable means of doing so. *CKRC*, 255 F. 3d at 866; *Mossville*, 370 F. 3d at 1241.

Since the emission standards in today's rule must be met at all times, the standards need to account for performance variability that could occur on any single day of these sources' operation (assuming proper design and operation). See *Mossville*, 370 F. 3d at 1242 (upholding MACT floor because it was established at a level that took into account sources' long term performance, not just performance on individual days). Moreover, since EPA's database consists of single data points (because there are no continuous emission monitors for HAPs in stack emissions), EPA must of necessity estimate long-term performance, including daily maximum performance, from this limited set of short term data.

b. *EPA Reasonably Considered Variability in Ranking Sources to Identify the Best Performers and in Considering the Range of Best Performing Sources' Performance Over Time to Identify an Emission Level that the Average of Those Sources Can Achieve.* (1) *Selecting Best Performing Sources.* Each of the floor methodologies used in the rule considers various factors in ranking which sources are the best performing. For each methodology, we therefore consider the quantifiable variability of

[60] See also *Chemical Manufacturers Ass'n* v. *EPA*, 870 F. 2d 177, 228 (5th Cir. 1989) ("The same plant using the same treatment method to remove the same toxic does not always achieve the same result. Tests conducted one day may show a different concentration of the same toxic than are shown by the same test the next day. This variability may be due to the inherent inaccuracy of analytical testing, (i.e. 'analytical variability,' or to routine fluctuations in a plant's treatment performance.")

the ranking factors in determining which are the best performing sources. 69 FR at 21230–31. Specifically, we assess run-to-run variability (normally the only type of variability which we can quantify) of the factors used under each methodology to rank best performers. Where SRE/Feed is the ranking methodology, we thus assess run-to-run variability of hazardous waste HAP feedrate and of system removal efficiency. Where ranking is based on sources' emissions (the straight emissions methodology), we assess the run-to-run variability of emission levels. Where we use the air pollution control device methodology for ranking, we assess the run-to-run variability of emissions of the lowest-emitting sources (as we do for straight emissions) using the best air pollution control devices. For hydrochloric acid production furnaces, we assess the run-to-run variability of total chlorine system removal efficiency. *Id.*[61]

To account for run-to-run variability in these ranking factors, we rank sources by the 99th percentile upper prediction limit (UPL99). The UPL99 is an estimate of the value that the source would achieve in 99 of 100 future tests if it could replicate the operating conditions of the compliance test. *Id.* at 21231.

(2). *Assessing the Best Performers' Level of Performance Over Time.* Once we identify the best performing sources, we need to consider their emissions variability to establish a floor level that the average of the best performing sources can achieve day-in, day-out. There are two components of emissions variability that must be considered: run-to-run variability and test-to-test variability. Run-to-run emissions variability encompasses variability in individual runs comprising the compliance tests, and includes uncertainties in correlation of monitoring parameters and emissions, and imprecision of stack test methods and laboratory analyses. See 69 FR at 21232.[62] Test-to-test emissions variability is the variability that exists between multiple compliance tests conducted at different times and includes the variability in control device collection efficiency caused by testing at different points in the maintenance cycle of the emission control device[63], and the variability caused by other uncontrollable factors such as using a different stack testing crew or different analytical laboratory, and by different weather conditions (e.g., ambient moisture and temperature) that may affect measurements.

We are able to quantify run-to-run variability. We do so by applying a 99th percentile *modified* upper prediction limit to the averaged emissions of the best performing sources. *Id.* at 21233 and Technical Support Document Volume III section 7.2. The modified upper prediction limit accounts for run-to-run variability of the best performers by pooling their run variance (i.e., within-test condition variability).[64] See *Chemical Manufacturer's Ass'n* v *EPA*, 870 F. 2d 177, 228 (5th Cir. 1989) (upholding use of a variability factor derived, as here, by pooling the performance variability of the best performing plants). Using this approach, we ensure that the average of the best performing sources will be able to achieve the floor in 99 of 100 future performance tests, assuming these best performing sources could replicate their performance when attempting to operate under identical conditions to those used for the compliance test establishing the source as best performing. As just noted, we call this value the modified UPL 99.

The only instance in which we are able to quantify test-to-test variability (as noted above, the other significant component of total operating variability) is for fabric filters (baghouses) when used to control emissions of particulate matter. The modified UPL 99 in these instances reflects not only run-to-run variability, but test-to-test variability as well. That total variability is expressed by the Universal Variability Factor which is derived from analyzing long-term variability in particulate matter emissions for best performing sources across all of the source categories sources that are equipped with fabric filters. 69 FR at 21233. See also the discussion below in Section III.A.2.

Test-to-test variability must be accounted for in other instances as well, however. It follows that if the performance of most efficient fabric filters varies over time relative to particulate matter emissions, then so does their performance relative to the non-mercury metal HAP emissions. We also believe that particulate matter emissions variability from sources equipped with back-end controls other than fabric filters also exists, and is furthermore likely to be higher than what was calculated for fabric filters because there are more uncertainties associated with the correlations between operating parameter limits and control efficiency for these devices.[65] Again, it clearly follows that if the performance of these other control devices varies relative to particulate matter emissions (perhaps even more than what has already been quantified for fabric filters), then so does their performance relative to the non-mercury metal HAP emissions.

Although we cannot quantify this test-to-test variability, we can document its existence and its significance. We conducted two parallel analyses examining all situations where we had multiple test conditions for the sources ranked as best performing performing (examining separate pools for best performing sources under both the straight emissions and SRE/feed ranking methodologies). These analyses showed that these sources' emissions do in fact vary over time, sometimes significantly. In many instances sources had poorer system removal efficiencies and higher emission levels than those in the compliance test used to identify the source as best performing. We further projected that in many instances these best performing sources would not achieve their own UPL 99; the statistically determined prediction limit which captures 99 out of 100 future three-run test averages for the source, if they were to operate at the poorer system removal efficiency of its earlier test and used the federate of its later (best-performing) compliance test. This is significant because the UPL 99 reflects all of a source's run-to-run

[61] These ranking methodologies are discussed later in this section of the preamble, and in USEPA, "Technical Support Document for HWC MACT Standards, Volume III: Selection of MACT Standards," September 2005, Section 7.

[62] Analytic variability exists, and normally must be accounted for in establishing technology-based standards based on performance of the best-performing plants. *Chemical Manufacturers Ass'n* v. *EPA*, 870 F. 2d at 230.

[63] There are myriad factors that affect performance of an emissions control device. These factors change over time, including during the maintenance cycle of the device, such that it is virtually impossible to conduct future compliance tests under conditions that replicate the performance of the control device. See USEPA, "Technical Support Document for HWC MACT Standards, Volume III: Selection of MACT Standards," September 2005, Section 5.3.

[64] We note that the Agency used a statistical approach when proposing the NESHAP for Electric Utility Steam Generating Units. See memo from William Maxwell, EPA, to Utility MACT Project Files, entitled, "Analysis of variability in determining MACT floor for coal-fired electric utility steam generating units," dated Nov. 26, 2003, Docket A–92–55.

[65] For example, sources equipped with electrostatic precipitators generally establish multiple operating limits to best assure compliance with the emission standard (feed control limits, power input limits, etc.). There is not an exact correlation between emission levels and operating levels because there are several factors that can affect the control efficiency of these air pollution control systems, such as variations in inlet loads, power inputs, spark rates, humidity, as well as particle resistivity. See USEPA, "Technical Support Document for the HWC MACT Standards, Volume III: Selection of MACT Standards," September 2005, Sections 16 and 17.

variability. Failure to meet the UPL 99 thus shows both that further variability exists, namely test-to-test variability, and that it is a significant component of total variability. We obtained similar results when we projected best performing sources' performance based on each of these sources' overall system removal efficiency obtained by pooling the removal efficiencies of all of its tests. In many instances, moreover, these projected levels exceeded floor levels calculated by using the straight emissions approach, which ranks best performers as those with the lowest emission levels. This point is discussed further in Section III.B below. EPA's analysis is set out in detail in chapters 16 and 17 of Volume III of the Technical Support Document.[66]

EPA's conclusion is that total variability includes both run-to-run and test-to-test variability, and that both must be accounted for in determining which are the best performing sources and what are their levels of performance over time. As explained in the following Sections B and C, EPA has accordingly adopted floor methodologies which account for this total variability either quantitatively or qualitatively. The approach advocated by the commenter simply ignores that variability exists. Since this approach is contrary to both fact and law, EPA is not adopting it.

c. *Quantifying Run-to-Run Variability at the 99th Percentile Level Is Reasonable.* We selected the 99% prediction limit to ensure a reasonable level " namely the 99th percentile—of achievability for sources designed and operated to achieve emission levels equal to or better than the average of the best performing sources.[67] Because of the randomness of the emission values, there is an associated probability of the average of the best performing sources, and similarly designed and operated sources, not passing the performance test conducted under the same conditions.[68] At a 99% confidence level, the average of the best performing sources could expect to achieve the floor in 99 of 100 future performance tests conducted under the same conditions as its performance test.. The commenter thus sharply mischaracterizes a 99% confidence level as the worst performance of a best performing source.: the level in fact assumes identical operating conditions as those of the performance test.

EPA routinely establishes not-to-exceed standards (daily maximum values which cannot be exceeded in any compliance test) using the 99% confidence level. *National Wildlife Federation* v. *EPA*, 286 F. 3d 554, 572 (D.C. Cir. 2002).[69] At a confidence level of only 97% for example, the average of the best performing sources could expect to achieve the floor in only 97 of 100 future performance tests.

We note that the choice of a confidence level is *not* a choice regarding the stringency of the emission standard. Although the numerical value of the floor increases with the confidence level selected it only appears to become less stringent. If EPA selected a lower confidence interval, we would necessarily adjust the standard downward due to the expectation that a source would not be expected to achieve the standard for uncontrollable reasons a larger per cent of the time. We would then have to account in some manner for this inability to achieve the standard. See *Weyerhaeuser* v. *Costle*, 590 F. 2d 1011, 1056–57 (D.C. Cir. 1978) (also upholding standards established at 99 % confidence level). The governing issue is what level of confidence should the average of the best performing sources, and similarly designed and operated sources, have of passing the performance test demonstrating compliance with the standard. We believe that the 99% confidence level is a confidence level within the range of values we could have reasonably selected.[70]

d. *Considering Intersource Variability by Pooling Run-to-Run Variability is Appropriate.* The commenter believes that any attempt by EPA to add a variability factor to adjust for intersource variability is unlawful and arbitrary and capricious. We see no statutory prohibition in considering intersource run-to-run variability of the best performing sources (which is all our floor calculation does, by considering the pooled run-to-run variability of the best performing sources). Section 112(d)(3) states that MACT floors are to reflect the "*average* emission limitation achieved" but does not specify any single method of ascertaining an average. Considering the average run-to-run variability among the group of best performing sources is well within the language of the provision (and was upheld in *CMA*, as noted above; see 870 F. 2d at 228). The commenter's further argument that 'average' can only mean average of emission levels achieved in performance tests is inconsistent with the holding in *Mossville*, 370 F. 3d at 1242, that EPA must account for variability in developing MACT floors and that individual performance tests do not by themselves account for such variability.

We believe that it is reasonable and necessary to account for intersource variability of the best performing sources by taking the pooled average of the best performing sources' run-to-run variability. This is an aspect of identifying the average performance of those sources. Emissions data for each best performing source are random in nature, and this random nature is characterized by a stochastic distribution. The stochastic distribution is defined by its central tendency (average value) and the amount of dispersion from the point of central tendency (variance or standard deviation). Consequently, to define the performance of the average of the best performing sources, we must consider the average of the average emissions for the best performing sources as well as the pooled variance for those sources. Hence, we must consider intersource variability to identify the floor—the average performance of the best performing sources.

The commenter further states that EPA's attempt to adjust for intersource variability is unlawful, arbitrary, and capricious. EPA set floors at the 99th percentile worst emission level that it believed any source within the group of best performers could achieve, according to the commenter. The 99th percentile worst performance that could be expected from a source within the best performers is, simply put, not the average performance of the sources in that group, according to the commenter.

The commenter misunderstands our approach to calculate the floor—the floor is not the 99th percentile highest emission level that any best performing source could achieve. The floor for

[66] We explain in those sections that these projections assume that system removal efficiencies are constant across differing HAP federates and that the sources' historical (poorer) system removal efficiencies were not the primary result of operating at poorer "controllable" conditions relative to the most recent test condition. These are reasonable assumptions, as explained in section 17. 3 of Volume III of the Technical Support Document, although these assumptions also create a measure of uncertainty regarding the emissions projections.

[67] Note, again, that the variability we quantify by these analyses is within-test condition variability only. We cannot quantify test-to-test variability and thus cannot quantify sources' total variability.

[68] See Volume III of the Technical Support Document, Section 7.2 .

[69] The opinion notes further that percentiles for standards expressed as long-term average typically use a lower confidence level (usually 95 %c) due to the opportunity to lower the overall distribution with multiple measurements. 286 F. 3d at 573. The standards in this rule are necessarily daily maximum standards because continuous emissions monitors for HAP do not exist or have not been demonstrated on all types of Subpart EEE sources.

[70] See also *Chemical Mfrs. Ass'n* v. *EPA*, 870 F. 2d at 229 (99th percentile daily variability factor is reasonable); 227 ("the choice of statistical methods is committed to the sound discretion of the Administrator").

existing sources is calculated as the 99th percentile modified upper prediction limit of the average of the best performing sources. It represents the average of the best performing sources' emissions levels plus the pooled within-test condition variance of the best performing sources. The floor for existing sources is not the highest 99th percentile upper prediction limit for any best performing source as the commenter states.

e. *Why isn't Total Variability Already Accounted for by Compliance Test Conditions?*

Comment: One commenter states that EPA's use of variability factors along with worst-case data is unlawful and arbitrary and capricious. EPA has stated that its use of worst case "compliance" data accounts for variability. EPA admits that compliance data reflect special worst case conditions created artificially for the purpose of obtaining lenient permit limits, according to the commenter. EPA provides no reason whatsoever to believe that a source would continue to operate under such conditions even one percent of the time. Thus, the commenter concludes, by applying a 99 percent variability factor to compliance test data, EPA ensures that the adjusted data do not accurately reflect the performance of any source. Accordingly, EPA's use of a variability factor is unlawful.

The commenter also states that, to increase compliance data with the reality that sources will not be operating under the worst case conditions except during permit setting tests, the Agency's use of a variability factor with compliance data is arbitrary and capricious.

Response: All but two standards in the final rule are based on compliance test data—when sources maximized operating parameters that affect emissions to reflect variability of those parameters and to achieve emissions at the upper end of the range of normal operations. Use of these data is appropriate both because they are data in EPA's possession for purposes of section 112(d)(3) and because these data help account for best performing sources' operating variability. *CKRC*, 255 F. 3d at 867.

The main thrust of the comment is that total variability is accounted for by the conditions of the performance test, so that making further adjustments to allow for additional variability is improper. The commenter believes that the floor should be calculated simply as the average emissions of the best performing sources and that this floor would encompass the range of operations of the average of the best performing sources. We disagree.

The compliance test is designed to mirror the outer end of the *controllable* variability occurring in normal operations. These controllable factors include the amount of HAP fed to a source in hazardous waste, and controllable operating parameters on pollution control equipment (such as power input to ESPs, or pressure drop across wet scrubbers, factors which are reflected in the parametric operating limits written into the source's permit and which are based on the results of the compliance testing). However, this is plainly not all of the variability a source experiences. Other components of run-to-run variability, including variability relating to measuring (both stack measurements and measurements at analytic laboratories) are not reflected, for example. Nor is test-to-test variability reflected, notably the point in the maintenance cycle that testing is conducted and the variability associated with those inherently differing test conditions even though the source attempts to replicate the test conditions (e.g., measurement variability attributable to use of a different test crew and analytical laboratory and different weather conditions such as ambient temperature and moisture). Other changes that occur over time are due to a wide variety of factors related to process operation, fossil fuels, raw materials, air pollution control equipment operation and design, and weather. Sampling and analysis variations can also occur from test to test (above and beyond those accounted for when assessing within-test variability) due to differences in emissions testing equipment, sampling crews, weather, and analytical laboratories or laboratory technicians.

Thus, there is some need for a standard to account for this additional variability, and not simply expect for a single performance test to account for it. The analyses in Sections 16 and 17 of Volume III of the Technical Support Document confirm these points.

Moreover, the best performing sources (and the average of the best performers) must be able to replicate the compliance test if they are to be able to continue operating under their full range of normal operations. It is thus no answer to say that the best performing sources could operate under a more restricted set of conditions in subsequent performance tests and still demonstrate compliance, so that there is no need to assure that results of initial performance tests can be replicated. To do so would no longer allow the best performing sources (and thus the average of the best performing sources) to operate under their full range of normal operations, and thus impermissibly would fail to account for their total variability.

As discussed throughout this preamble, emissions variability—run-to-run and test-to-test variability—is real and must be accounted for if a best performing source is to be able to replicate the emissions achieved during the initial compliance test. We consequently conclude that we must account for variability in establishing floor levels, and that merely considering the average of compliance test data fails to do so. We have therefore quantified run-to-run variability using standard statistical methodologies, and accounted for test-to-test variability either by quantifying it (in the case of fabric filter particulate matter removal performance) or accounting for it qualitatively (in the case of the SRE/feed ranking methodology).

Comment: The commenter notes that if EPA believes that single performance test results do not accurately capture source's variability, the solution is to gather more data, not to avoid using a straight emissions methodology. EPA cannot use this as an excuse for basing floor levels on a chosen technology rather than the performance of the best performing sources.

Response: There is no obligation for EPA to gather more performance data, since the statute indicates that EPA is to base floor levels on performance of sources "for which the Administrator has emissions information." Section 112(d)(3)(A); *CKRC*, 255 F. 3d at 867 (upholding EPA's decision to use the compliance test data in its possession in establishing MACT standards). Indeed, the already-tight statutory deadlines for issuing MACT standards would be even less feasible if EPA took further time in data gathering. EPA notes further that because particulate matter continuous emission monitors are not widely used, even further data gathering would be limited to snapshot, single performance test results, still leaving the problem of estimating variability from a limited data set.[71] See also *Sierra Club* v. *EPA*, 167 F. 3d at 662 ("EPA typically has wide latitude in determining the extent of data-gathering necessary to solve a problem").

Thus, EPA has no choice but to assess best performers and their level of performance on the basis of limited amounts of data per source. As explained in the previous response to

[71] Performance tests take an average of 5–8 days to conduct, and cost approximately from $200,000—$500,000 per test. The commenter's off-hand suggestion appears to have ignored these realities.

comments, EPA has selected a methodology that reasonably do so.

EPA notes further that it has carefully examined those instances where there are multiple test conditions (usually compliance tests conducted at different times) for sources ranked as best performing. This analysis confirms EPA's engineering judgment that total variability is not fully encompassed in the single test condition results used to identify these sources as best performing, and that without taking this additional variability into account, best performing sources would be unable to achieve the floor standard reflecting their own performance in those single test conditions.[72]

2. Universal Variability Factor for Particulate Emissions Controlled with a Fabric Filter

Comment: One commenter states that, in calculating the universal variability factor (UVF) to account for total variability—test-to-test variability and within-test variability—for sources controlling particulate matter with a fabric filter, it appears that EPA considered the variability of sources that are not best performing sources. If so, EPA has contravened the law.

The commenter also states that EPA's attempt to use a variability factor derived from an analysis of variability of multiple sources is unlawful. If EPA considers variability at all, it must consider the relevant source's variability.

Response: We developed the particulate matter UVF for sources equipped with a fabric filter using data from best performing sources only.[73]

It is reasonable to aggregate particulate matter emissions data across source categories for all best performing sources equipped with a fabric filter because the relationship between standard deviation and emissions of particulate matter is not expected to be impacted by the source category type.[74] Rather, particulate emissions from fabric filters are a function of seepage (i.e., migration of particles through the filter cake) and leakage (i.e., particles leaking through pores, channels, or pinholes formed as the filter cake builds up). The effect of seepage and leakage on emissions variability should not vary across source categories.[75] Put another way, fabric filter particulate matter reduction is relatively independent of inlet loadings to the fabric filter. 69 FR 21233. This is confirmed by the fact that there are no operating parameters that can be readily changed to increase emissions from fabric filters, *id.*, so control efficiencies reflected in test conditions from different source types will still accurately reflect fabric filter control efficiency.

3. Test-to-Test Variability

Comment: Several commenters state that EPA seems to have ignored test-to-test variability resulting from changes that occur over time such as: normal and natural changes in a wide variety of factors related to process operation, fuels, raw materials, air pollution control equipment operation and design, and differences in emissions testing equipment, sampling crews, weather, analytical laboratories or laboratory technicians. All these sources of variation are expected in that they are typical and are not aberrations. In addition, there are unexpected sources of variability that occur in real-world operations, which also must be accommodated according to commenters.

Commenters state that using compliance test data and assessing within-test condition variability (i.e., run variance) do not fully account for test-to-test variability and thus understates total variability. Consequently, the average of the best performing sources may not be able to achieve the same emission level under a MACT performance test when attempting to operate under the same conditions as it did during the compliance test EPA used to establish the floor. Even though sources generally operated at the extreme high end of the range of normal operations during the compliance tests EPA uses to establish the standards, the average of the best performing sources would need to operate under those same compliance test conditions to establish the same operating envelope—the operating envelope needed to ensure the source can operate under the full range of normal emissions.

Response: We agree with commenters that we have not quantified test-to-test variability when establishing the floors for standards other than particulate matter where a best performing source uses a fabric filter. We are able to quantify only within-test variability (i.e., run-to-run variability) for the other floors, which is only one component of total variability. This is one reason we use the SRE/Feed approach wherever possible rather than a straight emissions approach to rank the best performing sources to calculate the floor—the SRE/Feed ranking approach derives floors that better estimate the levels of best performing sources' performance. See also discussion in Part Four, Section III.A, and the discussion below documenting that test-to-test variability can be substantial.

Comment: One commenter states that EPA should use the universal variability factor (UVF) that accounts for total variability for particulate matter controlled with a fabric filter to derive a correction factor to account for the missing test-to-test variability component of variability for semivolatile metals and low volatile metals. The commenter then suggests that the within-test variability for semivolatile and low volatile metals be adjusted upward by the correction factor to correct for the missing test-to-test variability component.

The commenter focused on cement kilns and compared the total variability imputed from the UVF for the three cement kiln facilities used to establish the UVF to the within-test variability (i.e., run variance) for each facility. The commenter determined that, on average for the three facilities, total variability was a factor of 4.2 higher than within-test variability. Because semivolatile and low volatile metals are also controlled with a fabric filter, the commenter suggested that the total variability of particulate matter could be used as an estimate of the total variability for semivolatile and low volatile metals. Thus, the commenter suggested that the within-test condition variability for semivolatile and low volatile metals be increased by a factor of 4.2 to account for total variability when calculating floors.

Response: As stated throughout this preamble, we believe that there is variability in addition to within-test condition (i.e., run-to-run) variability that we cannot quantify—that we refer to as test-to-test variability. We also do not believe this test-to-test variability is captured by compliance test operating conditions as discussed above, and thus establishing the floor using emissions data representing the extreme high end of the range of normal emissions does not account for test-to-test variability. We disagree, however, with the commenter's attempts to quantify the remaining test-to-test variability for floors other than particulate matter

[72] USEPA; "Technical Support Document for the HWC MACT Standards, Volume III: Selection of MACT Standards,", September 2005, Sections 16 and 17.

[73] USEPA, "Draft Technical Support Document for HWC MACT Standards, Volume III: Selection of MACT Standards,", March 2004, p. 5–4.

[74] In addition, emissions are not generally affected by particulate inlet loading.

[75] See USEPA, "Technical Support Document for the HWC MACT Standards, Volume III: Selection of MACT Standards," September 2005, Section 5.3.

where all best performing sources are equipped with fabric filters.

We generally agree with the commenter's approach for extracting the test-to-test component of variability using the UVF curve for particulate matter controlled with a fabric filter.[76] The commenter has documented that for cement kilns, test-to-test variability of particulate emissions controlled with a fabric filter is on average a factor of 4.2 higher than within-test variability.

We believe the commenter's suggestion to adopt this correction factor to semivolatile and low volatile metals is technically flawed and for several reasons would present statistical difficulties. First, total variability for semivolatile metals and low volatile metals controlled with a fabric filter can be different from the total variability of particulate matter controlled with a fabric filter because: (1) The test methods are different (i.e., Method 5 for particulate matter and Method 29 for metals) and thus sample extraction and analysis methods differ; (2) the factors that affect partitioning of particulate matter to combustion gas (i.e., entrainment) are different from the factors that affect semivolatile metal partitioning to the combustion gas (i.e., metal volatility); and (3) the volatility of semivolatile metals is affected by chlorine feedrates.

Second, adopting a variability factor applicable to fabric filters for use on electrostatic precipitators [77] is problematic because both test-to-test and within-test variability of these emission control devices can be vastly different. Factors that affect emissions variability for sources equipped with a fabric filter include: (1) Bag wear and tear due to thermal degradation and chemical attack; and (2) variability in flue gas flowrate. Factors that affect emissions variability for sources equipped with an electrostatic precipitator are different (see discussion in Section III.B above) and include: variations in particle loading and particle size distribution, erosion of collection plates, and variation in fly ash resistivity due to changes atmospheric moisture and in sulfur feedrate (e.g. different type of coal).

Finally, the approach raises several difficult statistical questions including: (1) What is the appropriate number of runs to use to identify the degrees of freedom and the t-statistic in the floor calculations (e.g., should we use the number of runs available for metals emissions for the source or the number of runs available for particulate matter emissions from which the correction factor is derived); and (2) should we use a generic correction factor for all source categories or calculate source category-specific or source-specific correction factors.

For these reasons, we believe the approach we use for quantifying baghouse particulate matter collection variability is not readily transferable to other types of control devices and other HAP. We therefore are not applying a quantified correction factor in the final rule but rather are using a MACT ranking methodology that qualitatively accounts for total emission variability, notably test-to-test variability.

B. SRE/Feed Methdology

1. Description of the Methodology

As proposed, we are using the System Removal Efficiency (SRE)/Feed approach to determine the pool of best performing sources for those HAP whose emissions can be controlled in part by controlling the hazardous waste feed of the HAP—that is, controlling the amount of HAP in the hazardous waste fed to the source. These are HAP metals and chlorine. Our basic approach is to determine the sources in our database with the lowest hazardous waste feedrate of the HAP in question (semi-volatile metals, low volatile metals, mercury, or chlorine), and the sources with the best system removal efficiency for the same HAP. The system removal efficiency is a measure of the percentage of HAP that is removed prior to being emitted relative to the amount fed to the unit from all inputs (hazardous waste, fossil fuels, raw materials, and any other input). The pool of best performing sources are those with the best combination of hazardous waste feedrate and system removal efficiency as determined by our ranking procedure, separate best performer pools being determined for each HAP in question (SVM, LVM, mercury, and chlorine), reflecting the variability inherent in each of these ranking factors (see A.2.a.(1) above). We then use the emission levels from these sources to calculate the emission level achieved by the average of the best performing sources, as also explained in the previous section. This is the MACT floor for the HAP from the source type. For new sources, we use the same methodology but select the emission level (adjusted statistically to account for quantifiable variability) of the source with the best combined ranking. A more detailed description of the methodology is found in Volume III of the Technical Support Document, section 7.3.

This methodology provides a reasonable estimate of the best performing sources and their level of performance for HAP susceptible to hazardous waste feed control. As required by section 112(d)(2), EPA has considered measures that reduce the volume of emissions through process changes, or that prevent pollutant release through capture at the stack, and assessed how these control measures are used in combination. Section 112(d)(2)(A), (C) and (E). Hazardous waste feed control is clearly a process change that reduces HAP emissions; air pollution control systems collect pollutants at the stack. These are the best systems and measures for controlling HAP emissions from hazardous waste combustors. 69 FR at 21226. In considering these factors, EPA has necessarily considered such factors as design of different air pollution control devices, waste composition, pollution control operator training and behavior, and use of pollution control devices and methodologies in combination. *CKRC*, 255 F. 3d at 864–65 (noting these as factors, in addition to a particular type of air pollution control device, that can influence pollution control performance); 69 FR at 21223 n. 47 (system removal efficiency measures all internal control mechanisms as well as back-end emission control device performance).

EPA also believes that this methodology reasonably estimates the best performing sources' level of performance by accounting for these sources' total variability, including their performance over time. The methodology quantifies run-to-run variability. See 69 FR at 21232–33. It does not quantify test-to-test variability because we are unable to do so for these pollutants. (See sections A. 2.a.(2) and 3 above.) Although all variability must be accounted for when calculating floors, the only definitive way to accurately quantify this test-to-test emissions variability is through evaluation of long-term continuous emissions monitoring data, which do not presently exist. We believe, however, that SRE/Feed methodology provides some margin for estimating this additional, non-quantifiable variability. This is illustrated in the technical support document (volume III section 17), which clearly shows that the straight emissions approach underestimates (indeed, fails to account

[76] We note, however, that an argument could be made for using a source or condition-specific correction factor rather than averaging the correction factors for all sources within a source category.

[77] We infer that the commenter suggests that we use this correction factor for semivolatile and low volatile metals controlled by both electrostatic precipitators and fabric filters since the majority of cement kilns are equipped with electrostatic precipitators.

for) lower emitting sources' long-term emissions variability. These lower emitting sources that would otherwise not meet the floor levels on individual days under the straight emission approach would be able (or otherwise are more capable) to do so under the SRE/feed approach.

EPA further believes that the SRE/Feed methodology appropriately accounts for design variability that exists across sources for categories, like those here, which consist of a diverse and heterogeneous mixture of sources. This is especially true of incinerators and boilers, for which there are smaller on-site units that are located at widely varying industrial sectors that essentially combust single, or multiple wastestreams that are specific to their industrial process, and off-site commercial units dealing with many different wastes of different origins and HAP metal and chlorine composition. EPA believes that these variations are best encompassed in the SRE/Feed approach, rather than with a subcategorization scheme that could result in anomalous floor levels because there are fewer sources in each source subcategory from which to assess relative performance.[78] See *Mossville*, 370 F. 3d at 1240 (upholding floor methodology involving reasonable estimation, rather than use of emissions data, when sources in the category have heterogeneous emission characteristics due to highly variable HAP concentrations in feedstocks).

Use of the SRE/Feed approach also avoids basing the floor standards on a combination of the lowest emitting low feeding sources and the lowest emitting high feeding sources. For example, the five lowest emitting incinerators for semivolatile metals that would comprise the MACT pool using a straight emissions methodology include three sources that are the first, second, and fourth lowest feeding sources among all the incinerators.[79] The other two best performing incinerators have the first and second best system removal efficiencies (and the highest two metal feedrates). It is noteworthy that the highest feed control level among these best performing sources is over three orders of magnitude higher than the feed control level of the lowest feeding best performing source.[80] Establishing limits dominated by both superior feed control sources and back-end controlled sources would result in floor levels that are not reflective of the range of emissions exhibited by either low feeding sources or high feeding sources and would more resemble new source standards for both of these different types of combustors. Such floors could lead to situations, for example, where commercial sources could find it impracticable to achieve the standards without reducing the overall scope of their operations (since the standard could operate as a direct constraint on the amount of hazardous waste that could be fed to the device, in effect depriving a combustion source of its raw material). Similarly, low feeding sources that cannot achieve this floor level may be required to add expensive back-end control equipment that would result in minimal emission reductions, likely forcing the smaller on-site source to cease hazardous waste treatment operations and to instead send the waste to a commercial treatment unit.

The inappropriateness of a straight emissions-based approach for feed controlled pollutants for commercial hazardous waste combustors is further highlighted by the fact that several commercial hazardous waste combustors that are achieving the design level of the particulate matter standard are not achieving the semivolatile and/or low volatile metals straight emissions based design level, and, in some instances, floor level.[81] This provides further evidence that low feeding sources are in fact biasing some of the straight emissions-based floors to the extent that even the sources with the most efficient back-end control devices would be incapable of achieving the emission standards calculated on a straight emission basis.

These results are inconsistent with the intent of the section 112 (d) (see 2 Legislative History at 3352 (House Report) stating that MACT is not intended to drive sources out of business). Standards that could force commercial sources to reduce the overall scope of their operations are also inconsistent with requirements and objectives of the Resource Conservation and Recovery Act to require treatment of hazardous wastes before the wastes can be land disposed, and to encourage hazardous waste treatment. RCRA sections 3004 (d), (e), (g) and 1003 (a) (6); see also section 112 (n) (7) of the CAA, stating that section 112 (d) MACT standards are to be consistent with RCRA subtitle C emission standards for the same sources to the maximum extent practicable (consistent with the requirements of section 112 (d)); moreover, EPA doubts that a standard which precludes effective treatment mandated by a sister environmental statute must be viewed as a type of best performance under section 112 (d). The SRE/Feed methodology avoids this result by always considering hazardous waste feed control in combination with system removal efficiency and according equal weight to both means of control in the ranking process.

It is also important to emphasize what the SRE/Feed methodology does not evaluate: Feed control of HAP in fossil fuel or raw material inputs to these devices. Emission reduction of these HAP are controllable by back-end pollution control devices which remove a given percentage of pollutants irrespective of their origin and is assured by the system removal efficiency portion of the methodology, as well as through the particulate matter standard (see section IV.A below). Feed control of these inputs is not a feasible means of control, however. HAP content in raw materials and fossil fuel can be highly variable, and so cannot even be replicated by a single source. Raw material and fossil fuel sources are also normally proprietary, so other sources would not have access to raw material and fossil fuel available (in its performance test) to a source with low HAP fossil fuel and raw material inputs. Such sources would thus be unable to duplicate these results. Moreover, there are no commercial-scale pretreatment processes available for removing or reducing HAP content in raw materials or fossil fuels to these units. See technical support document volume III section 17.5 and 25; see also 69 FR at 21224 and n. 48.

2. Why Aren't the Lowest Emitters the Best Performers?

Some commenters nonetheless argue that best performing sources can only mean sources with the lowest HAP

[78] At proposal, we conducted a technical analysis to determine potential subcategorization options. We then conducted an analysis to determine if these different types of sources exhibited statistically different emissions. Although EPA in the end determined that these source categories should not be subcategorized further, this decision was based in part because the SRE/Feed methodology better accounts for the range of emissions from the best performing sources for these diverse combustion types. See USEPA, "Technical Support Document for the HWC MACT Standards, Volume III: Selection of MACT Standards," September 2005, Section 4, for an explanation of the subcategorization assessment, which includes examples of anomalous floor results for certain subcategorization approaches.

[79] See USEPA, "Technical Support Document for the HWC MACT Standards, Volume III: Selection of MACT Standards," September 2005, Appendix C, Table "E_INC_SVMCT" and, to determine relative feed control and SRE rankings for these sources, Appendix E Table "SF_INC_SVMCT".

[80] Source 340 had a semivolatile metal feed control MTEC of 892 µg/dscm, whereas source 327 had a semivolatile metal feed control MTEC of 3,080,571 µg/dscm.

[81] See USEPA, "Technical Support Document for the HWC MACT Standards, Volume III: Selection of MACT Standards," September 2005, Section 17.4

emissions, and that the SRE/Feed methodology is therefore flawed because it does not invariably select lowest emitters as best performers.[82] The statute does not compel this result. There is no language stating that lowest emitting sources are by definition the best performers. The floor for existing sources is to be based on the average emission limitation achieved by the "best performing" 12 per cent of sources. Section 112(d)(3)(A). This language does not specify how "best performing" is to be determined: by means of emission level, emission control efficiency, measured over what period of time, etc. See *Sierra Club* v. *EPA*, 167 F. 3d at 661 (language of floor requirement for existing sources "on its own says nothing about how the performance of the best units is to be calculated"). Put another way, this language does not answer the question of which source is the better performing: one that emits 100 units of HAP but also feeds 100 units of that HAP, or one that emits 101 units of the HAP but feeds 10,000 units. See 69 FR at 21223. Moreover, new source floors are to be based on the performance of the "best controlled" similar source achieved in practice. Section 112(d)(3). "Best controlled" can naturally be read to refer to some means of control such as system removal efficiency as well as to emission level.

Use of a straight emissions approach to identify floor levels can lead to arbitrary results. Most important, as explained above, it leads to standards which cannot be achieved consistently even by the best performing sources because operating variability is not accounted for. This is shown in section 17 of volume III of the technical support document. These analyses show that (a) emissions from these sources do in fact vary from test-to-test, and that no two snapshot emission test results are identical; (b) our statistical approach that quantifies within test, run-to-run variability underestimates the best performing sources' long term, test-to-test variability;[83] (c) best performing sources under the straight emissions approach advocated by the commenter (i.e. the lowest emitting sources) had other test conditions that did not achieve straight emission floor levels; (d) best performing sources under the straight emissions approach are projected, based on two separate analyses using reasonable assumptions, not to achieve the straight emissions floor standard based on these sources' demonstrated variations in system removal efficiencies over time (i.e., from test-to-test); and (e) SRE/feed methodology yields floor levels (i.e. the floor standards in the rule) that better estimate the emission levels reflecting the performance over time of the best performing sources. See *Mossville*, 370 F. 3d at 1242 (floor standard is reasonable because it accommodated best performing source's highest level of performance (i.e. its total variability), even though the level of the standard was higher than any individual measurement from that source).

As noted earlier, the straight emissions methodology can also limit operation of commercial units because the standard reflects a level of hazardous waste feed control which could force commercial units to burn less hazardous waste because such standards more resemble new source standards. The straight emissions methodology also arbitrarily reflects HAP levels in raw materials and fossil fuels, an infeasible means of control for any source.

Another arbitrary, and indeed impermissible, result of the straight emissions methodology is that in some instances (noted in responses below) the methodology results in standards which would force sources identified as best performing to install upgraded air pollution control equipment. This result undermines section 112 (d) (2) of the statute, by imposing what amounts to a beyond the floor standard without consideration of the beyond the floor factors: the cost of achieving those reductions, as well as energy and nonair environmental impacts.

Comment: The commenter states that because MACT floors must reflect the "actual performance" of the relevant best performing hazardous waste combusters, this means that the lowest emitters must be the best performers. The commenter cites *CKRC* v. *EPA*, 255 F. 3d at 862 and other cases in support.

Response: As explained in the introduction above, the statute does not specify that lowest emitters are invariably best performers. Nor does the caselaw cited by the commenter support this position. The D.C. Circuit has held repeatedly that EPA may determine which sources are best performing and may "reasonably estimate" the performance of the top 12 percent of these sources by means other than use of actual data. *Mossville*, 370 F. 3d at 1240–41 (collecting cases). In *Mossville*, sources had varying levels of vinyl chloride emissions due to varying concentrations of vinyl chloride in their feedstock. Individual measurements consequently did not adequately represent these sources' performance over time. Not-to-exceed permit limits thus reasonably estimated sources' performance, corroboration being that individual sources with the lowest long-term average performance occasionally came close to exceeding those permit limits. *Id.* at 1241–42. The facts are similar here, since our examination of best performing sources with multiple test conditions likewise shows instances where these sources would be unable to meet floors established based solely on lowest emissions (including their own). As here, EPA was not compelled to base the floor levels on the lowest measured emission levels.

Comment: The same commenter maintains that it is clear from the caselaw that MACT floors must reflect the relevant best performing sources' "actual performance", and that this must refer to the emissions level it achieves.

Response: As just stated, the D.C. Circuit has repeatedly stated that EPA may make reasonable estimates of sources' performance in assessing both which sources are best performing and the level of their performance. The court has further indicated that EPA is to account for variability in assessing sources' performance for purposes of establishing floors, and this assessment may require that EPA make reasonable estimates of performance of best performing sources. *CKRC*, 255 F. 3d at 865–66; *Mossville*, 370 F. 3d at 1241–42. See discussion in A.1.a above.

Comment: The commenter generally maintains that EPA's floor approaches consider only the performance of back-end pollution control technology and so fail to capture other means of HAP emission control that otherwise would be captured if EPA were to assess performance based on the emission levels each source achieved.

Response: EPA agrees that factors other than end-of-stack pollution control can affect metal HAP and chlorine emissions. This is why EPA assesses performance for these HAP by considering combinations of system removal efficiency (which measures every element in a control system resulting in HAP reduction, not limited to efficiency of a control device), and hazardous waste HAP feed control. Standards for dioxins and other organic HAP (which have no hazardous waste feed control component) likewise assess every element of control.

[82] In fact, many of the sources identified as best performing under the SRE/Feed methodology are also the lowest emitting, although this is not invariably the case.

[83] Best performing sources pursuant to the straight emissions methodology are projected to be unable to achieve the levl of their of their performance test emissions even after they are adjusted upward to account for run-to-run variability.

EPA also accounts for the variability of HAP levels in the (essential) use of raw materials and fossil fuels by assessing performance of back-end control but not evaluating fuel/raw material substitution, which, as discussed later in the response to comments section, are infeasible means of control. *Mossville*, 370 F. 3d at 1241–42, is instructive on this point. The court held that the constant change in raw materials justified EPA's use of a regulatory limit to estimate a floor level. The reasonableness of this level was confirmed by showing that the highest individual data point of a best performing source was nearly at the level of the regulatory limit. Under the commenter's approach, the court would have had no choice but to hold that the level the source achieved in a single test result using 'clean' raw materials—i.e. the 'level achieved' in the commenter's language—dictated the floor level.

See part four, section III.C for EPA's response to this comment as it relates to the methodologies for the particulate matter standard and total chlorine standard for hydrochloric acid production furnaces.

Comment: The commenter notes that the SRE/Feed methodology does not account for all HAP emissions, failing to account for metal and chlorine feedrates in raw materials and fossil fuels.

Response: The methodology does not assess the effect of feed "control" of HAP levels in raw materials or fossil fuels which may be inputs to the combustion units. This is because such control may not be replicable by an individual source, or duplicable by any other source. See 69 FR at 21224 and n. 48; *Sierra Club* v. *EPA*, 353 F. 3d 976, 988 ("substitution of cleaner ore stocks was not * * * a feasible basis on which to set emission standards. Metallic impurity levels are variable and unpredictable both from mine to mine and within specific ore deposits, thereby precluding ore-switching as a predictable and consistent control strategy").[84] EPA's methodology does account for HAP control of all inputs by assessing system removal efficiency, which measures reductions of HAPs in all inputs (including fossil fuel and raw materials) to a hazardous waste combustion unit. Further, nonmercury metal HAP emissions attributable to raw materials and fossil fuels are effectively controlled with the particulate matter standard, a standard that is based on the sources with best back-end control devices. The only element which is not controlled is what cannot be: HAP levels in feeds for which fuel or raw material switching is simply not an available option.

Comment: The commenter further maintains, however, that the means by which sources may be achieving levels of performance are legally irrelevant (citing *National Lime Ass'n* v. *EPA*, 233 F. 3d 625 , 634 and 640 (D.C. Cir. 2000)). The fact that sources with "cleaner" raw material and fossil fuel inputs may not intend to have resulting lower HAP emissions is therefore without legal bearing.

Response: The issue here is not one of intent. The Court, in *National Lime*, rejected the argument that sources' lack of intent to control a HAP did not preclude EPA from establishing a section 112(d) standard for that HAP. See 233 F. 3d at 640, rejecting the argument that HAP metal control achieved by use of back-end control devices (baghouses) could not be assessed by EPA because the sources used the back-end control devices to control emissions of particulate matter. The case did not consider the facts present here, where the issue is not a source's intent, but rather a means of control which involves happenstance (composition of HAP in raw materials and fossil fuel used the day the test was conducted) and so is neither replicable nor duplicable.

National Lime also held that EPA must establish a section 112(d) emission standard for every HAP emitted by a major source. 233 F. 3d at 634. EPA is establishing emission standards for all HAP emitted by these sources. In establishing these standards, EPA is not evaluating emission reductions attributable to the type of fossil fuel and raw material used in the performance tests, because this is not a "feasible basis on which to set emission standards." *Sierra Club*, 353 F. 3d at 988.

EPA thus does not agree with this comment because the issue is not a source's intent but rather whether or not to assess emission reductions from individual test results which reflect an infeasible means of control.

Comment: The commenter maintains, however, that even if individual sources (including those in the pool of best performing sources) cannot reduce HAP concentrations in raw materials and fossil fuels, they may achieve the same reductions by adding back-end pollution control. Nothing in section 112(d)(3) says that sources have to use the means of achieving a level of performance that other best performing sources used.

Response: The thrust of this comment is essentially to impermissibly bypass the beyond-the-floor factors set out in section 112(d)(2) under the guise of adopting a floor standard. Suppose that EPA were to adopt a floor standard dominated by emission levels reflecting HAP concentrations present in a few sources' raw materials and fossil fuels during their test conditions. Suppose further that some sources have to upgrade their back-end control equipment to operate at efficiencies better than the average level demonstrated by the best performing sources, because test results based on fossil fuel and raw material levels are neither replicable nor duplicable. In this situation, EPA believes that it would have improperly adopted a beyond-the-floor standard because EPA would have failed to consider the beyond-the-floor factors (cost, energy, and nonair environmental impacts) set out in section 112(d)(2).[85]

Comment: EPA has not substantiated its claim that sources cannot switch fossil fuels or raw materials.

Response: At proposal we evaluated fuel switching and raw material substitution as beyond-the-floor technologies for cement kilns and lightweight aggregate kilns and stated these technologies would not be cost effective.[86] We also discussed why fuel switching is not an appropriate floor control technology for solid fuel-fired boilers. 69 FR at 21273. Upon further evaluation, we again conclude that fuel switching and raw material substitution are not floor control technologies and are not cost effective beyond-the-floor technologies for cement kilns, lightweight aggregate kilns, and solid fuel-fired boilers.[87]

Comment: EPA has failed to document the basis for its SRE ranking.

[84] Although this language arose in the context of a potential beyond-the-floor standard, EPA believes that the principle stated is generally applicable. MACT standards, after all, are technology-based, and if there is no technology (i.e. no available means) to achieve a standard—i.e. for a source to achieve a standard whenever it is tested (as the rules require)—then the standard is not an achieveable one.

[85] Analysis of the levels of HAP in raw matrial and nonhazardous waste fuels suggests that this is a realistic outcome. Our analysis shows that emissions attributable to raw material and fossil fuel can be significant relative to the level of the straight emissions-based floor design level and floor (the methodology advocated by the commenter), and therefore could inappropriately impact a source's ability to comply with such a floor standard. See USEPA, "Technical Support Document for the HWC MACT Standards, Volume III: Selection of MACT Standards," September 2005, Section 17.6.

[86] See, for example, 69 FR at 21252, where we discuss the use of fuel-switching or raw material substitution as a possible beyond-the-floor control for mercury at cement kilns.

[87] See USEPA, "Technical Support Document for the HWC MACT Standards, Volume III: Selection of MACT Standards, September 2005, Sections 11 and 25, for further discussion.

Specifically, EPA has not stated how it measured sources' SREs, or how it knows those rankings are accurate.

Response: System removal efficiency is a parameter that is included in our database that is calculated by the following formula:

$$SRE = 100 \times \frac{[(\text{total HAP mass feedrate}) - (\text{stack gas HAP mass emission rate})]}{\text{total HAP mass feedrate}}$$

The HAP feedrate and emission data are components of the database that were extracted from emission test reports for each source. We use system removal efficiency for each relevant pollutant or pollutant group (e.g., semivolatile metals, low volatile metals, mercury, total chlorine) whenever the data allows us to calculate a reliable system removal efficiency. For example, we generally do not use system removal efficiencies that are based on normal emissions data because of the concern that normal feed data are too sensitive to sampling and measurement error. See 69 FR at 21224.[88]

The system removal efficiencies used in our ranking process are reliable and accurate because the feed and emissions data originate from compliance tests that demonstrate compliance with existing emission standards (primarily RCRA requirements). As such, the data are considered to have excellent accuracy and quality. RCRA trial burn and certification of compliance reports are typically reviewed in detail by the permitting authority. The compliance tests and test reports generally contain the use of various quality assurance procedures, including laboratory, method, and field blanks, spikes, and surrogate samples, all of which are designed to minimize sampling and analytical inaccuracies. EPA also noticed the data base for this rule for multiple rounds of comment and has made numerous changes in response to comment to assure accuracy of the underlying data. Thus, EPA concludes the calculated system removal efficiencies used in the ranking process are both reliable and accurate.

Comment: EPA's approach with regard to use of stack data is internally contradictory. EPA uses stack data in establishing floors, but does not use stack data to determine which performers are best. EPA has failed to explain this contradiction.

Response: Emission levels are used to calculate system removal efficiencies in order to assess each source's relative back-end control efficiency. Also, as explained in the introduction to this comment response section, the SRE/Feed methodology uses the stack emission levels of the sources using the best combinations of hazardous waste feed control and system-wide air pollution control (expressed as HAP percent removal over the entire system) to calculate the floors. The data are adjusted statistically to account for quantifiable forms of variability (run-to-run variability). This methodology reasonably selects best performing sources (for HAP amenable to these means of control), and reasonably estimates these sources' performance over time. As further stated in section B.2 above, using a straight emissions approach to identify best performers and their level of performance can lead to standards for these HAP that do not fully account for variability (including variability resulting from varying and/or uncontrollable amounts of HAP in raw materials and fossil fuels) and could force installation of *de facto* beyond-the-floor controls without consideration of the section 112(d)(2) beyond-the-floor factors.

EPA thus does not see the contradiction expressed by the commenter. Use of the straight emissions approach as advocated by the commenter would lead to standards that do not reasonably estimate sources' performance and which could not be achieved even by the best performers with individual test conditions below the average of the 12 percent of best performing sources. These problems would be compounded many-fold if the data were not normalized and adjusted to at least account for quantifiable variability, steps the commenter also opposes. EPA's use of emissions data (suitably adjusted) after identifying best performers through the ranking methodology avoids these problems and reasonably estimates best performers' level of performance.

Comment: The commenter rejects EPA's finding (69 FR at 21226) that individual test results in the data base do not fully express the best performing sources' performance. The commenter gives a number of reasons for its criticisms, which we answer in the following sequence of comments listed a though f.

a. *Comment:* The commenter states that EPA claims emission levels do not fully reflect variability in part because they are sometimes based on tests where the source was feeding low levels of HAP during the test. The commenter claims this is inconsistent with the fact that EPA preferentially uses worst-case emissions obtained from tests where the sources spiked their feedstreams with metals, and that the mere possibility that these emissions do not reflect test data from conditions where variability was not maximized does not mean those data fail to represent a source's actual performance. The commenter also states that "EPA's apparent suggestion that the best performing sources could not replicate the average performance of the sources with the lowest emissions is unsubstantiated and unexplained. Assuming that EPA accurately assesses a source's actual performance, the source can replicate that performance."

Response: HAPs in raw materials and fossil fuels contribute to a source's emissions. EPA has concerns that a straight emissions approach to setting floors may not be replicable by the best performing sources nor duplicable by other non-best performing sources because of varying concentration levels of HAP in raw material and nonhazardous waste fuels. The best performing sources operated under compliance test conditions as the commenter suggests. However, raw material and nonhazardous fuel HAP concentrations for the best performing sources will change over time, perhaps due to a different source of fuel or raw material quarry location, which could affect their ability to achieve the floor level that was based on emissions obtained while processing different fossil fuel or raw materials. EPA takes sharp issue with the commenter's statement that a single performance test result is automatically replicable so long as it is measured properly in the first instance. This statement is incorrect even disregarding HAP contributions in raw materials and fossil fuels since, as noted previously in section A.2.e, there are many other sources of variability

[88] See USEPA, "Technical Support Document for the HWC MACT Standards, Volume II: Database," September 2005, Section 2, for further discussion on system removal efficiencies, which includes sample calculations and references to the database that contain the calculated system removal efficiencies for each source and each HAP or HAP group.

which will influence sources' performance over time (i.e., in subsequent performance tests).

A straight emissions approach for establishing semivolatile and low volatile metal floors may result in instances where the best performing sources would not be capable of achieving the standards if their raw material and nonhazardous waste fuel HAP levels change over time. For each cement kiln and lightweight aggregate kiln, we estimated the emissions attributable to these raw materials and fossil fuels assuming each source was operating with hazardous waste HAP feed and back-end control levels equivalent to the average of the best performing sources (the difference in emissions across sources only being the result of the differing HAP levels in the nonhazardous waste feeds). The analysis shows that emissions attributable to these nonhazarous waste feedstreams (raw materials and fossil fuels) varies across sources, and can be significant relative to the level of the straight emissions-based floor design level and floor, and therefore could inappropriately impact a source's ability to comply with the floor standard.[89]

b. *Comment:* The commenter states that EPA must consider contributions to emissions from raw materials and fossil fuels, that it is irrelevant if sources from outside the pool of best performing sources can duplicate emission levels reflecting "cleaner" raw materials and fossil fuels used by the best performing sources, and that sources unable to obtain such "cleaner" inputs may always upgrade other parts of their systems to achieve that level of performance.

Response: As previously discussed, EPA's methodology does account for HAP control of all inputs by assessing system removal efficiency, which measures reductions of HAPs from all inputs. Further, nonmercury metal HAP emissions attributable to raw materials and fossil fuels are effectively controlled with the particulate matter standard, a standard that is based on the sources with lowest emissions from best back-end control devices. We are not basing any standards on performance of sources not ranked as among the best performing.

c. *Comment:* The commenter disputes EPA's conclusions that failure of sources to meet all of the standards based on a straight emissions methodology at once shows that the methodology is flawed. The standards are not mutually dependent, so the fact that they are not achieved simultaneously is irrelevant. There is no reason a best performer for one HAP should be a best performer for other HAP.

Response: EPA agrees with this comment. On reflection, EPA believes that because all our standards are not technically interdependent (i.e., implementation of one emission control technology does not prevent the source from implementing another control technology), the fact that sources are not achieving all the standards simultaneously does not indicate a flaw in a straight emissions approach. See *Chemical Manufacturers Ass'n*, 870 F. 2d at 239 (best performing sources can be determined on a pollutant-by-pollutant basis so that different plants can be best performers for different pollutants).

d. *Comment:* Several commenters took the opposite position that EPA must assure that all existing source standards must be achievable by at least 6 percent of the sources, and that all new source standards must be achievable by at least one existing source.

Response: As discussed above, we are not obligated to establish a suite of floors that are simultaneously achievable by at least six percent of the sources because the standards are not technically interdependent. Nonetheless, the SRE/Feed methodology does result in existing floor levels (when combined with the other floor levels for sources in the source category) that are simultaneously achievable by at least six percent of the sources (or, for source categories that have fewer than 30 sources, by at least two or three sources).[90] However, for the new source standards, three of the source categories do not include any sources that are simultaneously achieving all the standards (incinerators, cement kilns, and lightweight aggregate kilns). Again, similar to existing sources, EPA is not obligated to establish a suite of new source floors that are simultaneously achievable by at least one existing source because these standards are not technically interdependent. We conclude that a new source can be designed (from a back-end control perspective) to achieve all the new source standards.[91]

e. *Comment:* The commenter criticizes EPA's discussion at 69 FR 21227–228 indicating that both hazardous waste feed control and back-end pollution control are superior means of HAP emission control and treatment standards should be structured to allow either method to be the dominant control mechanism.

Response: EPA is not relying on this part of the proposed preamble discussion as justification for the final rule, with the one exception noted in the response to the following comment.

f. *Comment:* Considerations of proper waste disposal policy are not relevant to MACT floor determinations. In any case, the possibility that some commercial waste combustors may upgrade their back-end pollution control systems to meet standards reflecting low hazardous waste HAP feedrates, or divert wastes to better-controlled units, is positive, not negative.

Response: As discussed in section B.1 above, there are instances where standards derived by using a straight emissions approach are based on a combination of lowest emitting low feeding sources and lowest emitting higher feeding sources. Resulting floor standards would thus reflect these low hazardous waste feedrates and could put some well-controlled commercial incinerators in the untenable situation of having to reduce the amount of hazardous waste that is treated at their source. Our database verifies that such an outcome is in fact realistic.[92]

This type of standard would operate as a direct constraint on the amount of hazardous waste that could be fed to the device, in effect depriving a combustion source of its raw material. In this instance, hazardous wastes could not be readily diverted to other units because the low feeding hazardous waste sources tend not to be commercial units. In these circumstances, there would be a significant adverse nonair environmental impact. Hazardous waste is required to be treated by Best Demonstrated Available Technology (BDAT) before it can be land disposed. RCRA sections 3004 (d), (e), (g), and (m); *Hazardous Waste Treatment Council* v. *EPA*, 866 F. 2d 355, 361 (D.C.Cir. 1990) (upholding Best Demonstrated Available Technology treatment requirement). Most treatment standards for organic pollutants in hazardous waste can only be achieved by combustion. Leaving some hazardous wastes without a

[89] See USEPA, "Final Technical Support Document for the HWC MACT Standards, Volume III: Selection of MACT Standards," September 2005, Section 17.6.

[90] These achievability analyses did not account for the additional test-to-test variability that we cannot quantify.

[91] See USEPA, "Technical Support Document for the HWC MACT Standards, Volume V: Emission Estimates and Engineering Costs," September 2005, Section 4.2.3 for a discussion that explains how such a new source could be designed to achieve the new source standards.

[92] See USEPA, "Technical Support Document for the HWC MACT Standards, Volume III: Selection of MACT Standards", September 2005, Section 17.4.

treatment option is in derogation of these statutory requirements and goals, and calls into question whether a treatment standard that has significant adverse nonair environmental impacts must be viewed as best performing. See *Portland Cement Ass'n* v. *Ruckelshaus, 486 F. 2d 375 , 386 (D.C. Cir. 1973); Essex Chemical Co.* v. *EPAEPA*, 486 F. 2d 427, 439 (D.C. Cir. 1973). The commenter's statement that waste disposal policy is not relevant to the MACT standard-setting process is not completely correct, since section 112 (n) (7) of the Clean Air Act directs some accommodation between MACT and RCRA standards for sources combusting hazardous waste. Part of this accommodation is using a methodology to evaluate best performing sources that evaluates as best performers those using the best combination of hazardous waste feed control (among other things, an existing control measure under RCRA rules) and system-wide removal.

We assessed whether we could address this issue by subcategorizing commercial incinerators and on-site incinerators. Applying the straight emission approach to such a subcategorization scheme, however, yields anomalous results due to the scarcity of available and complete compliance test data from commercial incinerators. Calculated floor levels for semivolatile metals and low volatile metals for the commercial incinerator subcategory equate to 2,023 and 111 μg/dscm, respectively (both higher than the current interim standards).[93] We conclude that the SRE/Feed methodology better addresses this issue because it yields floor levels that better represent the performance of the best performing commercial incinerators and onsite incinerators alike by applying equal weights to hazardous waste feed control and back-end control in the ranking process.

EPA notes, however, that its choice of the SRE/Feed methodology is justified independent of considerations of adverse impact on hazardous waste treatment and disposal.

Comment: The commenter reiterates its comments with respect to floor levels for new sources.

Response: EPA's previous responses to comments apply to both new and existing source standards.

Comment: Two commenters recommend that EPA define the single best performing source as that source with the lowest aggregated SRE/Feed aggregated score (as proposed), as opposed to the source with the lowest emissions among the best performing existing sources (an approach on which we requested comment).

Response: We agree with the commenters because this is consistent with our methodology for defining best performers for existing sources and assessing their level of performance. We note, however, that with respect to the new source standards, we encountered two instances where the SRE/Feed methodology identified multiple sources with identical single best aggregated scores, resulting in a tie for the best performing source. This occurred for the mercury and low volatile metal new source standards for incinerators. In these instances, EPA applied a tie breaking procedure that resulted in selecting as the single best performing source as that source (of the tied sources) with the lowest emissions. We believe this is a reasonable interpretation of section112(d)(3), which states the new source standard shall not be less stringent than the emission control that is achieved in practice by the best controlled similar *source* ("source" being singular, not plural). Moreover, we believe use of the emission level as the tie-breaking criteria is reasonable, not only because it is a measure of control, but because we have already fully accounted for hazardous waste feedrate control and system removal efficiency in the ranking methodology. To choose either of these factors to break the tie would give that factor disproportionate weight.

C. Air Pollution Control Technology Methodologies for the Particulate Matter Standard and for the Total Chlorine Standard for Hydrochloric Acid Production Furnaces

At proposal, EPA used what we termed "air pollution control technology" methodologies to estimate floor levels for particulate matter from all source categories as a surrogate for non-mercury HAP metals, and for total chlorine from hydrochloric acid furnace production furnaces. 69 FR at 21225–226. Under this approach, we do not estimate emission reductions attributable to feed control, but instead assess the performance of back-end control technologies.[94] We are adopting the same methodologies for these HAP in the final rule. Because the details of the approaches differ for particulate matter and for total chlorine, we discuss the approaches separately below.

1. Air Pollution Control Device Methodology for Particulate Matter

Our approach to establishing floor standards for particulate matter raises three major issues.

The first issue is whether particulate matter is an appropriate surrogate for non-enumerated HAP metals from all inputs, and for all non-mercury HAP metals in raw material and fossil fuel inputs. This issue is discussed at section IV.A of this part, where we conclude that particulate matter is indeed a reasonable surrogate for these metal HAP.

The second issue is why EPA is not evaluating some type of feed control for the particulate matter floor. There are two potential types of feed control at issue: hazardous waste feed control of nonenumerated metals, and feed control of non-mercury HAP metals in raw material and fossil fuel inputs. With respect to feed control of non-enumerated metals in hazardous waste, as discussed in more detail in section IV.A of this part, we lack sufficient reliable data on non-enumerated metals to assess their feedrates in hazardous waste. In addition, there are significant questions about whether feedrates of the non-enumerated metals can be optimized along with SVM and LVM feedrates. We also have explained elsewhere why control of hazardous waste ash feedrate would be technically inappropriate, since it would not properly assess feed control of nonenumerated metals in hazardous waste. See also 69 FR at 21225.

We have also explained why we are not evaluating control of feedrates of HAP metals in raw materials and fossil fuels to hazardous waste combusters: it is an infeasible means of control. See section B of this part. We consequently are not evaluating raw material and fossil fuel ash feed control in determining the level of the various floors for particulate matter.

a. *The methodology.* The final issue is the means by which EPA is evaluating back-end control. Essentially, after determining (as just explained) that back-end control is the means of controlling non-mercury metal HAP and that particulate matter is a proper surrogate for these metals, EPA is using its engineering judgment to determine what the best type of air pollution control device (i.e., back-end control) is to control particulate matter (and, of course, the contained HAP metals). We then ascertain the level of performance by taking the average of the requisite number of sources (either 12 % or five,

[93] See USEPA, "Technical Support Document for the HWC MACT Standards, Volume III: Selection of MACT Standards", September 2005, Section 4. and Appendix C, Table "E–INC–SVM–CT–COM" and Table "E–INC–LVM–CT-COM"

[94] See generally USEPA, "Technical Support Document for the HWC MACT Standards, Volume III: Selection of MACT Standards", September 2005, Section 7.4 and 7.5.

depending on the size of the source category) equipped with the best back-end control with the lowest emissions.[95] These floor standards are therefore essentially established using a straight emissions methodology. We have determined that baghouses (also termed fabric filters) are generally the best air pollution control technology for control of particulate matter, and that electrostatic precipitators are the next best.

b. *Why not select the lowest emitters?* Although sources with baghouses tended to have the lowest emission levels for particulate matter, this was not invariably the case. There are certain instances when sources controlled with electrostatic precipitators (or, in one instance, a venturi scrubber) had lower emissions in individual test conditions than sources we identified as best performing which were equipped with baghouses.[96] Under the commenter's approach, we must always use these lowest emitting sources as the best performers.

We again disagree. We do not know if these sources equipped with control devices other than baghouses with lower emissions in single test conditions would actually have lower emissions over time than sources equipped with baghouses because we cannot assess their uncontrollable emissions variability over time. Our data suggests that they likely are not better performing sources. We further conclude that our statistical procedures that account for these sources' within test, run-to-run emissions variability underestimates these sources long-term emissions variability. This is not the case for sources equipped with baghouses, where we have completely assessed, quantified, and accounted for long-term, test-to-test emissions variability through application of the universal variability factor.[97] The sources equipped with control devices other than baghouses with lower snapshot emissions data could therefore have low emissions in part because they were operating at the low end of the "uncontrollable" emissions variability profile for that particular snapshot in time. The basis for these conclusions, all of which are supported by our data, are found in section 16 of volume III of the technical support document.

We therefore conclude sources equipped with baghouses are the best performers for particulate matter control not only based on engineering judgment, but because we are able to reliably quantify their likely performance over time. The straight emissions methodology ignores the presence of long-term emissions variability from sources not equipped with baghouses, and assumes without basis that these sources are always better performing sources in instances where they achieved lower snapshot emissions relative to the emissions from baghouses, emissions that have notably already been adjusted to account for long-term emissions variability.

A straight emissions approach also results in inappropriate floor levels for particulate matter because it improperly reflects/includes low ash feed when identifying best performing sources for particulate matter. 69 FR at 21228. For example, the MACT pool of best performing liquid fuel boilers for particulate matter under the straight emissions approach includes eight sources, only one of which is equipped with a back-end control device. These sources have low particulate matter emissions solely because they feed low levels of ash. The average ash inlet loadings for these sources are well over two orders of magnitude lower than the average ash inlet loading for the best performing sources that we identify with the Air Pollution Control Technology approach. (Of course, since ash loadings are not a proper surrogate for HAP metals, these sources' emissions are lowest for particulate matter but not necessarily for HAP metals.) The straight emissions approach would yield a particulate matter floor level of 0.0025 gr/dscf (with a corresponding design level of 0.0015 gr/dscf). There is not one liquid fuel boiler that is equipped with a back-end control that achieved this floor level, much less the design level. The best performing source under the air pollution control technology approach, which is equipped with both a fabric filter and HEPA filter, did not even make the pool of best performing sources for the straight emissions approach. Yet this unit has an excellent ash removal efficiency of 99.8% and the lower emitting devices' removal efficiencies are, for the most part, 0% because they do not have any back-end controls. EPA believes that it is arbitrary to say that these essentially uncontrolled devices must be regarded as "best performing" for purposes of section 112(d)(3). We therefore conclude that a straight emissions floor would not be achievable for any source feeding appreciable levels of ash, even if they all were to upgrade with baghouses, or baghouses in combination with HEPA filters, and that a rote selection of lowest emitters as best performers can lead to the nonsensical result of uncontrolled units being classified as best performers.

Comment: Commenter claims end-of-stack control technology is not the only factor affecting emissions of particulate matter, stating that EPA admits that particulate matter emission levels are affected by the feedrate of ash. Accordingly, the performance of a source's end-of-stack control technology is not a reasonable estimate of that source's total performance.

Response: The particulate matter standard serves as a surrogate control for the non-enumerated metals in the hazardous waste streams (for all source categories), and all nonmercury metal HAP in the nonhazardous waste process streams (essentially, raw materials and fossil fuels) for cement kilns, lightweight aggregate kilns, and liquid fuel boilers. The commenter suggests that the APCD approach inappropriately ignores HAP feed control in the assessment of best performing sources. We conclude that it would not be appropriate to use a methodology that directly assesses feed control, such as the SRE/Feed methodology, to determine particulate matter floors. First, direct assessment of total ash feed control would inappropriately assess and seek to control (even though variability of raw material and fossil fuel inputs are uncontrollable) raw material and fossil fuel HAP input, as well as raw material and fossil fuel input. Controlling raw material and fossil fuel HAP input is infeasible, as previously discussed. It also inappropriately limits theses sources' feedstocks that are necessary for their associated production process.

Second, we do not believe that developing a floor standard based on hazardous waste feed control of nonenumerated metals (as opposed to feed control of these metals in raw material and fossil fuels) is appropriate or feasible. In part four, section IV.A, we explain that we lack the data to reliably assess direct feedrate of these metals in hazardous waste. In addition, we also discuss that it is unclear (the lack of certainty resulting from the sparse available data) that hazardous waste feed control of the nonenumerated metals is feasible. The majority of these metals are not directly regulated under existing RCRA requirements, so sources have optimized control of the other HAP

[95] As explained in the responses below, the approach varies slightly if the requisite number of sources do not all use the best back-end pollution control technology. In that case, EPA includes in its pool of best performers the lowest emission levels from sources using the next best pollution control technology.

[96] See USEPA, "Technical Support Document for the HWC MACT Standards, Volume III: Selection of MACT Standards," September 2005, Section 22.

[97] See USEPA, "Technical Support Document for the HWC MACT Standards, Volume III: Selection of MACT Standards," September 2005, Section 5.3.

metals, raising issues of whether simultaneous optimization of feed control of the remaining metals is feasible. Moreover, even if one were to conclude that hazardous waste feed control is feasible for the nonenumerated metal HAPs, hazardous waste ash feedrates are not reliable indicators of nonmercury metal HAP feed control levels and are therefore inappropriate parameters to assess in the MACT evaluation process. For example, a source could reduce its ash feed input by reducing the amount of silica in its feedstreams. This would not result in feed control or emission reductions of metal HAP.[98]

Finally, hazardous waste ash feed control levels do not significantly affect particulate matter emissions from cement kilns, lightweight aggregate kilns, and solid fuel-fired boilers because the majority of particulate matter that is emitted originates from the raw material and nonhazardous fuel. Hazardous waste ash feed control levels also do not significantly affect particulate matter emissions from sources equipped with baghouses because these control devices are not sensitive to particulate matter inlet loadings.[99]

Thus, even if one were to conclude that the nonenumerated metal HAPs are amenable to hazardous waste feed control, explicit use of ash feed control in a MACT methodology would not assure that each source's ability to control either nonmercury metal HAP or surrogate particulate matter emissions is assessed. The Air Pollution Control Device methodology identifies and assesses (with the surrogate particulate matter standard) the known technology that always assures metal HAP emissions are being controlled to MACT levels—that technology being back-end control.

Comment: Commenter claims the Air Pollution Control Device approach to calculate particulate matter floors is flawed because the performance of back-end control technology alone does not reflect the performance of the relevant best sources that otherwise would be reflected if EPA were to assess performance based on the emission levels each source achieved because, as EPA admits, it fails to account for the effect of ash feed rate.

Response: We explain above why the Air Pollution Control Technology approach properly identifies the relevant best performing sources for purposes of controlling non-mercury metal HAP (measured as particulate matter), irrespective of ash feed rates. Typically, this results in selecting the sources with the lowest particulate matter emission rates, the result the commenter advocates. This is because we evaluate sources with the best-performing (*e.g.* lowest emitting) baghouses, and particulate matter emissions from baghouses are not significantly affected by inlet particulate matter loadings. Where the pool of best performing sources includes sources operating some other type of back-end control device (because insufficient numbers of sources are equipped with baghouses to comprise 12% of sources, or five sources (depending on the size of the source category)), we again use the lowest particulate matter emission level from the sources equipped with second best technology. Although these data do not reflect test-to-test variability, they are the best remaining data in EPA's possession to estimate performance and EPA is therefore, as required by section 112 (d) (3) (A) and (B), using the data to fill out the requisite percentage of sources for calculating floors.

Comment: Commenter states that EPA has failed to demonstrate how it reasonably estimated the actual performance of each source's end-of-stack control technology because: (1) It failed to acknowledge that there can be substantial differences between the performance of different models of the same type of technology; and (2) it did not explain or support its rankings of pollution control devices.

Response: As discussed in sections 7.4 and 16.2 of volume III of the technical support document and C.1 of this comment response section, we rank associated back-end air pollution control device classes (e.g., baghouses, electrostatic precipitators, etc.), after assessing particulate matter control efficiencies from hazardous waste combustors that are equipped with the associated back-end control class. The data used to make this assessment are included in our database. We also evaluated particulate matter control efficiencies from other similar source categories that also use these types of control systems, such as municipal waste combustors, medical waste incinerators, sewage sludge combustors, coal-fired boilers, oil fired boilers, non-hazardous industrial waste combustors, and non-hazardous waste Portland cement kilns.[100]

After we assign a ranking score to each back-end control class, we determine the number of sources that are using each of these control technology classes. We then identify the MACT control technology or technologies to be those best ranked back-end controls that are being used by 12 percent of the sources (or used by five sources in instances where there are fewer than 30 sources). We then look only at those sources using MACT back-end control and rank order all these sources first by back-end control type, and second by emissions. For example, in instances where there is more than one MACT back-end control, we array the emissions from the sources equipped with the top ranked back-end controls from best to worst (i.e., lowest to highest), followed by the emissions from sources equipped with the second ranked back-end controls from best to worst, and so on. We then determine the appropriate number of sources to represent 12 percent of the source category (5 in instances where there are fewer than 30 sources). If 10 sources represented 12% of the sources in the source category, we would then select the emissions from best ranked 10 sources in accordance with this ranking procedure to calculate the MACT floor. This methodology results in selection of lowest emitters using best back-end air pollution control as pool of the best performing sources.

The commenter is correct that there can be differences between the performance of different models of the same type of technology. We are not capable of thoroughly assessing differences in designs of each air pollution control device in a manner that could be used in the MACT evaluation process, so that we would only select, for example, baghouses of a certain type. Each baghouse, for example, will be designed differently and thus will have different combinations of design aspects that may or may not make that baghouse better than other baghouses (e.g., bag types, air to cloth ratios, control mechanisms to collect accumulated filter cake and maintain optimum pressure drops). We also do not have detailed design information for each source's air pollution control system; such an assessment would therefore not be

[98] For the same reason, even if feed control of total inputs (i.e. raw material and fossil fuel as well as hazardous waste fuel) were feasible, it would be technically inappropriate to use ash feedrates as a surrogate: ash feed control allows sources to selectively reduce the ash feeds without reducing the metal HAP portion of that feed. Back-end control, in contrast, unselectively removes a percentage of everything that is fed to the combustor.

[99] See USEPA, "Technical Support Document for the HWC MACT Standards, Volume III: Selection of Mact Standards," September 2005, Section 3.1.

[100] See USEPA, "Technical Support Document for th HWC MACT Standards, Volume III: Selection of MACT Standards," September 2005, Section 5.3 and 16.2, for further discussion.

possible even if the information could be used to assess relative performance.

We instead account for this difference by selecting sources with the lowest emissions that are using the defined MACT back-end controls to differentiate the performance among those sources that are using that technology (the best performer being the source with the lowest emissions, as just explained). For example, in situations where more than 12% of the sources are using the single best control technology (e.g., more than 12% of incinerators use baghouses to control particulate matter), we use the emissions from the lowest emitting sources equipped with baghouses to calculate the MACT floor. In instances where there are two defined MACT technologies (i.e., 12% of sources do not use the single best control technology), we use all the emissions data from sources equipped with the best ranked control class, and then subsequently use only the lowest emissions from the sources equipped with the second ranked back-end controls.

Comment: EPA did not say how it picked the best performers if more than twelve percent used the chosen technologies. If EPA used emissions data to differentiate performance, the Agency is necessarily acknowledging that emissions data are a valid measure of sources' performance—in which case the Agency's claims to the contrary are arbitrary and capricious.

Response: We did use emissions data to select the pool of best performers where over 12% use the best type of emissions control technology, as explained in the previous response. Emissions data is obviously one means of measuring performance. EPA's position is that it need not be the exclusive means, in part because doing so leads to arbitrary results in certain situations. Our use of emission levels to rank sources that use the best particulate matter control (i.e., baghouses) does not lead to arbitrary results, however. First, we are assessing emission levels here as a means of differentiating sources using a known type of pollution control technology. More importantly, the adjusted emission levels from sources equipped with baghouses are the most accurate measures of performance because these emissions have been statistically adjusted to accurately account for long-term variability through application of the universal variability factor.

Comment: Commenter states that EPA, in its support for its Air Pollution Control Technology Approach used to calculate particulate matter floors, claims that an emissions-based approach would result in floor levels that "could not necessarily be achieved by sources using the chosen end-of-stack technology," citing 69 FR at 21228. Commenter claims that it is settled law that standards do not have to be achievable through the use of any given control technology, and that it is also erroneous to establish floors at levels thought to be achievable rather than levels sources actually achieve.

Response: EPA is not establishing floor levels based on assuring the standards are achievable by a particular type of end-of-stack technology (or, for that matter, any end-of-stack technology). The floor levels in today's final rule reasonably estimate average performance of the requisite percent of best performing sources without regard for whether the levels themselves can be achieved by a particular means. Floor standards for particulate matter are based on the performance of those sources with the lowest emissions using the best back-end control technology (most often baghouses, and sometimes electrostatic precipitators). EPA uses this approach not to assure that the floors are achievable by sources using these control devices, but to best estimate performance of the best performing sources, including these sources' variability.

2. Total Chlorine Standard for Hydrochloric Acid Production Furnaces

We are adopting the methodology we proposed to estimate floor levels for total chlorine from hydrochloric acid production furnaces. 69 FR at 21225–226. As stated there, we are defining best performers as those sources with the best total chlorine system removal efficiency. We are not assessing a level of control attributable to control of chlorine in feedstocks because this would simply prevent these furnaces from producing their ultimate product. Further details are presented in responses below.

Comment: Basing the standard for hydrochloric acid production furnaces on the basis of system removal efficiency rather than chlorine emission reduction is impermissible. Even though these devices' purpose is to produce chlorinated product, the furnaces can use less chlorinated inputs. EPA's proposed approach is surreptitious, an impermissible attempt to assure that the standards are achievable by all sources using EPA's chosen technology, the approach already rejected in *CKRC*.

Response: EPA disagrees. There is nothing in the text of the statute that compels an approach that forces sources to produce less product to achieve a MACT floor standard. Yet this is the consequence of the comment. If standards were based on levels of chlorine in feedstock to these units, less product would be produced since there would be less chlorine to recover. EPA has instead reasonably chosen to evaluate best performing/best controlled sources for this source category by measuring the efficiency of the entire chlorine emission reduction system. Indeed, the situation here is similar to that in *Mossville*, where polyvinyl chloride production units fed raw materials containing varying amounts of vinyl chloride depending on the product being produced. This led to variable levels of vinyl chloride in plant emissions. Rather than holding that EPA must base a floor standard reflecting the lowest amount of vinyl chloride being fed to these units, the court upheld a standard estimating the amount of pollution control achievable with back-end control. 370 F. 3d at 1240, 1243. In the present case, as in *Mossville*, the standard is based on actual performance of back-end pollution control (although here EPA is assessing actual performance of the control technology rather than estimating performance by use of a regulatory limit, making the situation here *a fortiorari* from that in *Mossville*), and does not reflect "emission variations not related to technological performance". 370 F. 3d at 1240.

It also should be evident that EPA is not establishing a standard to assure its achievability by a type of pollution control technology, as the commenter mistakenly asserts. The standard for total chlorine is based on the average of the best five sources " best meaning those sources with greatest (most efficient) system removal efficiencies. EPA did not, as in *CKRC*, establish the standard using the highest emission limit achieved by a source operating a particular type of control.

Comment: The commenter generally maintains that EPA's methodology to determine total chlorine floors for hydrochloric acid production furnaces fails to capture other means of HAP emission control that otherwise would be captured if EPA were assess performance based on the emission levels each source achieved.

Response: As discussed above, the standard for total chlorine is based on the sources with the best system removal efficiencies. System removal efficiency encompasses all means of MACT floor control when assessing relative performance because: (1) Chlorine feed control is not a MACT floor technology for these sources; and (2) the measure of system removal efficiency accounts for every other controllable factor that can affect

emissions (e.g., operating practices, worker training, proper maintenance, pollution control device type, etc).

D. Format of Standards

1. Thermal Emissions

EPA proposed, and is finalizing standards for HAP metals and chlorine (the HAPs amenable to hazardous waste feed control) emitted by energy recovery units (cement kilns, lightweight aggregate kilns, and liquid fuel boilers) expressed in terms of pounds of HAP attributable to the hazardous waste fuel per million british thermal units (BTUs) of hazardous waste fired. 69 FR at 21219–20. EPA received many comments on this issue to which we respond below and in the Response to Comment Document. Some initial discussion of the issue is appropriate, however.

a. *Expressing Standards in Terms of a Normalizing Parameter is Reasonable.* First, using a thermal emissions form of a standard is an example of expressing standards in terms of a normalizing parameter. EPA routinely normalizes emission standards either by expressing them as stack HAP concentrations or by expressing the standards in units of allowable mass emissions per amount of production or raw material processed. Emission concentration-based standards normalize the size of each source by accounting for volumetric gas flowrate, which is directly tied to the amount of raw material each source processes (and subsequently the amount of product that is produced). Metal and particulate matter emission standards for commercial and industrial solid waste incinerators are expressed in emission concentration format. See § 60.2105. The particulate matter standard for Portland cement kilns is expressed as mass of allowable emissions per mass of raw material processed. See § 63.1342. The particulate matter, mercury, and hydrogen chloride standards for nonhazardous waste industrial boilers are expressed as pounds of allowable emissions per million British thermal units (BTUs). See § 63.7500.

Technology-based standards typically normalize emissions because such a format assures equal levels of control across sources per amount of raw material that is processed, and allows EPA to equally assess source categories that comprise units that differ in size. By normalizing the emissions standard we better ensure the same percentage of emission reduction per unit of raw material processed by each source.[101] See *Weyerhaeuser* v. *Costle*, 590 F. 2d 1011, 1059 (D.C. Cir. 1978) (technology-based standards are typically expressed in terms of volume of pollutants emitted per volume of some type of unit of production).

There is no legal bar to this approach since the statute does not directly address the question of whether a source emitting 100 units of HAP per unit of production but 100 units of HAP overall is a better performer (or, for new sources, better controlled) than a source emitting 10 units of HAP per unit of production but emitting 101 units overall.[102] One commenter appeared to suggest that we should assess performance on mass feedrates and mass emission rates, without normalizing. Such an approach would yield nonsensical results because the best performing sources would more likely be the smallest sources in the source category (smaller sources generally have lower mass emission rates because they process less hazardous waste). This would likely yield emission standards that would not be achievable by the larger sources that more likely are better controlled sources based on a HAP removal efficiency basis.[103] Normalization by unit of production is another way of expressing unit size; so that normalizing on this basis is a reasonable alternative to subcategorization on a plant size-by-plant size basis. See section 112(d)(1) (size is an enumerated basis for subcategorizing).

b. *Using Hazardous Waste Thermal Input as the Normalizing Parameter is Permissible and Reasonable.* Normalization of standards based on thermal input is analogous. For energy recovery units (in this rule, kilns and most liquid fuel boilers), normalizing on the basis of thermal input uses a key feed input as the normalizing parameter, allowing comparison of units with different inputs rather than separately evaluating these units by size and type (see section 112(d)(1)). Again, this approach is legally permissible. The statute does not answer the question of which source is better performing, the source emitting 100 pounds of HAP per million BTUs hazardous waste but 100 pounds of HAP overall or the source emitting 10 pounds of HAP per million BTUs hazardous waste but emitting 101 pounds overall.

The approach also is reasonable. First, as with other standards expressed in normalized terms, by normalizing the emissions standard we ensure the same percentage of emission reduction per unit of raw material processed by each source, thus allowing meaningful comparison among sources. For example, emission concentration-based standards normalize the size of each source by accounting for volumetric gas flowrate, which is directly tied to the amount of raw material each source processes (and subsequently to the amount of product that is produced), and assures equal levels of control per amount of product. Normalization on the basis of HAP amount in hazardous waste per BTU level in the hazardous waste similarly assures equal levels of control across sources per amount of raw material that is processed. Here, the raw material is the hazardous waste fuel, expressed as units of energy. It is reasonable to regard a hazardous waste fuel as a raw material to an energy recovery device. Indeed, fuels are the only input to boilers, so fuels are necessarily such units' sole raw material.[104] [105] Hazardous waste burning cement kilns and lightweight aggregate kilns produce a product in addition to recovered energy and so process other raw materials. However, the reason these units use hazardous waste as inputs is typically to recover usable energy from the wastes. Hence, the hazardous waste fuel is reasonably viewed as a raw material to these devices.

In this regard, we note that our choice of normalizing parameter essentially says that best performers with respect to hazardous waste fuel burned in energy recovery units are those using the lowest HAP feedrate (for metals and chlorine) per amount of energy

[101] A more familiar example of normalization is the Earned Run Average (ERA), which normalizes a baseball pitchers' earned runs on the basis of nine innings pitched in order to make comparisons among pitchers possible.

[102] Or, put another way, the statute does not directly address the question of whether a small source that emits 10 units of HAP is better than a much larger source with better back-end control (but feeding the same raw material at a higher mass feedrates) that emits 100 units of HAP.

[103] See USEPA, "Technical Support Document for the HWC MACT Standards, Volume III: Selection of MACT Standards," September 2005, Section 6.0.

[104] EPA thus has expressed the MACT standards for particulate matter, mercury, and hydrogen chloride standards for nonhazardous waste industrial boilers as pounds of allowable emissions per million BTUs. § See 63.7500. This normalization considers the total heat input into the combustion device. Normalizing by total heat input would not be appropriate for hazardous waste combustors for metals and chlorine because this would implicitly account for, and in turn require the use of, feed control of HAP in non hazardous waste fuels. This is inappropriate for the reasons discussed in Section III.B of this Part.

[105] We distinguish (i.e., subcategorize) liquid fuel boilers that process hazardous waste with heating values less than 10,000 BTU/lb from those processing hazardous wastes with heating content greater than 10,000 BTU/lb. Although boilers that process hazardous waste with heating values less than 10,000 BTU/lb are still considered to be energy recovery units, we conclude a thermal emissions normalization approach for these sources is not appropriate. See Part Four, Section VI.D.

recovered.[106] This approach accords well with the requirement in section 112(d)(2) that EPA take energy considerations into account in developing MACT, and also that the Agency consider front-end means of control such as input substitution (section 112(d)(2)(A)). In addition, our choice furthers the RCRA goal of encouraging properly conducted recycling and reuse (RCRA section 1003(b)(6)), which is of relevance here in that Congress directed EPA to consider the RCRA emission controls for hazardous waste combustion units in developing MACT standards for these units, and to ensure "to the maximum extent possible, and consistent with [section 112]" that section 112 standards are "consistent" with the RCRA scheme. CAA section 112(n)(7).[107] Conversely, emission concentration-based standards, the methodology that otherwise would be used to calculate emission concentration-based standards, may result in standards that are biased against sources that recover more energy from hazardous waste. This may discourage sources from recovering energy from hazardous waste because such standards do not normalize each source's allowable emissions based on the amount of hazardous waste it processes for energy recovery purposes. See 69 FR at 21219 and responses below.

Second, use of this normalizing parameter makes it much more likely that hazardous waste feed controls will be utilized by these devices as an aspect of emissions control. See section 112(d)(2)(A) (use of measures reducing the volume of pollutants emitted through "substitution of materials"); *CKRC*, 255 F. 3d at 865 (EPA to consider means of control in addition to back-end pollution control technology when establishing MACT floors). As explained in our discussion of the SRE/Feed methodology, the MACT floor level for metals and chlorine reflects the best combination of hazardous waste feedrate, and total HAP removal efficiency. See section III.B. However, if standards for energy recovery units are expressed in terms of mass of HAP per volume of stack gas, then it would be relatively easy for these energy recovery devices to achieve a standard, without decreasing concentrations of HAP in their hazardous waste fuels, by diluting the HAP contribution of hazardous waste with emissions from fossil fuel. A thermal emissions format prevents this type of dilution from happening because it ignores additions of stack gases attributable to burning fossil fuels. *Weyerhaeuser*, 590 F. 2d at 1059 (use of production of a unit as a normalizing parameter serves "the commendable purpose" of preventing plants from achieving emission limitations via dilution).

For example, assume there are two identical energy recovery units with identical back-end control devices (that reflect the performance of the average of the best performing sources). Source A fulfills 25% of its energy demand from the combustion of hazardous waste; source B fulfills 50% of its energy demand from the combustion of hazardous waste. Also assume that the hazardous waste for these two sources have equivalent energy contents. If these sources were required to comply with an emission concentration based-standard (e.g., µg/dscm), source A would be allowed to feed hazardous waste containing twice the metal content (on a mass concentration basis, e.g., ppm), and would be allowed to emit metal HAP at the same mass emission rate relative to source B. This is because this source is effectively diluting its emissions with the emissions that are being generated by the fossil fuels.[108] A thermal emissions standard format does not allow sources to dilute their emissions with the emissions from fossil fuel inputs because it directly regulates the emissions and feeds associated with the hazardous waste fuel. Under a thermal emissions format both sources would be required to feed hazardous waste with the same thermal feed concentrations (on a lb HAP per million BTU hazardous waste basis), and source A would be required to process hazardous waste with an equivalent concentration of metal HAP (on a mass basis) and also be required to emit half as much metal HAP (on a mass emission rate basis) relative to source B, because source A is processing half as much hazardous waste fuel, thus vindicating the hazardous waste feed control aspect of the standard (see also note below regarding the likelihood of sources using hazardous waste feed control). Further, the thermal feed concentration with which these sources must comply reflects the feed control of the average performance of the best performing sources (on a mass of HAP per million BTU basis). Such a requirement assures that these sources are processing the cleanest hazardous waste fuels to recover energy and are reducing HAP emissions to MACT levels.

We note that it would not be appropriate to express the emission standards for incinerators, hydrochloric acid production furnaces, and solid fuel boilers in terms of thermal emissions. As just explained, the choice of a normalizing parameter is fitted to the nature of the device to which it is applied in order to allow the most meaningful comparisons between devices of like type. We therefore conclude that a thermal emissions format (i.e., normalizing parameter) for incinerators is not appropriate because the primary function of incinerators is to thermally treat hazardous waste (as opposed to recovering energy from the hazardous waste). See 67 FR at 17362 (April 19, 1996). Our database indicates that most incinerators processed hazardous waste during their emissions tests that had, on average, heating values below 10,000 BTU/lb.[109] We have emission test hazardous waste heating value information for 62 incinerators in our database. Of these 62 sources, 40 sources processed hazardous waste with an average heating value of less than 10,000 BTU/lb. The other 22 sources processed hazardous waste with heating values greater than 10,000 BTU/lb in at least one test condition, although we note that 14 of these 22 sources also processed hazardous waste in different test conditions with heating values lower than 10,000 BTU/lb.[110]

We assessed whether we should subcategorize incinerators, similar to how we subcategorize liquid fuel boilers, based on the BTU content of the hazardous waste. Incinerators do recover energy from processing high BTU wastes. Some incinerators are equipped with waste heat boilers, and high BTU hazardous waste can displace fossil fuels that otherwise would have to be burned to thermally treat low BTU wastestreams. However, such energy recovery is considered to be a secondary product because their primary function is to thermally treat hazardous waste. A

[106] As explained earlier, the ultimate ranking of best performers then further evaluates system removal efficiency, best performers then being defined in terms of the combination of hazardous waste thermal feed and system removal efficiency. See USEPA, "Technical Support Document for the HWC MACT Standards, Volume III: Selection of MACT Standards", September 2005, Section 7.3.

[107] EPA would adopt the thermal format for the standards, however, whether or not the approach furthered RCRA objectives.

[108] This example assumes there are no HAP emissions attributable to the fossil fuels.

[109] As discussed later, the heating values of hazardous wastes processed at cement kiln and lightweight aggregate kilns are primarily 10,000 BTU/lb or greater.

[110] These data are based on a compilation of heating contents for every incinerator test condition in the database where the source reported such heating content, and include both the most recent test conditions as well as older test conditions. Incinerator test condition heating values range from a low of 790 to a high of 19,800 BTU/lb, with a median value of 7800 BTU/lb.

thermal emissions normalization approach for incinerators that combust hazardous wastes with heating values greater than 10,000 BTU/lb would therefore not be appropriate because the normalized parameter would not be tied to the primary production output that results from the processing of hazardous waste (i.e., treated hazardous waste). In confirmation, no commenters suggested that we apply a thermal emissions format to incinerators.

We also conclude that a thermal emission format is inappropriate for hydrochloric acid production furnaces. These devices recover chlorine, an essential raw material in the process, from hazardous waste. The classic normalizing parameter of amount of product (HCl) produced is therefore the obvious normalizing parameter for these sources. It is true that some hydrochloric acid production furnaces recover energy from high BTU hazardous wastes. See 56 FR at 7141/1 and 7141–42 (Feb. 21, 1991). Some sources are equipped with waste heat boilers, and high BTU wastes help sustain the combustion process, which is necessary to liberate the chlorine from the wastestreams prior to recovering the chlorine in the scrubbing systems. Again, energy recovery is not the primary function of these types of sources.[111] Hydrochloric acid production furnace hazardous waste heating values range from 1,100 to 11,000 BTU/lb (the median energy content for these sources is slightly above 6,000 BTU/lb). The range of hazardous waste heating contents from these sources is much lower than the ranges for cement kilns, lightweight aggregate kilns, and liquid fuel boilers, supporting the premise that energy recovery is of secondary importance. In addition, and critically, the hazardous waste that is processed in these units contains high concentrations of chlorine, confirming that the wastes serve as feedstock for hydrochloric acid production, even if the wastes also have energy value.[112] No commenters suggested that we apply a thermal emissions format to hydrochloric acid production furnaces.

We consider the processing of hazardous waste in solid fuel boilers to be more reflective of energy recovery (relative to incinerators and hydrochloric acid production furnaces) because these sources directly recover the heat that is released from the combustion of the waste streams. However, as stated at proposal, not all these sources are processing hazardous wastes for energy recovery. 69 FR at 21220. These boilers are generally not commercial units, and so tend to burn whatever hazardous wastes are generated at the facility where they are located. Heating values for this source category range from 1,300 to 10,500 BTU/lb, with a median value of 8,000 BTU/lb. We therefore conclude that thermal emission standards for these sources are not appropriate because most of these sources are processing hazardous waste with energy content lower than 10,000 BTU/lb. As discussed in section VI.D, we conclude that 10,000 BTU/lb is an appropriate level that distinguishes whether thermal emission standards or mass emission concentration-based standards are appropriate. We also note that no commenters suggested that we apply a thermal emissions format to solid fuel boilers.

Comment: Commenters state that thermal emission standards are inappropriate because sources burning hazardous waste with a higher energy content or higher percent hazardous waste firing rate (i.e., one that fulfills a greater percentage of its total energy demand from the hazardous waste) would be allowed to emit more HAP.

Response: Part of this comment would apply regardless of what normalizing parameter is used. Technology-based standards (including MACT standards) are almost always expressed in terms of some type of normalizing parameter, i.e., "X" amount of HAP may be emitted per unit of normalizing parameter. This allows a meaningful comparison between units of different size and production capacity. A consequence is that the overall mass of HAP emissions varies, but the rate of control remains constant per the normalizing unit. As explained in the introduction to this section, this approach is both routine and permissible.

Cement kilns, lightweight aggregate kilns, and liquid fuel boilers combust hazardous waste to recover valuable energy. Recovering energy is an integral part of their production process. As discussed at proposal, emission concentration-based standards (and the methodology that otherwise would be used to calculate emission concentration-based standards) may result in standards that are biased against sources that recover more energy from hazardous waste. 69 FR at 21219. This may discourage sources from recovering energy from hazardous waste because such standards do not normalize each source's allowable emissions based on the amount of hazardous waste it processes for energy recovery purposes. A source that fulfills 100 percent of its energy demand from hazardous waste would be required to limit its mass HAP emissions to the same levels as an identical source that satisfies, for example, only 10 percent of its energy demand from hazardous waste and 90% from coal. This would inappropriately discourage the safe recovery of energy from hazardous waste, and could in turn result in greater consumption of valuable fossil fuels that otherwise would be consumed.

Sources which fulfill a greater percentage of their energy demand from hazardous waste (either by processing hazardous wastes that are higher in energy content, or by simply processing more hazardous waste) will be allowed to emit more HAP (on a mass emission rate basis) than an identical source that satisfies less of its total energy demand from hazardous waste. This is appropriate because: (1) The source fulfilling a greater percentage of its energy demand from hazardous waste is processing more raw material than the other source (the raw material being the energy content of the waste); and (2) The source fulfilling a lower percentage of its energy demand requirements from hazardous waste would not be allowed to dilute its emissions with nonhazardous waste fuels, and we would thus assure that all sources implement hazardous waste feed control to levels consistent with MACT.[113] This

[111] EPA notes that when first adopting RCRA air emission standards for hydrochloric acid recovery furnaces (then called 'halogen acid furnaces'), EPA indicated that those furnaces designed as boilers would be subject to the emission standards for boilers. 56 FR at 7040. This determination did not have regulatory consequence, since all hydrochloric acid production furnaces were subject to the same emission standards whether they were classified as boilers or as industrial furnaces. Thus, EPA was not concluding that some hydrochloric acid furnaces existed for the primary purpose of recovering energy in the 1991 rulemaking. 56 FR at 7139 ("[Hydrochloric acid recovery furnaces] are typically modified firetube boilers that process secondary waste streams containing 20 to 70 per cent chlorine or bromine to produce a halogen acid product by scrubbing acid from the combustion gases").

[112] Hazardous waste chlorine feedrates that are included in our database (expressed as MTECs) range from a low of 46,000,000 µg/dscm to a high of 294,000,000 µg/dscm. On a mass chlorine percentage basis, these wastes range from 17% to 82%, noting that these percentages did not include the chlorine that was also spiked during the emissions tests). See USEPA, "Technical Support Document for the HWC MACT Standards, Volume III: Selection of MACT Standards", September 2005, Section 15.

[113] Although the rule does not require use of feed control (or any particular means of control to achieve a standard), the rule assures that all sources' emissions will reflect the emissions of the sources with the best hazardous waste federates expressed in terms of amount of HAP per BTU of hazardous waste. Because this format eliminates

Continued

was illustrated in the example provided in the introduction to this comment response section.

Similarly, two sources that combust hazardous waste with the same energy content and the same metal concentrations (on both a thermal concentration and mass-based concentration basis), but at different hazardous waste firing rates, would be required to achieve identical back-end control device operating efficiencies to comply with a thermal emissions-based standard. Holding these factors constant, thermal emission standards require sources to achieve identical percent reductions of the HAP that is processed within the combustor via removal with an air pollution control device. A thermal emission standard format is thus equally stringent for these sources on a percent HAP removal basis, irrespective of the amount of hazardous waste it processes for energy recovery, and better assures that sources burning smaller amounts of hazardous waste (from an energy recovery perspective) are also controlling emissions as well as the average of the best performing sources.

Sources processing higher energy content hazardous wastes would be allowed to feed hazardous wastes with higher metal and chlorine mass-based concentrations relative to other sources combusting lower energy content wastes. To illustrate this, assume there are two sources (named C and D) with identical back-end control systems and identical mass feedrates of hazardous waste. Also assume the hazardous waste of source C has twice the energy content as compared to the hazardous waste processed by source D. A thermal emission standard will allow Source C to feed a hazardous waste that has twice the metals concentration (as measured on a mass basis) as compared to source D, even though both sources would be required to comply with equivalent thermal feed rates limitations. Notably, however: (1) Source C is displacing (*i.e.*, not using) twice as much valuable fossil fuel as the source with the lower energy content hazardous waste, and is feeding twice as much raw material—the raw material being energy content contained in the hazardous waste; (2) source C cannot exceed the feed control levels (expressed on a lbs of HAP per million BTU basis) that was achieved by the average of the best performing sources (assuming its back-end control efficiency is equivalent to the average performance demonstrated by the best performing sources); and (3) source D is required to have lower mass concentrations of metals in its hazardous waste because it is firing poorer quality hazardous waste fuel (from an energy recovery perspective) and because it is feeding less of the same raw material (measured by energy content). Thus, the thermal emissions format appropriately encourages and promotes the processing of clean, high energy content hazardous waste fuels (consistent with evaluating hazardous waste feed control as an aspect of MACT, and not just relying on control solely through use of back end technology), and does so equally for all sources because it normalizes the allowable emissions based on the amount of energy each source recovers from the hazardous waste. Put another way, source C in the above example is controlling HAP emissions to the same extent as the average of the best performing sources per every BTU of hazardous waste fuel it processes (as is source D).

We note that this is a hypothetical example. In practice the average energy content of hazardous waste processed at cement kilns does not vary significantly across sources. Cement kilns burn hazardous wastes with relatively consistent energy contents because that is what their production process necessitates. This is supported by our database and by comments received from the Cement Kiln Recycling Coalition.[114] Heating values of hazardous wastes processed at cement kilns during compliance tests (information which is included in our database) range from 10,300 to 17,600 BTU/lb, with a median value of 12,400 BTU/lb. We note that these are snapshot representations of hazardous waste heating content from these sources that originate from compliance tests. We also have long term average hazardous waste heating measurements from cement kilns indicating that the heating content of the hazardous wastes on average range from 9,900 to 12,200 BTU/lb, with a median value of 11, 500 BTU/lb. We thus conclude that the commenter's concern regarding sources being allowed to emit more HAP if they process hazardous waste with higher energy content is overstated for these sources.

Energy content of hazardous wastes processed in liquid fuel boilers and lightweight aggregate kilns varies more than energy content of hazardous wastes processed by cement kilns, and sources with higher energy content wastes would be allowed to emit more metals than identical sources burning identical volumes of lower energy content wastes (although the degree of control is identical per BTU of hazardous waste fuel processed).[115] Again, these are hypothetical examples. Each energy recovery unit will have an upper bound on the amount of energy it can process from the hazardous waste. Sources that process higher energy content hazardous wastes would not necessarily feed the same volume of hazardous waste as compared to sources processing lower energy content hazardous wastes because they cannot exceed the thermal capacity of their combustion unit. Under a thermal emission standard format, the mass emission rates that would be allowed for identical sources that fulfill 100 percent of their energy demand from hazardous waste and that have differing hazardous waste energy contents would be identical. Although the source with the higher energy content hazardous waste would have a higher allowable mass-based hazardous waste feed concentration, this source would have to process less hazardous waste (on a mass basis) to remain within its thermal capacity. This helps to ensure that its mass HAP emission rate is similar to other sources that process lower energy content hazardous waste.

One commenter's apparent concern with thermal emissions seems to center on an assertion that sources will intentionally blend nonhazardous, high heating value wastes or fuels with low energy, high metal bearing hazardous wastes in order to increase the energy content of these metal bearing wastes so that they will be subject to higher allowable emissions via thermal emission standards. We specifically address that comment later as it relates to commercial energy recovery units (lightweight aggregate kilns and cement kilns). We note here, however, that we do not consider that comment to be of practical concern for liquid fuel boilers

consideration of stack gas attributable to fossil fuel emissions, and thus eliminates the dilutive effect of these emissions, the likelihood that sources will in fact use hazardous waste feed control as part of their control strategy is great.

[114] See comment submitted by the Cement Kiln Recycling Coalition, USEPA. "Comment Response Document to the Proposed HWC MACT Standards, Volume 1: MACT Standards," September 2005. Section 3.3. Also see USEPA, "Technical Support Document for the HWC MACT Standards, Volume III: Selection of MACT Standards," September 2005, Section 23.

[115] The hazardous waste heating values of liquid fuel boilers range from 2,200 to 21,000 BTU/lb, with a median value of 14,800. Heating values of lightweight aggregate kilns range from 4,900 to 16,900 BTU/lb, with a median value of 14,800. We note that the low end heating value for lightweight aggregate kilns reflects one source and is not typical of heating values used by the other commercial lightweight aggregate kiln facilities, and are similar to the heating values of cement kilns.

because they do not engage in commercial fuel blending practices.

Comment: A commenter states that EPA's assessment of thermal emissions to identify the relevant best sources is inappropriate because thermal emissions are not emission levels, but rather a ratio of emissions to the heat content in a source's hazardous waste.

Response: This comment challenges the basic idea of normalization, since the comment would be the same regardless of the normalizing parameter being used. Thermal emissions are emission levels that are normalized to account for the amount of energy (*i.e.*, raw material) these sources recover by processing hazardous waste. Similarly, a mass emission concentration (*i.e.*, μg/dscm) is a ratio of the emissions to the volume of combustion gas that is generated, which normalize emissions to account for differences in the size of the combustion units (as well as differences in production capacity). This rulemaking assesses performance and expresses emission standards in both of these formats; both formats normalize the emissions so that we may better assess emission control efficiencies equally across sources based on the percent of HAP in the feed (whether thermal feed or feed normalized based on combustor size)[116] that is controlled or removed from the stack gas prior to being emitted into the atmosphere. As discussed above, technology-based standards have historically assessed performance after normalizing emissions based on the amount of raw material processed by the given industry sector. Thermal emissions normalize each source's emissions based on the amount of raw material (hazardous waste fuel) it processes, and are therefore appropriate to assess and identify the relevant best performers. Finally, as previously explained, this approach is consistent with both the language of section 112 (d) (2) and (3), and the purpose of these provisions.

Comment: A commenter states that EPA's assessment of thermal emissions to identify the relevant best sources is inappropriate because it ignores HAP emissions attributable to the nonhazardous fuel and raw material.

Response: Thermal emission standards do not directly control HAP emissions attributable to the fossil fuels and raw material, in the sense that we did not assess feed control of fossil fuels or raw materials. However, this issue is not related to our choice to use thermal content of hazardous waste as a normalizing parameter. Rather, the issue is whether feed control of fossil fuels and raw materials is a feasible means of control at all. We have determined that it is not, and that only back-end control (expressed as system removal efficiency) is feasible. Moreover, today's rule controls emissions from HAP in raw material and fossil fuels. All non-mercury metal HAP emissions attributable to fossil fuels or raw material are effectively and efficiently controlled to the level of the average of the best performing sources with the surrogate particulate matter standard, as well as the system removal efficiency component of the SRE/Feed methodology.

Comment: EPA has failed to document sources' actual feedrates. Feedrates are presented either as MTECs (where hazardous waste HAP feedrates are divided by gas flow rates) or as thermal feedrates, (where feedrate is expressed as the mass of HAP per million BTUs of hazardous waste fired). This is impermissible, since it does not measure actual feed levels.

Response: This comment essentially takes the position that it is legally impermissible to normalize standards, *i.e.*, express standards on a common basis. EPA rejects this comment for the reasons stated in the introduction to this section.

Comment: A commenter states that an increasing number of fuel blenders are producing fuels with a minimum heating content and maximum metals content in order to maximize revenues because high metal bearing wastes command a higher revenue on the commercial waste market. The commenter states that thermal emission standards are not appropriate because they are based on the implicit assumption that energy recovery entails metals feed.

Response: Contrary to what the commenter suggests, the thermal emissions format will more likely discourage the alleged practice of fuel blenders producing fuels with a minimum heat content and maximum metals content because the standard limits the allowable metal emissions based on the amount of energy contained in the hazardous waste. Thus, a source with a lower energy waste would have to ensure that the mass concentration of metals is also lower to comply with the thermal emission formatted standard. The source would consequently emit less metals (on a mass basis) because of the lower metal mass concentration in the waste fuel. Thermal emission standards reflect the reality that the hazardous waste fuels that are currently processed safely and efficiently in energy recovery units to displace valuable fossil fuel do in fact contain metal HAP. From a feed control perspective, the thermal emissions format appropriately requires sources to process high energy content hazardous waste fuels that reflect the thermal feed control levels achieved by the average of the best performing sources, and does so equally for all sources because it normalizes the allowable emissions based on the amount of energy each source recovers from the hazardous waste.

Comment: A commenter states that EPA should be concerned that fuel blenders and kilns will use the thermal emission standard format to increase the allowable metals feedrates for their units. The commenter claims that sources could inappropriately convert non-hazardous waste fuel to hazardous waste fuel by simply putting coal in a bunker in which hazardous waste was once stored, or mixing nonhazardous waste fuel oil with hazardous waste. The commenter states that a facility with a low hazardous waste firing rate, and relatively low allowable emissions can become a facility with a high hazardous waste percent firing rate, with higher allowable emissions, simply by 'creative' use of the hazardous waste mixture rule. The commenter suggests that EPA clearly state that the hazardous waste thermal emission standards apply only to the hazardous waste portion of the fuel blend mixture. The commenter further suggests that EPA require fuel blenders to report the amount of nonhazardous waste fuel that is contained in the fuel blend, and that cement kilns use this to determine allowable metal feed rates based on the original hazardous waste energy content.

Response: We do not believe hazardous waste combustors will engage in the practice of redesignating their fossil fuels, *i.e.*, coal, as hazardous wastes with creative use of the mixture rule in order to increase their allowable metal HAP emission rate. That would require large quantities of coal to be newly classified as hazardous waste. The coal, and the unit where the coal is stored, would subsequently become subject to all applicable subtitle C requirements, which include storage and closure/post closure requirements. We believe this disincentive will discourage this hypothetical practice.

Moreover, as previously discussed, today's rule does not allow cement kiln or lightweight aggregate kiln emissions to exceed the interim standards. The fact that we are issuing emission

[116] For emission concentration-based standards we normalize hazardous waste feed control levels by calculating what we call maximum theoretical emission concentrations, which are equivalent to the HAP mass feed rate divided by gas flow rate.

standards for some pollutants in the thermal emissions standard format will not encourage fuel blenders to send more metals to these commercial energy recovery sources because their allowable emission concentrations are, by definition, either equivalent to or more stringent than the current limitations with which they are complying. Thus, even if the fuel blenders and energy recovery units engaged in this practice, they could not emit more metals than they are currently allowed to emit. We therefore conclude that it is not necessary to promulgate complicated regulatory provisions that would increase the reporting and recordkeeping requirements of fuel blenders and energy recovery units in order to address a hypothetical scenario that likely would never occur.

Finally, we note that combustion of certain high HAP metal content wastes is already prohibited under RCRA rules. See 40 CFR 268.3. Such wastes remain prohibited from combustion even if they are mixed with fossil fuel so that the mixture has a higher energy content. *U.S.* v. *Marine Shale Processors*, 81 F. 3d 1361, 1366 (5th Cir. 1996) (an unrecyclable hazardous waste is not recycled when it is mixed with a usable non-waste and the mixture is processed). Thus, the dilution prohibition in § 268.3 serves as a further guard against the commenter's concern.

Comment: A commenter states that the thermal emissions format may be problematic because it is based on a flawed assumption that metal HAP from the cement kiln raw material and hazardous waste partition in equal proportions to the total stack gas emissions. The commenter believes that metal retention in the raw materials is higher than the hazardous waste, suggesting that thermal emission standards allow an arbitrary increase in allowable hazardous waste metals emissions. The commenter suggests that EPA require that compliance demonstrations be conducted only under conditions where the metals content in the hazardous waste is significantly higher than the metal content in the raw material to minimize this bias.

Response: The commenter has not provided any emissions data to support this claim, nor does the EPA know of data available that reaches this conclusion. We do not believe there is a significant difference in the partitioning rates of these metals in a cement kiln.[117] Even if there is a difference, this would not result in an arbitrary increase of allowable hazardous waste metals emissions. The thermal emission standards were calculated using thermal emissions data that are based on each source's compliance test. These tests were conducted at hazardous waste feed control levels that represented the upper bound of feed control levels these sources see on a day-to-day basis. To accomplish this, sources spiked metals into the hazardous waste prior to combusting the wastes. The amount of metals that were contained in the hazardous waste streams, after accounting for these spiked metals, far exceeded the metal levels that were contained in the raw material. Thus the differences in partitioning, if any, would likely be overshadowed by the fact that the majority of the metals were contained in the hazardous waste.

Notably, any partitioning bias that that may be present would also have been present during these compliance tests. As a result, this potential bias would be built into the emission standard and thus would not result in an arbitrary increase in allowable hazardous waste metals emissions because these sources will again demonstrate compliance under testing conditions similar to those used to generate the data used to calculate the MACT floors. We conclude that it is not necessary to provide additional prescriptive regulatory language that would require sources to demonstrate system removal efficiencies under testing conditions that exhibit a high ratio of hazardous waste metal content to raw material metal content because the regulations implicitly require sources to demonstrate hazardous waste metal feed control levels that represent the upper range of their allowable feed control levels.[118]

Comment: A commenter states that compliance with standards expressed in a thermal emissions format is problematic because the measurement of energy content of hazardous waste fuel blends is subject to significant variability due to the nature of the test. The commenter also claims that heating value measurements of waste streams that are mixtures of solids and liquids tend be biased high, which would inappropriately give these sources higher allowable metal emission limitation.

Response: There are standard ASTM procedures that reliably measure the energy content of the hazardous waste. Any parameter that is measured for compliance purposes is subject to method imprecision and variability. We do not believe that hazardous waste energy content measurements result in imprecision and variability above and beyond the measurement methods that are currently used to assure compliance with emission concentration-based standards.

The commenter did not provide evidence that supports the claim that energy content measurement and/or sampling methods consistently result in a positive bias. If a bias were consistently present for these types of wastes, then one would expect it to be also reflected in the measured data for which we based the emission standards, which would fully address the commenter's concern. Nonetheless, we note that all hazardous waste sampling and analysis procedures must be prescribed in each source's feedstream analysis plan, which can be reviewed by the permitting authority upon request. These feedstream analysis plans must ensure that sampling and analysis procedures are unbiased, precise, and that the results are representative of the feedstream. See § 63.1208(b)(8). More information on obtaining a representative samples can be found in EPA's SW–846 publication.[119] These procedures involve acquiring several sub-samples that provide integration over the breadth, depth and surface area of the waste container and obtaining replicate samples (see Ch. 13.3.1 of SW–846).

Comment: A commenter states that BTU measurements can be reported as either a higher heating value or a lower heating value, and suggests that EPA require sources to use the lower heating value calculation when determining allowable hazardous waste feed control levels. The commenter seems to imply that use of higher heating values will inappropriately result in higher allowable metal feed rates for fuel blends that contain aqueous waste.

Response: The BTU data in our database that we use to calculate the emission standards reflect higher heating values. It is standard practice in the incineration/combustion industry to report the gross heat of combustion (or

[117] We reference comments submitted by the cement kiln recycling coalition that address this very point. See USEPA, "Comment Response Document to the Proposed HWC MACT Standards, Volume 1: MACT Standards," September 2005, Section 3.3. We have evaluated these comments and find them persuasive on this issue.

[118] Although today's final rule allows sources to extrapolate their allowable hazardous waste feed control levels to levels that are higher than the level demonstrated in the comprehensive performance test, sources must still spike metals into the hazardous waste during the test in order to assure that the system removal efficiency used for the extrapolation procedure is reliable and accurate.

[119] SW–846, "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods."

higher heating value). We conclude that sources should use the higher heating value rather than the lower heating value for all compliance determinations because these are method-based emission standards. Fuel blends that contain aqueous wastes will not be inappropriately rewarded with higher allowable feed rates because any fuel mixture that contain aqueous mixtures will have lower reported heating values, irrespective of whether they are reported as higher heating values or lower heating values.[120]

E. Standards Can Be No Less Stringent Than the Interim Standards

Comment: Several commenters oppose EPA's position in the proposed rule that the replacement standards can be promulgated at a level no less stringent than the interim standards for incinerators, cement kilns, and lightweight aggregate kilns. In instances where the calculated replacement standard is less stringent than the interim standard, the commenters oppose EPA's position of "capping" the replacement standard at the level of the interim standard to prevent backsliding from those levels. Instead, commenters recommend that EPA calculate and finalize the existing and new source floor levels without regard to the interim standards. One commenter also notes that the interim standards are simply a placeholder without the necessary statutory basis to qualify as emission limitations for purposes of establishing MACT floors. Another commenter, however, supports EPA's position to prevent backsliding to levels less stringent than the interim standards.

Response: We maintain that the replacement standards can be no less stringent than existing standards, including the interim standards under §§ 63.1203–1205, for incinerators, cement kilns, and lightweight aggregate kilns. These standards were promulgated on February 13, 2002, and sources were required to comply with them no later than September 30, 2003, unless granted a one-year extension (see § 63.1206(a)). Thus, all hazardous waste combustors are currently complying with the interim standards. The comment that the standards lack some type of requisite statutory pedigree misses the central point of our interpretation of the statute: motivation for achieving a standard (be it regulatory compulsion, statutory requirement, or some other reason) is irrelevant in determining levels of MACT floors. *National Lime* v. *EPA*, 233 F. 3d at 640. What matters is the level of performance, not what motivated that level.

As a result, the replacement standards promulgated today ensure that sources will emit HAP at levels no higher than levels achieved under current regulations. We do this in this rule, when necessary, by either capping a calculated floor level by the interim standard (when both the calculated floor level and interim standard are expressed in the same format of the standard) or by adopting dual standards in cases where formats of the standard vary (so that comparison of stringency cannot be uniformly determined (as for cement kilns and lightweight aggregate kilns, as explained in the preceding section above and in the following response). In this case, the sources are subject to both the replacement and interim standards.

Comment: One commenter states that some proposed standards expressed in a thermal emissions format would allow some sources to emit semivolatile metals at levels higher than the interim standard. The commenter states that EPA reached incorrect conclusions when making relative stringency comparisons between standards expressed in a thermal emissions and mass concentrations format because, in part, EPA assumed an average F-factor (e.g., semivolatile metals for cement kilns).[121] In addition, the commenter notes that the actual relationship between standards expressed in terms of thermal emissions and mass concentrations is complex and depends on a number of factors. As a result, the commenter urges EPA to adopt dual standards (*i.e.*, promulgate the MACT standard as both the standard expressed in a thermal emissions format and also the interim standard expressed in a mass concentration format) to prevent backsliding.

Response: Even though a source may operate in compliance with a standard expressed in a thermal emission format, a source may or may not also be in compliance with the corresponding mass concentration interim standard (e.g., the semi- and low volatile metal emission standards for cement and lightweight aggregate kilns of §§ 63.1204 and 63.1205, respectively). As reflected in the comment, making a judgment as to whether a replacement standard is more stringent than the interim standard for the HAP is not always a straightforward calculation. As we discussed in the proposed rule[122] and echoed by the commenter, comparing standards in the thermal emissions format to those in a mass concentration format involves assumptions that vary on a site-specific basis and can vary over time, including the hazardous waste fuel replacement rate, contributions to emissions from nonhazardous waste inputs such as raw materials and nonhazardous waste fuels such as coal, how close to the standard a source elects to comply, the system removal efficiency demonstrated during testing, and the type and composition, including heating value, of fuels burned.

To ensure that sources operating under standards expressed in a thermal emissions format will not emit HAP metals at levels higher than currently achieved under the interim standards, we adopt a dual standard to prevent emissions increasing to levels higher than the interim standards. The dual standard structure includes both the standard expressed in a thermal emissions format and the interim standard, which is expressed in a mass concentration format. We apply this concept to several standards including semivolatile metals, low volatile metals, and mercury[123] for cement kilns and semivolatile metals and low volatile metals for lightweight aggregate kilns. This approach ensures that sources are not emitting HAP metals above the levels of the interim standards because we cannot reliably determine that emissions under a standard expressed in a thermal emissions format would not exceed the interim standard for all sources in the category. See §§ 63.1220(a)(2)–(a)(4), and (b)(2)–(b)(4) and 63.1221(a)(3)–(a)(4) and (b)(3)–(b)(4).

We evaluated the relative stringency of the standards expressed in the thermal emissions format compared to the interim standards for the entire source category in order to determine if the dual standard scheme could be avoided. We determined that we could not. For some HAP groups we found that many sources in the category would have the potential to exceed the interim

[120] The difference between the higher heating value and lower heating value of an aqueous waste is insignificant relative to the difference in heating value between an aqueous waste and an organic liquid waste fuel.

[121] An F-factor is an estimate of the amount of combustion gas volume that is generated per fuel heat input for a given type of fuel, expressed in units, for example, cubic feet of combustion gas per million British thermal units (BTU) of fuel burned. In the proposal, EPA used F-factors to convert the emission standards expressed on a thermal basis to mass concentrations in order to make a judgment as to the relative stringency of the proposed MACT standards relative to the interim standards.

[122] For example, see 69 FR at 21255–258, 267–271.

[123] Although the mercury standard promulgated for cement kilns is not expressed using a thermal emission format basis, the same concept applies because the mercury standard is a hazardous waste feed concentration standard, which is a different format than the interim standard.

standards for that HAP.[124] In this case, we considered simply "capping" the standard expressed in the thermal emission format by the interim standard (*i.e.*, the promulgated standard would only be expressed in a mass concentration format). However, we conclude that this approach would not be appropriate because the standard expressed in a thermal emission format would likely be more stringent than the mass concentration for some sources, and the statute requires that MACT floors reflect this superior level of performance.

In other cases we found that the standards expressed in the thermal emissions format would not likely exceed the interim standards by the majority of sources operating under typical conditions.[125] While our analysis (based on information in our data base) shows in these cases that the emission standard expressed in a thermal emission format would not likely result in an exceedance of the interim standard, this conclusion may not be true because the assumptions may not be valid for a particular source or site-specific factors may change in future operations. For example, HAP metal emissions could increase over time due to increases in HAP contributions from raw materials or alternative raw materials. Given this potential, we adopt dual standards for the HAP metal standards in order to ensure that standards expressed in a thermal emissions format will not exceed emission levels achieved under the interim standards.[126]

Comment: Several commenters state that the interim standards do not reflect the average performance of the best sources, and so cannot be the basis for floor levels.

Response: In those few situations where we have established floor levels at the level of the interim standards, we have done so as the best means of estimating performance of the best performing sources. Based on the available data to us, the average of the best performing sources exceeds the level of the interim standards in a few instances. Under these circumstances, the binding regulatory limit becomes the best means available to us to estimate performance. See *Mossville*, 370 F. 3d at 1241–42 (accepting regulatory level as a floor standard where sources' measured performance is not a valid means of determining floor levels, and where such data contains results as high as those regulatory levels).

F. How Can EPA's Approach to Assessing Variability and its Ranking Methodologies Be Reasonable When They Result in Standards Higher Than the Interim Standards?

A commenter argued that EPA's floor methodologies, in particular its consideration of variability beyond that demonstrated in single test conditions, the SRE/feed and Air Pollution Control Device methodologies, must be arbitrary because in a few instances projected standards using these approaches were higher than the current interim standards, a level every source (not just the best performers) are achieving. Commenters also noted that one of the new source standards calculated under these approaches was higher than an existing source standard, another arbitrary result.

EPA believes that these seeming anomalies (which are infrequent) result from the database used to calculate performance and standards, rather than from the approaches to assessing variability or the two questioned floor methodologies. The data base is from test results which preceded EPA's adoption of the interim standards. Thus, the level of performance required by the later rule is not necessarily reflected in pre-rule test data. In confirmation, some of the standards computed using straight emission approaches also are higher than the interim standards. Other anomalies arise simply due to scarcity of data (floor levels for certain HAP emitted by lightweight aggregate kilns especially, where there are only nine sources total). In these situations there is a greater likelihood that one or more of the best performing sources will have relatively high emissions because we are required to use data from five sources to comprise the MACT pool whenever we have data from fewer than 30 sources, and a small amount of data can skew the result. See § 112(d)(3)(B).[127]

For example, many of the calculated new source chlorine floors were slightly higher than the calculated existing source standards because we assumed all sources with measured emissions below 20 ppmv were in fact emitting at 20 ppmv (see part four, section I.C). We generally are unable to differentiate a single best performing source among these best performers because many/all of the best performing sources emissions are adjusted to the same emission level. The calculated new source floor can be slightly higher than the existing source floor because the variability factor that is applied to the single best performing source is based on only one test condition (with three emission test runs). This results in a higher level of uncertainty relative to the existing source standard, which is based on a compilation of emissions data from several sources that have essentially the same projected emissions as a result of the method bias correction factor. The variability factor that is applied to the emissions of the single best performing source is therefore higher than the variability factor for the existing source floor because there are fewer degrees of freedom in the statistical analysis.[128] Likewise, many of the calculated solid fuel boiler new source standards were slightly higher than the calculated existing source standards because, as discussed above, there are fewer degrees of freedom when assessing the variability from a single best performing source. The solid fuel boiler "anomalies" also occur using a straight emissions methodology. See USEPA, "Technical Support Document for the HWC MACT Standards, Volume III: Selection of MACT Standards," September, 2005, Section 19, for further discussion that summarizes and explains these so-called anomalies.

[124] An example for each category is semivolatile metals thermal emissions standard for existing cement and lightweight aggregate kilns. See USEPA, "Final Technical Support Document for the HWC MACT Standards, Volume III: Selection of MACT Standards," Section 23.1, September 2005.

[125] An example is the emission standards for low volatile metals for existing and new cement kilns and new lightweight aggregate kilns. See USEPA, "Final Technical Support Document for the HWC MACT Standards, Volume III: Selection of MACT Standards," Section 23.1, September 2005.

[126] In response to a comment regarding the implementation of dual standards, we note the promulgation of a new provision allowing sources to petition the Administrator to waive the HAP metal feedrate operating parameter limits for either the emissions standards expressed in a thermal emissions format (or the mercury feed concentration standard for cement kilns) or the interim standards based on documentation that the feedrate operating parameter limit is not needed to ensure compliance with the relevant standard on a continuous basis. See new § 63.1209(g)(1)(iv) and Comment Response Document, Volume I, Section 3.5.

[127] See USEPA, "Technical Support Document for the HWC MACT Standards, Volume III: Selection of MACT Standards," September 2005, Section 19, for further discussion.

[128] For a single test condition the t factor used in variability factor calculation has n–1 degrees of freedom where n is the number of runs for that condition. For the MACT floor calculation the t factor has X–N degrees of freedom where X is the total number of runs from all sources in the MACT pool and N is the number of sources in the pool. See USEPA, "Technical Support Document for the HWC MACT Standards, Volume III: Selection of MACT Standards," September, 2005, Section 7.1 for more information on the floor calculation procedure.

IV. Use of Surrogates

A. Particulate Matter as Surrogate for Metal HAP

Comment: A commenter states that EPA's use of particulate matter as a surrogate for nonenumerated metals is unlawful and arbitrary and capricious because although particulate matter emissions may provide some indication of how good a source's end-of stack control of such metals is, it does not indicate what its actual metal emission levels are.[129] The commenter states that emissions of these metals can vary based on metal feed rate without having any appreciable effect on particulate matter emission levels. Thus a particulate matter standard does not necessarily ensure that metal emissions are reduced to the metal emission levels achieved by the relevant best performing sources. To support this assertion, the commenter states that EPA is on record saying "low particulate matter emissions do not necessarily guarantee low metal HAP emissions, especially in instances where the hazardous waste feeds are highly concentrated with metal HAP." 69 FR at 21221.

Response: The final rule uses a particulate matter standard as a surrogate to control: (1) Emissions of nonenumerated metals that are attributable to all feedstreams (both hazardous waste and remaining inputs); and (2) all nonmercury metal HAP emissions (both enumerated and nonenumerated metal HAP) from the nonhazardous waste process feeds at cement kilns, lightweight aggregate kilns, and liquid fuel boilers (e.g., emissions attributable to coal and raw material at a cement kiln, and emissions attributable to fuel oil for liquid fuel boilers). Incinerators, liquid and solid fuel boilers may elect to comply with an alternative to the particulate matter standard that would limit emissions of all the semivolatile metal HAPs and low volatile metal HAPs. See § 63.1219(e).

The particulate matter standard is a necessary, effective, and appropriate surrogate to control nonmercury metal HAPs. The record demonstrates overwhelmingly that when a hazardous waste combustor emits particulate matter, it also emits nonmercury HAP metals as part of that particulate matter, and that when particulate matter is removed from emissions the nonmercury HAP metals are removed with it.[130] Nonmercury metal HAP emissions are therefore reduced whenever particulate matter emissions are reduced. The particulate matter standard thus is an effective and appropriate surrogate that assures sources are controlling these metal HAP with an appropriate back-end control technology. *National Lime* v. *EPA*, 233 F. 3d at 639. The nonenumerated metal HAP are no different than other semivolatile or low volatile metals in that they also will be effectively controlled with a back-end particulate matter air pollution control device.

We also considered the possibility of developing a standard for nonenumerated HAP metals instead of a PM standard (*i.e.*, regulating these metals directly, rather than through use of a surrogate). We conclude for several reasons, however, that issuing emission standards for these nonenumerated metals in lieu of a particulate matter standard would not adequately control nonmercury metal HAPs to levels achieved by the relevant best performing sources.

We generally lack sufficient compliance test emissions data for the noneneumerated metals to assess the relevant best performing sources, because, as discussed below, most of these metals were not directly regulated pursuant to RCRA air emission standards.[131] Although we have more emissions data for these metals that are based on (so called) normal operations, we still lack sufficient emissions data to establish nonenumerated metal standards for all the source categories. Use of normal data may also be problematic because of the concern raised by the cement kiln and lightweight aggregate kiln stakeholders that our normal metals emissions data obtained from compliance tests are not representative of the range of actual emissions at their sources. Cement kiln and lightweight aggregate kiln stakeholders submitted long-term hazardous waste mercury feed control data that support their assertion. Although these stakeholders did not submit long-term normal hazardous waste feed control data for the nonenumerated metals, we can still see that use of the normal nonenumerated metal snapshot emissions in our database to determine MACT floors could raise similar concerns with respect to whether the normal data in fact represents average emissions at these sources, and their level of performance.

Use of particulate matter emissions data to assess the relevant best performers for nonenumerated metal HAP is therefore more appropriate for two reasons. Compliance test data better account for emissions variability and avoid the normal emissions bias discussed above. We also have much more particulate matter emissions data from more sources, which better allows us to evaluate the true range of emissions from all the sources within the source category and to assess and identify the relevant top performing 12 percent of the sources.

It would be inappropriate to assess total stack gas emissions of nonenumerated metals for cement kiln and lightweight aggregate kilns when determining the relevant best performers because these emissions would, in part, reflect the metal feed levels in these sources' nonhazardous waste process feedstreams. This is not appropriate because nonhazardous process feedstream control is not a feasible means of control. See part four, section III.B.1. A potential solution to this problem would be to identify the relevant best performers by assessing each source's hazardous waste thermal emissions for these nonenumerated metals (given that hazardous waste thermal emissions exclude by definition emissions attributable to inputs other than hazardous waste, *i.e.* raw materials and fossil fuels). This, however, would be problematic because, aside from the data limitation issues, the majority of the nonenumerated metals data reflect normal emissions which often do not contain the highest feed rates used by the source. As a result, we cannot assess performance on a thermal emissions basis because of the uncertainty associated with system removal efficiencies at such low metal feedrates. Furthermore, even if we could issue hazardous waste thermal emissions standards for these metals, a particulate matter emission standard would still be necessary to control nonmercury metal HAP emissions from the nonhazardous waste process feedstreams.

[129] "Enumerated" metals are those HAP metals directly controlled with an emission limit, *i.e.*, lead, cadmium, chromium, arsenic and beryllium. The remaining nonmercury metal HAP (*i.e.*, antimony, cobalt, manganese, nickel, and selenium) are called "nonenumerated" metal HAP (note that arsenic and berrylium are nonenumerated metals for liquid fuel boilers because the low volatile metal emission standard applies only to chrome).

[130] This statement is equally true for any emitting source, not just hazardous waste combustors. It is well established that semivolatile and low volatile metals exist in solid particulate form at typical air pollution control device operating temperatures. This is supported by (1) known operating temperature ranges of air pollution control devices used by hazardous waste combustors; (2) known metal volatility equilibrium relationships; and (3) extensive technical literature. See USEPA, "Technical Support Document for the HWC MACT Standards, Volume III: Selection of MACT Standards," September 2005, Section 3.1.

[131] At best, we may have enough compliance test data for antimony and selenium to adequately assess relevant best performers for only incinerators and lightweight aggregate kilns.

Emission standards for these nonenumerated metals could require sources to implement hazardous waste feed control (for these metals) to comply with the standard.[132] We are less assured that these sources were implementing hazardous waste feed control for these nonenumerated metals at the time they conducted the emissions tests (which serve as the basis for floor calculations) because most of these metals were never directly regulated pursuant to the RCRA emission standards.[133] This means that sources tended to optimize (or at least concentrate their efforts on) control of the metals that are regulated. Although these metals were being controlled with each source's back-end control device, sources may not have been controlling these metal feedrates because they probably were not subject to specific feedrate limitations (feed control of the enumerated metal HAP does not ensure feed control of these nonenumerated metal HAP). Furthermore, simultaneous feed control of all these metals, when combined with enumerated semivolatile and low volatile metals, may not be possible because the best performing sources for all these metals may collectively represent a hazardous waste feedstream that does not exist in practice (from a combined metal concentration perspective) because there likely would be different best performers for each of the metal HAP or metal HAP groups.[134] We thus conclude that back-end control as measured and assessed by each source's particulate matter emissions is the appropriate floor technology to assess when identifying the relevant best performers for nonenumerated HAP metals and estimating these sources' level of performance.

Comment: A commenter states that EPA's rationale for use of particulate matter as a surrogate for nonenumerated metals is flawed because EPA has provided no data in the proposal to justify its hypothesis that particulate matter is an appropriate surrogate for non-enumerated metal HAP. The commenter also states that the proposed emission standards for particulate matter for existing sources discriminate against boilers and process heaters that burn clean (*i.e.*, little or very low concentrations of HAP metals) hazardous waste fuels. The commenter suggests that if there are sufficient data, EPA should consider developing an alternative emission standard for total HAP metals for new and existing liquid fuel boilers, as was done for the Subpart DDDDD National Emission Standards for Hazardous Air Pollutants for Industrial/Commercial/Institutional Boilers and Process Heaters.

Response: As previously discussed in this section, particulate matter reflects emissions of nonmercury metal HAPs because these compounds comprise a percentage of the particulate matter (provided these metals are fed into the combustion unit). The technologies that have been developed and implemented to control particulate matter also control nonmercury metal HAP. Since nonmercury metal HAP is a component of particulate matter, we can use particulate matter as a surrogate for these metals. Further justification for the use of particulate matter as a surrogate to control metal HAP is included in the technical support document.[135]

We conclude that we do not have enough nonenumerated metal emissions data to calculate alternative total metal emission floors for liquid fuel boilers. The most problematic of these metals are manganese and cobalt, where we have emission data from only three sources. We have much more compliance test particulate matter emissions data from liquid fuel boilers, and thus conclude that the particulate matter standard best reflects the emission levels achieved by the relevant best performers.

Similar to the above discussion, calculating an alternative total metal emissions floor raises questions regarding the method used to calculate such floors. Hazardous waste combustor metal emissions have traditionally been regulated in volatility groupings because the volatility of the metal affects the efficiency of back-end control (*i.e.*, semivolatile metals are more difficult to control than low volatile metals because they volatilize in the combustor and then condense as small particulates prior to or in the emission control device). When identifying the best performing sources, we previously have, in general, only evaluated sources that have metal emissions information for every metal in the volatility grouping. This approach could prove to be problematic since it is not likely many sources will have emissions data for all the metals.

Although we could not calculate alternative total metal emission floor standards based on the available emissions data we have, we agree with the commenters' view that sources that burn hazardous waste fuels with low levels of nonenumerated metals should be allowed to comply with a metals standard rather than the particulate matter standard. We proposed an alternative to the particulate matter standard (see 69 FR at 21331) for incinerators, liquid, and solid fuel boilers that was a simplified version of the alternative particulate matter standard that is currently in effect for incinerators pursuant to the interim standards (see § 63.1206(b)(14)). We received no adverse comment and are promulgating this alternative as proposed. The alternative metal standards apply to both enumerated and nonenumerated metal HAP, excluding mercury. For purposes of these alternative requirements, each nonenumerated metal is classified as either a semivolatile or a low volatile metal and subsequently grouped with the associated semivolatile and low volatile enumerated metals. The semivolatile and low volatile metals standards under this alternative are the same as those that apply to other liquid fuel boilers, but the standard would apply to all metal HAP, not just those enumerated in the generic low volatile metal and semivolatile metal standards. See §§ § 63.1216(e), 63.1217(e) and 63.1219(e).

B. Carbon Monoxide/Hydrocarbons and DRE as Surrogates for Dioxin/Furan

Comment: One commenter states that the dioxin/furan floors for new and existing solid fuel boilers is unlawful and arbitrary and capricious. EPA established the floor for dioxin/furan for these sources as compliance with the carbon monoxide or hydrocarbon standard and the destruction and removal efficiency (DRE) standard. The

[132] Sources that otherwise would be equipped with what is considered to be a MACT back-end control devices (*i.e.*, a control device achieving the final rule particulate matter standard) may not be able to achieve these metal emissions standards due to varying metal feed levels (both within sources and across sources). Such an outcome may require a source to limit the amount of metal that is fed into the combustion unit to achieve the standard.

[133] Antimony is the only nonenumerated metal that is directly regulated pursuant to the boilers and industrial furnace regulations. See § 266.106.

[134] We generally cannot combine these nonenumerated metals into the associated semivolatile or low volatile metal volatility groupings promulgated in this final rule for purposes of establishing "grouped" emission standards because we cannot mix compliance test data with normal emissions data when calculating floors (the majority of the standards included in this final rule are based on compliance test data, and the majority of the data we have for nonenumerated metals being normal). Furthermore, if we were to separately group the normal nonenumerated metal emission data into their associated semivolatile or low volatile metal group, we may encounter data limitation issues because each source would need to have measured each of the nonenumerated metals in that associated metal volatility group in order for us to conclude that the emission data adequately represents the sources combined emissions of semivolatile or low volatile metals.

[135] See USEPA, "Technical Support Document for the HWC MACT Standards, Volume III: Selection of MACT Standards," September 2005, Section 3.1.

commenter states that EPA has not shown that carbon monoxide or hydrocarbon emissions correlate to dioxin/furan emissions, and, accordingly, has not shown that the carbon monoxide or hydrocarbon standard, together with the DRE standard, are valid surrogates.

This commenter also states that it is inappropriate for EPA to use carbon monoxide or hydrocarbons and DRE as surrogates to establish dioxin/furan floors for liquid fuel boilers with wet or no air pollution control devices and for hydrochloric acid production furnaces. The commenter believes EPA inappropriately justifies these surrogates by claiming that a numerical dioxin/furan floor would not be replicable by the best sources or duplicable by the others. The commenter states that EPA has no discretion to avoid setting floors for a HAP just because it believes that HAP is not controlled with a technology. Rather, EPA must set floors reflecting the relevant best sources' actual performance. Such floors necessarily will be duplicable by the relevant best sources themselves. That they cannot be replicated by other sources is irrelevant according to the commenter.

In addition, the commenter states that EPA does not claim or demonstrate that the carbon monoxide and hydrocarbon floors for solid fuel boilers reflect the average emission levels achieved by the relevant best sources.

Finally, the commenter also notes that EPA appears to argue that its carbon monoxide or hydrocarbon standard and DRE standard could be viewed as work practice standards under section 112(h) which allows EPA to establish work practice standards in lieu of emission standards only if it is not be feasible to set the former. Because EPA has made no such demonstration, setting work practice standards to control dioxin/furan emissions from boilers would be unlawful according to the commenter.

Response: The commenter raises four issues: (1) Are the carbon monoxide/hydrocarbon standard and the DRE standard adequate surrogate floors to control dioxin/furan; (2) floors for existing sources must be established as the average emission limitation achieved by the best performing sources irrespective of whether the limitation is duplicable by the best performing sources or replicable by other sources; (3) EPA has not explained how the carbon monoxide and hydrocarbon floors reflect the average emission limitation achieved by the relevant best sources; and (4) EPA cannot establish work practice standards for dioxin/furan under section 112(h) because it has not demonstrated that setting an emission standard is infeasible under section 112(h)(1).

Carbon Monoxide and Hydrocarbons Are Adequate Surrogates to Control Dioxin/Furan when Other Controls Are Not Effective or Achievable. Carbon monoxide and hydrocarbons (coupled with the DRE standard) are the best available surrogates to control dioxin/furan emissions when a numerical floor would not be achievable and when other indirect controls, such as control of the gas temperature at the inlet of a dry particulate matter control device to 400F, are not applicable or effective.[136]

As we explained at proposal, operating under good combustion conditions to minimize emissions of organic compounds such as polychlorinated biphenyls, benzene, and phenol that can be precursors to dioxin/furan formation is an important requisite to control dioxin/furan emissions.[137] See 69 FR at 21274. Minimizing dioxin/furan precursors by operating under good combustion practices plays a part in controlling dioxin/furan emissions, and that role is substantially enhanced when there are no other dominant factors that relate to dioxin/furan formation and emission (e.g., operating a dry particulate matter control device at temperatures above 400F).

Carbon monoxide and hydrocarbons are widely accepted indicators of combustion conditions. The current RCRA regulations for boilers and hydrochloric acid production furnaces use emissions limits on carbon monoxide and hydrocarbons to control emissions of toxic organic compounds. See 56 FR 7150 (February 21, 1991) documenting the relationship between carbon monoxide, combustion efficiency, and emissions of organic compounds. In addition, carbon monoxide and hydrocarbons are used by many CAA standards for combustion sources to control emissions of organic HAP, including: MACT standards for hazardous waste burning incinerators, hazardous waste burning cement kilns, hazardous waste burning lightweight aggregate kilns, Portland cement plants, and industrial boilers; and section 129 standards for commercial and industrial waste incinerators, municipal waste combustors, and medical waste incinerators. Finally, hydrocarbon emissions are an indicator of organic hazardous air pollutants because hydrocarbons are a direct measure of organic compounds.

Commenters on our proposed MACT standards for hazardous waste incinerators, cement kilns, and lightweight aggregate kilns stated that EPA's own surrogate evaluation[138] did not demonstrate a relationship between carbon monoxide or hydrocarbons and organic HAP at the carbon monoxide and hydrocarbon levels evaluated. See 64 FR at 52847 (September 30, 1999). Several commenters on that proposed rule noted that this should not have been a surprise given that the carbon monoxide and hydrocarbon emissions data evaluated were generally from hazardous waste combustors operating under good combustion conditions (and thus, relatively low carbon monoxide and hydrocarbon levels). Under these conditions, emissions of HAP were generally low, which made the demonstration of a relationship more difficult. These commenters noted that there may be a correlation between carbon monoxide and hydrocarbons and organic HAP, but it would be evident primarily when actual carbon monoxide and hydrocarbon levels are higher than the regulatory levels. We agreed with those commenters, and concluded that carbon monoxide and hydrocarbon levels higher than those we established as emission standards for hazardous waste burning incinerators, cement kilns, and lightweight aggregate kilns are indicative of poor combustion conditions and the potential for increased emissions organic HAP. We continue to believe that carbon monoxide and hydrocarbons are adequate surrogates for organic HAP which may be precursors for dioxin/furan formation and note that the commenter did not explain why our technical analysis is problematic.

Emissions that Are Not Replicable or Duplicable Are Not Being "Achieved". The commenter believes that floors must be established as the average emission limitation of the best performing sources irrespective of whether they are replicable by the best performing sources or duplicable by other sources. To the contrary, emission

[136] As discussed in Part Two, Section V, we view the carbon monoxide, hydrocarbon, and destruction removal efficiency standards as unaffected by the Court's vacature of the September 1999 challenged regulations for incinerators, cement kilns, and lightweight aggregate kilns. We are therefore not re-promulgating and reopening consideration of these standards in today's final rule for these source categories.

[137] Operating under good combustion conditions also helps minimize soot formation on boiler tubes. Research has shown that operating under conditions that can form soot followed by operating under good combustion conditions can lead to dioxin/furan formation. See Section 2.4 of Volume III of the Technical Support Document.

[138] See Energy and Environmental Research Corporation, "'Surrogate Evaluation of Thermal Treatment Systems,'" Draft Report, October 17, 1994.

levels that are not replicable by the best performing sources are not being "achieved" by those sources and cannot be used to establish the floor.

For solid fuel boilers, we explained at proposal why dioxin/furan emissions are not replicable by the best performing sources (or duplicable by other sources): there is no dominant, controllable means that sources are using that can control dioxin/furan emissions to a particular level. See 69 FR at 21274–75. We explained that data and information lead us to conclude that rapid quench of post-combustion gas temperatures to below 400 °F—the control technique that is the basis for the MACT standards for dioxin/furan for hazardous waste burning incinerators, and cement and lightweight aggregate kilns—is not the dominant dioxin/furan control mechanism for coal-fired boilers. We believe that sulfur contributed by the coal fuel is a dominant control mechanism by inhibiting formation of dioxin/furan. Nonetheless, we do not know what minimum level of sulfur provides significant control. Moreover, sulfur in coal causes emissions of sulfur oxides, a criteria pollutant, and particulate sulfates. For this reason, as well as reasons stated at 69 FR 21275, we are not specifying a level of sulfur in coal for these sources as a means of dioxin/furan control.

The same rationale applies to liquid fuel boilers with no air pollution controls or wet air pollution control systems and to hydrochloric acid production furnaces—there is no dominant, controllable means that sources are using that can control dioxin/furan emissions to a particular emission level.[139] Thus, best performer dioxin/furan emissions are not replicable by the best performing sources (or duplicable by other sources). For these sources, the predominant dioxin/furan formation mechanism for other source categories—operating a fabric filter or electrostatic precipitator above 400F—is not a factor.

Given that these sources are not using controllable means to control dioxin/furan to a particular emission level, there is no assurance that the best performers can achieve in the future the emission level reported in the compliance test in our data base. Put another way, the test data do not reflect these sources' variability, and the variability is largely unquantifiable given the uncertainties regarding control mechanisms plus the environmental counter-productiveness of encouraging use of higher sulfur coal. Hence, that reported emission level is not being "achieved" for the purpose of establishing a floor.

Finally, we note that beyond-the-floor controls such as activated carbon can control dioxin/furan to a particular emission level. If a source were to install activated carbon, it could achieve the level demonstrated in a compliance test, after adjusting the level to account for emissions variability to ensure the measurement was replicable. The commenter argues that such a result is mandatory under the straight emissions approach (the only way the commenter believes best performers can be determined). Doing so, however, would amount to a surreptitious beyond-the-floor standard (forcing adoption of a control technology not used by any existing source), without considering the beyond-the-floor factors set out in section 112(d)(2). In fact, we considered beyond-the-floor standards based on use of activated carbon for these sources—solid fuel boilers, liquid fuel boilers with wet or no emission control device, and hydrochloric acid production furnaces—but rejected them for reasons of cost. The cost-effectiveness ranged from $2.5 million to $4.9 million per gram TEQ of dioxin/furan removed. In contrast, the cost-effectiveness of the beyond-the-floor standard we promulgate for liquid fuel boilers equipped with dry emission control devices is $0.63 million per gram TEQ of dioxin/furan removed.[140]

Consequently, we are not promulgating a beyond-the-floor standard for dioxin/furan for these sources, and do not believe we should adopt such a standard under the guise of determining floor levels.

The Carbon Monoxide and Hydrocarbon Floors Are Appropriate MACT Floors. We explained at proposal why the carbon monoxide standard of 100 ppmv and the hydrocarbon standard of 10 ppmv are appropriate floors. See 69 FR at 21282. The floor level for carbon monoxide of 100 ppmv is a currently enforceable Federal standard. Although some sources are achieving carbon monoxide levels below 100 ppmv, it is not appropriate to establish a lower floor level because carbon monoxide is a conservative surrogate for organic HAP. Organic HAP emissions may or may not be substantial at carbon monoxide levels greater than 100 ppmv, and are extremely low when sources operate under the good combustion conditions required to achieve carbon monoxide levels in the range of zero to 100 ppmv.[141] (See also the discussion below regarding the progression of hydrocarbon oxidation to carbon dioxide and water). As such, lowering the carbon monoxide floor below 100 ppmv may not provide significant reductions in organic HAP emissions. Moreover, it would be inappropriate to establish the floor blindly using a mathematical approach—the average emissions for the best performing sources—because the best performing sources may not be able to replicate their emission levels (and other sources may not be able to duplicate those emission levels) using the exact types of good combustion practices they used during the compliance test documented in our data base. This is because there are myriad factors that affect combustion efficiency and, subsequently, carbon monoxide emissions. Extremely low carbon monoxide emissions cannot be assured by controlling only one or two operating parameters.

We proposed a floor level for hydrocarbons of 10 ppmv even though the currently enforceable standard for boilers and hydrochloric acid production furnaces is 20 ppmv because: (1) Although very few sources elect to comply with the RCRA standard for hydrocarbons rather than the standard for carbon monoxide, those that comply with the hydrocarbon standard have hydrocarbon levels well below 10 ppmv; and (2) reducing hydrocarbon emissions within the range of 20 ppmv to 10 ppmv may reduce emissions of organic HAP.

Although all sources are likely to be achieving hydrocarbon levels below 10 ppmv, it is not appropriate to establish a lower floor level because hydrocarbons are a surrogate for organic HAP. Although total hydrocarbons would be reduced at a floor level below 10 ppmv, we do not know whether

[139] We note that the same rationale also applies to incinerators with wet or no air pollution control equipment and that are not equipped with a waste heat boiler.

[140] See USEPA, "Technical Support Document for the HWC MACT Standards, Volume III: Selection of MACT Standards," September 2005, Sections 12, 13, and 15.

[141] We note, however, that this general principle may not always apply. There are data that indicate that even though carbon monoxide levels are below 100 ppmv, hydrocarbon levels may not always be below 10 ppmv. See 64 FR at 52851 and Part Four, Section IV B. and C. of this preamble. An example of how this might occur, although not a likely practical scenario, is if combustion is quenched before substantial carbon monoxide can be generated, leaving unburned hydrocarbons in the stack gas. Because of this potential (although unlikely) concern, the rule requires sources that elect to monitor carbon monoxide rather than hydrocarbons to conduct a one-time test to document that hydrocarbons are below 10 ppmv and to establish operating limits on parameters that affect combustion conditions (i.e., the same operating parameters that we use for compliance assurance with the DRE standard). See § 63.1206(b)(6).

organic HAP would be reduced substantially. As combustion conditions improve and hydrocarbon levels decrease, the larger and easier to combust compounds are oxidized to form smaller compounds that are, in turn, oxidized to form carbon monoxide and water. As combustion continues, carbon monoxide is then oxidized to form carbon dioxide and water. Because carbon monoxide is a difficult-to-destroy refractory compound (*i.e.*, oxidation of carbon monoxide to carbon dioxide is the slowest and last step in the oxidation of hydrocarbons), it is a conservative surrogate for destruction of hydrocarbons, including organic HAP, as discussed above. As oxidation progresses and hydrocarbon levels decrease, the larger, heavier compounds are destroyed to form smaller, lighter compounds until ideally all hydrocarbons are oxidized to carbon monoxide (and then carbon dioxide) and water. Consequently, the relationship between total hydrocarbons and organic HAP becomes weaker as total hydrocarbon levels decrease to form compounds that are not organic HAP, such as methane and acetylene.[142]

Moreover, as discussed above for carbon monoxide, it would be inappropriate to establish the floor blindly using a mathematical approach—the average emissions for the best performing sources—because the best performing sources may not be able to replicate their emission levels (and other sources may not be able to duplicate those emission levels) using the exact types of good combustion practices they used during the compliance test documented in our data base. This is because there are myriad factors that affect combustion efficiency and, subsequently, hydrocarbon (and carbon monoxide) emissions. Extremely low hydrocarbon emissions cannot be assured by controlling only one or two operating parameters.

The Standards for CO and HC Are Not Work Practice Standards. The floor standards for CO or HC for boilers and hydrochloric acid production furnaces are quantified emission limits. The standards consequently are not work practice standards (even though they represent levels showing good combustion control). CAA section 302(k). EPA's reference to section 112(h)(1) at proposal (69 FR at 21275) was consequently erroneous.

[142] USEPA, Technical Support Document for HWC MACT Standards, Volume III: Selection of MACT Standards and Technologies, July 1999, Section 12.1.2.

C. Use of Carbon Monoxide and Total Hydrocarbons as Surrogate for Non-Dioxin Organic HAP[143]

Comment: A commenter states that neither the total hydrocarbon nor carbon monoxide standard alone provides adequate surrogate control for organic HAP. Accordingly, EPA must include standards for both. Hazardous waste combustors could have total hydrocarbon levels below the standard during the carbon monoxide compliance tests, but higher total hydrocarbon levels at other times during normal operation because there are many variables that can affect total hydrocarbon emissions, and these will not all be represented during the carbon monoxide compliance test. The commenter states that EPA is on record stating that carbon monoxide limits alone may not by itself minimize organic emissions because products of incomplete combustion can result from small pockets within the combustion zone where adequate time, temperature, turbulence and oxygen have not been provided to completely oxidize these organics. The commenter also states that EPA is on record stating that total hydrocarbon levels can exceed good combustion condition levels when carbon monoxide levels are below 100 ppmv.

Response: The final rule requires compliance with destruction and removal efficiency and carbon monoxide or hydrocarbon standards as surrogates to control non-dioxin organic HAP emissions[144] from liquid fuel boilers, solid fuel boilers, and hydrochloric acid production furnaces. These are effective and reliable surrogates to control organic HAP. We conclude that simultaneous measurement of both total hydrocarbons and carbon monoxide with continuous emission monitors is not necessary because each serves as a reliable surrogate to control organic HAP emissions. The commenter has cited EPA preamble language that was included in the April 19, 1996 proposed rule for hazardous waste incinerators, cement kilns, and lightweight aggregate kilns. In that rule we proposed to require compliance with both the total hydrocarbon standard and the carbon monoxide standard. We requested comment on whether these requirements were redundant, and we later requested comment on whether we should allow sources to comply with either the carbon monoxide standard or the total hydrocarbon standard. We clarified, however, that allowing sources to comply with the carbon monoxide standard would be contingent on the source demonstrating compliance with the hydrocarbon standard during the compliance test. We believed this was necessary because we had limited data that showed a source could have total hydrocarbon levels exceeding 10 ppmv even though their carbon monoxide emission levels were below 100 ppmv. EPA subsequently promulgated this approach in the September 1999 Final Rule. 62 FR 52829.

Today's rule adopts the same approach for liquid and solid fuel boilers and hydrochloric acid production furnaces. We again conclude that it is not necessary to require sources to verify compliance with both of these standards on a continuous basis with two separate continuous emission monitors, given the redundancy of these measurement techniques. Total hydrocarbon emission measurements are a more direct indicator of organic HAP emissions than carbon monoxide. Hence, continuous compliance with this standard always assures that organic HAP are well controlled. Carbon monoxide is a conservative indicator of combustion efficiency because it is a product of incomplete combustion and because it is a refractory compound that is more thermally stable than hydrocarbons. The hydrocarbon products of incomplete combustion that are simultaneously formed during incomplete, or inefficient, combustion conditions can be subsequently oxidized later in the combustion process. In such instances carbon monoxide will likely still be prevalent in the exhaust gas even though the products of incomplete combustion were later oxidized. The conservative nature of carbon monoxide as an indicator of good combustion practices is supported by our data. At carbon monoxide levels less than 100 ppmv, our data indicates that there is no apparent relationship between carbon monoxide and hydrocarbons (other than that hydrocarbon levels are generally below 10 ppm when carbon monoxide levels are below 100 ppm). For example, a source with a carbon monoxide level of 1 ppm is no more likely to have lower

[143] As discussed in part two, section V, we view carbon monoxide, hydrocarbon, and destruction removal efficiency standards as unaffected by the Court's vacature of the September 1999 challenged regulations for incinerators, cement kilns, and lightweight aggregate kilns. We are therefore not re-promulgating and did not reconsider these standards in today's final rule for these source categories.

[144] As discussed in the previous section, these standards are also used as surrogates to control dioxin/furans for hydrochloric acid production furnaces, solid fuel-fired boilers, and liquid fuel-fired boilers that are not equipped with dry air pollution control devices.

measured hydrocarbons than a source achieving a carbon monoxide emission level of 100 ppm.[145]

We consider the few instances where the data showed total hydrocarbon levels above 10 ppmv while carbon monoxide levels are below 100 ppmv to be anomalies. Even so, we have accounted for this by requiring compliance with the hydrocarbon standard during the compliance test if a source elects to comply with the carbon monoxide standard. See §§ § 63.1216(a)(5)(i), 1217(a)(5)(i), and 1218(a)(5)(i).

We disagree with the commenter's assertion that the total hydrocarbon compliance demonstration during the compliance test is insufficient. Sources are required to establish numerous operating requirements based on operating levels that were demonstrated during the test, including minimum operating temperature, maximum feed rates, minimum combustion zone residence time, and operating requirements on the hazardous waste firing system that control liquid waste atomization efficiency. Sources must comply with these operating requirements on a continuous basis. Compliance with these requirements, in addition to the requirements to comply with the carbon monoxide and destruction and removal standards, adequately assure sources are controlling organic HAP emissions to MACT levels.

Comment: A commenter states that EPA's proposed use of surrogates for organic HAP do not ensure that each of the organic HAP (e.g., polychlorinated biphenyls and polyaromatic hydrocarbons) are reduced to the level of the HAP emitted by the relevant best performing sources. EPA has not shown the necessary correlation between either the total hydrocarbon or carbon monoxide standards and organic HAP, and neither is a reasonable surrogate according to the commenter.

Response: Carbon monoxide and total hydrocarbon monitoring are widely used and accepted indicators of combustion efficiency, and hence control organic HAP, which are destroyed by combustion.[146] Sources that are achieving carbon monoxide of emission levels of 100 ppm or a hydrocarbon emission levels of 10 ppm are known to be operating pursuant to good combustion practices. This is supported by an extensive data analysis we used to support identical standards for incinerators, cement kilns, and lightweight kilns which were promulgated in the September 1999 Final Rule. We are applying the same rationale to support these standards for boilers and hydrochloric acid production furnaces.

Today's rule requires continuous compliance with either a carbon monoxide and hydrocarbon standard, in combination with a destruction and removal efficiency standard, as surrogates to control organic HAP. We conclude that sources which comply with these standards are operating under efficient combustion conditions, assuring non-dioxin organic HAP are being oxidized, thus limiting emissions to levels reflecting MACT. Efficient combustion of hazardous waste minimizes emissions of organic HAP that are fed to the combustion chamber as well as emissions attributable to products of incomplete combustion that may form within the combustion chamber or post combustion. We are not capable of issuing emission standards for each organic HAP because of data limitations and because such emission standards may not be replicable by individual sources or duplicable by the other best performing sources because of the complex nature of combustion and post combustion formation of products of incomplete combustion.

V. Additional Issues Relating to Variability and Statistics

Many commenters raised issues relating to emissions variability and statistics other than those discussed above in Section III.A: (1) Variability dampening for data sets containing nondetects; (2) imputation of variability to address variability dampening for data sets containing nondetects; and (3) our analysis of variance procedures to identify subcategories. We present comments and responses on the remaining topics below.

A. Data Sets Containing Nondetects

Comment: One commenter states that EPA's approach of assuming measurements that are below detection limits are present at the detection limit dampens the variability of the data set. Thus, the variability of ranking parameters is understated when ranking sources to identify the best performers and emissions variability is understated when calculating the floor.

Response: We agree with the commenter. For the final rule, we use an approach to address nondetects whereby a value is assigned to each nondetect within its possible range such that the 99th percentile upper prediction limit for the data set (i.e., test condition runs for each source) is maximized. Although this approach maximizes the deviation among runs containing nondetect measurements, the test condition average is lower because we no longer assume the nondetect analyte is present at the level of detection. See response to comments discussion below for more information on this statistical approach to address variability of nondetects.

We use this measurement imputation approach to address variability of feedrate data sets containing nondetects for source ranking purposes and to address variability of emissions data sets containing nondetects when calculating floors. We do not apply the measurement implementation approach to system removal efficiency (SRE) data sets where feedrates or emissions contain nondetects, however. Statistical imputation of nondetect SREs is complicated given that SRE is derived from feedrate and emissions data, both of which could contain nondetect measurements.[147] Our inability to apply the imputation approach to SREs is not a major concern, however, because system removal efficiency is used as a source ranking criterion only (i.e., it is not used as the standard, except for hydrochloric acid production furnaces where there are no nondetect feedrate or emissions measurements), and there are few instances where system removal efficiencies are derived from nondetect feedrate or emissions data.

B. Using Statistical Imputation To Address Variability of Nondetect Values

On February 4, 2005, EPA distributed by email to major commenters on the proposed rule a direct request for comments on a limited number of issues that were raised by the public comments on the proposed rule. The nondetect measurement imputation approach discussed above was one of the issues for which we requested comment. We discuss below the major comments on the approach.

Comment: Most commenters state that they agree with either the concept or the approach in principle but cannot

[145] See USEPA, "Technical Support Document for the HWC MACT Standards, Volume III: Selection of MACT Standards," September 2005, Section 3.2 and USEPA, "Final Technical Support Document for the HWC MACT Standards, Volume III: Selection of MACT Standards and Technologies," July 1999, Section 5.1.

[146] This is why almost all of the RCRA Land Disposal Restiction treatment standards for organic waste, which standards are for the most part established at an analytic detection level for the organic HAP in question plus a variability factor, are based on the performance of combustion technology. See 40 CFR Part 268.40–43.

[147] See USEPA, "Technical Support Document for the HWC MACT Standards, Volume III: Selection of MACT Standards," September 2005 Section 7.3.

provide substantive comments. These commenters indicate they cannot provide substantive comments because they cannot determine the implications of using the approach given that we did not provide the resulting floor calculations. One commenter suggests that, before blindly applying this arbitrary estimate of a nondetect value, a reality check should be done to validate that this is reasonable by consulting what is published on the method variability, as well as by checking variability factors derived for other data in the database that are above the detection limit.

Another commenter voiced significant concerns with the approach. The commenter states that EPA contradicts its assumption at proposal that all data that are reported as nondetect are present at the detection limits by now admitting that the true value is between zero and the level of detection. The commenter concludes that EPA now proposes to retreat from its assumption that undetected pollutants are always present at the detection limits not because that assumption is false but because it does not generate sufficiently lenient floors. The commenter believes that this underscores that EPA's statistical analysis approach cannot possibly give an accurate picture of *any* source's actual emission levels. Accordingly, it cannot possibly satisfy EPA's obligation to ensure that its floors reflect the average emission levels achieved by the relevant best performing sources.

The commenter also states that EPA's imputation approach is independently flawed because it assumes—again inaccurately—that the value for a nondetect is always either the highest value or lowest value in the allowable range. In reality the undetected values will necessarily fall in a range between the highest and lowest, and thus yield less variability than EPA would assume.

Response: We agree in theory with the commenter who suggests that the results of the imputation approach should be checked to see if it overstates variability for nondetect data by comparing the results of the imputation approach with the actual variability for detected measurements in the data set. We considered comparing the relative standard deviation derived from the imputation approach for data sets with nondetects, to the relative standard deviation for the data set using a regression analysis. Under the regression analysis approach, we considered relating the relative standard deviation of detected data sets to the average measurement. We would determine this relationship for each standard for which we have nondetect data, and use the relationship to impute the standard deviation for a data set containing nondetects.[148]

We could not perform this analysis, however, because: (1) We have very few detected measurements for the data sets for several standards and could not establish the relationship between relative standard deviation and emission concentration for those data sets; and (2) moreover, for many data sets where detected measurements would have been adequate to establish the relationship, it would have been problematic statistically to extrapolate the relationship to the very low values assigned to the nondetect measurements (e.g., 100% of the detection limit; the value assigned by our statistical imputation approach).[149]

This commenter also suggests that we check the resultant standard deviation after imputation by consulting what is published on the method variability. The commenter did not explain, however, how method variability relates to the variability of nondetect data.

Moreover, we believe that the imputation approach is one approach we could have reasonably used to estimate variability of nondetect data. We first attempted to apply standard statistical techniques to address the nondetect issue. We investigated standard interval censoring techniques to calculate maximum likelihood estimates (MLE) of the average and standard deviation that provide the best fit for a normal distribution for the data containing nondetect values, taking into account that each nondetect data point can be anywhere within its allowable interval. These techniques are not applicable, however, to data sets where all data are nondetects, as is the case for many of our data sets. In that situation, we approximated the mean as the average of the midpoints of the nondetect intervals, and the standard deviation as one half of the possible range of the data.

After working with this MLE/Approximation approach for some time and iteratively developing complicated algorithms to address problems as they arose, we concluded that we needed a simpler approach that could be applied to all data sets. Accordingly, we developed the statistical imputation approach discussed in Section IV.A above.

For 22 separate floors, we compared the results of the approaches we considered for nondetects: (1) Nondetects present at the detection limit (i.e., full detection limit approach); (2) MLE; (3) MLE combined with an approximation approach (i.e., MLE/Approximation approach; and (4) statistical imputation.[150] The MLE approach was only applicable to 2 of the 22 floor data sets, and the numerical algorithm failed to converge on an answer for one of those. The MLE/Approximation approach sometimes results in floors that are unrealistically high (i.e., it calculated 5 of 22 floors that were higher than the statistical imputation approach, which always produces floors that are equal to or higher than assuming nondetects are present at the full detection limit), and sometimes fails to converge on an answer. Because of these limitations, we do not use either the MLE or MLE/Approximation approach.

We believe the statistical imputation approach is preferable to the full detection limit approach because it: (1) Accounts for variability of data sets containing nondetects; (2) can be applied to all data sets containing nondetects; and (3) results in reasonable floor levels. In most cases, floors calculated using statistical imputation are close to those calculated by the full detection limit approach. The statistical imputation approach can produce substantially higher floors than the full detection limit approach, however, when a relatively high nondetect is reported because of a high detection limit. Nonetheless, the statistical imputation approach calculated floors that were 30% higher than the full detection limit approach for only 2 of the 22 floors.

We reject the comment that our approach to handling nondetect data is a mere manipulation to raise the floor. The commenter observes that EPA appears to determine that its initial approach of assuming the worst-case for nondetect data—that the data are present at the detection limit—did not produce floors that were high enough, and consequently applies another manipulation—statistical imputation of nondetect measurements—that assumes the nondetect data are present at lower levels but nonetheless generates floors that are even higher than before. Although the commenter is correct

[148] Note that, under this approach, we would continue to assume that the nondetect analyte is present at the detection limit.

[149] Note that this was not the case where we use a regression analysis of relative standard deviation versus total chlorine measurements to impute a standard deviation for values below 20 ppmv that we corrected to 20 ppmv to address the low bias of Method 0050. In that situation, we have several total chlorine measurements very close to 20 ppmv.

[150] See USEPA, "Technical Support Document for the HWC MACT Standards, Volume III: Selection of MACT Standards," September 2005, Section 5.4.

about the outcome of our handling of nondetect data the floors are generally higher after statistically imputing nondetect measurements than if nondetects are simply assumed to be present at the detection limit—our rationale for handling nondetects is sound. At proposal, we assumed that nondetects are present at the detection limit. We do not know (nor does anyone else) whether a nondetect value is actually present at 1% or 99% of the detection limit. We thought that assuming that all values were at the limit of detection would reasonably estimate the range of performance a source could experience for these nondetect measurements. This approach inherently maximizes the average emissions but minimizes emissions variability.

Commenters on the proposed rule state that assuming nondetects are present at the detection limit dampens emissions variability—a consideration necessary to ensure that a source's performance over time is estimated reasonably. *Mossville*, 370 F. 3d at 1242 (daily maximum variability must be accounted for in MACT standards [including floors] which must be achieved continuously). See also *CMA*, 870 F. 2d at 232 (EPA not even obligated to use data from plants that consistently reported nondetected values in calculating variability factors for best performing plants). We agree with these commenters, and are using the statistical imputation approach to address the concern. Relative to our proposed approach of assuming nondetect measurements are present at the detection limit, the statistical imputation approach reduces the average of the data set for a source while maximizing the deviation of the data set. These are competing and somewhat offsetting factors when calculating the floor for existing sources given that we use a modified 99th percentile upper prediction limit to calculate the floor—the floor is the average of the test condition averages for the best performers plus the pooled variance of their runs. See *CMA*, 870 F. 2d at 232 (upholding approach to variability for datasets with nondetect values where various conservative assumptions in methodology offset less conservative assumptions).

We further disagree with this commenter's view that the statistical imputation approach is independently flawed because it assumes that the value for a nondetect is always either the highest value or lowest value in the allowable range. The commenter states that, in reality, the undetected values will necessarily fall in a range between the highest and lowest, and thus yield less variability than EPA would assume. Although the commenter is correct that the true value of a nondetect measurement is likely to be in the range between the highest or lowest value possible rather than at either extreme, we do not know where the true value is within that range. To ensure that variability is adequately considered in establishing a floor, the statistical imputation approach, by design, maximizes the deviation by assuming the nondetect value is at one end of the range or the other, whichever results in a higher average for the data set.

C. Analysis of Variance Procedures To Assess Subcategorization

We use analysis of variance (ANOVA) to determine whether subcategories of sources have significantly different emissions. For two subsets of emissions, the variance of the data between the two subsets is compared to the variance within the subsets. The ratio of these two variances is called the F-statistic. The larger the F-statistic the more likely the underlying data distributions are different. To make a decision regarding the difference between the two subsets, we compare this calculated F-statistic to an F-value associated with a particular confidence level.

One commenter has raised several concerns with our use of the ANOVA procedure in the selection of incinerator subcategories.

Comment: The ANOVA procedure is based upon the assumption that the underlying distribution of both data sets has a normal shape. For incinerator emissions data this assumption is not valid. A log-probability plot shows that particulate emission data is better described by a lognormal distribution. Prior to conducting the ANOVA procedure, the data should be log-transformed.

Response: We use probability plots, Skewness Coefficients, and Correlation Coefficient/Shapiro-Wilks testing to evaluate whether it is more appropriate to analyze emissions data for ANOVA and floor calculations assuming the data represent a normal or lognormal distribution. We believe it is reasonable to assume the data represent a normal distribution for several reasons.

The purpose of the ANOVA subcategorization analysis is to determine if there is a significant difference in emission levels between potential subcategories to warrant establishing separate floors for the subcategories. Although in some cases it may appear that a data set in its entirety may be better represented by a lognormal distribution, the high emissions data causing the right-hand skew will be truncated when we identify the best performing sources—those with the lowest emissions—to calculate floors. This moves the appearance of a skewed distribution toward one that is more symmetric and thus, more representative of a normal distribution.

In addition, our analyses showed: (1) The probability plots do not suggest that either assumed distribution is significantly or consistently better; (2) the data set arithmetic averages tend to be in the neighborhood of the medians, indicating the data sets are not significantly skewed and more closely normal than lognormal; and (3) in some cases, neither assumed distribution could be statistically rejected.[151]

Comment: Some of the data sets used for comparison have very few members. This means that the within-group variance for a small data set would have to be very low for the two groups to be judged as separate.

Response: We agree, but note that as the sample sizes change, the critical values are also changing depending on the degrees of freedom.

Comment: Only emissions data were considered in the ANOVA tests. Feed rate and removal efficiency should have been considered as well.

Response: Differences between subcategories in feedrates or system removal efficiency are irrelevant if there is no significant difference in emissions between the subcategories. The purpose of considering subcategorization is to determine if there are design, operation, or maintenance differences between subcategories that could affect the type or concentration of HAP emissions and thus sources' ability to achieve the floor absent subcategorization. Consequently, it is appropriate to consider emissions only when evaluating subcategorization.

Comment: The confidence level used by EPA for the F-statistic in all cases was 95 percent. If the calculated F-statistic were equal to this 95 percent confidence value, it would mean that there is only a 5 percent chance that data for the two subsets were drawn from the same parent distribution. A less stringent (lower) confidence level would be more appropriate for this analysis.

The commenter evaluated particulate emissions for specialty incinerators (i.e., munitions, chemical weapons and mixed waste incinerators) and non-specialty incinerators (all others). The commenter log-transformed the data and

[151] USEPA, "Technical Support Document for the HWC MACT Standards, Volume III: Selection of MACT Standards," September 2005, Section 8.2.

determined that there was only a 30 percent chance that the two data sets could come from the same parent distribution. This result, together with the vastly different operating characteristics for the two types of incinerators, argues for their being treated as separate categories, according to the commenter.

Response: A confidence level of 95% assigns a probability of 0.95 of accepting the hypothesis when there is no difference between subcategories and hence a probability of 0.05 of rejecting a true hypothesis. This reduces the probability to 5% of rejecting a true hypothesis. A less stringent confidence level would increase the chances of rejecting a true hypothesis. The farther apart the averages of the two potential subcategories are, the more likely they are to be statistically different and the more likely you are to be wrong if you hypothesize that they are not different.

A 95% confidence level is most often used for ANOVA because it is generally believed that being wrong one time out of 20 is an acceptable risk for purposes of ANOVA. In addition, statisticians are comfortable with a 95% confidence level because, in a normal distribution, 95% of the data fall within 2 (actually 1.96) standard deviations of the mean.

Other confidence levels could be used for ANOVA—99% or 90%—if there is a good reason to deviate from the general default of 95%. A 99% confidence level is the second most commonly used confidence level and is generally used when it is very important that you be sure that you are right (i.e., where you can only accept the risk of being wrong 1 time out of 100) before you classify the populations (in this case subcategories) as different. Occasionally, but much less frequently, confidence levels of 90% or less are used. But, we note that these situations are so infrequent that some statistics books provide tables for the ANOVA F-statistic only at the 95% and 99% confidence levels.

For these reasons, we believe that the 95% confidence level is an appropriate level among those we could have reasonably selected.

VI. Emission Standards

A. Incinerators

Comment: A commenter states that EPA's subcategorization (and assignment of differing dioxin/furan standards as a result) between incinerators with wet or no air pollution control device and incinerators equipped with dry air pollution control devices or waste heat boilers is unlawful because incinerators equipped with a given type of pollution control equipment are not different "classes," "types," or "sizes" of source. The commenter implies that EPA justifies this subcategorization by stating that these sources have different emission characteristics, which is no less unlawful and arbitrary than subcategorizing based on the pollution control devices they use.

Response: We agree that it would not be appropriate to subcategorize source categories based on a given air pollution control technique. See 69 FR at 403 (Jan. 4, 2004). As stated at proposal, we do not subcategorize incinerators with respect to dioxin/furans based on the type of air pollution control device used. 69 FR at 21214. For example, with respect to dioxin/furans, it would not be appropriate subcategorize based on whether a source is using: (1) Good combustion practices; (2) a carbon bed; (3) an activated carbon injection system; or (4) temperature control at the inlet to its dry air pollution control device. These devices and practices are what control dioxin/furan emissions. Today's final rule does not subcategorize based on these control devices and practices. Instead, our subcategorization approach recognizes the potential of some emission control equipment to create pollutant emissions that subsequently must be addressed.[152]

Dioxin/furans are unique in that these pollutants are not typically present in the process inputs, but rather are formed in the combustor or in post combustion equipment. The primary cause of dioxin/furan emissions from incinerators not equipped with waste heat boilers is post combustion formation by surface-catalyzed reactions that occur within the dry air pollution system.[153] This is evidenced by the statistically significant higher dioxin furan emissions for incinerators with dry air pollution control systems compared to those without dry systems.

Incinerators with dry air pollution systems are designed to effectively control metal and particulate matter emissions through use of baghouses, electrostatic precipitators, etc. Incinerators that are designed in this manner have the potential for elevated dioxin/furan emissions because dry air pollution control systems provide locations where surface-catalyzed reactions can occur (e.g., on particles on fabric filter bags or electrostatic precipitator plates). Thus, for purposes of dioxin/furan formation and control, incinerators equipped with dry air pollution systems are in fact different "types" of incinerators because of their unique pollutant generation characteristics.

On the other hand, incinerators with wet air pollution control systems are generally designed to effectively reduce total chlorine emissions (with the use of wet scrubbers) and metals and particulate matter emissions. There generally is a tradeoff, however, in that these types of incinerators may not be as efficient in reducing particulate matter and metal emissions compared to incinerators that are equipped with baghouses and dry electrostatic precipitators. These types of incinerators generally do not have the potential to have elevated dioxin/furan emissions because they do not provide locations where surface catalyzed reactions can occur. For purposes of dioxin/furan emission formation and control, sources with wet air pollution control systems are thus likewise different types of incinerators.[154]

Subcategorizing dry air pollution systems and wet air pollution control systems for purposes of establishing a dioxin/furan standard is no different than subcategorizing incinerators equipped with waste heat boilers. The waste heat boiler is the origin of the dioxin/furan that is generated. These incinerators are designed to efficiently recover heat from the flue gas to produce useful energy. A result of this type of incinerator design, however, is that it also provides a location where surface catalyzed reactions can occur (i.e., the boiler tubes), potentially resulting in elevated dioxin/furan formation (and emissions if not properly controlled).

An alternative approach that does not subcategorize these sources, but rather identifies best performing sources as those sources with the lowest emissions irrespective of whether they have a wet

[152] Although we subcategorize between incinerators with wet or no air pollution control device and incinerators equipped with dry air pollution control devices or waste heat boilers for the floor analysis, the calculated dioxin furan floors for both subcategories for existing sources were determined to be less stringent than the current interim standard. Subsequently, the final rule emission limitations for both subcategories are, for the most part, identical, and equivalent to the interim standard. See USEPA, "Technical Support Document for the HWC MACT Standards, Volume III: Selection of MACT Standards," September 2005, Section 10.1, for further discussion.

[153] See USEPA, "Technical Support Document for the HWC MACT Standards, Volume IV: Selection of MACT Standards," September 2005, Section 3, for further discussion.

[154] A similar analogy applies to incinerators that are not equipped with air pollution systems. These incinerators are not designed to control emissions of metals, chlorine, and particulate matter (perhaps because emission levels are low due to low HAP feed levels). Similar to incinerator types with wet systems, this design does not provide the locations for surface catalyzed reactions to occur, which leads us to conclude that these are different types of incinerator with respect to dioxin/furan control.

or dry air pollution control device, would yield floors that would not be achievable unless all the sources, including the best performers, adopted beyond-the-floor technology. The calculated dioxin/furan floor for existing incinerators and liquid fuel boilers using such an approach would be 0.008 and 0.009 ng TEQ/dscm, respectively.[155] All of the best performing sources for these calculated floors had either wet air pollution systems or no air pollution control systems. The floor technology used by these sources is good combustion practices. As a result, these floor levels would not be replicable by these best performing sources nor duplicable by other sources through use of the same good combustion practices because of the uncertainties associated with dioxin/furan generation mechanisms and rates that can vary both within sources and across sources, potentially leading to significant variability in emission levels.[156] Sources equipped with wet or no air pollution systems would thus likely be required to install carbon systems to comply with these standards, a technology used by only four incinerators (none of which were best performers in the above discussed floor analysis). Such an outcome should be viewed as a beyond-the-floor technology and therefore assessed pursuant to the factors enumerated in section 112(d)(2). Furthermore, it is unclear, and perhaps doubtful, that these floors would be achievable by these sources even if they were to install beyond-the-floor controls such as activated carbon systems because no sources using activated carbon are currently achieving those floor levels. We therefore conclude that it is appropriate, and necessary, to subcategorize these types of incinerators for purposes of calculating dioxin/furan floor standards.

B. Cement Kilns

1. Hg Standard

Comment: Several commenters recommend that EPA use a commenter-submitted dataset, which includes three years of data documenting day-to-day levels of mercury in hazardous waste fuels fired to all hazardous waste burning cement kilns, to identify a MACT floor for existing and new cement kilns. Several commenters state that *existing* cement kilns should have the option to comply with either of the following mercury standards: (1) A hazardous waste feed concentration limit, expressed in ppmw, based on an evaluation of the five best performing sources within the commenter-submitted dataset (documenting day-to-day levels of mercury in the hazardous waste over a three year period); or (2) a hazardous waste maximum theoretical emissions concentration (MTEC), expressed in units of µg/dscm, developed by projecting emissions of the best performing sources assuming mercury concentrations in the hazardous waste were at the source's 99th percentile level in the commenter-submitted dataset. To identify the best performing sources, the commenter suggests selecting the five sources with the lowest median mercury concentrations in the dataset. For existing sources, the commenters' evaluation yields a hazardous waste feed concentration limit of 3.3 ppmw and a stack concentration emission limit of 150 µg/dscm (rounded to two significant figures and considering mercury contributions only from the hazardous waste). For *new* cement kilns, the commenters recommend a mercury standard in the format of a hazardous waste feed concentration limit only, expressed in ppmw, based on the single source with the lowest 99th percentile level of mercury in hazardous waste. The commenters recommend a mercury standard of 1.9 ppmw for new sources.

Response: We agree with commenters that the commenter-submitted dataset documenting the day-to-day levels of mercury in hazardous waste fuels fired to all hazardous waste burning cement kilns is the best available data to identify floor levels for existing and new cement kilns. See discussion in Part Four, Section I.D. However, we disagree with the commenters' suggested format of the mercury standard for existing sources. Establishing the mercury standard as the commenters' suggest (i.e., 3.3 ppmw in the hazardous waste feed *or* 150 µg/dscm as a hazardous waste MTEC) fails to consider the interim mercury standards. As discussed in Part Four, Section III.E, there can be no backsliding from the levels of performance established in the interim standards. While not every source feeding hazardous waste with a maximum mercury concentration of 3.3 ppmw would exceed the interim standard, most sources using more than 50 percent hazardous waste as fuel (i.e., replacing at least half its fossil fuel with hazardous waste) would exceed the interim standard, emitting mercury higher than the levels allowed under §§ 63.1204(a)(2) and 63.1206(b)(15) of the interim standards.[157] The hazardous waste MTEC of 150 µg/dscm calculated by the commenters is also higher than the level currently allowed under § 63.1206(b)(15) of the interim standards. Since sources cannot backslide from the levels of the interim standards, if we were to accept the commenters' floor analysis results as presented (which we are not), then we would "cap" each calculated standard (i.e., 3.3 ppmw hazardous waste feed concentration and 150 µg/dscm in stack emissions) at the interim standard level. This would result in a mercury standard for existing sources of 3.3 ppmw hazardous waste feed *and* a hazardous waste feed MTEC of 120 µg/dscm *or* 120 µg/dscm as a stack gas concentration limit. We note this is similar to the mercury standard adopted today: a hazardous waste feed concentration limit of 3.0 ppmw *and* a hazardous waste feed MTEC of 120 µg/dscm or 120 µg/dscm as a stack gas concentration limit. For an explanation of why we derived a level of 3.0 ppmw from the data, see Section 7.5.3 of Volume III of the Technical Support Document.

The commenters' suggested new source mercury standard of 1.9 ppmw in the hazardous waste has the same deficiency. New sources with a hazardous waste fuel replacement rate of approximately 75% could emit mercury at levels higher than currently allowed under the interim standards. After capping the calculated standard at the interim standard level, we would identify the mercury standard for new sources as a hazardous waste concentration limit of 1.9 ppmw in the hazardous waste and a hazardous waste feed MTEC of 120 µg/dscm *or* 120 µg/dscm as a stack gas concentration limit. For reasons discussed in Section 7.5.3 of Volume III of the Technical Support Document, this is indeed the mercury standard we are promulgating for new cement kilns.

The commenters also suggest that the best performing sources should be identified as those with the lowest three-year median concentration of mercury in hazardous waste. Although this approach would be permissible, we conclude that it is more appropriate to identify the best performers (or single best performer for new sources) by

[155] See USEPA, "Technical Support Document for the HWC MACT Standards, Volume III: Selection of MACT Standards," September 2005, Section 20 and Appendix C, tables labeled "E-INC-all-DF" and "E-LFB-all-DF".

[156] Dioxin/furan formation mechanisms are complex. Sources equipped with wet or no air pollution control systems cannot rely on good combustion practices alone to achieve these floor levels because they cannot "dial in" to a specific emission level, as is the case with typical back-end control systems that control particulate matter and metals, for example. See Part Four, Section IV.B.

[157] USEPA, "Technical Support Document for HWC MACT Standards, Volume III: Selection of MACT Standards," Section 23.4, September 2005.

selecting those with the lowest 99th percentile upper level mercury concentrations. (This is not a statistically determined upper prediction limit; there is sufficient data for an arithmetically calculated 99th percentile to reliably reflect sources' performance.) We believe that this approach best accounts for the variability experienced by best performing sources over time.

A detailed discussion of the MACT floor analysis for existing and new cement kilns is presented in Section 7.5.3 of Volume III of the Technical Support Document. In summary, the mercury standard for existing cement kilns is 3.0 ppmw in the hazardous waste feed *and* 120 µg/dscm as a hazardous waste maximum theoretical emission concentration feed limit or 120 µg/dscm as a stack gas concentration limit. For new sources the mercury standard is 1.9 ppmw in the hazardous waste feed and 120 µg/dscm as a hazardous waste maximum theoretical emission concentration feed limit or 120 µg/dscm as a stack gas concentration limit.[158]

Comment: Two commenters oppose EPA's proposed approach to base compliance with the mercury standard on averaged annual emissions. The commenters state an annual average would allow mercury emissions to exceed the interim standard because a source could burn high concentrations of mercury waste over a short period and still comply with an annual limit by burning low concentration wastes at other times. These commenters support the concept of a 12-hour rolling average feedrate limit (i.e., the current requirement under the interim standards) in conjunction with an emission standard no less stringent than the interim standard.

Response: We agree with these comments. Cement kilns must establish a 12-hour rolling average feedrate limit of mercury to comply with these standards. The mercury standards for cement kilns are "capped" at the interim standard level to prevent backsliding from the current level of performance. This is accomplished by expressing the standard as a limit on the mercury concentration in the hazardous waste (with the rolling average) and either an emission concentration limit or hazardous waste maximum theoretical emission concentration feed limit. See § 63.1209(l)(1)(iii).

2. Total Chlorine

Comment: One commenter states that the proposed MACT floor approach is inconsistent with the statutory definition of MACT because EPA's selection of a routinely achievable system removal efficiency (SRE) was arbitrary and not representative of the best performing sources. Instead, the commenter suggests EPA identify a MACT SRE based on the five sources with the best SREs and apply that SRE to the MACT chlorine feed level. Later, in supplemental comments, the same commenter suggests two alternative approaches to identify a floor level. One approach applies a ranking methodology based on emissions and chlorine feed, and the second suggested approach applies a triple ranking method based on emissions, feed, and chlorine SRE. Other commenters, however, supported EPA's proposed approach.

Response: We are adopting the same approach we proposed at 69 FR at 21259. As we explained, this is a variant of the SRE/Feed approach, the variant involving the degree of system removal efficiency achieved by the best performing sources. In summary, to determine the floor level we first identify the best performing sources according to their hazardous waste chlorine feedrate. The best performing sources are those that have the lowest maximum theoretical emissions concentration (MTEC), considering variability. We then apply an SRE of 90 percent (the specific point in contention) to the best performing sources' total MTEC (i.e., thus evaluating removal of total chlorine across the entire system, including chlorine contributions to emissions from all feedstreams such as raw materials and fossil fuels) to identify the MACT floor, which is expressed as a stack gas emissions concentration in parts per million by volume. This approach defines the MACT floor as an emission level that the best performing sources could achieve if the source limits the feedrate of chlorine in the hazardous waste to the MACT level (i.e., the level achieved by the average of the best performing five sources) while also achieving an SRE that accounts for the inherent variability in raw material alkalinity and (to a lesser degree) cement kiln dust recycle rates, and production requirements. 69 FR at 21259.

Under this approach, we are evaluating hazardous waste feed control as we do for other sources. One commenter objects to our determination that an SRE of 90 percent is representative of the best performing sources because we have not established a MACT SRE—the average SRE achieved by the best performing sources.

There is no doubt that the cement manufacturing process is capable of capturing significant quantities of chlorine when favorable conditions exist within the kiln system. Our usual approach of establishing an SRE by ranking the most efficient SREs taken from individual compliance tests, however, would result in a standard that would not be achievable because it may not be duplicable by the best performers or certainly would not be replicable by others, given that it is a function of various highly variable parameters, especially levels of alkali metals (e.g., sodium and potassium) and volatile compounds (e.g., chlorine and sulfur) in the raw materials. Alkalis and volatiles vary at a given best performer facility (in fact, at all facilities) as different strata are mined in the quarry, and across facilities due to different sources of raw materials. Raw material substitution is infeasible and counter to the objective of producing quality product (i.e., a product with low alkali content).

Cement kilns thus are not able to design or operate to achieve a specific SRE at the high (most efficient) end of the range of test conditions. This is demonstrated by our calculations of system removal efficiency data, which is essentially a collection of performance "snapshots." See SRE data summarized in Table 1 at the end of this response; see also *Mossville*, 370 F. 3d at 1242 (maximum emission variability associated with raw material variability needs to be accounted for in MACT floor determination since the standard must be met at all times under all operating conditions). The performance data of the "apparent" best performers—upwards of 99 percent—identified by the commenter are simply a snapshot in the possible range of performance and are not replicable in the future due to factors which are uncontrollable by the source, as just explained. In confirmation, cement kilns achieving this level of removal in one test proved incapable of replicating their own result in other tests even though individual sources each have their own proprietary source of raw materials. See results in table for Giant (SC), Essroc (IN), Holcim (MO), Giant (PA), and LaFarge (KS) all

[158] Please note that we do not regard this standard as a work practice standard under section 112(h)(1) of the Act, because part of the standard includes an emission limit which is measured at the stack. EPA believes the special requirements of section 112(h)(1) apply when a work practice is the exclusive standard.

of whom would violate a 99 + percent standard based on their own operating results.

TABLE 1.—SUMMARY OF SYSTEM REMOVAL EFFICIENCY DATA FOR WET PROCESS CEMENT KILNS [159]

Facility	Number Runs in Data Base	Low SRE Run (%)	High SRE Run (%)	Average SRE of All Runs (%)
LaFarge (OH)	3	99.1	99.4	99.3
Giant (SC)	24	95.5	99.8	99.0
Essroc (IN)	13	97.3	99.9	98.7
Holcim (MO)	6	96.4	99.9	98.4
LaFarge (KS)	12	95.7	99.3	98.1
Giant (PA)	17	87.7	99.4	97.1
Continental (MO)	3	95.7	97.0	96.5
Ash Grove (AR)	37	85.1	98.8	95.1
Texas Industries (TX)	6	88.8	97.0	93.6
Holcim (MS)	9	76.5	99.2	90.0

[159] See Section 3.6 of Volume II (Specific MACT Standards) of Comment Response Document, September 2005.

However, the data indicate that SRE is reasonably quantifiable to a point. Based on our data base of system removal efficiency information from 130 test conditions where total chlorine was evaluated, we conclude that a system removal efficiency of 90 percent is a reasonable estimate of MACT SRE.[160]

We also reject the commenter's three suggested alternative approaches to identify a MACT SRE to apply to the MACT feed level. The commenter's methods all suffer a common flaw: They fail to recognize and take into account the limitations of the total chlorine SRE data. For example, as just demonstrated, available data show that considering the SRE data associated with the most recent compliance test as a ranking factor will result in unachievable standards due to the varying effectiveness of chlorine capture (which impacts emissions) depending on the raw material mix characteristics. Considering only the most recent compliance test data as suggested yields results that are unachievable because the best performer's SRE data are likely biased high (e.g., sources that happen to test under favorable conditions are likely to be identified as best performers), which would not be replicable by even that source on a day-to-day basis.

3. Semivolatile and Low Volatile Metals

Comment: Commenters oppose EPA's proposed approach to treat each kiln as a separate and unique source in the SRE/Feed MACT floor analysis for cement kilns.[161] Commenters state that the approach is an improper way to perform a statistical analysis and reduces the variability in emissions that otherwise would be observed in a MACT pool of five unique sources. Variability is reduced because co-located kilns at the same plant share many of the factors that comprise front-end and back-end controls. As a result, the calculated MACT floors for SVMs and LVMs for cement kilns are too stringent. The commenters' recommended solution (in instances where co-located kilns are among the top five performers) is to use only the data from the best performing co-located kiln, exclude any lesser performing kilns at the plant site, and then include the next-best performing non-co-located kiln in the MACT pool. Implementing their recommendation, the commenters state that the MACT floor for SVMs increases from 4.0×10^{-4} to 7.4×10^{-4} lbs/MMBtu and the floor for LVMs increases from 1.4×10^{-5} to 1.8×10^{-5} lbs/MMBtu. Another commenter generally supports EPA's approach noting that the variability factor applied to the emissions data already accounts for variability.

Response: We consider sources that are not identical as unique sources and emissions data and information from unique sources are considered separate sources in the floor analyses. An example of an "identical" source in our data base is compliance test data from a similar on-site combustion unit used in place of a compliance test for another unit (*i.e.*, emissions testing of an identical unit was not conducted). These sources and their associated data are called "data in lieu of" sources in our data based on the RCRA provisions under § 266.103(c)(3)(i). We acknowledge that co-located sources may in fact share certain similar operation features (e.g., use of raw material from the same quarry, use of the same coal and hazardous waste burn tank to fire the kilns); however, given that the co-located sources (except those designated as data in lieu of) are not designed identically, and given their hazardous waste feed control levels were not identical during testing, we conclude we must consider each source as a unique source in the floor analyses.[162]

Comment: Commenter states that EPA's proposed standards for new cement kilns are unachievable due to problems with its accounting for variability, in part because EPA did not consider geographic differences when assessing feed control levels. The concentrations of hazardous constituents in the waste in a particular region are likely to be different than in the waste from another geographical region due to types of industrial sectors located within each region. Sources cannot reasonably arrange for transportation of lower HAP wastes generated across the country and cannot treat the hazardous waste to remove or reduce HAP concentrations. The commenter cites several court decisions that support their assertions. Commenter believes that while this represents a problem for developing both the new and existing source floors, it is a greater predicament for the new

[160] As discussed a number of times earlier, we are not basing any standards on feed control of HAP in raw material and fossil fuel input. We instead are controlling HAP attributable to those inputs by means of end-of-stack emission standards which reflect removal of HAP by some type of control device. This approach is consistent with the discussion above, since we are not basing the cement kiln chlorine standard on control of any raw material input, but rather on some type of back-end removal efficiency.

[161] It is common for cement manufacturing plants to operate multiple cement kilns at the same plant.

[162] Nonetheless, we analyzed the SVM and LVM floors for cement kilns as suggested by the commenter. Results of the analysis are presented in "Technical Support Document for HWC MACT Standards, Volume III: Selection of MACT Standards," Section 8.8, September 2005.

source floor because this floor level is based on test data for only one source.

Response: We are not obligated to account for varying hazardous waste feed control levels occurring because of differing HAP generation rates in different locations (for commercial sources), or because different production process types generate higher or lower levels HAP concentration wastes. Hazardous waste feed control is a legitimate control technology. The commenter seems to suggest that we should subcategorize low feeding sources and high feeding sources based on their hazardous waste feed control level. This would inappropriately subcategorize sources based on differing levels of controls, which we do not do. See 69 FR at 403 (January 5, 2004). Nonetheless, as previously discussed, the SRE/Feed methodology lessens the impact of feed control variations across commercial units because it results in fewer situations where best performing back-end controlled sources (from a particulate matter emissions perspective) cannot achieve the semivolatile and low volatile metal design levels and floors.

For new source standards, the single best performing cement kiln sources for semivolatile metals and low volatile metals were not the lowest hazardous waste feed controlled source (both floors were based on sources with the fourth best, (i.e., lowest, hazardous waste feed control level). We therefore do not believe these sources are atypically low hazardous waste feeders relative to the other best performing sources in the existing source MACT pools.

C. Lightweight Aggregate Kilns

1. Mercury Standard

Comment: One commenter, an operator of lightweight aggregate kilns subject to this rule, recommends that EPA establish the mercury standard for lightweight aggregate kilns at a hazardous waste feed concentration limit of 3.3 ppmw for existing sources and 1.9 ppmw for new sources, which is the same standard suggested in public comments by a trade organization representing hazardous waste burning cement kilns. The commenter notes that these mercury limits are appropriate for lightweight aggregate kilns because the commenter's two lightweight aggregate manufacturing facilities participate in the same hazardous waste fuel market as the majority of cement kilns. Moreover, the commenter maintains that its parent company also owns and operates two cement kilns and that its lightweight aggregate kilns receive hazardous waste from many of the same generators that provide hazardous waste fuel to the cement kilns. Consequently, the commenter states that the cement industry's data set of actual mercury feed concentrations in the hazardous waste best represents the full range of hazardous waste fuel concentrations that exist in the waste fuel market (see also Part Four, Sections I.D and E).

Response: We disagree with the commenter. Although the cement industry's set of mercury feed concentration data in the hazardous waste may represent the full range of concentrations for the cement kiln source category, we cannot conclude the same for lightweight aggregate kilns because the commenter states that the mercury dataset are only applicable to its kilns.[163] Further, the commenter provides no specific information or data to support the conclusion that its suggested approach is justified for the other lightweight aggregate kiln facility.

We also disagree with the commenter as to the appropriateness of establishing the mercury standard in the format of a hazardous waste feed concentration (i.e., 3.3 ppmw for existing sources and 1.9 ppmw for new sources) for lightweight aggregate kilns. A hazardous waste feed concentration standard is improper for this source category because one lightweight aggregate kiln facility's sources (although not the commenter's) controls mercury emissions using wet scrubbing. Thus, a hazardous waste feed concentration standard would inappropriately limit the mercury concentration in hazardous waste for sources that use control equipment capable of capturing mercury. A source with control equipment should not be restricted to a hazardous waste feed concentration standard that is based on sources that can only control mercury emissions through limiting the amount of mercury in the hazardous waste.

In any case, as explained earlier in our discussion of cement kiln mercury standard, we believe that it is preferable to establish an emission standard to assure that the actual amount of mercury emitted by these sources is controlled by means of a numerical standard for stack emissions.

Comment: One commenter agrees that a source may not be able to achieve the mercury standard due to raw material contributions that might cause an exceedance of the emission standard in spite of a source using properly designed and operated MACT floor control technologies, including controlling the levels of metals in the hazardous waste. The commenter opposes the proposed alternative standard of 42 μg/dscm, which is expressed as a hazardous waste maximum theoretical emissions concentration. Instead, the commenter suggests that EPA maintain the alternative standard options of §§ 63.1206(b)(15) or 63.1206(b)(9).

Response: We agree with the commenter that the mercury standard should address the concern of raw material contributions causing an exceedance of the emission standard. We also agree that the proposed alternative standard of a hazardous waste maximum theoretical emissions concentration of 42 μg/dscm is an improper standard because the underlying data are unrepresentative. See discussion in Part Four, Section I.E. We note that the mercury standard promulgated today is 120 μg/dscm as a stack gas concentration limit or 120 μg/dscm as a hazardous waste maximum theoretical emission concentration feed limit. The alternative mercury standard sought by the commenter under § 63.1206(b)(15) is a limit of 120 μg/dscm as a hazardous waste maximum theoretical emission concentration, which is included in the mercury standard promulgated today. This should address the commenter's concern.

Comment: One commenter supports a mercury standard with short-term compliance limits (e.g., 12-hour rolling average feedrate limits) as opposed to the annual limit proposed.

Response: For reasons discussed in Part Four, Section I.E, we are using a different mercury dataset than at proposal. We solicited comment on a floor approach using these data in a notice[164] sent directly to certain commenters. We are adopting that approach today. The monitoring requirements of the mercury standard for lightweight aggregate kilns includes short-term averaging periods (*i.e.*, not to exceed a 12-hour rolling average), as recommended by the commenter.

2. Total Chlorine Standard

Comment: One commenter supports excluding from the floor analysis all lightweight aggregate kiln sources that lack air pollution control devices for chlorine, such as scrubbing technology. The floor analysis should simply exclude sources without back-end controls according to the commenter.

[163] We note that the commenter-submitted dataset is not amenable for use in establishing standards expressed in a thermal emission format because sufficient information on the characteristics of the hazardous waste (*e.g.*, heating value of hazardous waste) were not provided.

[164] See docket item OAR–2004–0022–0370.

Response: We disagree. For the final rule, we are using the SRE/Feed MACT floor approach which defines best performers as those sources with the best combined front-end hazardous waste feed control and back-end air pollution control efficiency. The commenter's suggestion would exclude emissions data from two of the three facilities in this source category even though valid emissions data from these sources are available (and therefore ordinarily to be used, see *CKRC*, 255 F. 3d at 867), and these sources achieved the best front-end hazardous waste feed control in the category. We note that the best feedrate controlled sources have hazardous waste thermal feed levels that are approximately one-fifth the level of the source's with back-end controls. These data describe the level of performance of sources in the category and must be evaluated in the MACT floor analysis. We also note that even if we were to implement the commenter's suggestion, the MACT floor results would not change for existing and new lightweight aggregate kilns because the total chlorine emissions data of the source with back-end air pollution controls (after considering variability) are higher than the standards promulgated today. Thus, the commenter's suggestion also would result in a standard that would be capped by the interim standard.

3. Beyond-the-Floor Standards

Comment: One commenter opposes EPA's proposed decision to promulgate a beyond-the-floor standard for dioxin/furans for existing and new lightweight aggregate kilns based on performance of activated carbon injection.

Response: For the final rule, we conclude that a beyond-the-floor standard for lightweight aggregate kilns is not warranted. The Clean Air Act requires us to consider costs and non-air quality impacts and energy requirements when considering more stringent requirements than the MACT floor. In the proposed rule, we estimated that the incremental annualized compliance costs for lightweight aggregate kilns to achieve the beyond-the-floor standard would be approximately $1.8 million and would provide an incremental reduction in dioxin/furan emissions of 1.9 grams TEQ per year (see 69 FR at 21262). At proposal we judged costs of approximately $950,000 per additional gram of dioxin/furan TEQ removed as justified, and, therefore, we proposed a beyond-the-floor standard. Since proposal, we made several changes to the dioxin/furan data base as the result of public comments. One implication of these changes is a lower national emissions estimate for dioxin/furans for lightweight aggregate kilns. We now estimate an incremental reduction in dioxin/furan emissions of 1.06 grams TEQ per year with costs ranging between $1.6 and $2.2 million per additional gram of dioxin/furan TEQ removed. Based on these costs and consideration of the non-air quality impacts and energy requirements (including more waste generated in the form of spent activated carbon, and more energy consumed), we conclude that a beyond-the-floor standard for existing and new lightweight aggregate kilns is no longer justified. For an explanation of the beyond-the-floor analysis, see Section 12.1.2 of Volume III of the Technical Support Document. We note that EPA also retains its authority under RCRA section 3005(c) (the so-called omnibus permitting authority) by which permit writers can adopt more stringent emission standards in RCRA permits if they determine that today's standards are not protective of human health and the environment.

D. Liquid Fuel Boilers

1. Mercury Standard Not Achievable When Burning Legacy Mixed Waste

Comment: One commenter states that the proposed liquid fuel boiler mercury standard is not achievable by a commercial boiler, DSSI (Diversified Scientific Services, Inc.) that burns mercury-bearing low level radioactive waste that is also a hazardous waste (so-called 'mixed waste') that was generated years ago (so-called, legacy waste). The waste is an organic liquid containing high concentrations of mercury. The boiler is equipped with a wet scrubber which provides good mercury control—93%, system removal efficiency according to the commenter.

The commenter states that the proposed liquid fuel boiler mercury standard is not achievable using feedrate control and/or additional back-end control. Waste minimization is not an option because the waste has already been generated. Further, available national treatment capacity for mercury-bearing, low-level radioactive organic hazardous waste is very limited. The only other hazardous waste combustion facility authorized to treat such waste is the Department of Energy incinerator at Oak Ridge, Tennessee. Waste treatment volumes at that facility are restricted by the mercury feed rate limitation for the incinerator. In addition, the feedrate of the waste cannot be practicably reduced because of the large back-log of waste that must be treated.

The commenter suggests that their boiler be subject to the incinerator mercury standard because the mixed waste has far higher concentrations of mercury than wastes burned by other boilers and, as a consequence, the boiler is more incinerator-like with respect to the feedrate of mercury.

Response. We agree with the commenter's suggestion. The final rule subjects this commercial liquid fuel boiler to the mercury standard for incinerators. We are classifying this source as a separate type of source for purposes of the mercury standard, because the type of mercury-containing waste it processes is dramatically different from that processed by other liquid fuel boilers, effectively making this a different type of source for purposes of a mercury standard [165]. The source thus feeds mercury at concentrations exceeding that of any boiler but at concentrations within the range processed by hazardous waste incinerators. The maximum test condition average MTEC [166] for mercury for the remaining liquid fuel boilers is 20 μg/dscm. All the liquid fuel boiler mercury data represent "normal" data, i.e., data that were not spiked. (The lack of spiked data in the liquid fuel boiler data base, in and of itself, indicates that these sources do not process mercury-bearing waste and do not need the operational flexibility gained by spiking to account for occasional higher concentration mercury wastes.) DSSI's 2002 mercury test condition average MTEC was spiked to 3500 μg/dscm. In other words, DSSI needs the operational flexibility to feed 175 times more mercury than any other liquid fuel boiler. Incinerators, on the other hand, had mercury MTECs that ranged to 110,000 μg/dscm in 2002. In fact, DSSI's mercury feed rate is the eighth highest of the 40 incinerators, including DSSI, for which we have 2002 mercury feed rate data. DSSI's process feed is thus within the upper range of mercury feed found at incinerators.

We believe it is well within the broad discretion accorded us in section 112(d)(1) to subcategorize among "types" and "classes" of sources within a category. See also *Weyerhaeuser* v. *Costle*, 590 F. 2d at 254, n. 70 (D.C. Cir. 1978) (similar raw waste characteristics justify common classification) and *Chemical Manufacturers Ass'n* v. *EPA*, 870 F. 2d 177, 253–54 and n. 340 (5th

[165] See CAA section 112 (d) (1)), authorizing EPA to distinguish among different "types * * * of sources within a category or subcategory" in developing MACT standards.

[166] Maximum theoretical emission concentration is the feedrate normalized by gas flowrate assuming zero system removal efficiency.

Cir. 1989) (same). We note that this boiler will be subject to the liquid fuel boiler standards for all HAP other than mercury (the only HAP where the issue of appropriate classification arises).

Not surprisingly, given the disparity in waste concentration levels, the DSSI boiler, even though equipped with back end control comparable to best performing commercial incinerators, achieves mercury emission levels less than an order of magnitude higher than the other hazardous waste-burning liquid fuel boilers, few of which use back end control that is effective for mercury.[167] This emission disparity likewise indicates that DSSI is treating a different type of waste than other liquid fuel boilers.

The nature of the mercury-bearing waste further confirms that it is of a different type than that processed by other hazardous waste burning liquid fuel boilers. The waste is a remediation waste, a type of waste burned routinely by commercial hazardous waste incinerators but almost never by a liquid fuel boiler.

Moreover, the waste is a legacy, mixed waste generated decades ago in support of the United States' strategic nuclear arsenal. It is not amenable to the types of control all other liquid fuel boilers use to reduce mercury emissions—some type of feed control or other minimization technique. We investigated whether any waste minimization options are feasible for this waste, and find that they are not. Normally, waste minimization is accomplished by one of three means: eliminating the use of mercury in the process to prevent it from being in the waste; pretreating the waste before burning to remove the mercury; or sending it to another facility better suited to handle the waste. Changing the production process to eliminate or reduce the mercury content of the waste is not an option because this waste has already been generated. Pretreatment is already practiced to the maximum extent feasible by settling out and separating the heavier mercury from the liquid components after thermal desorbtion. The remaining organic liquid that is burned by the mixed waste boiler contains concentrations of mercury (in organo-mercury and other organic soluble forms) that are orders of magnitude higher than burned by other liquid fuel boilers. Much of the waste cannot be feasibly pretreated to remove mercury because this legacy, mixed waste comes from many highly diverse sources. It is not practical or feasible to investigate how to remove the mercury from wastes of such varied and unique origins.

Only one other facility could potentially treat this mixed waste, DOE's incinerator at Oak Ridge, Tennessee, whose permit allows the incinerator to manage mixed waste. However, waste treatment volumes for mercury-bearing wastes at that facility are restricted by the mercury feed rate limitation in the incinerator's permit. The DOE incinerator alone cannot assure national capacity for mercury-bearing, low-level radioactive organic hazardous waste. In addition, the back-end emission controls of the mixed waste boiler are superior to those used by most incinerators, including the Oak Ridge incinerator. This boiler uses a highly effective wet scrubbing system—the principal MACT floor back-end control for mercury used by incinerators—that achieves over 93% system removal efficiency. This is superior control compared to most incinerators, including the one at Oak Ridge which achieves 75 to 85% removal.[168]

Thus, this mixed waste boiler is reasonably classified a different type of source with respect to mercury waste than other hazardous waste-burning liquid fuel boilers, based on the nature of the waste burned and confirmed by the source's mercury emissions. We note that, although the final rule subjects only the DSSI mixed waste boiler to the incinerator mercury standard, we would conclude that any other liquid fuel boiler with the same fact pattern (i.e., that met the same criteria as the DSSI boiler as discussed above) should also be subject to the incinerator mercury standard rather than the liquid fuel boiler mercury standard.

Comment. One commenter states that EPA's standards for all sources must reflect the actual emission levels achieved by the relevant best sources. If EPA wishes to subject the boiler source and incinerators to the same emission standards, however, it is entirely within the Agency's power to do so.

Response. We agree. There is no functional difference between this boiler and incinerators with respect to mercury feed rate and the type of waste processed (incinerators often treat remediation wastes). Therefore, the most relevant sources for the purposes of clarification in this case are incinerators, not liquid fuel boilers.

Accordingly, we have classified DSSI as an incinerator for purposes of a mercury standard (*i.e.*, made it subject to the mercury standard for incinerators), and have included the DSSI mercury data with the incinerator data when assessing mercury standards for incinerators.

Comment. In something of a contradiction, the same commenter argues that the mixed waste boiler source (DSSI) does not claim that it cannot meet the relevant mercury standard for liquid fuel boilers, but only that it cannot do so "using either feedrate control or MACT floor back end emission control." Floors must reflect the emission levels that the relevant best sources actually achieve, not what is achievable through the use of a chosen emission control technology. It is flatly unlawful—and essentially contemptuous of court—for EPA even to entertain the source's argument that the source should be subject to a less stringent emission standard based on the levels they believe would be achievable through the use of one chosen control technology.

The commenter also states that the source acknowledges that it could achieve a better emission level, and apparently meet the relevant standards, by using activated carbon. Their argument that doing so would generate large quantities of spent radioactive carbon does not support its attempt to avoid Clean Air Act requirements; the alternative to the source accumulating large quantities of radioactive carbon is releasing large quantities of radioactive and toxic pollution into the environment.

Response. DSSI cannot meet the liquid boiler mercury standard because it burns a unique waste that resembles wastes processed by hazardous waste incinerators (in terms of mercury concentration and provenance) and is unlike any mercury-containing waste burned by the remaining liquid fuel boilers. See the earlier discussion showing that DSSI needs the operational flexibility to feed 175 times more mercury than any other liquid fuel boiler, but that DSSI's process feed is within the upper range of mercury feed found at incinerators.

We agree that DSSI is processing different types of mercury-bearing wastes than those combusted by all other liquid fuel boilers. We believe that establishing a different mercury standard for DSSI is warranted, as it would for any source with demonstrably unique, unalterable feedstock which is

[167] USEPA, "Technical Support Document for HWC MACT Standards, Volume I: Description of Source Categories," September 2004, Section 2.4.4.

[168] For more explanation concerning mixed waste sources, limitations on the concentrations of mercury fed to these sources, and the system removal efficiency achieved, see USEPA, "Technical Support Document for HWC MACT Standards, Volume III: Selection of Standards," September 2005, Section 8.7.

more difficult to treat than that processed by other sources otherwise in the same category.

How DSSI chooses to comply with the incinerator mercury standard (for example, whether it must use some other type of emissions control technology) is not germane to this decision. We note that today's mercury standard for incinerators will force this source to lower its mercury emissions, since it is unlikely that it can meet today's 120 μg/dscm standard at all times without some changes in operations.

Comment. The source argues that waste minimization is not feasible for legacy mixed waste that has already been generated. It is not possible to travel back in time and unmake mixed legacy waste that already has been created. That obvious fact, however, lends no support to their argument that it should be allowed to burn mixed legacy waste with less stringent emission standards, according to one commenter.

Response. As discussed above, the mercury standard for liquid fuel boilers is not achievable for this source because it is a different type and class of boiler, based on the type of mercury-containing hazardous waste it processes. Because this boiler has mercury feed rates that resemble those of incinerators—not liquid fuel boilers—and waste minimization is not possible, subjecting the boiler to the mercury incinerator standard is a reasonable means of sub-categorization pursuant to the discretionary authority provided us by section 112(d)(1) of the Clean Air Act.

Comment. The commenter states that it is entirely possible to dispose of mixed legacy waste without burning it. Specifically, currently available technologies such as chemical oxidation and precipitation can be used to treat mixed legacy waste without burning it—and without releasing mercury into the air. Therefore, mixed legacy waste should not be burned at all; it should be disposed of safely through the application of one of these more advanced technologies.

Response. First, these wastes must be treated before they can be land disposed. RCRA sections 3004(d), (g)(5), and (m). They also must meet a standard of 0.025 mg/l measured by the Toxicity Characteristic Leaching Procedure before land disposal is permissible. 40 CFR 268.40 (standard for "all other nonwastewaters that exhibit the characteristic of toxicity for mercury").[169] EPA's technical judgment is that it would be very difficult to meet this standard by any means other than combustion. Moreover, as an organic liquid, the waste is readily amenable to treatment by combustion. In addition, combustion is a legal form of treatment for the waste. EPA did not propose to change or otherwise reconsider these treatment standards in this rulemaking, and is not doing so here. We note, however, that 40 CFR 268.42 and 268.44 provide means by which generators and treatment facilities can petition the Agency to seek different treatment standards from those specified by rule, and set out requirements for evaluating such petitions.

We note further that, because this waste is radioactive, exceptional precautions need to be taken in its handling. The nonthermal treatment alternatives mentioned by the commenter ignore the potential for radiation exposure if nonthermal treatment is used. Concerns (some of which are mentioned in DSSI's comment) include: Nonthermal treatment would (or could) increase worker exposure; desire to reduce handling of radioactive materials in general; need to avoid contaminating equipment that subsequently requires decontamination or handling as radioactive material; minimizing the generation of additional radioactive waste residues; reducing the amount of analysis of radioactive materials, which causes potential exposure, generation of radioactive wastes and equipment; wastes are varied and often of small volumes, which makes it difficult to develop routine procedures. Nonthermal treatment alternatives are also not currently available to DOE to manage the diversity and volume of DOE mixed waste. It is thus our belief that the commenter has not fully explored the implications of its position, especially with regard to radiation exposure.

If the commenter wishes to pursue this issue, EPA believes the appropriate context is through the Land Disposal Restriction mechanisms described above.

Comment. The commenter states that the source argues that feedrate control is not "practical." There appears to be no record evidence indicating what would make feedrate control impractical and why any such obstacle could not be overcome.

Response. Feedrate control to the extent necessary to achieve the liquid fuel boiler standards is not practical for reasons just discussed. This source is one of two available sources that is authorized to treat mixed waste, and the other source is not likely to have the ability to burn mercury-bearing organic waste in the future due to permit limitations and size constraints.

Comment. The commenter states that mixed legacy waste should not be burned at all. If there are truly no other facilities that are currently permitted to dispose of mixed legacy waste, such waste should be stored until a facility that can treat such waste safely—e.g., through chemical oxidation—can be permitted.

Response. The commenter's suggestion is beyond the scope of today's rulemaking. The suggestion is also illegal, since RCRA prohibits the storage of hazardous waste for extended periods. See RCRA section 3004(j); and *Edison Electric Inst.* v. *EPA*, 996 F. 2d 326, 335–37 (DC Cir. 1993) (illegal under RCRA section 3004(j) to store hazardous waste pending development of a treatment technology). EPA also notes that it retains authority under RCRA section 3005(c) (the so-called omnibus permitting authority) by which permit writers can adopt more stringent emission standards in RCRA permits if they determine that today's standards are not protective of human health and the environment.

2. Different Mercury, Semivolatile Metals, Chromium, and Total Chlorine Standards for Liquid Fuel Boilers Depending on the Heating Value of the Hazardous Waste Burned

Comment. Several commenters state that liquid fuel boilers should have an alternative concentration-based standard in addition to the thermal emission-based standard. Liquid fuel boilers are typically "captive" units that burn waste fuels generated from on-site or nearby manufacturing operations, rather than accepting wastes from a wide variety of other sources. Because they have captive fuel sources, operators generally do not have fuel blending capabilities. Liquid fuel boilers "burn what they have," and as such have very limited operational flexibility. EPA should not penalize boilers that have the same mass concentrations of metals or chlorine in their waste compared to other boilers, but which wastes have a lower heating value than wastes burned by other boilers. (The "penalty" is that emissions limits that are normalized by the heating value of the hazardous waste require that less volume of lower heating value waste can be burned compared to higher heating value fuel.) This problem is made worse by the limited data base for liquid fuel boilers,

[169] Although the legacy waste that DSSI is burning is nominally classified as a nonwastewater due to its high organic content, it is in fact a liquid matrix, meaning that the treatment standard of 0.025 μg/l is effectively a total standard.

the lack of historical data to verify that these standards are achievable over time, and having most or all of the measured emissions below detection limits. In addition, most of the mercury and semivolatile metal data EPA has in the data base were obtained during normal operations and while the source demonstrated compliance with RCRA's chromium standard—the other metals data were available only because stack method Method 29 reports data for all RCRA metals, even ones that are not at issue for the compliance test. (Sources generally elected to comply with the BIF Tier I metals emissions levels, but Tier III for chromium. Thus, the Method 29 test for chromium will give emissions results for all the metals—even those not subjected to stack testing—not just chromium.)

Response. As explained earlier in Part Four, Section V.A., EPA has selected normalizing parameters that best fit the input to the combustion device. A thermal normalizing parameter (i.e., expressing the standards in terms of amount of HAP contributed by hazardous waste per thermal content of hazardous waste) is appropriate where hazardous waste is being used in energy-recovery devices as a fuel, since the waste serves as a type of fuel. Using a thermal normalizing parameter in such instances avoids the necessity of subcategorizing based on unit size.

The commenters raise the other side of the same issue. As the commenters point out, some liquid fuel boilers burn lower Btu hazardous waste because that is the waste available to them, and those with waste that has a low heating value are, in their words, "penalized," compared to those with a high(-er) heating value. Also, since these are not commercial combustion units, they normally lack the opportunity to blend wastes of different heating values to result in as-fired high heating value fuels. If boiler standards are normalized by hazardous waste heating value, sources with lower heating value waste must either reduce the mass concentration of HAP or increase the waste fuel heating value (or increase the system removal efficiency) compared to sources with wastes having the same mass concentration of HAP but higher heating value.

Moreover, the thermal normalizing parameter is not well suited for a hazardous waste that is not burned entirely for its fuel value. In cases where the lower heating value waste is burned, the boiler is serving—at least in part—as a treatment device for the lower heating value hazardous waste. When this occurs, the better normalizing parameter is the unit's gas flow (a different means of accounting for sources of different size), where the standard is expressed as amount of HAP per volume of gas flow (the same normalizing parameter used for most of the other standards promulgated in today's final rule.)

The commenters requested that liquid fuel boilers be able to select the applicable standard (i.e., to choose between normalizing parameters) and further requested that we assess the performance of these units (for the purpose of establishing concentration-based MACT floor levels) by using the same MACT pool of best performing sources expressed on a thermal emissions basis.

Neither of these suggestions is appropriate. Choice of normalizing parameter is not a matter of election, but rather reflects an objective determination of what parameter is reasonably related to the activity conducted by the source. Moreover, the commenter's suggestion to use thermal emissions to measure best performance for a concentration-based standard does not make sense. It arbitrarily assumes that the best performers with respect to low and high heating value wastes are identical.

Instead, we have established two subcategories among the liquid fuel boilers: those burning high and those burning low heating value hazardous waste. The normalizing parameter for sources burning lower energy hazardous waste is that used for the other hazardous waste treatment devices, gas flow rate, so that the standard is expressed as concentration of HAP per volume of gas flow (a concentration-based form of the standard.) The normalizing parameter for sources burning higher energy content hazardous waste is the thermal parameter used for energy recovery devices, such as cement kilns and lightweight aggregate kilns. For the purposes of calculating MACT floors, the best performers are then drawn from those liquid fuel boilers burning lower energy hazardous waste for the lower heating value subcategory, and from those liquid fuel boilers burning higher energy hazardous waste for the higher heating value subcategory[170]. (See Section 23.2 of Volume III of the Technical Support Document for more information.)

Moreover, liquid fuel boilers are not irrevocably placed in one or the other of these subcategories. Rather, the source is subject to the standard for one or the other of these subcategories based on the as-fired heating value of the hazardous waste it burns at a given time. Thus, when the source is burning for energy recovery, then the thermal emissions-based standard would apply. When the source is burning at least in part for thermal destruction, then the concentration based standard would apply. This approach is similar to how we have addressed the issue of normalization in other rules where single sources switch back and forth among inputs which are sufficiently different to warrant separate classification.[171]

We next considered what an appropriate as-fired heating value would be for each liquid fuel boiler subcategory. Although we have used 5000 Btu/lb (the heating value of lowest grade fuels such as scrap wood) in past RCRA actions as a presumptive measure of when hazardous waste is burned for destruction (see, e.g. 48 FR 11159 (March 16, 1983)), we do not think that measure is appropriate here. We used the 5,000 Btu/lb level to delineate burning for destruction from burning for energy recovery at a time when that determination meant the difference between regulation and nonregulation. See 50 FR 49166–167 (Nov. 29, 1985). This is a different issue from choosing the most reasonable normalizing parameter for regulated units (*i.e.*, units which will be subject to a standard in either case).

Instead, we are adopting a value of 10,000 Btu/lb as the threshold for subcategorization. This is approximately the heating value of commercial liquid fossil fuels. 63 FR 33782, 33788 (June 19, 1998) It is also typical of current hazardous waste burned for energy recovery. *Id.* Moreover, EPA has used this value in its comparable fuel specification as a means of differentiating fuels from waste. See *id.* and Table 1 to 40 CFR section 261.38, showing that EPA normalizes all

[170] We also agree that liquid fuel boilers present several unique circumstances, namely: they are often unable to blend fuel and have limited operational flexibility as a result; our data base on these sources' performance is relatively small; much of our mercury and semivolatile metals data is at or near detection limits; and much of the mercury and semivolatile metals data was obtained for other purposes, namely from risk burns or as a result of Method 29 testing to demonstrate compliance with a RCRA chromium standard. While not immediately important to the topic at hand—namely that not all liquid fuel boilers burn for energy recovery—they are secondary issues that we need to closely consider to make sure we do not estimate what the best performing 12% of sources are achieving in an unreasonable manner.

[171] See NESHAP for Stationary Combustion Turbines, 40 CFR section 63.6175 (definitions of "diffusion flame gas-fired stationary combustion turbine", "diffusion flame oil-fired stationary combustion turbine", "lean pre-mix gas-fired stationary combustion turbine" and "lean premix oil-fired stationary combustion turbine").

constituent concentrations to a 10,000 Btu/lb level in its specification for differentiating fuels from wastes.

We next examined the waste fuel being burned at cement kilns and lightweight aggregate kilns, which burn hazardous waste fuels to drive the process chemistry to produce products[172], to cross-check whether 10,000 Btu/lb is a reasonable demarcation value for subcategorizing. 10,000 Btu/lb is the minimum heating value found in burn tank and test report data we have for cement kilns and lightweight aggregate kilns[173]. We believe the cement kiln and light weight aggregate kiln data confirm that this is an appropriate cutpoint, since these sources are energy recovery devices that blend hazardous wastes into a consistent, high heating value fuel for energy recovery in their manufacturing process.

We then separated the liquid fuel boiler emissions data we had into two groups, sources burning hazardous waste fuel with less than 10,000 Btu/lb and all other liquid fuel boilers, and performed separate MACT floor analyses. (See Sections 13.4, 13.6, 13.7, 13.8, and 22 of Volume III of the Technical Support Document.) We calculated concentration-based MACT standards for these sources from their respective mercury, semivolatile metals, chromium, and total chlorine data.

Liquid fuel boilers will need to determine which of the two subcategories the source belongs in at any point in time. Thus, you must determine the as-fired heating value of each batch of hazardous waste fired so that you know the heating value of the hazardous waste fired at all times.[174] If the as-fired heating value of hazardous wastes varies above and below the cutpoint (i.e., 10,000 Btu/lb) at times, you are subject to the thermal emissions standards when the heating value is not less than 10,000 Btu/lb and the mass concentration standards when the heating value is less than 10,000 Btu/lb. To avoid the administrative burden of frequently switching applicable operating requirements between the subcategories, you may elect to comply with the more stringent operating requirements that ensure compliance with the standards for both subcategories.

Comment: EPA's attempt to give actual performance two different meanings within a single floor approach is unlawful, unexplained, internally inconsistent, and arbitrary. If EPA believes that mass-based emissions constitute sources' actual performance, the best performing sources must be those with the best mass based emissions—not thermal emissions.

Response: As just explained, we agree with this comment, and have developed MACT floors independently for the two subcategories of liquid fuel boilers. Thus, we have defined two separate MACT pools based on the thermal input of the waste fuel and derived two separate and consistent MACT standards for sources when they burn solely for energy recovery, and when they do not.

We also note that a source cannot "pick and choose" the less stringent of the two standards and comply with those. The source must be in compliance with the set of standards that apply.

3. Alternative Particulate Matter Standard for Liquid Fuel Boilers

Comment: A commenter requested that EPA establish standards that allow boilers the option to comply with either a concentration-based particulate matter standard or thermal emissions-based particulate matter standard.

Response: We determined that it is appropriate to express the particulate matter emission standard as a concentration-based standard consistently across source categories and not to give boilers the option to comply with a thermal emissions-based particulate matter standard. As discussed in Part Four, Section III.D as well as the preceding section, metal and chlorine concentration-based emission standards can be biased against sources that process more hazardous waste (from an energy demand perspective), in part because the SRE/Feed methodology assesses feed control of each source when identifying the best performing sources; the ranking procedure thus favors sources with lower percentage hazardous waste firing rates (keeping all other assessment factors equal). The thermal emission standard format eliminates this firing rate bias, which amounts to a limitation on the amount of raw material (hazardous waste fuel to an energy recovery device) that may be processed, when identifying best performing sources.

The methodology we use to identify best performing sources for particulate matter emissions is not affected by the firing rate bias in the manner that metal and chlorine emissions are. This is primarily because we define best performing sources as those with the best back-end air pollution control technology; feed control is not assessed (specifically ash feed control) for raw materials, fossil fuel, or unenumerated HAP metal in the hazardous waste. The hazardous waste firing rate bias is therefore not present when we identify the best performing particulate matter sources because a source's hazardous waste firing rate is not a direct factor in the ranking procedure.

We also note that four of the nine best performing liquid fuel boilers for particulate matter are equipped with fabric filters. Particulate matter emissions from sources equipped with fabric filters are not significantly affected by ash inlet loading. This is not true for metals and chlorine, given metal and chlorine emissions from fabric filters tend to increase at increased feed rates. See Volume III of the Technical Support Document, Sections 5.3 and 7.4. We conclude that the hazardous waste firing rate issue is not a concern for these sources given their particulate matter emissions would not be significantly affected by increased hazardous waste firing rates.

4. Long-term, Annual Averaging Is Impermissible

Comment: Standards expressed as long-term limits are legally impermissible because those levels, by definition, would sometimes be greater than the average emission levels achieved by the best performing sources. Compliance also must be measured on a continuous basis, under section 302(k) of the Act. Thus, floor levels (and standards) for mercury expressed as long-term limits are illegal.

Response: The commenter maintains that the statutory command in section 112(d)(3)(A) to base floor standards for existing sources on "the average emission limitation achieved by the best performing 12 percent of * * * existing sources" precludes establishing standards expressed as long term averages because certain daily values could be higher. We do not accept this position. The statute does not state what type of "average" performance EPA must assess. Long term, i.e., annual, averaging of performance is quite evidently a type of average, and so is permissible under the statutory text. Moreover, it is reasonable to establish

[172] The Norlite light-weight aggregate kiln was not included in this analysis because they claim they are *not* burning for energy recovery. The waste Norlite burns is 4,860 Btu/lb or lower. This is indicative of a source burning solely for thermal treatment of the waste and not, at least in part, for energy recovery. See 40 CFR 266.100(d)(2)(ii).

[173] The cement kiln burn tank data and test report data shows the minimum heating values of 9,900 and 10,000 Btu/lb, respectively, for the hazardous waste. The minimum lightweight aggregate kiln heating values for hazardous waste was 10,000 Btu/lb, excluding the Norlite source.

[174] If you burn hazardous waste in more than one firing nozzle, you must determine the mass-weighted average heating value of the as-fired hazardous waste across all firing nozzles.

standards on this basis (the standards being the average of the best performing sources, expressed as a long-term average), where sufficient data exist. Indeed, since the principal health concern posed by the emitted HAP is from chronic exposure (i.e. cumulative exposure over time), long-term standards (which reduce the long-term distribution of emitted HAP) arguably would be preferable in addressing the chief risks posed by these sources' emissions.

We establish standards with long-term averaging limits whenever we use normal data to estimate long-term performance. We do this in the few instances where there are insufficient data (whether normal data or compliance test data) to estimate each source's short term emission levels (e.g., mercury and semivolatile metal standards for liquid fuel boilers).[175] One or two snapshot data based on normal operations are not likely to reflect a source's short-term operating levels in part because feed control levels can vary over time.[176] See *Mossville*, 370 F. 3d at 1242 (varying feed rates lead to different emission levels, and this variability must be encompassed within the floor standard because the standard must be met at all times). As a result, snapshot normal emissions, when averaged together, better reflect a source's long term average emissions. An emission standard based on normal data that is averaged together, but expressed as a short-term limit, would not be achievable by the best performing sources because it would not adequately account for their emissions variability. See *National Wildlife Federation* v. *EPA*, 286 F. 3d at 572–73 ("[c]ontinuous operation at or near the daily maximum would in fact result in discharges that exceed the long-term average. Likewise, setting monthly limitations at the 99th percentile would not insure that the long-term average is met"). Long-term limits better account for this variability because such limits allow sources to average their varying feed control levels over time while still assuring average emissions over this period are below the levels demonstrated by the best performing sources.

Indeed, under the commenter's approach where no averaging of intra-source data would be allowed, sources would not be in compliance with the standards during the performance tests themselves. The tests consist of the average of three data runs, so half of the emissions-weighted data points would be impermissibly higher than the average during the test used to derive today's emission standards.

EPA also does not see that section 302(f) of the Act, cited by the commenter, supports its position. That provision indicates that the emission standards EPA establishes must limit the quantity, rate, or concentration of air pollutants on a continuous basis. A standard expressed as a long-term average does so by constraining the overall distribution of emissions to meet a long-term average. Also, long term limits result in emission standards that are lower than those that otherwise would be implemented on a short-term basis. The short-term limit would have to reflect the best performing sources' short term emissions variability (i.e., the maximum amount of variability a source could experience during a single test period). *National Wildlife Federation*, 286 F. 3d at 571–73.

Comment: Other commenters argued the opposite point, that ERA has no data to show that an annual average is achievable, and EPA should establish a longer averaging period.

Response: We believe that all sources can achieve the mercury and semivolatile metals standards for liquid fuel boilers on an annual basis using some combination of MACT controls, i.e., feed control, back end control, or some combination of both. We agree that we have a small data set for these standards, but also believe that it is intuitive that a liquid fuel boiler can meet these standards on an annual basis, because one year is sufficiently more than any seasonal (i.e., several month long) production of certain items that may not be represented by the tests we have.

This informs us that an average of less than a year may not be achievable. It does not inform us that averaging of more than a year is required, since variations that occur with a year are averaged together. An annual average is sufficient for a source to determine whether an individual waste stream impacts negatively on the compliance of the liquid fuel boiler and take measures to address the issue.

5. Gas Fuel Boilers

Comment: How can a boiler burning only gaseous waste also be burning hazardous waste? Uncontained gases are not considered hazardous waste under RCRA. Why are boilers that burn only gasses part of the liquid fuel boiler subcategory?

Response: We agree with the commenter that boilers that burn gasses are unlikely to burn hazardous wastes. However, gas fuel hazardous waste boilers have existed in the past,[177] and we believe we need to define a MACT standard for them. Therefore, we included gas fuel boilers in the liquid fuel boiler subcategory for reasons cited in the proposed rule. See 69 FR at 21216.

E. General

1. Alternative to the Particulate Matter Standards

Comment: Commenters state that some incinerators are currently complying with the alternative to the particulate matter standard provision pursuant to the interim standards. See § 63.1206(b)(14). The eligibility and operating requirements for the alternative to the particulate matter standard in the Interim Standards are different than the proposed alternative to the particulate matter standard in the replacement rule. Specifically, the proposed alternative to the particulate matter standard would no longer require sources to demonstrate a 90% system removal efficiency or a minimum hazardous waste metal feed control level to be eligible for the alternative. Commenters request that EPA clarify in the final rule that the proposed alternative to the particulate matter standard supersedes the requirements in the Interim Standards.

Response: We are finalizing the alternative to the particulate matter standard for incinerators as proposed, with the exception that the alternative metal emission limitations have been revised as a result of database changes since proposal. See § 1219(e) and part three, section II.A. We considered superseding the interim standard alternative to the particulate matter standard requirements (63.1206(b)(14)) immediately (upon promulgation) by replacing it with the revised alternative

[175] Two emission standards in this rulemaking are based on normal data but are expressed as short term limits (the mercury standards for lightweight aggregate and cement kilns). However, in these instances we had enough normal data to reasonably estimate each source's maximum emissions, thus allowing us to express the standard as a short term limit. See USEPA, "Technical Support Document for HWC MACT Standards, Volume III: Selection of MACT Standards," September 2005, Sections 11.2 and 12.2.

[176] This is not the case for floors that are based on compliance tests because sources spiked their hazardous wastes to account for variability in hazardous waste feedrate. See Part Four, Section III.C above. Normal data, however, are a snapshot of what occurred on that day and are not likely to be representative over the long term, especially for mercury and semivolatile metals for liquid fuel boilers, where these limited data were almost entirely below the analytic detection limit.

[177] For example, sources 2014 and 2015 owned by Environmental Purification Industries in Toledo, Ohio, were considered hazardous waste boilers at the time the Phase II data base was noticed in the June 27, 2000, despite the fact that these boilers burned only gasses. These boilers have since stopped burning hazardous waste.

standard provisions finalized in today's rule. Although the eligibility requirements for the alternative to the particulate matter standard finalized today are less stringent than the interim standard requirements, the metal emission limitations that are also required by the alternative finalized today are by definition equivalent to or more stringent than the metal limitations in the interim standard alternative. We therefore cannot completely supersede the interim standard provisions immediately (upon promulgation) because sources have three years to comply with more stringent standards. We are instead revising the interim standard provisions of § 63.1206(b)(14) to only reflect the revised alternative standard eligibility criteria (specifically, we have removed the requirements to achieve a given system removal efficiency and hazardous waste metal HAP feed control level).[178] These eligibility criteria revisions become effective immediately with respect to the interim standards because they are less stringent than the current requirements. Sources should modify existing Notifications of Compliance and permit requirements as necessary prior to implementing these revised procedures.

Comment: One commenter is opposed to the alternative to the particulate matter standard because it ignores the health effects/benefits that are attributable to particulate matter.

Response: Particulate matter is not defined as a hazardous air pollutant pursuant the NESHAP program. See CAA 112(b)(1). We control particulate matter as a surrogate for metal HAP. See part four, section IV.A. As a result, a particulate matter standard is not necessary in instances where metal HAP emission standards can alternatively and effectively control the nonmercury metal HAP that is intended be controlled with the surrogate particulate matter standard. The alternative to the particulate matter standard in the final rule accomplishes this. We acknowledge that particulate matter emission reductions result in health benefits. That in itself does not give EPA the authority under § 112(d)(2) to directly regulate particulate matter, however.

[178] Sources can only use § 63.1206(b)(14) for purposes of complying with the interim standards. After the compliance date for today's rule, incinerators electing to comply with the alternative to the particulate matter standard must comply with the provisions found in § 63.1219(e).

2. Assessing Risk as Part of Consideration of Nonair Environmental Impacts

Comment: Commenter states that EPA has inappropriately failed to consider emissions of persistent bioaccumulative pollutants in its beyond-the-floor analysis despite EPA's acknowledgment that these HAPs have non-air quality health and environmental impacts.

Response: EPA has taken the consistent position that considerations of risk from air emissions have no place when setting MACT standards, but rather are to be considered as part of the residual risk determination and standard-setting process made under section 112 (f) of the statute. EPA thus interprets the requirement in section 112 (d) (2) that we consider "non-air quality health and environmental impacts" as applying to the by-product outputs from utilization of the pollution control technology, such as additional amount of waste generated, and water discharged.[179] EPA's interpretation was upheld as reasonable in *Sierra Club* v. *EPA*, 353 F. 3d 976, 990 (D.C. Cir. 2004) (Roberts, J.).

VII. Health-Based Compliance Alternative for Total Chlorine

A. Authority for Health-Based Compliance Alternatives

Comment: One commenter states there is no established health threshold for either HCl or chlorine.

Response: Although EPA has not developed a formal evaluation of the potential for HCl or chlorine carcinogenicity (e.g., for IRIS), the evaluation by the International Agency for Research on Cancer stated that there was inadequate evidence for carcinogenicity in humans or experimental animals and thus concluded that HCl and chlorine are not classifiable as to their carcinogenicity to humans (Group 3 in their categorization method). Therefore, for the purposes of this rule, we have evaluated HCl and chlorine only with regard to non-cancer effects. In the absence of specific scientific evidence to the contrary, it has been our policy to classify non-carcinogenic effects as threshold effects. RfC development is the default approach for threshold (or nonlinear) effects.

Comment: One commenter states that the proposal is an inappropriate forum for bringing forward such a significant change in the way that MACT standards are established under Section 112(d) of the Clean Air Act. A precedent-setting change of the magnitude that EPA has raised should be discussed openly and carefully with all affected parties, rather than being buried in several individual proposed standards.

Response: Including health-based compliance alternatives for hazardous waste combustors does not mean that EPA will automatically provide such alternatives for other source categories. Rather, as has been the case throughout the MACT rule development process, EPA will undertake in each individual rule to determine whether it is appropriate to exercise its discretion to use its authority under CAA section 112(d)(4) in developing applicable emission standards. Stakeholders for those affected rules will have ample opportunity to comment on the Agency's proposals.

Comment: One commenter states that the proposed approach is contrary to the intent of the CAA which explicitly calls for a general reduction in HAP emissions from all major sources nationwide through the establishment of MACT standards based on technology, rather than risk, as a first step.

Response: For pollutants for which a health threshold has been established, CAA section 112(d)(4) allows the Administrator to consider such threshold level, with an ample margin of safety, to establish emission standards.

Comment: One commenter states that the proposed approach would take the national air toxics program back to the time-consuming NESHAP process that existed prior to the Clean Air Act Amendments of 1990.

Response: We disagree that allowing a health-based compliance alternative in the final rule will alter the MACT program or affect the schedule for promulgation of the remaining MACT standards. Today's rule is the last MACT rule to be promulgated, and the health-based compliance alternative did not delay promulgation of the rule.

Comment: A commenter is concerned that the proposal would remove the benefit of the "level-playing field" that would result from the proper implementation of technology-based MACT standards.

Response: Providing health-based compliance alternatives in the final rule for sources that can meet them will assure the application of a uniform set of requirements across the nation. The final rule and its criteria for demonstrating eligibility for the health-based compliance alternatives apply uniformly to all hazardous waste combustors except hydrochloric acid

[179] See USEPA, "Technical Support Document for the HWC MACT Standards, Volume V: Emission Estimates and Engineering Costs," September 2005, Section 6, for a discussion of the non-air impact that were assessed for this final rule.

production furnaces. The final rule establishes two baseline levels of emission reduction for total chlorine, one based on a traditional MACT analysis and the other based on EPA's evaluation of the health threat posed by emissions of HCl and chlorine. All hazardous waste combustor facilities must meet one of these baseline levels, and all facilities have the same opportunity to demonstrate that they can meet the alternative health-based emission standards. We also note that additional uniformity is provided by limiting the health-based compliance alternatives for incinerators, cement kilns, and lightweight aggregate kilns to the emission levels allowed by the Interim Standards.

Comment: Several commenters state that site-specific emission limits are inappropriate under section 112(d)(4) because they are not emission standards. One commenter asserts that the Agency's position that the limits are based on uniform procedures is flawed because the process allows "any scientifically-accepted, peer-reviewed risk assessment methodology for your site-specific compliance demonstration." This is not a "uniform" procedure, according to the commenter. There are a host of variables that influence the results of an accepted methodology. The commenter reasons that, without some standardization of those variables, there is no uniform or standard analysis. Each permitting authority could establish its view of appropriate variables; there would be no national consistency.

Several other commenters assert that EPA has the authority to establish an exposure-based emission limit for total chlorine. One commenter notes that one issue that often arises when considering risk-based standards is whether EPA has authority under section 112 to establish an exposure-based emission limit. The commenter states that the concern seems to be that some stakeholders construe the Act's statutory provisions as requiring uniform emission limitations at all facilities, rather than emissions that are measured at places away from the source and that vary from facility to facility. The commenter does not see any legal impediment to establishing exposure-based limits.

The commenter notes that, first, under section 112, EPA has authority to establish "emission standards." Emission standards are defined to be a requirement established by the State or the Administrator which limits the quantity, rate or concentration of emissions of air pollutants on a continuous basis * * * to assure continuous emission reduction, and any design, equipment, work practice or operational standard promulgated under this chapter. EPA's alternate risk-based emission standard will limit the quantity, rate or concentration of the emissions. The commenter states that there is no requirement in the definition that specifies where the emission standard is to be measured, nor is there such a requirement anywhere in the statute.

Second, the commenter notes that EPA's proposed exposure-based limit will result in facilities establishing operating parameter limitations, or OPLs. These OPLs qualify as emission limitations because they are "operational standards" being promulgated under section 112, according to the commenter. They will be measured at the facility, not at the point of exposure. Finally, the commenter reasons that the limitations EPA is establishing are uniform. They uniformly protect the individual most exposed to emission levels no higher than a hazard index of 1.0. Consequently, the commenter believes that there is nothing in the statute that prevents the Agency from promulgating exposure-based emission standards.

Response: We agree with the commenters who believe the Agency has the authority to establish health-based compliance alternatives under a national exposure standard. In particular, we agree with the commenter that the health-based compliance alternatives are national standards since they provide a uniform and national measure of risk control, and also that the health-based compliance alternatives are "emission standards" because they limit the quantity, rate or concentration of total chlorine emissions.

Section 112(d)(4) authorizes EPA to bypass the mandate in section 112(d)(3) in appropriate circumstances. Those circumstances are present for hazardous waste combustors other than hydrochloric acid production furnaces. Section 112(d)(4) provides EPA with authority, at its discretion, to develop health-based compliance alternatives for HAP "for which a health threshold has been established," provided that the standard reflects the health threshold "with an ample margin of safety."

Both the plain language of section 112(d)(4) and the legislative history indicate that EPA has the discretion under section 112(d)(4) to develop health-based compliance alternatives for some source categories emitting threshold pollutants, and that those standards may be less stringent than the corresponding MACT standard (including floor standards) would be.[180] EPA's use of such standards is not limited to situations where every source in the category or subcategory can comply with them. As with technology-based standards, a particular source's ability to comply with a health-based standard will depend on its individual circumstances, as will what it must do to achieve compliance.

In developing health-based compliance alternatives under section 112(d)(4), EPA seeks to ensure that the concentration of the particular HAP to which an individual exposed at the upper end of the exposure distribution is exposed does not exceed the health threshold. The upper end of the exposure distribution is calculated using the "high end exposure estimate," defined as "a plausible estimate of individual exposure for those persons at the upper end of the exposure distribution, conceptually above the 90th percentile, but not higher than the individual in the population who has the highest exposure" (EPA Exposure Assessment Guidelines, 57 FR 22888, May 29, 1992). Assuring protection to persons at the upper end of the exposure distribution is consistent with the "ample margin of safety" requirement in section 112(d)(4).

We agree with the view of several commenters that section 112(d)(4) is appropriate for establishing health-based compliance alternatives for total chlorine for hazardous waste combustors other than hydrochloric acid production furnaces. Therefore, we have established such compliance alternatives for affected sources in those categories. Affected sources which believe that they can demonstrate compliance with the health-based compliance alternatives may choose to comply with those compliance alternatives in lieu of the otherwise applicable MACT-based standard.

Comment: One commenter states that the risk assessments would not provide an ample margin of safety because background exposures are not taken into account. There is no accounting for other chlorine compounds from other sources at the facility, or from other neighboring facilities. The commenter believes that there is no evidence in the section 112(f) residual risk assessments produced thus far that emissions from collocated sources will actually be pursued by EPA. The commenter also notes that the Urban Air Toxics program cannot be relied upon to address ambient background. This program,

[180] See also Legislative History at 876 (section 112(d)(4) standard may be less stringent than MACT).

required under section 112(k), was to be completed by 1999. However, the strategy has not been finalized and the small amount of activity in this area is focused on *voluntary* emission reductions rather than federal requirements. Finally, the commenter notes that control of criteria pollutants via State Implementation Plans to achieve compliance with the NAAQS is problematic. For particulate matter (PM) and ozone, new NAAQS were set in 1997 and seven years later the nonattainment designations are still being determined. The designation process will be followed by a 3 year period to prepare State Implementation Plans and several more years to carry out those plans. In the meantime, there will be high levels of PM and ozone in the air near many hazardous waste combustors in New Jersey which will exacerbate exposures to chlorine and hydrogen chloride.

Response: Total chlorine missions from collocated hazardous waste combustors must be considered in establishing health-based compliance alternatives under § 63.1215. Ambient levels of HCl or chlorine attributable to other on-site sources, as well as off-site sources, are not considered, however. As we indicated in the Residual Risk Report to Congress and in the recent residual risk rule for Coke Ovens, the Agency intends to consider facility-wide HAP emissions as part of the ample margin of safety determination for CAA section 112(f) residual risk actions. 70 FR at 19996–998 (April 15, 2005); see also, 54 FR at 38059 (Sept. 14, 1989) (benzene NESHAP).

Comment: Several commenters state that acute exposure guideline levels (AEGLs) are *once-in-a-lifetime* exposure levels. They assert that, because short term exposures at a Hazard Index greater than 1.0 may occur more than once in a lifetime, using AEGLs for the purpose of setting risk-based short-term limits for HCl and chlorine does not provide an "ample margin of safety."

Response: To assess acute exposure, we proposed to use acute exposure guideline levels for 1-hour exposures (AEGL–1) as health thresholds. We have investigated commenters' concerns, however, and conclude that AEGLs are not likely to be protective of human health because individuals may be subject to multiple acute exposures at a Hazard Index greater than 1.0 from hazardous waste combustors. Consequently, we use acute Reference Exposure Levels (aRELs) rather than acute exposure guideline levels (AEGLs) as acute exposure thresholds for the final rule. See also Part Two, Section IX.D above. Acute RELs are health thresholds below which there would be no adverse health effects while AEGL–1 values are health thresholds below which there may be mild adverse effects.

Acute exposures are relevant (in addition to chronic exposures) and the acute exposure hazard index of 1.0 could be exceeded multiple times over an individual's lifetime. Although we concluded at proposal that the chronic exposure Hazard Index would always be higher than the acute exposure Hazard Index, and thus would be the basis for the total chlorine emission rate limit, this conclusion relates to acute versus chronic exposure to a constant, maximum average emission rate of total chlorine from a hazardous waste combustor. See 69 FR at 21300. We explained that acute exposure must nonetheless be considered when establishing operating requirements to ensure that short-term emissions do not result in an acute exposure Hazard Index of greater than 1.0. This is because total chlorine and chloride feedrates to a hazardous waste combustor (e.g., commercial incinerator) can vary substantially over time. Although a source may remain in compliance with a feedrate limit with a long-term averaging period (e.g., 12-hour, monthly, or annual) based on the chronic Hazard Index, the source could feed chlorine during short periods of time that substantially exceed the long-term feedrate limit. This could result potentially in emissions that exceed the one-hour (i.e., acute exposure) Hazard Index. Consequently, we discussed at proposal the need to establish both short-term and long-term total chlorine and chloride feedrate limits to ensure that neither the chronic exposure nor the acute exposure Hazard Index exceeds 1.0.[181]

We conclude that 1-hour Reference Exposure Levels (aRELs) are a more appropriate health threshold metric than AEGL–1 values for hazardous waste combustors given that the acute Hazard Index limit of 1.0 may be exceeded multiple times over an individual's lifetime, albeit resulting from uncontrollable factors. The California Office of Health Hazard Assessment has developed acute health threshold levels that are intended to be protective for greater than once in a lifetime exposures. The acute exposure levels are called acute Reference Exposure Levels and are available at *http://www.oehha.ca.gov/air/acute_rels/acuterel.html.*

The 1-hour REL values for hydrogen chloride and chlorine are 2.1 mg/m^3 and 0.21 mg/m^3, respectively. The AEGL–1 values for hydrogen chloride and chlorine are 2.7 mg/m^3 and 1.4 mg/m^3, respectively. Although there is little difference between the 1-hour REL and AEGL–1 values for hydrogen chloride, the 1-hour REL for chlorine is substantially lower than the AEGL–1 value.

In summary, we believe that aRELs are a more appropriate health threshold metric than AEGL–1 values for establishing health-based compliance alternatives for hazardous waste combustors because aRELs are "no adverse effect" threshold levels that are intended to be protective for multiple exposures.

Comment: One commenter states that the health-based compliance alternative is unlawful because the proposal does not address ecological risks that may result from uncontrolled HAP emissions, including risks posed to those areas where few people currently live, but sensitive habitats exist.

Response: An ecological assessment is normally required under CAA section 112(d)(4) to assess the presence or absence of "adverse environmental effects" as that term is defined in CAA section 112(a)(7). To identify potential multimedia and/or environmental concerns, EPA has identified HAP with significant potential to persist in the environment and to bioaccumulate. This list does not include hydrogen chloride or chlorine.

We also note that health-based total chlorine emission limits for incinerators, cement kilns, and lightweight aggregate kilns cannot be higher than the current Interim Standards. See § 63.1215(b)(7). Thus, the ecological risk from total chlorine emissions from these sources will not be increased under the health-based limits.

In addition, we note that only 2 of 12 solid fuel boilers have total chlorine emissions higher than 180 ppmv, and only 1 liquid fuel boiler has emissions higher than 170 ppmv. Thus, boilers generally have low total chlorine emissions which would minimize ecological risk.

Consequently, we do not believe that emissions of hydrogen chloride or chlorine from hazardous waste boilers will pose a significant risk to the environment, and facilities attempting to comply with the health-based

[181] Note that we conclude for the final rule that most sources are not likely to exceed the acute Hazard Index because they will establish a 12-hour rolling average chlorine feedrate limit and their chlorine feedrates are not likely to vary substantially over that averaging period. Thus, we believe that most sources will not be required to establish an hourly rolling average chlorine feedrate limit. The owner/operator must determine whether the hourly rolling average chloride feedrate limit can be waived under § 63.1215(d).

alternatives for these HAP are not required to perform an ecological assessment.

B. Implementation of the Health-Based Standards

Comment: Several commenters are concerned that the health-based compliance alternative will place an intensive resource demand on state and local agencies to review and approve facilities' eligibility demonstrations, and State and local agencies may not have adequate expertise to review and approve the demonstrations. One commenter states that permitting authorities do not have the expertise to review eligibility demonstrations that are based on procedures other than those included in EPA's Reference Library, as would be allowed. The commenter also states that, if the health-based compliance alternative is promulgated, EPA should establish one standard method for the analyses so there is consistency nationwide. If EPA offers more than one method, EPA should do all of the risk assessment reviews, instead of passing the responsibility, without clear direction, to the permitting authorities, according to the commenter.

Response: The health-based compliance alternatives for total chlorine that EPA has adopted in the final rule should not impose significant resource burdens on states. The required compliance demonstration methodology is structured in such a way as to avoid the need for states to have significant expertise in risk assessment methodology. We have considered the commenters' concerns in developing the criteria defining eligibility for these compliance alternatives, and the approach that is included in the final rule provides clear, flexible requirements and enforceable compliance parameters. The final rule provides two ways that a facility may demonstrate eligibility for complying with the health-based compliance alternatives. First, look-up tables allow facilities to determine, using a limited number of site-specific input parameters, whether emissions from their sources might cause the Hazard Index limit to be exceeded. Second, if a facility cannot demonstrate eligibility using a look-up table, a modeling approach can be followed. The final rule presents the criteria for performing this modeling.

Only a portion of hazardous waste combustors will submit eligibility demonstrations for the health-based compliance alternatives. Of these sources, several should be able to demonstrate eligibility based on simple analyses—using the look-up tables. However, some facilities will require more detailed modeling. The criteria for demonstrating eligibility for the compliance alternatives are clearly defined in the final rule. Moreover, under authority of RCRA section 3005(c)(3), multi-pathway risk assessments will typically have already been completed for many hazardous waste combustors to document that emissions of toxic compounds, including total chlorine, do not pose a hazard to human health and the environment. Thus, state permitting officials have already reviewed and approved detailed modeling studies for many hazardous waste combustors. The results of these studies could be applied to the eligibility demonstration required by this final rule.

Because these requirements are clearly defined, and because any standards or requirements created under CAA section 112 are considered applicable requirements under 40 CFR part 70, the compliance alternatives would be incorporated into title V programs, and states would not have to overhaul existing permitting programs.

Finally, with respect to the burden associated with ongoing assurance that facilities that opt to do so continue to comply with the health-based compliance alternatives, the burden to states will be minimal. In accordance with the provisions of title V of the CAA and part 70 of 40 CFR (collectively "title V"), the owner or operator of any affected source opting to comply with the health-based compliance alternatives is required to certify compliance with those standards every five years on the anniversary of the comprehensive performance test. In addition, if the facility has reason to know of changes over which the facility does not have control, and these changes could decrease the allowable HCl-equivalent emission rate limit, the facility must submit a revised eligibility demonstration. Further, before changing key parameters that may impact an affected source's ability to continue to meet the health-based emission standards, the source is required to evaluate its ability to continue to comply with the health-based compliance alternatives and submit documentation to the permitting authority supporting continued eligibility for the compliance alternative. Thus, compliance requirements are largely self-implementing and the burden on states will be minimal.

Comment: One commenter suggests that the look-up tables would have more utility if EPA developed tables for each source category to ensure the HCl-equivalent emission rate limits reflected stack parameters representative of each source category. Similarly, another commenter notes that a look-up table designed to be applicable to all hazardous waste combustors is very conservative and will have limited utility. This commenter does not suggest that EPA develop look-up tables for each class of hazardous waste combustors, however. Rather, the commenter suggests that since look-up tables have already been developed for industrial boilers that do not burn hazardous waste[182] hazardous waste combustors should be allowed to use those look-up tables instead of the look-up tables proposed for hazardous waste combustors.

Response: We noted at proposal that the emission rates provided in the look-up table for hazardous waste combustors are more stringent than those promulgated for solid fuel industrial boilers that do not burn hazardous waste. This is because the key parameters used by the SCREEN3 atmospheric dispersion model (i.e., stack diameter, stack exit gas velocity, and stack exit gas temperature) to predict the normalized air concentrations that EPA used to establish HCl-equivalent emission rates for solid fuel industrial boilers that do not burn hazardous waste are substantially different for hazardous waste combustors. Thus, the maximum HCl-equivalent emission rates for hazardous waste combustors would generally be lower than those EPA established for solid fuel industrial boilers that do not burn hazardous waste.

Nonetheless, we agree with the commenter's concerns that the look-up tables would have more utility if they better reflected the range of stack properties representative of hazardous waste combustors. Accordingly, we examined the stack parameters for all hazardous waste-burning sources in our data base (except for hydrochloric acid production furnaces that are not eligible for the health-based emission standards). After analyzing the relationships among the various stack parameters (i.e., stack height, stack diameter, stack gas exhaust volume, and exit temperature), we concluded that the look-up table should be modified to treat both stack diameter and stack height as independent variables rather than relying on stack height alone.

We developed separate tables for short-term (i.e., 1-hour) HCl-equivalent

[182] See Table 2 of Appendix A to Subpart DDDDD, Part 63.

emissions limits to protect against acute health effects and long-term (i.e., annual) emission limits to protect against chronic effects from exposures to chlorine and hydrogen chloride. As discussed above, we used the acute Reference Exposure Level (aREL) developed by Cal-EPA as the benchmark for acute health effects. We used EPA's Reference Concentrations (RfC) as the benchmark for chronic health effects from exposures occurring over a lifetime.

Emission limits in the look-up table are expressed in terms of HCl-toxicity equivalent emission rates (lbs/hr). To convert your total chlorine emission rate (lb/hr) to an HCl-equivalent emission rate, you must adjust your chlorine emission rate by a multiplicative factor representing the ratio of the HCl health risk benchmark to the chlorine health risk benchmark. For 1-hour average HCl-equivalent emission rates, the ratio is the ratio of the aREL for HCl (2100 micrograms per cubic meter) to the aREL for chlorine (210 micrograms per cubic meter), or a factor of 10.[183] For annual average emissions, the ratio is the ratio of the RfC for HCl (20 micrograms per cubic meter) to the RfC of chlorine (0.2 micrograms per cubic meter), or a factor of 100. See § 63.1215(b).

We used the SCREEN3 air dispersion model to develop the emission limits in the look-up tables. SCREEN3 is a screening model that estimates air concentrations under a wide variety of meteorological conditions in order to identify the meteorological conditions under which the highest ambient air concentrations are likely to occur and what the magnitude of the ambient air concentrations are likely to be. The SCREEN3 model implements the procedures in EPA's "Screening Procedures for Estimating the Air Quality Impact of Stationary Sources, Revised" (EPA–454/R–92–019, U.S. Environmental Protection Agency, Office of Air Quality Planning and Standards, Research Triangle Park, NC, October 1992). Included are options for estimating ambient air concentrations in simple elevated terrain and complex terrain. Simple elevated terrain refers to terrain elevations below stack top. We did not use the complex terrain option in the development of the look-up tables because of the site-specific nature of plume impacts in areas of complex terrain. Therefore, the look-up tables cannot be used in areas of complex terrain (which we define generally as terrain that rises above stack top). Sources located in complex terrain (i.e., as a practical matter, sources other than those that are located in flat or simple elevated terrain as discussed below and thus cannot use the look-up tables) must use site-specific modeling procedures to establish HCl-equivalent emission rates.

We looked at two generic terrain scenarios for purposes of the look-up table. In one we assumed the terrain rises at a rate of 5 meters for every 100 meter run (i.e., a slope of 5 percent) and that terrain is "chopped off" above stack top (following the convention for such analyses in simple elevated terrain). In the other we assumed flat terrain. As can be seen from the tables in § 63.1215, the emission limits with flat terrain are significantly higher than those with simple elevated terrain. To reasonably ensure that the emission limits are not substantially over-stated (e.g., by a factor of 2), the simple elevated terrain table must be used whenever terrain rises to an elevation of one half (½) the stack height within a distance of 50 stack heights.

For both the simple elevated terrain and flat terrain scenarios, we performed model runs for urban and rural dispersion conditions, with and without building downwash. We selected the highest (ambient air concentration) values at each distance from among the four runs for each of the terrain scenarios.

As can be seen from the tables in § 63.1215, the HCl-equivalent emission rate limits range from 0.13 pounds per hour on an annual average (for a 0.3 meter diameter stack that is 5 meters tall that lies within 30 meters of the property boundary) to 340 pounds per hour (for a 4.0 meter diameter stack that is 100 meters tall that lies 5000 meters from the property boundary) when located in simple elevated terrain. In flat terrain, the range is from 0.37 to 1100 pounds per hour on an annual average. This contrasts with the look-up table at proposal, where the comparable range was from 0.0612 pounds per hour (for a 5 meter stack height at a distance of 30 meters) to a maximum of 18 pounds per hour (for stack heights of 50 meters or greater, at distances of 500 meters or greater).

If you have more than one hazardous waste combustor on site, the sum of the ratios for all combustors of the HCl-equivalent emission rate to the HCl-equivalent emission rate limit cannot exceed 1.0. See § 63.1215 (c)(3)(v). This will ensure that the Hazard Index of 1.0 is not exceeded considering emissions from all on-site combustors.

Comment: Several commenters state that facilities should be allowed to establish an averaging period for the total chlorine and chloride feedrate limit that is shorter than an annual rolling average. Commenters are referring to the feedrate limit to ensure compliance with the annual average HCl-equivalent emission rate limit. Commenters are concerned with the data handling issues that could arise from calculating, recording, and reporting an annual rolling average feedrate level that is updated hourly, and note that a shorter averaging period would make the limit more stringent.

Response: We agree with commenters, and conclude, moreover, that a 12-hour averaging period rather than an annual averaging period will be imposed on the vast majority of sources as a practical matter. This is because sources must establish a limit on the feedrate of total chlorine and chloride to ensure compliance with the semivolatile metals emission standards. See § 63.1209(n). The feedrate limit for total chlorine and chloride is established under § 63.1209(n) as the average of the hourly rolling averages for each test run, and the averaging period is 12 hours. Thus, the averaging period for the feedrate limit for semivolatile metals—12-hour rolling average updated hourly—trumps the annual rolling average averaging period that would otherwise apply here.[184]

Sources may also demonstrate compliance with the semivolatile metals standard by assuming all semivolatile metals in feedstreams are emitted. See § 63.1207(m)(2). Sources that do not have emission control equipment, such as most liquid fuel boilers, are particularly likely to use this approach. Under this approach, there is no concern regarding increased volatility of metals as chlorine feedrates increase, and such sources are not subject to a feedrate limit for chlorine for compliance assurance with the semivolatile metal standard. These sources may establish an averaging period for the feedrate of total chlorine and chloride for compliance with the health-based compliance alternative for total chlorine of not to exceed one year.[185]

[183] We note that this factor of 10 ratio of the aRELs of HCl to chlorine is based on current aREL values and is subject to change. You must use current aREL (and RfC) values when you conduct your eligibility demonstration. See § 63.1215(b)(4 and 5).

[184] To also ensure compliance with the annual average HCl-equivalent emission rate limit, however, the numerical value of the feedrate limit established during the semivolatile metals performance test cannot exceed the value calculated as the annual average HCl-equivalent emission rate limit divided by [1 − system removal efficiency], where you demonstrate the total chlorine system removal efficiency during the comprehensive performance test.

[185] We note that we have also applied this "not-to-exceed" approach to establishing the duration of

Comment: Several commenters offered suggestions on whether a short-term feedrate limit was needed for total chlorine and chloride (*i.e.*, chlorine) as EPA suggested, and if EPA continues to consider it necessary, how the limit should be established.

One commenter states that it is not necessary to set short-term limits for chlorine feedrates. If EPA concludes that short-term limits are necessary, however, the commenter recommended these options: (1) Cap the feedrate at a level that is extrapolated up to the feedrate associated with Interim Standard for incinerators; (2) if the facility uses the site-specific option to set emission limits, the dispersion models can easily be used to set a 1-hour (or longer) limit; and (3) if the facility uses the look up table (which at proposal provided only annual average HCl-equivalent emission rate limits), a short-term limit can be set based on a multiplier of the annual limit'10 times the annual limit as recommended by documents in EPA's Air Toxics Risk Assessment Reference Library.

Another commenter states that, if EPA were to promulgate a short-term feedrate limit, the EPA-endorsed factor of 0.08 employed to translate maximum hourly concentrations to annual concentrations could be used to identify the maximum hourly feedrate limit.

Finally, another commenter states that extrapolation of the chlorine feedrate (from the level during the comprehensive performance test when the source documents compliance with the annual average HCl-equivalent emission rate limit) should be allowed to 100% of the 1-hour average HCl-equivalent emission rate limit because numerous safety factors have already been included in the health risk threshold values, look-up tables, and modeling demonstration.

Response: At proposal, we explained that sources would establish an annual average feedrate limit on chlorine as the feedrate level during the comprehensive performance test demonstrating compliance with the annual average HCl-equivalent emission rate limit.[186] Only long-term exposures—maximum annual average exposures—need be considered when confirming that the chlorine feedrate during the comprehensive performance test (i.e., average of the hourly rolling averages for each run) is acceptable because the annual exposure Hazard Index limit (i.e., not to exceed 1.0) would always be exceeded before the 1-hour Hazard Index limit (i.e., not to exceed 1.0). Thus, the feedrate limit associated with annual exposures would always be more stringent than the feedrate limit associated with 1-hour exposures. See 69 FR at 21299.

We further explained at proposal, however, the need to establish a short-term feedrate limit for chlorine to ensure that the 1-hour HCl-equivalent emission rate did not exceed the 1-hour average HCl-equivalent emission rate limit due to variability in the chlorine feedrate during the annual averaging period for the feedrate limit. We requested comment on approaches to establish this 1-hour chlorine feedrate limit, including extrapolating feedrates to 100% of the 1-hour average HCl-equivalent emission rate limit. See 69 FR at 21304.

In the final rule we have corrected and refined these procedures. The final rule requires you to establish a long-term chlorine feedrate limit to maintain compliance with the annual average HCl-equivalent emission rate limit as either: (1) The chlorine feedrate during the comprehensive performance test if you demonstrate compliance with the semivolatile metals emission standard during the test (see § 63.1209(o)); or (2) if you comply with the semivolatile metals emission standard under § 63.1207(m)(2) by assuming all metals in the feed to the combustor are emitted, the annual average HCl-equivalent emission rate limit divided by [1 − system removal efficiency] where you demonstrate the system removal efficiency during the comprehensive performance test. See discussion in Part Two, Section IX.H, of this preamble. If you establish the chlorine feedrate limit based on the feedrate during the performance test to demonstrate compliance with the semivolatile metals emission standard, the averaging period for the feedrate limit is a 12-hour rolling average. If you establish the chlorine feedrate limit based on the system removal efficiency during the performance test, the averaging period is up to an annual rolling average.

The final rule also requires you to establish an hourly rolling average chlorine feedrate limit if you determine under § 63.1215(d)(3) that the 1-hour average HCl-equivalent emission rate limit may be exceeded. That feedrate limit is established as the 1-hour HCl-equivalent emission rate limit divided by [1 − system removal efficiency].

Under § 63.1215(d)(3), you must establish an hourly rolling average chlorine feedrate limit unless you determine considering specified criteria that your chlorine feedrates will not increase over the averaging period for the long-term chlorine feedrate limit (*i.e.*, 12-hour rolling average or (up to) annual rolling average) to a level that may result in an exceedance of the 1-hour average HCl-equivalent emission rate limit. The criteria that you must consider are: (1) The ratio of the 1-hour average HCl-equivalent emission rate based on the total chlorine emission rate you select for each combustor to the 1-hour average HCl-equivalent emission rate limit for the combustor; and (2) the potential for the source to vary chlorine feedrates substantially over the averaging period for the long-term chlorine feedrate limit.

For example, if a source's primary chlorine-bearing feedstreams have a relatively constant chlorine concentration over the averaging period for the chlorine feedrate limit to ensure compliance with the annual average HCl-equivalent emission rate limit (*e.g.*, generally 12-hours), as may be the case for commercial sources feeding from large burn tanks or on-site sources where chlorine levels in wastes are fairly constant, you may conclude that there is little probability that 1-hour feedrates would vary substantially over the averaging period. Thus, a 1-hour rolling average chlorine feedrate limit may not be warranted. Even if chlorine feedrates could vary substantially over the long-term feedrate averaging period, however, an hourly rolling average feedrate limit still may not be warranted if the source's 1-hour average HCl-equivalent emission rate is well below the 1-hour HCl-equivalent emission rate limit. See Part Two, Section IX.H, of this preamble for a discussion of the relationship between emission rates, emission rate limits, and feedrate limits.

We disagree with the commenter who states that short-term chlorine feedrate limits are not necessary. The 1-hour average HCl-equivalent emission rate limit could potentially be exceeded for sources with highly variable chlorine feedrates and where the 1-hour HCl-equivalent emission rate is relatively high compared to the 1-hour HCl-equivalent emission rate limit. The 1-hour average HCl-equivalent emission rate limit could be exceeded even though the source remains in compliance with the annual average HCl-equivalent emission rate limit [and,

averaging periods for the limits on all operating parameters established under § 63.1209. See new § 63.1209(r) and USEPA, "Final Technical Support Document for HWC MACT Standards, Volume IV: Compliance with HWC MACT Standards, September 2005, Section 2.4.6.

[186] We discussed at proposal that the feedrate limit to ensure compliance with the long-term Hazard Index limit of not to exceed 1.0 would be the average of the hourly rolling averages for each test run, with compliance based on an annual average. Note that, under the final rule however, the long-term chlorine feedrate limit is established as the annual average HCl-equivalent emission rate limit divided by [1 − system removal efficiency]. See § 63.1215(g)(2).

moreover, the 12-hour rolling average or (up to) annual rolling average chlorine feedrate limit).

We agree with commenters that suggest that the hourly rolling average chlorine feedrate limit should be extrapolated from performance test feedrates up to 100% of the 1-hour average HCl-equivalent emission rate limit. The final rule requires you to establish the hourly rolling average feedrate limit (if a limit is required under § 63.1215(d)(3)) as the 1-hour HCl-equivalent emission rate limit divided by [1 − system removal efficiency]. Establishing the hourly rolling average feedrate in this manner ensures that the 1-hour HCl-equivalent emission rate limit is not exceeded, and thus that the aREL-based Hazard Index of 1.0 is not exceeded.

We also agree in principle with commenters that suggest that the hourly rolling average feedrate limit be based on the 1-hour average HCl-equivalent emission rate limit which is based on emissions modeling. These commenters suggested that we use a multiplier of 10 or 12.5 (*i.e.*, 1/0.08) to project 1-hour average HCl-equivalent emission rate limits from the annual average HCl-equivalent emission rate limits. Rather than use these approaches to project 1-hour average emissions from annual average emissions, however, we use emissions modeling to develop look-up tables for both 1-hour average HCl-equivalent emission rate limits and annual average HCl-equivalent emission rate limits. For sources that use site-specific risk assessment to demonstrate eligibility, they will use the same models to estimate 1-hour average maximum ambient concentrations. Thus, the final rule uses modeling to establish directly 1-hour average HCl-equivalent emission rate limits rather than approximating those limits from annual average HCl-equivalent emission rate limits as commenters suggest. In summary, the final rule requires you to establish the 1-hour average HCl-equivalent emission rate limit by either using Tables 3 or 4 in § 63.1215 to look-up the limit, or conducting a site-specific risk analysis. Under the site-specific risk analysis option, the 1-hour average HCl-equivalent emission rate limit would be the highest emission rate that the risk assessment estimates would result in an aREL-based Hazard Index not exceeding 1.0 at any off-site receptor location.

We do not agree that the short-term feedrate limit should be capped at the level corresponding to the Interim Standards for incinerators, cement kilns, and lightweight aggregate kilns. The final rule caps the total chlorine emission rate and the annual average HCl-equivalent emission rate limit at the level equivalent to the Interim Standard for total chlorine. Thus, the long-term chlorine feedrate limit (12-hour rolling average or (up to) an annual rolling average) is capped at the level corresponding to the Interim Standards for incinerators, cement kilns, and lightweight aggregate kilns. The hourly rolling average feedrate limit to maintain compliance with the 1-hour average HCl-equivalent emission rate limit, however, can exceed the numerical value of the long-term chlorine feedrate limit because the 1-hour average HCl-equivalent emission rate limit is substantially higher than the annual average HCl-equivalent emission rate limit. Thus, capping at the interim standard level is inappropriate unless the interim standard were somehow re-expressed as a 1-hour limit.

Comment: Many commenters state that requiring prior approval of the eligibility demonstration would be unworkable. Commenters are concerned that the permitting authority may not approve the demonstration prior to the compliance date even though the source has submitted complete and accurate information and has responded to any requests for additional information in good faith. Commenters are also concerned that the permitting authority may disapprove the demonstration too late for the source to take other measures to comply with the total chlorine MACT standard. Once commenter recommends the following alternative approach: (1) If the regulatory agency does not act on a risk demonstration within the 6-month period, it is conditionally deemed approved; and (2) if a risk demonstration is disapproved, the source would have to comply with the MACT emission standards no later than three years after notice of disapproval and, in the interim, sources would comply with current emission limits for total chlorine.

Another commenter suggests that, if the permitting authority has neither approved nor disapproved the eligibility demonstration by the compliance date, the source may begin complying on the compliance date with the alternative health-based limits specified in the eligibility demonstration.

Finally, another commenter states that facilities should be granted a three-year extension of the compliance date if the Agency denies a good-faith eligibility demonstration. The commenter is concerned that sources will not have time to install additional controls or take other measures after a denial is issued but prior to the compliance date.

Response: We agree with commenters that requiring prior approval of the eligibility demonstration may be unworkable for the reasons commenters suggest. We also agree with commenters that sources who make a good-faith eligibility demonstration but whose demonstration is denied by the permitting authority may need additional time to install controls or take other measures to comply with the MACT emission standards.

Accordingly, the final rule does not require prior approval of the eligibility demonstration for existing sources. If your permitting authority has not approved your eligibility demonstration by the compliance date, and has not issued a notice of intent to disapprove your demonstration, you may nonetheless begin complying, on the compliance date, with the HCl-equivalent emission rate limits and associated chlorine feedrate limits you present in your eligibility demonstration.

In addition, the final rule states that the permitting authority should notify you of approval or intent to disapprove your eligibility demonstration within 6 months after receipt of the original demonstration, and within 3 months after receipt of any supplemental information that you submit. A notice of intent to disapprove your eligibility demonstration, whether before or after the compliance date, will identify incomplete or inaccurate information or noncompliance with prescribed procedures and specify how much time you will have to submit additional information or comply with the total chlorine MACT standards. The permitting authority may extend the compliance date of the total chlorine MACT standards to allow you to make changes to the design or operation of the combustor or related systems as quickly as practicable to enable you to achieve compliance with the total chlorine MACT standards.

Comment: One commenter states that proposed § 63.1215(f)(1)(A) should have required sources to conduct a new comprehensive performance test only if there are changes that would decrease the HCl-equivalent emission rate limit below the HCl-equivalent emission rate demonstrated during the comprehensive performance test. Similarly, the commenter suggests that a retest should not be required if a change increases the HCl-equivalent emission rate limit but the source elects to maintain the current feedrate limit.

Another commenter states that the Agency should clarify that if there are any changes that are not controlled by the facility owner/operator, and the

facility is required to change its design or operation to lower chlorine emissions to address the changes, the facility may request up to three years to make such changes.

Response: We generally agree with the commenters and have revised the rule as follows: (1) A new comprehensive performance test is required to reestablish the system removal efficiency for total chlorine only if you change the design, operation, or maintenance of the source in a manner that may decrease the system removal efficiency (e.g., the emission control system is modified in a manner than may decrease total chlorine removal efficiency); and (2) if you use the site-specific risk analysis option for your eligibility demonstration and changes beyond your control (e.g., off-site receptors newly residing or congregating at locations exposed to higher ambient levels than originally estimated) dictate a lower HCl-equivalent emission rate limit and you must make changes to the design, operation, or maintenance of the combustor or related systems to comply with the lower limit, you may request that the permitting authority grant you additional time to make those changes as quickly as practicable.

Comment: Several commenters state that the proposed approach for calculating chlorine emissions to address the potential bias using Method 26/26A attributable to high bromine or sulfur levels in feedstreams is not statistically valid. They indicate that the approach could lead to collection of total chlorine, hydrogen chloride and chlorine data that are contradictory and difficult to apply in a compliance situation. One commenter suggests that using Method 26/26A results for sources with bromine and sulfur dioxide, while recognizing that there is bias in the sampling method, will result in a valid compliance approach.

Response: We agree with commenters that the proposed approach to avoid the bias when feedstreams contain high levels of bromine or sulfur (bromine/chlorine ratio in feedstreams of greater than 5 percent, or sulfur/chlorine ratio in feedstreams of greater than 50 percent) during the comprehensive performance test may be problematic. The proposed approach would have required you to use Method 320/321 or ASTM D 6735–01 for hydrogen chloride measurements, to use Method 26/26A for total chlorine (i.e., hydrogen chloride and chlorine combined) measurements, and to calculate chlorine levels by difference. The potential problem is that chlorine emission levels are generally a very small portion of total chlorine measurements, and variability in the hydrogen chloride or total chlorine measurements due to method imprecision or other factors could result in inaccurate estimations of chlorine emission levels.

We do not agree, however, that using Method 26/26A for chlorine measurements for combustors feeding high levels of bromine or sulfur is acceptable—the chlorine measurement may be biased low. Chlorine emission levels must be determined as accurately as possible given that the long-term health threshold for chlorine is 100 times the threshold for HCl, and the short-term health threshold for chlorine is 10 times the threshold for HCl (i.e., using current RfCs and aRELs). To ensure that a conservative estimate of the chlorine emission rate is used to establish the alternative health-based emission limits and to address commenters' concerns, the final rule requires that you determine chlorine emissions to be the higher of: (1) The chlorine value measured by Method 26/26A, or an equivalent method; or (2) the chlorine value calculated by difference between the combined hydrogen chloride and chlorine levels measured by Method 26/26A, or an equivalent method, and the hydrogen chloride measurement from EPA Method 320/321 or ASTM D 6735–01, or an equivalent method.

Comment: Several commenters state the procedures for calculating HCl-equivalent emission rates cannot merely reference an outside source, such as a Web site, unless that reference specifies that the contents of the source are as of a date certain. To specify use of health threshold values that can change over time provides inadequate opportunity for notice and comment on the regulation.

Response: We believe that the best available sources of health effects information should be used for risk or hazard determinations. To assist us in identifying the most scientifically appropriate toxicity values for our analyses and decisions, the Web site to be used for RfCs identifies pertinent toxicity values using a default hierarchy of sources, with EPA's Integrated Risk Information System (IRIS) being the preferred source. The IRIS process contains internal and external peer review steps and IRIS toxicity values represent EPA consensus values. When adequate toxicity information is not available in IRIS, however, we consult other sources in a default hierarchy that recognizes the desirability of these qualities in ensuring that we have consistent and scientifically sound assessments. Furthermore, where the IRIS assessment substantially lags the current scientific knowledge, we have committed to consider alternative credible and readily available assessments (e.g., the acute Relative Exposure Levels established by the California Office of Health Hazard Assessment). For our use, these alternatives need to be grounded in publicly available, peer-reviewed information. We agree with the commenter that the issue of changing toxicity values is a general challenge in setting health-based regulations. However, we are committed to establishing such regulations that reflect current scientific understanding, to the extent feasible.

C. National Health-Based Standards for Cement Kilns

Comment: One commenter states that our suggestion at proposal that it would be appropriate to establish a single national emission rate type standard applicable to all cement kilns based on the worst-case scenario cement kiln is unduly burdensome as it discounts the benefits of improved dispersion realized by facilities that have invested in taller stacks that minimize downwash effects. The commenter recommends a dual limit for cement kilns such that the HCl equivalent emission rate is limited to both: (1) A 130 ppmv total chlorine emission standard (the Interim Standard) coupled with a chlorine feedrate limit based on a 12-hour rolling average; and (2) a Hazard Index of 1.0.

Response: We have decided not to include a separate national standard for cement kilns in the final rule for several reasons: (1) We have no assurance that the Cl_2/HCl volumetric ratio exhibited during the most recent compliance test, and that was the basis for the commenter documenting in a study[187] that the Hazard Index of 1.0[188] was not exceeded, is representative of ratios in the past or future; (2) the commenter's recommended emission standard for cement kilns—130 ppmv total chlorine emission limit and a Hazard Index of 1.0—is equivalent to the requirements under § 63.1215 applicable to other hazardous waste combustors to establish site-specific emission limits; (3) the MACT standard for total chlorine for cement kilns is 120 ppmv such that the health-based standard that the commenter recommends—130 ppmv,

[187] See Trinity Consultants, "Analysis of HCl/Cl2 Emissions from Cement Kilns for 112(d)(4) Consideration in the HWC MACT Replacement Standards," September 17, 2003.

[188] The HCl/Cl_2 ratio for the total chlorine measurement is important because the current RfC for chlorine is 0.2 μg/m³ while the current RfC for HCl is 20 μg/m³. Thus, when calculating HCl-equivalent emission rate limits, chlorine emissions are currently multiplied by a factor of 100.

the Interim Standard—would provide little compliance relief; and (4) even though the final rule does not provide a separate national health-based standard for cement kilns, cement kilns may apply for the health-based compliance alternatives applicable to other hazardous waste combustors.

Prior to publication of the proposed rule, the commenter submitted results of site-specific risk assessments for all cement kiln facilities showing that both the long-term and short term Hazard Index of 1.0 would not be exceeded at any facility assuming: (1) Sources emit total chlorine at the Interim Standard level of 130 ppmv; and (2) total chlorine emissions are apportioned between HCl and chlorine according to the apportionment exhibited during the most recent compliance test.

At proposal, we requested comment on how to ensure that the 130 ppmv concentration-based standard would ensure that total chlorine emission rates (lb/hr) would not increase to levels that may exceed the Hazard Index limit of 1.0 given that: (1) The partitioning ratio between HCl and chlorine could change over time such that a larger fraction of total chlorine could be emitted as chlorine, which has a much lower health risk threshold; and (2) the mass emission rate of total chlorine could increase. See 69 FR at 21306.

The commenter has addressed the concern about the mass emission rate of total chlorine potentially increasing by suggesting that the health-based standard include a limit on the feedrate of total chlorine and chloride at the level used in their risk assessment supporting a separate national standard for cement kilns. The commenter has also addressed the concern about the HCl and chlorine apportionment ratio changing over time by suggesting that the standard also include a requirement that the Hazard Index of 1.0 not be exceeded. We agree that sources need to account for variability in the chlorine to HCl ratio (see § 63.1215(b)(6)) and that periodic checks to ensure that the Hazard Index of 1.0 is not exceeded are needed. We believe the best way to ensure that the health-based compliance alternatives for total chlorine for cement kilns are protective with an ample margin of safety is through the procedures of § 63.1215 where site-specific emission rate limits are established rather than under a separate national standard for cement kilns.

VIII. Implementation and Compliance

A. Compliance Assurance Issues for both Fabric Filters and Electrostatic Precipitators (and Ionizing Wet Scrubbers)

1. Implementation Issues

Comment: Several commenters state that design and performance specifications and explicit detailed test procedures to determine conformance with the specifications are needed so that manufacturers can certify that their bag leak detection systems and particulate matter detection systems meet applicable criteria. Absent design and performance specifications and test procedures, commenters assert that the "manufacturer's certification" cannot ensure the performance capabilities of the devices.

Response: In general, we believe adherence to manufacturer's written specifications and recommendations is an appropriate approach to reasonably ensure performance of a bag leak detection system or particulate matter detection system, and we have retained that provision in the final rule. We agree, however, that there may be cases where other procedures are more appropriate than the manufacturer's recommendations to ensure performance of a bag leak detection system or particulate matter detection system. Consequently, the rule allows you to request approval for alternative monitoring procedures under § 63.1209(g)(1).[189] We note that you may use references other than EPA's Guidance Document, "Fabric Filter Bag Leak Detection Guidance," September 1997 to identify appropriate performance specifications for the bag leak detection system or particulate matter detection system, including: PS–11 for PM CEMS; PS–1 for opacity monitors; and CPS–001 for opacity monitoring below 10% opacity. You may use these references to support your request for additions to, or deviations from, manufacturer's specifications.

Comment: One commenter states that bag leak detection systems and particulate matter detection systems should have a detection limit of 1.0 mg/acm to ensure peak performance is maintained rather than explicitly allowing sources to request approval for a detection limit on a site-specific basis as the rule currently allows. Several other commenters state that the bag leak detection system or particulate matter detection system need not have a detection limit as low as 1.0 mg/acm to detect increases in normal emissions. One commenter believes that bag leak detection systems installed on cement kilns should be allowed to have a detection limit of 10 mg/acm because: (1) A detection limit requirement of 10 mg/acm is more than sufficient to protect the particulate matter emission limit and to detect increases in particulate matter concentration given that the current particulate matter emission limit for existing kilns is 63 mg/dscm; (2) a detection limit requirement of 10 mg/acm is consistent with the requirement for bag leak detection systems in Subpart LLL, Part 63, for cement plants that choose to install bag leak detection systems on finish mills and raw mills, for bag leak detection systems and particulate matter detection systems installed on lime kilns under Subpart AAAAAA, and for industrial boilers under Subpart DDDDD; (3) a 10 mg/acm detection limit is achievable using state-of-the-art transmissometers (the actual instrument used in a continuous opacity monitoring system (COMS) at cement plants having kiln stack diameters of 2–3 meters, or greater; and (4) it is unclear if any bag leak detection system device can actually be demonstrated to achieve a 1.0 mg/acm detection limit except by extrapolation from tests conducted at higher dust loadings and theoretical arguments based on signal-to-noise ratios or other parameters. This commenter also recommends that EPA establish a 10 mg/am^3 detection limit for all cement kilns rather than provide for site-specific determinations because allowing site-specific determinations is likely to create confusion in the selection of monitoring devices and further complicate the manufacturer's certification of performance requirements.

Response: The current requirement for the bag leak detection system sensitivity/detection limit applicable to incinerators and lightweight aggregate kilns is 1.0 mg/acm unless you demonstrate under § 63.1209(g)(1) that a lower sensitivity (i.e., higher detection limit) would detect bag leaks. We proposed to apply the bag leak detection system requirements to all hazardous waste combustors equipped with fabric filters and promulgate that requirement today. Although we also requested comment whether detection limits higher than 1.0 mg/acm should be allowed, none of the comments has convinced us to alter our view that the rule should allow higher detection limits on a site-specific basis. Similarly,

[189] See discussion in Part Five, Section III.C, for an explanation of how the alternative monitoring provisions of § 63.1209(g)(1) relate to those of § 63.8(f).

we believe that the same detection limit requirement should apply to particulate matter detection systems that you may elect to use for compliance monitoring for your electrostatic precipitator or ionizing wet scrubber in lieu of site-specific operating parameter limits.

Both bag leak detection systems and particulate matter detection systems must be able to detect particulate emission in the range of normal concentrations. For example, to establish the alarm level for the bag leak detection system, you must first adjust detector gain/sensitivity and response time based on normal operations. Although the alarm level for particulate matter detection systems will be established based on operations during the comprehensive performance test or higher (see discussion below), the detector must be responsive within the range of normal operations for you to effectively minimize exceedances of the alarm level.

The range of normal emission concentrations will generally be well below both the particulate matter standard and emissions during the comprehensive performance test. Consequently, we disagree with commenters that believe the detection limit need only be within the range of emissions at the particulate matter emission standard. On the other hand, normal emissions may be well above 1.0 mg/acm such that a higher detection limit (e.g., 10 mg/acm) may be appropriate on a site-specific basis.

We also disagree with the comment that bag leak detection systems (or particulate matter detection systems) may not be able actually to achieve a 1.0 mg/acm detection limit. EPA is aware of bag leak detection system instruments certified to meet levels of 0.2 mg/m^3 and particulate matter detection systems can readily achieve detection limits well below 1.0 mg/acm.[190]

Comment: One commenter states that a continuous opacity monitoring system (COMS) that can achieve a detection level of 10 mg/acm or less can be used to monitor electrostatic precipitator performance. The commenter believes that allowing a COMS for compliance under Subpart EEE is also appropriate because cement kilns will be operating under the requirements of Subpart LLL (for cement kilns that do not burn hazardous waste) at times, which requires compliance with an opacity standard using a COMS.

Response: You may use a COMS (i.e., transmissometer) that meets the detection limit requirement as discussed above (i.e., 1.0 mg/acm or a higher detection limit that you document under an alternative monitoring petition under § 63.1209(g)(1) would routinely detect particulate matter loadings during normal operations) as the detector for your bag leak detection system or particulate matter detection system.

2. Compliance Issues

Comment: One commenter states that, if the bag leak detection system or particulate matter detection system exceeds the alarm level or an operating parameter limit (OPL) is exceeded, the automatic waste feed cutoff (AWFCO) system must be initiated. Allowing a source to exceed the alarm level for 5% of the time in a 6-month period does not ensure continuous compliance.

Response: Although the AWFCO system must be initiated if an OPL is exceeded, we believe that allowing exceedances of the bag leak detection system or particulate matter detection system alarm level up to 5% of the time in a 6-month period is reasonable. Requiring initiation of the AWFCO for an exceedance of an OPL is reasonable because sources generally can control directly the parameter that is limited. Examples are the feedrate of metals or chlorine, or pressure drop across a wet scrubber. Bag leak detection systems and particulate matter detection systems, however, measure mass emissions of particulate matter, a parameter that is affected by many interrelated factors and that is not directly controllable. We believe that the 5 percent alarm rate is a reasonable allowance for sources due to difficult-to-control variations in particulate matter emissions. More important, although the bag leak detection system and particulate matter detection system measure mass emissions of particulate matter, the detector response is not correlated to particulate matter emission concentrations to the extent necessary for compliance monitoring.[191] Thus, triggering the alarm level is not evidence that the particulate matter emission standard has been exceeded.

The purpose of a BLDS or PMDS is to alert the operator that the PM control device is not functioning properly and that corrective measures must be undertaken. We believe that using a BLDS or PMDS for compliance assurance better minimizes emissions of PM (and metal HAP) than use of operating parameter limits (which are linked to the automatic waste feed cutoff system). APCD operating parameters often have an uncertain relationship to PM emissions while the BLDS and PMDS provide real-time information on actual PM mass emission levels.[192]

Comment: One commenter states that requiring a notification if the bag leak detection system or particulate matter detection system set point is exceeded more than 5% of the time in a 6-month period is not cost-effective. Sources using bag leak detection systems have not linked exceedances to the data logging system and would incur an expense to do so.

Response: We continue to believe that limiting the aggregate duration of exceedances in a 6-month period is a reasonable approach to gage the effectiveness of the operation and maintenance procedures for the combustor. We note that recent MACT standards for several other source categories use this approach, including standards for industrial boilers and process heaters and standards for lime kilns.

Comment: One commenter states that EPA did not present a rationale for requiring a notification within 5 working days if the bag leak detection system or particulate matter detection system set point is exceeded more than 5% of the time during a 6-month period. The commenter notes that this notice is not required under the Subpart DDDDD boiler and process heater MACT. The commenter also notes that the source is required to take corrective measures under both the operation and maintenance plan and bag leak detection systems and particulate matter detection systems requirements. The commenter believes that requiring a report to the permitting authority is duplicative, unnecessary, and increases the burden on regulated facilities without providing additional protection to human health or the environment.

Response: If a source exceeds the alarm set point more than 5% of the time in a 6-month period, it is an indication that the operation and maintenance plan may need to be revised. Requiring the source to report the excess exceedances to the permitting

[190] USEPA, "Technical Support Document for HWC MACT Standards, Volume IV: Compliance with the HWC MACT Standards," September 2005, Appendix C, Section 4.0.

[191] Actually, the BLDS is not correlated at all to PM concentrations, and the alarm level for a PMDS may or may not be approximately correlated to PM concentrations. See § 63.1206(c)(9).

[192] Moreover, for FFs, we are not aware of any APCD operating parameters that correlate well with PM emissions. Thus, sources must use a BLDS or PMDS for compliance assurance. For ESPs and IWSs, we are not aware of generic APCD parameters that correlate well with PM emissions. See discussion below in Section VIII.C of the text. Consequently, although the rule allows sources with ESPs and IWSs to establish site-specific operating parameter limits, sources are encouraged to use a PMDS.

authority serves as a notification that the authority may need to review the operation and maintenance plan with the source to determine if changes are warranted.

We agree with the commenter, however, that it is not necessary to require that the report be submitted within five working days of the end of the 6-month block period. Consequently, the final rule requires you to submit the report within 30 days of the end of the 6-month block period. Allowing 30 days to submit the report rather than 5 days as proposed is reasonable. We are concerned that 5 days may not be enough time to complete the report given that several exceedances toward the end of the 6-month block period may cause you to exceed the 5% time limit and that there may be many individual exceedances that need to be included in the report. We acknowledge that it may take some time to prepare the report given that you must describe the causes of each exceedance and the revisions to the operation and maintenance plan you have made to mitigate the exceedances.

Comment: One commenter notes that there is no guidance on how to calculate when the set-point has been exceeded more than 5 percent of the operating time within a 6 month period. The commenter notes that the MACT for industrial boilers and process heaters provides minimal instruction on how this is to be done, but it is not specific enough to enable facilities to ensure that they are in compliance with this requirement.

Response: For the final rule, we have adopted the procedures specified in the industrial boiler and process heater MACT for calculating the duration of exceedances of the set point. Those procedures are as follows:

1. You must keep records of the date, time, and duration of each alarm, the time corrective action was initiated and completed, and a brief description of the cause of the alarm and the corrective action taken.

2. You must record the percent of the operating time during each 6-month period that the alarm sounds.

3. In calculating the operating time percentage, if inspection of the fabric filter, electrostatic precipitator, or ionizing wet scrubber demonstrates that no corrective action is required, no alarm time is counted.

4. If corrective action is required, each alarm shall be counted as a minimum of 1 hour.

Although the commenter indicates that these procedures are not specific enough to ensure that sources are in compliance with the requirements, the commenter did not indicate the deficiencies or suggest additional requirements. If you need additional guidance on compliance with this provision, you should contact the permitting authority.

Comment: One commenter supports the approach of listing the shutting down of the combustor as a potential—but not mandatory—corrective measure in response to exceeding an alarm set point. Several commenters suggest, however, that EPA should specify that corrective measures could include shutting off the hazardous waste feed rather than shutting down the combustor. Other commenters state that it is inappropriate to imply that shutting down the combustor must be part of a corrective measures program for responding to exceedance of a set point. These commenters believe that the requirement to take corrective action upon the alarm is sufficiently protective. The facility should determine if shutting down the combustor is a necessary response to avoid noncompliance with a standard.

Response: You must operate and maintain the fabric filter, electrostatic precipitator, or ionizing wet scrubber to ensure continuous compliance with the particulate matter, semivolatile metals, and low volatile metals emission standards. Your response to exceeding the alarm set point should depend on whether you may be close to exceeding an operating parameter limit (e.g., ash feedrate limit for an incinerator or liquid fuel boiler equipped with an electrostatic precipitator) or an emission standard. If so, corrective measures should include, as commenters suggest, cutting off the hazardous waste feed. Corrective measures could also include, however, shutting down the combustor as the ultimate immediate corrective measure if an emission standard may otherwise be exceeded. Consequently, the final rule continues to require you to alleviate the cause of the alarm by taking the necessary corrective measure(s) which may include shutting down the combustor. This provision does not imply that shutting down the combustor is the default corrective measure. Rather, it implies that the ultimate immediate response, absent other effective corrective measures, would be to shut down the combustor.

Comment: One commenter states that periods of time when the combustor is operating but the bag leak detection system or particulate matter detection system is malfunctioning should not be considered exceedances of the set-point.

Response: If the bag leak detection system or particulate matter detection system is malfunctioning, the source cannot determine whether it is operating within the alarm set point. Accordingly, it is reasonable to consider periods when the bag leak detection system or particulate matter detection system is malfunctioning as exceedances of the set point.

B. Compliance Assurance Issues for Fabric Filters

Comment: One commenter states that establishing the set point for the bag leak detection system at twice the detector response achieved during bag cleaning as recommended by EPA guidance would not be sensitive enough to detect gradual degradation of the fabric filter, nor would it be low enough to require the operator of the source to take corrective measures that would ensure effective operation of the baghouse over time.

Response: The commenter expresses the same concern that EPA raised at proposal. See 69 FR at 21347. We have concluded, however, that it may be problematic to establish an alarm set point for fabric filters based on operations during the comprehensive performance test. This is because, as noted in earlier responses and at 69 FR at 21233, it is much more difficult to "detune" a fabric filter than an electrostatic precipitator to maximize emissions during the performance test.[193] Consequently, emissions from fabric filters that have not been detuned during the performance test may not be representative of the range of normal emissions caused by factors such as bag aging. Baghouse performance degrades over time as bags age. In addition, establishing the alarm set point based on operations during the performance test for baghouses that have not been detuned would establish more stringent compliance requirements on sources that perform the best—the lower the emissions, the lower the alarm set point. This would unfairly penalize the best performing sources.

For these reasons, the final rule requires you to establish the alarm set-point for bag house detection systems using principles provided in USEPA, "Fabric Filter Bag Leak Detection Guidance," (EPA–454/R–98–015, September 1997).

Comment: One commenter states that the bag leak detection system requirement should not apply to the coal mill baghouse for cement kilns with indirect-fired coal mill systems where a fraction of kiln gas is taken

[193] One approach to detune a fabric filter to simulate the extreme high range of normal operations would be to install a butterfly valve that allows a portion of the combustion gas to by-pass a section of the baghouse.

from the preheater and routed to the coal mill and subsequently to a baghouse before entering the stack. The commenter notes that the PM in this gas is nearly exclusively coal dust, and the baghouse is substantially smaller than the baghouse for the kiln.

Response: We believe that a bag leak detection system is a reasonable approach to monitor emissions for the coal mill baghouse to ensure compliance with the particulate matter (and semivolatile and low volatile metals) emission standards. These systems are inexpensive to install and operate. Annualized costs are approximately $24,000.[194] Although the commenter did not suggest an alternative monitoring approach, and we are not aware of a less expensive and effective approach, we note that sources may petition the permitting authority under § 63.1209(g)(1) to request an alternative monitoring approach.

C. Compliance Issues for Electrostatic Precipitators and Ionizing Wet Scrubbers

Comment: Several commenters believe that a particulate matter detection system may not be necessary for monitoring of electrostatic precipitators and ionizing wet scrubbers. Commenters state that site-specific operating parameter limits linked to the automatic waste feed cutoff system can effectively monitor and ensure the performance of electrostatic precipitators and ionizing wet scrubbers. Particulate matter detection systems on cement kilns would have to operate in a high moisture stack environment (all kilns burning hazardous waste that are equipped with electrostatic precipitators are wet process kilns), with the potential for condensation and/or water droplet interference. Commenters state that when water droplets are present, many of these devices are not applicable.

Response: The final rule provides sources equipped with electrostatic precipitators or ionizing wet scrubbers the alternative of using a particulate matter detection system or establishing site-specific operating parameter limits for compliance assurance. If a particulate matter detection system is used, corrective measures must be taken if the alarm set point is exceeded. If the source elects to establish site-specific operating parameter limits, the limits must be linked to the automatic waste feed cutoff system.

In response to commenters' concern that high moisture stack gas may be problematic for particulate matter detection systems, we note that extractive light-scattering detectors and beta gauge detectors can effectively operate in high moisture environments. We acknowledge, however, that the cost of these extractive detector systems is substantially higher than transmissometers or in situ light-scattering detectors.

Comment: One commenter states that EPA must set minimum total power requirements for both ionizing wet scrubbers and electrostatic precipitators because allowing permit officials to establish compliance operating parameters on a site-specific basis frustrates the intention of the CAA by obviating the requirements for federal standards. The commenter asserts that a minimum total power requirement is monitorable, recordable, and reportable, three requirements that are necessary for these facilities to come into, and remain in compliance with, their Title V operating permits.

Other commenters state that electrostatic devices are not easily characterized by operating parameters in a "one-size-fits-all" fashion. The significant operating parameters for electrostatic devices are secondary voltage, secondary current, and secondary power (the product of the first two items). The relationship between these parameters and performance of the unit differ between applications and unit types. For example, inlet field power can increase as unit performance appears to decrease. In this case, an operating parameter other than secondary power by field would be more appropriate. The commenter notes that, in its various proposals over the years, EPA has discussed a number of approaches to establish operating parameter limits for electrostatic devices, including: Minimum total secondary power; minimum secondary power by field; pattern of increasing power from inlet to outlet field; and minimum secondary power of the last ⅓ of fields (or the last field). Commenters have also proposed: minimum specific power (secondary power divided by flue gas flow rate); minimum secondary voltage and/or secondary current; and total secondary voltage and/or secondary current. The commenter concludes that it is not surprising that there is so little agreement on the right approach, because different units and applications respond differently. EPA's proposal to let facilities and local regulators determine the best approach is far wiser than regulating from a distance.

Response: We agree with the commenters that state that it is not practicable to establish operating parameter limits that would effectively ensure performance of all electrostatic devices. Accordingly, the final rule continues to allow sources to establish site-specific operating parameter limits for these devices.

We disagree with the commenter's assertion that site-specific operating parameter limits obviate the requirements for federal standards. The site-specific operating parameter limits merely reflect the truism that no two sources are identical and so what each needs to do to comply with the uniform standards may differ. The final rule provides consistent, federally-enforceable emission standards. Necessary flexibility in compliance assurance for those emission standards does not undermine the uniformity of those standards. In addition, we disagree with the commenter's concern that without a minimum power limit, there will be no monitorable, recordable, and reportable Title V permit limits for electrostatic devices. To the contrary, site-specific operating parameter limits can and will be monitored, recorded, reported, and linked to the automatic waste feed cut-off system. And, if a source elects to use a particulate matter detection system in lieu of establishing site-specific operating parameter limits, the detector response will be monitored, recorded, reported, and linked to requirements to take corrective measures if the alarm set point is exceeded.

Comment: One commenter asserts that the use of electrostatic precipitator total power input data (sum of the product of kilovolts times milliamps for each electrostatic precipitator field) is one acceptable approach as a site-specific parameter to monitor electrostatic precipitator performance. Limits on power input for each field (or particular fields) are not warranted.

Response: A limit on total power input to a multifield electrostatic device is generally not an acceptable operating parameter for compliance assurance. We have documented that when total power input was held constant for a four-field electrostatic precipitator while the power input to the fourth field was decreased, emissions of particulate matter doubled from 0.06 gr/dscf to 0.12 gr/dscf. See 66 FR at 35143 (July 3, 2001). Thus, if the total power input during the comprehensive performance test were used as the operating parameter limit, particulate matter emissions could exceed the emission

[194] USEPA, "Technical Support Document for HWC MACT Standards, Volume IV: Compliance with the HWC MACT Standards," September 2005, Appendix C.

standard because of changes in other parameters that were not limited even though total power input did not exceed the parametric limit.

Notwithstanding our concern that a limit on total power input to a multifield electrostatic device is generally not an effective operating parameter for compliance assurance, this does not preclude you from documenting to the permitting authority that total power input is an effective compliance assurance parameter for your source. See § 63.1209(m)(1)(iv).

Comment: Several commenters suggest that the rule should offer various approaches to establish an achievable particulate matter detection system alarm level on a site-specific basis in lieu of the approach we proposed (i.e., average detector response during the comprehensive performance test): (1) Use the 2 times the maximum peak height or 3 times the baseline concepts developed in EPA's bag leak detection guidance documents; (2) allow spiking to set the alarm set point given that PS 11 allows for spiking as a way to calibrate PM CEMs; (3) establish the limit as the 99th percentile upper prediction limit of the average response during each performance test run instead of the average of the test run averages; (4) allow upward extrapolation from the average of the test run averages to some percentage of the particulate matter emissions standard (fraction could be variable depending upon how close to the standard the facility is during the compliance test); or (5) set the alarm point at the maximum test run.

Response: We agree with several of the commenters' suggestions: explicitly allowing spiking (and emission control device detuning) during the comprehensive performance test to maximize controllable operating parameters to simulate the full range of normal operations; and upward extrapolation of the detector response. See discussion below.

The final rule is consistent with commenters' suggestion to establish the alarm level for particulate matter detection systems on fabric filters based on the concepts in the Agency's guidance document on bag leak detection systems. Commenters made this suggestion in response to our request for comments on requiring particulate matter detection systems on fabric filters and establishing the alarm level based on the detector response during the comprehensive performance test. See 69 FR at 21347. The final rule requires bag leak detection systems on all fabric filters and suggests that you establish the alarm level using concepts in the bag leak detection system guidance. [195]

Neither the suggestion to establish the alarm level at the 99th percentile upper prediction limit (UPL99) based on the average response during the comprehensive performance test runs nor the suggestion to establish the alarm level at the maximum test run response would control PM emissions at the level achieved during the performance test or provide some assurance that the PM standard was not being exceeded, unless the detector response is correlated to PM concentrations. For example, if the detector response does not relate linearly to PM concentration (or if the response changes w/changes in particulate characteristics), the UPL99 detector response could relate to a much higher (e.g., 99.9th percentile) PM concentration. In addition, even if the detector response were correlated to PM concentration, there is no assurance that the correlation would be consistent over the range of the average detector response during the performance test to the UPL99 detector response. Note that under PS–11 for PM CEMS, even after complying with rigorous procedures to correlate the detector response to PM concentrations, the detector response may be extrapolated only to 125% of the highest PM concentration used for the correlation. Thus, the final rule does not use these approaches to establish the alarm level.

If you elect to use a particulate matter detection system in lieu of site-specific operating parameters for your electrostatic precipitator or ionizing wet scrubber, you must establish the alarm level using either of two approaches. See Appendix C of USEPA, "Technical Support Document for HWC MACT Standards, Volume IV: Compliance with the HWV MACT Standards," September 2005. Under either approach, you may maximize controllable operating parameters during the comprehensive performance test to simulate the full range of normal operations (*e.g.*, by spiking the ash feedrate and/or detuning the electrostatic device). [196]

You may establish the alarm set-point as the average detector response of the test condition averages during the comprehensive performance test.

Alternatively, you may establish the alarm set point by extrapolating the detector response. Under the extrapolation approach, you must approximate the correlation between the detector response and particulate matter emission concentrations during an initial correlation test. You may extrapolate the detector response achieved during the comprehensive performance test (*i.e.*, average of the test condition averages) to the higher of: (1) A response that corresponds to 50% of the particulate matter emission standard; or (2) a response that correlates to 125% of the highest particulate matter concentration used to develop the correlation.

To establish an approximate correlation of the detector response to particulate matter emission concentrations, you should use as guidance Performance Specification–11 for PM CEMS (40 CFR Part 60, Appendix B), except that you need only conduct only 5 runs to establish the initial correlation rather than a minimum of 15 runs required by PS–11. In addition, the final rule requires you to conduct an annual Relative Response Audit (RRA) for quality assurance as required by Procedure 2—Quality Assurance Requirements for Particulate Matter Continuous Emission Monitoring Systems at Stationary Sources, Appendix F, Part 60. [197] The RRA is required on only a 3-year interval, however, after you pass two sequential annual RRAs.

The rule requires only minimal correlation testing because the particulate matter detection system is used for compliance assurance only—as an indicator for reasonable assurance that an emission standard is not exceeded. The particulate matter detection system is not used for compliance monitoring—as an indicator of continuous compliance with an

[195] Note that a bag leak detection system is a type of particulate matter detection system for purposes of this discussion. A triboelectric detector is normally used for a bag leak detector system because it is very inexpensive and has a low detection limit. A triboelectric detector meets the criterion for a particulate matter detector in a particulate matter detection system in that it detects relative mass emissions of particulate matter within the range of normal emission concentrations. (Note further, however, that a triboelectric detector cannot be correlated to particulate matter concentrations and thus cannot be used as a particulate matter CEMS. Note also that a triboelectric detector cannot be used on sources equipped with electronic control devices.) The alarm level for a bag leak detection system would be established using the concepts discussed in the Agency's guidance document on bag leak detection systems. The alarm level for a particulate matter detection system used on a fabric filter, however, (preferable with a detector other than a triboelectric device that could be correlated to PM concentrations) would be established based on the detector response during the comprehensive performance test.

[196] Note, however, that bypassing or detuning an emission control system could cause PM stratification and could make it difficult to pass the PS–11 performance criteria you use as guidelines for a PMDS.)

[197] You perform an RRA by collecting three simultaneous reference method PM concentration measurements and PM CEMS measurements at the as-found source operating conditions and PM concentration.

emission standard. Because particulate matter detection system correlation testing and quality assurance is much less rigorous than the requirements of PS–11 for a PM CEMS, the particulate matter detection system response cannot be used as credible evidence of exceedance of the emission standard.

D. Fugitive Emissions

Comment: A commenter does not support EPA's proposed approach to allow alternative techniques that can be demonstrated to prevent fugitive emissions without the use of instantaneous pressure limits given that the CAA requires continuous compliance with the standards and given positive pressure events can result in fugitive emissions, irrespective of facility design.

Response: Rotary kilns can be designed to prevent fugitive emissions during positive pressure events. As stated in the February 14, 2002 final rule, and subsequently in the April 20, 2004 proposed rule, there are state-of-the-art rotary kiln seal designs (such as those with shrouded and pressurized seals) which are capable of handling positive pressures without fugitive releases. See 67 FR at 6973 and 69 FR at 21340. We have included documentation of such kiln designs in the docket.[198] Instantaneous combustion zone pressure limits thus may not be necessary to assure continuous compliance with these fugitive emission control requirements. Our approach to allow alternative techniques that have been demonstrated to prevent fugitive emissions is therefore reasonable and appropriate. We note that these alternative techniques must be reviewed and approved by the appropriate delegated regulatory official.[199]

Comment: A commenter disagrees with EPA's clarification that fugitive emission control requirements apply only to fugitives attributable to the hazardous waste, given that the CAA does not distinguish between HAP emissions that come from hazardous waste streams and other HAP emissions.

Response: The fugitive emission control requirements in today's final rule originated from the RCRA hazardous waste combustion fugitive emission control requirements for incinerators and boilers and industrial furnaces.[200] The primary focus of these RCRA requirements is to ensure hazardous waste treatment operations are conducted in a manner protective of human health and the environment.[201] It is therefore appropriate to clarify that the intent of this requirement is to control fugitive emission releases from the combustion of hazardous waste.

Furthermore, MACT requirements for source categories that do not combust hazardous waste (e.g., industrial boilers, Portland cement kilns, and commercial and industrial solid waste incinerators) do not have combustion chamber fugitive emission control requirements for the non-hazardous waste inputs or outputs (e.g., clinker product for cement kilns or coal and natural gas fuels for industrial boilers). We have previously taken the position that emissions not affected by the combustion of hazardous waste (e.g., clinker coolers, raw material handling operations, etc.) are regulated pursuant to the applicable nonazardous waste MACT rules.[202, 203] We conclude the clarification that the fugitive emission control requirements applies only to fugitive emissions that result from the combustion of hazardous waste is appropriate because it regulates emissions attributable to nonhazardous waste streams to the same level of stringency that otherwise would apply if the source did not combust hazardous waste.[204]

Comment: A commenter states that the instantaneous monitoring requirements are inappropriate because (1) EPA has not demonstrated that the average of the top 12% of boilers are capable of operating with no instantaneous deviations from the negative pressure requirements; and (2) these requirements, though not standards themselves, effectively increase the stringency of the standard itself beyond what even the best available technology can achieve.

Response: As previously discussed, the fugitive emission control requirements included in today's rule originated from the RCRA hazardous waste combustion chamber fugitive emission control requirements. These provisions allow sources to control fugitive emissions by "maintaining the combustion zone pressure lower than atmospheric pressure, or an alternative means of control equivalent to maintenance of combustion zone pressure lower than atmospheric pressure." All sources that must comply with the provisions of this rule are, or were, required to control fugitive emissions from the combustion unit pursuant to RCRA.

The monitoring requirements in today's rule do not increase the stringency of the standard beyond what the best available technology can achieve. Although we do not have data that confirm negative pressure is being maintained on an instantaneous basis (as we define it)[205] for at least 12 percent of the boilers, we believe this is current practice and readily achievable by most sources.[206] These requirements have been in force for many years, and there is no basis for stating that they are unachievable (EPA is not aware of industrywide noncompliance with these provisions, the necessary premise of the comment). First, maintaining negative pressure is the option that most boilers elect to implement to demonstrate compliance with the RCRA fugitive emission control requirements. Second, negative pressure is readily achieved on an instantaneous basis in boilers through use of induced draft fans. Third, the requirements we are finalizing today for boilers are identical to the fugitive emission control requirements that hazardous waste incinerators, cement kilns, and lightweight aggregate kilns are currently complying with pursuant to the EEE interim standard regulations. See § 63.1206(c)(5). Most of these sources maintain negative combustion chamber pressure through use of induced draft fans, providing further evidence that continuously maintaining combustion

[198] See USEPA, "Technical Support Document for the HWC MACT Standards, Volume IV: Compliance With the HWC MACT Standards," September 2005, Section 10.

[199] See § 63.1206(c)(5)(i)(C) and (D).

[200] See § 266.102(e)(7) and § 264.345(d).

[201] Section 3004(a) of RCRA requires the Agency to promulgate standards for hazardous waste treatment, storage, and disposal facilities as necessary to protect human health and the environment. The standards for hazardous waste incinerators generally rest on this authority. § 3004(q) of RCRA requires the Agency to promulgate standards for emissions from facilities that burn hazardous waste fuels (e.g., cement and lightweight aggregate kilns, boilers, and hydrochloric acid production furnaces) as necessary to protect human health and the environment.

[202] See 69 FR at 21203 and 64 FR at 52871, and § 63.1206(b)(1)(ii).

[203] Portland cement manufacturing facilities that combust hazardous waste are subject to both Subpart EEE and Subpart LLL, and hydrochloric acid production facilities that combust hazardous waste may be subject to both Subpart EEE and Subpart NNNNN. In these instances Subpart EEE controls HAP emissions from the cement kiln and hydrochloric acid production furnace stack (and also fugitive emissions from the combustion chamber), while Subparts LLL and NNNNN would control HAP emissions from other operations that are not directly related to the combustion of hazardous waste (e.g., clinker cooler emissions for cement production facilities, and hydrochloric acid product transportation and storage for hydrochloric acid production facilities).

[204] This issue has little relevance given that the measures taken to control the fugitive emissions from the combustion of hazardous waste will also control the fugitive emission associated with other feedstreams.

[205] The February 14, 2002 Final Amendments Rule clarifies that that a reasonable pressure monitoring frequency that could meet the intent of "instantaneous" would be once every second. See 67 FR at 6974.

[206] Commenters did not provide data to the contrary.

zone pressure lower than ambient pressure is readily achievable by well designed and operated boilers.[207]

We note that use of instantaneous pressure monitoring is not a requirement. A source can elect to implement any of the four compliance options to control combustion system leaks as well as request to use alternative monitoring approaches. See §§ 63.1206(c)(5) and 63.1209(g). The instantaneous pressure monitoring option offers sources a method that satisfies the intent of the rule that can be applied at numerous sources. The inclusion of this requirement in today's rule is thus an attempt to simplify the review process for both regulators and affected sources; the absence of prescriptive compliance options in this case may likely result in time-consuming site-specific negotiations that would prolong the review and approval of comprehensive performance test workplans.

Comment: A commenter believes that requiring an instantaneous waste-feed cutoff when these pressure excursions occur is short-sighted and will result in greater HAP emissions. The commenter recommends EPA instead allow the use of reasonable pressure averaging periods in lieu of instantaneous pressure requirements.

Response: As discussed in the February 14, 2002 Final Amendments Rule, automatic waste feed cutoffs are appropriate non-compliance deterrents, and are necessary whenever an operating limit is exceeded. See 67 FR at 6973. Pressure excursions that result in combustion system leaks (and subsequently lead to automatic waste feed cutoffs) should be prevented by maintaining negative pressure in the combustion zone. We agree that needless triggering of automatic waste feed cutoffs due to short term pressure fluctuations that do not result in combustion system leaks would provide less environmental protection, not more. Today's rule offers three alternative options that do not require the use of instantaneous pressure monitoring to control combustion system leaks. See § 63.1206(c)(5). The use of averaging periods in these alternatives is not prohibited. Sources that elect to use an alternative compliance option must demonstrate that the alternative method is equivalent to maintaining combustion zone pressure lower than ambient pressure or, that the alternative approach prevents fugitive emissions.

[207] The commenter did not provide information that would lead us to conclude that these requirements are harder to implement for boilers than for incinerators, cement kilns, and lightweight aggregate kilns.

E. Notification of Intent To Comply and Compliance Progress Report

1. Notice of Intent To Comply

In the NPRM, we proposed to re-institute the Notification of Intent to Comply (NIC) because we felt that it offered many benefits in the early stages of MACT compliance. As discussed in the 1998 "fast track" rule (63 FR 33782) and in the proposal, the NIC serves several purposes: as a planning and communication tool in the early implementation stages, to compensate for lost public participation opportunities when using the RCRA streamlined permit modification procedure to make upgrades for MACT compliance, and as a means to share information and provide public participation opportunities that would be lost when new units are not required to comply with certain RCRA permit requirements and performance standards. Please refer to the proposal at 69 FR 21313–21316 for additional discussion of the regulatory history, purpose, and implementation of the NIC provisions.

Overall, most commenters supported our decision to finalize NIC provisions. However, they also feel that the NIC should only be required for sources that have not completed a NIC previously (i.e., Phase 2 sources or Phase 1 sources that did not meet the previous NIC deadline) and for sources that need to make upgrades to comply with the final standards (i.e., either Phase 1 or Phase 2). They suggest that if sources do not need to make upgrades, then they should not be required to complete the NIC process, if they had done so previously. To require a second NIC would only add to the administrative burden and is not in line with Agency efforts to reduce reporting burdens. We agree that if Phase 1 sources do not need to make upgrades to comply with the Replacement Standards and if they completed the NIC process before, then it is not necessary to do so again.

In addition to the comment discussed above, a few commenters proposed that for sources who must still comply with the NIC because they wish to make upgrades, that the NIC public notice be combined with the Title V re-opening or renewal public notice. They point out that sources with existing Title V permits will have their permits re-opened or renewed to incorporate the new applicable requirements (i.e., Phase 1 Replacement or even Phase 2 Standards) shortly after the NIC public notice and meeting are to occur. Title V permit re-openings and renewals require: public notice, a minimum of 30 days for comment, and an opportunity to request a hearing.

While we do agree that the Title V re-opening and renewal requirements provide adequate information to the public and an opportunity for the public to comment and request a hearing, we are concerned that the timing requirements for the NIC may not correspond with the timing requirements for title V permit reopenings, revisions, and renewals. The public review of the draft NIC and subsequent public meeting are scheduled to occur 9 and 10 months, respectively, after the rule's effective date. On the other hand, Title V permits for major sources that have a remaining permit term of greater than 3 years from the rule's promulgation date will need to be re-opened, but this re-opening may not occur until 18 months beyond the promulgation date of the rule. Also, Title V permits that have a remaining permit term of less than 3 years from the rule's promulgation date will need to be renewed, but the timing of the renewal is contingent upon the individual permit term, not the timing requirements for public review of the draft NIC and public meeting. Thus, we do not believe there is ample opportunity to combine the requirements of the NIC and Title V process for the vast majority of sources.[208] Also, those sources that need to make upgrades to comply with the final standards and that need to modify any applicable conditions in their RCRA permit will not be able to request the streamlined modification procedure (see 40 CFR 270.42(j)) until they meet the NIC requirements. So the earlier they comply with the NIC requirements, the earlier they can begin upgrading their combustion units.

Another commenter suggested a change to the regulations at § 63.1210(c)(1) to account for sources that will cease burning hazardous waste prior to or on the compliance date. The regulations, as proposed, require sources to hold an informal public meeting to discuss anticipated activities described in the draft NIC even if they plan to cease burning hazardous waste. The commenter also suggested a similar change to § 63.1210(b)(2) that requires the draft NIC be made available for public review no later than 30 days

[208] We recognize that there may be instances when states can coordinate the Title V permit re-opening, revision, and renewal process with the NIC timeframe requirements. Where this is possible, we encourage states (or other permitting authorities) to coordinate the two processes. By coordinating the two, duplication with respect to material content and public participation would be eliminated for both sources and states.

prior to the public meeting. We agree with the commenter that it does not make sense to require sources that intend to cease burning hazardous waste to submit a NIC that discusses anticipated activities that will allow them to achieve compliance with the standards. We also agree that it is not necessary for those sources to hold an informal public meeting, since there are no MACT compliance activities to discuss. However, we believe that the public should be provided notice of the draft NIC so that they are aware of the source's intentions to cease burning and the steps (and key dates) the source will undertake to stop hazardous waste combustion activities.

With regard to Phase 2 sources, we had proposed that all Phase 2 sources comply with the same NIC requirements as the Phase 1 sources. Commenters did not express opinions in favor or against the NIC for Phase 2 sources. We believe that the NIC is beneficial in several respects. As mentioned previously, it serves as a planning and communication tool in the early implementation stages, it compensates for lost public participation opportunities when using the RCRA streamlined permit modification procedure to make upgrades for MACT compliance, and it is a tool to share information and provide public participation opportunities that would be lost when new units are not required to comply with certain RCRA permit requirements and performance standards. Ultimately, it creates more public confidence in the permitting process and so promotes a more stable regulatory environment.

For today's rule, we are finalizing our decision to re-institute the NIC provisions for Phase 1 and Phase 2 sources. We are including a few minor changes and clarifications to improve the proposed regulatory language based on commenters' suggestions. Section 63.1210(b) is revised so that Phase 1 sources that previously complied with the NIC requirements, and that do not need to make upgrades to comply with the Replacement Standards, are not required to comply with the NIC again. Sections 63.1210(b)(1)(iv) and (b)(2) have been revised and (c)(5) has been added so that sources that intend to cease burning hazardous waste prior to or on the compliance date are only required to prepare a (draft) NIC, make a draft of the NIC available for public review no later than 9 months after the effective date of the rule, and submit a final NIC to the Administrator no later than one year following the effective date of the rule. Last, we have revised language in § 63.1210(b) based upon a commenter's concerns that the term you "will" implies that sources are required meet their "estimated" dates for achieving key activities. We have removed "will" and replaced it with "anticipate" to more accurately represent the objective of the NIC, which is for sources to communicate their plans for complying with the standards in two years.

2. Compliance Progress Report

In the proposal, we explained why we thought a compliance progress report would be beneficial. In short, we believed it would help regulatory agencies determine whether Phase 1 and Phase 2 sources were making sufficient headway in their efforts to meet the compliance date. The progress report would be due to the regulatory agency at the midway point of the 3 year compliance period and would serve to update the information the source provided in its NIC. However, because we do not have any experience to draw upon regarding the value of the progress report, we requested comment on whether or not it should be required.

In response to our request for comment, all commenters were opposed to the progress report. They cited several reasons, with the most consistent one being that the progress report serves no useful purpose and imposes unnecessary additional burdens on sources. As we discussed above, sources and regulatory agencies will be focusing on the NIC as well as initial Title V applications, re-openings, revisions, and renewals during this three year compliance period. We agree with the commenter who noted that there is already significant interaction between sources and regulatory authorities during this period. Furthermore, we learned through implementation of the Interim Standards that some regulatory agencies found it difficult to manage the notices, applications, requests, and test plans that were due prior to the compliance date. Therefore, we have decided not to finalize any compliance progress report requirements for today's rule.

F. Startup, Shutdown, and Malfunction Plan

Comment: One commenter states that an exceedance of a standard or operating requirement during a malfunction should be a violation not only because source owners and operators need an incentive to minimize exceedances caused by malfunctions, but also because an exemption for malfunction periods would violate the plain language of the CAA. The commenter notes that an emission standard is defined by 42 U.S.C. § 7602(k) as a standard that "limits the quantity, rate, or concentration of emissions of air pollutants on a continuous basis, including any requirement relating to the operation of maintenance of a source to assure continuous emission reduction, and any design, equipment, work practice or operational standard * * *." The commenter concludes that a standard that contains a malfunction exemption does not apply "on a continuous basis" as required by the statute. Likewise, the commenter concludes that an exemption for startup and shutdown periods would also violate this unambiguous statutory language.

The commenter also notes that, although some courts have held that a technology-based standard must provide some kind of an exemption for unavoidable technology failures, the rationale for such an exemption is that the underlying standard is based on the performance of a particular control technology that cannot be expected to function properly all of the time. The commenter believes that neither the rationale nor the exemption apply to section 112(d) standards, which are not based on the performance of any particular technology but instead must reflect the "maximum degree of reduction" that can be achieved, irrespective of the measures used by a source to achieve that reduction. CAA § 112(d)(2).

The commenter states that, even assuming for the sake of argument that EPA has authority to depart from the statutory language and carve out a startup, shutdown, and malfunction exemption, any such exemption must be narrowly drafted to apply only where a source demonstrates that a violation was unavoidable. See, e.g., *Marathon Oil*, 564 F.2d at 1272–73. As EPA recognizes, emission exceedances that occur during SSM events are frequently avoidable. See 69 FR at 21339/3 (noting that "proper operation and maintenance of equipment" helps avoid exceedances during startup, shutdown, and malfunction events), 69 FR at 21339/2 (describing the industry view that "some" exceedances that occur due to malfunctions are unavoidable). Thus, the commenter concludes that, even if a Marathon Oil-type exemption applies to a § 112(d) standard, it would be unlawful and arbitrary for EPA to exempt sources from liability for all emission exceedances occurring during startup, shutdown, and malfunction events. Rather, such an exemption could only apply where a source demonstrates that a given exceedance was unavoidable.

Many other commenters state that it would be illegal to require compliance with the emission standards and operating requirements during startup, shutdown, and malfunction events. The commenters note that EPA and the courts have long recognized that technology fails at times, despite a source's best efforts to maintain compliance. For this reason, the courts have recognized that technology-based standards such as EPA's § 112(d)(2) MACT standards must account for such unavoidable technology failures if the standards are to be truly "achievable." Thus, the standards must excuse noncompliance with the actual emission standards during startup, shutdown, and malfunction events.

These commenters also note that EPA took the position in the September 1999 final MACT rule for hazardous waste combustors that exceedance of an operating requirement during startup, shutdown, or malfunction events was a violation if hazardous waste remained in the combustion chamber. The commenters note that industry groups challenged the rule, and while the D.C. Circuit did not reach this issue because it vacated the emission standards, it pointed out that "industry petitioners may be correct that EPA should have exempted HWCs from regulatory limits during periods of startup, shutdown, and malfunction, permitting sources to return to compliance by following the steps of a startup, shutdown, and malfunction plan filed with the Agency." *CKRC* v. *EPA*, 255 F.3d 855, 872 (2001). Commenters conclude that, after reading this language, EPA officials wisely decided that hazardous waste combustors should not be required to meet the MACT emission standards and operating limits during startup, shutdown, and malfunction events.

Response: We agree with commenters who state that sources must be exempt from technology-based emission standards and operating limits during startup, shutdown, and malfunction events. Technology is imperfect and can malfunction for reasons that are not reasonably preventable. The regulations must provide relief for such situations. We believe that existing case law supports this position. See, e.g., *Chemical Mfr's Ass'n* v. *EPA*, 870 F. 2d at 228–230 (daily maximum limitations established at 99th percentile reasonable because rules also provide for upset defense for unavoidable *exceedances*); *Marathon Oil* v. *EPA*, 541 F. 2d at 1272–73 (acknowledged by commenter). As commenters noted, the D.C. Circuit also intimated in *CKRC* that some type of exception from compliance with standards during startup, shutdown and malfunction periods was required.

We do not agree with the commenter who contends that the § 112(d) MACT standards are not technology-based standards because they are not based on the performance of any particular technology but instead must reflect the "maximum degree of reduction" that can be achieved, irrespective of the measures used by a source to achieve that reduction. On the contrary, the standards must reflect the average performance of the best performing sources, which performance is achieved using technical controls—air pollution control devices, and for some pollutants, hazardous waste feedrate control. Those controls can fail for reasons that are not reasonably preventable. We note further that the situation was the same in the Clean Water Act cases which the commenter seeks to distinguish. Like section 112(d) standards, Clean Water Act standards are technology-based (reflecting Best Practicable Technology or Best Available Technology, see CWA sections 304 (b) and 301 (b)) and do not require use of any particular type of technology. See also *Mossville*, 370 F. 3d at 1242 (EPA must account for foreseeable variability in establishing MACT floor standards).

We agree with the commenter who states that any exemption from the emission standards and operating requirements during malfunctions must apply only where a source demonstrates that a violation was unavoidable. We note that the term malfunction is defined in § 63.2 as "any sudden, infrequent, and not reasonably preventable failure of air pollution control and monitoring equipment, process equipment, or a process to operate in a normal or usual manner which causes, or has the potential to cause, the emission limitations in an applicable standard to be exceeded. Failures that are caused in part by poor maintenance or careless operation are not malfunctions." We believe this definition largely addresses the commenter's concern.

We acknowledge, however, that emissions can increase during malfunctions and potentially exceed the standards and agree that exceedances must be minimized. Accordingly, the final rule (and the current rule for incinerators, cement kilns, and lightweight aggregate kilns) requires that sources maintain compliance with the automatic hazardous waste feed cutoff system during malfunctions and notify the permitting authority if they have 10 or more exceedances of an emission standard or operating limit during a 6-month block period when hazardous waste is in the combustion chamber. See § 63.1206(c)(2)(v). This will alert the permitting authority that the source's operation and maintenance plan may not be adequate to maintain compliance with the emission standards and that the authority may need to direct the source to revise the plan under § 63.6(e)(3)(vi). Finally, we note that sources must report all excess emissions semiannually under § 63.10(e)(3) if an emission standard or operating limit is exceeded, including during malfunctions.

Comment: One commenter states that any exemption for emission exceedances during startup, shutdown, or malfunction events would violate the RCRA mandate for standards necessary "to protect human health and the environment." 42 U.S.C. 6924(a). The commenter reasons that, because EPA's RCRA standards are health-based rather than technology-based, no unavoidability defense is available. Given that EPA concludes that the hazardous waste combustor MACT rule satisfies both its CAA and RCRA mandates, the emission standards and operating requirements cannot be waived during startup, shutdown, and malfunction events.

Response: We agree that the RCRA mandate to ensure protection of human health and the environment applies at all times, including during startup, shutdown, and malfunction events. Accordingly, the existing MACT requirements for incinerators, cement kilns, and lightweight aggregate kilns give sources the option of continuing to comply with RCRA permit requirements to control emission during these events, or to comply with special MACT requirements that are designed to be proactive and reactive and intended to be equivalent to the incentive to minimize emissions during these events provided by the RCRA requirements. See existing § 63.1206(c)(2)(ii). The special MACT requirements require sources to include proactive measures in the startup, shutdown, and malfunction plan to minimize the frequency and severity of malfunctions and to submit the startup, shutdown, and malfunction plan to the permitting authority for review and approval. We proposed to require boilers and hydrochloric acid production furnaces to comply with those same provisions providing for equivalence between the two sets of requirements, and promulgate those provisions today.

Comment: One commenter states that the rule should clarify the definitions of startup, shutdown, and malfunctions to preclude sources from improperly

classifying as unavoidable exceedances those exceedances that could have been avoided had the source implemented an appropriate operation and maintenance plan. Many other commenters state that the current definitions in § 63.2 clearly define these terms.

Response: We believe the definitions of startup, shutdown, and malfunction are clearly defined in § 63.2, and combined with the startup, shutdown, and malfunction plan requirements, will preclude sources from improperly classifying as malfunctions events that could have been reasonably prevented by following appropriate procedures in the operation and maintenance plan. As discussed above, the definition of malfunction clearly states that failures that are caused in part by poor maintenance or careless operation are not malfunctions.

Comment: One commenter states that all stack bypasses, automatic waste feed cutoffs, and excursions from the operating parameter limits should be considered malfunctions.

Response: All failures resulting in stack bypasses, automatic waste feed cutoff, and excursions from the operating parameter limits are not malfunctions. As discussed above, failures caused in part by poor maintenance or careless operation are not malfunctions.

Comment: One commenter states that the rule should require sources to expand the startup, shutdown, and malfunction plan to address specific proactive measures that the source has considered and is taking to minimize the frequency and severity of malfunctions. Many other commenters believe that it is not necessary to expand the scope of the startup, shutdown, and malfunction plan beyond that required under § 63.6(e)(3) for other MACT source categories.

Response: We do not believe that it is necessary to expand the scope of the startup, shutdown, and malfunction plan generically for all hazardous waste combustors to address specific proactive measures that the source has considered and is taking to minimize the frequency and severity of malfunctions. Imposing additional requirements in particular situations is appropriate, however. For example, as discussed above, this expanded plan is required for sources that elect to meet the RCRA mandate using provisions of the startup, shutdown, and malfunction plan. See § 63.1206(c)(2)(ii). In addition, the plan with expanded scope may be appropriate for sources that have demonstrated an inability to minimize malfunctions. Consequently, the permitting authority should consider expanding the scope of the startup, shutdown, and malfunction plan on a site-specific basis under authority of § 63.6(e)(3)(vii) if the source has excessive exceedances during malfunctions. See § 63.1206(c)(2)(v)(A)(*3*) defining excessive exceedances during malfunctions and requiring reporting of the exceedances in the excess emissions report required under § 63.10(e)(3).

Comment: Two commenters state that all startup, shutdown, and malfunction plans should be submitted for review and approval by the delegated authority and made available for a 60-day public review period. Review and approval of the plans is needed in light of EPA's acknowledgment that most excess emissions would occur during startup, shutdown, and malfunctions. One of these commenters also believes that the regulations should provide for the public review period to be extended as necessary to accommodate a thorough public review. The reviewing authority should be required to provide a written response to public comments explaining any decision to reject a public comment suggesting ways for a facility to limit emissions during startup, shutdown, and malfunction events.

Many other commenters have concerns with requiring review and approval of startup, shutdown, and malfunction plans, except as required under § 63.1206(c)(2)(ii) for sources that elect to meet the RCRA mandate using provisions of the startup, shutdown, and malfunction plan as discussed above.

Response: Commenters express the same views here that they expressed under the rulemaking the Agency recently completed to revise the startup, shutdown, and malfunction plan requirements of the General Provisions applicable to all MACT source categories. See 68 FR at 32589–93 (May 30, 2003).

EPA concluded in that final rule that the Administrator may at any time request in writing that the owner or operator submit a copy of any startup, shutdown, and malfunction plan (or a portion thereof). Upon receipt of such a request, the owner or operator must promptly submit a copy of the requested plan (or a portion thereof) to the Administrator. In addition, the Administrator must request that the owner or operator submit a particular startup, shutdown, or malfunction plan (or a portion thereof) whenever a member of the public submits a specific and reasonable request to examine or to receive a copy of that plan or portion of a plan.

These provisions to provide the Administrator and the public with access to startup, shutdown, and malfunction plans, coupled with the provisions of § 63.6(e)(3)(vii) under which the Administrator must require the source to make changes to a deficient plan, should ensure that startup, shutdown, and malfunction plans are complete and accurate. We note that under § 63.6(e)(3)(vii) the Administrator must require the source to revise the plan if the plan: (1) does not address a startup, shutdown, or malfunction event that has occurred; (2) fails to operate the source (including associated air pollution control and monitoring equipment) during a startup, shutdown, or malfunction event in a manner consistent with the general duty to minimize emissions; (3) does not provide adequate procedures for correcting malfunctioning process and/or air pollution control and monitoring equipment as quickly as practicable; or (4) includes an event that does not meet the definition of startup, shutdown, or malfunction listed in § 63.2.

The commenter advocating that all hazardous waste combustors should be required to submit their startup, shutdown, and malfunction plans for review and approval did not explain why the concerns the Agency expressed in the General Provisions rulemaking (see 68 FR at 32589–93) are not valid for hazardous waste combustors. Accordingly, we do not believe it is appropriate to deviate from the General Provisions to require that all hazardous waste combustors submit their startup, shutdown, and malfunction plans for review.

G. Public Notice of Test Plans

1. What Are the Revised Public Notice Requirements for Test Plans?

Prior to the proposal, it was brought to our attention that the Agency did not provide any direction in the 1999 final rule regarding how and when sources should notify the public, what the notification should include, or where and for how long performance test plans should be made available. Consequently, we proposed to add clarifying language to the § 63.1207(e)(2) public notification requirement for approved performance test and CMS performance evaluation test plans because we believe that providing opportunities for timely and adequate public notice is necessary to fully inform nearby communities of a source's plans to initiate important waste management activities. The proposed clarifications are based upon the *RCRA Expanded Public Participation Rule* (60 FR 63417, December 11, 1995) requirements for

public notification of an impending trial burn test. As a result, we did not feel that the clarifications imposed any new or additional requirements upon sources that will conduct a MACT comprehensive performance test or confirmatory performance test.

Commenters generally supported the clarifications to the public notice.[209] However, they suggested a change to the proposed requirement to provide notice of test plan approval no later than 60 days prior to conducting the test. The basis for suggesting a change is that many sources had not received approval of their test plans 60 days prior to the deadline for initiating their test under the Interim Standards. Moreover, several sources did not receive approval until well after the deadline for initiating the test. The problem created for these sources is that the required 60 day notification of the approved test plan effectively determines when the source will be able to begin its test. In other words, its test would need to be postponed until the approved test plan had been noticed for 60 days. Thus, commenters provided several possible alternatives.

One alternative that would avoid causing delays to testing is to require the public notice when the source submits its test plan. Although this fulfills the notification requirement, this alternative has a shortfall: The notice would occur at least one year (barring any extensions) in advance of the test and given this long period of time, the test plan is likely to be modified prior to approval. A second alternative is to provide notice of the test plan 60 days before the test as before, but regardless of approval status. This alternative is improved over the first, but still faces the same problem of potentially not offering the public an opportunity to view a final approved plan. A third alternative is to issue notice of the test plan as soon as it is approved. With this alternative, the public will have the most up-to-date information; however, it may not be until a few days prior to commencement of the test. Ideally, the second and third alternatives could be combined to provide the best possible chance of providing the public with an approved test plan in a reasonable period of time prior to the test. On the other hand, that would potentially require the facility to issue two notices if the test plan is not approved 60 days prior to the test. We do not believe this would be reasonable given that sources will be focused on activities associated with the impending test.

[209] See 69 FR 21347–21349.

In consideration of practicality, we believe that the second alternative provides an adequate solution. As we mentioned, the drawback is that the public may not have the opportunity to view an approved test plan. However, we believe it is more important that the public be aware of a source's plans (*i.e.*, how and when) for conducting the performance test.[210] This way, if they have questions, there will be 60 days in which they may contact the regulatory authority or the source before the test is scheduled to begin. This alternative will also eliminate the conflict associated with the confirmatory performance test. The regulations at § 63.1207(e)(1)(ii) specify that a source must submit to the regulatory authority its notice of intent to conduct a confirmatory performance test and the applicable test plans at least 60 calendar days prior to the date the test is to begin. Since we are no longer requiring that the test plans be approved before issuing public notice, sources would then provide notice of their confirmatory performance test plan to the public at the same time they submit their notice of intent and test plans to the regulatory authority. Therefore, we are requiring that sources issue the public notice of test plans 60 days in advance of commencing the performance test, whether their test plans have been approved or not. The regulations at § 63.1207(e)(2) have been revised accordingly.

One last concern related to the public notice of approved test plans involves sources that choose to conduct a performance test without an approved test plan (*e.g.*, both time extensions provided by §§ 63.7(h) and 63.1207(e)(3) have expired or due to other circumstances, the source has elected to begin the test without approval). Because we did not believe any sources would choose or need to do so, we did not propose any guidance or regulations specific to issuing notice to the public of their test plans. Nevertheless, a few commenters raised this possibility indirectly in their discussion of the problematic 60 day notice of approved test plan requirement. The revised proposal addresses this concern by no longer requiring that test plans be approved before issuing public notice. Thus, sources that choose to begin their test without an approved plan will have complied with the requirement to issue public notice. Irrespective of the public notice requirements for noticing test plans, we expect that sources will notify their regulatory authority of their decision to proceed with their test in the absence of plan approval.

[210] We expect that some source's test plans may be modified after notice is issued and prior to approval or commencement of their test. However, even under the previous regulations, test plans could be modified after they had been approved and public noticed. It is often a necessary consequence as sources continue to prepare the combustion unit for the test.

2. What Are the Revised Public Notice Requirements for the Petition To Waive a Performance Test?

In the Final Amendments Rule (67 FR 6968, February 14, 2002), the Agency did not provide direction regarding how, when, where, and what should be included in the public notice for a petition for time extension if the Administrator fails to approve or deny test plans.[211] In the proposal, we believed it important to provide clarification regarding when the notice must be issued and what it should contain. Thus, we proposed to revise paragraph § 63.1207(e)(3)(iv).

We received only one comment in response to the proposed requirements. The commenter did not express any concern over the requirements themselves, but rather suggested a change to terminology used. The commenter feels that the terms "to waive a performance test" or "waiver" as used in § 63.1207(e)(3)(iv) could be confusing to readers when we are actually referring to a time extension for commencing the test. Although we agree the terminology could be confusing, 40 CFR 63.1207(e)(3) clearly uses the term "waiver" in the context of an extension of time to conduct the performance test at a later date, implying that the deadline can be waived in this specific situation. The use of the term waiver is derived from the General Provisions requirements for requesting a waiver of performance tests (§ 63.7(h)). Thus, § 63.7(h)(3) provides the basis by which sources may petition, in the form of a waiver, for a time extension under § 63.1207(e)(3). In consideration of the above and that the existing regulations of § 63.1207(e)(3)(i)-(iii) consistently use the term waiver, we do not feel that a change to § 63.1207(e)(3)(iv) is warranted.

H. Using Method 23 Instead of Method 0023A

Comment. Most commenters support our proposal to allow the use of Method 23 instead of Method 0023A if a source includes this request in the comprehensive test plan to the permitting authority. Some commenters believe that Method 23 should be

[211] Sections 63.1207(e)(2) and (e)(3) each require public notice, but neither had provided any direction on how, when, where, and what should be included in their respective notices until today's final rule.

allowed in all cases without prior approval or on a source category basis.

Response. We proposed to allow sources to use Method 23 for dioxin and furan testing instead of SW–846 Method 0023A in situations where the enhanced procedures found in Method 0023A would not increase measurement accuracy. We proposed this change in the July 3, 2001, proposed rule, and again in the April 20, 2004, proposal. See 66 FR at 35137 and 69 FR at 21342.

The final rule promulgates this change as proposed. See § 63.1208(b)(1)(i). You may use Method 23 in lieu of Method 0023A after justifying use of Method 23 as part of your performance test plan that must be reviewed and approved the delegated permitting authority. You may be approved to use Method 23 considering factors including whether previous Method 0023A analyses document that dioxin/furan are not detected, are detected at low levels in the front half of Method 0023A, or are detected at levels well below the emission standard, and the design and operation of the combustor has not changed in a manner that could increase dioxin/furan emissions. We note that coal-fired boilers and combustors equipped with activated carbon injection systems may not be able to support use of Method 23, however, because these sources' stack gas is likely to contain carbonaceous particulate. Thus, these sources are likely to benefit the most from using Method 0023A.

The final rule does not automatically allow use of Method 23 for particular source categories because we cannot assess whether all sources in a category meet the conditions for use of Method 23—generally that quality assurance may not be improved—such as those listed above. These determinations can only be made on a site specific basis by the permitting authority most familiar with the particular source.

Comment: Commenters do not believe that an additional petition process (*i.e.*, under § 63.1209(g)(1)) is necessary before allowing use of Method 23. Instead, EPA should require that the use of Method 23 should be submitted with the test plan to the regulatory agency for approval.

Response: We agree that a separate petition is unnecessary. Sources should include a justification to use Method 23 in the performance test plan that is submitted for review and approval. This will allow the permitting authority to determine whether use of Method 23 is appropriate for the source.

Comment: Two commenters state that "the justification of the use of Method 23 will not be by the existing system of a petition to EPA, but will be included as a part of the performance test plan that is submitted to the delegated regulatory authority for review and approval. This means that the expertise, training, and decision-making will not be consistent across the country. This is especially a problem because of the severe resource, training and staff reductions among the delegated regulatory authorities across the country and from region to region. The decision to allow or disallow use of Method 23 should come specifically, for each case, from EPA consideration of the submitted justification, based on the knowledge and expertise of trained and experienced EPA staff. This is important for uniformly applying the testing requirements all across the country."

Response: We disagree, and we believe the responses to comments in today's rule make clear when Method 23 is an acceptable substitute for Method 0023A. If the source has carbon in the flue gas, as is the case with coal-fired boilers, boilers with carbon injection, and other sources likely to have a substantial amount of carbonaceous particulate matter in the flue gas, Method 0023A will generally be preferable because it includes procedures to account for dioxin and furan bound to carbonaceous particulate matter found in the probe and filter. In other situations, Method 23 will generally give the same results at a lower cost.

I. Extrapolating Feedrate Limits for Compliance With the Liquid Fuel Boiler Mercury and Semivolatile Metal Standards

Comment: One commenter questions whether allowing sources to extrapolate metal feedrates downward from the levels achieved during the comprehensive performance test to establish a metal feedrate limit will ensure compliance with the emission standards.

Response: The mercury and semivolatile metals standards for liquid fuel boilers are annual average emission limits where compliance is established by a rolling average mercury feedrate limit with an averaging period not to exceed an annual rolling average (updated hourly).[212] We use this approach because the emissions data used to establish the standards are more representative of normal emissions than compliance test emissions.[213]

As we explained at proposal, to ensure compliance with the mercury and semivolatile metal emission standards for liquid fuel boilers, you must document during the comprehensive performance test a system removal efficiency for the metals and back-calculate from the emission standard a maximum metal feedrate limit that must not be exceeded on an (not to exceed) annual rolling average. See 69 FR at 21311–12. If your source is not equipped with an emission control system (such as activated carbon to control mercury) for the metals in question, however, you must assume zero system removal efficiency. This is because, although a source that is not equipped with an emission control system may be able to document a positive system removal efficiency in a single test, that removal efficiency is not likely to be reproducible. Rather, it is likely to be an artifact of the calculation of emissions and feeds rather than a removal efficiency that can reliably be repeated.

To ensure that you can calculate a valid, reproducible system removal efficiency for sources equipped with a control system that effectively controls the metal in question, you may need to spike metals in the feed during the comprehensive performance test at levels that may result in emissions that are higher than the standard. This is appropriate because compliance with an emission standard derived from normal emissions data is based on compliance with an (not to exceed) annual average feedrate limit calculated as prescribed here, rather than compliance with the emission standard during the comprehensive performance test.[214]

The commenter is concerned that downward extrapolation from the levels achieved during the comprehensive performance test to establish a metal feedrate limit may not ensure

[212] If you select an averaging period for the feedrate limit that is greater than a 12-hour rolling average, you must calculate the initial rolling average as though you had selected a 12-hour rolling average, as provided by § 63.1209 (b)(5)(i). This is reasonable because allowing a longer period of time before calculating the initial rolling average would not effectively ensure compliance with the feedrate limit. You must calculate rolling averages thereafter as the average of the available one-minute values until enough one-minute values are available to calculate the rolling average period you select. We note that this is an approach allowed for calculating rolling averages under different modes of operation at § 63.1209(q)(2)(ii). At that time and thereafter, you update the rolling average feedrate each hour with a 60-minute average feedrate.

[213] See USEPA, "Technical Support Document for HWC MACT Standards, Volume III: Selection of HWC MACT Standards," September 2005, Section 13.

[214] The emission standard accounts for long-term variability by incorporating an (not to exceed) annual averaging period that is implemented by an (not to exceed) annual average chlorine feedrate limit. Thus, because the emission level achieved during the performance test relates to daily (or hourly) variability, an exceedance of the emission standard during the test is not a violation.

compliance with the standard because system removal efficiency may be lower at lower feedrates.

This is a valid concern, and we have investigated it since proposal. We conclude that downward extrapolation of feedrates for the purpose of complying with the mercury and semivolatile metals emission standards for liquid fuel boilers will ensure compliance with the emission standards under the conditions discussed below.

We investigated the theoretical relationship between stack gas emissions and feedrate considering vapor phase metal equilibrium, the chlorine, mercury, and semivolatile metal feedrates for liquid fuel boilers in our data base, and the mercury and semivolatile emission standards for liquid fuel boilers.[215] We considered sources equipped with dry particulate matter controls and sources equipped with wet particulate matter controls.

Sources Equipped with Dry Controls. For sources equipped with dry controls other than activated carbon, mercury is not controlled. Thus, you must assume zero system removal efficiency. Consequently, if you are in the low Btu subcategory and comply with the mercury standard expressed as a mass concentration (μg/dscm), the mercury feedrate limit expressed as an MTEC (maximum theoretical emission concentration, μg/dscm) is equivalent to the emission standard.[216] If you are in the high Btu subcategory and comply with the mercury standard expressed as a hazardous waste thermal emission concentration (lb/MM Btu), the mercury feedrate limit expressed as a hazardous waste thermal feed concentration (lb/MM Btu) is also equivalent to the emission standard.

For semivolatile metals, the theoretical relationship between emissions and feedrate indicates that downward extrapolation introduces only a trivial error 0.17% at an emission rate 100 times the standard irrespective of the level of chlorine present. Id. Nonetheless, to ensure the error is minimal and to be practicable, you should limit semivolatile emissions during the comprehensive performance test to five times the emission standard.

Sources Equipped with Wet Scrubbers. For sources equipped with wet scrubbers, we conclude that the approach we use for semivolatile metals for dry scrubbers will also be appropriate to extrapolate a semivolatile metal feedrate limit for wet scrubbers. To ensure that downward extrapolation of the feedrate limit is conservative and to be practicable, you should limit semivolatile metal emissions during the comprehensive performance test to five times the emission standard.

For mercury, ensuring control with wet systems is more complicated because the level of chlorine present affects the formation of mercuric chloride which is soluble in water and easily controlled by wet scrubbers. Elemental mercury has very low solubility in scrubber water and is not controlled. The worst-case situation for conversion of elemental mercury to soluble mercuric chloride would be when the chlorine MTEC is lowest and the mercury MTEC is highest. We conclude that downward extrapolation of mercury feedrates is conservative for feedstreams that contain virtually no chlorine, *e.g.*, below an MTEC of 100 μg/dscm. In addition, we conclude that downward extrapolation is appropriate[217] for boilers feeding chlorinated feedstreams provided that during the performance test: (1) Scrubber blowdown has been minimized and the scrubber water has reached steady-state levels of mercury prior to the test (*e.g.*, by spiking the scrubber water); (2) scrubber water pH is minimized (*i.e.*, you establish a minimum pH operating limit based on the performance test as though you were establishing a compliance parameter for the total chlorine emission standard); and (3) temperature of the scrubber water is maximized (*i.e.*, you establish a maximum scrubber water temperature limit).

J. Temporary Compliance With Alternative, Otherwise Applicable MACT Standards

Comment: One commenter requests clarification on the requirements applicable to a source that switches to an alternative mode of operation when hazardous waste is no longer in the combustion chamber under the provisions of § 63.1206(b)(1)(ii). The commenter suggests that § 63.1206(b)(1)(ii) can imply that the complete compliance strategy needs to be switched over to the alternative section 112 or 129 requirements, even though compliance with the Subpart EEE requirements for monitoring, notification, reporting, and recordkeeping remains environmentally protective under Subpart EEE. For example, the commenter notes that § 63.1206(b)(1)(ii) could be incorrectly interpreted to require a source to comply with illogical requirements when the source temporarily switches to alternative, otherwise applicable standards, including standards testing and opacity monitoring under the alternative section 112 or 129 requirements. The commenter states that this interpretation makes little sense because a source that temporarily changes its mode of operation will continue to do testing under Subpart EEE, Part 63, or, in the case of opacity, the alternative section 112 requirements for cement kilns would necessarily require duplicate systems and compliance with redundant limits because a source may already be using a bag leak detection system or a particulate matter detection system. The commenter suggests only requiring sources to comply with the otherwise applicable emission standards under the alternative section 112 or 129 requirements while still operating under the various associated compliance requirements of Subpart EEE, part 63.

Response: The commenter requests clarification of § 63.1206(b)(1)(ii), which states that if a source is not feeding hazardous waste to the combustor and the hazardous waste residence time has expired (*i.e.*, the hazardous waste feed to the combustor has been cut off for a period of time not less than the hazardous waste residence time), then the source may elect to comply temporarily with alternative, otherwise applicable standards promulgated under the authority of sections 112 and 129 of the Clean Air Act.[218] As we have explained in previous notices,[219] sources that elect to invoke § 63.1206(b)(1)(ii) to become temporarily exempt from the emission standards and operating requirements of Subpart EEE, Part 63, remain an affected source under Subpart EEE (and only Subpart EEE) until the source is no longer an affected source by meeting the requirements specified in Table 1 of § 63.1200. Of course, a source can elect not to use the alternative requirements for compliance during periods when

[215] USEPA, "Technical Support Document for HWC MACT Standards, Volume IV: Compliance with the HWC MACT Standards," September 2005, Section 2.5 and Appendix B.

[216] Note, however, that you convert the MTEC (μg/dscm) to a mass feedrate (lb/hr) by considering the average gas flowrate of the test run averages during the comprehensive performance test to simply implementation and compliance.

[217] Mercury SRE is constant as the mercury feedrate decreases.

[218] Examples include 40 CFR part 60, subparts CCCC and DDDD for commercial and industrial solid waste incinerators, 40 CFR part 63, subpart LLL for Portland cement manufacturing facilities, 40 CFR part 63, subpart DDDDD for industrial/commercial/institutional boilers and process heaters, and 40 CFR part 63, subpart NNNNN for hydrochloric acid production facilities.

[219] This provision has been discussed in several Federal Register notices including 64 FR at 52904 (September 30, 1999), 66 FR at 35090, 35145 (July 3, 2001), 67 FR at 6979 (February 14, 2002), and 69 FR at 21203 (April 20, 2004).

they are not feeding hazardous waste, but, if so, the source must comply with all of the operating and monitoring requirements and emission standards of Subpart EEE at all times.[220] To implement § 63.1206(b)(1)(ii) a source defines the period of compliance with the otherwise applicable sections 112 and 129 requirements as an alternative mode of operation under § 63.1209(q). In order to be exempt from the emission standards and operating requirements of Subpart EEE, a source documents in the operating record that they are complying with the otherwise applicable Section 112 and 129 requirements specified under § 63.1209(q).

The commenter recommends that the complete compliance strategy need not be switched over to the alternative section 112 and 129 requirements when temporarily switching to the alternative standards. In general, we disagree. The intent of § 63.1206(b)(1)(ii) is to ensure that a source is complying with all requirements of sections 112 and 129 as an alternative mode of operation in lieu of the requirements under Subpart EEE. In the 1999 final rule we stated that the source must comply with all otherwise applicable standards under the authority of sections 112 and 129. Specifically, the source must comply with all of the applicable notification requirements of the alternative regulation, comply with all of the monitoring, recordkeeping, and testing requirements of the alternative regulation, modify the Notice of Compliance (or Documentation of Compliance) to include the alternative mode(s) of operation, and note in the operating record the beginning and end of each period when complying with the alternative regulation. See 64 FR at 52904. A source that elects to comply with otherwise applicable standards under § 63.1206(b)(1)(ii) must specify all requirements of those standards, not only the emission standards applicable under the sections 112 and 129 standards, but also the associated monitoring and compliance requirements and notification, reporting, and recordkeeping requirements in the operating record under § 63.1209(q).

The commenter suggests that a source should be able to comply with the otherwise applicable emission standards, while continuing to operate under the associated compliance requirements for the HAP under Subpart EEE. An example would be a cement kiln source complying with the dioxin and furan monitoring requirements under § 63.1209(k) of Subpart EEE for the dioxin and furan standards under § 63.1343(d) under Subpart LLL. We did not determine, when promulgating the provisions of §§ 63.1206(b)(1)(ii) and 63.1209(q)(1), that the monitoring provisions under Subpart EEE are equivalent to the associated monitoring requirements under the otherwise applicable 112 and 129 standards, or indeed, whether they are even well-matched. Such a determination would require notice and opportunity for comment, which we have not provided. However, this should not be interpreted to mean that a similar determination could not be made on a site-specific basis given that the MACT general provisions allow a source to request alternative monitoring procedures under § 63.8(f)(4). Certainly, a source can apply under this provision that the compliance requirements under Subpart EEE satisfy the associated monitoring requirements under the otherwise applicable 112 and 129 standards.

We also disagree with the commenter that emissions testing under the alternative standards of sections 112 and 129 is an example of an illogical requirement under § 63.1206(b)(1)(ii). Performance testing generally is required to demonstrate compliance with the emission standards and to establish limits on specified operating parameters to ensure compliance is maintained. In order to take advantage of the alternative under § 63.1206(b)(1)(ii), a source needs to show that compliance with and establish operating parameter limits for the otherwise applicable standards of sections 112 and 129. Thus, testing in order to establish operating parameter limits will be necessary. However, this does not mean that a separate performance test with the alternative sections 112 or 129 standards is necessarily required. We note that a source can make use of the performance test waiver provision under § 63.7(h) of the general provisions to request that the performance test under the alternative sections 112 and 129 standards be waived because the source is meeting the relevant standard(s) on a continuous basis by continuing to comply with Subpart EEE for the relevant HAP. This approach may be practicable for sources that can demonstrate that their level of performance during testing under Subpart EEE, including the associated operating and monitoring limits, will undoubtedly ensure continuous compliance with the emissions standards and the associated operating limits of alternative sections 112 and 129 standards.

Finally, the commenter notes that Subpart LLL (the alternative section 112 standards for cement kilns) includes opacity monitoring while Subpart EEE may not. The commenter states that this unnecessarily would require duplicate systems and compliance with redundant limits because of the bag leak detection and particulate matter detection system requirements under Subpart EEE. We respond that Subpart LLL specifies opacity as a standard (see § 63.1343(b)(2)), and, therefore, cement kilns subject to Subpart EEE must comply with the opacity standard when electing to comply temporarily with the requirements of Subpart LLL. We note that the opacity standard under Subpart EEE does not apply to cement kilns that are equipped with a bag leak detection system under § 63.1206(c)(8) and to sources using a particulate matter detection system under § 63.1206(c)(9). However, a cement kiln may use an opacity monitor that meets the detection limit requirements as the detector for a bag leak detection system or particulate matter detection system. See Part Four, Section VIII.A-C of the preamble.

K. Periodic DRE Testing and Limits on Minimum Combustion Chamber Temperature for Cement Kilns

Comment: Several commenters oppose the need for cement kilns that burn at locations other than the normal flame zone to demonstrate compliance with the destruction and removal efficiency (DRE) standard during each comprehensive performance test. These commenters recommend that EPA remove the requirement of § 63.1206(b)(7)(ii) for cement kilns citing that existing rule provisions (i.e., the requirements under § 63.1206(b)(5) pertaining to changes that may adversely affect compliance) are sufficient to require additional DRE testing after changes are made that may adversely affect combustion efficiency. Commenters question EPA's position that cement kilns that burn hazardous waste at locations other than the normal flame zone demonstrate a variability in DRE sufficient to justify the expense of re-testing for DRE with each performance test. Commenters point to EPA's data base that includes DRE results from over 30 tests with nearly 250 runs showing consistent DRE results, including sources burning hazardous waste at locations other than the normal flame zone, being achieved by cement kilns. The commenters note several burdens associated with DRE

[220] However, the operating requirements do not apply during startup, shutdown, or malfunction provided that hazardous waste is not in the combustion chamber. See § 63.1206(b)(1)(i).

testing that do not result in improved environmental benefit including the purchase of expensive exotic virgin chemicals for performance testing, the risks to workers and contractors associated with the handling of these chemicals, and increasing the length of operation at stressful kiln operating conditions necessary to conduct DRE testing at minimum combustion chamber temperatures. Alternatively, commenters recommend that EPA revise the DRE requirements such that periodic testing is no longer required for cement kilns (that burn at locations other than the normal flame zone) after they have successfully achieved the DRE standard over multiple testing cycles (e.g., two or three) under similar testing regimes. That is, the source should only be required to demonstrate compliance with the DRE standard a maximum of two or three times until the source (that burns at locations other than the normal flame zone) modifies the system in a manner that could affect the ability of it to achieve the DRE standard.

Response: We are revising the requirements of § 63.1206(b)(7)(ii) such that cement kilns that feed hazardous waste at locations other than the normal flame zone need only demonstrate compliance with the DRE standard during three consecutive comprehensive performance tests provided that the source has successfully demonstrated compliance with the DRE standard in each test and that the design, operation, and maintenance features of each of the three tests are similar. These revisions do not affect sources that burn hazardous waste only in the normal flame zone.[221]

Prior to today's change, we required sources that feed hazardous waste in locations other than the flame zone to perform periodic DRE testing every 5 years to ensure that the DRE standard continues to be achieved over the life of the unit. See § 63.1206(b)(7)(ii). We justified this requirement because of concerns that sources that feed hazardous waste at locations other than the flame zone have a greater potential of varying DRE performance due to their hazardous waste firing practices. As we stated in the 1999 rule, we were concerned that the DRE may vary over time due to the design and operation of the hazardous waste firing system, and that those variations may not be identical or limited through operating limits set during a single DRE test (similar to what we concluded for sources that burn hazardous waste only in the normal flame zone). See 64 FR at 52850.

Commenters now question the need for subsequent DRE testing at cement kilns that feed hazardous waste at locations other than the normal flame zone once a cement kiln demonstrates compliance with the MACT DRE standard. The regulatory requirement for the destruction and removal efficiency standard has proved to be an effective method to determine appropriate process controls necessary for the combustion of hazardous waste. We are not convinced that only one DRE test is sufficient to ensure that a cement kiln that burns hazardous waste at locations other than the normal flame zone will continue to meet the DRE standard because temperatures are lower and gas residence times are shorter at the other firing locations. This is especially true given the industry trend to convert to the more thermally efficient preheater/precalciner kiln manufacturing process.[222] Precalciner kilns use a secondary firing system (i.e., flash furnace) at the base of the preheater tower to calcine the raw material feed outside the rotary kiln. This results in two separate combustion processes that must be controlled " one in the kiln and the other in the flash furnace. The gas temperature necessary for calcining the limestone raw material in the flash furnace is lower than the temperature required making the clinker product. We conclude, therefore, that it is necessary, in spite of the concerns raised by commenters, to retain periodic DRE testing to ensure continued compliance with the DRE standard necessary for the control of nondioxin/furan organic HAP.

We also acknowledge, however, the concerns raised by the commenters. Our DRE data base of operating cement kilns includes results from approximately 25 DRE tests and nearly 200 runs.[223] All data show compliance with the DRE standard. Of these, approximately one-quarter of the data are from cement kilns that burned hazardous waste at locations other than the normal flame zone (e.g., injecting waste at midkiln in a wet process kiln), but we do not have DRE results from every operating cement kiln. Considering available DRE data and the concerns of the commenters, we believe that DRE testing during three consecutive comprehensive performance tests is sufficient to provide needed certainty about DRE performance while reducing the overall costs and toxic chemical handling concerns to the regulated source. Thus, we are revising the requirements of § 63.1206(b)(7)(ii) such that cement kilns that feed hazardous waste at locations other than the normal flame zone need only demonstrate compliance with the DRE standard during three consecutive comprehensive performance tests provided that the source has successfully demonstrated compliance with the DRE standard in each test and that the design, operation, and maintenance features of each of the three tests are similar. If a facility wishes to operate under new operating parameter limits that could be expected to affect the ability to meet the DRE standard, then the source would need to conduct another DRE test. Once the facility has conducted another three DRE tests under the new operating limits, then subsequent DRE testing would not be required. Accordingly, we are revising the requirements of § 63.1206(b)(7)(ii).

Comment: Several commenters support EPA's proposal to delete the requirement to establish an operating limit on the minimum combustion chamber temperature for dioxin/furans under § 63.1209(k)(1) for cement kilns. These commenters point to the high temperatures of approximately 2500°F required to make the clinker product. These high temperatures are fixed by the reaction kinetics and thermodynamics occurring in the burning zone and cannot be reduced below minimum values at the whim of the operator and still make a marketable product. In addition to deleting the minimum combustion chamber temperature limit for dioxin/furans, commenters also recommend, for similar reasons, that EPA delete the minimum combustion chamber temperature requirement under § 63.1209(j)(1) associated with the destruction and removal efficiency standand. Commenters note that demonstrating the minimum temperature requires operating under stressful operating conditions that can

[221] The DRE demonstration for these sources need be made only once during the operational life of a source, either before or during the initial comprehensive performance test, provided that the design, operation, or maintenance features do not change in a manner that could reasonably be expected to affect the ability to meet the DRE standard. See §§ 63.1206(b)(7) and 63.1207(c)(2)(ii). The source would ensure continued compliance by operating under the operating parameter limits established during this DRE test.

[222] For example, Ash Grove Cement in Chanute, KS replaced their two wet process cement kilns with one preheater/precalciner kiln in 2001. Holcim Inc in Holly Hill, SC has also recently constructed a new preheater/precalciner kiln to replace two wet process cement kilns. Keystone Cement Company in Bath, PA is considering replacing their two wet process cement kilns with a new preheater/precalciner kiln. See docket item OAR–2004–0022–0384.

[223] U.S. EPA, "Final Technical Support Document for HWC MACT Standards, Volume III: Selection of MACT Standards and Technologies," Section 23.4, September 2005.

lead to upset conditions and potentially damage the integrity of the manufacturing equipment. Other commenters oppose, however, deletion of the minimum combustion chamber temperature limit for cement kilns. These commenters state that all combustion sources, including cement kilns, must meet a minimum combustion chamber temperature limit to control dioxin/furans and organic HAP emissions given that some cement kilns feed hazardous waste at locations other than the high temperature clinker-forming zone of the kiln.

Response: We are deleting as proposed the requirement to establish a minimum combustion chamber temperature limit for dioxin/furan under § 63.1209(k)(2) for cement kilns. See 69 FR at 21343. However, we retain the requirement for cement kilns to establish and comply with a minimum combustion chamber temperature limit for the destruction and removal efficiency standard under § 63.1209(j)(1).[224]

As discussed in the 1999 rule, nondioxin/furan organic hazardous air pollutants are controlled by the DRE standard and the carbon monoxide and hydrocarbon standards. See 64 FR at 52848–52852. This standard was not reopened in the present rulemaking. We note, however, that the DRE standard determines appropriate process controls necessary for the combustion of hazardous waste. Establishing and monitoring a minimum temperature of the combustion chamber is a principal factor in ensuring combustion efficiency and destruction of toxic organic compounds. As discussed in the previous response, we believe this is especially true given the industry trend to convert to the more thermally efficient preheater/precalciner kiln manufacturing process, which use two separate combustion processes. We conclude that it is necessary, in spite of the concerns raised by commenters, to retain the minimum combustion chamber temperature limit as related to the DRE standard to ensure that combustion efficiency within the entire kiln system is maintained for the control of nondioxin/furan organic HAP.

However, we acknowledge the difficulties that cement kiln operators face in establishing a minimum combustion chamber temperature limit, including the stressful operating conditions necessary to establish the limit. As we stated at proposal, our data indicate that limiting the gas temperature at the inlet to the particulate matter control device is a critical parameter in controlling dioxin/furan emissions in cement kilns. See 69 FR at 21344. Therefore, we believe that an operating limit on the minimum combustion chamber temperature is less important to ensure compliance with the dioxin/furan standard than to ensure compliance with the DRE standard. Thus, we remove the requirement to establish a minimum combustion chamber temperature limit for dioxin/furan under § 63.1209(k)(2) for cement kilns. This change does not affect the other operating parameter limits under § 63.1209(k) that must be established for dioxin/furans, including a limit on the gas temperature at the inlet to the particulate matter control device.

Comment: One commenter supports the use of previous minimum combustion zone temperature data, regardless of the test age, in lieu of conducting new, stressful DRE testing. That is, if a cement kiln is required to conduct future DRE tests, then the source should not have to re-establish a minimum combustion chamber temperature limit during the new test. Rather, the source should have the option to submit minimum combustion chamber temperature results in lieu of re-establishing the limit.

Response: We reject the commenter's suggestion for reasons discussed above. We believe that it is necessary to retain the link between the minimum combustion chamber temperature limit and the DRE test itself, which will ensure that the combustion efficiency of the entire system will be maintained for the control of nondioxin/furan organic HAP.

Comment: One commenter supports deletion of the minimum combustion chamber temperature requirement for dioxin/furan under § 63.1209(k)(2) for lightweight aggregate kilns.

Response: We reject the commenter's suggestion. Our data base of dioxin/furan emissions data shows substantial variability in test results at each source.[225] This may indicate that factors other than limiting kiln exit gas temperatures may be influencing significantly dioxin/furan formation in lightweight aggregate kilns. As such, we conclude that removing the minimum combustion chamber temperature limit would not be appropriate at this time due to the uncertain nature of dioxin/furan formation in lightweight aggregate kilns. Thus, we are retaining the requirement to establish a minimum combustion chamber temperature limit for dioxin/furans under § 63.1209(k)(2) and § 63.1209(j)(1) for lightweight aggregate kilns.

L. One Time Dioxin and Furan Test for Sources Not Subject to a Numerical Limit for Dioxin and Furan

Comment. Commenters support the one-time dioxin/furan test for sources not subject to a numerical dioxin and furan standard. Commenters agree that previous testing should be allowed to document the one time test.

Response. The final rule requires sources that are not subject to a standard with numerical dioxin and furan levels[226] to conduct a one-time dioxin and furan test as part of their initial comprehensive performance testing: lightweight aggregate kilns that elect to control the gas temperature at the kiln exit rather than comply with a dioxin/furan standard of 0.20 ng TEQ/dscm, solid fuel boilers, liquid fuel boilers with wet or no air pollution control systems, and HCl production furnaces. We will use these data as part of the process of addressing residual risk under CAA section 112(f) and evaluating future MACT standards under section 112(d)(6). The results may also be used as part of the RCRA omnibus permitting process.

Comment. EPA proposed that source not subject to a numerical dioxin and furan limit conduct a dioxin and furan test under worst-case conditions. Commenters state that operating under worst-case conditions is inconsistent with the CAA Section 112(f) process, which is to consider actual (i.e., normal) emissions. Commenters suggest that we require the tests be conducted under normal to above normal conditions.

Response. Section 112 (f) standards evaluate allowable emission levels, although actual emissions levels may also be considered. See 70 FR at 19998–

[224] Under the interim standards, cement kilns must establish and continuously monitor limits on minimum gas temperature in the combustion zone for both the dioxin/furan and DRE standards. As discussed in the preceding paragraph, a source may not need to conduct DRE testing during each comprehensive performance test. If DRE testing is required, then the source will need to establish a minimum combustion zone temperature limit as required under the DRE standard. However, if DRE testing is not required, then (according to the changes made today) the cement kiln will not be required to establish the minimum combustion chamber temperature limit under the dioxin/furan standard during a subsequent comprehensive performance test. The minimum combustion chamber temperature operating limit established during previous testing remains in effect, however.

[225] For example, dioxin/furan emissions from source number 307 range from a low of 0.024 to a high of 57.9 ng TEQ/dscm. See "Source Category Summary Sheets" available in the docket or USEPA, "Final Technical Support Document for HWC MACT Standards, Volume II: HWC Data Base," September 2005.

[226] These sources do, however, need to comply with the carbon monoxide or hydrocarbon standards, as well as the DRE standard as surrogates to comply with today's dioxin and furan emissions control requirements.

19999 (April 15, 2005). Although we agree with the commenter that, in general, emissions in the range of normal to maximum are considered for section 112(f) determinations, we believe that dioxin/furan testing to provide information of use in section 112(f) residual risk determinations should be conducted under conditions where controllable operating conditions are maximized to reflect the full range of expected variability of those parameters which can be controlled. This is because dioxin/furan emissions may relate exponentially with the operating conditions that affect formation. We believe that dioxin/furan emissions relate exponentially with gas temperature at the inlet to an ESP or fabric filter,[227] and are concerned that emissions may also relate exponentially with the operating parameters (discussed below) that affect emissions from sources subject to the one-time dioxin/furan emissions test. Emissions testing under operating conditions that are in the range of "normal to above normal" may be exponentially lower than emissions under operating conditions reflecting maximum daily variability of the source. Since testing under normal operating conditions makes no effort to assess operating variability, emissions during such testing would fail to reflect expected daily maximum operating variability and so would not represent time-weighted average emissions and would under-represent health risk from chronic exposure.

Although we acknowledge that sources will not exhibit maximum operating variability each day of operation, we believe that it is important to assess the upper range of emissions that these sources may emit to properly evaluate under section 112(f) whether the MACT standards for dioxin/furan for these sources (i.e., absent a numerical emission standard) protect public health with an ample margin of safety.[228]

In addition, we note that emissions reflecting daily maximum variability would be most useful for section 112(d)(6) determinations in the future because they would represent the full range of emissions variability that results from controllable operating conditions.

For these reasons, the final rule requires sources to test under feed and operating conditions that are most likely to reflect maximized expected daily variability of dioxin/furan emissions, as proposed. Such testing is similar to a comprehensive performance test to demonstrate compliance with a numerical dioxin/furan emission standard where operating limits would be established based on operations during the test. As a practical matter, however, we note that many of the operating parameters discussed below, although controllable to some extent, cannot be quantified and cannot be controlled to replicate the condition in a future test. In addition, some operating parameters we identify may not have as strong a relationship to dioxin/furan emissions as others. Consequently, the operating conditions are generally described subjectively.

Based on currently available research, you should consider the following factors to ensure that you conduct the test under operating conditions that seek to fully reflect maximum daily variability of dioxin/furan emissions: (1) Dioxin/furan testing should be conducted at the point in the maintenance cycle for a boiler when the boiler tubes are more fouled and soot-laden, and not after maintenance involving soot or ash removal from the tubes; (2) dioxin/furan testing should be performed following (or during) a period of feeding normal or greater quantities of metals; (3) dioxin/furan testing should be performed while feeding normal or greater quantities of chlorine; (4) the flue gas temperature in some portion of the heat recovery section of a boiler should be within the dioxin formation temperature window of 750 to 400°F during the testing; (5) the testing should not be conducted under optimal combustion conditions (e.g., combustion chamber temperature should be in the range of normal to the operating limit; hazardous waste feedrate and combustor through put should be in the range of normal to maximum); (6) for units equipped with wet air pollution control systems, the testing should be conducted after a high solids loading has developed in the scrubber system (consistent with normal operating cycles); and (7) for solid fuel boilers, the sulfur content of the coal should be equivalent to or lower than normal coal sulfur levels (within the range of sulfur levels that the source utilizes), and the gas temperature at the inlet to the electrostatic precipitator or fabric filter should be close to the operating limit. In addition, unless sulfur compounds are routinely fed to the boler, dioxin/furan testing should not be performed after a period of firing high sulfur fuel or injection of sulfur additives. See 69 FR at 21308 for more information.

Comment: Commenters state that we should delete the one-time testing requirement for dioxin and furans. The Clean Air Act at Section 114(a)(1)(D) allows EPA to request "any person" to sample emissions. Applying the Section 114 authority to an entire subcategory of sources is overly broad, particularly in the context of having already established appropriate surrogates for dioxin and furan in a MACT rule. Commenters are not aware of EPA taking this approach in previous efforts. (Section 114 requests have focused on collecting existing information from sources facing future MACT standards). Commenters oppose this approach because it established a precedent they do not favor, and will bring about significant costs and difficulties to provide the data. They suggest that we delete the proposed requirements for a one-time dioxin and furan test.

Response: We believe that section 114(a)(1)(D) of the Clean Air Act provides us the authority to require sources to conduct a one time test to generate data which can be used in making later section 112 (f) determinations for the source category. The results of the testing may also inform the section 112(d)(6) review and the RCRA omnibus permitting processes. The fact that section 114 specifically indicates that a purpose of gathering information under section 114 is to assist in developing national rules indicates that the provision can have wide sweep extending to all sources in a category. See 69 FR at 21307–308 for a full explanation.

We believe a dioxin and furan test costs approximately $10,000 when conducted along with other testing. We do not believe this cost is significant, and sources must only perform this test once, not more frequently as would be the case to ensure compliance with a standard. We also allow sources to use prior testing to meet this requirement, and allow sources to use "data in lieu" so they can test one source if they have more than one of the same identical sources.

We do not believe that obtaining these data will be difficult, and note that the permitting authority can assist sources in planning their tests.

M. Miscellaneous Compliance Issues

Comment: Several commenters state that § 63.1206(c)(3)(iv) requiring an automatic waste feed cutoff (AWFCO) if

[227] See USEPA, "Technical Support Document for HWC MACT Standards, Volume IV: Compliance," July 1999, Chapter 3.

[228] Dioxin/furan are some of the most toxic compounds known due to their bioaccumulation potential and wide range of health effects, including carcinogenesis, at exceedingly low doses. Exposure via indirect pathways is a chief reason that Congress singled out dioxin/furan for priority MACT control in CAA section 112(c)(6). See S. Rep. No. 128, 101st Cong. 1st Sess. at 154–155.

a parameter linked to the AWFCO is exceeded should be revised to reflect § 63.1206(c)(2)(v)(A)(1). Section 63.1206(c)(2)(v)(A)(1) states that, if the AWFCO is affected by a malfunction such that the malfunction itself prevents immediate and automatic cutoff of the hazardous waste feed, you must cease feeding hazardous waste as quickly as possible.

Response: We agree with commenters in principle, but note that the automatic waste feed cutoff system may fail for reasons other than a malfunction. That is, equipment or other failures are malfunctions only if they meet the definition of malfunction at § 63.2. Failures that result from improper maintenance or operation are not malfunctions. Consequently, the final rule revises § 63.1206(c)(3)(iv) to state that if the AWFCO is affected by a failure such that the failure itself prevents immediate and automatic cutoff of the hazardous waste feed, you must cease feeding hazardous waste as quickly as possible. Revised § 63.1206(c)(3)(iv) does not refer to malfunctions, however, because the AWFCO system may fail for reasons other than a malfunction. The reference in § 63.1206(c)(2)(v)(A)(1) to malfunctions is appropriate because that paragraph addresses requirements during malfunctions.

Comment: Several commenters note that the proposed rule did not include a sunset provision for the Interim Standards applicable to incinerators, cement kilns, and lightweight aggregate kilns after the compliance date of the standards we promulgate today (i.e., the "permanent replacement standards"). Commenters are concerned that, although the Agency intends for the replacement standards to be more stringent than the Interim Standards, that may not be the case in all situations because of the different format used for some of the replacement standards. For example, several of the replacement standards for cement kilns and lightweight aggregate kilns are expressed as hazardous waste thermal emissions.

Response: Although we are promulgating the replacement standards in a format that ensures they are not less stringent than the Interim Standards, we agree with commenters that not sunsetting the Interim Standards may lead to confusion as to which standards apply. Consequently, we include a sunset provision in today's rule for the Interim Standards. The Interim Standards will be superseded by the final rule promulgated today on the compliance date.

We note, however, that the Interim Standards for total chlorine continue to apply to sources that establish health-based limits for total chlorine under § 63.1215. Consequently, we have incorporated the total chlorine Interim Standards in § 63.1215 as they apply as a cap to the health-based emission limits.

Comment: Several commenters state that the rule should allow extrapolation of ash and chlorine feedrates to establish feedrate limits corresponding to the particulate matter and total chlorine standards. Commenters believe the rationale we use to allow extrapolation of metals feedrates is also applicable to ash and chlorine.

Response: The final rule does not allow you to extrapolate ash and chlorine feedrates achieved during the comprehensive performance test to establish feedrate limits comparable to the particulate matter and total chlorine emission standards.

We do not allow extrapolation of ash to the particulate matter emission standard because particulate matter (i.e., soot) may form in the combustor, particularly at times of unstable combustion conditions. Consequently, extrapolating from ash feedrates may underestimate particulate matter emissions and may not ensure compliance with the particulate matter emission standard.

We do not allow extrapolation of chlorine feedrates to the total chlorine emission standard because chlorine feedrate is an operating parameter limit to ensure compliance with the semivolatile metal emission standard. Because an increase in chlorine feedrate can increase the volatility of semivolatile metals and we do not know the precise relationship among chlorine feedrate, metal volatility, and metals emissions, extrapolating the chlorine feedrate achieved during the comprehensive performance test to a feedrate comparable to the total chlorine emission standard may not ensure compliance with the semivolatile metal emission standard. If a source complies with the semivolatile metals emission standard under § 63.1207(m)(2) where the performance test is waived, however, by assuming zero system removal efficiency and limiting the semivolatile feedrate (expressed as a maximum theoretical emission concentration) to the level of the emission standard, the source may request under § 63.1209(g)(1) to extrapolate chlorine feedrates during the comprehensive performance test up to the total chlorine emission standard.

Comment: Several commenters state that the proposed regulatory language under §§ 63.1206(b)(9)(i) and 63.1206(b)(10)(i) is inconsistent with the proposed preamble, which states that sources should be allowed to petition for alternative standards provided they submit information showing that HAP contributions to emissions from the raw materials are preventing the source from achieving the emissions standard though the source is using MACT control.[229] The commenters state that the proposed regulatory language, despite the intent signaled in the proposed preamble, inappropriately excludes the provisions of §§ 63.1206(b)(9)(i) and 63.1206(b)(10)(i) as an alternative option when complying with the replacement emission standards under §§ 63.1220 and 63.1221.

Response: We agree with the commenters. The proposed regulatory text inadvertently excluded the alternative standard provisions from use by cement and lightweight aggregate kilns under the replacement standards. Accordingly, we are revising the introductory text of §§ 63.1206(b)(9)(i) and 63.1206(b)(10)(i) by making the alternative standards available under the replacement standards.

Comment: One commenter states that the availability of the alternative standard for mercury under § 63.1206(b)(10)(i) should not be conditioned upon mercury being present only at levels below the detection limit in raw materials, as specified under § 63.1206(b)(10)(i)(B). The commenter suggests that the approach for mercury should be the same as for other HAP such as semi- and low volatile metals under § 63.1206(b)(10)(i)(A).

Response: The commenter misreads the alternative standard provisions under § 63.1206(b)(10)(i). We note that § 63.1206(b)(10) includes two separate provisions for cement kilns. The first provision allows sources to petition for an alternative standard when a source cannot achieve a standard because of HAP metal or chlorine concentrations in their raw material feedstocks cause an exceedance of a standard despite the source's use of MACT control. See § 63.1206(b)(10)(i)(A). The term "regulated metals" specified in § 63.1206(b)(10)(i)(A) includes mercury, semivolatile metals, and low volatile metals. The second provision allows a source to petition for an alternative mercury standard when mercury is not present at detectable levels in the source's raw materials. § 63.1206(b)(10)(i)(B). These two provisions are indeed separate as

[229] For example, see 69 FR at 21268.

discussed in the 1999 rule. See 64 FR at 52962–967. Also note that the conjunction separating paragraphs (b)(10)(i)(A) and (b)(10)(i)(B) is "or," not "and."

Given the potential confusion of the term "regulated metals," we are clarifying the regulatory text by specifying the three metal HAP volatility groups that comprise the term "regulated metals." See revised § 63.1206(b)(10)(i)(A). Finally, given that the alternative standard provisions are similar for lightweight aggregate kilns, we are also clarifying §§ 63.1206(b)(9)(i)(A) and (b)(9)(iv).

IX. Site-Specific Risk Assessment Under RCRA

A. What Is the Site-Specific Risk Assessment Policy?

The Site-Specific Risk Assessment (SSRA) Policy has undergone several revisions since its inception in the 1993 draft Combustion Strategy. Currently, it is the same policy as we expressed in the 1999 final rule preamble. In the 1999 rule, we recommended that for hazardous waste combustors subject to the Phase 1 MACT standards, permitting authorities should evaluate the need for an SSRA on a case-by-case basis. Further, while SSRAs are not anticipated to be necessary for every facility, they should be conducted where there is some reason to believe that operation in accordance with the MACT standards alone may not be protective of human health and the environment. For hazardous waste combustors not subject to the Phase 1 standards, we continued to recommend that SSRAs be conducted as part of the RCRA permitting process. See 64 FR 52841. Since 1999, we have provided additional clarification of the appropriate use of the SSRA policy and technical guidance in an April 10, 2003 memorandum from OSWER's Assistant Administrator to the EPA Regional Administrators entitled, "Use of the Site-Specific Risk Assessment Policy and Guidance for Hazardous Waste Combustion Facilities" (see Docket # OAR–2004–0022–0083). Most importantly, in this memorandum we reiterated that where a permitting authority concludes that a risk assessment is necessary for a particular combustor, the basis for this decision must be substantiated in each case. The factual and technical basis for any decisions to conduct a risk assessment must be included in the administrative record for the facility per 40 CFR 124.7, 124.8, 124.9, and 124.18. In addition, if the facility, or any other party, files comments on a draft permit decision objecting to the permitting authority's conclusions regarding the need for a risk assessment, the permitting authority must respond fully to the comments. Any permit conditions determined to be necessary based either on the SSRA, or because the facility declined to conduct an SSRA, also must be documented and supported in the administrative record.

Today, we are codifying additional regulatory language providing authority for SSRAs while maintaining the same basic SSRA policy. It is important to note that all of the requirements of Part 124 referred to above will continue to apply to actions taken in accordance with the additional regulatory language we are codifying. The SSRA regulatory provisions, which establish that the need for an SSRA should be determined on a case-by-case basis, apply equally to both Phase 1 and Phase 2 sources.

B. Why Might SSRAs Continue To Be Necessary for Sources Complying With Phase 1 Replacement Standards and Phase 2 Standards?

EPA conducted a national evaluation of human health and ecological risk for the MACT standards as proposed in the 1996 NPRM and then revised the evaluation to include more facilities for the 1999 final rulemaking. Based on the results of the final national risk evaluation for hazardous air pollutants (excluding non-dioxin products of incomplete combustion), we concluded that sources complying with the MACT standards generally would not pose an unacceptable risk to human health or the environment. For today's final rule, we did not conduct another national risk assessment as we did for the 1999 rule. Rather, for both the April 20, 2004 NPRM and today's final rule we conducted a comparative risk analysis, comparing the Phase 1 Replacement and Phase 2 Standards to the 1999-promulgated Phase 1 Standards, to determine if there were any significant differences that might influence or impact the potential risk. Similar to the proposal, the comparative analysis conducted for today's final rule focused on several key characteristics: emission rates, stack height, stack gas buoyancy, meteorological conditions (which include a number of variables), population parameters including density and radial distribution, and correlations among the characteristics themselves. The results of the comparative analysis suggest that the MACT standards for both Phase 1 and Phase 2 sources are generally protective. Therefore, separate national emissions standards under RCRA are unnecessary. See Part Seven: How Does the Final Rule Meet the RCRA Protectiveness Mandate? Although we have concluded that the Phase 1 Replacement and Phase 2 standards are generally protective, as we discussed in the 2004 proposal (69 FR 21325), there may be instances where we cannot assure that emissions from each source will be protective of human health and the environment, and therefore an SSRA may be necessary. Furthermore, it should be noted that, just as for the risk assessment for the 1999 rule, the comparative analysis does not account for cumulative emissions at a source or background exposures from other sources.

Before discussing factors that may lead permit authorities to consider whether or not to conduct an SSRA, it should be noted that the Agency generally does not expect that facilities that have conducted risk assessments will have to repeat them. As we explained in the 1999 final rule preamble, changes to comply with the MACT standards should not cause an increase in risk for the vast majority of facilities given that the changes will likely be the addition of pollution control equipment or a reduction in the hazardous waste being burned (see 64 FR 52842). Instances where a facility may need to repeat a risk assessment would be related to changes in conditions that would likely lead to increased risk. For example, if the only changes at a facility relate to the exposed population (a new housing development is constructed within a few square miles of the source), what was once determined to be protective under a previous risk assessment may now be beyond acceptable levels. Another example would be where a hazardous waste burning cement kiln that previously monitored hydrocarbons in the main stack elects to install a mid-kiln sampling port for carbon monoxide or hydrocarbon monitoring to avoid restrictions on hydrocarbon levels in the main stack. Thus, the stack hydrocarbon emissions may increase (64 FR 52843, footnote 29). In such situations, we would anticipate that the risk assessment would not have to be entirely redone. It may be as limited as collecting relevant new data for comparison purposes, leading to a decision not to repeat any portion of a risk assessment. Or, it may be more inclusive such that modifications would be made to specific inputs to or aspects of the risk assessment using data from a previous risk assessment, risk burn or comprehensive performance test. In recognition of this, we have added an additional factor to the list of factors at § 270.10(l)(1) to indicate that a previously conducted risk assessment

would be relevant in evaluating changes in conditions that may lead to increased risk. The factor reads as follows: "Adequacy of any previously conducted risk assessment, given any subsequent changes in conditions likely to affect risk." The following discussion is intended mainly to address facilities that have not yet conducted an SSRA (i.e., where it has been determined that one is needed).

In the proposal we discussed our conclusion that almost all of the proposed standards for Phase 1 sources were equivalent to or more stringent than the 1999 final standards, with the exception of the mercury standard for new and existing LWAKs and the total chlorine standard for new LWAKs. However, there are additional standards for Phase 1 sources finalized in today's rulemaking that are less stringent than the 1999 final standards. In addition to those discussed in the proposal, the following standards are less stringent than the 1999 final standards: mercury for new cement kilns and semi-volatile metals for existing cement kilns; dioxin/furan for existing and new LWAKs, mercury for existing and new LWAKs, and total chlorine for existing and new LWAKs. Because these standards exceed the levels which were evaluated in the 1999 national risk assessment, especially with respect to mercury and dioxin/furan standards for which the national risk assessment showed high end risks at or near levels of concern, permit authorities may decide on a case-by-case basis that an SSRA is appropriate to determine whether the less stringent Replacement standards are protective. In addition, the comparative analysis results suggest concern regarding the dioxin/furan standard for LWAKs and thus, permit authorities may consider site-specific factors in determining whether the standard is sufficiently protective.

Specific to Phase 2 sources, we mentioned earlier that we conducted the same comparative risk analysis for Phase 2 sources as we did for Phase 1 sources (i.e., by comparing the Phase 2 standards to the 1999 final standards for Phase 1 sources). Although several MACT standards for Phase 2 sources are more stringent than the BIF standards under RCRA, there are a few MACT standards that may be cause for concern on a case-by-case basis, as they are either less stringent than some of the 1999 final standards or the comparative risk analysis suggests concern. They are: The particulate matter standard (and certain metals such as antimony and thallium), mercury standard, and total chlorine standard for solid fuel-fired boilers (SFBs); the dioxin/furan standard (carbon monoxide or total hydrocarbon as surrogate controls, versus a numerical standard) for HCl production furnaces; and the dioxin/furan standard for liquid fuel-fired boilers (LFBs) with dry APCDs. In addition, dioxin/furan emissions data for LFBs with wet or no APCDs indicate : an observed level (1.4 ng TEQ/dscm) of more than three times the highest dioxin/furan standard evaluated in the 1999 national risk assessment (69 FR 21285).[230] Thus, these standards may warrant site-specific risk consideration, especially with respect to the dioxin/furan standards. That is, due to the complexity of the dioxin/furan formation mechanism and given the toxicity of dioxin/furans,[231] an SSRA may be needed based on the specific emission levels of each source not subject to a numerical standard. For additional discussion on the protectiveness of standards, please refer to Part Seven: How Does the Final Rule Meet the RCRA Protectiveness Mandate?

There are also site-specific factors beyond the standards that can be important to the SSRA decision making process. As discussed in the proposal, examples include a source's proximity to a water body or endangered species habitat, repeated occurrences of contaminant advisories for nearby water bodies, the number of hazardous air pollutant emission sources within a facility and the surrounding community, whether or not the waste feed to the combustor is made up of persistent, bioaccumulative or toxic contaminants, and sensitive receptors with potentially significantly different exposure pathways, such as Native Americans (69 FR 21326). Also, there are several uncertainties inherent in the 1999 national risk assessment.[232] Thus, the same uncertainties related to the fate and transport of mercury in the environment and the biological significance of mercury exposures in fish (i.e., once mercury has been transformed into methylmercury, it can be ingested by the lower trophic level organisms where it can bioaccumulate in fish tissue), as well as the risk posed by non-dioxin products of incomplete combustion, remain today and may influence a permitting authority's decision. Last, we are finalizing the option for Phase 2 area sources to comply with specific MACT standards as provided by CAA §112(c)(6) specific pollutants authority. These area sources may need to conduct an SSRA for the remaining RCRA standards that they choose to comply with (i.e., since they do not address the potential risk from indirect exposures to long-term deposition of metals onto soils and surface waters).[233]

In addition to the examples provided in the previous paragraph, we also expressed that an SSRA may be necessary with respect to the proposed thermal emission standards. With respect to Phase 1 sources, we had noted in the proposal that the thermal emission standards for semi-volatile and low volatile metals for cement kilns and LWAKs may be of concern because they directly address emissions attributable to hazardous waste versus a source's total HAP metal emissions. See 69 FR 21326. However, we are requiring sources to comply with both the thermal emission standards and the Interim Standards in today's final rulemaking, since compliance with the thermal emission standards may not always assure compliance with the Interim Standards. As a result, the thermal emission standards for cement kilns and LWAKs no longer pose the uncertainties that they had in the proposal.[234] In regard to Phase 2 sources, the concern at the time of proposal was with respect to the thermal emission standards for liquid fuel-fired boilers. However, the comparative analysis for today's final rulemaking for liquid fuel-fired boilers, which is based on total stack emissions from these sources while assuming compliance with the thermal standards, does not suggest that risks for LFBs are cause for concern (except as otherwise noted, e.g., dioxins).

C. What Changes Are EPA Finalizing With Respect to the Site-Specific Risk Assessment Policy?

In the 1999 final rule preamble, we included a revised site-specific risk assessment (SSRA) policy recommendation to account for promulgation of the new technology-based CAA MACT standards for Phase

[230] The comparative analysis did not specifically suggest concern as it has for other source categories, but per the reference to the proposal, we have some concern regarding the protectiveness of the standard.

[231] There is ongoing uncertainty in cancer and other health effects levels for chlorinated dioxins and furans.

[232] Uncertainties stem from a lack of information regarding the behavior of mercury in the environment and a lack of sufficient emissions data and parameter values (e.g., bioaccumulation values) for nondioxin products of incomplete combustion. See 64 FR 52840–52841.

[233] Currently, there are only five area sources that this may apply to; they are interim status units in the process of conducting an SSRA as part of their final permits.

[234] An exception would be the semivolatile metal Interim standard for existing cement kilns, which is less stringent than the 1999 final standard. As we noted, permit authorities may consider the need for an SSRA as a result.

1 sources. We recommended that permitting authorities evaluate the need for an SSRA on a case-by-case basis for hazardous waste combustors subject to the Phase 1 MACT standards. For hazardous waste combustors not subject to the Phase 1 standards, we continued to recommend that SSRAs be conducted as part of the RCRA permitting process if necessary to protect human health and the environment. We indicated that the RCRA omnibus provision authorized permit authorities to require applicants to submit SSRA results where an SSRA was determined to be necessary. For the reasons described in the previous subsection, we believe that additional controls may be necessary on a site-specific basis to ensure that adequate protection is achieved in accordance with RCRA.

Consequently, because SSRAs are likely to continue to be necessary at some facilities (mainly those that have not previously conducted an SSRA), we concluded that it is more appropriate to include a regulatory provision that explicitly provides for the permit authority to require SSRAs on a case-by-case basis and add conditions to RCRA permits based on SSRA results. Therefore, instead of relying on RCRA § 3005(c)(3) and its associated regulations at § 270.10(k) when permitting authorities conduct or require a risk assessment on a site-specific basis (i.e., as applicable to those newly entering the RCRA permit process), we had proposed to codify the authorities provided by sections 3004(a) and (q) and 3005(b). See proposed regulations at 69 FR 21383–21384, §§ 270.10(l) and 270.32(b)(3). In proposing to codify these authorities, we stated that we were not requiring that SSRAs automatically be conducted for hazardous waste combustion units, but that the decision of whether or not a risk assessment is necessary must be made based upon relevant factors associated with an individual combustion unit and that there are combustion units for which an SSRA will not be necessary. Further, we explained that the proposed language would provide notice to the regulated community that an SSRA may be necessary to support a source's permit, while reminding the permit agency of the need to evaluate whether an SSRA would be necessary on a site-specific basis.

Despite our efforts to explain that by codifying these provisions, we are only modifying the statutory authority under which we implement the SSRA policy while maintaining the same SSRA policy from a substantive standpoint, commenters generally opposed EPA's proposed codification. The comment most frequently presented was that the proposed regulatory language is not helpful to anyone (i.e., regulated community, the public or permitting agencies), is redundant with the omnibus authority, and sets an extremely low hurdle for regulators to require SSRAs.

We disagree that the new regulatory language is not helpful and that it sets an extremely low hurdle for regulators to require SSRAs. We believe that the new provisions are beneficial in two ways: (1) They provide notice to the regulated community and public that an SSRA may be necessary to support a source's permit; and (2) they remind the permitting agencies of the importance of evaluating whether an SSRA would be necessary on a site-specific basis. The new regulatory provision in no way expands or supplements the authority on which EPA had previously relied—i.e., omnibus and § 270.10(k), thus it does not provide any more or less authority to permit authorities (i.e., lower or raise the hurdle) to require SSRAs. We agree that, because the proposed language provides permitting authorities with no greater authority than the omnibus authority, it is somewhat duplicative of § 270.10(k). However, as noted, EPA believes this provision offers important benefits to both the agency and the regulated community, and as explained further below, EPA has adopted a slightly modified version of the proposal pursuant to RCRA § 3004(a) and § 3005(b). See also discussion in subsection F.

Another common view expressed by commenters is that, although extensive risk assessments that have been performed for more than a decade, showing lack of risk to human health and the environment, EPA continues to require SSRAs without a technical evaluation of the historical results. To the contrary, EPA Regional permit writers have found that certain chemicals (especially dioxin and mercury)[235] pose excess risk in certain circumstances—even under the Interim Standards—and consequently find it necessary to assess risk to human health and the environment based on site-specific conditions at the facility. In EPA Regions 7 and 10 for example, some facilities have RCRA risk-based permit conditions that establish more frequent sampling or limits on feed rate for specified metals to ensure that ecologically sensitive areas are not adversely impacted.

Many commenters also state that CAA § 112(f) residual risk process is the appropriate method to assess risk for hazardous waste combustors complying with MACT, not RCRA risk assessments. Specifically, one commenter argued that EPA lacked statutory authority to rely on the omnibus provisions to require SSRA and SSRA-based controls on the grounds that § 112(f) of the Clean Air Act establishes a specific provision to control any residual risk from combustor emissions. We disagree with commenters for two reasons. First, as we explained in the 1999 final rule preamble, the omnibus provision is a RCRA statutory requirement and the CAA does not override RCRA. Promulgation of the MACT standards, therefore, does not duplicate, supersede, or otherwise modify the omnibus provision or its applicability to the sources covered by today's rule. Second, the SSRA under RCRA is usually conducted prior to issuance of the final permit. The CAA residual risk determination is generally made eight years after promulgation of the MACT standards for a source category. Accordingly, a permit authority currently facing a permit decision could not rely on these yet unwritten residual risk standards to resolve its identified concern that the MACT standard may not be sufficiently protective at an individual site. In addition, even though we believe that § 3005(c)(3) and its associated regulations provide the authority to require and perform SSRAs and to write permit conditions based on SSRA results, we are not relying on these provisions as the authority for § 270.10(l). Rather, we are relying on §§ 3004(a) and (q) and 3005(b). See 69 FR 21327.

With respect to the costs incurred when conducting an SSRA, several commenters raised the concern that our approximations do not include portions of actual costs (e.g., data gathering, QA/QC, and third party consultants, risk assessors, and plant personnel time to coordinate and review SSRA efforts and collect facility data), thus resulting in artificially low costs. Commenters cited additional reasons why they feel that EPA's cost estimates are too low including our assumptions that: (1) SSRAs are a one-time or infrequent cost; (2) most SSRAs fall under "normal" versus "unusual" situations; and (3) the cost of conducting a risk burn during a

[235] Dioxin is a common risk driver due to ongoing uncertainty in cancer and other health effects levels for chlorinated dioxins and furans. Mercury is also a common risk driver due to uncertainties implicit in the quantitative mercury analysis. See discussion in Part Seven, Section II. and 65 FR 52997. Thus, it is not uncommon for permit authorities to require risk-based RCRA permit limits (based on risk assessment results) to control emissions of these pollutants.

trial burn adds only 20% more to the cost.

Regarding the comment that we did not include actual costs for our estimates of overall costs to conduct an SSRA, we agree that some costs were overlooked. We did include the costs related to conducting an SSRA under "normal" and "unusual" conditions, SSRA data collection in conjunction with a regular performance burn, and a full independent risk burn including protocol, sampling, analysis, and report. However, we did not capture facility time associated with data collection and management related to the SSRA. Consequently, we have revised our cost estimate for performing these activities; see chapter 4 of the background document entitled, Assessment of the Potential Costs, Benefits, and Other Impacts of the Hazardous Waste Combustion MACT Replacement Standards—Final Rule, October 12, 2005.

In response to the broader comment that our cost estimates are too low (for several reasons mentioned previously), we agree that our estimate of a 20% additional cost to conduct a risk burn with a trial burn may have been conservative and therefore, we have adjusted our previous estimate to include a range of 20% to 40%. The total SSRA cost range has also been updated from $141K–$370K to $157K–$815K.[236] With respect to our assumption that the majority of SSRAs are conducted under "normal" conditions (lending to overall lower cost estimates), we do believe that the majority of future SSRAs will fall under the "normal" conditions.[237] We believe this is appropriate due to: lack of new facilities coming on-line for which there is no previous test data; availability of commercial modeling software; and finalization of the "Human Health Risk Assessment Protocol for Hazardous Waste Combustion Facilities" guidance, or "HHRAP" guidance. However, we do recognize that some facilities can be more complex than others in the hazardous waste combustion universe. Therefore, we have identified a portion of facilities that are likely to incur "unusual" costs for a future SSRA and have revised our cost analysis to reflect inclusion of these higher-cost facilities. See background document, Assessment of the Potential Costs, Benefits, and Other Impacts of the Hazardous Waste Combustion MACT Replacement Standards—Final Rule, October 12, 2005.

Also, we maintain our assumption that SSRAs generally represent a one-time cost unless a facility significantly changes its operations or if receptors change such that an increase in risk is anticipated as a result. Even so, as explained earlier in subsection B., we would anticipate that the risk assessment would not have to be entirely redone. It may be as limited as collecting relevant new data for comparison purposes, leading to a decision not to repeat any portion of a risk assessment. Or, it may be more inclusive such that modifications would be made to specific inputs to or aspects of the risk assessment using data from a previous risk assessment, risk burn or comprehensive performance test. With respect to chemical weapons demilitarization facilities, we recognize that due to their specialized waste streams and multiple treatment units, SSRAs, in many cases, are not one-time events and as a result, their SSRA costs are relatively high. The high costs can be attributed to the necessity for each chemical weapons demilitarization facility to perform surrogate trial burns and then agent trial burns for each furnace and each agent campaign (e.g., GB (Sarin), VX, and HD (Sulfur Mustard)). For example, a chemical weapons demilitarization facility would conduct GB trial burns on all the furnaces and then complete destruction of the GB stockpile, followed by VX trial burns and VX stockpile and finally, the HD trial burns and the HD stockpile. This effectively extends the input to the risk assessment of the trial burn data over most of the operational life of the facility.

Last, several commenters raised the concern that EPA's proposal to codify the authority to require SSRAs on a case-by-case basis and add conditions to RCRA permits based on SSRA results, violates the due process protections afforded under the current structure, where SSRAs are required and performed pursuant to RCRA § 3005(c)(3) omnibus authority. Commenters were further concerned that the proposed language in § 270.10(l) would remove existing procedural safeguards by allowing the Agency to require a very expensive SSRA before the draft permit is even issued, thus violating EPA's own procedural standards as well as due process. It appears as though commenters believe that the procedures (and procedural protections) currently applicable whenever an SSRA is conducted are unique to circumstances in which the permitting authority proceeds under the authority of RCRA § 3005(c)(3)—the "omnibus" provision. This is incorrect. All of the specific procedural requirements the commenters have raised would be applicable whether the permitting authority proceeded under § 270.10(l), as EPA proposed, or pursuant to RCRA § 3005(c)(3) and § 270.10(k), as is the current practice.

All of the requirements established in Part 124 continue to apply, whether EPA proceeds under § 270.10(l) or under § 270.10(k). As we discussed in the proposal, the basis for the decision to conduct a risk assessment, or to request additional information to evaluate risk or determine whether a risk assessment is necessary, must be included in the administrative record for the facility and made available to the public during the comment period for the draft permit. See 40 CFR 124.7 [statement of basis]; 124.9 [administrative record for draft permit]; 124.18 [administrative record for final permit]. If the facility, or any other party, files comments on a draft permit decision objecting to the permitting authority's conclusions regarding the need for a risk assessment, the permitting authority must respond fully to the comments. Any permit conditions determined to be necessary based either on the SSRA, or because the facility declined to conduct an SSRA, also must be documented and supported in the administrative record.

The commenters' concern that § 270.10(l) allows the permitting authority to require the SSRA prior to the issuance of a draft permit, and therefore the applicant would have no opportunity to comment or challenge that determination, is equally unfounded. There is effectively no practical or substantive distinction between the circumstance when a permit authority communicates the decision that an SSRA is necessary to issue the permit prior to issuing the draft permit, or as part of the draft permit. In either case, if a facility refuses to provide a risk assessment or data to support a risk assessment requested under this provision, the regulations at part 124 make clear that the appropriate recourse is for the permit authority to deny the permit (See 40 CFR 124.3(d); 124.6(b) and 270.10(c). The basis for the denial would essentially be the same in either case—that the information before the agency gives rise to a concern that the MACT may not be sufficiently protective,

[236] The high end of this range applies only to those systems operating under "unusual conditions" (the available data suggest that there are only five such facilities).

[237] Normal conditions assume use of previously collected performance burn data, use of standard commercial modeling software that meet Agency guidance, and limited interactions with State and Federal oversight authorities. Unusual conditions assume the need for site-specific modeling, extensive interactions with stakeholders and regulators, an extended time frame, and targeted ecological analyses.

which the agency is unable to dispel based on the information before it. Consequently, the permit authority cannot determine that the permit meets RCRA's standard for permit issuance. An as noted above, all of the requirements of Part 124 would apply to actions taken in accordance with § 270.10(l). For additional discussion on this issue, please refer to the Response to Comments background document for this final rule.[238]

Despite the many reasons offered by commenters opposing our proposal, we continue to believe that our proposed approach is appropriate. As discussed in the proposal (69 FR 21327) and in the previous subsection, although the Phase 1 Replacement and Phase 2 standards provide a high level of protection (i.e., they are generally protective) to human health and the environment, thereby allowing us to nationally defer the RCRA emission requirements to MACT, additional controls may be necessary on an individual source basis to ensure that adequate protection is achieved in accordance with RCRA. Until today, we have relied exclusively upon RCRA § 3005(c)(3) and its associated regulations at § 270.10(k) when conducting or requiring an SSRA. We continue to believe that § 3005(c)(3) and its associated regulations provide the authority to require and perform SSRAs and to write permit conditions based on SSRA results. In fact, as the next subsection will explain, EPA will likely continue to include permit conditions based on the omnibus authority in some circumstances when conducting these activities, and state agencies in states with authorized programs will continue to rely on their own authorized equivalent. However, because SSRAs are likely to continue to be necessary at some facilities, we are finalizing the authority to require them on a case-by-case basis and add conditions to RCRA permits based on SSRA results under the authority of RCRA §§ 3004(a) and (q) and 3005(c). Therefore, we are finalizing §§ 270.10(l) and 270.32(b)(3) with some minor modifications to provide further clarification of the Agency's intent.

D. How Will the New SSRA Regulatory Provisions Work?

The new regulatory provisions are finalized under both base program authority (§ 3004(a) and § 3005(b)) and HSWA authority (§ 3004(q)). That is, changes made to regulations applicable to boilers are promulgated under HSWA authority, whereas changes made to regulations applicable to incinerators are promulgated under non-HSWA authority. Consequently, when it is determined that an SSRA is needed, the applicability of these provisions will vary according to the type of combustion unit (whether it is regulated under 3004(q), or only 3004(a) and 3005(b)), and the authorization status of the state. Depending on the facts, the new authority would be applicable, or the omnibus provision would remain the principal authority for requiring SSRAs and imposing risk-based conditions where appropriate. See 69 FR 21327.

According to the state authorization section of this preamble (see Part Five, Section IV.), EPA does not consider these provisions to be either more or less stringent than the pre-existing federal program, since they simply make explicit an authority that has been and remains available under the omnibus authority and its implementing regulations. Thus, states with authorized equivalents to the federal omnibus authority will not be required to adopt these provisions, so long as they interpret their omnibus authority broadly enough to require risk assessments where necessary.[239]

The provisions of §§ 270.10(l) and 270.32(b)(3) adopted in today's rule are substantially similar to the provisions EPA proposed. Section 270.10(l) continues to explicitly provide that a permit authority has the authority to evaluate, on a case-by-case basis, the need for an SSRA. EPA has also retained its proposed language that explicitly provides that, where an SSRA is determined to be necessary, the permit authority may require a permittee or an applicant to conduct an SSRA, or to provide the regulatory agency with the information necessary to conduct an SSRA on behalf of the permittee/applicant. The final provision also essentially retains the standard laid out in the proposal: that a permit authority may decide that an SSRA is warranted based on a conclusion that additional controls beyond those required pursuant to 40 CFR parts 63, 264, 265, or 266 may be needed to ensure protection of human health and the environment under RCRA. In § 270.32(b)(3), EPA has also explicitly codified the authority for permit authorities to require that the applicant provide information, if needed, to make the decision of whether an SSRA should be required.

However, EPA has adopted some further clarifications to the final provisions in response to comments. In response to comments that the regulatory language EPA had proposed still fails to provide the regulated community with adequate notice that an SSRA might be required, and what that might entail, EPA has included additional language to address those issues. Specifically, EPA has included a sentence stating that the information required under § 270.10(l) can include the information necessary to evaluate the potential risk to human health and/or the environment resulting from both direct and indirect exposure pathways. EPA has also added language to remind permit authorities that the determination that the MACT standards may not be sufficiently protective is to be based only on factors relevant to the potential risk from the hazardous waste combustion unit at the site, and has provided a list of factors to guide the permit authority in making that determination. See subsections E. and F. for further discussion. The applicability language of §§ 270.19, 270.22, 270.62, and 270.66 also has been amended to allow a permit authority that has determined that an SSRA is necessary to continue to apply the relevant requirements of these sections on a case-by-case basis and as they relate to the performance of the SSRA after the source has demonstrated compliance with the MACT standards.

As previously noted, the requirements at 40 CFR Part 124 continue to apply to actions taken to implement § 270.10(l). Thus, if the permitting authority concludes that a risk assessment or additional information is necessary for a particular combustor, the permitting authority must provide the factual and technical basis for its decision in the permit's administrative record and must make it available to the public during the comment period for the draft permit. If the facility or any other party files comments on a draft permit decision objecting to the permitting authority's conclusions regarding the need for an SSRA, the authority must respond fully to the comments. In addition, the SSRA must be included in the administrative record and made available to the public during the comment period. Any additional conditions and limitations determined to be necessary as a result of the SSRA must be documented and supported in the administrative record as well.[240]

[238] See final Response to Comment to the HWC MACT Standards, Volume 5, Miscellaneous.

[239] Authorized states are required to modify their programs only when EPA enacts federal requirements that are more stringent or broader in scope than existing federal requirements. This applies to regulations promulgated under both HSWA and non-HSWA authorities.

[240] Additional clarification on the appropriate use of the SSRA policy and technical guidance is provided in the April 10, 2003 memorandum from Marianne Lamont Horinko entitled "Use of the Site-

E. What Were Commenters' Reactions to EPA's Proposed Decision Not To Provide National Criteria for Determining When an SSRA Is or Is Not Necessary?

In the proposal, we stated that we were not proposing national criteria (e.g., guiding factors) for determining when an SSRA is necessary. Although we had developed a list of qualitative guiding factors for permit authorities to consult when considering the need for an SSRA in the September 1999 final rulemaking (revised from the April 1996 NPRM), we never intended for them to comprise an exclusive list for several reasons. Mainly, we felt that the complexity of multi-pathway risk assessments precluded the conversion of the qualitative guiding factors into more definitive criteria. See 69 FR 21328.

Commenters generally agreed that the risk assessment guidance and policy should not be codified. They agreed in principle that it is important to keep the decision to require an SSRA flexible because factors vary from facility to facility. However, several commenters raised the concern that the proposed language of § 270.10 (l) was too vague. For example, one commenter suggested that any additional guidance clarifying how risk assessments should be performed and that providing standards or goals to be achieved by the operating conditions would be helpful. Another commenter felt that EPA should identify specific factors that the regions and authorized states should consider, and specific criteria that should be met, before requiring an SSRA or additional emission controls or other standards. We agree with commenters that additional guidance would be beneficial and have taken a number of actions in this regard. First, EPA is adopting a more detailed regulatory provision that provides a non-exclusive list of guiding factors for permit authorities to use in determining whether the MACT will be sufficiently protective at an individual site, and consequently, whether an SSRA is warranted. Section 270.10(l) now requires that the permit writer's evaluation of whether compliance with the standards of 40 CFR part 63, Subpart EEE alone is protective of human health or the environment be based on factors relevant to the potential risk from a hazardous waste combustion unit, including, as appropriate, any of the specifically enumerated factors. These factors reflect the eight guiding factors that EPA has discussed in several rule preambles. See 61 FR 17372, 64 FR 52842, and 69 FR 21328. However, EPA has also incorporated a few minor revisions to reflect the standards promulgated today, and to reflect the fact that the factors will be codified.

EPA has revised the language of the factors so that the language is consistent between the provisions. Consistency of phrasing is generally more important in regulations, which are binding, than in guidance. For example, some of the factors listed in the 1999 preamble used the phrase "presence or absence" while other used the phrase "identities and quantities." EPA has adopted the phrase "identities and quantities," on the grounds that it more precisely expresses the concept intended by both phrases. EPA has also made minor revisions to reduce redundant text, and to shorten the provisions, in the interests of clarity. For example, rather than addressing the proximity of receptors in two factors, EPA addresses this issue in a single factor. However, nothing contained in either of the original factors was deleted as part of this revision. None of the revisions described here substantively change the issues to be considered from those contained in the original eight guiding factors.

In addition to these minor technical revisions, EPA has included language to clarify that one potentially relevant factor for consideration is the "identities and quantities of persistent, bioaccumulative or toxic pollutants considering enforceable controls in place to limit those pollutants." This reflects changes made between the proposed and final MACT standards (e.g., the proposed rule called for beyond-the-floor dioxin limits for some sources; those were not promulgated in the final rule).

Another change is the EPA has deleted the factor that listed "concerns raised by the public." The regulation will allow the decision to be based on any one of the listed factors, and public concern, unaccompanied by an identifiable risk, would not provide an adequate basis for determining that an SSRA was warranted.

Finally, as discussed previously in subsection B., EPA has added an additional factor to indicate that a previously conducted risk assessment would be relevant in evaluating changes in conditions that may lead to increased risk. The factor reads as follows: "Adequacy of any previously conducted risk assessment, given any subsequent changes in conditions likely to affect risk." See § 270.10(l)(1).

One commenter raised the concern that the eight guiding factors the Agency specified in its Federal Register notice at 64 FR 52842 (September 30, 1999) did not adequately focus on the central question of whether there are likely to be emissions that would be uncontrolled under the Subpart EEE final rule. They argued that, as an example, under guiding factor #5, if the waste containing highly toxic constituents are being addressed by the Subpart EEE standards, the fact that there might be such wastes should not justify an SSRA. The commenter apparently misunderstands that the factors were not intended to function as stand-alone criteria for requiring an SSRA—i.e., to use their example, the commenter believes that the mere fact that highly toxic constituents are present in the waste would justify an SSRA without consideration of whether the MACT emission standards were sufficiently protective. This is an incorrect reading of EPA's proposed regulation. Rather, the factors were always intended to function as considerations that might be relevant to the determination of whether the MACT was sufficiently protective. However, the regulatory structure EPA has adopted in the final rule makes perfectly clear that the critical determination is that "compliance with the standards of 40 CFR part 63, Subpart EEE alone may not be protective of human health or the environment." Further, the provision states that this determination is to be based only on factors relevant to the potential risk from the hazardous waste combustion unit, including, as appropriate, the listed factors. EPA believes that these provisions make clear that the determination of whether to require an SSRA is to be based on consideration of the conditions at the facility site, including, for example, an evaluation of all enforceable controls in place to limit emissions. Further discussion of EPA's revised provisions can be found in subsection F.

Second, as discussed in more detail below, EPA is issuing a revised risk assessment guidance document that we believe will provide additional insight to help users. While clearly delineating between risk management and risk assessment, the HHRAP explains in great detail a recommended process for performing and reporting on cost-effective, scientifically defensible risk assessments. It includes numerous recommended defaults, while at the same time is flexible enough to incorporate site-specific values. Although the HHRAP provides numerous recommendations, it remains merely guidance and consequently leaves the final decisions up to the permitting authority. We believe that

Specific Risk Assessment Policy and Guidance for Hazardous Waste Combustion Facilities." (See Docket # OAR–2004–0022–0083).

the revised HHRAP guidance will provide further assistance to permit writers, risk assessors and facilities in determining whether or not to conduct an SSRA and what and how much information is required for the SSRA.

F. What Are EPA's Responses to the Cement Kiln Recycling Coalition's Comments on the Proposal and What is EPA's Final Decision on CKRC's Petition?

In the proposal, we provided a lengthy discussion in response to CKRC's petition for rulemaking (69 FR 21325–21331). In its petition, CKRC presented two requests with respect to SSRAs: (1) That EPA repeal the existing SSRA policy and technical guidance because CKRC believes that the policy and guidance "are regulations issued without appropriate notice and comment rulemaking procedures"; and (2) after EPA repeals the policy and guidance, "should EPA believe it can establish the need to require SSRAs in certain situations, CKRC urges EPA undertake an appropriate notice and comment rulemaking process seeking to promulgate regulations establishing such requirements." Additionally, CKRC stated that it does "not believe that these SSRAs are in any event necessary or appropriate" and that they disagree with EPA's use of the RCRA omnibus provision as the authority to conduct SSRAs. Finally, CKRC raised three general concerns: (1) Whether an SSRA is needed for hazardous waste combustors that will be receiving a RCRA permit when the combustor is in full compliance with the RCRA boiler and industrial furnace regulations and/or with the MACT regulations; (2) how an SSRA should be conducted; and (3) what is the threshold level for a "yes" or "no" decision that additional risk-based permit conditions are necessary. We believe our tentative decision in the proposal addressed each request and concern presented in their petition. However, in its comments, CKRC has restated many of the same issues with new emphasis. Thus, we believe it is appropriate to address their major comments in the following paragraphs.[240a]

1. Whether SSRAs Are Necessary for Facilities in Full Compliance With BIF or MACT Regulations

In its comments, CKRC continues to question the need for any SSRAs at facilities that are in full compliance with the MACT EEE standards. CKRC also states that "[our] Petition challenged EPA to explain why, if there is any need for SSRAs at all under RCRA, there is a rational basis for why it has limited the entire SSRA program to hazardous waste combustors." They argue that, "The point is that if the "omnibus" words in RCRA mean what EPA says they mean for hazardous waste combustors, why do they not mean the same thing for all of the other TSD facilities that also pose the same kind of "what-if" hypotheticals that EPA throws out in its preamble?"

As discussed above in subsection B., and in greater detail below, EPA believes that risk assessments will continue to be necessary at some facilities. For example, based on the inconclusive results from the national risk assessment conducted for the 1999 final rule and the comparative risk analysis conducted for today's rule, EPA is not able to conclude that all MACT standards will be sufficiently protective for every facility (e.g., non-dioxin PICs not previously modeled, no numerical dioxin/furan emission standard for solid fuel-fired boilers, liquid fuel-fired boilers with wet or no APCDs, and hydrochloric acid production furnaces, etc.). EPA also provided examples of site-specific factors that might lead risk assessors to decide that the MACT standards may not be sufficiently protective, and therefore an SSRA may be necessary (e.g., if a source's emissions are comprised of persistent bioaccumulative or toxic contaminants). EPA also discussed this issue at length in both the 2004 proposal, and the 1999 rule preamble. See 69 FR 21326 and 64 FR 52842. Given these uncertainties, the SSRA provides significant support for the Agency's 1006(b) determination supporting the elimination of separate RCRA emission standards for MACT EEE facilities.

We disagree that our discussion of standards (and site-specific factors) that may warrant a risk evaluation at certain types of facilities are mere "what-if" hypotheticals. The examples that we discussed in both the earlier preambles and above were based on the 1999 national risk assessment and a comparative risk analysis, which concluded that either there was not enough information to make a definitive protectiveness determination or that uncertainty in cancer and other health effects levels of dioxin and furans, for instance, make it difficult to draw conclusions about potential risks. Furthermore, the discussions with respect to the protectiveness of certain standards (i.e., some are less stringent today than the 1999 standards) in subsection B., present a reasonable basis for permitting authorities to consider whether or not risk should be evaluated. In support of our position that the examples we have provided in the 1999 final rule preamble, the 2004 proposed rule preamble, and this final rule, are more than "what-if" hypotheticals, we have placed copies of completed risk assessments where risk-based limits were found to be necessary in the docket for today's final rule (see OAR–2004–0022).

The CKRC fails to acknowledge that there are many aspects of hazardous waste combustors and the combustion process itself, which make this category of TSD facilities different from others, and which factor heavily into our SSRA policy. Consider that many combustion facilities feed a wide array of waste streams comprised of many hazardous constituents. The combustion of these constituents results in complex chemical processes (which are difficult to predict) occurring throughout the combustion unit. The end product is stack emissions comprised of a variety of compounds different from those that enter the process, and thus are difficult to predict because they can vary greatly based on the many variables of the individual combustion unit, making them difficult to address (*i.e.*, there are no specific emissions standards to limit certain compounds such as products of incomplete combustion). For example, in attempting to maximize the destruction of organic compounds, products of incomplete combustion are often generated as a consequence. Further, due to stack dispersion, hazardous waste combustors have the potential to affect several square miles. Other types of TSD facilities' operations typically do not encompass such complex processes or have the potential to adversely affect receptors for several square miles.

It should be noted that hazardous waste combustors are not the only type of TSD subjected to site-specific evaluations of risk. We take a site-specific approach to regulating miscellaneous units under Part 264, subpart X. Because it is not possible to develop performance standards and emission limits for each type of treatment unit that may fall under this broad category, we rely on general environmental performance standards to meet our mandate under §§ 3004 (a) and (q) that standards governing the operation of hazardous waste facilities be protective of human health and the environment. For example, § 264.601(c) requires "Prevention of any release that may have adverse effects on human

[240a] CKRC provided numerous comments organized by subtitles. Rather than relying on this format in the preamble, we have organized the comments and responses according to the concerns initially raised in the petition, and consistent with the discussion presented in the proposal.

health or the environment due to migration of waste constituents in the air, considering: * * * (6) the potential for health risks caused by human exposure to waste constituents; and * * *" For all intents and purposes, subparts X units are subject to SSRAs as well.

In addition, the question of whether an SSRA continues to be necessary is partly a function of the fact that EPA is seeking to rely on CAA MACT standards in order to eliminate RCRA emissions standards for these facilities. As noted above, because the MACT is technology-based, and because of uncertainties in our national risk assessments, permit writers' ability to conduct an SSRA in individual cases provides important support for our deferral.

RCRA §§ 3004(a) and (q) mandate that standards governing the operation of hazardous waste combustion facilities be protective of human health and the environment. To meet this mandate, we originally developed national combustion standards under RCRA, taking into account the potential risk posed by direct inhalation of the emissions from these sources. With advancements in risk assessment science since promulgation of the original national standards (*i.e.*, 1981 for incinerators and 1991 for boilers and industrial furnaces), it became apparent that the risk posed by indirect exposure (*e.g.*, ingestion of contaminants in the food chain) to long-term deposition of metals, dioxins/furans and other organic compounds onto soils and surface waters should be assessed in addition to the risk posed by direct inhalation exposure to these contaminants. We also recognized that the national assessments performed in support of the original hazardous waste combustor standards did not take into account unique and site-specific considerations which might influence the risk posed by a particular source. Therefore, until EPA was able to revise its regulations, to ensure the RCRA mandate was met on a facility-specific level for all hazardous waste combustors, we strongly recommended that site-specific risk assessments (SSRAs), including evaluations of risk resulting from both direct and indirect exposure pathways, be conducted as part of the RCRA permitting process. In those situations where the results of an SSRA showed that a facility's operations could pose an unacceptable risk (even after compliance with the RCRA national regulatory standards), additional risk based, site-specific permit conditions could be imposed pursuant to RCRA's omnibus authority, § 3005(c)(3).

Rather than establish separate emission standards under RCRA, EPA decided to coordinate its revisions to the RCRA emissions standards for hazardous waste combustors with the adoption of the MACT standards pursuant to § 112(d) of the CAA. See 64 FR 52832. In the rulemaking establishing the MACT standards for incinerators, cement kilns and lightweight aggregate kilns (Phase 1 sources), relying on RCRA § 1006(b), EPA determined that in most cases, the MACT standards would be sufficiently protective that separate RCRA emission standards and operating conditions would not need to be included in the facility's RCRA permit. However, for a variety of reasons, EPA lacked sufficient factual basis to conclude that a complete deferral of RCRA requirements could be supported for all facilities.

Section 1006(b) conditions EPA's authority to reduce or eliminate RCRA requirements on the Agency's ability to demonstrate that the integration meets RCRA's protectiveness mandate (42 U.S.C. 6005(b)(1)). See *Chemical Waste Management* v. *EPA*, 976 F.2d 2, 23, 25 (D.C. Cir. 1992). To support its RCRA § 1006(b) determination, EPA conducted a national evaluation of both direct and indirect human health and ecological risks to determine if the MACT standards would satisfy the RCRA mandate to protect human health and the environment. That evaluation, however, did not quantitatively assess the proposed standards with respect to mercury and nondioxin products of incomplete combustion. This was due to a lack of adequate information regarding the behavior of mercury in the environment and a lack of sufficient emissions data and parameter values (*e.g.*, bioaccumulation values) for nondioxin products of incomplete combustion. Since it was not possible to suitably evaluate the proposed standards for the potential risk posed by mercury and nondioxin products of incomplete combustion, in order to support our 1006(b) determination, we continued to recommend that SSRAs be conducted for some facilities as part of the permitting process until we could conduct a further assessment once final MACT standards were promulgated and implemented. Specifically, we recommended that for hazardous waste combustors subject to the Phase 1 MACT standards—hazardous waste burning incinerators, cement kilns and light-weight aggregate kilns—permitting authorities should evaluate the need for an SSRA on a case-by-case basis. We further stated that while SSRAs are not anticipated to be necessary for every facility, they should be conducted where there is some reason to believe that operation in accordance with the MACT standards alone may not be protective of human health and the environment. For hazardous waste combustors not subject to the Phase 1 standards, we continued to recommend that SSRAs be conducted as part of the RCRA permitting process. See 64 FR 52841. As discussed in subsection B., EPA believes that SSRAs may continue to be necessary for some Phase 1 facilities. For the Phase 2 sources, our comparative risk analysis generally indicates that, although the MACT standards for Phase 2 sources are appreciably more stringent than the current RCRA BIF standards, an SSRA may be necessary to confirm that a facility will operate in a way that is protective of human health and the environment.

Thus, for both Phase 1 and Phase 2 sources, we continue to believe that SSRAs may be necessary for some facilities.[241] We generally believe the MACT standards will be protective; in most cases they are substantially more protective than the existing RCRA part 264, 265, and 266 requirements. However, because HWCs manage hazardous waste and process it by burning and emitting the by-products into the air, a multitude of potential exposure pathways exist. These exposure pathways can also vary substantially based on site-specific factors associated with an individual combustion unit and the surrounding site. Such factors make it difficult for the Agency to conclude that a single, national risk assessment provides adequate factual support for its determination that the technology-based MACT standards will be sufficiently protective. This is further complicated by the fact that, for certain parameters, the Agency lacked sufficient information to quantitatively assess the risk, but is relying on a combination of quantitative and qualitative assessments of the MACT standards' protectiveness.

Nonetheless, EPA does not believe that the uncertainty is so great that it would preclude a deferral under 1006(b) for the affected categories of facilities; nor does EPA believe that these uncertainties necessarily support requiring a risk assessment for all such facilities. Conditions at the facility

[241] As discussed in section B., we expect that facilities that have previously conducted an SSRA will not need to conduct another in consideration of today's final standards. Only those facilities newly subject to the RCRA permitting requirements, or existing sources where changes in conditions could lead to increased risk, may need to conduct or modify an existing SSRA.

might confirm that the MACT standards are sufficiently protective, without the need for a facility-wide risk assessment. For example, if the results of the MACT testing demonstrated that the facility's dioxin emissions fall below the levels estimated in the database EPA used for its comparative risk assessment, the uncertainties in EPA's comparative risk assessment would not, by itself, support a decision to require an SSRA. Such decisions require an evaluation of the conditions at the site, and EPA believes it important to retain the flexibility for permit authorities to take these conditions into account. Accordingly, EPA believes that the regulatory structure adopted in today's rule strikes the appropriate balance between these competing factors.

In response to EPA's statement in the proposal that non-HAP emissions, which were beyond the direct scope of MACT, may pose risk which could necessitate an SSRA (69 FR 21326), CKRC pointed out that the same could be said for other types of TSDs, such as landfills, land treatment systems, etcetera, and EPA has not addressed this point in its preamble. As previously noted, combustion units are distinct from other types of TSDs due to the wide array of waste streams being fed to the unit, the complex chemical processes throughout the combustion unit, stack emissions comprised of a wide variety of compounds that are difficult to address, and the potential to impact receptors for several square miles due to stack dispersion. A further distinction is that EPA is seeking to rely on the MACT standards to eliminate national RCRA stack emissions standards under § 1006(b). Unless EPA can affirmatively demonstrate that RCRA's protectiveness standards are met, the Agency cannot eliminate RCRA requirements. A number of uncertainties remain concerning the protectiveness of the MACT standards based on the uncertainties remaining in the supporting national risk assessment and comparative analysis, and the variability of site-specific factors from one facility to another. Permitting authorities' ability to resolve these uncertainties through the use of the SSRA, where appropriate, provides important support for the Agency's 1006(b) finding. Furthermore, as we have noted, under omnibus, to the extent permitting authorities believe there are problems with other types of TSDs, they can impose requirements and request additional information, including an SSRA in accordance with § 270.10(k). Also as previously noted, Part 264, subpart X specifically incorporates site-specific consideration of risk into its regulatory framework.

Next, CKRC comments that EPA has a non-discretionary duty under CAA § 112(f) to address and take care of any "residual risk" from MACT facilities in the future in any event. We discussed why we do not believe that the residual risk process should or can take the place of an SSRA under RCRA in subsection C. of this SSRA preamble, as well as in the 1999 rule preamble (64 FR 52843). In short, because the residual risk standards have not yet been established, permit writers cannot rely on this process in reaching current permitting decisions or in acting on currently pending permit applications.

2. Codification of EPA's Technical Guidance

In response to our explanation in the proposal that risk assessment guidelines should be flexible and reflect current science, CKRC gave three comments: (1) Not a word of the current SSRA guidelines has been changed in 3 years; (2) it is easy to write regulations that have provisions that might be applied differently in different situations, and at least many basic, fundamental points can go in regulations, while some details can be in guidance—EPA writes regulations accompanied by "fill in the small details" guidance all the time; and (3) EPA seems to have no real problems with regulatory fixes anyway. In addition, CKRC provides several comments related to the previous three throughout their comment document, which are addressed below.

None of these comments address the specific issue EPA raised, which is that, while it certainly is possible to codify our risk assessment guidance, for a variety of reasons, we disagree that it would be appropriate to issue these technical recommendations as a regulation. As we previously explained, risk assessment—especially multi-pathway, indirect exposure assessment—is a highly technical and evolving field. Any regulatory approach EPA might codify in this area is likely to become outdated, or at least artificially constraining, shortly after promulgation in ways that EPA cannot anticipate now. In support of this, we noted specific examples of problems we experienced in implementing the BIF regulations. See 69 FR 21330. Further, we explained that at the time of codification, BIF risk assessments were not intended to address indirect routes of exposure, thus making the parameters easier to implement. Today, however, risk assessments are more complex due to the necessary inclusion of multi-pathway and indirect exposure routes. Given the complexity of multi-pathway and indirect exposure assessments and the fact that risk science is continuously evolving, it would be difficult and again, overly constraining, to codify risk parameters today. We note as well, in this regard, that several commenters agreed that codification of EPA's risk assessment guidance would be too constraining for both the agency and the regulated community.

We also believe that a guidance approach is consistent with the fact that permit authorities must make site-specific decisions whether to do risk assessments at all. We think that it makes little sense to allow this kind of flexibility regarding whether to do a risk assessment and for what purposes, while prescribing how one must be conducted if one is required. In fact, permitting authorities, in some cases, have developed their own guidance methodologies responsive to the specific needs associated with their facilities. For example, North Carolina, Texas, and New York have each developed their own risk assessment methodologies. Further, facilities that choose to conduct SSRAs themselves can choose alternative approaches in applying methodologies as well. We think this flexibility employed in the field supports our judgment that risk assessment methodologies should not be codified. CKRC's comments failed to address any of these issues.

Turning to the remainder of CKRC's specific points—CKRC's assertion that the technical guidance has not been amended in the past three years is inaccurate. A revised HHRAP guidance, that has been amended to take into account the technical recommendations from both the public comments and peer review, is published in conjunction with this rule. In addition, as noted above, in some cases, permitting authorities have developed their own methodologies responsive to the specific needs associated with their facilities.

With respect to CKRC's third point, the regulatory corrections made to the MACT rules were necessary either to fix an error or omission or to resolve potential legal issues. To codify technical tools and chemical information pertinent to the risk process simply is not prudent, as this information is continually changing and would almost always be out of date. Granted, when this information is presented in guidance, it can just as easily become outdated, however, facilities and risk assessors are free to use the most up-to-date air modeling tools and toxicity values available (i.e., they would not be bound to regulations requiring the use of obsolete tools and

information). We continue to believe that publishing our technical recommendations as regulation would remove much of the flexibility that is important in evaluating risk on a site-specific basis.

CKRC discounts EPA's statement that codification of risk assessment is the exception arguing that "Neither TSCA or CERCLA, however, specifically commands EPA to define the type of information necessary for a permit application through the rulemaking process as RCRA does. Moreover, the TSCA and CERCLA examples EPA cites are not analogous to the situation where a permit applicant can be denied a permit—or at least strung through months or years of tortuous and costly submissions, revision, and resubmission—to obtain a permit."

Even if TSCA and CERCLA were not considered to be analogous, that does not change EPA's fundamental rationale that codification of highly technical risk assessment guidance is not appropriate. EPA does not believe that RCRA § 3005(b) requires EPA to codify an exhaustive list of every possible piece of information that might be required in a permit. To some extent, that is the reason for having a permit process—to allow site specific conditions to be taken into account. Nevertheless, EPA has revised part 270, pursuant to RCRA § 3004(a) and § 3005(b) to specifically provide that a risk assessment may be necessary, where there is reason to believe that the MACT standards may not be sufficiently protective. This was done wholly to address the petitioner's concern that the current regulations do not adequately provide notice that an SSRA might be necessary as part of a permit application. This provision, while it does not provide as much detail as the petitioner wishes, clearly "defines the type of information necessary for a permit application."

CKRC complains that the Agency did not address in its proposed response the petitioner's discussion of the "strong case law compelling the conclusion that 'guidance' documents EPA has issued for conducting SSRAs must be subjected to notice-and-comment rulemaking." EPA has chosen not to respond to CKRC's legal interpretation because we believe that it is clear that the guidance documents do not impose mandatory requirements, and therefore need not be issued by notice and comment rulemaking. Nevertheless, EPA notes that in the proposal, the Agency explained that we were in the process of reviewing the guidance documents, and, to the extent we found language that could be construed as limiting discretion, we committed to revise the documents to make clear that they are non-binding. See 69 FR 21329. We specifically noted that CKRC indicated in its petition that, in its view, the documents contain language that could be construed as mandatory. While EPA does not necessarily agree, and believes that, in context, it is clear that the recommendations in the documents are discretionary, EPA nonetheless reviewed the documents to ensure that they are carefully drafted. Consequently, under the standards articulated in *Appalachian Power Co.* v. *EPA*, 208 F.3d 1015 (D.C. Cir. 2000) and subsequent case law, the final HHRAP guidance is truly guidance and does not require notice-and-comment rulemaking. The HHRAP explains in great detail an acceptable process for performing and reporting on cost-effective, scientifically defensible risk assessments. It includes numerous recommended defaults, while at the same time provides the risk assessor or facility full opportunity to incorporate site-specific values in place of the defaults. The HHRAP offers numerous recommendations, but requires nothing. EPA has placed a copy of the final guidance document in the docket for today's action (see OAR–2004–0022).

CKRC believes that EPA's technical guidance imposes information requirements upon the RCRA permit applicant that are not contained in any regulations and in fact exceed by orders of magnitude any information requirements contained in the part 270 regulations. We disagree that anything contained in HHRAP is "required" in any way. Moreover, to the extent any individual facility believes the information requested is inappropriate or unnecessary, they can challenge that as part of the permitting process.

Lastly, CKRC argues that "The procedures EPA has been using to issue and revise the SSRA guidance do not by any measure comply with the full panoply of procedures and protections offered by the APA process. Most critically, when EPA merely solicits comments on draft guidance documents, it has no duty to respond to comments and provide a rational basis and justification in defense of its choices in the face of comments. EPA is essentially running its entire SSRA program on the basis of "draft" guidance versions for which EPA has never to this day prepared any response to comments." As previously noted, EPA believes the final HHRAP is merely guidance and therefore, EPA is not required to proceed through notice and comment rulemaking pursuant to § 553 of the APA. However, because we want the HHRAP guidance to be useful and clear, we have solicited public review and comment. As a result, it has been improved over the years by including revisions to the guidance based upon feedback from users of the guidance and from experience in the field. A response to comments document has been prepared and released along with the final HHRAP and final MACT rules, even though the Agency was not required to do so. More to the point, because it is only guidance, sources will have the opportunity to raise questions or comments on anything in the guidance as part of the permitting process and the permitting authority will be required to respond to those comments as part of the permitting process. See 40 CFR part 124. Sources will also have the right to challenge the responses or use of the guidance as part of the permitting process.

3. Codification of Criteria for Determining That Additional Risk-Based Permit Conditions or an SSRA Is Necessary

CKRC argues that EPA's proposed regulatory changes should not be considered as a partial grant because EPA has not codified specific criteria in the proposed regulations for permit authorities to use to decide whether to require an SSRA; to set the risk levels that are deemed protective; or to otherwise provide any further definition as to what it means to protect human health and the environment.

In its petition, CKRC requested that after we repeal the policy and guidance (per the first request), "should EPA believe it can establish the need to require SSRAs in certain situations, CKRC urges EPA to undertake an appropriate notice and comment rulemaking process seeking to promulgate regulations establishing such requirements." As discussed at length in both the proposal (69 FR 21325–21327) and the preceding paragraphs, we believe that we have established certain circumstances where the MACT standards may not be protective and that an SSRA may be warranted, based on relevant site-specific factors associated with an individual combustion unit. Consequently, we are finalizing regulations that explicitly authorize permitting authorities to conduct or require an SSRA on a site-specific basis. This, in our view, grants the second of CKRC's requests. Our response directly addresses a number of CKRC's concerns: (1) Through a notice and comment rulemaking process, EPA has established circumstances in which an SSRA may be necessary; and (2) EPA's regulations will now explicitly

acknowledge that an SSRA might be necessary as part of the permitting process, thereby addressing the petitioner's concern that EPA's past approach of relying on RCRA's omnibus authority to implement this policy violates the requirements of RCRA § 3005(b). And as discussed further below, EPA has codified criteria for permit authorities to use to determine whether to require an SSRA.

While it does not provide exactly what CKRC requested, the regulated community has had a full opportunity to comment on the need for an SSRA both as part of the 1999 rulemaking and, again, as part of this rulemaking to adopt the provisions of § 270.10(l), which contain an explicit reference to the potential need for an SSRA as part of the permitting process pursuant to RCRA § 3004(a) and § 3005(b). As previously explained, § 270.10(k) does not explicitly mention the potential for an SSRA to be required. Although the rule does not identify a priori that an SSRA will be required in an individual circumstance, but defers that determination to the permitting process, the final rule reflects EPA's findings that an SSRA is not anticipated to be necessary in every circumstance—only where site-specific conditions give the permit authority reason to believe that additional controls beyond those required pursuant to 40 CFR parts 63, 264, 265, or 266 may be necessary to protect human health and the environment.

CKRC argues that EPA's decision not to codify national criteria renders the regulation impermissibly vague, and therefore, "in their view totally deficient as a legal matter." The petitioner argues that the rule is essentially "a bootstrap attempt to avoid rulemaking requirements by establishing 'rules' that give no more guidance or direction than general terms in the statute and in no way channel the decision maker's discretion or put the public on notice of anything." According to CKRC, this unbridled discretion is manifest in three ways: (1) No criteria explain how a permit writer is to decide whether to require an SSRA; need merely to conclude "reason to believe"; (2) there are absolutely no limits on what type of information or assessments the permit writer may demand and the proposed reg. does not even hint at what type of information or assessments might be demanded; and (3) there is not a word of guidance or specification as to what it means to "ensure protection of human health and the environment." The petitioner argues that as a consequence, the proposed § 270.10(l) would be struck down as a "standardless regulation."

EPA disagrees that the provisions at § 270.10(l) are impermissibly vague, or otherwise inconsistent with the cases the petitioner cites. In the cited cases the courts found that the regulated entity bore the entire burden of determining how to comply with the challenged regulation in the complete absence of a government-generated standard or guidance. See *Maryland* v. *EPA*, 530 F.2d 215, 220 (4th Cir. 1975); *South Terminal Corp* v. *EPA*, 504 F.2d 646, 670 (1st Cir. 1974). This is entirely distinct from the regulations codified at § 270.10(l).

In § 270.10(l) EPA identified the standard for when a risk assessment may be necessary: where the regulatory authority identifies factors or conditions at the facility that indicate that the MACT standards may not be sufficiently protective, and defers the articulation of the more precise requirement to the permitting process, where the onus falls on the permitting authority to identify the basis for its determination. Until the permitting authority provides this further guidance, the regulated entity incurs no obligation. The mere fact that specific factors or facility conditions that form the basis for the determination that an SSRA is warranted will be subsequently identified through the permitting process does not invalidate the regulation. See *Ethyl Corp* v. *EPA*, 306 F.3d 1144, 1149–1150 (D.C. Cir. 2002).

The regulation also identifies the categories of information that might be required for MACT EEE facilities: The information must be necessary to determine whether additional controls are needed to ensure protection of human health and the environment; it can include the information necessary to evaluate the potential risk from both direct and indirect exposure pathways; or it can include the information necessary to determine whether such an assessment is necessary. Here as well, EPA's reliance on the permitting process to provide further specification of the required information is not improper.

Moreover, as discussed above in subsection C., in response to commenters' concerns, EPA has revised § 270.10(l) to provide more detail, both with respect to the basis for the determination that an SSRA is necessary, and with respect to the type of information the permit authority might need. EPA has added language to remind permit authorities that the determination that the MACT standards may not be sufficiently protective is to be based only on factors relevant to the potential risk from the hazardous waste combustion unit at the site. EPA has also added language to § 270.10(l) to identify guiding factors for permitting authorities to consult in determining whether the MACT will be sufficiently protective at an individual site. Although the list of guiding factors is not all-inclusive, they offer a structure for risk managers (as well as the regulated community) to use to frame the evaluation of whether a combustor's potential risk may or may not be acceptable.

Finally, we note that, unlike the circumstances in the cited cases, § 270.10 is promulgated in the context of an existing permitting regime. The regulatory standards at 40 CFR part 124 provide further structure for both the regulated community and the permit authority. For similar reasons, EPA disagrees that the cited cases compel the Agency to establish risk levels that are deemed protective, or to otherwise provide any further definition as to what it means to protect human health and the environment. We discussed at length throughout the proposal the reasons we believe it would not be appropriate to codify either an exclusive set of national criteria for determining that an SSRA (or additional risk-based permit conditions) would be necessary, or a uniform risk level. The decision to require an SSRA is inherently site specific, thus permitting authorities need to have the flexibility to evaluate a range of factors that can vary from facility to facility. See 69 FR 21328–21331. CKRC has neither presented new factual or policy reasons that would cause the Agency to reconsider the tentative decisions presented in the proposal, nor specifically addressed the issues underlying EPA's decision. Instead, the petitioner has merely reiterated the concerns presented in its petition and its general disagreement with EPA's decision.

EPA also disagrees that its new regulatory structure grants permit writers unbridled discretion for many of the same reasons that EPA does not believe that § 270.10(l) is impermissibly vague. As EPA has previously explained, the requirements at Part 124 continue to apply to actions taken to implement § 270.10(l). Moreover, the language of § 270.10(l) makes clear that the onus initially falls on the permitting authority to identify the basis for its conclusion that the MACT standards may not be sufficiently protective. As both part 124 et. seq., and EPA's preamble discussions make clear, facilities will continue to have the opportunity to comment on and challenge the determination. See §§ 124.10, 124.11, and 124.19. The

regulatory structure adopted in § 270.10(l) mirrors the structure Congress established in sections 3004 and 3005; although 3004 directs EPA to establish national standards, section 3005 recognizes that those standards will be applied on a case-by-case basis through the permitting process, to allow site-specific conditions to be taken into account, and to supplement those standards as necessary.

EPA has also provided recommendations through guidance on how an SSRA can be conducted. Although the recommendations are not binding, they provide risk managers (as well as the facility) with a starting point from which to determine whether a combustor's potential risk may or may not be acceptable.

CKRC argues that it appears that rather than following the statutory authorities and requirements to review and amend regulations every 3 years as necessary (RCRA § 2002(b)), EPA decided to take the easy way out and impose, through non-rulemaking "guidance", massive, costly, and confusing requirements leaving unbridled discretion to its permit writers.

We disagree that the Agency has attempted to avoid rulemaking in this context. EPA has conducted several rulemakings to amend our regulations. The first was in 1999, when we adopted revised emission standards under the authority of both § 112(d) of the CAA and RCRA to more rigorously control toxic emissions from burning hazardous waste in incinerators, cement kilns, and lightweight aggregate kilns. See 64 FR 52828. At the time, we noted that "today's rule fulfills our 1993 and 1994 public commitments to upgrade emission standards for hazardous waste combustors." We have continued to revise our regulations consistent with and based on the facts before the Agency, taking into account the arguments presented in CKRC's petition. As explained above, we believe that the facts do not support granting all of CKRC's requests. Rather we believe that the MACT standards will generally be protective, and that permit authorities should reach the decision to require an SSRA based on a variety of factors and concerns specific to their sites. In addition, as previously addressed, we believe that our risk assessment guidance should remain as guidance. Several other commenters agree that the guidance should not be codified.

The petitioner argues that the regulation EPA has proposed to adopt is so vague, that it is essentially not a regulation, and that consequently, even if finalized, it would not be sufficient to comply with the requirement in RCRA § 3005(b) to specify in regulations, the information necessary to obtain a permit. They compare the level of detail in § 270.10(l) to the lengthy regulations (codified in 40 CFR part 270) specifying in great detail the information required when one is submitting a RCRA permit application, arguing that "these regulations cover 75 pages of fine print in Code of Federal Regulations," to demonstrate that this regulation would be insufficient under RCRA § 3005(b). In further support of this argument, CKRC cites *Ethyl Corporation* v. *EPA*, 306 F.3d 1144 (D.C. Cir. 2002).

EPA disagrees that its regulations are in any way inconsistent with the decision in *Ethyl Corp.* At issue in that case was a regulation issued pursuant to section 206(d) of the CAA. Section 206(d) provides that EPA "shall, by regulation, establish methods and procedures for making tests under this section." 42 U.S.C. 7525(d). The court found that "with CAP 2000, [the challenged regulation] the EPA does not claim to have itself articulated even a vague durability test. Rather CAP 2000 requires that 'the manufacturer shall propose a durability program' for EPA approval. 40 CFR 86.182301(a). It thus falls on the forbidden side of the line." *Ethyl Corp.*, 306 F.3d at 323–324. The Court distinguished the challenged regulation from the situation in which an agency issues a "vague" regulation, and relies on subsequent proceedings to flesh out the specific details. And as the court explained, where "Congress had not specified the level of specificity expected of the agency, we held that the agency was entitled to broad deference in picking the suitable level." 306 F.3d at 323 (citing *American Trucking Associations* v. *DOT*, 166 F.3d 374 (D.C. Cir. 1999) and *New Mexico* v. *EPA*, 114 F.3d 290 (D.C. Cir. 1997).

In § 270.10(l) EPA has articulated the standard for when a risk assessment may be necessary: where the regulatory authority has identified factors or conditions at the facility that indicate that the MACT standards may not be sufficiently protective. EPA has also adopted a list of factors on which permit writers are to rely in reaching this determination. EPA has also identified the categories of information that might be required for MACT EEE facilities: The information must be necessary to determine whether additional controls are needed to ensure protection of human health and the environment; it can include the information necessary to evaluate the potential risk from both direct and indirect exposure pathways; or it can include the information necessary to determine whether such an assessment is necessary. While it does not provide as much detail as the petitioner wishes, this provision unquestionably "defines the type of information necessary for a permit application."

Thus, the issue turns on the level of specificity that RCRA § 3005(b) requires, and EPA does not believe that RCRA § 3005(b) requires EPA to publish a list of every possible piece of information that might be required in a permit. Section 3005(b) merely establishes a broad directive that "each application for a permit under this section shall contain such information as may be required under regulations promulgated by the Administrator," and that it shall include the information contained in subsections (1) and (2), leaving to EPA's discretion to determine the level of specificity at which to promulgate regulations. To some extent, this reflects the reason for having a permit process—to allow site specific conditions to be taken into account. The regulatory structure adopted in § 270.10 mirrors the structure Congress established in RCRA § 3004 and § 3005. Despite the petitioner's comparison to the length of part 270, the length of these provisions are not indicative of any determination of the precise level of detail that § 3005(b) requires, but reflects the fact that EPA has adopted requirements specific to individual types of units. Moreover, notwithstanding the petitioner's characterization, the language at § 270.10(l) is comparable to many other provisions in 40 CFR part 270. See, for example: §§ 270.14(b)(8); 270.16(h)(1)–(2); 270.22(a)(6)(i)(C); 270.22(c).

Lastly, CKRC argues that the proposed regulation is particularly problematic, because it extends beyond "information" that may already exist. CKRC says that it is one thing to demand that a party go out and gather existing information, but another thing to demand that an applicant conduct "assessments." Moreover, nothing in the regulations prohibits a permit authority from demanding revised assessments, and even more revised assessments. We agree that permit authorities have the authority to require facilities to provide additional information beyond that which already exists. However, based on feedback from EPA Regional permit writers, SSRAs generally represent a one-time cost. We do not expect that facilities that have conducted risk assessments will have to repeat them. As discussed in the 1999 final rule preamble, changes to comply with the MACT standards should not cause an increase in risk for the vast majority of facilities given that the changes, in all

probability, will be the addition of pollution control equipment or a reduction in the hazardous waste being burned (see 64 FR 52842). Instances where a facility may need to repeat a risk assessment would be related to changes in conditions that would likely lead to increased risk.[242] In such situations, we would anticipate that the risk assessment would not have to be entirely redone. It may be as limited as collecting relevant new data for comparison purposes, leading to a decision not to repeat any portion of a risk assessment. Or, it may be more inclusive such that modifications would be made to specific inputs to or aspects of the risk assessment using data from a previous risk assessment, risk burn or comprehensive performance test. As discussed in subsection B., we have added a new regulatory provision to indicate a previously conducted risk assessment would be relevant in evaluating changes in conditions that may lead to increased risk. The factor reads as follows: "Adequacy of any previously conducted risk assessment, given any subsequent changes in conditions likely to affect risk."

4. EPA's Cost Estimates for SSRAs

CKRC raised several objections to our cost estimates for conducting an SSRA, and provided higher cost estimates ($200K to $1M, with upper bound of $1.3M). We suggested in the proposal, that the higher cost figures provided by CKRC were likely incurred prior to the 1998 release of the Human Health Risk Assessment Protocol (HHRAP) guidance document. We believe our lower cost estimates can be attributed to the fact that we based them on the conduct of future SSRAs that will benefit from substantially better guidance and commercially available software.

Multiple issues regarding the cost information we provided in the proposal are raised by CKRC. The first of five issues is that CKRC believes that EPA's methods for calculating costs associated with future SSRAs do not include data gathering costs, QA/QC, third party consultants in addition to risk assessors and plant personnel time to coordinate and review SSRA efforts and collect facility data. We disagree with this statement in part; the estimates developed by the Agency do include data gathering costs, QA/QC, and third-party consultants. (Refer to the proposed rule's support document entitled: Preliminary Cost Assessment for Site Specific Risk Assessment, November 2003, Docket # OAR–2004–0022; and the Assessment of the Potential Costs, Benefits, and Other Impacts of the Hazardous Waste Combustion MACT Replacement Standards—Final Rule, October 12, 2005, for a description of how the estimates were arrived at.) However, we agree with CKRC that the method used to develop SSRA costs does not capture facility time associated with data collection and management related to the SSRA. Consequently, we have adjusted our SSRA cost estimates to account for these activities by incorporating costs associated with time needed for facility data collection and management efforts associated with the SSRA, and will assume that engineering staff are required to perform these tasks.

The second issue concerns the extent to which cement kiln SSRAs are consistent with EPA's "normal" assumptions. We do not question the accuracy of the costs submitted by CKRC. However, it is not clear that the costs submitted by CKRC represent typical future costs for SSRA implementation at all facilities in the universe. Certain of the CKRC cost estimates (e.g., those submitted by Ash Grove and Holcim) reflect implementation of SSRAs over a number of years in the 1990s, while SSRA implementation was in its early stages. In other cases (e.g., estimates provided by Solite) costs appear to be consistent with EPA estimates. While we do not dispute the accuracy of these costs, earlier costs are likely to reflect the deliberative process common with early SSRAs.

For the third issue, CKRC's points out that EPA's estimate of 20 percent additional cost for adding a risk burn during a trial burn may be low; CKRC asserts that additional test costs can add up to 40 percent depending on the circumstances. We agree with this and have adjusted the range of total SSRA costs as necessary to assure that a range of additional test costs for separate risk burns (20 to 40 percent incremental cost) are included. For revised figures, see background document, Assessment of the Potential Costs, Benefits, and Other Impacts of the Hazardous Waste Combustion MACT Replacement Standards—Final Rule, October 12, 2005.

CKRC's fourth issue is that EPA does not appear to include more than evaluations of stack emissions in its estimates of SSRA costs. We disagree with this comment. The estimates of SSRA costs developed by the Agency reflect total contractor costs for performing an SSRA at a facility under different sets of conditions, and are not limited to stack emissions.

In the fifth cost-related issue, CKRC asserts that EPA's average estimates might be reasonable if the SSRA process were limited to the submission and acceptance of one SSRA effort. CKRC contends, however, that its members' experiences with SSRAs have involved coordination with state and regional offices and multiple revisions and submissions. Again, we do not question the experiences and costs of specific facilities. However, we anticipate that the 2003 Memorandum, Use of the Site-Specific Risk Assessment Policy and Guidance for Hazardous Waste Combustion Facilities, and the Human Health Risk Assessment Protocol for Hazardous Waste Combustion Facilities guidance, which is finalized and released in conjunction with today's rule, will provide facilities and regulators with a clearer understanding of SSRA policy and guidance and will support a more efficient SSRA process. EPA's future SSRA cost estimates are based on current or recent cost data from multiple practitioners, and likely reflect a more efficient process than that experienced by some CKRC members in the 1990s.

X. Permitting

As discussed in the proposal, we believe that the permitting approach we adopted in the 1999 final rule is still the most appropriate means to avoid duplication to the extent practicable and to streamline requirements. Thus, both Phase 1 and Phase 2 sources will comply with their RCRA emission limits and operating requirements until they demonstrate compliance with the MACT standards by conducting a comprehensive performance test (CPT), submitting a Notification of Compliance (NOC) documenting compliance to the Administrator or delegated state, and then requesting to have their RCRA permits modified to remove the duplicative RCRA requirements (unless a sunset clause had been added previously that inactivates specified requirements upon compliance with MACT).[243] Ultimately, the MACT air emissions and related operating requirements will reside in the CAA Title V permit, while all other aspects

[242] For example, hazardous waste burning cement kilns that previously monitored hydrocarbons in the main stack may elect to install a mid-kiln sampling port for carbon monoxide or hydrocarbon monitoring to avoid restrictions on hydrocarbon levels in the main stack. Thus, their hydrocarbon emissions may increase. (64 FR 52843, footnote 29.) Another example would be if the only change at a facility relates to the exposed population; what was acceptable in a previous risk assessment may not be any longer.

[243] Although we expect that the vast majority of Phase 1 sources will have had their RCRA permits modified by the time this rule is promulgated, we acknowledge that there may be a few permits yet to be modified.

of the combustion unit and the facility (e.g., corrective action, general facility standards, other combustor specific concerns such as material handling, risk-based emission limits and operating requirements, and other hazardous waste management units) will remain in the RCRA permit. A new pictorial timeline has been provided to highlight milestones of the MACT compliance process. See figure 1 at the end of this section.

A. What is the Statutory Authority for the RCRA Requirements Discussed in this Section?

EPA is finalizing amendments to modify RCRA permits in today's rule pursuant to sections 1006(b), 2002, 3004, 3005 and 7004(b) of RCRA. 42 U.S.C. §§ 6905(b), 6912, 6924, 6905, and 6074. Our approach is likewise consistent with section 112(n)(7) of the Clean Air Act which indicates that EPA should strive to harmonize requirements under section 112 and RCRA requirements for hazardous waste combustion sources. With respect to the regulatory framework that is discussed in this section, we are finalizing the process to eliminate the existing RCRA stack emissions national standards for hazardous air pollutant for Phase 2 sources as we had done for Phase 1 sources in the 1999 final rule. That is, after submittal of the NOC established by today's rule and, where applicable, once RCRA permit modifications are completed at individual facilities, RCRA national stack emission standards will no longer apply to these hazardous waste combustors (unless risk-based permit conditions are determined necessary).

We originally issued emission standards under the authority of section 3004(a) and (q) of RCRA, which calls for EPA to promulgate standards "as may be necessary to protect human health and the environment." We believe that the final MACT standards are generally protective of human health and the environment, and that separate RCRA emission standards are not needed to protect human health and the environment. See Part Seven, How Does the Final Rule Meet the RCRA Protectiveness Mandate? for a discussion of this topic. RCRA section 1006(b) directs EPA to integrate the provisions of RCRA for purposes of administration and enforcement and to avoid duplication, to the maximum extent practicable, with the appropriate provisions of the Clean Air Act (and other federal statutes). This integration must be done in a way that is consistent with the goals and policies of these statutes. Therefore, based on its findings regarding the protectiveness of the MACT standards, and pursuant to section 1006(b), EPA is generally eliminating the existing RCRA stack emission standards to avoid duplication with the new MACT standards. The amendments made today to allow new combustion units to comply with the MACT standards upon start-up, versus the RCRA stack emissions national standards, are based on the principle of avoiding duplication between programs.

We are not stating that RCRA permit conditions to control emissions from these sources will never be necessary, only that the national RCRA standards appear to be unnecessary. Under the authority of RCRA's "omnibus" clause section 3005(c)(3); (see §§ 270.32(b)(2) and (b)(3)), RCRA permit authorities may impose additional terms and conditions on a site-specific basis as may be necessary to protect human health and the environment. Thus, if MACT standards are not protective in an individual instance, RCRA permit writers will establish permit limits that are protective.

In RCRA, Congress gave EPA broad authority to provide for public participation in the RCRA permitting process. Section 7004(b) of RCRA requires EPA to provide for, encourage and assist public participation in the development, revision, implementation, and enforcement of any regulation, guideline, information, or program under the Act.

B. Did Commenters Express any Concerns Regarding the Current Permitting Requirements?

Generally speaking, commenters favor maintaining the permitting approach and requirements referred to above. This approach was finalized in the 1999 rule and has been implemented, and in a few cases is currently being implemented, for Phase 1 sources complying with the Interim Standards Rule. However, several commenters raised similar concerns regarding certain aspects of the transition process from RCRA to MACT and Title V permitting.

1. Removal of Duplicative RCRA Permit Conditions

One comment is in regard to Phase 1 sources that have been fully transitioned (i.e., have had duplicative RCRA permit conditions and requirements removed or that have been "sunsetted") to compliance with the Interim Standards that may need to make upgrades to comply with the revised Phase 1 MACT Standards. The concern is that Phase 1 sources needing to make upgrades for MACT should be able to do so without a RCRA permit modification (unless risk-based conditions are present). We agree with the commenters that as long as the technology upgrades (e.g., equipment changes to upgrade air pollution control equipment) do not affect any remaining conditions in the RCRA permit, the regulations do not require a permit modification. For those Phase 1 sources that need to make upgrades to comply with the revised standards, they should address the specific upgrades in their draft Notification of Intent to Comply (NIC) and during the informal NIC public meeting so that the regulatory authority and public are aware of the source's activities and plans for compliance. We encourage early communication between the source and the RCRA permit writer to ensure a common understanding of whether a RCRA permit modification will be needed.

Additionally, Phase 1 sources must comply with the provisions of § 63.1206(b)(5) for changes in facility design. We do not anticipate that upgrades made to comply with the Replacement Standards will adversely affect a source's compliance with the Interim Standards. Therefore, consistent with § 63.1206(b)(5)(ii), sources must document the change in their operating record, revise their NOC and resubmit it to the permitting authority (per § 63.9(h)), and, as necessary, revise their start-up, shutdown, and malfunction plan.[244]

Several commenters felt that we should re-emphasize the importance of removing duplicative RCRA permit conditions and requirements. We agree with the commenters that this is an important action for regulatory agencies. In addition to comments received, we also have learned through the implementation process for the Interim Standards, that some state agencies are not removing duplicative requirements from the RCRA permit. We have clearly stated in several preambles and guidance documents that we believe it is appropriate to retain only the RCRA risk-based conditions that are more stringent than the applicable MACT limits (i.e., if the RCRA condition has been determined to limit risk to an acceptable level and is necessary to protect human health and the environment) in the RCRA permit after

[244] The requirements in § 63.1206(b)(5)(ii) call for sources to revise (as necessary) the performance test plan, DOC, NOC, and start-up, shutdown, and malfunction plan. For sources complying with the Interim Standards, it is not necessary to revise the performance test plan or the DOC, since they were developed in preparation for compliance with the Interim Standards.

compliance with MACT.[245] However, we also acknowledge that in certain cases it may not be clear which compliance requirement is more stringent. For example, standards under MACT are expressed as concentration based limits (micrograms/dry standard cubic meter) while certain RCRA standards are expressed as mass emission rate limits (grams/second). Also, averaging times between the two programs differ: MACT requires hourly rolling averages whereas RCRA requires instantaneous values. This is an unfortunate consequence of moving compliance from a risk-based program to a technology-based program. Because we cannot definitively say when a RCRA requirement is more stringent than a MACT requirement and consistently apply it to all sources, we are relying on sources and permitting agencies to work together to determine which requirement is more stringent. If the MACT requirement is determined to be more stringent, the permitting agency can remove the requirement from the RCRA permit.

In adopting a permitting approach to place the MACT air emissions and related operating requirements in the CAA Title V permit and to keep all other aspects of the combustion unit and the facility in the RCRA permit, our intent was and still is, to minimize duplication to the extent practicable and to eliminate the potential for dual enforcement. We view it as an unnecessary duplication of effort between programs as well as an unnecessary expenditure of resources and costs for both facilities and regulatory authorities to maintain a RCRA permit and a Title V permit that contain duplicative requirements, when there are viable mechanisms (i.e., Class 1 modification procedure at 270.42 Appendix I, section A.8, or Class 2 or 3 if a state has not adopted the Class 1 procedure) in place to avoid doing so.

Nevertheless, we believe that states should have the flexibility to decide how they will allocate their resources, which is why we did not include a single transition approach for implementing agencies to follow in the 1999 rule or in today's rule. So, in such cases where a state agency chooses not to adopt the transition language (i.e. the Class 1 modification procedure at 270.42 Appendix I, section A.8) into their state requirements (e.g., because the state's procedures are broader in scope or more stringent than the federal requirements) or is unable to reach an agreement between its RCRA and air programs regarding which standards are more stringent, the Title V permitting authority should document these issues, including any continuing RCRA permit requirements, in the title V permit's statement of basis (40 CFR §§ 70.7(a)(5) and 71.7(a)(5)). This will help to ensure that the source is clear regarding its compliance obligations, which is a main goal of the Title V program. Further, for purposes of clarification and as a matter of courtesy, we urge regulatory authorities that choose to impose dual compliance requirements, to also provide a written justification to the source explaining the reasons for their decisions.

2. Transition of Interim Status Phase 2 Units From RCRA to CAA Permits

In response to our discussion in the proposal regarding RCRA permitting for interim status Phase 2 units (69 FR 21324), two commenters suggest that EPA establish policy and/or regulation that discourage further RCRA permitting work for interim status Phase 2 sources. Their comments are directed our statement in the proposal that the RCRA combustion permitting procedures in 40 CFR part 270 also continue to apply until you demonstrate compliance. As noted in this statement, we intended for Phase 2 sources to continue to be subject to RCRA permitting requirements for air emissions standards and related operating parameters, including trial burn planning and testing, until they have demonstrated compliance with the MACT standards by conducting a comprehensive performance test and submitting an NOC to the Agency. However, we also provided several factors that should be taken into consideration when determining whether to proceed with the RCRA permit process such as: the facility's permit status at the time the MACT rule becomes final, the facility's anticipated schedule for MACT compliance, the priorities and schedule of the regulatory agency, and the level of environmental concern at a given site (69 FR 21324).

To support their position, the commenters noted that time and resources would be conserved and duplicative and overlapping activities could be minimized if Phase 2 sources were permitted solely via Title V. Also, they argued that it would avoid expending resources to modify the RCRA permit once the source has demonstrated compliance with MACT. We agree with commenters that every effort should be made to conserve resources and avoid duplication to the extent possible. However, we do not believe it is appropriate to establish policy or regulation that permitting authorities must suspend the RCRA permit process (whether it pertains to interim status or renewals), especially in cases where considerable time and effort has been invested and the permit is close to final issuance. As before, we strongly encourage sources and regulatory authorities to work together to establish an approach that will provide for the most practical transition. For example, we strongly recommend that sunset provisions be included in a permit that will be issued well in advance of compliance with MACT to avoid duplication and a later modification to remove the duplicative RCRA conditions. Also, it would make more sense to transition a source to MACT compliance prior to issuing the RCRA permit if it will comply with MACT early.

3. Transition From Compliance With the Interim Standards to the Replacement Standards

A specific question that has been raised relates to the applicable standards and operating parameters that the source must comply with during the period between the rule's effective date for the Phase 1 Replacement Standards and submission of their new NOC. Upon the publication date of the rule, the Replacement Standards (and Phase 2 Standards) will become effective and sources will have 3 years to come into compliance. During this 3-year period, Phase I sources' existing title V permits will either be reopened to include the Replacement Standards, or the permitting authority will have incorporated the Replacement Standards during permit renewal. In this example, a Phase 1 source's Title V permit has been reopened, revised, or renewed and includes the Replacement Standards, the compliance date has not yet passed, no new documentation of compliance (DOC) for the replacement standards has been included in the operating record, and the source has not yet conducted a comprehensive performance test and submitted a new NOC (therefore it still has an NOC containing the operating parameters for compliance with the Interim Standards).

In the above scenario, the question asked is whether the source should comply with the Interim Standards in the current NOC or the Replacement Standards in the Title V permit. The

[245] As an example, a RCRA permit could specify a higher minimum operating temperature than what is necessary for the facility to achieve compliance with MACT. The lower minimum operating temperature under MACT may be sufficient, unless the RCRA permit authority determines that the higher RCRA temperature is necessary to limit risk to an acceptable level for that facility. There should be a connection between the RCRA limit and protection of human health and the environment when retaining a RCRA limit.

source should comply with the Interim Standards until the compliance date of the Replacement Standards. Although the Title V permit now includes the Replacement Standards, the permit will also include the Replacement Standards' future compliance date. With regard to the transition from the Interim Standards NOC to the Replacement Standards DOC, we are revising the regulations at § 63.1211(c) to render the NOC, which documented compliance with the Interim Standards, inapplicable upon inclusion of the DOC for the Replacement Standards in the operating record by the compliance date. Thus, the source will not be placed in a situation where it must continue to ensure compliance with the operating parameters established in the NOC for the Interim Standards, while seeking to comply with the Replacement Standards and operating parameters in its DOC. Although it can be assumed that the source would still be able to comply with its Interim Standard-based NOC because the Replacement Standards are the same as or more stringent than the Interim Standards, we believe that the revision to render the previous NOC inapplicable provides a clearer and more sensible approach.

4. Changes to Title V Permits

Both the Replacement Standards and the Phase 2 Standards will necessitate permit reopenings or revisions to some existing title V permits; other permits will incorporate the requirements upon renewal. 40 CFR §§ 70.7 and 71.7 include the requirements for Title V permit revisions, reopenings, and renewals. Also, approved Title V permitting authorities may have additional requirements. Please refer to the appropriate permitting authority and its individual Title V permits program to determine the necessary requirements and procedures.

With respect to incorporating minor revisions into the Title V permit, one commenter had asked, for example, whether revisions made to the NOC to reflect minor operating changes could be incorporated into the permit by reference rather than through the reopening procedures. Determining the appropriate Title V permit reopening or revision requirements is based on the nature of the change and the source specific permit terms and conditions, and is therefore difficult to generalize. We recommend that sources work with their Title V permit authorities to determine the appropriate requirements and procedures that are applicable to any specific situation. However, we would like to note that, when incorporating requirements by reference into the Title V permit is appropriate, this does not necessarily obviate the need for permit revisions if the material incorporated by reference is subsequently revised. For more information on incorporation by reference, please refer to the Office of Air Quality Planning and Standards' "White Paper Number 2 for Improved Implementation of the Part 70 Operating Permits Program" (March 5, 1996), Section II.E.2.c. This paper can be found at: *http://www.epa.gov/ttn/oarpg/t5/memoranda/wtppr-2.pdf.*

C. Are There Any Changes to the Proposed Class 1 Permit Modification Procedure?

In the NPRM, we proposed a new Class 1, with prior Agency approval, permit modification procedure to help further minimize potential conflicts between the RCRA permit requirements and MACT requirements. See 69 FR 21384 and proposed § 270.42(k). During implementation of the Interim Standards for Phase 1 sources, it became evident that there are two significant instances where RCRA permit limits may overlap with MACT requirements: during initial (and future) performance testing and during the period between placement of the documentation of compliance (DOC) in the operating record and the final modification of the RCRA permit after receipt of the NOC. We discussed several existing approaches (e.g., a class 2 or 3 modification, request for approval submitted via the RCRA trial burn plan or coordinated MACT/RCRA test plan, or through a temporary authorization) for addressing these instances, noting that none provided an optimal solution.

All commenters agreed that the new Class 1 modification procedure is the appropriate and most efficient method to enable specific RCRA permit conditions to be waived during instances of overlap referred to above. However, a few commenters were concerned with the requirements in proposed § 270.42(k)(2)(ii) and (k)(3), that require sources to submit their permit modification request upon approval of the test plan and the requirement for the Director to approve or deny the request within 30 days, or within 60 days with an extension. This timeframe is feasible only for those sources that have received approval of their test plans at least 60 days prior to their scheduled date for commencing their performance test. We acknowledged the potential impracticality of this requirement in the proposal, but at the time believed that few sources, if any, would conduct their performance tests without an approved test plan. While this still may be true, we have learned that sources who received extensions for testing (so that they would have an approved plan), typically commenced their test shortly after approval. Consequently, this still would not allow enough time to review and approve the permit modification before the test begins. Thus, the new Class 1 modification would be of no benefit to facilities that conduct their tests without an approved test plan, or to facilities that received extensions and need to begin their tests upon or shortly after approval of the test plan. Also, we found one other circumstance where the timeframes could be problematic: If a permitting agency has allowed sources to begin pretesting/testing upon approval of the test plan. Again, a source would not be able to have RCRA permit requirements waived in time to begin its test.

We agree with commenters that the proposed requirements in 270.42(k)(2)(ii) and (iii) do not provide any flexibility to waive RCRA permit limits for sources that (1) do not have an approved test plan but choose to conduct their test; (2) are granted an extension to their test date because they do not yet have an approved test plan; and (3) may begin testing upon approval of their test plans. Our original intent to require prior Agency approval for the new Class 1 permit modification procedure was to ensure that the proposed test conditions would be sufficiently protective when specific RCRA requirements are waived and that a source has met the regulatory requirements for performance test plans. We still believe that review and approval is an important step; however, we also believe it should not be a barrier and therefore, should occur in advance of a source commencing its performance test. As a result, we have revised the proposed regulatory language in 270.42(k)(2)(i) to specify that sources submit their permit modification requests with their test plans, to allow potentially up to one year for approval (*i.e.*, the performance test plan is due one year before the test is to begin). Also, so that approval does not impede the commencement of the performance test, we have revised the proposed language in 270.42(k)(2)(ii) so that the Director can choose whether to issue approval of the permit modification request contingent upon approval of the performance test plan.[246] In that respect,

[246] In all likelihood, we anticipate that the RCRA permit authority will have reviewed the modification request along with the test plans, worked with its Air counterparts and the source to resolve any concerns, and have prepared the permit

Continued

the RCRA permit authority would continue to have an extra measure of assurance in circumstances that may demand it.

D. What Permitting Approach Is EPA Finalizing for New Units?

1. Why Did EPA Propose a Separate Permitting Approach?

As discussed in the proposal, the current RCRA regulations at §§ 264.340, 265.340, 266.100, 270.19, 270.22, 270.62, and 270.66 do not address how or when new combustion units will comply with the MACT standards. Consequently, the part 270 regulations imply that a new unit must obtain a complete RCRA permit before it can demonstrate compliance with the MACT standards. It was never our intent for new units to develop a trial burn plan and provide suggested conditions for the various phases of operation in the RCRA permit application, given that these conditions will become inactive or need to be removed from their permits upon demonstrating compliance with MACT. To rectify our previous omission, we suggested several options that would allow units newly entering the RCRA permit process [247] (and that will comply with the Subpart EEE requirement upon start-up) to forego certain RCRA permit requirements and performance standards. In developing the options that would enable new units to forego certain RCRA requirements, we noted the importance of public participation opportunities under the MACT/CAA framework equivalent to those provided under the RCRA framework. Thus, each option was constructed in such a way that would streamline the RCRA requirements, but continue to provide early and frequent public participation commensurate with the requirements of the RCRA Expanded Public Participation Rule (60 FR 63417, December 11, 1995).

2. What Options Did EPA Propose for Permitting New Units?

In our preferred approach, we proposed that new units not be required to develop a trial burn plan and provide suggested conditions for the various phases of operation in their RCRA permit application. Instead, new units would only be required to address the remaining RCRA activities at the facility in their permit application (or modification request) including corrective action, general facility standards, other combustor specific concerns such as materials handling, risk-based emission limits and operating requirements, and other hazardous waste management units. While this approach appears to be ideal from the standpoint of reducing the regulatory burden to sources and RCRA permit authorities, we noted that even though a new unit will be required to meet the RCRA public participation requirements as part of the permit application process, the operations and emission information specific to the combustor would no longer be provided. Thus, we focused on certain compliance activities under the MACT/CAA framework (i.e., the Notification of Intent to Comply requirements) that would allow for combustor-specific information to be made available to the public as it would have been under the full RCRA permit process.

Regarding the three additional approaches or "options", each considered a different point in the RCRA permit process where a new unit could "transition" to compliance with the MACT standards (see 69 FR 21319). Under the first option, a new unit could transition to MACT compliance after it had submitted its RCRA Part B application. The Part B however, would not include the trial burn plan information. The new unit would only be required to discuss the compliance activities related to the combustor as part of the RCRA informal public meeting. In the second option, we proposed that a new unit would transition after its RCRA permit has been issued. Here, the new unit would be required to develop a trial burn plan which provided its proposed operations and emissions information and to discuss its compliance activities via the RCRA informal public meeting. Then, a permit would be issued, but it would not contain operating and emissions requirements in order to avoid a future modification to remove them. For the third option, the transition point would have been after the new unit places the DOC in its operating record, which is the compliance point for MACT. This option is more inclusive than the second because it requires the new unit to have a draft permit that covers the construction and shakedown period.

3. Which Option Is EPA Finalizing?

For today's final rule, we are adopting our preferred, proposed approach: new units will not be required to follow the full RCRA permitting process for establishing combustor operations and emissions. Thus, new units are not subject to the combustor-specific RCRA permit requirements and performance standards (i.e., to develop a trial burn plan, provide suggested conditions for the various phases of operation in their permit application, and subsequently operate under those conditions). However, because these units remain hazardous waste treatment units, they are still required to obtain a RCRA permit, or to modify an existing RCRA permit to include a new unit, prior to construction. They need only address the remaining hazardous waste management activities at the facility in their permit application (or modification request) including corrective action, general facility standards, other combustor specific concerns such as materials handling, risk-based emission limits and operating requirements, and other hazardous waste management units. As we noted in the previous section and will discuss again more thoroughly in the next section, we are relying on the NIC process to provide the public with the combustor-specific information that previously would have been provided under the full RCRA permit process.

Almost all commenters supported our preferred approach to not require that new units complete the full RCRA permit process and to rely on the NIC requirements and the MACT/CAA framework to provide a level of public participation that is commensurate with the requirements under RCRA. Commenters generally agreed that our preferred approach achieves this goal while streamlining the RCRA permit process for new units. One commenter felt that the Title V and New Source Review programs (NSR) provide sufficient requirements to regulate new combustion units. We disagree that either or both of those programs fully address the hazardous waste and public participation components commensurate with that provided by the approach we are finalizing today. For instance, a unit may be constructed and operating before a Title V permit is issued, which directly conflicts with RCRA's early public participation requirements. Also, in some instances, public participation may not be a required component of state issued NSR permits (see footnote regarding public participation and SIPs below). However, we do believe that the NSR program will play an important role regarding the exchange of information, as we will discuss in the section below. With respect to the remaining three options presented in the proposal (69 FR 21319–

modification approval prior to issuance of the test plan approval.

[247] Units "newly" entering the RCRA permit process refers to a newly constructed facility, thus newly constructed hazardous waste combustion unit; an existing facility that constructs a new unit; or an existing facility that converts a non-hazardous fuel combustion unit to a hazardous waste fuel combustion unit.

21320) that suggested a transitional approach (i.e., each option explored progressive points in the RCRA permit process where facilities could transfer over to MACT without fully completing the RCRA process), nearly all commenters were in agreement that they would require more work to implement than is necessary and consequently oppose them.

4. How Will Permitting for New Units Work?

In the proposed rule, we created an approach that utilizes the NIC requirements and the MACT/CAA framework with the intent of ensuring that the requirements of the RCRA Expanded Public Participation Rule would continue to be fulfilled. The four requirements for public participation as they relate to hazardous waste combustion units are: (1) Permit applicants must hold an informal public meeting before applying for a permit; (2) permit agencies must announce the submission of a permit application which will tell community members where they can view the application while the agency reviews it; (3) permitting agencies may require a facility to set up an information repository at any point during the permitting process if warranted; and (4) permitting agencies must notify the public prior to a trial (or test) burn.

As discussed in the preamble to the proposal (69 FR 21318), we believe that the NIC process addresses the first two RCRA public participation requirements. The NIC process requires a source to make its draft NIC, which discusses the source's plan for coming into compliance with the MACT standards, available for public review and to hold an informal public meeting to discuss the activities contained in the NIC. While the NIC process gives the public an early opportunity to participate in the unit's compliance planning process early on, a few components are still missing before we can consider the first 2 RCRA public participation requirements to be fulfilled under the MACT framework. One component is that there is no permit action associated with the NIC requirements. However, the NSR program can provide a permit mechanism that will determine whether or not a source may be constructed.[248] The steps associated with obtaining an NSR permit, or a "pre-construction" permit, are similar, but not necessarily identical to that required under RCRA. They are: (1) Preparation of the permit application (sources must provide the location, design, construction, and operation information) and participation in pre-application meetings; (2) issuance of permit application completeness determination by the State; (3) development and negotiation of draft permit; (4) opportunity for public notice and comment on the draft permit; (5) response of permitting authority to public comments; (6) possible administrative and judicial appeals; and (7) permit issuance/denial.[249]

A second component is that the NIC does not provide the information on the proposed combustor operations or emissions information that would normally be available as part of the RCRA process. To address these gaps between RCRA and MACT, we are requiring an approach similar to that which was proposed. New sources must: (1) Prepare a draft NIC and make it available to the public at the same time as their RCRA pre-application meeting notice; (2) provide a draft of their comprehensive performance test (CPT) plan (to the public) to coincide with the draft NIC and RCRA pre-application meeting notices; and (3) hold their NIC public meeting with their RCRA informal public meeting. The first two requirements ensure that the public is provided with most of the same information that would have been available via the RCRA trial burn plan prior to the source burning hazardous waste. Other information not required by the NIC or CPT plan, such as the combustion unit's design specifications will, in most cases, be available to the public through the NSR permit application. We recommend that sources submit a copy of their NSR permit application to the RCRA permit authority so that this information is readily available for development of the RCRA permit. The third requirement allows the public to inquire and comment on both the new unit's proposed activities and operations. By requiring new sources to develop, notice, and hold a combined public meeting that encompasses the NIC, draft CPT plan, and RCRA pre-application notice information, the public will be provided with all information related to the combustor's compliance plans as well as its operating plans and emissions estimates prior to burning hazardous waste. See new requirements in § 63.1212.

With respect to the requirements we are finalizing today, we received only one comment that expressed concern. The concern is that the requirement to submit the CPT plan is too early in the compliance process. For example, the RCRA application is submitted approximately 2–3 years before start-up whereas the CPT plan is required 1.5 years after the final NIC is due.[250] The commenter feels that the facility would not have enough time to learn about the "detailed nuances of the system". However, the commenter does note that it is possible to submit the CPT plan, but it will not be as complete or refined as it would be if it was submitted according to the deadline for existing units. We agree with the commenter that a considerable amount of planning is required of the source to be able to draft the CPT plan at such an early stage, but we are only requiring that a draft of the CPT plan be made available, with the final CPT plan due 6 months prior to the source's compliance date. Moreover, at this early stage, we liken the development of the draft CPT plan to the development of the trial burn plan. Even though it may not be as complete or refined as it will be when the final CPT plan is due, we believe that it will still be of benefit to the public and the regulatory authority, but also to the source in terms of advance planning for the design of the unit through start-up of the unit.

The components thus far, have satisfied the first (2) two RCRA public participation requirements. The third RCRA public participation requirement enables a regulatory authority to evaluate the need for and require a facility to establish and maintain an information repository. The establishment of an information repository is typically required only when there are concerns or unique information needs of a community. The purpose of the information repository is to make information regarding the facility (and combustion unit) available to the public during the permit issuance process and during the life of the permit. In the preamble, we noted that

[248] We believe that the majority of new units will be classified as major sources for NSR permitting (requiring either prevention of significant deterioration or nonattainment permits), however, those that do not, will likely be required to obtain a minor NSR permit. In few cases, new sources (e.g., newly constructed as opposed to modified) may not be required to obtain an NSR permit if its potential to emit does not exceed the NSR threshold level.

[249] With respect to numbers 4 and 5, many States omitted the public participation steps in their federally approved SIPs. This was the reason why Sierra Club had been opposed to our efforts to simply rely on NSR permitting to provide public participation opportunities that would have been otherwise provided under the traditional RCRA permit process for new units. Today, however, many SIPs have been revised to address public participation requirements.

[250] Comprehensive performance test plans are required to be submitted one year in advance of the scheduled test. The submittal date would be as late as 2.5 years after the effective date of the rule assuming no extensions are granted.

although the Title V permit process contains a provision that any materials relevant to the permit decision be made available to interested persons (see § 70.7(h)(2) and § 71.11(d)), the information may not be made available until well after the combustor is constructed and operating. Consequently, we have chosen to adopt additional provisions under the NIC requirements that parallel the requirements of § 124.33.

We had proposed two options that would allow a regulatory authority to require, on a case-by-case basis, a source to establish an information repository specific to the combustor. The first option was to place such a provision in the NIC regulations and the second option was to amend the applicability language in § 124.33 to include combustion sources that will comply with Part 63, subpart EEE upon start-up. Two commenters felt that the second option would create problems as far as organization (i.e., by modifying the RCRA regulations to include a provision solely for new units complying with MACT). We agree that the second option could be confusing and that it would be more appropriate to keep all new requirements for new units in one set of regulations. Therefore, we are finalizing a provision that will allow for an information repository to be established specific to the combustor (recall that a repository established pursuant to the RCRA permit will include documents relevant to the facility only), if deemed appropriate, under the NIC regulations. See new § 63.1212(c). Under the NIC regulations, the repository could include the NIC, test plans, draft Title V permit and application, reports, et cetera.

The fourth and final RCRA public participation requirement to be fulfilled is for the regulatory authority to notify the public of an impending trial burn or test burn. As discussed in the RCRA Expanded Public Participation Rule, the RCRA permit authority will typically provide the notice at least 30 days in advance of the test (60 FR 63426, December 11, 1995). Similarly, the MACT regulations require an existing or new unit to provide notice to the public that the CPT plan (and the continuous monitoring system performance evaluation test plan) is available for review. The regulations in § 63.1207(e)(2) fulfill this requirement. Although the CPT plan may not be approved before the public is notified, the intent is to provide notice to the public of a future test. We believe that the MACT regulations provide public notice of the test plans that are commensurate with the RCRA regulations and thus, no additional regulatory revisions or amendments are needed.

4.a. Process for New Units Seeking an Initial RCRA Permit

We anticipate that the process for new units seeking an initial permit will work as follows. Any new unit would begin the process by developing and compiling the information necessary for the RCRA draft permit (e.g., information required for the part A application at § 270.13, the relevant general information for the part B application according to Part 270) and the applicable NSR permit.[251] The information needed to compile the draft NIC and draft CPT plan would be gathered simultaneously, as if the source were developing the trial burn plan. When the source has compiled its RCRA permit application, draft NIC and draft CPT plan, it would submit a RCRA pre-application meeting notice at least 30 days prior to the date scheduled for the RCRA informal public meeting according to §§ 124.31(b) and (d). At the time of the RCRA pre-application meeting notice, the source would also issue notice of the NIC public meeting (at least 30 days prior to the NIC meeting) according to § 63.1210(c)(3), so that the two meetings can occur at the same time. In order for the public to be able to view all information relevant to the combustor before the combined RCRA pre-application and NIC public meeting, the source would make the draft NIC and draft CPT plan available to the public for review at the same time the notices for the meetings are issued. To aid the RCRA permit authority in its development of the draft RCRA permit (*i.e.*, mainly for purposes of evaluating risk), we strongly recommend that the source also provide copies of the draft NIC, draft CPT plan, and NSR application (if applicable) to the RCRA permit authority. It is our hope that the availability of information will expedite the development of the draft permit. All notices should be presented to the public in sufficient time to allow for a combined RCRA informal public meeting and NIC public meeting.

Following the combined public meeting, the source will submit its RCRA permit application and the RCRA regulatory authority will prepare and issue a draft permit. The public will then have an opportunity to comment on the draft permit and request a public hearing. Upon resolution of any issues surrounding the draft permit, a final RCRA permit will be issued. The RCRA process is the same as before, but should be reasonably shorter. Finally, the new unit may begin burning hazardous waste when it can assure it will operate in compliance with the MACT standards (*i.e.*, by placing a documentation of compliance in its operating record on the day it begins burning hazardous waste). See new regulatory language at § 63.1212(c). To aid readers in understanding the above process, we have included a pictorial timeline. Please see figure 2.

Finally, it may also be feasible to combine an NSR pre-application meeting and public notice of the draft NSR permit with the process described above. Thus, we recommend that sources work closely with their Air and RCRA permit agencies so that the NSR public notices and meetings may be coordinated with the RCRA and NIC notices and meetings so time and resources are efficiently utilized.

4.b. Process for New Units Modifying an Existing RCRA Permit

The process of adding a new unit to an existing permit is accomplished through a Class 3 permit modification (see § 270.42 (c) for requirements). The requirements governing public notices of the draft NIC, draft CPT plan, and holding a combined public meeting are essentially the same as new units seeking an initial permit. The process is as follows. The source prepares and submits its RCRA permit modification request (and if applicable, NSR application). It must then publish a notice of the modification request seven days later, followed by a public meeting no earlier than 15 days after publication of the notice for the modification request, and no later than 15 days before the close of the 60-day comment period. As with new units that are submitting an initial RCRA permit application, it is also important for sources seeking to modify their permit to coordinate their NIC public meeting with their RCRA permit modification public meeting. This is made possible due to the flexibility of the NIC public meeting; it can be held any time prior to the 10 month deadline. After the combined public meeting and the close of the comment period, the permit authority will either grant or deny the modification request. If approved, the source may then begin construction or modification of the unit. To aid readers in understanding the timing of the

[251] Because the information required for NSR permit is less comprehensive than a RCRA permit, it allows for a much shorter time period for issuance. The average time for issuing a PSD permit, for example, after receiving an application is slightly more than 7 months, but varies depending upon public involvement and negotiation of the application content. USEPA. Docket A–2001–19, Document II–A–01. *NSR 90-Day Review Background Paper*, June 22, 2001.

above process, we have included a pictorial timeline. Please see figure 2.

Again, it may be feasible to combine an NSR pre-application meeting and public notice of the draft NSR permit with the process described above. Thus, we recommend that sources work closely with their Air and RCRA permit agencies so that the NSR public notices and meetings may be coordinated with the RCRA and NIC notices and meetings so time and resources are efficiently utilized.

E. What Other Permitting Requirements Were Discussed in the Proposal?

At proposal, we discussed where most Phase 1 sources would be in terms of their transition from their RCRA permit requirements to compliance with the MACT Interim Standards (see 69 FR 21321). The transition process was discussed with respect to both the RCRA permit and the Title V permit. However, when we discussed the Title V permit requirements in the proposal, we did not elaborate on the transition between the Interim Standards and Replacement Standards. Because we believe that such a discussion would be helpful to readers, we have included general information describing how the transition process would work for most sources in Section B. Did Commenters Express any Concerns Regarding the Current Permitting Requirements?, subsections 3 and 4.

For Phase 2 sources, we proposed the same permitting approach as we did for Phase 1 sources. Today, we are finalizing as proposed, the following for Phase 2 sources: (1) the new Phase 2 emissions standards will be placed only in the CAA regulations at 40 CFR part 63, subpart EEE, and be implemented through the air program; (2) with few exceptions, the analogous standards in the RCRA regulations no longer apply once a facility demonstrates compliance with the MACT standards in subpart EEE and any duplicative requirements have been removed from the RCRA permit; and (3) the new standards will be incorporated into operating permits issued under Title V of the CAA rather than be incorporated into RCRA permits. Consequently, we are finalizing the proposed changes to §§ 270.22 and 270.66 to implement the above. Also applicable to Phase 2 sources via today's final rule are the changes and additions we finalized in the 1999 final rule for Phase 1 sources. These include a streamlined RCRA permit modification procedure to allow sources to make upgrades to comply with MACT (§§ 270.42(j) and 270.42 appendix I, section L.9), a second streamlined RCRA permit modification procedure to remove conditions from a permit that are no longer applicable (§ 270.42 appendix I, section A.8), an addition to § 270.235 to specify conditions for start-up, shutdown, and malfunction plan and integrate them with the CAA program, and an amendment to the interim status regulations at § 270.72 to exempt interim status facilities from the reconstruction limitation when making upgrades to comply with MACT.

Also, we are finalizing three new permitting changes that are applicable to both Phase 1 and 2 sources. Two have been discussed previously in this section and are: (1) A new streamlined RCRA permit modification procedure designed to reduce overlap during the transition from RCRA to MACT (§§ 270.42(k) and 270.42, appendix I, L.10); and (2) regulatory provisions stating that new units are no longer subject to the full array of RCRA combustion permitting requirements. The third change is discussed above in Section IX. Site-Specific Risk Assessment Under RCRA and finalizes our response to a petition for rulemaking with respect to site-specific risk assessments (SSRAs). As part of this change we have decided to adopt regulatory language that specifically provides clarification of authority for RCRA permit writers to evaluate the need for and, where appropriate, require SSRAs and to add conditions to RCRA permits that they determine, based on the results of an SSRA, are necessary to protect human health and the environment.

Last, as explained in part four section II.A, we are finalizing our decision to regulate emissions of dioxin/furans, mercury, polycyclic organic matter, and polychlorinated biphenyls from Phase 2 area sources under section 112(d).[252] This means that Phase 2 area sources are subject to MACT standards only for these hazardous air pollutants (HAP) in the final rule. To reiterate, they are: Dioxin/furans, mercury, and polycyclic organic matter (controlled by the surrogates DRE and carbon monoxide/hydrocarbon). For the remaining HAP (hydrogen chloride and chlorine gas and metals other than mercury), Phase 2 area sources may either comply with the MACT standards for Phase 2 major sources or continue complying with the RCRA standards and requirements of their RCRA permit.


In the 2004 proposal, we stated that we were not making a positive area source finding for Phase 2 area sources as we have for Phase 1 area sources (69 FR 21212 and 21325). Regardless of this, however, the Phase 2 area sources are still subject to the requirement to obtain a Title V permit because they are subject to section 112 standards under this subpart. See § 502(a) of the CAA and 40 CFR §§ 70.3(b)(2) and 71.3(b)(2).

It is important to note that the Title V applications for the Phase 2 area sources will need to contain emissions information relative to all regulated air pollutants (to determine applicable requirements, fees, etc.) that are being emitted from the units subject to the MACT standards, not just the specific HAP pollutants regulated by the MACT standards (see §§ 70.5(c)(3)(i) and 71.5(c)(3)(i)). Although, the permit itself would contain standards only for the HAP subject to MACT standards (the § 112(c)(6) HAP). A Phase 2 area source which chooses to control hydrogen chloride, chlorine gas, and metals other than mercury by continuing to comply with the relevant RCRA standards and the requirements of its RCRA permit should note this choice in its Title V application and cite to the relevant requirements of this subpart. This will help ensure that the permitting authority is aware that these requirements apply in lieu of the MACT standards for Phase 2 major sources. The permitting authority should also document this choice in the statement of basis for the source's Title V permit. See §§ 70.7(a)(5) and 71.7(a)(5). Finally, for the units at a source which are subject to the subpart EEE MACT standards, all CAA applicable requirements to which these units are subject, *e.g.*, State Implementation Plan requirements, not just the relevant Subpart EEE requirements, must be included in the Title V permits issued to these sources. See §§ 70.3(c)(2) and 71.3(c)(2). For more information regarding § 112(c)(6) and how it relates to Phase 2 area sources, see Part Four, Section II.A., "Area Source Boilers and Hydrochloric Acid Production Furnaces".

BILLING CODE 6560-50-P


[252] As explained in the Comment Response Document vol. V, although § 502(a) allows EPA to exempt area sources from title V permitting requirements if EPA finds that those requirements would be (among other things) "unnecessarily burdensome", we believe that Title V requirements remain appropriate for these sources given the highly toxic nature of the HAP and the importance of affording opportunity for public participation as provided for in the Title V permit issuance process.

Figure 1. Time Line for Phase 1 Replacement Standards and Phase 2 Standards[253]



[253] Because of the variability of the Title V program requirements, most Title V permit actions (application due dates, revisions, reopenings, etc.) are not included in this timeline. Please refer to the particular source's current Title V permit status, the Title V regulations, and the individual permitting authority's Title V program requirements.

Figure 2. NIC and CPT Plan Time Line for New Units



Part Five: What Are the CAA Delegation Clarifications and RCRA State Authorization Requirements?

I. Authority for This Rule

Today's rule amends the promulgated standards located at 40 CFR part 63, subpart EEE. It amends the standards for the Phase 1 source categories—incinerators, cement kilns, and lightweight aggregate kilns that burn hazardous waste, and it also amends subpart EEE to establish MACT standards for the Phase 2 source categories—boilers and hydrochloric acid production furnaces that burn hazardous waste. Additionally, this rule amends several RCRA regulations located in 40 CFR part 270 to reflect changes in applicability, addition of a new permit modification procedure, and additions related to site-specific assessments and permitting.

II. CAA Delegation Authority

Before discussing the clarifications being finalized today, it is important to first highlight a few key aspects of delegation authority. Recall from the proposal that a state, local, or tribal (S/L/T) agency must be delegated authority under CAA section 112(l) before it can exercise the delegable provisions' authorities. The delegable authorities can be found in 40 CFR 63.91(g)(1)(i), also known as Category I Authorities. A S/L/T agency that has applied for and received delegation authority can approve: test plans, requests for minor and in most cases, intermediate changes to monitoring and test methods, performance test waivers, and several other Category I Authorities. Please note that even though a S/L/T agency may have an approved Title V permit program, it cannot exercise delegable authorities or be the primary enforcement authority if it has not received delegation authority under CAA section 112(l). Moreover, when a S/L/T agency has not taken delegation of a section 112 standard, the agency can only incorporate the section 112 standard's requirements into its Title V permits, (and then implement and enforce these requirements through its title V permits) when it has adequate authority under State, local, or tribal law which allows it to conduct the above actions without delegation. See, *e.g.*, the proposed Federal Plan for Commercial and Industrial Solid Waste Incinerators, November 25, 2002 (67 FR 70640, 70652). Please also refer to 69 FR 21335 of the proposal and the fact sheet entitled, Clean Air Act Delegation for the HWC NESHAP at: *http://www.epa.gov/epaoswer/hazwaste/combust/toolkit/factshts.htm* to learn more about the advantages of receiving delegation authority.

Also, we would like to point out that there are several delegation options that S/L/T agencies can receive. Regardless, many S/L/T agencies choose the "straight delegation" option when applying for delegation approval. Straight delegation means that these agencies have agreed to implement and enforce federal MACT standards as they have been written in the promulgated requirements. As a result, many EPA Regions and states have established memoranda of agreement that essentially provide automatic delegation of each future MACT, as opposed to the state applying for delegation of each future MACT, which requires a rulemaking to implement. For more information related to the delegation options and procedures, please refer to the fact sheet, Clean Air Act Delegation for the HWC NESHAP at: *http://www.epa.gov/epaoswer/hazwaste/combust/toolkit/factshts.htm* and EPA's delegation website at: *http://www.epa.gov/ttnatw01/112(l)/112-lpg.html.*

III. Clarifications to CAA Delegation Provisions for Subpart EEE

In the proposal, we discussed the need to provide additional clarification for the delegable and non-delegable authorities within Subpart EEE based upon our implementation experience with the Phase 1 Interim Standards and the Clarifications to Existing National Emissions Standards for Hazardous Air Pollutants Delegation' Provisions final rule published on June 23, 2003 (68 FR 37334). Although the June 23, 2003 final rule provided clarification and streamlined the delegable provisions for each existing NESHAP, it overlooked several non-delegable and delegable authorities within Subpart EEE. It provided clarification on the non-delegable authorities of Subpart EEE as they relate to major alternatives to the standards themselves and to test methods, monitoring, or recordkeeping and reporting under the General Provisions.[254] However, it omitted major alternatives specific to Subpart EEE such as: test methods under §§ 63.1208(b) and 63.1209(a)(1); monitoring under § 63.1209(a)(5) and; recordkeeping and reporting under § 63.1211(a) through (d). Therefore, the following paragraphs will explain which authorities in Subpart EEE are delegable and are not delegable to S/L/T agencies that have been delegated authority and will provide some examples of or references to alternative requests associated with each delegable or non-delegable provisions authority.

To review, the regulations at 40 CFR 63.90 define three types of alternative requests. Alternative requests or "changes" to a particular delegable or non-delegable provision are classified as major, intermediate, or minor depending upon the degree (*i.e.*, potential to be nationally significance, potential to reduce the stringency of the standard, etc.) of change being requested. An alternative request that qualifies as a major change is not delegable to S/L/T agencies, even when they have delegation authority. These requests must be sent to the EPA Region or, if it concerns a test method under §§ 63.7(e)(2)(ii) and (f), 63.1208(b) and 63.1209(a)(1) or a standard under §§ 63.1200, 63.1206(a), or 63.1216–63.1221, then it must be sent to our Office of Air Quality Planning and Standards (OAPQS).[255] An alternative request that qualifies as an intermediate or minor change is delegable. However, the EPA Region may choose whether or not they will delegate authority to S/L/T agencies to approve intermediate and, even some minor changes during the delegation approval process. In addition to the regulations, the guidance document entitled, How to Review and Issue Clean Air Act Applicability Determinations and Alternative Monitoring (EPA 305–B–99–004, February 1999) provides a listing of delegable and non-delegable authorities in Tables 1 and 2, as well as descriptions and examples of major, intermediate, and minor changes in Attachment 1.

A. Alternatives to Requirements

Any change to a promulgated standard is considered a major change and as noted above, must be sent to OAQPS (see contact information in footnote). The reason why a change to a standard must be sent to EPA Headquarters is because the change must be established through national rulemaking, regardless of the degree of change sought. Thus, only OAQPS can approve alternative requests for changes to standards. Additionally, any change to applicability requirements and compliance dates (*e.g.*, requirements that ensure that the standards are achieved as EPA intended) are also

[254] For example, the final rule included approval of alternatives to requirements in §§ 63.1200, 63.1203, through 63.1205, and 63.1206(a); approval of major alternatives to test methods under § 63.7(e)(2)(ii) and (f); approval of major alternatives to monitoring under § 63.8(f) and; approval of major alternatives to recordkeeping and reporting under § 63.10(f).

[255] For contact information, please visit *www.epa.gov/ttn/emc/staffdir.html.*

considered major and also must be sent to OAQPS for approval. Specific to Subpart EEE, alternative requirement requests including those pursuant to §§ 63.1200, 63.1206(a), or 63.1216–63.1221 are considered major changes and consequently are non-delegable. The regulations at § 63.1214(c) correctly identified the requirements in Subpart EEE, however we have revised them today (as we proposed) to reflect the new sections that house the Phase 1 Replacement Standards and Phase 2 Standards.

There are a few exceptions to the above, however. Subpart EEE incorporates specific provisions for sources to request alternative standards which are delegable because they have been established through rulemaking. In fact, several alternative standards are self-implementing meaning that the source only need specify in their DOC which standard it will comply with. The alternative to the particulate matter standard in § 63.1206(b)(14) and the emissions averaging standards for cement kilns with in line kiln raw mills and preheater or preheater/precalciner kilns with dual stacks in § 63.1204(d) and (e) are three examples. There are also alternative standards that sources may petition to comply with. They include: Alternatives to the standards for existing and new LWAKs at § 63.1206(9) and cement kilns at § 63.1206(b)(10) and the alternative risk-based standard for total chlorine at § 63.1215. Sources choosing to comply with these alternative standards must receive approval from their delegated S/L/T agency prior to implementing them.[256] With respect to changes to compliance dates, requests under § 63.1213 specifically allow sources to request an extension to the compliance date for the installation of pollution prevention or waste minimization controls. Again, because this provision has been specified in subpart EEE, it is not considered a major change and is delegable.

B. Alternatives to Test Methods

With respect to test methods, we noted above that the final delegations rule stated that major alternatives to the test methods at §§ 63.7(e)(2)(ii) and (f) were not delegable. Therefore, as we proposed, it is necessary to add major alternatives to 63.1208(b), which specifies the test methods sources must use to determine compliance with subpart EEE. Also, we are adding the CEMS monitoring requirement under § 63.1209(a)(1). It is regarded as a test method because it serves as a benchmark method for demonstrating compliance with the emission standards. Both sections are delegable to S/L/T agencies as long as they have been delegated authority and as long as the alternative requests comprise minor or intermediate changes. However, a major change to either of these test method sections must be sent to OAQPS for approval.[257] Only OAQPS can approve major changes to test methods because they are designated in the standard as the means for determining compliance with an emission standard. The proposed revisions to § 63.1214 are finalized today to include major alternatives to test methods under §§ 63.1208(b) and 63.1209(a)(1) as non-delegable authorities.

C. Alternatives to Monitoring

For monitoring, the final delegations rule stated that major alternatives to monitoring at § 63.8(f) were not delegable, but did not reference monitoring specific to subpart EEE. In subpart EEE, the monitoring requirements are located in § 63.1209. This section also includes two provisions specific to alternative monitoring, thus removing some of the "guesswork" when trying to discern whether a request for change is minor, intermediate, or major. One is located at § 63.1209(a)(5), Petitions to use CEMS for other standards and the other is located at § 63.1209(g)(1), Alternative monitoring requirements other than continuous emissions monitoring systems. Each is discussed in the following paragraphs.

In the proposal, we explained that a request to use other monitoring in lieu of a CEMS is always considered a major change due to CEMS generally being considered a more accurate measure of compliance. However, if a source requests to use a CEMS in lieu of a required operating parameter, it may be considered an intermediate change. Since publication of the proposal, performance specifications have been promulgated for PM CEMS (and mercury CEMS).[258] Consequently, today we view requests per § 63.1209(a)(5) to use PM CEMS as intermediate changes to monitoring. Although the implementation of PM CEMS according to PS–11 (69 FR 1786 and 40 CFR part 60, Appendix B; January 12, 2004) and Procedure 2 (see also 40 CFR part 60, Appendix F) is largely "self-implementing," sources wishing to apply to use of PM CEMS should develop and submit QA/QC plans specifying audit frequencies to account for site-specific stack conditions. We believe that other site-specific issues that may need to be addressed prior to use of the CEMS, such as a source's request to deviate from PS–11 or a source's selection of the correct correlation curve(s), are properly addressed under EPA's established policies and procedures for alternative method requests. We believe that a petition to use PM CEMS under § 63.8(f) is still the appropriate mechanism, but that sources can submit their petitions to their delegated S/L/T agency for review and approval, and we recommend that EPA Regional offices work with these agencies to monitor implementation. Thus, with the exception of petitions to use PM CEMS in lieu of an operating parameter which is considered an intermediate change, we are finalizing our proposed revision to § 63.1214(c) to include major alternatives to monitoring under § 63.1209(a)(5) as a non-delegable authority.

Section 63.1209(g)(1), Alternative monitoring requirements other than continuous emissions monitoring systems, contains the other alternative monitoring provision. This provision allows sources to request alternative monitoring methods to monitor compliance, except for those standards that must be monitored with a CEMS (e.g., those in § 63.1209(a)(1)), and to request a waiver of an operating parameter limit. We provided several examples of alternative parameter monitoring for which a request may be submitted under this section in the proposal at 69 FR 21337. They include use of: a different detector, different monitoring location, a different method as recommended by the manufacturer, or a different averaging period that is more stringent than the applicable standard. In the proposal, we stated that we believe the majority of requests submitted pursuant to § 63.1209(g)(1) are not major and discussed in the preamble amending the language in § 63.1209(g)(1) so that these types of changes could be reviewed and approved by the delegated S/L/T agency. However, when we added

[256] The alternative risk-based standard for total chlorine at § 63.1215 requires sources to submit their eligibility demonstration to both the delegated S/L/T agency and to the Risk and Exposure Assessment Group in Research Triangle Park, NC for review, even though the delegated S/L/T agency can grant or deny approval.

[257] For contact information, please visit *www.epa.gov/ttn/emc/staffdir.html*.

[258] Although performance specifications have been promulgated for mercury CEMS, there has not been as much experience in implementing these devices for hazardous waste combustion sources (or similar sources) as there has been for PM CEMS at this time. Therefore, we believe it appropriate to continue sending requests to use mercury CEMS in lieu of an operating parameter to the appropriate EPA Region for review and approval.

language to § 63.1209(g)(1) to allow for the above, we inadvertently referred to an approved Title V program instead of a S/L/T agency which has taken delegation of subpart EEE. We have corrected and finalized the proposed language. Therefore, whether minor or intermediate, requests under § 63.1209(g)(1) may be sent to your delegated S/L/T agency for review and approval.

Please note that 63.1209(g)(1) cannot be used when requesting major changes to the monitoring required by the standard. Such changes typically involve new unproven monitoring methods. Unproven monitoring methods refer to those where the technology or procedures are not generally accepted by the scientific community (§ 63.90(a)). If you are uncertain whether your request constitutes a new unproven monitoring method, which is considered a major change, you should submit your request to your EPA Region. The regulatory language in 63.1209(g)(1) has been revised to reflect this clarification.

D. Alternatives to Recordkeeping and Reporting.

As with the others, the final delegation provisions' rule only cited the waiver of recordkeeping and reporting requirements of § 63.10(f) as a non-delegable provision. Thus, it is necessary to add the relevant subpart EEE recordkeeping and reporting requirements of § 63.1211. Section 63.1211 is delegable in its entirety to S/L/T agencies unless an alternative request is determined to be a major change. An alternative request that is a major change, such as decreases in record retention for all records, must be sent to your EPA Region for review and approval. Similar to the monitoring section, § 63.1211 contains a specific alternative provision. Section 63.1211(d) Data Compression, allows sources to request to use data compression techniques to record data from CMS and CEMS on a frequency less than that required by § 63.1209. We view the alternative request to be a minor change because available guidance provides criteria for defining fluctuation and data compression limits. See 64 FR 52961 and 52962, September 30, 1999. Therefore, requests submitted under 63.1211(d) can be consistently evaluated by delegated S/L/T agencies. Section 63.1214(c) has been revised to specify that major alternatives to 63.1211(a)—(c) are non-delegable authorities.

E. Other Delegation Provisions

Although not discussed in the proposal, it is important to note that issuing applicability determinations is another delegable authority. The EPA document How to Review and Issue Clean Air Act Applicability Determinations and Alternative Monitoring (EPA 305–B–99–004, February 1999) provides guidance regarding who has the lead for issuing applicability determinations. In general, Regions may delegate the authority to issue applicability determinations to S/L/T agencies when the determinations are routine in nature. However, delegation of authority for certain applicability determinations should be retained by the Regions. These include applicability determinations that: (1) Are unusually controversial or complex; (2) have bearing on more than one state or district (are multi-Regional); (3) appear to create conflict with previous policy or determinations; (4) are a legal issue which has not previously been considered (a matter of first impression); or (5) raise new policy questions. It is recommended that Regional offices require notification when S/L/T agencies issue applicability determinations.

IV. RCRA State Authorization and Amendments to the RCRA Regulations

Under section 3006 of RCRA, EPA may authorize qualified states to administer their own hazardous waste programs in lieu of the federal program within the state. Following authorization, EPA retains enforcement authority under sections 3008, 3013, and 7003 of RCRA, although authorized states have primary enforcement responsibility. The standards and requirements for state authorization are found at 40 CFR Part 271.

Prior to enactment of the Hazardous and Solid Waste Amendments of 1984 (HSWA), a State with final RCRA authorization administered its hazardous waste program entirely in lieu of EPA administering the federal program in that state. The federal requirements no longer applied in the authorized state, and EPA could not issue permits for any facilities in that state, since only the state was authorized to issue RCRA permits. When new, more stringent federal requirements were promulgated, the state was obligated to enact equivalent authorities within specified time frames. However, the new federal requirements did not take effect in an authorized state until the state adopted the federal requirements as state law.

In contrast, under RCRA section 3006(g) (42 U.S.C. 6926(g)), which was added by HSWA, new requirements and prohibitions imposed under HSWA authority take effect in authorized states at the same time that they take effect in unauthorized states. EPA is directed by the statute to implement these requirements and prohibitions in authorized states, including the issuance of permits, until the state is granted authorization to do so. While states must still adopt HSWA related provisions as state law to retain final authorization, EPA implements the HSWA provisions in authorized states until the states do so.

Authorized states are required to modify their programs only when EPA enacts federal requirements that are more stringent or broader in scope than existing federal requirements. RCRA section 3009 allows the states to impose standards more stringent than those in the federal program (see also 40 CFR 271.1). Therefore, authorized states may, but are not required to, adopt federal regulations, both HSWA and non-HSWA, that are considered less stringent than previous federal regulations.

We discussed in the proposal which RCRA regulations we intended to amend and their impact on state authorization procedures. Today, we are finalizing those amendments in §§ 270.10, 270.22, 270.32, 270.42, 27062, 270.66, and 270.235. In addition, we are amending the regulations in §§ 264.340 and 266.100 to reflect changes that have been made based upon comments. Today's amendments fall under both HSWA and non-HSWA authorities. That is, changes made to regulations applicable to boilers and industrial furnaces are promulgated under HSWA authority, whereas changes made to regulations applicable to incinerators are promulgated under non-HSWA authority. [259] All of the amendments made today are considered to be either less stringent or equivalent to the existing Federal program, which means that states are not required to adopt and seek authorization for these provisions regardless of whether they are finalized under non-HSWA or HSWA authorities. Nevertheless, we strongly encourage states to become authorized for today's amendments.

[259] When new requirements and prohibitions (that are more stringent than the previous federal regulations) are imposed under non-HSWA authority, the new federal requirements do not take effect in an authorized state until the state adopts the federal requirements as law. Conversely, when imposed under HSWA authority, the new federal requirements are federally enforceable in an authorized state until the necessary changes to a state's authorization are approved by EPA.

Experience has shown that when states have been authorized for previous amendments (i.e., those finalized in the 1999 rule) that were intended to facilitate the transition from the RCRA program to MACT and the CAA Title V program, the process has proven to be less cumbersome. For a more detailed discussion of non-HSWA and HSWA authorities with respect to how and when they take effect, please refer to the proposal's preamble discussion at 69 FR 21338.

Several RCRA sections that have been enacted as part of HSWA apply to today's rule: 3004(o), 3004(q), and 3005(c)(3). Thus, if a state is not authorized for the boiler and industrial furnace regulations, these provisions are federally enforceable in an authorized state until the necessary changes to a state's authorization are approved by us. See RCRA section 3006, 42 U.S.C. 6926. We are adding today's requirements to Table 1 in 271.1(j) where rulemakings promulgated pursuant to HSWA authority are identified.

Part Six: Impacts of the Final Rule

I. What Are the Air Impacts?

Table 1 below shows the emissions reductions achieved by the final rule for all existing hazardous waste combustors. For Phase I sources—incinerators, cement kilns, and lightweight aggregate kilns—the emission reductions represent the difference in emissions between sources controlled to today's standards and estimated emissions when complying with the interim MACT standards promulgated on February 13, 2002. Thus, the significant emissions reductions already achieved by the interim standards are not reflected in the estimates shown in Table 1.[260] For Phase II sources—solid fuel boilers, liquid fuel boilers, and hydrochloric acid production furnaces—the reductions represent the difference in emissions between today's standards and the current baseline of control provided by 40 CFR part 266, subpart H.

Nationwide baseline HAP and particulate matter emissions from hazardous waste combustors are estimated to be approximately 12,650 tons per year at the current baseline level of control. Depending on the number of facilities demonstrating compliance with health-based compliance alternatives for total chlorine, the total reduction of HAP and particulate matter for existing sources could be between approximately 2,260 and 3,380 tons per year. A discussion of the emission estimates methodology and results are presented in "Technical Support Document for HWC MACT Replacement Standards, Volume V: Emission Estimates and Engineering Costs" that is available in the docket.

TABLE 1.—NATIONWIDE ANNUAL EMISSIONS REDUCTIONS OF HAP AND OTHER POLLUTANTS

Pollutant	Estimated emission reductions (tons per year)
Dioxin/furans[1]	0.20
All HAP metals	19.5
Mercury	0.21
Semivolatile metals (Cd, Pb)	2.9
Low volatile metals (As, Be, Cr)	6.5
Other metals (Co, Mn, Ni, Sb, Se)	9.9
HCl and chlorine gas[2]	1220
Particulate matter	2,140

[1] Dioxin/furan emission reductions are expressed as grams TEQ per year.

[2] We are promulgating health-based compliance alternatives for total chlorine for hazardous waste combustors other than hydrochloric acid production furnaces in lieu of the MACT technology-based emission standards (see Part Four, Section VII of the preamble for details). Given that a number of sources may elect to comply with the health-based compliance alternatives, the estimated reductions of total chlorine represent an upper bound estimate.

II. What Are the Water and Solid Waste Impacts?

We estimate that water usage for existing sources will increase between 400 million and 1.6 billion gallons per year as a result of today's rule. The upper range estimate represents the water usage assuming no sources elect to comply with the health-based compliance alternatives for total chlorine, while the lower range estimate represents water usage assuming all sources elect the alternative. Water usage increases are estimated for reducing combustion gas temperatures with evaporated spray coolers for dioxin/furan control as well as for new particulate matter and acid gas air pollution control equipment. The increased water usage will also result in an increase in wastewater generation. Depending on the number of sources that elect to comply with the health-based compliance alternatives for total chlorine, we also estimate that up to 775 million gallons of wastewater may be generated.

We estimate that the generation of solid waste will increase between approximately 8,700 tons and 12,200 tons per year depending on the number of sources that elect to comply with the health-based compliance alternatives for total chlorine. Of these totals, approximately 250 tons per year will be classified as hazardous waste subject to RCRA Subtitle C regulations. We estimate the remainder—between 8,450 and 11,950 tons per year—will be classified and managed as a non-hazardous industrial waste subject to Subtitle D of RCRA. The costs associated with these disposal and water requirements are accounted for in the annualized compliance cost estimates. A discussion of the methodology used to estimate impacts is presented in "Technical Support Document for HWC MACT Replacement Standards, Volume V: Emission Estimates and Engineering Costs" that is available in the docket. We note that the nonair quality health and environmental impacts effects for both floor and beyond-the-floor options are discussed in the technical support document and are part of our consideration of such factors under section 112(d)(2).

III. What Are the Energy Impacts?

We estimate that the national annual energy usage as a result of this rule will increase between approximately 73 million and 85 million kilowatt hours (kWh) depending on the number of sources that elect to comply with the health-based compliance alternatives for total chlorine. The increase results from the electricity required to operate air pollution control equipment installed to meet the standards. The increase energy usage costs are accounted for in the annualized compliance cost estimates. A discussion of the methodology used to estimate impacts is presented in "Technical Support Document for HWC MACT Replacement Standards, Volume V: Emission Estimates and Engineering Costs." We note that the energy effects for both floor and beyond-the-floor options are discussed in the technical support document and are part of our consideration of such factors under section 112(d)(2).

IV. What Are the Control Costs?

Control costs, as presented in this section, refer only to engineering, operation, and maintenance costs associated with unit/system upgrades necessary to meet the final standards. These costs do not incorporate any market-based adjustments. All costs presented in this section are annualized estimates in 2002 dollars.

[260] USEPA, "Final Technical Support Document for HWC MACT Standards, Volume V: Emission Estimates and Engineering Costs," Section 3, July 1999.

We estimate there are a total of 267 sources [261] that may be subject to requirements of this final rule. Of this total, there are 116 boilers (104 liquid fuel boilers plus 12 solid fuel boilers), 92 on-site incinerators, 25 cement kilns, 15 commercial incinerators, nine (or seven) lightweight aggregate kilns, and ten hydrochloric acid (HCl) production furnaces.

Total national private sector engineering costs for the final standards are estimated at $40.2 million per year.[262] This estimate reflects total non market adjusted upgrade costs (engineering, plus administrative and permitting), excluding chlorine control costs.[263] All Phase II sources combined (liquid fuel boilers, coal fired boilers, and HCl production furnaces) represent 86 percent of this total. The average private sector engineering cost, *excluding* permitting and administrative, is projected to be highest for liquid fuel boilers, at $256,300 per source. Coal fired boilers are second at approximately $170,246 per source. Total engineering costs to cement kilns and HCl production furnaces are estimated to average $113,600, and $16,645 per source, respectively. Commercial incinerators are projected to experience engineering costs averaging $12,300 per source. On-site incinerators and LWAKs will face the lowest engineering costs at $10,200 and $3,330, respectively.

For all Phase I sources (141 sources; commercial incinerators, on-site incinerators, cement kilns, and lightweight aggregate kilns), total average annualized non market-adjusted compliance costs (*including* permitting and administrative [264]) are estimated at $39,700 per source. The combined Phase II sources (126 sources; solid and liquid fuel-fired boilers and hydrochloric acid production furnaces) have total average annualized non market-adjusted compliance costs of approximately $274,500 per source. Across all sectors covered by today's rule (Phase I and Phase II sources), total annualized compliance costs were found to average $150,500 per source.

Private sector engineering costs (control) costs have also been assessed on a per ton (U.S.) basis. Captive energy recovery sources (solid and liquid fuel-fired boilers, and hydrochloric acid production furnaces) burned a total of 944,667 tons of hazardous waste in 2003. These facilities are projected to experience the highest average incremental control costs, at approximately $37 per ton of waste burned. Commercial energy recovery sources (cement kilns and LWAKs), burning an estimated 999,076 tons in 2003, are projected to experience average incremental control costs of approximately of $3.00 per ton. Captive (on-site) and commercial incinerators burn an estimated 925,828 tons and 447,524 tons per year, respectively. These sources are estimated to experience average incremental engineering costs of $2.15 per ton and $0.80 per ton, respectively.

The aggregate control costs presented in this section do not reflect the anticipated real world cost burden on the economy. Any market disruption, such as the requirements in this final rule, will cause a short-term disequilibrium in the hazardous waste burning market, resulting in a natural economic process designed to reach the new market equilibrium. Actual cost impacts to society are more accurately measured by taking into account market adjustments in the targeted industry, plus secondary (societal) costs. Total market-adjusted costs plus secondary costs are commonly termed Social Costs, and are generally less than total engineering costs due to efficiencies implemented during the market adjustment process. Social Costs theoretically represent the total real world costs of all goods and services society must give up in order to gain the added protection to human health and the environment. Social Costs are presented in Part VI of this Section.[265]

V. What Are the Economic Impacts?

Economic impacts may be measured through several factors. This section presents estimated economic impacts relative to market exits, waste reallocations, and employment impacts. Economic impacts presented in this section are distinct from social costs, which correspond only to the estimated monetary value of market disturbances.

A. Market Exit Estimates

The hazardous waste combustion industry operates in a dynamic market, with systems entering and exiting the market on a routine basis. Our analysis defines "market exit" as ceasing to burn hazardous waste. We have projected post-rule hazardous waste combustion system market exits based on economic feasibility only. Social, liability, and informational issues are not incorporated into our market exit analysis.

Market exit estimates are derived from a breakeven analysis designed to determine system viability. This analysis is subject to several assumptions, including: Cost assumptions concerning the per sector baseline cost of hazardous waste burning, cost estimates for necessary pollution control devices (including operation and maintenance), prices for combustion services, and estimated waste quantities burned at these facilities. It is important to note that, for most sectors, exiting the hazardous waste combustion market is not equivalent to closing a plant. (Actual plant closure may occur only in the case of a commercial incinerator closing all systems.)

We estimate that 39 systems, representing about 15 percent of the total affected universe, may stop burning hazardous waste in response to the final standards. Approximately 59,000 tons of hazardous waste may be diverted from these closed systems.

These estimates assume no chlorine controls are put in place as a direct result of the rule.[266] Of the estimated 39 market exits, 26 are projected to be on-site incinerators and 8 are liquid fuel boilers. Three commercial incinerator systems may exit the market in response to the final rule. However, these systems are considered economically marginal in the baseline. Two coal-fired boiler systems are also projected to exit the market. No cement kilns, lightweight aggregate kilns, or HCl production furnaces are projected to exit the market as a result of the final rule. Market exit estimates were found to be identical

[261] For purposes of this discussion, a source is defined as the air pollution control system associated with one or more hazardous waste combustion unit(s). A facility may operate one or more sources. Note that this total includes two LWAK units limited by system burn constraints. Exclusion of these two units results in a total of 265 independent sources.

[262] Not included here are total annual government costs. These costs, with or without chlorine control, are approximately $0.5 million/year.

[263] We are finalizing the incorporation of section 112(d)(4) of the Clean Air Act to establish risk-based standards for total chlorine for hazardous waste combustors (except for hydrochloric acid production furnaces). The low-end of this cost range assumes all facilities emit total chlorine levels below risk-based levels of concern. Under this scenario, no total chlorine controls are assumed to be necessary. The total engineering cost with chlorine control is estimated at $46.7 million/year.]

[264] See Exhibit 4–3 in the economic assessment background document.

[265] Beyond-the-Floor standards were assessed for all floors. These findings are available in Appendix F and G of the engineering background document: See: Final Technical Support Document for HWC MACT Standards, Volume V—Emissions Estimates and Engineering Costs.

[266] Even though we are allowing sources (except hydrochloric acid production furnaces) to invoke § 112(d)(4) in lieu of MACT chlorine control requirements, we have not attempted to estimate the following: (1) The total number of sources that may elect to implement this provision, and, (2) what level of control may be necessary following a § 112(d)(4) risk-based determination, since this would vary on a site-by-site basis.

when the cost of chlorine control is included in the model.

B. Waste Reallocations

Some on-site combustion systems (sources) may no longer be able to cover their hazardous waste burning costs as a result of final rule requirements. These sources are projected to divert or reroute their wastes to different hazardous waste combustion sources (usually some type of commercial unit).[267] For multiple system facilities, this diversion may include on-site (non-commercial) waste consolidation among fewer systems at the same facility. Under current market conditions, non-combustion alternatives are generally not economically feasible, and in any case, would normally be unable to achieve the RCRA Land Disposal Restriction Treatment standards, which are based on the performance of combustion technology (which optimizes destruction of organic HAP).

As mentioned above, our economic model indicates that approximately 59,000 tons (U.S.) of hazardous waste may be reallocated. This figure represents approximately 1.8 percent of the total 2003 quantity of hazardous waste burned at all sources. On-site consolidations account for nearly 24 percent (13,915 tons) of all diverted waste. Commercial incinerators are projected to receive the vast majority (42,722 tons, or 73 percent) of all off-site waste reallocations. Cement kilns and LWAKs are projected to receive the remaining reallocation (2,289 tons). Currently, there is more than adequate capacity to accommodate all off-site hazardous waste diversions.

C. Employment Impacts

Today's rule is projected to induce employment shifts across all affected sectors. These shifts may occur as specific combustion facilities find it no longer economically feasible to keep all of their systems running, or to stay in the hazardous waste market at all. When this occurs, workers at these locations may lose their jobs or experience forced relocations. At the same time, the rule is projected to result in positive employment impacts, as new purchases of pollution control equipment stimulate additional hiring in the pollution control manufacturing sector, and as additional staff are required at selected combustion facilities to accommodate reallocated waste and/or various compliance activities.

[267] This analysis includes the cost of waste transport to alternative combustion sources, burning fees, and purchase of alternative fuels (if appropriate).

1. Employment Impacts—Dislocations (Losses)

Employment dislocations in the combustion industry are projected to occur when facilities consolidate waste into fewer systems, or when a facility exits the hazardous waste combustion market altogether. Operation and maintenance labor hours are expected to be reduced for each system that stops burning hazardous waste. For each facility that completely exits the market, employment dislocations may also include supervisory and/or administrative personnel.

Total employment dislocations resulting from implementation of the final standards are estimated at 310 full-time-equivalent (FTE) jobs. On-site incinerators account for about 62 percent of this total, followed by commercial incinerators (about 24 percent), and liquid-fuel boilers (about 12 percent). The large number of on-site incinerators drives the impacts within this sector.

2. Employment Impacts—Positive

In addition to employment dislocations, our analysis indicates that today's rule may also result in positive employment impacts. These positive impacts are projected to occur to both the air pollution control industry and to combustion firms as they hire personnel to accommodate reallocated waste and/or comply with the various requirements of the rule. Hazardous waste combustion sources are projected to need additional operation and maintenance personnel for the new pollution control equipment and other compliance activities, such as new reporting and record keeping requirements.

The total annual positive employment impact associated with the final standards is estimated at 323 FTEs. Positive employment impacts to the air pollution control industry[268] are projected at 93 FTEs, or about 29 percent of this total. At 183 jobs, liquid-fuel boilers are projected to experience the greatest positive employment impact among all combustors.

While it may appear that our analysis suggests overall net positive employment impacts, such a conclusion would be inappropriate. Because the positive employment impacts and employment dislocations occur in different sectors of the economy, they should not be added together. Doing so would mask important distributional effects of the rule. In addition, these employment estimates reflect within sector impacts only and therefore do not account for potential displacements across sectors. This may occur if investment funds are diverted from other areas of the larger economy.

[268] Manufacturers and distributors of air pollution control devices are projected to increase sales as a result of this action.

VI. What Are the Social Costs and Benefits of the Final Rule?

The value of any regulatory action is traditionally measured by the net change in social welfare that it generates. Our economic assessment conducted in support of today's final rule evaluated compliance (control) costs, and economic impacts, as discussed above. The Assessment also analyzed social costs, benefits, small entity impacts, and other impacts (e.g., children's health, unfunded mandates). To conduct this analysis, we examined the current combustion market and practices, developed and implemented a methodology for examining compliance and social costs, applied an economic model to analyze industry economic impacts (discussed above), examined benefits, and followed appropriate guidelines and procedures for examining equity considerations, children's health, and other impacts. The data applied in this analysis were the most recently available at the time of the analysis. Because our data were limited, the findings from these analyses should be more accurately viewed as national estimates.

A. Combustion Market Overview

The hazardous waste industry consists of three key segments: hazardous waste generators, fuel blenders/intermediaries, and hazardous waste burners. Hazardous waste is combusted at four main types of facilities: commercial incinerators, on-site incinerators, waste burning kilns (cement kilns and lightweight aggregate kilns), and industrial boilers. Commercial incinerators are generally larger in size and designed to manage virtually all types of solids, as well as liquid wastes. On-site incinerators are more often designed as liquid-injection systems that handle liquids and pumpable solids. Waste burning kilns and boilers generally burn hazardous wastes to generate heat and power for their manufacturing processes.

As discussed above, we have identified a total of 267 hazardous waste burning sources (systems) currently in operation in the United States. Liquid fuel-boilers account for 104 sources, followed by on-site incinerators at 92 sources. Cement kilns, hydrochloric acid production furnaces, and commercial incinerators account for 25, 10, and 15 sources, respectively. Solid

fuel boilers and lightweight aggregate kilns make up the remainder, at 12 and nine systems, respectively. These 267 sources are operated at a total of 145 different facilities. A single facility may have one or more combustion systems. Facilities with multiple systems may have different types of hazardous waste burning units. Combustion systems operating at chemical manufacturing facilities (NAICS 325) were found to account for about 70 percent of the total number of facilities and manage about 58 percent of all hazardous waste burned in 2003.

The EPA Biennial Reporting System (BRS) reports a total demand for all combusted hazardous waste, across all facilities, at 3.32 million tons (U.S. ton) in 2003. Commercial energy recovery (cement kilns and lightweight aggregate kilns) burned about 30 percent of this total. Hazardous waste destruction at on-site incinerators and commercial incinerators accounted for 28 percent and 13 percent, respectively. Captive energy recovery accounted for the remainder, at 29 percent of the total.

About 65 percent of all hazardous waste burned in 2003 was organic liquids. This is followed by solids (14 percent), inorganic liquids (11 percent), and sludges (10 percent). Hazardous gases were found to represent a negligible portion, at about 0.08 percent of the total quantity burned in 2003. In terms of hazardous waste generating sources, the Basic Organic Chemical Manufacturing e sector (NAICS 325) generated approximately 32 percent of all hazardous waste burned in 2001, followed by pesticides and agricultural chemicals, business services, organic fibers, medicinal chemicals, pharmaceuticals, plastics materials and resins, petroleum, and miscellaneous.

Companies that generate large quantities of uniform hazardous wastes generally find it more economical and efficient to combust these wastes on-site using their own noncommercial systems. Commercial incineration facilities manage a wide range of hazardous waste streams generated in small to medium quantities by diverse industries. Cement kilns, lightweight aggregate kilns, and boilers derive heat and energy by burning high-Btu (solvents and organics) liquid hazardous wastes.[269] Sometimes these wastes are blended with fossil fuels where system operators choose to not derive all of their energy input from hazardous waste.

Regulatory requirements, liability concerns, and economics influence the demand for hazardous waste combustion services. Regulatory forces influence the demand for combustion by mandating certain hazardous waste treatment standards (land disposal restriction requirements, etc.). Liability concerns of waste generators affect combustion demand because combustion, by destroying organic wastes, greatly reduces the risk of future environmental problems. Finally, if alternative waste management options are more expensive, hazardous waste generators will likely choose to send their wastes to combustion facilities in order to increase overall profitability.

Throughout much of the 1980s, hazardous waste combustors enjoyed a strong competitive position and generally maintained a high level of profitability. During this period, EPA regulations helped stimulate a greatly expanded market. In addition, federal permitting requirements, as well as powerful local opposition to siting of new incinerators, constrained the entry of new combustion systems. As a result, combustion prices rose steadily, ultimately reaching record levels in 1987. The high profits of the late 1980s induced many firms to enter the market, in spite of the difficulties and delays anticipated in the permitting and siting process.

Hazardous waste markets have changed significantly since the late 1980s. In the early 1990s, substantial overcapacity resulted in fierce competition, declining prices, poor financial performance, numerous project cancellations, system consolidations, and facility closures. Since the mid 1990s, several additional combustion facilities have closed, while many of those that have remained open have consolidated their operations. Available (prior to this final rule) excess commercial capacity is currently estimated at about 21 percent of the total 2003 quantity combusted.

B. Baseline Specification

Proper and consistent baseline specification is vital to the accurate assessment of incremental costs, benefits, and other economic impacts associated with today's rule. The baseline essentially describes the world absent the rule. The incremental impacts of today's rule are evaluated by predicting post MACT compliance responses with respect to the baseline. The baseline, as applied in this analysis, is the point at which today's rule is promulgated. Thus, incremental cost and economic impacts are projected beyond the standards established in the February 13, 2002 Interim Standards Final Rule.

C. Analytical Methodology and Findings—Social Cost Analysis

Total social costs include the value of resources used to comply with the standards by the private sector, the value of resources used to administer the regulation by the government, and the value of output lost due to shifts of resources away from the current market equilibrium. To evaluate these shifts in resources and changes in output requires predicting changes in behavior by all affected parties in response to the regulation, including responses of directly-affected entities, as well as indirectly-affected private parties.

For this analysis, social costs are grouped into two categories: Economic welfare (changes in consumer and producer surplus), and government administrative costs. The economic welfare analysis conducted for today's rule uses a simplified partial equilibrium approach. In this analysis, changes in economic welfare are measured by summing the changes in consumer and producer surplus. This simplified approach bounds potential economic welfare losses associated with the rule by considering two scenarios: Compliance costs assuming no market adjustments, and market adjusted compliance costs.

The annualized private sector compliance (engineering) costs of $40.2 million, as presented in Section IV, assume no market adjustments. Our best estimate of total social costs incorporates rational market adjustments and all government costs. Under this scenario, increased compliance (engineering) costs are examined in the context of likely incentives hazardous waste combustion facilities have to continue burning, and the competitive balance in the market.

Total annualized market-adjusted net private-sector costs are estimated at $22.1 million.[270] In addition to the net private sector costs, total annual government costs are approximately $0.50 million. Thus, our best estimate of total social costs of this final rule is $22.6 million per year.

The $22.1 million figure incorporates a net gain to selected Phase I sources and an estimated $3.6 million cost

[269] Many cement kilns are also able to burn a certain level of non liquid waste.

[270] We are finalizing alternative risk-based total chlorine standards for hazardous waste combustors (except for hydrochloric acid production furnaces). The net private sector costs of $22.1 million/year may be considered a lower-bound estimate that assumes facilities emit total chlorine (TCI) below risk-based levels of concern (i.e., no TGI controls are assumed to be necessary). Total net private sector market-adjusted costs would increase to approximately $28.1 million per year if we were to assume all sources were to comply with technology-based TCI standards (as opposed to the risk-based standards).

(price) increase to pre-existing customers of commercial hazardous waste combustion facilities. On-site incinerators are projected to experience total market-adjusted cost increases of approximately $1.5 million/year. All phase II sources account for approximately $31.9 million in increased costs. Our economic model indicates that, of the Phase I source categories, commercial incinerators, cement kilns, and LWAKs would experience net gains following all market adjustments. The total net gain for these three source categories is estimated at $14.8 million per year. Commercial incinerators would receive about 98 percent of the total gain ($14.5 million/year). Gains to commercial facilities occur due to marginally higher prices, increased waste receipts, and relatively low upgrade costs, when compared to the other sources.

D. Analytical Methodology and Findings—Benefits Assessment

This section discusses the monetized and non monetized benefits to human health and the environment potentially associated with today's final rule. Monetized human health benefits are derived from reductions in particulate matter (PM) and dioxin/furan exposure, and are based on a Value of Statistical Life (VSL) estimate of $6.2 million.[271] Non monetized benefits are associated with human health, ecological, and waste minimization factors.

1. Monetized Benefits

Total monetized human health benefits for the final standards are estimated to range from $5.61 million/year to $6.31 million/year. This estimate includes human health benefits associated with avoided PM and dioxin/furans exposure. The range is driven by alternative discount rate assumptions (no discount rate, 3 percent, or 7 percent) for mortality valuation. PM benefits represent 99 percent of the total monetized human health benefits.

Particulate Matter

Results from our risk assessment extrapolation procedure[272] are used to evaluate incremental human health benefits potentially associated with particulate matter emission reductions from hazardous waste combustion facilities. This analysis applied avoided human health benefits factors from the March 2004 Assessment document,[273] combined with more recent emissions estimates for particulate matter.

Reduced PM emissions are estimated to result in monetized human health benefits of approximately $6.29 million per year. This is an undiscounted figure. Avoided PM morbidity cases account for $3.42 million of this total, and include: respiratory illness, cardiovascular disease, chronic bronchitis, work loss days, and minor restricted activity. Chronic bronchitis accounts for approximately 89 percent of the total value of avoided PM morbidity cases. All morbidity cases are assumed to be avoided within the first year following reduced PM emissions and are not discounted under any scenario.

Avoided premature deaths (mortality) are valued at $2.87 million per year, undiscounted. Assuming a discount rate of three and seven percent, PM mortality benefits would be $2.52 million and $2.19 million, respectively. Our discounted analysis of PM mortality benefits assumes that 30 percent of premature mortalities occur during the first year, 50 percent occur evenly from the second through the fifth years, and the remaining 20 percent occur evenly from the sixth through the twentieth years.[274] Due to limitations in the risk analysis, this assessment of PM benefits does not consider corresponding health benefits associated with the reduction of HAP metals carried by the PM.

Dioxin/furan—Dioxin/furan emissions are projected to be reduced by a total of 0.2 grams per year under the final standards. In the July 23, 1999 Addendum to the Assessment, cancer risk reductions linked to consumption of dioxin-contaminated agricultural products accounted for the vast majority of the 0.36 cancer cases per year that were expected to be avoided due to the 1999 standards. Cancer risk reductions associated with the final standards are expected to be less than 0.36 cases per year, but greater than zero.

At this time, the Agency is still using a cancer risk slope factor of 1.56×10^5 $[mg/kg/day]^{-1}$ for dioxin. This cancer slope factor is derived from the Agency's 1985 health assessment document for polychlorinated dibenzo-p-dioxins[275] and represents an upper bound 95th percentile confidence limit of the excess cancer risk from a lifetime exposure. For the past several years the Agency has been conducting a reassessment of the human health risks associated with dioxin and dioxin-like compounds. In October of 2004 this reassessment[276] was delivered to the National Academy of Sciences (NAS) for review.

Evidence compiled from this draft reassessment indicates that the carcinogenic effects of dioxin/furans may be six times as great as believed in 1985, reflecting an upper bound cancer risk slope factor of 1×10^6 $[mg/kg/day]^{-1}$ for some individuals. Agency scientists' more likely (central tendency) estimates (derived from the ED_{01} rather than the LED_{01}) result in slope factors and risk estimates that are within 2–3 times of the upper bound estimates (i.e., between 3×10^5 $[mg/kg/day]^{-1}$ and 5×10^5 $[mg/kg/day]^{-1}$) based on the available epidemiological and animal cancer data. However, risks could be as low as zero for some individuals. Use of the alternative upper bound cancer risk slope factor could result in a higher human health monetized health benefit associated with premature cancer deaths avoided in response to the final standard for dioxin/furans. The assessment of upper bound cancer risk using this alternative slope factor should not be considered current Agency policy. The standards for dioxin in today's final rule were not based on this draft reassessment.

Total non-discounted human health benefits associated with projected dioxin reductions are estimated at $0.02 million/year. These benefits may range from $0.01 million/year to nearly zero, applying a discount rate of 3 percent and 7 percent, respectively. Our discounted estimates incorporate an assumed latency period of 21 and 34 years from exposure to death.

2. Non-Monetized Benefits

We examined, but did not monetize human health benefits potentially associated with reduced exposure to lead, mercury, and total chlorine. Non monetized ecological benefits

[271] Monetized benefits associated with avoided premature mortality reflect a VSL range of $1.1 million to $11.4 million, with a central VSL estimate of $6.2 million. These values are derived from willingness-to-pay based VSL estimates presented in U.S. EPA, Regulatory Impact Analysis for the Final Clean Air Interstate Rule, March 2005.

[272] Inferential Risk Analysis in Support of Standards for Emissions of Hazardous Air Pollutants from Hazardous Waste Combustors.

[273] Assessment of the Potential Costs, Benefits, and Other Impacts of the Hazardous Waste Combustion MACT Replacement Standards: Proposed Rule, March 2004 (Chapter 6), and Addendum to the Assessment.

[274] See: U.S. EPA. March 2005. Regulatory Impact Analysis for the Final Interstate Air Quality Rule.

[275] USEPA. 1985. Health Assessment Document for Polychlorinated Dibenzo-p-Dioxins. EPA/600/8-84/014F. Final Report. Office of Health and Environmental Assessment. Washington, DC. September, 1985.

[276] U.S.EPA. Exposure and Human Health Reassessment of 2,3,7,8-Tetrachlorodibenzo-p-Dioxin (TCDD) and Related Compounds National Academy Sciences (NAS) Review Draft, December 2003. [Note: Toxicity risk factors presented in this document should not be considered EPA's official estimate of dioxin toxicity, but rather reflect EPA's ongoing effort to reevaluate dioxin toxicity].

potentially associated with reductions in dioxin/furan; selected metals, total chlorine, and particulate matter were also examined. Finally, waste minimization is examined as a non-monetized benefit.

Lead—The final standards are expected to reduce lead emissions by approximately 2.5 tons per year. In comparison, the 1999 standards were expected to reduce lead emissions by 89 tons per year, and were expected to reduce cumulative lead exposures for two children, ages zero to five, to less than 10 μg/dL. The lead benefits associated with these final standards are therefore expected to be modest. The final standards will also result in reduced lead levels for children of sub-populations with especially high levels of exposure. Children of subsistence fishermen, commercial beef farmers, and commercial dairy farmers who face the greatest levels of cumulative lead exposure may also experience comparable reductions in overall exposure as a result of the MACT standards.

Mercury—The HWC MACT final standards are expected to reduce mercury emissions by approximately 0.21 tons per year, approximately 93 percent less than the four-ton reduction expected under the 1999 Standards. We do not attempt to quantify the mercury-related benefits associated with today's final standards. However, because the reduction in mercury emissions represents a fraction of the reduction expected under the 1999 Standards, the mercury-related benefits of the final standards are likely to be less than the corresponding benefits under the 1999 Standards.

To characterize the benefits associated with reduced mercury emissions, the 1999 Assessment measured changes in hazard quotients for populations living near hazardous waste combustion facilities. For any given population, the hazard quotient is the ratio of the actual level of exposure to a safe level of exposure. A hazard quotient greater than one implies that a population is potentially at risk. The exposure quotient analysis in the 1999 Assessment found that the measurable benefits of reduced mercury emissions under the 1999 Standards were likely to be small because baseline exposures were relatively low. In addition, many of the studies examining the adverse health effects of mercury are inconclusive. Over the past several years, however, scientists have conducted three large-scale studies of individuals in the Faroe Islands, New Zealand, and the Seychelles Islands examining the relationship between mercury exposure in women and the neuro-development of their unborn children.[277] The New Zealand and Faroe Islands studies both found a statistically significant relationship between maternal methylmercury exposure and IQ decrements in the unborn children of these women. In its 2000 report on the toxicological effects of methylmercury, the National Research Council suggested that integrating the results of all three studies could be useful for risk assessment purposes.[278] Such an integrative risk assessment, later published by Ryan et al. in 2005, served as the basis of the Agency's health effects analysis for the Clean Air Mercury Rule (CAMR).[279] The regulatory impact analysis for CAMR summarizes several of the adverse health effects that may be linked to mercury and reviews the epidemiological literature examining the link between these effects and exposure to mercury.[280]

Total Chlorine—We were not able to quantify the benefits associated with reductions in total chlorine emissions. Total chlorine is a combination of hydrogen chloride and chlorine gas. The final standards are projected to reduce total annual chlorine emissions by about 107 tons per year[281] (HCl production furnaces only). Hydrogen chloride is corrosive to the eyes, skin, and mucous membranes. Acute inhalation can cause eye, nose, and respiratory tract irritation and inflammation, and pulmonary edema. Chronic occupational inhalation has been reported to cause gastritis, bronchitis, and dermatitis in workers. Long term exposure can also cause dental discoloration and erosion. Chlorine gas inhalation can cause bronchitis, asthma and swelling of the lungs, headaches, heart disease, and meningitis. Acute exposure causes more severe respiratory and lung effects, and can result in fatalities in extreme cases. The exposure levels established under 112(d)(4) are expected to reduce chlorine exposure for people in close proximity to hazardous waste combustion facilities, and are therefore likely to reduce the risk of all associated health effects.

Ecological Benefits—We examined ecological benefits through a comparison of the 1999 Assessment and today's final standards. Ecological benefits in the 1999 Assessment were based on reductions of approximately 100 tons per year in dioxin/furans and selected metals. Lead was the only pollutant of concern for aquatic ecosystems, while mercury appeared to be of greatest concern for terrestrial ecosystems. Dioxin/furan and lead emission reductions also provided some potential benefits for terrestrial ecosystems. The final standards are expected to reduce dioxin/furan and selected metal emissions by about 12 percent to 13 percent of the 1999 estimate, resulting in fewer incremental benefits than those estimated for the 1999 Assessment (and later, for the 2002 Interim Standards). However, the 1999 Assessment did not estimate the ecological benefits of MACT standards for hazardous waste burning industrial boilers and HCl production furnaces. These systems were excluded from the universe in 1999 but are part of the universe addressed by today's final standards. As a result, while the total ecological benefits of the final rule are likely to be modest, areas near facilities with boilers may enjoy more significant ecological benefits under the final standards than areas near facilities that have already complied with the 2002 Interim standards.

Mercury, lead, and chlorides are among the HAPs that can cause damage to the health and visual appearance of

[277] Grandjean, P., K. Murata, E. Budtz-Jorgensen, and P. Weihe. 2004. "Autonomic Activity in Methylmercury Neurotoxicity: 14–Year Follow-Up of a Faroese Birth Cohort." Journal of Pediatrics.144:169–76; Kjellstrom, T., P. Kennedy, S. Wallis, A. Stewart, L. Friberg, B. Lind, P. Witherspoon, and C. Mantell. 1989. Physical and mental development of children with prenatal exposure to mercury from fish. Stage 2: Interviews and psychological tests at age 6. National Swedish Environmental Protection Board Report No. 3642; Crump, K.S., T. Kjellstrom, A.M. Shipp, A. Silvers, and A. Stewart. 1998. "Influence of prenatal mercury exposure upon scholastic and psychological test performance: benchmark analysis of a New Zealand cohort." Risk Analysis. 18(6):701–713; Davidson, P.W., G.J. Myers, C. Cox, C. Axtell, C. Shamlaye, J. Sloane-Reeves, E. Cernichiari, L. Needham, A. Choi, Y. Wang, M. Berlin, and T.W. Clarkson. 1998. "Effects of prenatal and postnatal methylmercury exposure from fish consumption on neurodevelopment: outcomes at 66 months of age in the Seychelles Child Development Study." Journal of the American Medical Association. 280(8):701–707; and Myers, G.J., P.W. Davidson, C. Cox, C.F. Shamlaye, D. Palumbo, E. Cernichiari, J. Sloane-Reeves, G.E. Wilding, J. Kost, L.S. Huang, and T.W. Clarkson. 2003. "Prenatal methylmercury exposure from ocean fish consumption in the Seychelles child development study." Lancet. 361(9370):1686–92.

[278] National Research Council of the National Academy of Sciences, Toxicological Effects of Methylmercury. 2000, p. 299.

[279] Ryan, L.M. Effects of Prenatal Methylmercury on Childhood IQ: A Synthesis of Three Studies. Report to the U.S. Environmental Protection Agency. 2005; U.S. EPA. Regulatory Impact Analysis of the Clean Air Mercury Rule: Final Report. March 2005.

[280] U.S. EPA. Regulatory Impact Analysis of the Clean Air Mercury Rule: Final Report. March 2005.

[281] This is a lower bound estimate that assumes all other sources will implement 112(d)(4) and will not move to reduce TCl emissions from current baseline levels.

plants.[282] While the total value of forest health is difficult to estimate, visible deterioration in the health of forests and plants can cause a measurable change in recreation behavior. Several studies that measure the change in outdoor recreation behavior according to forest health have attempted to place a value on aesthetic degradation of forests.[283] Although these studies are available, additional research is needed to fully understand the effects of these Haps on the forest ecosystem. Thus, these benefits are not quantified in this analysis.

Emissions that are sufficient to cause structural and aesthetic damage to vegetation are likely to affect growth as well. Little research has been done on the effects of compounds such as chlorine, heavy metals (as air pollutants), and PM on agricultural productivity.[284] Even though the potential for visible damage and production decline from metals and other pollutants suggests the final standards could increase agricultural productivity, we have not monetized the benefits of these changes.

3. Waste Minimization Benefits

Facilities that burn hazardous waste and remain in operation following implementation of the final standards are expected to experience marginally increased costs as a result of these standards. This will result in an incentive to pass these increased costs on to their customers in the form of higher combustion prices. In the 1999 Assessment we conducted a waste minimization analysis to inform the expected price change. The analysis concluded that the demand for hazardous waste combustion is relatively inelastic. While a variety of waste minimization alternatives are available for managing hazardous waste streams that are currently combusted, the costs of these alternatives generally exceed the cost of combustion. When the additional costs of compliance with the MACT standards are taken into account, waste minimization alternatives still tend to exceed the higher combustion costs. This relative inelasticity suggests that, in the short term, large reductions in the amount of hazardous waste requiring combustion are not likely to occur. However, over the longer term (*i.e.* as production systems are updated), companies may continue to seek alternatives to expensive hazardous waste-management. This may include process adjustments that result, to some degree in source reduction of hazardous waste and the increased generation of non hazardous waste. To the extent that increases in combustion prices provide additional incentive to adopt more efficient processes, the final standards may contribute to longer term process-based hazardous waste minimization efforts.

No hazardous waste minimization impacts are captured in our quantitative analysis of costs and benefits.[285] A quantitative assessment of the benefits associated with waste minimization may result in double-counting of some of the benefits described earlier. For example, waste minimization may reduce emissions of hazardous air pollutants and therefore have a positive effect on public health. Furthermore, emission reductions beyond those necessary for compliance with the final standards are not addressed in the benefits assessment. In addition, waste minimization is likely to result in specific types of benefits not captured in this Assessment. For example, waste generators that engage in waste minimization may experience a reduction in their waste handling costs and could also reduce the risk related to waste spills and waste management. Finally, waste minimization procedures potentially stimulated by today's action may result in additional costs to facilities that implement these technologies. These factors have not been assessed in our analysis but are likely to at least partially offset corresponding benefits.

4. Conclusion

Total non-discounted monetized human health benefits associated with the final standards are estimated at $6.31 million/year. Annualized discounted benefits were found to range from $5.61 million to $5.95 million/year. The range reflects an alternative discount rate of 3 percent and 7 percent for mortality benefits.

It is important to emphasize that monetized benefits represent only a portion of the total benefits associated with this rule. A significant portion of the benefits are not monetized, as discussed above, due to data and analytical limitations. Specifically, ecological benefits, and human health benefits associated with reductions in chlorine, mercury, and lead are not quantified or monetized. In some regions these benefits may be significant. In addition, specific sub-populations near combustion facilities, including children and minority populations, may be disproportionately affected by environmental risks and may therefore enjoy more significant benefits. Visibility benefits associated with reduced PM are also expected from this final rule. For a complete discussion of the methodology, data, findings, and limitations associated with our benefits analysis the reader is encouraged to review the Assessment document,[286] and the Addendum to the Assessment.

Part Seven: How Does the Final Rule Meet the RCRA Protectiveness Mandate?

As discussed in more detail below, we believe today's final standards are generally protective of human health and the environment. We therefore finalize and apply these standards, in most instances, in lieu of the RCRA air emission standards applicable to these sources.

I. Background

Section 3004(a) of RCRA requires the Agency to promulgate standards for hazardous waste treatment, storage, and disposal facilities as necessary to protect human health and the environment. The standards for hazardous waste incinerators generally rest on this authority. In addition, § 3004(q) requires the Agency to promulgate standards for emissions from facilities that burn

[282] Although the primary pollutants which are detrimental to vegetation aesthetics and growth are tropospheric ozone, sulfur dioxide, and hydrogen fluoride (three pollutants which are not regulated in the MACT standards), some literature exists on the relationship between metal deposition and vegetation health. (Mercury Study Report to Congress Volume VI, 1997) (Several studies are cited in this report.)

[283] See, for example, Brown, T.C. et al. 1989, Scenic Beauty and Recreation Value: Assessing the Relationship, In J. Vining, ed., *Social Science and Natural Resources Recreation Management*, Westview Press, Boulder, Colorado; this work studies the relationship between forest characteristics and the value of recreational participation. Also see Peterson, D.G. et al. 1987, Improving Accuracy and Reducing Cost of Environmental Benefit Assessments. Draft Report to the U.S. EPA, by Energy and Resource Consultants, Boulder, Colorado; Walsh et al. 1990, Estimating the public benefits of protecting forest quality, Journal of Forest Management, 30:175–189., and Homes et al. 1992, Economic Valuation of Spruce-Fir Decline in the Southern Appalachian Mountains: A comparison of Value Elicitation Methods. Presented at the Forestry and the Environment: Economic Perspectives Conference, March 1, 1992 Jasper, Alberta, Canada for estimates of the WTP of visitors and residents to avoid forest damage.

[284] MacKenzie, James J., and Mohamed T. El-Ashry, *Air Pollution's Toll on Forests and Crops* (New Haven, Yale University Press, 1989).

[285] Note that this rule does, in fact, consider hazardous waste feed control. Feed control can be implemented by each source through waste minimization procedures. See: Final Technical Support Document for HWC MACT Standards, Volume V–Emissions Estimates and Engineering Costs.

[286] Assessment of the Potential Costs, Benefits, and Other Impacts of the Hazardous Waste Combustion MACT Final Rule Standards. September 2005.

hazardous waste fuels (e.g., cement and lightweight aggregate kilns, boilers, and hydrochloric acid production furnaces) as necessary to protect human health and the environment. Using RCRA authority, the Agency has established emission (and other) standards for hazardous waste combustors that are either entirely risk-based (e.g., site-specific standards for metals under the Boiler and Industrial Furnace rule), or are technology-based but determined by a generic risk assessment to be protective (e.g., the DRE standard for incinerators and BIFs).

The MACT standards finalized today implement the technology-based regime of CAA § 112(d). There is, however, a residual risk component to air toxics standards. Section 112(f) of the Clean Air Act requires the Agency to impose, within eight years after promulgation of the technology-based standards promulgated under § 112(d) (i.e., the authority for today's final standards), additional controls if needed to protect public health with an ample margin of safety or to prevent adverse environmental effect.

RCRA § 1006(b) directs that EPA "integrate all provisions of [RCRA] for purposes of administration and enforcement and * * * avoid duplication, to the maximum extent possible, with the appropriate provisions of the Clean Air Act * * *" Thus, although considerations of risk are not ordinarily part of the MACT process, in order to avoid duplicative standards where possible, we have evaluated the protectiveness of the standards finalized today.

As noted above, under RCRA, EPA must promulgate standards "as may be necessary to protect human health and the environment." RCRA § 3004(a) and (q). Technology-based standards developed under CAA § 112 do not automatically satisfy this requirement, but may do so in fact. See 59 FR at 29776 (June 6, 1994) and 60 FR at 32593 (June 23, 1995) (RCRA regulation of secondary lead smelter emissions unnecessary at this time given stringency of technology-based standard and pendency of § 112(f) determination). If the MACT standards, as a factual matter, are sufficiently protective to also satisfy the RCRA mandate, then no independent RCRA standards are required. Conversely, if MACT standards are inadequate, the RCRA authorities would have to be used to fill the gap.

II. Evaluation of Protectiveness

For the purpose of satisfying the RCRA statutory mandates, the Agency has conducted an evaluation of the degree of protection afforded by the MACT standards being finalized today. We have not conducted a comprehensive risk assessment for this rulemaking as was done for incinerators, cement kilns, and lightweight aggregate kilns in the 1999 MACT rule where we concluded that the promulgated standards were generally protective and therefore, the RCRA standards need not be retained. However, we noted that in certain instances, permit authorities may invoke the omnibus authority (RCRA § 3005(c)(3) and its implementing regulations at § 270.10(k)) if there is some reason to believe that additional controls beyond those required pursuant to 40 CFR parts 63, 264, 265, and 266 may be needed to ensure protection of human health and the environment under RCRA.

For this final rule, we instead compared the risk-related characteristics of the sources covered by the 1999 rule to the sources covered by today's rule (e.g., estimated emissions, stack characteristics, meteorology, and population). For a description of the methodology and technical discussion of its application, see "Inferential Risk Analysis in Support of Standards for Emissions of Hazardous Air Pollutants from Hazardous Waste Combustors," in the docket for today's rule. We performed a large array of statistical comparisons and from these we attempted to make inferences about whether risks would be expected to be about the same, less than, or greater than the risks estimated for 1999 rule. We think the comparative analysis lends additional support to our view that today's final standards are generally protective. We received no comments either in support of or in opposition to our use of the comparative analysis to evaluate the protectiveness of the standards being finalized today or our view that the standards are generally protective.

While we regard the final standards as generally protective, the comparative analysis suggests some concern for solid fuel-fired boilers (SFBs) with regard to the particulate matter standard (and certain metals such as antimony and thallium), mercury, and total chlorine standards (other than the alternative risk-based chlorine standards). The analysis also suggests some concern for hydrochloric acid (HCl) production furnaces with regard to the dioxin/furan standard, where carbon monoxide and total hydrocarbon serve as surrogate control. However, because both SFBs and HCl production furnaces comprise such small source categories (4 SFB facilities and 8 HCl production facilities), it is difficult to reach firm conclusions. For example, for SFBs it was not possible to conduct hypothesis tests that could be considered valid involving correlations among variables for a number of variables in the analysis because of the small number of data points and the power of the tests to detect differences for those that were conducted was very low, which greatly diminishes the value of the results. (Indeed, no differences in correlations were found for SFBs at the 0.1 significance level—the level of significance that was used in the analysis.) Similarly, for HCl production furnaces the power of the tests to detect differences in correlations was quite low. It must be noted that the comparative analysis methodology was not intended for comparisons that involve relatively few facilities because it is grounded in tests of hypotheses and levels of statistical significance which generally require substantial amounts of data to produce firm conclusions. Nevertheless, in consideration of the indications of possible risks for the aforementioned standards, permit authorities may want to consider site-specific factors in determining whether or not the MACT standards are sufficiently protective for facilities that fall into these categories.

The comparative analysis may also raise possible concerns for lightweight aggregate kilns (LWAKs) and liquid fuel-fired boilers (LFBs) with dry APCDs with regard to the dioxin/furan standards, in view of the ongoing uncertainty in cancer and other health effects levels for chlorinated dioxins and furans. In particular, some recent estimates of the carcinogenicity of these compounds that consider both human and animal data, are higher than earlier estimates derived from animal data alone. However, like SFBs and HCl production furnaces, LWAKs and LFBs with dry APCDs both comprise small source categories (3 LWAK facilities and 7 dry APCD LFB facilities). This makes it very difficult to reach firm conclusions and suggests the need to consider site-specific factors in determining whether the MACT standards are sufficiently protective in these instances.

Except as noted, we believe today's final standards provide a substantial degree of protection to human health and the environment. We therefore do not believe that we need to retain the existing RCRA standards for boilers and hydrochloric acid production furnaces (just as we found that existing RCRA standards for incinerators, cement kilns, and lightweight aggregate kilns were no longer needed after the 1999 rule). However, as previously discussed in

more detail in Part Four, Section IX, site-specific risk assessments may be warranted on an individual source basis to ensure that the MACT standards provide adequate protection in accordance with RCRA.

Part Eight: Statutory and Executive Order Reviews

I. Executive Order 12866: Regulatory Planning and Review

Under Executive Order 12866 [58 FR 51735 (October 4, 1993)] the Agency, in conjunction with OMB's Office of Information and Regulatory Affairs (OIRA), must determine whether a regulatory action is "significant" and therefore subject to OMB review and the full requirements of the Executive Order. The Order defines "significant regulatory action" as one that is likely to result in a rule that may:

(1) Have an annual effect on the economy of $100 million or more or adversely affect in a material way the economy, a sector of the economy, productivity, competition, jobs, the environment, public health or safety, or State, local, or tribal governments or communities;

(2) Create a serious inconsistency or otherwise interfere with an action taken or planned by another agency;

(3) Materially alter the budgetary impact of entitlements, grants, user fees, or loan programs or the rights and obligations of recipients thereof; or

(4) Raise novel legal or policy issues arising out of legal mandates, the President's priorities, or the principles set forth in the Executive Order.

Pursuant to the terms of Executive Order 12866, it has been determined that this rule is a "significant regulatory action" because this action may raise novel legal or policy issues due to the methodology applied in development of the final standards. As such, this action was submitted to OMB for review. Changes made in response to OMB suggestions or recommendations are documented in the public record.

The total social costs for this rule are estimated at $22.6 million per year[287]. This figure is significantly below the $100 million threshold established under point number one above. Thus, this rule is not considered to be an economically significant action. However, in an effort to comply with the spirit of the Order, we have prepared an economic assessment in support of today's final rule. This document is entitled: Assessment of the Potential Costs, Benefits, and Other Impacts of the Hazardous Waste Combustion MACT Final Rule Standards, September 2005. We have also prepared an Addendum to this Assessment entitled: Addendum to the Assessment of the Potential Costs, Benefits, and Other Impacts of the Hazardous Waste Combustion MACT Final Rule Standards, September 2005. This Addendum captures changes made to the rulemaking following completion of the full Assessment document. The Assessment and Addendum were designed to adhere to analytical requirements established under Executive Order 12866, and corresponding Agency and OMB guidance; subject to data, analytical, and resource limitations. Findings presented under Part Six of this Preamble were developed in accordance with this guidance. The RCRA docket established for today's rulemaking maintains a copy of the Assessment and Addendum for public review. Interested persons are encouraged to read both documents to gain a full understanding of the analytical methodology, findings, and limitations associated with this report.

[287] This figure includes approximately $0.5 million/year in total government costs. Total social costs would increase to approximately $28.6 million per year if we were to assume all sources were to comply with technology-based TC1 standards.

II. Paperwork Reduction Act

We have prepared an Information Collection Request (ICR) document (ICR No. 1773.08) listing the information collection requirements of this final rule, and have submitted it for approval to the Office of Management and Budget (OMB) under the provisions of the Paperwork Reduction Act, U.S.C. 3501 *et seq.* OMB has assigned a control number 2050–0171 for this ICR. This ICR is available for public viewing in the EPA Docket Center, Room B102, 1301 Constitution Avenue NW., Washington, DC. Copy may also be obtained from the EDOCKET on the EPA Web site, or by calling (202) 566–1744. The information collection requirements are not enforceable until OMB approves them.

The public burden associated with this final rule is projected to affect 238 HWC units and is estimated to average 211 hours per respondent annually. The reporting and recordkeeping cost burden is estimated to average $5,640 per respondent annually.

Burden means total time, effort, or financial resources expended by persons to generate, maintain, retain, disclose, or provide information to or for a Federal agency. That includes the time needed to review instructions; develop, acquire, install, and utilize technology and systems for the purposes of collecting, validating, and verifying information, processing and maintaining information, and disclosing and providing information; adjust the existing ways to comply with any previously applicable instructions and requirements; train personnel to be able to respond to a collection of information; search data sources; complete and review the collection of information; and transmit or otherwise disclose the information.

An agency may not conduct or sponsor, and a person is not required to respond to, a collection of information unless it displays a currently valid OMB control number. The OMB control numbers for EPA's regulations are listed in 40 CFR part 9. When this ICR is approved by OMB, the Agency will publish a technical amendment to 40 CFR part 9 in the Federal Register to display the OMB control number for the approved information collection requirements contained in this final rule.

The EPA requested comments (see 70 FR 20748, Apr. 21, 2005) on the need for this information, the accuracy of the provided burden estimates, and any suggested methods for minimizing respondent burden, including through the use of automated collection techniques.

III. Regulatory Flexibility Act

The Regulatory Flexibility Act (RFA) as amended by the Small Business Regulatory Enforcement Fairness Act of 1996 (SBREFA), 5 U.S.C. 601 et seq., generally requires an agency to prepare a regulatory flexibility analysis of any rule subject to notice and comment rulemaking requirements under the Administrative Procedure Act, or any other statute. This analysis must be completed unless the agency is able to certify that the rule will not have a significant economic impact on a substantial number of small entities. Small entities include small businesses, small not-for-profit enterprises, and small governmental jurisdictions.

The RFA provides default definitions for each type of small entity. Small entities are defined as: (1) A small business as defined by the Small Business Administration's (SBA) regulations at 13 CFR 121.201; (2) a small governmental jurisdiction that is a government of a city, county, town, school district or special district with a population of less than 50,000; and (3) a small organization that is any not-for-profit enterprise which is independently owned and operated and is not dominant in its field.

After considering the economic impacts of today's final rule on small entities, I certify that this action will not

have a significant economic impact on a substantial number of small entities. We have determined that hazardous waste combustion facilities are not owned by small governmental jurisdiction or nonprofit organizations. Therefore, only small businesses were analyzed for small entity impacts. For the purposes of the impact analyses, small entity is defined either by the number of employees or by the dollar amount of sales. The level at which a business is considered small is determined for each North American Industrial Classification System (NAICS) code by the Small Business Administration.

Affected individual waste combustors (incinerators, cement kilns, lightweight aggregate kilns, solid and liquid fuel-boilers, and hydrochloric acid production furnaces) will bear the impacts of today's rule. These units will incur direct economic impacts (positive or negative) as a result of today's rule. Few of the hazardous waste combustion facilities affected by this rule were found to be owned by small businesses, as defined by the Small Business Administration (SBA). From our universe of 145 facilities, we identified eight facilities that are currently owned by small businesses. Four of these facilities are liquid boilers, two are on-site incinerators, one is a cement kiln, and one is a lightweight aggregate kiln (LWAK). Our analysis indicates that none of these facilities are likely to incur annualized compliance costs greater than one percent of gross annual corporate revenues. Cost impacts of the final standards were found to range from less than 0.01 percent to 0.46 percent of annual gross corporate revenues.

The reader is encouraged to review our regulatory flexibility screening analysis prepared in support of this determination. This analysis is incorporated as Appendix H of the *Assessment* document, and updated in the *Addendum*.

IV. Unfunded Mandates Reform Act of 1995

Signed into law on March 22, 1995, the Unfunded Mandates Reform Act (UMRA) calls on all federal agencies to provide a statement supporting the need to issue any regulation containing an unfunded federal mandate and describing prior consultation with representatives of affected state, local, and tribal governments.

Today's final rule is not subject to the requirements of sections 202, 204 and 205 of UMRA. In general, a rule is subject to the requirements of these sections if it contains "Federal mandates" that may result in the expenditure by State, local, and tribal governments, in the aggregate, or by the private sector, of $100 million or more in any one year. Today's final rule does not result in $100 million or more in expenditures for any of these categories. The aggregate annualized social cost for today's rule is estimated at $22.6 million.

V. Executive Order 13132: Federalism

Executive Order 13132, entitled "Federalism" (64 FR 43255, August 10, 1999), requires EPA to develop an accountable process to ensure "meaningful and timely input by State and local officials in the development of regulatory policies that have federalism implications." "Policies that have federalism implications" is defined in the Executive Order to include regulations that have "substantial direct effects on the States, on the relationship between the national government and the States, or on the distribution of power and responsibilities among the various levels of government."

Under Executive Order 13132, EPA may not issue a regulation that has federalism implications, that imposes substantial direct compliance costs, and that is not required by statute, unless the Federal government provides the funds necessary to pay the direct compliance costs incurred by State and local governments, or EPA consults with State and local officials early in the process of developing the regulation.

This final rule does not have federalism implications. It will not have substantial direct effects on the States, on the relationship between the national government and the States, or on the distribution of power and responsibilities among the various levels of government, as specified in the Order. The rule focuses on requirements for facilities burning hazardous waste, without affecting the relationships between Federal and State governments. Thus, Executive Order 13132 does not apply to this rule. Although section 6 of Executive Order 13132 does not apply to this rule, EPA did include various State representatives on our Agency workgroup. These representatives participated in the development of this rule.

VI. Executive Order 13175: Consultation and Coordination With Indian Tribal Governments

Executive Order 13175: Consultation and Coordination with Indian Tribal Governments (65 FR 67249, November 9, 2000), requires EPA to develop an accountable process to ensure "meaningful and timely input by tribal officials in the development of regulatory policies that have tribal implications." Our Agency workgroup for this rule included Tribal representation. We have determined that this final rule does not have tribal implications, as specified in the Order. No Tribal governments are known to own or operate hazardous waste combustors subject to the requirements of this final rule. Furthermore, this rule focuses on requirements for all regulated sources without affecting the relationships between tribal governments in its implementation, and applies to all regulated sources, without distinction of the surrounding populations affected. Thus, Executive Order 13175 does not apply to this rule.

VII. Executive Order 13045: Protection of Children From Environmental Health Risks and Safety Risks

Executive Order 13045: "Protection of Children from Environmental Health Risks and Safety Risks" (62 FR. 19885, April 23, 1997) applies to any rule that: (1) Is determined to be "economically significant" as defined under E.O. 12866, and (2) concerns an environmental health or safety risk that EPA has reason to believe may have a disproportionate effect on children. If the regulatory action meets both criteria, the Agency must evaluate the environmental health or safety effects of the planned rule on children, and explain why the planned regulation is preferable to other potentially effective and reasonably feasible alternatives considered by the Agency. Today's final rule is not subject to the Executive Order because it is not economically significant as defined under point one of the Order, and because the Agency does not have reason to believe the environmental health or safety risks addressed by this action present a disproportionate risk to children.

VIII. Executive Order 13211: Actions Concerning Regulations That Significantly Affect Energy Supply, Distribution, or Use

This rule is not subject to Executive Order 13211, "Actions Concerning Regulations That Significantly Affect Energy Supply, Distribution, or Use" (66 Fed. Reg. 28355 (May 22, 2001)). This rule, as finalized, will not seriously disrupt energy supply, distribution patterns, prices, imports or exports. Furthermore, this rule is not an economically significant action under Executive Order 12866.

IX. National Technology Transfer and Advancement Act

Section 12(d) of the National Technology Transfer and Advancement Act of 1995 ("NTTAA"), Public Law 104–113, 12(d) (15 U.S.C. 272 note) directs EPA to use voluntary consensus standards in its regulatory activities unless to do so would be inconsistent with applicable law or otherwise impractical. Voluntary consensus standards are technical standards (*e.g.*, materials specifications, test methods, sampling procedures, and business practices) that are developed or adopted by voluntary consensus standards bodies. The NTTAA directs EPA to provide Congress, through OMB, explanations when the Agency decides not to use available and applicable voluntary consensus standards.

This rulemaking involves environmental monitoring or measurement. Both Performance Based Measurement System (PBMS) and specific measurement methods are finalized under this rule. The PBMS approach is intended to be more flexible and cost-effective for the regulated community; it is also intended to encourage innovation in analytical technology and improved data quality. Where allowed, EPA is not precluding the use of any method, whether it constitutes a voluntary consensus standard or not, as long as it meets the performance criteria specified.

X. Executive Order 12898: Federal Actions To Address Environmental Justice in Minority Populations and Low-Income Populations

Executive Order 12898, "Federal Actions to Address Environmental Justice in Minority Populations and Low-Income Populations' (February 11, 1994) requires us to complete an analysis of today's rule with regard to equity considerations. The Order is designed to address the environmental and human health conditions of minority and low-income populations. This section briefly discusses potential impacts (direct or disproportional) today's rule may have in the area of environmental justice.

We have recently analyzed demographic data from the U.S. Census, and have previously examined data from two other reports: "Race, Ethnicity, and Poverty Status of the Populations Living Near Cement Plants in the United States" (EPA, August 1994) and "Race, Ethnicity, and Poverty Status of the Populations Living Near Hazardous Waste Incinerators in the United States" (EPA, October 1994). These reports examine the number of low-income and minority individuals living near a relatively large sample of cement kilns and hazardous waste incinerators and provide county, state, and national population percentages for various sub-populations. The demographic data in these reports provide several important findings when examined in conjunction with the risk reductions projected from today's rule.

We find that combustion facilities, in general, are not located in areas with disproportionately high minority and low-income populations. However, there is evidence that hazardous waste burning cement kilns are somewhat more likely to be located in areas that have relatively higher low-income populations. Furthermore, there are a small number of commercial hazardous waste incinerators located in highly urbanized areas where there is a disproportionately high concentration of minorities and low-income populations within one and five mile radii. The reduced emissions at these facilities due to today's rule could represent meaningful environmental and health improvements for these populations. Overall, today's rule should not result in any adverse or disproportional health or safety effects on minority or low-income populations. Any impacts on these populations are likely to be positive due to the reduction in emissions from combustion facilities near minority and low-income population groups. The Assessment document available in the RCRA docket established for today's rule discusses our Environmental Justice analysis.

XI. Congressional Review

The Congressional Review Act (CRA), 5 U.S.C. 801 *et seq.*, as added by the Small Business Regulatory Enforcement Fairness Act of 1996, generally provides that before a rule may take effect, the agency promulgating the rule must submit a rule report, which includes a copy of the rule, to each House of the Congress and to the Comptroller General of the United States. Prior to publication of the final rule in the Federal Register, we will submit all necessary information to the U.S. Senate, the U.S. House of Representatives, and the Comptroller General of the United States. Under the CRA, a major rule cannot take effect until 60 days after it is published in the Federal Register. This action is not a "major rule" as defined by 5 U.S.C. 804(2).

List of Subjects

40 CFR Part 9

Environmental protection, Reporting and recordkeeping requirements.

40 CFR Part 63

Environmental protection, Air pollution control, Hazardous substances, Incorporation by reference, Reporting and recordkeeping requirements.

40 CFR Part 260

Environmental protection, Administrative practice and procedure, Confidential business information, Hazardous waste, Reporting and recordkeeping requirements.

40 CFR Part 264

Environmental protection, Air pollution control, Hazardous waste, Insurance, Packaging and containers, Reporting and recordkeeping requirements, Security measures, Surety bonds.

40 CFR Part 265

Environmental protection, Air pollution control, Hazardous waste, Insurance, Packaging and containers, Reporting and recordkeeping requirements.

40 CFR Part 266

Environmental protection, Energy, Hazardous waste, Recycling, Reporting and recordkeeping requirements.

40 CFR Part 270

Environmental protection, Administrative practice and procedure, Confidential business information, Hazardous materials transportation, Hazardous waste, Reporting and recordkeeping requirements.

40 CFR Part 271

Administrative practice and procedure, Hazardous materials transportation, Hazardous waste, Intergovernmental relations, Reporting and recordkeeping requirements.

Dated: September 14, 2005.

Stephen L. Johnson,

Administrator.

■ For the reasons set out in the preamble, title 40, chapter I, of the Code of Federal Regulations is amended as follows:

PART 9—OMB APPROVALS UNDER THE PAPERWORK REDUCTION ACT

■ 1. The authority citation for part 9 continues to read as follows:

Authority: 7 U.S.C. 135 *et seq.*, 136–136y; 15 U.S.C. 2001, 2003, 2005, 2006, 2601–2671; 21 U.S.C. 331j, 346a, 348; 31 U.S.C. 9701; 33 U.S.C. 1251 *et seq.*, 1311, 1313d, 1314, 1318, 1321, 1326, 1330, 1342, 1344, 1345 (d) and (e), 1361; E.O. 11735, 38 FR 21243, 3 CFR, 1971–1975 Comp. p. 973; 42 U.S.C. 241, 242b, 243, 246, 300f, 300g, 300g–1, 300g–2,

300g–3, 300g–4, 300g–5, 300g–6, 300j–1, 300j–2, 300j–3, 300j–4, 300j–9, 1857 *et seq.*, 6901–6992k, 7401–7671q, 7542, 9601–9657, 11023, 11048.

■ 2. Section 9.1 is amended in the table under center heading "National Emission Standards for Hazardous Air Pollutants for Source Categories" by adding entry "63.1200–63.1221" in numerical order to read as follows:

§ 9.1 OMB approvals under the Paperwork Reduction Act.

* * * * *

40 CFR citation	OMB control No.
* * * * * * *	
National Emission Standards for Hazardous Air Pollutants for Source Categories[3]	
* * * * * * *	
63.1200–63.1221	2050–0171

[3]The ICRs referenced in this section of the table encompass the applicable general provisions contained in 40 CFR part 63, subpart A, which are not independent information collection requirements.

* * * * *

PART 63—NATIONAL EMISSION STANDARDS FOR HAZARDOUS AIR POLLUTANTS FOR SOURCE CATEGORIES

■ 1. The authority citation for part 63 continues to read as follows:

Authority: 42 U.S.C. 7401 *et seq.*

■ 2. Section 63.14 is amended by:
■ a. Removing paragraphs (i)(1) and (i)(2).
■ b. Redesignating paragraph (i)(3) as (i)(1).
■ c. Adding and reserving new paragraph (i)(2).
■ d. Revising paragraph (k).

The revisions and additions read as follows:

§ 63.14 Incorporations by reference.

* * * * *

(i) * * *

(2) [Reserved]

* * * * *

(k) The following materials are available for purchase from the National Technical Information Service (NTIS), 5285 Port Royal Road, Springfield, VA 22161, (703) 605–6000 or (800) 553–6847; or for purchase from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402, (202) 512–1800:

(1) The following methods as published in the test methods compendium known as "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods," EPA Publication SW–846, Third Edition. A suffix of "A" in the method number indicates revision one (the method has been revised once). A suffix of "B" in the method number indicates revision two (the method has been revised twice).

(i) Method 0023A, "Sampling Method for Polychlorinated Dibenzo-*p*-Dioxins and Polychlorinated Dibenzofuran Emissions from Stationary Sources," dated December 1996 and in Update III, IBR approved for § 63.1208(b)(1) of Subpart EEE of this part.

(ii) Method 9071B, "n-Hexane Extractable Material (HEM) for Sludge, Sediment, and Solid Samples," dated April 1998 and in Update IIIA, IBR approved for § 63.7824(e) of Subpart FFFFF of this part.

(iii) Method 9095A, "Paint Filter Liquids Test," dated December 1996 and in Update III, IBR approved for §§ 63.7700(b) and 63.7765 of Subpart EEEEE of this part.

(2) [Reserved]

■ 3. Section 63.1200 is amended by:
■ a. Revising the introductory text.
■ b. Revising paragraph (a)(2).
■ c. Adding entry (4) in Table 1 in paragraph (b).

The revisions and additions read as follows:

§ 63.1200 Who is subject to these regulations?

The provisions of this subpart apply to all hazardous waste combustors: hazardous waste incinerators, hazardous waste cement kilns, hazardous waste lightweight aggregate kilns, hazardous waste solid fuel boilers, hazardous waste liquid fuel boilers, and hazardous waste hydrochloric acid production furnaces. Hazardous waste combustors are also subject to applicable requirements under parts 260 through 270 of this chapter.

(a) * * *

(2) Both area sources and major sources subject to this subpart, but not previously subject to title V, are immediately subject to the requirement to apply for and obtain a title V permit in all States, and in areas covered by part 71 of this chapter.

(b) * * *

TABLE 1 TO § 63.1200.—HAZARDOUS WASTE COMBUSTORS EXEMPT FROM SUBPART EEE

If	And If	Then
* * * * * * *		
(4) You meet the definition of a small quantity burner under § 266.108 of this chapter		You are not subject to the requirements of this subpart (Subpart EEE).

* * * * *

■ 4. Section 63.1201 is amended in paragraph (a) by revising the definitions of "Hazardous waste combustor", "New source", and "TEQ", and adding definitions for "Btu", "Hazardous waste hydrochloric acid production furnace", "Hazardous waste liquid fuel boiler", "Hazardous waste solid fuel boiler", and "System removal efficiency" in alphabetical order to read as follows:

§ 63.1201 Definitions and acronyms used in this subpart.

(a) * * *

Btu means British Thermal Units.

* * * * *

Hazardous waste combustor means a hazardous waste incinerator, hazardous waste burning cement kiln, hazardous waste burning lightweight aggregate kiln, hazardous waste liquid fuel boiler, hazardous waste solid fuel boiler, or hazardous waste hydrochloric acid production furnace.

* * * * *

Hazardous waste hydrochloric acid production furnace and *Hazardous Waste HCl production furnace* mean a halogen acid furnace defined under § 260.10 of this chapter that produces aqueous hydrochloric acid (HCl) product and that burns hazardous waste at any time.

* * * * *

Hazardous waste liquid fuel boiler means a boiler defined under § 260.10 of this chapter that does not burn solid fuels and that burns hazardous waste at any time. Liquid fuel boiler includes boilers that only burn gaseous fuel.

* * * * *

Hazardous waste solid fuel boiler means a boiler defined under § 260.10 of this chapter that burns a solid fuel and that burns hazardous waste at any time.

* * * * *

New source means any affected source the construction or reconstruction of which is commenced after the dates specified under §§ 63.1206(a)(1)(i)(B), (a)(1)(ii)(B), and (a)(2)(ii).

* * * * *

System removal efficiency means [1 − Emission Rate (mass/time) / Feedrate (mass/time)] X 100.

* * * * *

TEQ means the international method of expressing toxicity equivalents for dioxins and furans as defined in U.S. EPA, Interim Procedures for Estimating Risks Associated with Exposures to Mixtures of Chlorinated Dibenzo-p-dioxins and -dibenzofurans (CDDs and CDFs) and 1989 Update, March 1989.

* * * * *

■ 5. Section 63.1203 is amended by:

■ a. Revising an undesignated center heading above the section heading.

■ b. Revising the section heading.

■ c. Revising paragraph (c)(3)(2).

The revisions and additions read as follows:

Interim Emissions Standards and Operating Limits For Incinerators, Cement Kilns, and Lightweight Aggregate Kilns

§ 63.1203 What are the standards for hazardous waste incinerators that are effective until compliance with the standards under § 63.1219?

* * * * *

(c) * * *

(3) * * *

(ii) You must specify one or more POHCs that are representative of the most difficult to destroy organic compounds in your hazardous waste feedstream. You must base this specification on the degree of difficulty of incineration of the organic constituents in the hazardous waste and on their concentration or mass in the hazardous waste feed, considering the results of hazardous waste analyses or other data and information.

* * * * *

■ 6. The section heading to § 63.1204 and paragraph (c)(3)(ii) are revised to read as follows:

§ 63.1204 What are the standards for hazardous waste burning cement kilns that are effective until compliance with the standards under § 63.1220?

* * * * *

(c) * * *

(3) * * *

(ii) You must specify one or more POHCs that are representative of the most difficult to destroy organic compounds in your hazardous waste feedstream. You must base this specification on the degree of difficulty of incineration of the organic constituents in the hazardous waste and on their concentration or mass in the hazardous waste feed, considering the results of hazardous waste analyses or other data and information.

* * * * *

■ 7. The section heading to § 63.1205 and paragraph (c)(3)(ii) are revised to read as follows:

§ 63.1205 What are the standards for hazardous waste burning lightweight aggregate kilns that are effective until compliance with the standards under § 63.1221?

* * * * *

(c) * * *

(3) * * *

(ii) You must specify one or more POHCs that are representative of the most difficult to destroy organic compounds in your hazardous waste feedstream. You must base this specification on the degree of difficulty of incineration of the organic constituents in the hazardous waste and on their concentration or mass in the hazardous waste feed, considering the results of hazardous waste analyses or other data and information.

* * * * *

■ 8. Section 63.1206 is amended by:

■ a. Revising paragraph (a).

■ b. Revising paragraphs (b)(1)(ii), (b)(6) introductory text, (b)(7)(i)(A), (b)(7)(ii), (b)(9)(i) introductory text, (b)(9)(i)(A), (b)(9)(iv)(A), (b)(9)(vi), (b)(9)(vii) introductory text, (b)(9)(viii)(D), (b)(9)(ix)(D), (b)(10)(i) introductory text, (b)(10)(i)(A), (b)(10)(vi), (b)(10)(vii) introductory text, (b)(10)(viii)(D), (b)(10)(ix)(D), (b)(11), (b)(13)(i) introductory text, (b)(13)(ii), and (b)(14).

■ c. Adding paragraph (b)(16).

■ d. Revising paragraphs (c)(1)(i) introductory text, (c)(3)(iv), (c)(6)(iii)(B) introductory text, (c)(6)(iv) introductory text, and (c)(7).

■ e. Adding paragraphs (c)(8) and (c)(9).

The revisions and additions read as follows:

§ 63.1206 When and how must you comply with the standards and operating requirements?

(a) *Compliance dates.* (1) *Compliance dates for incinerators, cement kilns, and lightweight aggregate kilns that burn hazardous waste.* (i) *Compliance date for standards under §§ 63.1203, 63.1204, and 63.1205.* (A) *Compliance dates for existing sources.* You must comply with the emission standards under §§ 63.1203, 63.1204, and 63.1205 and the other requirements of this subpart no later than the compliance date, September 30, 2003, unless the Administrator grants you an extension of time under § 63.6(i) or § 63.1213.

(B) *New or reconstructed sources.* (1) If you commenced construction or reconstruction of your hazardous waste combustor after April 19, 1996, you must comply with the emission standards under §§ 63.1203, 63.1204, and 63.1205 and the other requirements of this subpart by the later of September 30, 1999 or the date the source starts operations, except as provided by paragraph (a)(1)(i)(B)(2) of this section. The costs of retrofitting and replacement of equipment that is installed specifically to comply with this subpart, between April 19, 1996 and a source's compliance date, are not considered to be reconstruction costs.

(2) For a standard under §§ 63.1203, 63.1204, and 63.1205 that is more stringent than the standard proposed on April 19, 1996, you may achieve compliance no later than September 30, 2003 if you comply with the standard proposed on April 19, 1996 after September 30, 1999. This exception does not apply, however, to new or

reconstructed area source hazardous waste combustors that become major sources after September 30, 1999. As provided by § 63.6(b)(7), such sources must comply with the standards under §§ 63.1203, 63.1204, and 63.1205 at startup.

(ii) *Compliance date for standards under §§ 63.1219, 63.1220, and 63.1221.* (A) *Compliance dates for existing sources.* You must comply with the emission standards under §§ 63.1219, 63.1220, and 63.1221 and the other requirements of this subpart no later than the compliance date, October 14, 2008, unless the Administrator grants you an extension of time under § 63.6(i) or § 63.1213.

(B) *New or reconstructed sources.* (*1*) If you commenced construction or reconstruction of your hazardous waste combustor after April 20, 2004, you must comply with the new source emission standards under §§ 63.1219, 63.1220, and 63.1221 and the other requirements of this subpart by the later of October 12, 2005 or the date the source starts operations, except as provided by paragraph (a)(1)(ii)(B)(*2*) of this section. The costs of retrofitting and replacement of equipment that is installed specifically to comply with this subpart, between April 20, 2004, and a source's compliance date, are not considered to be reconstruction costs.

(*2*) For a standard under §§ 63.1219, 63.1220, and 63.1221 that is more stringent than the standard proposed on April 20, 2004, you may achieve compliance no later than October 14, 2008, if you comply with the standard proposed on April 20, 2004, after October 12, 2005. This exception does not apply, however, to new or reconstructed area source hazardous waste combustors that become major sources after October 14, 2008. As provided by § 63.6(b)(7), such sources must comply with the standards under §§ 63.1219, 63.1220, and 63.1221 at startup.

(2) *Compliance dates for solid fuel boilers, liquid fuel boilers, and hydrogen chloride production furnaces that burn hazardous waste for standards under §§ 63.1216, 63.1217, and 63.1218.* (i) *Compliance date for existing sources.* You must comply with the standards of this subpart no later than the compliance date, October 14, 2008, unless the Administrator grants you an extension of time under § 63.6(i) or § 63.1213.

(ii) *New or reconstructed sources.* (A) If you commenced construction or reconstruction of your hazardous waste combustor after October 12, 2005, you must comply with the new source emission standards of this subpart by the later of October 12, 2005, or the date the source starts operations, except as provided by paragraph (a)(2)(ii)(B) of this section. The costs of retrofitting and replacement of equipment that is installed specifically to comply with this subpart, between April 20, 2004, and a source's compliance date, are not considered to be reconstruction costs.

(B) For a standard in the subpart that is more stringent than the standard proposed on April 20, 2004, you may achieve compliance no later than October 14, 2008, if you comply with the standard proposed on April 20, 2004, after October 12, 2005. This exception does not apply, however, to new or reconstructed area source hazardous waste combustors that become major sources after October 14, 2008. As provided by § 63.6(b)(7), such sources must comply with this subpart at startup.

(3) *Early compliance.* If you choose to comply with the emission standards of this subpart prior to the dates specified in paragraphs (a)(1) and (a)(2) of this section, your compliance date is the earlier of the date you postmark the Notification of Compliance under § 63.1207(j)(1) or the dates specified in paragraphs (a)(1) and (a)(2) of this section.

(b) * * *

(1) * * *

(ii) When hazardous waste is not in the combustion chamber (i.e., the hazardous waste feed to the combustor has been cut off for a period of time not less than the hazardous waste residence time) and you have documented in the operating record that you are complying with all otherwise applicable requirements and standards promulgated under authority of sections 112 (e.g., 40 CFR part 63, subparts LLL, DDDDD, and NNNNN) or 129 of the Clean Air Act in lieu of the emission standards under §§ 63.1203, 63.1204, 63.1205, 63.1215, 63.1216, 63.1217, 63.1218, 63.1219, 63.1220, and 63.1221; the monitoring and compliance standards of this section and §§ 63.1207 through 63.1209, except the modes of operation requirements of § 63.1209(q); and the notification, reporting, and recordkeeping requirements of §§ 63.1210 through 63.1212.

* * * * *

(6) *Compliance with the carbon monoxide and hydrocarbon emission standards.* This paragraph applies to sources that elect to comply with the carbon monoxide and hydrocarbon emissions standards of this subpart by documenting continuous compliance with the carbon monoxide standard using a continuous emissions monitoring system and documenting compliance with the hydrocarbon standard during the destruction and removal efficiency (DRE) performance test or its equivalent.

* * * * *

(7) * * * (i) * * *

(A) You must document compliance with the Destruction and Removal Efficiency (DRE) standard under this subpart only once provided that you do not modify the source after the DRE test in a manner that could affect the ability of the source to achieve the DRE standard.

* * * * *

(ii) *Sources that feed hazardous waste at locations other than the normal flame zone.* (A) Except as provided by paragraph (b)(7)(ii)(B) of this section, if you feed hazardous waste at a location in the combustion system other than the normal flame zone, then you must demonstrate compliance with the DRE standard during each comprehensive performance test;

(B)(*1*) A cement kiln that feeds hazardous waste at a location other than the normal flame zone need only demonstrate compliance with the DRE standard during three consecutive comprehensive performance tests provided that:

(*i*) All three tests achieve the DRE standard in this subpart; and

(*ii*) The design, operation, and maintenance features of each of the three tests are similar;

(*iii*) The data in lieu restriction of § 63.1207(c)(2)(iv) does not apply when complying with the provisions of paragraph (b)(7)(ii)(B) of this section;

(*2*) If at any time you change your design, operation, and maintenance features in a manner that could reasonably be expected to affect your ability to meet the DRE standard, then you must comply with the requirements of paragraph (b)(7)(ii)(A) of this section.

* * * * *

(9) * * * (i) You may petition the Administrator to request alternative standards to the mercury or hydrogen chloride/chlorine gas emission standards of this subpart, to the semivolatile metals emission standards under §§ 63.1205, 63.1221(a)(3)(ii), or 63.1221(b)(3)(ii), or to the low volatile metals emissions standards under §§ 63.1205, 63.1221(a)(4)(ii), or 63.1221(b)(4)(ii) if:

(A) You cannot achieve one or more of these standards while using maximum achievable control technology (MACT) because of raw material contributions to emissions of mercury, semivolatile metals, low

volatile metals, or hydrogen chloride/chlorine gas; or

* * * * *

(iv) * * * (A) The alternative standard petition you submit under paragraph (b)(9)(i)(A) of this section must include data or information documenting that raw material contributions to emissions prevent you from complying with the emission standard even though the source is using MACT, as defined under paragraphs (b)(9)(viii) and (ix) of this section, for the standard for which you are seeking relief.

* * * * *

(vi) You must include data or information with semivolatile metals, low volatile metals, and hydrogen chloride/chlorine gas alternative standard petitions that you submit under paragraph (b)(9)(i)(A) of this section documenting that semivolatile metals, low volatile metals, and hydrogen chloride/chlorine gas emissions attributable to the hazardous waste only will not exceed the emission standards of this subpart.

(vii) You must not operate pursuant to your recommended alternative standards in lieu of emission standards specified in this subpart:

* * * * *

(viii) * * *

(D) For hydrogen chloride/chlorine gas, a hazardous waste chlorine feedrate corresponding to an MTEC of 2,000,000 µg/dscm or less, and use of an air pollution control device with a hydrogen chloride/chlorine gas removal efficiency of 85 percent or greater.

(ix) * * *

(D) For hydrogen chloride/chlorine gas, a hazardous waste chlorine feedrate corresponding to an MTEC of 14,000,000 µg/dscm or less, and use of an air pollution control device with a hydrogen chloride/chlorine gas removal efficiency of 99.6 percent or greater.

(10) * * * (i) You may petition the Administrator to request alternative standards to the mercury or hydrogen chloride/chlorine gas emission standards of this subpart, to the semivolatile metals emission standards under §§ 63.1204, 63.1220(a)(3)(ii), or 63.1220(b)(3)(ii), or to the low volatile metals emissions standards under §§ 63.1204, 63.1220(a)(4)(ii), or 63.1220(b)(4)(ii) if:

(A) You cannot achieve one or more of these standards while using maximum achievable control technology (MACT) because of raw material contributions to emissions of mercury, semivolatile metals, low volatile metals, or hydrogen chloride/chlorine gas; or

* * * * *

(vi) You must include data or information with semivolatile metals, low volatile metals, and hydrogen chloride/chlorine gas alternative standard petitions that you submit under paragraph (b)(10)(i)(A) of this section documenting that emissions of the regulated metals and hydrogen chloride/chlorine gas attributable to the hazardous waste only will not exceed the emission standards in this subpart.

(vii) You must not operate pursuant to your recommended alternative standards in lieu of emission standards specified in this subpart:

* * * * *

(viii) * * *

(D) For hydrogen chloride/chlorine gas, a hazardous waste chlorine feedrate corresponding to an MTEC of 720,000 µg/dscm or less.

(ix) * * *

(D) For hydrogen chloride/chlorine gas, a hazardous waste chlorine feedrate corresponding to an MTEC of 420,000 µg/dscm or less.

(11) *Calculation of hazardous waste residence time.* You must calculate the hazardous waste residence time and include the calculation in the performance test plan under § 63.1207(f) and the operating record. You must also provide the hazardous waste residence time in the Documentation of Compliance under § 63.1211(c) and the Notification of Compliance under §§ 63.1207(j) and 63.1210(d).

* * * * *

(13) * * *

(i) Cement kilns that feed hazardous waste at a location other than the end where products are normally discharged and where fuels are normally fired must comply with the carbon monoxide and hydrocarbon standards of this subpart as follows:

* * * * *

(ii) Lightweight aggregate kilns that feed hazardous waste at a location other than the end where products are normally discharged and where fuels are normally fired must comply with the hydrocarbon standards of this subpart as follows:

(A) Existing sources must comply with the 20 parts per million by volume hydrocarbon standard of this subpart;

(B) New sources must comply with the 20 parts per million by volume hydrocarbon standard of this subpart.

(14) *Alternative to the particulate matter standard for incinerators.* (i). *General.* In lieu of complying with the particulate matter standards under § 63.1203, you may elect to comply with the following alternative metal emission control requirements:

(ii) *Alternative metal emission control requirements for existing incinerators.* (A) You must not discharge or cause combustion gases to be emitted into the atmosphere that contain cadmium, lead, and selenium in excess of 240 µg/dscm, combined emissions, corrected to 7 percent oxygen; and,

(B) You must not discharge or cause combustion gases to be emitted into the atmosphere that contain antimony, arsenic, beryllium, chromium, cobalt, manganese, and nickel in excess of 97 µg/dscm, combined emissions, corrected to 7 percent oxygen.

(iii) *Alternative metal emission control requirements for new incinerators.* (A) You must not discharge or cause combustion gases to be emitted into the atmosphere that contain cadmium, lead, and selenium in excess of 24 µg/dscm, combined emissions, corrected to 7 percent oxygen; and,

(B) You must not discharge or cause combustion gases to be emitted into the atmosphere that contain antimony, arsenic, beryllium, chromium, cobalt, manganese, and nickel in excess of 97 µg/dscm, combined emissions, corrected to 7 percent oxygen.

(iv) *Operating limits.* Semivolatile and low volatile metal operating parameter limits must be established to ensure compliance with the alternative emission limitations described in paragraphs (e)(2) and (e)(3) of this section pursuant to § 63.1209(n), except that semivolatile metal feedrate limits apply to lead, cadmium, and selenium, combined, and low volatile metal feedrate limits apply to arsenic, beryllium, chromium, antimony, cobalt, manganese, and nickel, combined.

* * * * *

(16) *Compliance with subcategory standards for liquid fuel boilers.* You must comply with the mercury, semivolatile, low volatile metal, and total chlorine standards for liquid fuel boilers under § 63.1217 as follows:

(i) You must determine the as-fired heating value of each batch of hazardous waste fired by each firing system of the boiler so that you know the mass-weighted heating value of the hazardous waste fired at all times.

(ii) If the as-fired heating value of the hazardous waste is 10,000 Btu per pound or greater, you are subject to the thermal emission concentration standards (lb/million Btu) under § 63.1217.

(iii) If the as-fired heating value of the hazardous waste is less than 10,000 Btu/lb, you are subject to the mass or volume emission concentration

standards (μg/dscm or ppmv) under § 63.1217.

(iv) If the as-fired heating value of hazardous wastes varies above and below 10,000 Btu/lb over time, you are subject to the thermal concentration standards when the heating value is 10,000 Btu/lb or greater and the mass concentration standards when the heating value is less than 10,000 Btu/lb. You may elect to comply at all times with the more stringent operating requirements that ensure compliance with both the thermal emission concentration standards and the mass or volume emission concentration standards.

* * * * *

(c) * * * (1) * * * (i) You must operate only under the operating requirements specified in the Documentation of Compliance under § 63.1211(c) or the Notification of Compliance under §§ 63.1207(j) and 63.1210(d), except:

* * * * *

(3) * * *

(iv) *Failure of the AWFCO system.* If the AWFCO system fails to automatically and immediately cutoff the flow of hazardous waste upon exceedance of a parameter required to be interlocked with the AWFCO system under paragraph (c)(3)(i) of this section, you have failed to comply with the AWFCO requirements of paragraph (c)(3) of this section. If an equipment or other failure prevents immediate and automatic cutoff of the hazardous waste feed, however, you must cease feeding hazardous waste as quickly as possible.

* * * * *

(6) * * *

(iii) * * *

(B) Be trained under the requirements of, and certified under, one of the following American Society of Mechanical Engineers (ASME) standards: QHO–1–1994, QHO–1a–1996, or QHO–1–2004 (Standard for the Qualification and Certification of Hazardous Waste Incinerator Operators). If you elect to use the ASME program:

* * * * *

(iv) Control room operators of cement kilns, lightweight aggregate kilns, solid fuel boilers, liquid fuel boilers, and hydrochloric acid production furnaces must be trained and certified under:

* * * * *

(7) *Operation and maintenance plan*—(i) You must prepare and at all times operate according to an operation and maintenance plan that describes in detail procedures for operation, inspection, maintenance, and corrective measures for all components of the combustor, including associated pollution control equipment, that could affect emissions of regulated hazardous air pollutants.

(ii) The plan must prescribe how you will operate and maintain the combustor in a manner consistent with good air pollution control practices for minimizing emissions at least to the levels achieved during the comprehensive performance test.

(iii) This plan ensures compliance with the operation and maintenance requirements of § 63.6(e) and minimizes emissions of pollutants, automatic waste feed cutoffs, and malfunctions.

(iv) You must record the plan in the operating record.

(8) *Bag leak detection system requirements.* (i) If your combustor is equipped with a baghouse (fabric filter), you must continuously operate either:

(A) A bag leak detection system that meets the specifications and requirements of paragraph (c)(8)(ii) of this section and you must comply with the corrective measures and notification requirements of paragraphs (c)(8)(iii) and (iv) of this section; or

(B) A particulate matter detection system under paragraph (c)(9) of this section.

(ii) *Bag leak detection system specification and requirements.* (A) The bag leak detection system must be certified by the manufacturer to be capable of continuously detecting and recording particulate matter emissions at concentrations of 1.0 milligrams per actual cubic meter unless you demonstrate, under § 63.1209(g)(1), that a higher detection limit would routinely detect particulate matter loadings during normal operations;

(B) The bag leak detection system shall provide output of relative or absolute particulate matter loadings;

(C) The bag leak detection system shall be equipped with an alarm system that will sound an audible alarm when an increase in relative particulate loadings is detected over a preset level;

(D) The bag leak detection system shall be installed and operated in a manner consistent with available written guidance from the U.S. Environmental Protection Agency or, in the absence of such written guidance, the manufacturer's written specifications and recommendations for installation, operation, and adjustment of the system;

(E) The initial adjustment of the system shall, at a minimum, consist of establishing the baseline output by adjusting the sensitivity (range) and the averaging period of the device, and establishing the alarm set points and the alarm delay time;

(F) Following initial adjustment, you must not adjust the sensitivity or range, averaging period, alarm set points, or alarm delay time, except as detailed in the operation and maintenance plan required under paragraph (c)(7) of this section. You must not increase the sensitivity by more than 100 percent or decrease the sensitivity by more than 50 percent over a 365 day period unless such adjustment follows a complete baghouse inspection which demonstrates the baghouse is in good operating condition;

(G) For negative pressure or induced air baghouses, and positive pressure baghouses that are discharged to the atmosphere through a stack, the bag leak detector shall be installed downstream of the baghouse and upstream of any wet acid gas scrubber; and

(H) Where multiple detectors are required, the system's instrumentation and alarm system may be shared among the detectors.

(iii) *Bag leak detection system corrective measures requirements.* The operating and maintenance plan required by paragraph (c)(7) of this section must include a corrective measures plan that specifies the procedures you will follow in the case of a bag leak detection system alarm. The corrective measures plan must include, at a minimum, the procedures used to determine and record the time and cause of the alarm as well as the corrective measures taken to correct the control device malfunction or minimize emissions as specified below. Failure to initiate the corrective measures required by this paragraph is failure to ensure compliance with the emission standards in this subpart.

(A) You must initiate the procedures used to determine the cause of the alarm within 30 minutes of the time the alarm first sounds; and

(B) You must alleviate the cause of the alarm by taking the necessary corrective measure(s) which may include, but are not to be limited to, the following:

(*1*) Inspecting the baghouse for air leaks, torn or broken filter elements, or any other malfunction that may cause an increase in emissions;

(*2*) Sealing off defective bags or filter media;

(*3*) Replacing defective bags or filter media, or otherwise repairing the control device;

(*4*) Sealing off a defective baghouse compartment;

(*5*) Cleaning the bag leak detection system probe, or otherwise repairing the bag leak detection system; or

(*6*) Shutting down the combustor.

(iv) *Excessive exceedances notification.* If you operate the

combustor when the detector response exceeds the alarm set-point more than 5 percent of the time during any 6-month block time period, you must submit a notification to the Administrator within 30 days of the end of the 6-month block time period that describes the causes of the exceedances and the revisions to the design, operation, or maintenance of the combustor or baghouse you are taking to minimize exceedances. To document compliance with this requirement:

(A) You must keep records of the date, time, and duration of each alarm, the time corrective action was initiated and completed, and a brief description of the cause of the alarm and the corrective action taken;

(B) You must record the percent of the operating time during each 6-month period that the alarm sounds;

(C) In calculating the operating time percentage, if inspection of the fabric filter demonstrates that no corrective action is required, no alarm time is counted; and

(D) If corrective action is required, each alarm shall be counted as a minimum of 1 hour.

(9) *Particulate matter detection system requirements for electrostatic precipitators and ionizing wet scrubbers.* If your combustor is equipped with an electrostatic precipitator or ionizing wet scrubber, and you elect not to establish under § 63.1209(m)(1)(iv) site-specific control device operating parameter limits that are linked to the automatic waste feed cutoff system under paragraph (c)(3) of this section, you must continuously operate a particulate matter detection system that meets the specifications and requirements of paragraph (c)(9)(i) through (iii) of this section and you must comply with the corrective measures and notification requirements of paragraphs (c)(9)(iv) through (v) of this section.

(i) *Particulate matter detection system requirements.*—(A) The particulate matter detection system must be certified by the manufacturer to be capable of continuously detecting and recording particulate matter emissions at concentrations of 1.0 milligrams per actual cubic meter unless you demonstrate, under § 63.1209(g)(1), that a higher detection limit would routinely detect particulate matter loadings during normal operations;

(B) The particulate matter detector shall provide output of relative or absolute particulate matter loadings;

(C) The particulate matter detection system shall be equipped with an alarm system that will sound an audible alarm when an increase in relative or absolute particulate loadings is detected over the set-point

(D) You must install, operate, and maintain the particulate matter detection system in a manner consistent with the provisions of paragraph (c)(9) of this section and available written guidance from the U.S. Environmental Protection Agency or, in the absence of such written guidance, the manufacturer's written specifications and recommendations for installation, operation, maintenance and quality assurance of the system;

(E) You must include procedures for installation, operation, maintenance, and quality assurance of the particulate matter detection system in the site-specific continuous monitoring system test plan required under § 63.8(e)(3) of this chapter.

(F) Where multiple detectors are required to monitor multiple control devices, the system's instrumentation and alarm system may be shared among the detectors.

(G) You must establish the alarm set-point as provided by either paragraph (c)(9)(ii) or paragraph (c)(9)(iii) of this section.

(ii) *Establishing the alarm set-point without extrapolation.* (A) The alarm set-point is the average of the test run averages of the detector response achieved during the comprehensive performance test demonstrating compliance with the particulate matter emission standard.

(B) During the comprehensive performance test, you may simulate emission concentrations at the upper end of the range of normal operations by means including feeding high levels of ash and detuning the emission control equipment.

(C) You must comply with the alarm set-point on a 6-hour rolling average, updated each hour with a one-hour block average that is the average of the detector responses over each 15-minute block;

(iii) *Establishing the alarm set-point with extrapolation.* You may extrapolate the average of the test run averages of the detector response achieved during the comprehensive performance test as provided by paragraph (c)(9)(iii)(A) of this section to establish an alarm level after you approximate the correlation of the detector response to particulate matter concentration as prescribed by paragraph (c)(9)(iii)(B) of this section. You must comply with the extrapolated alarm set-point on a 6-hour rolling average, updated each hour with a one-hour block average that is the average of the detector responses over each 15-minute block.

(A) You may extrapolate the detector response up to a particulate matter concentration that is 50% of the particulate matter emission standard or 125% of the highest particulate matter concentration used to develop the correlation under paragraph (c)(9)(iii)(B) of this section, whichever is greater. The extrapolated emission concentration must not exceed the particulate matter emission standard.

(B) To establish an approximate correlation of the detector response to particulate matter emission concentrations, you should use as guidance Performance Specification-11 for PM CEMS (40 CFR Part 60, Appendix B), except that you need only conduct 5 runs to establish the initial correlation under Section 8.6 of Performance Specification 11.

(C) For quality assurance, you should use as guidance Procedure 2 of Appendix F to Part 60 of this chapter and the detector manufacturer's recommended procedures for periodic quality assurance checks and tests, except that:

(*1*) You must conduct annual Relative Response Audits as prescribed by Procedure 2 of Appendix F to Part 60 of this chapter (Section 10.3(6));

(*2*) You need only conduct Relative Response Audits on a 3-year interval after passing two sequential annual Relative Response Audits.

(D) An exceedance of the particulate matter emission standard by a particulate matter detection system for which particulate emission concentrations have been approximately correlated with the detector response under paragraph (c)(9)(iii) of this section is not evidence that the standard has been exceeded. The approximate correlation is used for compliance assurance to determine when corrective measures must be taken rather than for compliance monitoring.

(iv) *Particulate matter detection system corrective measures requirements.* The operating and maintenance plan required by paragraph (c)(7) of this section must include a corrective measures plan that specifies the procedures you will follow in the case of a particulate matter detection system alarm. The corrective measures plan must include, at a minimum, the procedures used to determine and record the time and cause of the alarm as well as the corrective measures taken to correct the control device malfunction or minimize emissions as specified below. Failure to initiate the corrective measures required by this paragraph is failure to ensure compliance with the emission standards in this subpart.

(A) You must initiate the procedures used to determine the cause of the alarm within 30 minutes of the time the alarm first sounds; and

(B) You must alleviate the cause of the alarm by taking the necessary corrective measure(s) which may include shutting down the combustor.

(v) *Excessive exceedances notification.* If you operate the combustor when the detector response exceeds the alarm set-point more than 5 percent of the time during any 6-month block time period, you must submit a notification to the Administrator within 30 days of the end of the 6-month block time period that describes the causes of the exceedances and the revisions to the design, operation, or maintenance of the combustor or emission control device you are taking to minimize exceedances. To document compliance with this requirement:

(A) You must keep records of the date, time, and duration of each alarm, the time corrective action was initiated and completed, and a brief description of the cause of the alarm and the corrective action taken;

(B) You must record the percent of the operating time during each 6-month period that the alarm sounds;

(C) In calculating the operating time percentage, if inspection of the emission control device demonstrates that no corrective action is required, no alarm time is counted; and

(D) If corrective action is required, each alarm shall be counted as a minimum of 1 hour.

■ 9. Section 63.1207 is amended by:
■ a. Revising paragraph (b)(1).
■ b. Adding paragraph (b)(3).
■ c. Revising paragraphs (c)(1) and (c)(2)(iii).
■ d. Adding paragraph (c)(3).
■ e. Revising paragraph (d)(4)(i).
■ f. Revising paragraphs (e)(2) and (e)(3)(iv).
■ g. Revising paragraphs (f)(1)(ii)(D), (f)(1)(x) introductory text, (f)(1)(xiii), (f)(1)(xiv), (f)(1)(xvi), and (f)(1)(xxv).
■ h. Adding paragraph (f)(1)(xv).
■ i. Revising paragraph (h)(2)(i).
■ j. Revising paragraph (j)(3).
■ k. Revising paragraph (l)(1) introductory text.
■ l. Revising paragraph (m)(2) introductory text.

The revisions and additions read as follows:

§ 63.1207 What are the performance testing requirements?

* * * * *

(b) * * *

(1) *Comprehensive performance test.* You must conduct comprehensive performance tests to demonstrate compliance with the emission standards provided by this subpart, establish limits for the operating parameters provided by § 63.1209, and demonstrate compliance with the performance specifications for continuous monitoring systems.

* * * * *

(3) *One-Time Dioxin/Furan Test for Sources Not Subject to a Numerical Dioxin/Furan Standard.* For solid fuel boilers and hydrochloric acid production furnaces, for lightweight aggregate kilns that are not subject to a numerical dioxin/furan emission standard under § 63.1221, and liquid fuel boilers that are not subject to a numerical dioxin/furan emission standard under § 63.1217, you must conduct a one-time emission test for dioxin/furan under feed and operating conditions that are most likely to reflect daily maximum operating variability, similar to a dioxin/furan comprehensive performance test.

(i) You must conduct the dioxin/furan emissions test no later than the deadline for conducting the initial comprehensive performance test.

(ii) You may use dioxin/furan emissions data from previous testing to meet this requirement, provided that:

(A) The testing was conducted under feed and operating conditions that are most likely to reflect daily maximum operating variability, similar to a dioxin/furan compliance test;

(B) You have not changed the design or operation of the source in a manner that could significantly affect stack gas dioxin/furan emission concentrations; and

(C) The data meet quality assurance objectives that may be determined on a site-specific basis.

(iii) You may use dioxin/furan emissions data from a source to represent emissions from another on-site source in lieu of testing (i.e., data in lieu of testing) if the design and operation, including hazardous waste feed and other feedstreams, of the sources are identical.

(iv) You must include the results of the one-time dioxin/furan emissions test with the results of the initial comprehensive performance test in the Notification of Compliance.

(v) You must repeat the dioxin/furan emissions test if you change the design or operation of the source in a manner that may increase dioxin/furan emissions.

(c) * * * (1) *Test date.* Except as provided by paragraphs (c)(2) and (c)(3) of this section, you must commence the initial comprehensive performance test not later than six months after the compliance date.

(2) * * * (iii) The data in lieu test age restriction provided in paragraph (c)(2)(i)(A) of this section does not apply for the duration of the interim standards (i.e., the standards published in the Federal Register on February 13, 2002, 67 FR 6792). See 40 CFR parts 63, 264, 265, 266, 270, and 271 revised as of July 1, 2002. Paragraph (c)(2)(i)(A) of this section does not apply until EPA promulgates permanent replacement standards pursuant to the Settlement Agreement noticed in the Federal Register on November 16, 2001 (66 FR 57715).

* * * * *

(3) For incinerators, cement kilns, and lightweight aggregate kilns, you must commence the initial comprehensive performance test to demonstrate compliance with the standards under §§ 63.1219, 63.1220, and 63.1221 not later than 12 months after the compliance date.

(d) * * *

(4) * * * (i) *Waiver of periodic comprehensive performance tests.* Except as provided in paragraph (c)(2) of this section, you must conduct only an initial comprehensive performance test under the interim standards (i.e., the standards published in the Federal Register on February 13, 2002); all subsequent comprehensive performance testing requirements are waived under the interim standards. The provisions in the introductory text to paragraph (d) and in paragraph (d)(1) of this section do not apply until EPA promulgates permanent replacement standards pursuant to the Settlement Agreement noticed in the Federal Register on November 16, 2001.

* * * * *

(e) * * *

(2) You must make your site-specific test plan and CMS performance evaluation test plan available to the public for review no later than 60 calendar days before initiation of the test. You must issue a public notice to all persons on your facility/public mailing list (developed pursuant to 40 CFR 70.7(h), 71.11(d)(3)(i)(E) and 124.10(c)(1)(ix)) announcing the availability of the test plans and the location where the test plans are available for review. The test plans must be accessible to the public for 60 calendar days, beginning on the date that you issue your public notice. The location must be unrestricted and provide access to the public during reasonable hours and provide a means for the public to obtain copies. The notification must include the following information at a minimum:

(i) The name and telephone number of the source's contact person;

(ii) The name and telephone number of the regulatory agency's contact person;

(iii) The location where the test plans and any necessary supporting documentation can be reviewed and copied;

(iv) The time period for which the test plans will be available for public review; and

(v) An expected time period for commencement and completion of the performance test and CMS performance evaluation test.

(3) * * *

(iv) *Public notice.* At the same time that you submit your petition to the Administrator, you must notify the public (e.g., distribute a notice to the facility/public mailing list developed pursuant to 40 CFR 70.7(h), 71.11(d)(3)(i)(E) and 124.10(c)(1)(ix)) of your petition to waive a performance test. The notification must include all of the following information at a minimum:

(A) The name and telephone number of the source's contact person;

(B) The name and telephone number of the regulatory agency's contact person;

(C) The date the source submitted its site-specific performance test plan and CMS performance evaluation test plans; and

(D) The length of time requested for the waiver.

(f) * * *

(1) * * *

(ii) * * *

(D) The Administrator may approve on a case-by-case basis a hazardous waste feedstream analysis for organic hazardous air pollutants in lieu of the analysis required under paragraph (f)(1)(ii)(A) of this section if the reduced analysis is sufficient to ensure that the POHCs used to demonstrate compliance with the applicable DRE standards of this subpart continue to be representative of the most difficult to destroy organic compounds in your hazardous waste feedstreams;

* * * * *

(x) If you are requesting to extrapolate metal feedrate limits from comprehensive performance test levels under §§ 63.1209(l)(1)(v) or 63.1209(n)(2)(vii):

* * * * *

(xiii) For cement kilns with in-line raw mills, if you elect to use the emissions averaging provision of this subpart, you must notify the Administrator of your intent in the initial (and subsequent) comprehensive performance test plan, and provide the information required by the emission averaging provision;

(xiv) For preheater or preheater/precalciner cement kilns with dual stacks, if you elect to use the emissions averaging provision of this subpart, you must notify the Administrator of your intent in the initial (and subsequent) comprehensive performance test plan, and provide the information required by the emission averaging provision;

(xv) If you request to use Method 23 for dioxin/furan you must provide the information required under § 63.1208(b)(1)(i)(B);

(xvi) If you are not required to conduct performance testing to document compliance with the mercury, semivolatile metals, low volatile metals, or hydrogen chloride/chlorine gas emission standards under paragraph (m) of this section, you must include with the comprehensive performance test plan documentation of compliance with the provisions of that section.

* * * * *

(xxv) If your source is equipped with a dry scrubber to control hydrogen chloride and chlorine gas, you must document in the comprehensive performance test plan key parameters that affect adsorption, and the limits you establish for those parameters based on the sorbent used during the performance test, if you elect not to specify and use the brand and type of sorbent used during the comprehensive performance test, as required by § 63.1209(o)(4)(iii)(A); and

* * * * *

(h) * * *

(2) * * *

(i) Operations when stack emissions testing for dioxin/furan, mercury, semivolatile metals, low volatile metals, particulate matter, or hydrogen chloride/chlorine gas is being performed; and

* * * * *

(j) * * *

(3) See §§ 63.7(g), 63.9(h), and 63.1210(d) for additional requirements pertaining to the Notification of Compliance (*e.g.*, you must include results of performance tests in the Notification of Compliance).

* * * * *

(l) *Failure of performance test*—(1) *Comprehensive performance test.* The provisions of this paragraph do not apply to the initial comprehensive performance test if you conduct the test prior to your compliance date.

* * * * *

(m) * * *

(2) You are not required to conduct performance tests to document compliance with the mercury, semivolatile metals, low volatile metals, or hydrogen chloride/chlorine gas emission standards under the conditions specified in this paragraph (m)(2). You are deemed to be in compliance with an emission standard if the twelve-hour rolling average maximum theoretical emission concentration (MTEC) does not exceed the emission standard:

* * * * *

■ 10. Section 63.1208 is amended by removing and reserving paragraph (a) and revising paragraphs (b)(1)(i) and (b)(5) to read as follows:

§ 63.1208 What are the test methods?

(a) [Reserved]

(b) * * *

(1) * * * (i) To determine compliance with the emission standard for dioxins and furans, you must use:

(A) Method 0023A, Sampling Method for Polychlorinated Dibenzo-*p*-Dioxins and Polychlorinated Dibenzofurans emissions from Stationary Sources, EPA Publication SW–846 (incorporated by reference— see § 63.14); or

(B) Method 23, provided in appendix A, part 60 of this chapter, after approval by the Administrator.

(*1*) You may request approval to use Method 23 in the performance test plan required under § 63.1207(e)(i) and (ii).

(*2*) In determining whether to grant approval to use Method 23, the Administrator may consider factors including whether dioxin/furan were detected at levels substantially below the emission standard in previous testing, and whether previous Method 0023 analyses detected low levels of dioxin/furan in the front half of the sampling train.

(*3*) Sources that emit carbonaceous particulate matter, such as coal-fired boilers, and sources equipped with activated carbon injection, will be deemed not suitable for use of Method 23 unless you document that there would not be a significant improvement in quality assurance with Method 0023A.

* * * * *

(5) *Hydrogen chloride and chlorine gas*—(i) *Compliance with MACT standards.* To determine compliance with the emission standard for hydrogen chloride and chlorine gas (combined), you must use:

(A) Method 26/26A as provided in appendix A, part 60 of this chapter; or

(B) Methods 320 or 321 as provided in appendix A, part 63 of this chapter, or

(C) ASTM D 6735–01, Standard Test Method for Measurement of Gaseous Chlorides and Fluorides from Mineral Calcining Exhaust Sources—Impinger Method to measure emissions of hydrogen chloride, and Method 26/26A to measure emissions of chlorine gas, provided that you follow the provisions in paragraphs (b)(5)(C)(*1*) through (*6*) of this section. ASTM D 6735–01 is available for purchase from at least one of the following addresses: American Society for Testing and Materials (ASTM), 100 Barr Harbor Drive, Post Office Box C700, West Conshohocken, PA 19428–2959; or ProQuest, 300 North Zeeb Road, Ann Arbor, MI 48106.

(*1*) A test must include three or more runs in which a pair of samples is obtained simultaneously for each run according to section 11.2.6 of ASTM Method D6735–01.

(*2*) You must calculate the test run standard deviation of each set of paired samples to quantify data precision, according to Equation 1 of this section:

$$RSD_a = (100)\,AbsoluteValue\left[\frac{C1_a - C2_a}{C1_a + C2_a}\right] \qquad (Eq.\ 1)$$

Where:

RSD_a = The test run relative standard deviation of sample pair a, percent.

$C1_a$ and $C2_a$ = The HCl concentrations, milligram/dry standard cubic meter (mg/dscm), from the paired samples.

(*3*) You must calculate the test average relative standard deviation according to Equation 2 of this section:

$$RSD_{TA} = \frac{\sum_{a=1}^{p} RSD_a}{p} \qquad (Eq.\ 2)$$

Where:

RSD_{TA} = The test average relative standard deviation, percent.

RSD_a = The test run relative standard deviation for sample pair a.

p = The number of test runs, ≥3.

(*4*) If RSDTA is greater than 20 percent, the data are invalid and the test must be repeated.

(*5*) The post-test analyte spike procedure of section 11.2.7 of ASTM Method D6735–01 is conducted, and the percent recovery is calculated according to section 12.6 of ASTM Method D6735–01.

(*6*) If the percent recovery is between 70 percent and 130 percent, inclusive, the test is valid. If the percent recovery is outside of this range, the data are considered invalid, and the test must be repeated.

(ii) *Compliance with risk-based limits under § 63.1215.* To demonstrate compliance with emission limits established under § 63.1215, you must use Method 26/26A as provided in appendix A, part 60 of this chapter, Method 320 as provided in appendix A, part 63 of this chapter, Method 321 as provided in appendix A, part 63 of this chapter, or ASTM D 6735–01, Standard Test Method for Measurement of Gaseous Chlorides and Fluorides from Mineral Calcining Exhaust Sources—Impinger Method (following the provisions of paragraphs (b)(5)(C)(*1*) through (*6*) of this section), except:

(A) For cement kilns and sources equipped with a dry acid gas scrubber, you must use Methods 320 or 321 as provided in appendix A, part 63 of this chapter, or ASTM D 6735–01 to measure hydrogen chloride, and the back-half, caustic impingers of Method 26/26A as provided in appendix A, part 60 of this chapter to measure chlorine gas; and

(B) For incinerators, boilers, and lightweight aggregate kilns, you must use Methods 320 or 321 as provided in appendix A, part 63 of this chapter, or ASTM D 6735–01 to measure hydrogen chloride, and Method 26/26A as provided in appendix A, part 60 of this chapter to measure total chlorine, and calculate chlorine gas by difference if:

(*1*) The bromine/chlorine ratio in feedstreams is greater than 5 percent; or

(*2*) The sulfur/chlorine ratio in feedstreams is greater than 50 percent.

* * * * *

■ 11. Section 63.1209 is amended by:

■ a. Revising paragraphs (a)(1)(ii), (a)(1)(iv)(D), (a)(1)(v)(D), and (a)(5).

■ b. Revising paragraph (b)(2)(ii).

■ c. Revising the heading of paragraph (g)(1) introductory text and paragraph (g)(1)(i).

■ d. Adding paragraph (g)(1)(iv).

■ e. Revising paragraphs (k)(1)(i) and (k)(2)(i).

■ f. Revising paragraph (l)(1).

■ g. Revising paragraphs (m)(1)(iv) introductory text and (m)(3).

■ h. Revising paragraph (n)(2).

■ i. Revising the heading of paragraph (o) introductory text and paragraph (o)(1).

■ j. Adding paragraph (r).

The revisions read as follows:

§ 63.1209 What are the monitoring requirements?

(a) * * *

(1) * * *

(ii) (A) *Cement kilns under § 63.1204*—Except as provided by paragraphs (a)(1)(iv) and (a)(1)(v) of the section, you must use a COMS to demonstrate and monitor compliance with the opacity standard under §§ 63.1204(a)(7) and (b)(7) at each point where emissions are vented from these affected sources including the bypass stack of a preheater or preheater/precalciner kiln with dual stacks.

(B) *Cement kilns under § 63.1220*—Except as provided by paragraphs (a)(1)(iv) and (a)(1)(v) of the section and unless your source is equipped with a bag leak detection system under § 63.1206(c)(8) or a particulate matter detection system under § 63.1206(c)(9), you must use a COMS to demonstrate and monitor compliance with the opacity standard under §§ 63.1220(a)(7) and (b)(7) at each point where emissions are vented from these affected sources including the bypass stack of a preheater or preheater/precalciner kiln with dual stacks.

(C) You must maintain and operate each COMS in accordance with the requirements of § 63.8(c) except for the requirements under § 63.8(c)(3). The requirements of § 63.1211(c) shall be complied with instead of § 63.8(c)(3); and

(D) Compliance is based on a six-minute block average.

* * * * *

(iv) * * *

(D) To remain in compliance, all six-minute block averages must not exceed the opacity standard.

(v) * * *

(D) To remain in compliance, all six-minute block averages must not exceed the opacity standard.

* * * * *

(5) *Petitions to use CEMS for other standards.* You may petition the Administrator to use CEMS for compliance monitoring for particulate matter, mercury, semivolatile metals, low volatile metals, and hydrogen chloride and chlorine gas under § 63.8(f) in lieu of compliance with the corresponding operating parameter limits under this section.

* * * * *

(b) * * *

(2) * * *

(ii) *Accuracy and calibration of weight measurement devices for activated carbon injection systems.* If you operate a carbon injection system, the accuracy of the weight measurement device must be ± 1 percent of the weight being measured. The calibration of the device must be verified at least once each calendar quarter at a frequency of approximately 120 days.

* * * * *

(g) * * *

(1) *Requests to use alternatives to operating parameter monitoring requirements.* (i) You may submit an application to the Administrator under this paragraph for approval of alternative operating parameter monitoring requirements to document compliance with the emission standards of this subpart. For requests to use additional CEMS, however, you must use paragraph (a)(5) of this section and § 63.8(f). Alternative requests to operating parameter monitoring requirements that include unproven monitoring methods may not be made under this paragraph and must be made under § 63.8(f).

* * * * *

(iv) *Dual Standards that incorporate the Interim Standards for HAP metals.* (A) *Semivolatile and Low Volatile Metals.* You may petition the Administrator to waive a feedrate operating parameter limit under paragraph (n)(2) of this section for either the emission standards expressed in a thermal emissions format or the interim standards based on documentation that the feedrate operating parameter limit is not needed to ensure compliance with the relevant standard on a continuous basis.

(B) *Mercury.* You may petition the Administrator to waive a feedrate operating parameter limit under paragraph (l)(1) of this section for either the feed concentration standard under §§ 63.1220(a)(2)(i) and (b)(2)(i) or the interim standards based on documentation that the feedrate operating parameter limit is not needed to ensure compliance with the relevant standard on a continuous basis.

* * * * *

(k) * * *

(1) * * * (i) For sources other than a lightweight aggregate kiln, if the combustor is equipped with an electrostatic precipitator, baghouse (fabric filter), or other dry emissions control device where particulate matter is suspended in contact with combustion gas, you must establish a limit on the maximum temperature of the gas at the inlet to the device on an hourly rolling average. You must establish the hourly rolling average limit as the average of the test run averages.

* * * * *

(2) * * * (i) For sources other than cement kilns, you must measure the temperature of each combustion chamber at a location that best represents, as practicable, the bulk gas temperature in the combustion zone. You must document the temperature measurement location in the test plan you submit under §§ 63.1207(e) and (f);

* * * * *

(l) *Mercury.* * * *

(1) *Feedrate of mercury.* (i) For incinerators and solid fuel boilers, when complying with the mercury emission standards under §§ 63.1203, 63.1216 and 63.1219, you must establish a 12-hour rolling average limit for the total feedrate of mercury in all feedstreams as the average of the test run averages.

(ii) For liquid fuel boilers, when complying with the mercury emission standards of § 63.1217, you must establish a rolling average limit for the mercury feedrate as follows on an averaging period not to exceed an annual rolling average:

(A) You must calculate a mercury system removal efficiency for each test run and calculate the average system removal efficiency of the test run averages. If emissions exceed the mercury emission standard during the comprehensive performance test, it is not a violation because the averaging period for the mercury emission standard is (not-to-exceed) one year and compliance is based on compliance with the mercury feedrate limit with an averaging period not-to-exceed one year.

(B) If you burn hazardous waste with a heating value of 10,000 Btu/lb or greater, you must calculate the mercury feedrate limit as follows:

(*1*) The mercury feedrate limit is the emission standard divided by [1 − system removal efficiency].

(*2*) The mercury feedrate limit is a hazardous waste thermal concentration limit expressed as pounds of mercury in hazardous waste feedstreams per million Btu of hazardous waste fired.

(*3*) You must comply with the hazardous waste mercury thermal concentration limit by determining the feedrate of mercury in all hazardous waste feedstreams (lb/hr) at least once a minute and the hazardous waste thermal feedrate (MM Btu/hr) at least once a minute to calculate a 60-minute average thermal emission concentration as [hazardous waste mercury feedrate (lb/hr) / hazardous waste thermal feedrate (MM Btu/hr)].

(*4*) You must calculate a rolling average hazardous waste mercury thermal concentration that is updated each hour.

(*5*) If you select an averaging period for the feedrate limit that is greater than a 12-hour rolling average, you must calculate the initial rolling average as though you had selected a 12-hour rolling average, as provided by paragraph (b)(5)(i) of this section. You must calculate rolling averages thereafter as the average of the available one-minute values until enough one-minute values are available to calculate the rolling average period you select. At that time and thereafter, you update the rolling average feedrate each hour with a 60-minute average feedrate.

(C) If you burn hazardous waste with a heating value of less than 10,000 Btu/lb, you must calculate the mercury feedrate limit as follows:

(*1*) You must calculate the mercury feedrate limit as the mercury emission standard divided by [1 − System Removal Efficiency].

(*2*) The feedrate limit is expressed as a mass concentration per unit volume of stack gas (μg/dscm) and is converted to a mass feedrate (lb/hr) by multiplying it by the average stack gas flowrate of the test run averages.

(*3*) You must comply with the feedrate limit by determining the mercury feedrate (lb/hr) at least once a minute to calculate a 60-minute average feedrate.

(*4*) You must update the rolling average feedrate each hour with this 60-minute feedrate measurement.

(*5*) If you select an averaging period for the feedrate limit that is greater than a 12-hour rolling average, you must calculate the initial rolling average as though you had selected a 12-hour rolling average, as provided by paragraph (b)(5)(i) of this section. You must calculate rolling averages thereafter as the average of the available one-minute values until enough one-minute values are available to calculate the rolling average period you select. At that time and thereafter, you update the rolling average feedrate each hour with a 60-minute average feedrate.

(D) If your boiler is equipped with a wet scrubber, you must comply with the following unless you document in the performance test plan that you do not feed chlorine at rates that may substantially affect the system removal efficiency of mercury for purposes of establishing a mercury feedrate limit based on the system removal efficiency during the test:

(*1*) Scrubber blowdown must be minimized during a pretest conditioning period and during the performance test:

(*2*) Scrubber water must be preconditioned so that mercury in the

water is at equilibrium with stack gas at the mercury feedrate level of the performance test; and

(3) You must establish an operating limit on minimum pH of scrubber water as the average of the test run averages and comply with the limit on an hourly rolling average.

(iii) For cement kilns:

(A) When complying with the emission standards under §§ 63.1220(a)(2)(i) and (b)(2)(i), you must:

(1) Comply with the mercury hazardous waste feed concentration operating requirement on a twelve-hour rolling average;

(2) Monitor and record in the operating record the as-fired mercury concentration in the hazardous waste (or the weighted-average mercury concentration for multiple hazardous waste feedstreams);

(3) Initiate an automatic waste feed cutoff that immediately and automatically cuts off the hazardous waste feed when the as-fired mercury concentration operating requirement is exceeded;

(B) When complying with the emission standards under §§ 63.1204, 63.1220(a)(2)(ii) and (b)(2)(ii), you must establish a 12-hour rolling average limit for the total feedrate of mercury in all feedstreams as the average of the test run averages;

(C) Except as provided by paragraph (l)(1)(iii)(D) of this section, when complying with the hazardous waste feedrate corresponding to a maximum theoretical emission concentration (MTEC) under §§ 63.1220(a)(2)(iii) and (b)(2)(iii), you must:

(1) Comply with the MTEC operating requirement on a twelve-hour rolling average;

(2) Monitor and record the feedrate of mercury for each hazardous waste feedstream according to § 63.1209(c);

(3) Monitor with a CMS and record in the operating record the gas flowrate (either directly or by monitoring a surrogate parameter that you have correlated to gas flowrate);

(4) Continuously calculate and record in the operating record a MTEC assuming mercury from all hazardous waste feedstreams is emitted;

(5) Initiate an automatic waste feed cutoff that immediately and automatically cuts off the hazardous waste feed when the MTEC operating requirement is exceeded;

(D) In lieu of complying with paragraph (l)(1)(iii)(C) of this section, you may:

(1) Identify in the Notification of Compliance a minimum gas flowrate limit and a maximum feedrate limit of mercury from all hazardous waste feedstreams that ensures the MTEC calculated in paragraph (l)(1)(iii)(B)(4) of this section is below the operating requirement under paragraphs §§ 63.1220(a)(2)(iii) and (b)(2)(iii); and

(2) Initiate an automatic waste feed cutoff that immediately and automatically cuts off the hazardous waste feed when either the gas flowrate or mercury feedrate exceeds the limits identified in paragraph (l)(1)(iv)(D)(1) of this section.

(iv) For lightweight aggregate kilns:

(A) When complying with the emission standards under §§ 63.1205, 63.1221(a)(2)(i) and (b)(2)(i), you must establish a 12-hour rolling average limit for the total feedrate of mercury in all feedstreams as the average of the test run averages;

(B) Except as provided by paragraph (l)(1)(iv)(C) of this section, when complying with the hazardous waste feedrate corresponding to a maximum theoretical emission concentration (MTEC) under §§ 63.1221(a)(2)(ii) and (b)(2)(ii), you must:

(1) Comply with the MTEC operating requirement on a twelve-hour rolling average;

(2) Monitor and record the feedrate of mercury for each hazardous waste feedstream according to § 63.1209(c);

(3) Monitor with a CMS and record in the operating record the gas flowrate (either directly or by monitoring a surrogate parameter that you have correlated to gas flowrate);

(4) Continuously calculate and record in the operating record a MTEC assuming mercury from all hazardous waste feedstreams is emitted;

(5) Initiate an automatic waste feed cutoff that immediately and automatically cuts off the hazardous waste feed when the MTEC operating requirement is exceeded;

(C) In lieu of complying with paragraph (l)(1)(iv)(B) of this section, you may:

(1) Identify in the Notification of Compliance a minimum gas flowrate limit and a maximum feedrate limit of mercury from all hazardous waste feedstreams that ensures the MTEC calculated in paragraph (l)(1)(iv)(B)(4) of this section is below the operating requirement under paragraphs §§ 63.1221(a)(2)(ii) and (b)(2)(ii); and

(2) Initiate an automatic waste feed cutoff that immediately and automatically cuts off the hazardous waste feed when either the gas flowrate or mercury feedrate exceeds the limits identified in paragraph (l)(1)(iv)(C)(1) of this section.

(v) *Extrapolation of feedrate levels.* In lieu of establishing mercury feedrate limits as specified in paragraphs (l)(1)(i) through (iv) of this section, you may request as part of the performance test plan under §§ 63.7(b) and (c) and §§ 63.1207 (e) and (f) to use the mercury feedrates and associated emission rates during the comprehensive performance test to extrapolate to higher allowable feedrate limits and emission rates. The extrapolation methodology will be reviewed and approved, as warranted, by the Administrator. The review will consider in particular whether:

(A) Performance test metal feedrates are appropriate (*i.e.*, whether feedrates are at least at normal levels; depending on the heterogeneity of the waste, whether some level of spiking would be appropriate; and whether the physical form and species of spiked material is appropriate); and

(B) Whether the extrapolated feedrates you request are warranted considering historical metal feedrate data.

* * * * *

(m) * * *

(1) * * *

(iv) *Other particulate matter control devices.* For each particulate matter control device that is not a fabric filter or high energy wet scrubber, or is not an electrostatic precipitator or ionizing wet scrubber for which you elect to monitor particulate matter loadings under § 63.1206(c)(9) of this chapter for process control, you must ensure that the control device is properly operated and maintained as required by § 63.1206(c)(7) and by monitoring the operation of the control device as follows:

* * * * *

(3) *Maximum ash feedrate.* Owners and operators of hazardous waste incinerators, solid fuel boilers, and liquid fuel boilers must establish a maximum ash feedrate limit as a 12-hour rolling average based on the average of the test run averages. This requirement is waived, however, if you comply with the particulate matter detection system requirements under § 63.1206(c)(9).

(n) * * *

(2) *Maximum feedrate of semivolatile and low volatile metals.* (i) *General.* You must establish feedrate limits for semivolatile metals (cadmium and lead) and low volatile metals (arsenic, beryllium, and chromium) as follows, except as provided by paragraph (n)(2)(vii) of this section.

(ii) For incinerators, cement kilns, and lightweight aggregate kilns, when complying with the emission standards under §§ 63.1203, 63.1204, 63.1205, and 63.1219, and for solid fuel boilers when complying with the emission standards

under § 63.1216, you must establish 12-hour rolling average limits for the total feedrate of semivolatile and low volatile metals in all feedstreams as the average of the test run averages.

(iii) *Cement kilns under § 63.1220*—(A) When complying with the emission standards under §§ 63.1220(a)(3)(i), (a)(4)(i), (b)(3)(i), and (b)(4)(i), you must establish 12-hour rolling average feedrate limits for semivolatile and low volatile metals as the thermal concentration of semivolatile metals or low volatile metals in all hazardous waste feedstreams. You must calculate hazardous waste thermal concentrations for semivolatile metals and low volatile metals for each run as the total mass feedrate of semivolatile metals or low volatile metals for all hazardous waste feedstreams divided by the total heat input rate for all hazardous waste feedstreams. The 12-hour rolling average feedrate limits for semivolatile metals and low volatile metals are the average of the hazardous waste thermal concentrations for the runs.

(B) When complying with the emission standards under §§ 63.1220(a)(3)(ii), (a)(4)(ii), (b)(3)(ii), and (b)(4)(ii), you must establish 12-hour rolling average limits for the total feedrate of semivolatile and low volatile metals in all feedstreams as the average of the test run averages.

(iv) *Lightweight aggregate kilns under § 63.1221*—(A) When complying with the emission standards under §§ 63.1221(a)(3)(i), (a)(4)(i), (b)(3)(i), and (b)(4)(i), you must establish 12-hour rolling average feedrate limits for semivolatile and low volatile metals as the thermal concentration of semivolatile metals or low volatile metals in all hazardous waste feedstreams as specified in paragraphs (n)(2)(iii)(A) of this section.

(B) When complying with the emission standards under §§ 63.1221(a)(3)(ii), (a)(4)(ii), (b)(3)(ii), and (b)(4)(ii), you must establish 12-hour rolling average limits for the total feedrate of semivolatile and low volatile metals in all feedstreams as the average of the test run averages.

(v) *Liquid fuel boilers under § 63.1217.* (A) *Semivolatile metals.* You must establish a rolling average limit for the semivolatile metal feedrate as follows on an averaging period not to exceed an annual rolling average.

(*1*) *System removal efficiency.* You must calculate a semivolatile metal system removal efficiency for each test run and calculate the average system removal efficiency of the test run averages. If emissions exceed the semivolatile metal emission standard during the comprehensive performance test, it is not a violation because the averaging period for the semivolatile metal emission standard is one year and compliance is based on compliance with the semivolatile metal feedrate limit that has an averaging period not to exceed an annual rolling average.

(*2*) *Boilers that feed hazardous waste with a heating value of 10,000 Btu/lb or greater.* You must calculate the semivolatile metal feedrate limit as the semivolatile metal emission standard divided by [1 − System Removal Efficiency].

(*i*) The feedrate limit is a hazardous waste thermal concentration limit expressed as pounds of semivolatile metals in all hazardous waste feedstreams per million Btu of hazardous waste fed to the boiler.

(*ii*) You must comply with the hazardous waste semivolatile metal thermal concentration limit by determining the feedrate of semivolatile metal in all hazardous waste feedstreams (lb/hr) and the hazardous waste thermal feedrate (MM Btu/hr) at least once a minute to calculate a 60-minute average thermal emission concentration as [hazardous waste semivolatile metal feedrate (lb/hr) / hazardous waste thermal feedrate (MM Btu/hr)].

(*iii*) You must calculate a rolling average hazardous waste semivolatile metal thermal concentration that is updated each hour.

(*iv*) If you select an averaging period for the feedrate limit that is greater than a 12-hour rolling average, you must calculate the initial rolling average as though you had selected a 12-hour rolling average, as provided by paragraph (b)(5)(i) of this section. You must calculate rolling averages thereafter as the average of the available one-minute values until enough one-minute values are available to calculate the rolling average period you select. At that time and thereafter, you update the rolling average feedrate each hour with a 60-minute average feedrate.

(*3*) *Boilers that feed hazardous waste with a heating value less than 10,000 Btu/lb.* (*i*) You must calculate the semivolatile metal feedrate limit as the semivolatile metal emission standard divided by [1 − System Removal Efficiency].

(*ii*) The feedrate limit is expressed as a mass concentration per unit volume of stack gas (μg/dscm) and is converted to a mass feedrate (lb/hr) by multiplying it by the average stack gas flowrate (dscm/hr) of the test run averages.

(*iii*) You must comply with the feedrate limit by determining the semivolatile metal feedrate (lb/hr) at least once a minute to calculate a 60-minute average feedrate.

(*iv*) You must update the rolling average feedrate each hour with this 60-minute feedrate measurement.

(*v*) If you select an averaging period for the feedrate limit that is greater than a 12-hour rolling average, you must calculate the initial rolling average as though you had selected a 12-hour rolling average, as provided by paragraph (b)(5)(i) of this section. You must calculate rolling averages thereafter as the average of the available one-minute values until enough one-minute values are available to calculate the rolling average period you select. At that time and thereafter, you update the rolling average feedrate each hour with a 60-minute average feedrate.

(B) *Chromium.* (*1*) *Boilers that feed hazardous waste with a heating value of 10,000 Btu/lb or greater.* (*i*) The feedrate limit is a hazardous waste thermal concentration limit expressed as pounds of chromium in all hazardous waste feedstreams per million Btu of hazardous waste fed to the boiler.

(*ii*) You must comply with the hazardous waste chromium thermal concentration limit by determining the feedrate of chromium in all hazardous waste feedstreams (lb/hr) and the hazardous waste thermal feedrate (MM Btu/hr) at least once a minute to calculate a 60-minute average thermal emission concentration as [hazardous waste chromium feedrate (lb/hr) / hazardous waste thermal feedrate (MM Btu/hr)]. You must update the rolling average feedrate each hour with this 60-minute average feedrate measurement.

(*2*) *Boilers that feed hazardous waste with a heating value less than 10,000 Btu/lb.* You must establish a 12-hour rolling average limit for the total feedrate (lb/hr) of chromium in all feedstreams as the average of the test run averages. You must update the rolling average feedrate each hour with a 60-minute average feedrate measurement.

(vi) *LVM limits for pumpable wastes.* You must establish separate feedrate limits for low volatile metals in pumpable feedstreams using the procedures prescribed above for total low volatile metals. Dual feedrate limits for both pumpable and total feedstreams are not required, however, if you base the total feedrate limit solely on the feedrate of pumpable feedstreams.

(vii) *Extrapolation of feedrate levels.* In lieu of establishing feedrate limits as specified in paragraphs (l)(1)(i) through (iii) of this section, you may request as part of the performance test plan under §§ 63.7(b) and (c) and §§ 63.1207(e) and (f) to use the semivolatile metal and low

volatile metal feedrates and associated emission rates during the comprehensive performance test to extrapolate to higher allowable feedrate limits and emission rates. The extrapolation methodology will be reviewed and approved, as warranted, by the Administrator. The review will consider in particular whether:

(A) Performance test metal feedrates are appropriate (*i.e.*, whether feedrates are at least at normal levels; depending on the heterogeneity of the waste, whether some level of spiking would be appropriate; and whether the physical form and species of spiked material is appropriate); and

(B) Whether the extrapolated feedrates you request are warranted considering historical metal feedrate data.

* * * * *

(o) *Hydrogen chloride and chlorine gas.* * * *

(1) *Feedrate of total chlorine and chloride.* (i) *Incinerators, cement kilns, lightweight aggregate kilns, solid fuel boilers, and hydrochloric acid production furnaces.* You must establish a 12-hour rolling average limit for the total feedrate of chlorine (organic and inorganic) in all feedstreams as the average of the test run averages.

(ii) *Liquid fuel boilers.* (A) *Boilers that feed hazardous waste with a heating value not less than 10,000 Btu/lb.* (*1*) The feedrate limit is a hazardous waste thermal concentration limit expressed as pounds of chlorine (organic and inorganic) in all hazardous waste feedstreams per million Btu of hazardous waste fed to the boiler.

(*2*) You must establish a 12-hour rolling average feedrate limit as the average of the test run averages.

(*3*) You must comply with the feedrate limit by determining the mass feedrate of hazardous waste feedstreams (lb/hr) at least once a minute and by knowing the chlorine (organic and inorganic) content and heating value (million Btu/lb) of hazardous waste feedstreams at all times to calculate a 60-minute average feedrate measurement as [hazardous waste chlorine feedrate (lb/hr) / hazardous waste thermal feedrate (million Btu/hr)]. You must update the rolling average feedrate each hour with this 60-minute average feedrate measurement.

(B) *Boilers that feed hazardous waste with a heating value less than 10,000 Btu/lb.* You must establish a 12-hour rolling average limit for the total feedrate of chlorine (organic and inorganic) in all feedstreams as the average of the test run averages. You must update the rolling average feedrate each hour with a 60-minute average feedrate measurement.

* * * * *

(r) *Averaging periods.* The averaging periods specified in this section for operating parameters are not-to-exceed averaging periods. You may elect to use shorter averaging periods. For example, you may elect to use a 1-hour rolling average rather than the 12-hour rolling average specified in paragraph (l)(1)(i) of this section for mercury.

■ 12. Section 63.1210 is amended by:
■ a. Revising the table in paragraph (a)(1) and the table in paragraph (a)(2).
■ b. Redesignating paragraph (b) as (d).
■ c. Adding new paragraph (b).
■ d. Adding new paragraph (c).

The revisions and additions read as follows:

§ 63.1210 What are the notification requirements?

(a) * * *

(1) * * *

Reference	Notification
63.9(b)	Initial notifications that you are subject to Subpart EEE of this Part.
63.9(d)	Notification that you are subject to special compliance requirements.
63.9(j)	Notification and documentation of any change in information already provided under § 63.9.
63.1206(b)(5)(i)	Notification of changes in design, operation, or maintenance.
63.1206(c)(7)(ii)(C)	Notification of excessive bag leak detection system exceedances.
63.1207(e), 63.9(e) 63.9(g)(1) and (3)	Notification of performance test and continuous monitoring system evaluation, including the performance test plan and CMS performance evaluation plan.[1]
63.1210(b)	Notification of intent to comply.
63.1210(d), 63.1207(j), 63.1207(k), 63.1207(l), 63.9(h), 63.10(d)(2), 63.10(e)(2).	Notification of compliance, including results of performance tests and continuous monitoring system performance evaluations.

[1] You may also be required on a case-by-case basis to submit a feedstream analysis plan under § 63.1209(c)(3).

(2) * * *

Reference	Notification, request, petition, or application 6
63.9(i)	You may request an adjustment to time periods or postmark deadlines for submittal and review of required information.
63.10(e)(3)(ii)	You may request to reduce the frequency of excess emissions and CMS performance reports.
63.10(f)	You may request to waive recordkeeping or reporting requirements.
63.1204(d)(2)(iii), 63.1220(d)(2)(iii)	Notification that you elect to comply with the emission averaging requirements for cement kilns with in-line raw mills.
63.1204(e)(2)(iii), 63.1220(e)(2)(iii)	Notification that you elect to comply with the emission averaging requirements for preheater or preheater/precalciner kilns with dual stacks.
63.1206(b)(4), 63.1213, 63.6(i), 63.9(c)	You may request an extension of the compliance date for up to one year.
63.1206(b)(5)(i)(C)	You may request to burn hazardous waste for more than 720 hours and for purposes other than testing or pretesting after making a change in the design or operation that could affect compliance with emission standards and prior to submitting a revised Notification of Compliance.
63.1206(b)(9)(iii)(B)	If you elect to conduct particulate matter CEMS correlation testing and wish to have federal particulate matter and opacity standards and associated operating limits waived during the testing, you must notify the Administrator by submitting the correlation test plan for review and approval.
63.1206(b)(8)(v)	You may request approval to have the particulate matter and opacity standards and associated operating limits and conditions waived for more than 96 hours for a correlation test.

Reference	Notification, request, petition, or application 6
63.1206(b)(9)	Owners and operators of lightweight aggregate kilns may request approval of alternative emission standards for mercury, semivolatile metal, low volatile metal, and hydrogen chloride/chlorine gas under certain conditions.
63.1206(b)(10)	Owners and operators of cement kilns may request approval of alternative emission standards for mercury, semivolatile metal, low volatile metal, and hydrogen chloride/chlorine gas under certain conditions.
63.1206(b)(14)	Owners and operators of incinerators may elect to comply with an alternative to the particulate matter standard.
63.1206(b)(15)	Owners and operators of cement and lightweight aggregate kilns may request to comply with the alternative to the interim standards for mercury.
63.1206(c)(2)(ii)(C)	You may request to make changes to the startup, shutdown, and malfunction plan.
63.1206(c)(5)(i)(C)	You may request an alternative means of control to provide control of combustion system leaks.
63.1206(c)(5)(i)(D)	You may request other techniques to prevent fugitive emissions without use of instantaneous pressure limits.
63.1207(c)(2)	You may request to base initial compliance on data in lieu of a comprehensive performance test.
63.1207(d)(3)	You may request more than 60 days to complete a performance test if additional time is needed for reasons beyond your control.
63.1207(e)(3), 63.7(h)	You may request a time extension if the Administrator fails to approve or deny your test plan.
63.1207(h)(2)	You may request to waive current operating parameter limits during pretesting for more than 720 hours.
63.1207(f)(1)(ii)(D)	You may request a reduced hazardous waste feedstream analysis for organic hazardous air pollutants if the reduced analysis continues to be representative of organic hazardous air pollutants in your hazardous waste feedstreams.
63.1207(g)(2)(v)	You may request to operate under a wider operating range for a parameter during confirmatory performance testing.
63.1207(i)	You may request up to a one-year time extension for conducting a performance test (other than the initial comprehensive performance test) to consolidate testing with other state or federally-required testing.
63.1207(j)(4)	You may request more than 90 days to submit a Notification of Compliance after completing a performance test if additional time is needed for reasons beyond your control.
63.1207(l)(3)	After failure of a performance test, you may request to burn hazardous waste for more than 720 hours and for purposes other than testing or pretesting.
63.1209(a)(5), 63.8(f)	You may request: (1) Approval of alternative monitoring methods for compliance with standards that are monitored with a CEMS; and (2) approval to use a CEMS in lieu of operating parameter limits.
63.1209(g)(1)	You may request approval of: (1) Alternatives to operating parameter monitoring requirements, except for standards that you must monitor with a continuous emission monitoring system (CEMS) and except for requests to use a CEMS in lieu of operating parameter limits; or (2) a waiver of an operating parameter limit.
63.1209(l)(1)	You may request to extrapolate mercury feedrate limits.
63.1209(n)(2)	You may request to extrapolate semivolatile and low volatile metal feedrate limits.
63.1211(d)	You may request to use data compression techniques to record data on a less frequent basis than required by § 63.1209.

(b) *Notification of intent to comply (NIC).* These procedures apply to sources that have not previously complied with the requirements of paragraph (b) of this section, and to sources that previously complied with the NIC requirements of § 63.1210, which were in effect prior to October 11, 2000, that must make a technology change requiring a Class 1 permit modification to meet the standards of §§ 63.1219, 63.1220, and 63.1221.

(1) You must prepare a Notification of Intent to Comply that includes all of the following information:

(i) General information:

(A) The name and address of the owner/operator and the source;

(B) Whether the source is a major or an area source;

(C) Waste minimization and emission control technique(s) being considered;

(D) Emission monitoring technique(s) you are considering;

(E) Waste minimization and emission control technique(s) effectiveness;

(F) A description of the evaluation criteria used or to be used to select waste minimization and/or emission control technique(s); and

(G) A general description of how you intend to comply with the emission standards of this subpart.

(ii) As applicable to each source, information on key activities and estimated dates for these activities that will bring the source into compliance with emission control requirements of this subpart. You must include all of the following key activities and dates in your NIC:

(A) The dates by which you anticipate you will develop engineering designs for emission control systems or process changes for emissions;

(B) The date by which you anticipate you will commit internal or external resources for installing emission control systems or making process changes for emission control, or the date by which you will issue orders for the purchase of component parts to accomplish emission control or process changes.

(C) The date by which you anticipate you will submit construction applications;

(D) The date by which you anticipate you will initiate on-site construction, installation of emission control equipment, or process change;

(E) The date by which you anticipate you will complete on-site construction, installation of emission control equipment, or process change; and

(F) The date by which you anticipate you will achieve final compliance. The individual dates and milestones listed in paragraphs (b)(1)(ii)(A) through (F) of this section as part of the NIC are not requirements and therefore are not

enforceable deadlines; the requirements of paragraphs (b)(1)(ii)(A) through (F) of this section must be included as part of the NIC only to inform the public of how you intend to comply with the emission standards of this subpart.

(iii) A summary of the public meeting required under paragraph (c) of this section;

(iv) If you intend to cease burning hazardous waste prior to or on the compliance date, the requirements of paragraphs (b)(1)(ii) and (b)(1)(iii) of this section do not apply. You must include in your NIC a schedule of key dates for the steps to be taken to stop hazardous waste activity at your combustion unit. Key dates include the date for submittal of RCRA closure documents required under subpart G, part 264 or subpart G, part 265 of this chapter.

(2) You must make a draft of the NIC available for public review no later than 30 days prior to the public meeting required under paragraph (c)(1) of this section or no later than 9 months after the effective date of the rule if you intend to cease burning hazardous waste prior to or on the compliance date.

(3) You must submit the final NIC to the Administrator no later than one year following the effective date of the emission standards of this subpart.

(c) *NIC public meeting and notice.* (1) Prior to the submission of the NIC to the permitting agency, and no later than 10 months after the effective date of the emission standards of this subpart, you must hold at least one informal meeting with the public to discuss anticipated activities described in the draft NIC for achieving compliance with the emission standards of this subpart. You must post a sign-in sheet or otherwise provide a voluntary opportunity for attendees to provide their names and addresses;

(2) You must submit a summary of the meeting, along with the list of attendees and their addresses developed under paragraph (b)(1) of this section, and copies of any written comments or materials submitted at the meeting, to the Administrator as part of the final NIC, in accordance with paragraph (b)(1)(iii) of this section;

(3) You must provide public notice of the NIC meeting at least 30 days prior to the meeting and you must maintain, and provide to the Administrator upon request, documentation of the notice. You must provide public notice in all of the following forms:

(i) *Newspaper advertisement.* You must publish a notice in a newspaper of general circulation in the county or equivalent jurisdiction of your facility. In addition, you must publish the notice in newspapers of general circulation in adjacent counties or equivalent jurisdiction where such publication would be necessary to inform the affected public. You must publish the notice as a display advertisement.

(ii) *Visible and accessible sign.* You must post a notice on a clearly marked sign at or near the source. If you place the sign on the site of the hazardous waste combustor, the sign must be large enough to be readable from the nearest spot where the public would pass by the site.

(iii) *Broadcast media announcement.* You must broadcast a notice at least once on at least one local radio station or television station.

(iv) *Notice to the facility mailing list.* You must provide a copy of the notice to the facility mailing list in accordance with § 124.10(c)(1)(ix) of this chapter.

(4) You must include all of the following in the notices required under paragraph (c)(3) of this section:

(i) The date, time, and location of the meeting;

(ii) A brief description of the purpose of the meeting;

(iii) A brief description of the source and proposed operations, including the address or a map (e.g., a sketched or copied street map) of the source location;

(iv) A statement encouraging people to contact the source at least 72 hours before the meeting if they need special access to participate in the meeting;

(v) A statement describing how the draft NIC (and final NIC, if requested) can be obtained; and

(vi) The name, address, and telephone number of a contact person for the NIC.

(5) The requirements of this paragraph do not apply to sources that intend to cease burning hazardous waste prior to or on the compliance date.

■ 13. Section 63.1211 is amended by:

■ a. Revising the table in paragraph (b).

■ b. Revising paragraph (c)(1).

The revisions read as follows:

§ 63.1211 What are the recordkeeping and reporting requirements?

* * * * *

(b) * * *

Reference	Document, Data, or Information
63.1200, 63.10(b) and (c)	General. Information required to document and maintain compliance with the regulations of Subpart EEE, including data recorded by continuous monitoring systems (CMS), and copies of all notifications, reports, plans, and other documents submitted to the Administrator.
63.1204(d)(1)(ii), 63.1220(d)(1)(ii)	Documentation of mode of operation changes for cement kilns with in-line raw mills.
63.1204(d)(2)(ii), 63.1220(d)(2)(ii)	Documentation of compliance with the emission averaging requirements for cement kilns with in-line raw mills.
63.1204(e)(2)(ii), 63.1220(e)(2)(ii)	Documentation of compliance with the emission averaging requirements for preheater or preheater/precalciner kilns with dual stacks.
63.1206(b)(1)(ii)	If you elect to comply with all applicable requirements and standards promulgated under authority of the Clean Air Act, including Sections 112 and 129, in lieu of the requirements of Subpart EEE when not burning hazardous waste, you must document in the operating record that you are in compliance with those requirements.
63.1206(b)(5)(ii)	Documentation that a change will not adversely affect compliance with the emission standards or operating requirements.
63.1206(b)(11)	Calculation of hazardous waste residence time.
63.1206(c)(2)	Startup, shutdown, and malfunction plan.
63.1206(c)(2)(v)(A)	Documentation of your investigation and evaluation of excessive exceedances during malfunctions.
63.1206(c)(3)(v)	Corrective measures for any automatic waste feed cutoff that results in an exceedance of an emission standard or operating parameter limit.
63.1206(c)(3)(vii)	Documentation and results of the automatic waste feed cutoff operability testing.
63.1206(c)(4)(ii)	Emergency safety vent operating plan.
63.1206(c)(4)(iii)	Corrective measures for any emergency safety vent opening.
63.1206(c)(5)(ii)	Method used for control of combustion system leaks.
63.1206(c)(6)	Operator training and certification program.
63.1206(c)(7)(i)(D)	Operation and maintenance plan.
63.1209(c)(2)	Feedstream analysis plan.

Reference	Document, Data, or Information
63.1209(k)(6)(iii), 63.1209(k)(7)(ii), 63.1209(k)(9)(ii), 63.1209(o)(4)(iii).	Documentation that a substitute activated carbon, dioxin/furan formation reaction inhibitor, or dry scrubber sorbent will provide the same level of control as the original material.
63.1209(k)(7)(i)(C)	Results of carbon bed performance monitoring.
63.1209(q)	Documentation of changes in modes of operation.
63.1211(c)	Documentation of compliance.

(c) * * *

(1) By the compliance date, you must develop and include in the operating record a Documentation of Compliance. You are not subject to this requirement, however, if you submit a Notification of Compliance under § 63.1207(j) prior to the compliance date. Upon inclusion of the Documentation of Compliance in the operating record, hazardous waste burning incinerators, cement kilns, and lightweight aggregate kilns regulated under the interim standards of §§ 63.1203, 63.1204, and 63.1205 are no longer subject to compliance with the previously applicable Notification of Compliance.

* * * * * *

■ 14. Section 63.1212 is added to subpart EEE to read as follows:

§ 63.1212 What are the other requirements pertaining to the NIC?

(a) *Certification of intent to comply.* The Notice of Intent to Comply (NIC) must contain the following certification signed and dated by a responsible official as defined under § 63.2 of this chapter: I certify under penalty of law that I have personally examined and am familiar with the information submitted in this document and all attachments and that, based on my inquiry of those individuals immediately responsible for obtaining the information, I believe that the information is true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment.

(b) *New units.* Any source that files a RCRA permit application or permit modification request for construction of a hazardous waste combustion unit after October 12, 2005 must:

(1) Prepare a draft NIC according to § 63.1210(b) and make it available to the public upon issuance of the notice of NIC public meeting per § 63.1210(c)(3);

(2) Prepare a draft comprehensive performance test plan pursuant to the requirements of § 63.1207 and make it available for public review upon issuance of the notice of NIC public meeting;

(3) Provide notice to the public of a pre-application meeting pursuant to § 124.30 or notice to the public of a permit modification request pursuant to § 270.42 and;

(4) Hold an informal public meeting 30 days following notice of NIC public meeting and notice of the pre-application meeting or notice of the permit modification request.

(c) *Information Repository specific to new combustion units.* (1) Any source that files a RCRA permit application or modification request for construction of a new hazardous waste combustion unit after October 12, 2005 may be required to establish an information repository if deemed appropriate.

(2) The Administrator may assess the need, on a case-by-case basis for an information repository. When assessing the need for a repository, the Administrator shall consider the level of public interest, the presence of an existing repository, and any information available via the New Source Review and Title V permit processes. If the Administrator determines a need for a repository, then the Administrator shall notify the facility that it must establish and maintain an information repository.

(3) The information repository shall contain all documents, reports, data, and information deemed necessary by the Administrator. The Administrator shall have the discretion to limit the contents of the repository.

(4) The information repository shall be located and maintained at a site chosen by the source. If the Administrator finds the site unsuitable for the purposes and persons for which it was established, due to problems with location, hours of availability, access, or other relevant considerations, then the Administrator shall specify a more appropriate site.

(5) The Administrator shall require the source to provide a written notice about the information repository to all individuals on the source mailing list.

(6) The source shall be responsible for maintaining and updating the repository with appropriate information throughout a period specified by the Administrator. The Administrator may close the repository at his or her discretion based on the considerations in paragraph (c)(2) of this section.

■ 15. Section 63.1214 is amended by revising paragraphs (c)(1), (c)(2), (c)(3), and (c)(4) to read as follows:

§ 63.1214 Implementation and enforcement.

* * * * * *

(c) * * *

(1) Approval of alternatives to requirements in §§ 63.1200, 63.1203, 63.1204, 63.1205, 63.1206(a), 63.1215, 63.1216, 63.1217, 63.1218, 63.1219, 63.1220, and 63.1221.

(2) Approval of major alternatives to test methods under §§ 63.7(e)(2)(ii) and (f), 63.1208(b), and 63.1209(a)(1), as defined under § 63.90, and as required in this subpart.

(3) Approval of major alternatives to monitoring under §§ 63.8(f) and 63.1209(a)(5), as defined under § 63.90, and as required in this subpart.

(4) Approval of major alternatives to recordkeeping and reporting under §§ 63.10(f) and 63.1211(a) through (c), as defined under § 63.90, and as required in this subpart.

■ 16. Section § 63.1215 is added to subpart EEE to read as follows:

§ 63.1215 What are the health-based compliance alternatives for total chlorine?

(a) *General.* (1) *Overview.* You may establish and comply with health-based compliance alternatives for total chlorine under the procedures prescribed in this section for your hazardous waste combustors other than hydrochloric acid production furnaces. You may comply with these health-based compliance alternatives in lieu of the emission standards for total chlorine provided under §§ 63.1216, 63.1217, 63.1219, 63.1220, and 63.1221. To identify and comply with the limits, you must:

(i) Identify a total chlorine emission concentration (ppmv) expressed as chloride ($Cl^{(-)}$) equivalent for each on-site hazardous waste combustor. You may select total chlorine emission concentrations as you choose to demonstrate eligibility for the risk-based limits under this section, except as provided by paragraph (b)(4) of this section;

(ii) Apportion the total chlorine emission concentration between HCl and Cl_2 according to paragraph (b)(6)(i) of this section, and calculate HCl and Cl_2 emission rates (lb/hr) using the gas flowrate and other parameters from the most recent regulatory compliance test.

(iii) Calculate the annual average HCl-equivalent emission rate as prescribed in paragraph (b)(2) of this section.

(iv) Perform an eligibility demonstration to determine if your HCl-equivalent emission rate meets the national exposure standard and thus is below the annual average HCl-equivalent emission rate limit, as prescribed by paragraph (c) of this section;

(v) Submit your eligibility demonstration for review and approval, as prescribed by paragraph (e) of this section, which must include information to ensure that the 1-hour average HCl-equivalent emission rate limit is not exceeded, as prescribed by paragraph (d) of this section;

(vi) Demonstrate compliance with the annual average HCl-equivalent emission rate limit during the comprehensive performance test, as prescribed by the testing and monitoring requirements under paragraph (e) of this section;

(vii) Comply with compliance monitoring requirements, including establishing feedrate limits on total chlorine and chloride, and operating parameter limits on emission control equipment, as prescribed by paragraph (f) of this section; and

(viii) Comply with the requirements for changes, as prescribed by paragraph (h) of this section.

(2) *Definitions.* In addition to the definitions under § 63.1201, the following definitions apply to this section:

1-Hour Average HCl-Equivalent Emission Rate means the HCl-equivalent emission rate (lb/hr) determined by equating the toxicity of chlorine to HCl using 1-hour RELs as the health risk metric for acute exposure.

1-Hour Average HCl-Equivalent Emission Rate Limit means the HCl-equivalent emission rate (lb/hr) determined by equating the toxicity of chlorine to HCl using 1-hour RELs as the health risk metric for acute exposure and which ensures that maximum 1-hour average ambient concentrations of HCl-equivalents do not exceed a Hazard Index of 1.0, rounded to the nearest tenths decimal place (0.1), at an off-site receptor location.

Acute Reference Exposure Level (aREL) means health thresholds below which there would be no adverse health effects for greater than once in a lifetime exposures of one hour. ARELs are developed by the California Office of Health Hazard Assessment and are available at *http://www.oehha.ca.gov/air/acute_rels/acuterel.html.*

Annual Average HCl-Equivalent Emission Rate means the HCl-equivalent emission rate (lb/hr) determined by equating the toxicity of chlorine to HCl using RfCs as the health risk metric for long-term exposure.

Annual Average HCl-Equivalent Emission Rate Limit means the HCl-equivalent emission rate (lb/hr) determined by equating the toxicity of chlorine to HCl using RfCs as the health risk metric for long-term exposure and which ensures that maximum annual average ambient concentrations of HCl equivalents do not exceed a Hazard Index of 1.0, rounded to the nearest tenths decimal place (0.1), at an off-site receptor location.

Hazard Index (HI) means the sum of more than one Hazard Quotient for multiple substances and/or multiple exposure pathways. In this section, the Hazard Index is the sum of the Hazard Quotients for HCl and chlorine.

Hazard Quotient (HQ) means the ratio of the predicted media concentration of a pollutant to the media concentration at which no adverse effects are expected. For chronic inhalation exposures, the HQ is calculated under this section as the air concentration divided by the RfC. For acute inhalation exposures, the HQ is calculated under this section as the air concentration divided by the aREL.

Look-up table analysis means a risk screening analysis based on comparing the HCl-equivalent emission rate from the affected source to the appropriate HCl-equivalent emission rate limit specified in Tables 1 through 4 of this section.

Reference Concentration (RfC) means an estimate (with uncertainty spanning perhaps an order of magnitude) of a continuous inhalation exposure to the human population (including sensitive subgroups) that is likely to be without an appreciable risk of deleterious effects during a lifetime. It can be derived from various types of human or animal data, with uncertainty factors generally applied to reflect limitations of the data used.

(b) *HCl-equivalent emission rates.* (1) You must express total chlorine emission rates for each hazardous waste combustor as HCl-equivalent emission rates.

(2) *Annual average rates.* You must calculate annual average toxicity-weighted HCl-equivalent emission rates for each combustor as follows:

$ER_{tw} = ER_{HCl} + ER_{Cl2} \times (RfC_{HCl}/RfC_{Cl2})$

Where:

ER_{LTtw} is the annual average HCl toxicity-weighted emission rate (HCl-equivalent emission rate) considering long-term exposures, lb/hr

ER_{HCl} is the emission rate of HCl in lbs/hr

ER_{Cl2} is the emission rate of chlorine in lbs/hr

RfC_{HCl} is the reference concentration of HCl

RfC_{Cl2} is the reference concentration of chlorine

(3) *1-hour average rates.* You must calculate 1-hour average toxicity-weighted HCl-equivalent emission rates for each combustor as follows:

$ER_{STtw} = ER_{HCl} + ER_{Cl2} \times (aREL_{HCl}/aREL_{Cl2})$

Where:

ER_{STtw} is the 1-hour average HCl toxicity-weighted emission rate (HCl-equivalent emission rate) considering 1-hour (short-term) exposures, lb/hr

ER_{HCl} is the emission rate of HCl in lbs/hr

ER_{Cl2} is the emission rate of chlorine in lbs/hr

$aREL_{HCl}$ is the 1-hour Reference Exposure Level of HCl

$aREL_{Cl2}$ is the 1-hour Reference Exposure Level of chlorine

(4) You must use the RfC values for hydrogen chloride and chlorine found at *http://epa.gov/ttn/atw/toxsource/summary.html.*

(5) You must use the aREL values for hydrogen chloride and chlorine found at *http://www.oehha.ca.gov/air/acute_rels/acuterel.html.*

(6) *Cl_2HCl ratios*—(i) *Ratio for calculating annual average HCl-equivalent emission rates.* (A) To calculate the annual average HCl-equivalent emission rate (lb/hr) for each combustor, you must apportion the total chlorine emission concentration (ppmv chloride ($Cl^{(-)}$) equivalent) between HCl and chlorine according to the historical average Cl_2/HCl volumetric ratio for all regulatory compliance tests.

(B) You must calculate HCl and Cl_2 emission rates (lb/hr) using the apportioned emission concentrations and the gas flowrate and other parameters from the most recent regulatory compliance test.

(C) You must calculate the annual average HCl-equivalent emission rate using these HCl and Cl_2 emission rates and the equation in paragraph (b)(2) of this section.

(ii) *Ratio for calculating 1-hour average HCl-equivalent emission rates.* (A) To calculate the 1-hour average HCl-equivalent emission rate for each combustor as a criterion for you to determine under paragraph (d) of this section if an hourly rolling average feedrate limit on total chlorine and chloride may be waived, you must apportion the total chlorine emission concentration (ppmv chloride ($Cl^{(-)}$) equivalent) between HCl and chlorine

according to the historical highest Cl_2/HCl volumetric ratio for all regulatory compliance tests.

(B) You must calculate HCl and Cl_2 emission rates (lb/hr) using the apportioned emission concentrations and the gas flowrate and other parameters from the most recent regulatory compliance test.

(C) You must calculate the 1-hour average HCl-equivalent emission rate using the se HCl and Cl_2 emission rates and the equation in paragraph (b)(3) of this section.

(iii) *Ratios for new sources.* (A) You must use engineering information to estimate the Cl_2/HCl volumetric ratio for a new source for the initial eligibility demonstration.

(B) You must use the Cl_2/HCl volumetric ratio demonstrated during the initial comprehensive performance test to demonstrate in the Notification of Compliance that your HCl-equivalent emission rate does not exceed your HCl-equivalent emission rate limit.

(C) When approving the test plan for the initial comprehensive performance test, the permitting authority will establish a periodic testing requirement, such as every 3 months for 1 year, to establish a record of representative Cl_2/HCl volumetric ratios.

(*1*) You must revise your HCl-equivalent emission rates and HCl-equivalent emission rate limits after each such test using the procedures prescribed in paragraphs (b)(6)(i) and (ii) of this section.

(*2*) If you no longer are eligible for the health-based compliance alternative, you must notify the permitting authority immediately and either:

(*i*) Submit a revised eligibility demonstration requesting lower HCl-equivalent emission rate limits, establishing lower HCl-equivalent emission rates, and establishing by downward extrapolation lower feedrate limits for total chlorine and chloride; or

(*ii*) Request a compliance schedule of up to three years to demonstrate compliance with the emission standards under §§ 63.1216, 63.1217, 63.1219, 63.1220, and 63.1221.

(iv) *Unrepresentative or inadequate historical Cl_2/HCl volumetric ratios.* (A) If you believe that the Cl_2/HCl volumetric ratio for one or more historical regulatory compliance tests is not representative of the current ratio, you may request that the permitting authority allow you to screen those ratios from the analysis of historical ratios.

(B) If the permitting authority believes that too few historical ratios are available to calculate a representative average ratio or establish a maximum ratio, the permitting authority may require you to conduct periodic testing to establish representative ratios.

(v) *Updating Cl_2/HCl ratios.* You must include the Cl_2/HCl volumetric ratio demonstrated during each performance test in your data base of historical Cl2/HCl ratios to update the ratios you establish under paragraphs (b)(6)(i) and (ii) of this section for subsequent calculations of the annual average and 1-hour average HCl-equivalent emission rates.

(7) *Emission rates are capped.* The hydrogen chloride and chlorine emission rates you use to calculate the HCl-equivalent emission rate limit for incinerators, cement kilns, and lightweight aggregate kilns must not result in total chlorine emission concentrations exceeding:

(i) For incinerators that were existing sources on April 19, 1996: 77 parts per million by volume, combined emissions, expressed as chloride ($Cl^{(-)}$) equivalent, dry basis and corrected to 7 percent oxygen;

(ii) For incinerators that are new or reconstructed sources after April 19, 1996: 21 parts per million by volume, combined emissions, expressed as chloride ($Cl^{(-)}$) equivalent, dry basis and corrected to 7 percent oxygen;

(iii) For cement kilns that were existing sources on April 19, 1996: 130 parts per million by volume, combined emissions, expressed as chloride ($Cl^{(-)}$) equivalent, dry basis and corrected to 7 percent oxygen;

(iv) For cement kilns that are new or reconstructed sources after April 19, 1996: 86 parts per million by volume, combined emissions, expressed as chloride ($Cl^{(-)}$) equivalent, dry basis and corrected to 7 percent oxygen;

(v) For lightweight aggregate kilns that were existing sources on April 19, 1996: 600 parts per million by volume, combined emissions, expressed as chloride ($Cl^{(-)}$) equivalent, dry basis and corrected to 7 percent oxygen;

(vi) For lightweight aggregate kilns that are new or reconstructed sources after April 19, 1996: 600 parts per million by volume, combined emissions, expressed as chloride ($Cl^{(-)}$) equivalent, dry basis and corrected to 7 percent oxygen.

(c) *Eligibility demonstration*—(1) *General.* (i) You must perform an eligibility demonstration to determine whether the total chlorine emission rates you select for each on-site hazardous waste combustor meet the national exposure standards using either a look-up table analysis prescribed by paragraph (c)(3) of this section, or a site-specific compliance demonstration prescribed by paragraph (c)(4) of this section.

(ii) You must also determine in your eligibility demonstration whether each combustor may exceed the 1-hour HCl-equivalent emission rate limit absent an hourly rolling average limit on the feedrate of total chlorine and chloride, as provided by paragraph (d) of this section.

(2) *Definition of eligibility.* (i) Eligibility for the risk-based total chlorine standard is determined by comparing the annual average HCl-equivalent emission rate for the total chlorine emission rate you select for each combustor to the annual average HCl-equivalent emission rate limit.

(ii) The annual average HCl-equivalent emission rate limit ensures that the Hazard Index for chronic exposure from HCl and chlorine emissions from all on-site hazardous waste combustors is less than or equal to 1.0, rounded to the nearest tenths decimal place (0.1), for the actual individual most exposed to the facility's emissions, considering off-site locations where people reside and where people congregate for work, school, or recreation.

(iii) Your facility is eligible for the health-based compliance alternative for total chlorine if either:

(A) The annual average HCl-equivalent emission rate for each on-site hazardous waste combustor is below the appropriate value in the look-up table determined under paragraph (c)(3) of this section; or

(B) The annual average HCl-equivalent emission rate for each on-site hazardous waste combustor is below the annual average HCl-equivalent emission rate limit you calculate based on a site-specific compliance demonstration under paragraph (c)(4) of this section.

(3) *Look-up table analysis.* Look-up tables for the eligibility demonstration are provided as Tables 1 and 2 to this section.

(i) Table 1 presents annual average HCl-equivalent emission rate limits for sources located in flat terrain. For purposes of this analysis, flat terrain is terrain that rises to a level not exceeding one half the stack height within a distance of 50 stack heights.

(ii) Table 2 presents annual average HCl-equivalent emission rate limits for sources located in simple elevated terrain. For purposes of this analysis, simple elevated terrain is terrain that rises to a level exceeding one half the stack height, but that does not exceed the stack height, within a distance of 50 stack heights.

(iii) To determine the annual average HCl-equivalent emission rate limit for a

source from the look-up table, you must use the stack height and stack diameter for your hazardous waste combustors and the distance between the stack and the property boundary.

(iv) If any of these values for stack height, stack diameter, and distance to nearest property boundary do not match the exact values in the look-up table, you must use the next lowest table value.

(v) *Adjusted HCl-equivalent emission rate limit for multiple on-site combustors.* (A) If you have more than one hazardous waste combustor on site, the sum across all hazardous waste combustors of the ratio of the adjusted HCl-equivalent emission rate limit to the HCl-equivalent emission rate limit provided by Tables 1 or 2 cannot exceed 1.0, according to the following equation:

$$\sum_{i=1}^{n} \frac{\text{HCl-Equivalent Emission Rate Limit Adjusted}_i}{\text{HCl-Equivalent Emission Rate Limit Table}_i} \leq 1.0$$

Where:

i = number of on-site hazardous waste combustors;

HCl-Equivalent Emission Rate Limit Adjusted$_i$ means the apportioned, allowable HCl-equivalent emission rate limit for combustor i, and

HCl-Equivalent Emission Rate Limit Table$_i$ means the HCl-equivalent emission rate limit from Table 1 or 2 to § 63.1215 for combustor *i*.

(B) The adjusted HCl-equivalent emission rate limit becomes the HCl-equivalent emission rate limit.

(4) *Site-specific compliance demonstration.* (i) You may use any scientifically-accepted peer-reviewed risk assessment methodology for your site-specific compliance demonstration to calculate an annual average HCl-equivalent emission rate limit for each on-site hazardous waste combustor. An example of one approach for performing the demonstration for air toxics can be found in the EPA's "Air Toxics Risk Assessment Reference Library, Volume 2, Site-Specific Risk Assessment Technical Resource Document," which may be obtained through the EPA's Air Toxics Web site at *http://www.epa.gov/ttn/fera/risk_atra_main.html.*

(ii) The annual average HCl-equivalent emission rate limit is the HCl-equivalent emission rate that ensures that the Hazard Index associated with maximum annual average exposures is not greater than 1.0 rounded to the nearest tenths decimal place (0.1).

(iii) To determine the annual average HCl-equivalent emission rate limit, your site-specific compliance demonstration must, at a minimum:

(A) Estimate long-term inhalation exposures through the estimation of annual or multi-year average ambient concentrations;

(B) Estimate the inhalation exposure for the actual individual most exposed to the facility's emissions from hazardous waste combustors, considering off-site locations where people reside and where people congregate for work, school, or recreation;

(C) Use site-specific, quality-assured data wherever possible;

(D) Use health-protective default assumptions wherever site-specific data are not available, and;

(E) Contain adequate documentation of the data and methods used for the assessment so that it is transparent and can be reproduced by an experienced risk assessor and emissions measurement expert.

(iv) Your site-specific compliance demonstration need not:

(A) Assume any attenuation of exposure concentrations due to the penetration of outdoor pollutants into indoor exposure areas;

(B) Assume any reaction or deposition of the emitted pollutants during transport from the emission point to the point of exposure.

(d) *Assurance that the 1-hour HCl-equivalent emission rate limit will not be exceeded.* To ensure that the 1-hour HCl-equivalent emission rate limit will not be exceeded when complying with the annual average HCl-equivalent emission rate limit, you must establish a 1-hour average HCl-equivalent emission rate for each combustor, establish a 1-hour average HCl-equivalent emission rate limit for each combustor, and consider site-specific factors including prescribed criteria to determine if the 1-hour average HCl-equivalent emission rate limit may be exceeded absent an hourly rolling average limit on the feedrate of total chlorine and chloride. If the 1-hour average HCl-equivalent emission rate limit may be exceeded, you must establish an hourly rolling average feedrate limit on total chlorine as provided by paragraph (f)(3) of this section.

(1) *1-hour average HCl-equivalent emission rate.* You must calculate the 1-hour average HCl-equivalent emission rate from the total chlorine emission concentration you select for each source as prescribed in paragraph (b)(6)(ii)(C) of this section.

(2) *1-hour average HCl-equivalent emission rate limit.* You must establish the 1-hour average HCl-equivalent emission rate limit for each affected source using either a look-up table analysis or site-specific analysis:

(i) *Look-up table analysis.* Look-up tables are provided for 1-hour average HCl-equivalent emission rate limits as Table 3 and Table 4 to this section. Table 3 provides limits for facilities located in flat terrain. Table 4 provides limits for facilities located in simple elevated terrain. You must use the Tables to establish 1-hour average HCl-equivalent emission rate limits as prescribed in paragraphs (c)(3)(iii) through (c)(3)(v) of this section for annual average HCl-equivalent emission rate limits.

(ii) *Site-specific analysis.* The 1-hour average HCl-equivalent emission rate limit is the HCl-equivalent emission rate that ensures that the Hazard Index associated with maximum 1-hour average exposures is not greater than 1.0 rounded to the nearest tenths decimal place (0.1). You must follow the risk assessment procedures under paragraph (c)(4) of this section to estimate short-term inhalation exposures through the estimation of maximum 1-hour average ambient concentrations.

(3) *Criteria for determining whether the 1-hour HCl-equivalent emission rate may be exceeded absent an hourly rolling average limit on the feedrate of total chlorine and chloride.* An hourly rolling average feedrate limit on total chlorine and chloride is waived if you determine considering the criteria listed below that the long-term feedrate limit (and averaging period) established under paragraph (c)(4)(i) of this section will also ensure that the 1-hour average HCl-equivalent emission rate will not exceed the 1-hour average HCl-equivalent emission rate limit you calculate for each combustor.

(i) The ratio of the 1-hour average HCl-equivalent emission rate based on the total chlorine emission rate you select for each hazardous waste combustor to the 1-hour average HCl-equivalent emission rate limit for the combustor; and

(ii) The potential for the source to vary total chlorine and chloride

feedrates substantially over the averaging period for the feedrate limit established under paragraph (c)(4)(i) of this section.

(e) *Review and approval of eligibility demonstrations*—(1) *Content of the eligibility demonstration*—(i) *General.* The eligibility demonstration must include the following information, at a minimum:

(A) Identification of each hazardous waste combustor combustion gas emission point (e.g., generally, the flue gas stack);

(B) The maximum and average capacity at which each combustor will operate, and the maximum rated capacity for each combustor, using the metric of stack gas volume (under both actual and standard conditions) emitted per unit of time, as well as any other metric that is appropriate for the combustor (e.g., million Btu/hr heat input for boilers; tons of dry raw material feed/hour for cement kilns);

(C) Stack parameters for each combustor, including, but not limited to stack height, stack diameter, stack gas temperature, and stack gas exit velocity;

(D) Plot plan showing all stack emission points, nearby residences and property boundary line;

(E) Identification of any stack gas control devices used to reduce emissions from each combustor;

(F) Identification of the RfC values used to calculate annual average HCl-equivalent emission rates and the aREL values used to calculate 1-hour average HCl-equivalent emission rates;

(G) Calculations used to determine the annual average and 1-hour average HCl-equivalent emission rates and rate limits, including calculation of the Cl_2/HCl ratios as prescribed by paragraph (b)(6) of this section;

(ii) *Additional content to implement the annual average HCl-equivalent emission rate limit.* You must include the following in your eligibility demonstration to implement the annual average HCl-equivalent emission rate limit:

(A) For incinerators, cement kilns, and lightweight aggregate kilns, calculations to confirm that the annual average HCl-equivalent emission rate that you calculate from the total chlorine emission rate you select for each combustor does not exceed the limits provided by paragraph (b)(7) of this section;

(B) Comparison of the annual average HCl-equivalent emission rate limit for each combustor to the annual average HCl-equivalent emission rate for the total chlorine emission rate you select for each combustor;

(C) The annual average HCl-equivalent emission rate limit for each hazardous waste combustor, and the limits on operating parameters required under paragraph (g)(1) of this section;

(D) Determination of the long-term chlorine feedrate limit, including the total chlorine system removal efficiency for sources that establish an (up to) annual rolling average feedrate limit under paragraph (g)(2)(ii) of this section;

(iii) *Additional content to implement the 1-hour average HCl-equivalent emission rate limit.* You must include the following in your eligibility demonstration to implement the 1-hour average HCl-equivalent emission rate limit:

(A) Determination of whether the combustor may exceed the 1-hour HCl-equivalent emission rate limit absent an hourly rolling average chlorine feedrate limit, including:

(*1*) Determination of the 1-hour average HCl-equivalent emission rate from the total chlorine emission rate you select for the combustor;

(*2*) Determination of the 1-hour average HCl-equivalent emission rate limit using either look-up Tables 3 and 4 to this section or site-specific risk analysis;

(*3*) Determination of the ratio of the 1-hour average HCl-equivalent emission rate to the 1-hour average HCl-equivalent emission rate limit for the combustor; and

(*4*) The potential for the source to vary total chlorine and chloride feedrates substantially over the averaging period for the long-term feedrate limit established under paragraphs (g)(2)(i) and (g)(2)(ii) of this section; and

(B) Determination of the hourly rolling average chlorine feedrate limit, including the total chlorine system removal efficiency.

(iv) *Additional content of a look-up table demonstration.* If you use the look-up table analysis to establish HCl-equivalent emission rate limits, your eligibility demonstration must also contain, at a minimum, the following:

(A) Documentation that the facility is located in either flat or simple elevated terrain; and

(B) For facilities with more than one on-site hazardous waste combustor, documentation that the sum of the ratios for all such combustors of the HCl-equivalent emission rate to the HCl-equivalent emission rate limit does not exceed 1.0.

(v) *Additional content of a site-specific compliance demonstration.* If you use a site-specific compliance demonstration, your eligibility demonstration must also contain, at a minimum, the following information to support your determination of the annual average HCl-equivalent emission rate limit for each combustor:

(A) Identification of the risk assessment methodology used;

(B) Documentation of the fate and transport model used;

(C) Documentation of the fate and transport model inputs, including the stack parameters listed in paragraph (d)(1)(i)(C) of this section converted to the dimensions required for the model;

(D) As applicable:

(*1*) Meteorological data;

(*2*) Building, land use, and terrain data;

(*3*) Receptor locations and population data, including areas where people congregate for work, school, or recreation; and

(*4*) Other facility-specific parameters input into the model;

(E) Documentation of the fate and transport model outputs; and

(F) Documentation of any exposure assessment and risk characterization calculations.

(2) *Review and approval*—(i) *Existing sources.* (A) If you operate an existing source, you must submit the eligibility demonstration to your permitting authority for review and approval not later than 12 months prior to the compliance date. You must also submit a separate copy of the eligibility demonstration to: U.S. EPA, Risk and Exposure Assessment Group, Emission Standards Division (C404–01), Attn: Group Leader, Research Triangle Park, North Carolina 27711, electronic mail address *REAG@epa.gov*.

(B) Your permitting authority should notify you of approval or intent to disapprove your eligibility demonstration within 6 months after receipt of the original demonstration, and within 3 months after receipt of any supplemental information that you submit. A notice of intent to disapprove your eligibility demonstration, whether before or after the compliance date, will identify incomplete or inaccurate information or noncompliance with prescribed procedures and specify how much time you will have to submit additional information or to achieve the MACT standards for total chlorine under §§ 63.1216, 63.1217, 63.1219, 63.1220, and 63.1221. If your eligibility demonstration is disapproved, the permitting authority may extend the compliance date of the total chlorine standards to allow you to make changes to the design or operation of the combustor or related systems as quickly as practicable to enable you to achieve compliance with the MACT total chlorine standards.

(C) If your permitting authority has not approved your eligibility demonstration by the compliance date, and has not issued a notice of intent to disapprove your demonstration, you may nonetheless begin complying, on the compliance date, with the HCl-equivalent emission rate limits you present in your eligibility demonstration.

(D) If your permitting authority issues a notice of intent to disapprove your eligibility demonstration after the compliance date, the authority will identify the basis for that notice and specify how much time you will have to submit additional information or to comply with the MACT standards for total chlorine under §§ 63.1216, 63.1217, 63.1219, 63.1220, and 63.1221. The permitting authority may extend the compliance date of the total chlorine standards to allow you to make changes to the design or operation of the combustor or related systems as quickly as practicable to enable you to achieve compliance with the MACT standards for total chlorine.

(ii) *New or reconstructed sources.* (A) *General.* The procedures for review and approval of eligibility demonstrations applicable to existing sources under paragraph (e)(2)(i) of this section also apply to new or reconstructed sources, except that the date you must submit the eligibility demonstration is as prescribed in this paragraph (e)(2)(ii).

(B) If you operate a new or reconstructed source that starts up before April 12, 2007, or a solid fuel boiler or liquid fuel boiler that is an area source that increases its emissions or its potential to emit such that it becomes a major source of HAP before April 12, 2007, you must either:

(*1*) Comply with the final total chlorine emission standards under §§ 63.1216, 63.1217, 63.1219, 63.1220, and 63.1221, by October 12, 2005, or upon startup, whichever is later, except for a standard that is more stringent than the standard proposed on April 20, 2004 for your source. If a final standard is more stringent than the proposed standard, you may comply with the proposed standard until October 14, 2008, after which you must comply with the final standard; or

(*2*) Submit an eligibility demonstration for review and approval under this section by April 12, 2006, and comply with the HCl-equivalent emission rate limits and operating requirements you establish in the eligibility demonstration.

(C) If you operate a new or reconstructed source that starts up on or after April 12, 2007, or a solid fuel boiler or liquid fuel boiler that is an area source that increases its emissions or its potential to emit such that it becomes a major source of HAP on or after April 12, 2007, you must either:

(*1*) Comply with the final total chlorine emission standards under §§ 63.1216, 63.1217, 63.1219, 63.1220, and 63.1221 upon startup. If the final standard is more stringent than the standard proposed for your source on April 20, 2004, however, and if you start operations before October 14, 2008, you may comply with the proposed standard until October 14, 2008, after which you must comply with the final standard; or

(*2*) Submit an eligibility demonstration for review and approval under this section 12 months prior to startup.

(f) *Testing requirements*—(1) *General.* You must comply with the requirements for comprehensive performance testing under § 63.1207.

(2) *System removal efficiency.* (i) You must calculate the total chlorine removal efficiency of the combustor during each run of the comprehensive performance test.

(ii) You must calculate the average system removal efficiency as the average of the test run averages.

(iii) If your source does not control emissions of total chlorine, you must assume zero system removal efficiency.

(3) *Annual average HCl-equivalent emission rate limit.* If emissions during the comprehensive performance test exceed the annual average HCl-equivalent emission rate limit, eligibility for emission limits under this section is not affected. This emission rate limit is an annual average limit even though compliance is based on a 12-hour or (up to) an annual rolling average feedrate limit on total chlorine and chloride because the feedrate limit is also used for compliance assurance for the semivolatile metal emission standard

(4) *1-hour average HCl-equivalent emission rate limit.* Total chlorine emissions during each run of the comprehensive performance test cannot exceed the 1-hour average HCl-equivalent emission rate limit.

(5) *Test methods.* (i) If you operate a cement kiln or a combustor equipped with a dry acid gas scrubber, you must use EPA Method 320/321 or ASTM D 6735–01, or an equivalent method, to measure hydrogen chloride, and the back-half (caustic impingers) of Method 26/26A, or an equivalent method, to measure chlorine gas.

(ii) *Bromine and sulfur considerations.* If you operate an incinerator, boiler, or lightweight aggregate kiln and your feedstreams contain bromine or sulfur during the comprehensive performance test at levels specified under paragraph (e)(2)(ii)(B) of this section, you must use EPA Method 320/321 or ASTM D 6735–01, or an equivalent method, to measure hydrogen chloride, and Method 26/26A, or an equivalent method, to measure chlorine and hydrogen chloride, and determine your chlorine emissions as follows:

(A) You must determine you chlorine emissions to be the higher of the value measured by Method 26/26A, or an equivalent method, or the value calculated by difference between the combined hydrogen chloride and chlorine levels measured by Method 26/26a, or an equivalent method, and the hydrogen chloride measurement from EPA Method 320/321 or ASTM D 6735–01, or an equivalent method.

(B) The procedures under paragraph (f)(2)(ii) of this section for determining hydrogen chloride and chlorine emissions apply if you feed bromine or sulfur during the performance test at the levels specified in this paragraph (f)(5)(ii)(B):

(*1*) If the bromine/chlorine ratio in feedstreams is greater than 5 percent by mass; or

(*2*) If the sulfur/chlorine ratio in feedstreams is greater than 50 percent by mass.

(g) *Monitoring requirements.* (1) *General.* You must establish and comply with limits on the same operating parameters that apply to sources complying with the MACT standard for total chlorine under § 63.1209(o), except that feedrate limits on total chlorine and chloride must be established according to paragraphs (g)(2) and (g)(3) of this section:

(2) *Feedrate limit to ensure compliance with the annual average HCl-equivalent emission rate limit.* (i) For sources subject to the feedrate limit for total chlorine and chloride under § 63.1209(n)(4) to ensure compliance with the semivolatile metals standard:

(A) The feedrate limit (and averaging period) for total chlorine and chloride to ensure compliance with the annual average HCl-equivalent emission rate limit is the same as required by § 63.1209(n)(4), except as provided by paragraph (g)(2)(i)(B) of this section.

(B) The numerical value of the total chlorine and chloride feedrate limit (*i.e.*, not considering the averaging period) you establish under § 63.1209(n)(4) must not exceed the value you calculate as the annual average HCl-equivalent emission rate limit (lb/hr) divided by [1 − system removal efficiency], where the system removal efficiency is calculated as prescribed by paragraph (f)(2) of this section.

(ii) For sources exempt from the feedrate limit for total chlorine and chloride under § 63.1209(n)(4) because they comply with § 63.1207(m)(2), the feedrate limit for total chlorine and chloride to ensure compliance with the annual average HCl-equivalent emission rate must be established as follows:

(A) You must establish an average period for the feedrate limit that does not exceed an annual rolling average;

(B) The numerical value of the total chlorine and chloride feedrate limit (*i.e.*, not considering the averaging period) must not exceed the value you calculate as the annual average HCl-equivalent emission rate limit (lb/hr) divided by [1 − system removal efficiency], where the system removal efficiency is calculated as prescribed by paragraph (f)(2) of this section.

(C) You must calculate the initial rolling average as though you had selected a 12-hour rolling average, as provided by paragraph (b)(5)(i) of this section. You must calculate rolling averages thereafter as the average of the available one-minute values until enough one-minute values are available to calculate the rolling average period you select. At that time and thereafter, you update the rolling average feedrate each hour with a 60-minute average feedrate.

(3) *Feedrate limit to ensure compliance with the 1-hour average HCl-equivalent emission rate limit.* (i) You must establish an hourly rolling average feedrate limit on total chlorine and chloride to ensure compliance with the 1-hour average HCl-equivalent emission rate limit unless you determine that the hourly rolling average feedrate limit is waived under paragraph (d) of this section.

(ii) You must calculate the hourly rolling average feedrate limit for total chlorine and chloride as the 1-hour average HCl-equivalent emission rate limit (lb/hr) divided by [1 − system removal efficiency], where the system removal efficiency is calculated as prescribed by paragraph (f)(2)(ii) of this section.

(h) *Changes.*—(1) *Changes over which you have control.* (i) *Changes that would affect the HCl-equivalent emission rate limit.* (A) If you plan to change the design, operation, or maintenance of the facility in a manner than would decrease the annual average or 1-hour average HCl-equivalent emission rate limit, you must submit to the permitting authority prior to the change a revised eligibility demonstration documenting the lower emission rate limits and calculations of reduced total chlorine and chloride feedrate limits.

(B) If you plan to change the design, operation, or maintenance of the facility in a manner than would increase the annual average or 1-hour average HCl-equivalent emission rate limit, and you elect to increase your total chlorine and chloride feedrate limits. You must also submit to the permitting authority prior to the change a revised eligibility demonstration documenting the increased emission rate limits and calculations of the increased feedrate limits prior to the change.

(ii) *Changes that could affect system removal efficiency.* (A) If you plan to change the design, operation, or maintenance of the combustor in a manner than could decrease the system removal efficiency, you are subject to the requirements of § 63.1206(b)(5) for conducting a performance test to reestablish the combustor's system removal efficiency and you must submit a revised eligibility demonstration documenting the lower system removal efficiency and the reduced feedrate limits on total chlorine and chloride.

(B) If you plan to change the design, operation, or maintenance of the combustor in a manner than could increase the system removal efficiency, and you elect to document the increased system removal efficiency to establish higher feedrate limits on total chlorine and chloride, you are subject to the requirements of § 63.1206(b)(5) for conducting a performance test to reestablish the combustor's system removal efficiency. You must also submit to the permitting authority a revised eligibility demonstration documenting the higher system removal efficiency and the increased feedrate limits on total chlorine and chloride.

(2) *Changes over which you do not have control that may decrease the HCl-equivalent emission rate limits.* These requirements apply if you use a site-specific risk assessment under paragraph (c)(4) of this section to demonstrate eligibility for the health-based limits.

(i) *Proactive review.* You must review the documentation you use in your eligibility demonstration every five years from the date of the comprehensive performance test and submit for review and approval with the comprehensive performance test plan either a certification that the information used in your eligibility demonstration has not changed in a manner that would decrease the annual average or 1-hour average HCl-equivalent emission rate limit, or a revised eligibility demonstration.

(ii) *Reactive review.* If in the interim between your comprehensive performance tests you have reason to know of changes that would decrease the annual average or 1-hour average HCl-equivalent emission rate limit, you must submit a revised eligibility demonstration as soon as practicable but not more frequently than annually.

(iii) *Compliance schedule.* If you determine that you cannot demonstrate compliance with a lower annual average HCl-equivalent emission rate limit during the comprehensive performance test because you need additional time to complete changes to the design or operation of the source, you may request that the permitting authority grant you additional time to make those changes as quickly as practicable.

BILLING CODE 6560–50–P

Table 1 of §63.1215: Annual Average HCl-Equivalent Emssion Rate Limits (lb/hr)--Flat Terrain												
	Distance to property boundary (m)											
Stack Diameter = 0.3 m												
Stack Height (m)	30	50	70	100	200	300	500	700	1000	2000	3000	5000
5	3.7E-01	4.9E-01	7.3E-01	9.1E-01	1.6E+00	2.3E+00	4.1E+00	5.7E+00	6.1E+00	1.0E+01	1.6E+01	2.9E+01
10	1.0E+00	1.0E+00	1.1E+00	1.5E+00	2.1E+00	2.7E+00	4.8E+00	5.7E+00	6.5E+00	1.1E+01	1.8E+01	3.2E+01
20	2.3E+00	2.3E+00	2.3E+00	2.3E+00	2.7E+00	3.7E+00	5.6E+00	7.4E+00	1.0E+01	1.9E+01	2.9E+01	5.2E+01
30	4.1E+00	4.1E+00	4.1E+00	4.2E+00	4.7E+00	6.0E+00	9.5E+00	1.3E+01	1.8E+01	3.3E+01	4.8E+01	7.9E+01
50	1.2E+01	1.2E+01	1.2E+01	1.2E+01	1.3E+01	1.5E+01	2.0E+01	2.8E+01	3.8E+01	7.1E+01	1.0E+02	1.6E+02
Stack Diameter = 0.5 m												
Stack Height (m)	30	50	70	100	200	300	500	700	1000	2000	3000	5000
5	8.5E-01	9.3E-01	1.4E+00	1.8E+00	3.0E+00	4.4E+00	7.2E+00	9.2E+00	1.3E+01	1.5E+01	2.0E+01	3.4E+01
10	1.4E+00	1.4E+00	1.6E+00	2.1E+00	3.9E+00	5.4E+00	8.3E+00	1.0E+01	1.3E+01	1.7E+01	2.3E+01	3.8E+01
20	3.7E+00	3.7E+00	3.7E+00	3.9E+00	4.9E+00	6.5E+00	8.5E+00	1.0E+01	1.3E+01	2.2E+01	3.2E+01	5.6E+01
30	5.5E+00	5.5E+00	5.5E+00	5.5E+00	5.6E+00	6.7E+00	1.0E+01	1.4E+01	1.9E+01	3.4E+01	4.9E+01	8.1E+01
50	1.4E+01	1.4E+01	1.4E+01	1.4E+01	1.4E+01	1.5E+01	2.1E+01	2.8E+01	3.9E+01	7.2E+01	1.0E+02	1.6E+02
Stack Diameter = 1.0 m												
Stack Height (m)	30	50	70	100	200	300	500	700	1000	2000	3000	5000
10	3.2E+00	3.6E+00	4.0E+00	5.4E+00	9.6E+00	1.3E+01	1.8E+01	2.3E+01	2.8E+01	4.5E+01	5.3E+01	6.5E+01
20	5.9E+00	5.9E+00	5.9E+00	6.1E+00	9.6E+00	1.3E+01	1.8E+01	2.3E+01	2.8E+01	4.5E+01	5.3E+01	7.5E+01
30	1.0E+01	1.0E+01	1.0E+01	1.0E+01	1.2E+01	1.3E+01	1.8E+01	2.3E+01	2.8E+01	4.5E+01	6.1E+01	9.3E+01
50	1.8E+01	1.8E+01	1.8E+01	1.8E+01	1.8E+01	1.8E+01	2.3E+01	3.1E+01	4.2E+01	7.7E+01	1.1E+02	1.7E+02
70	7.4E+01	7.4E+01	7.4E+01	7.4E+01	7.4E+01	7.4E+01	8.0E+01	1.0E+02	1.4E+02	2.1E+02	2.7E+02	4.0E+02
Stack Diameter = 1.5 m												
Stack Height (m)	30	50	70	100	200	300	500	700	1000	2000	3000	5000
10	4.1E+00	5.3E+00	6.4E+00	7.9E+00	1.3E+01	2.1E+01	2.7E+01	3.6E+01	4.8E+01	7.6E+01	9.1E+01	1.1E+02
20	7.6E+00	7.6E+00	7.6E+00	7.9E+00	1.3E+01	2.1E+01	2.7E+01	3.6E+01	4.8E+01	7.6E+01	9.1E+01	1.2E+02
30	1.3E+01	1.3E+01	1.3E+01	1.3E+01	1.8E+01	2.1E+01	2.7E+01	3.6E+01	4.8E+01	7.6E+01	9.1E+01	1.2E+02
50	2.3E+01	2.3E+01	2.3E+01	2.3E+01	2.3E+01	2.3E+01	2.7E+01	3.6E+01	4.8E+01	8.6E+01	1.2E+02	1.8E+02
70	1.0E+02	1.0E+02	1.0E+02	1.0E+02	1.0E+02	1.0E+02	1.1E+02	1.4E+02	1.8E+02	3.0E+02	4.0E+02	5.8E+02
Stack Diameter = 2.0 m												
Stack Height (m)	30	50	70	100	200	300	500	700	1000	2000	3000	5000
10	5.0E+00	6.9E+00	7.7E+00	9.8E+00	1.7E+01	2.8E+01	3.3E+01	4.4E+01	6.9E+01	1.0E+02	1.4E+02	1.6E+02
20	9.3E+00	9.3E+00	9.4E+00	1.0E+01	1.7E+01	2.8E+01	3.3E+01	4.4E+01	5.9E+01	1.0E+02	1.4E+02	1.8E+02
30	1.6E+01	1.6E+01	1.6E+01	1.6E+01	1.9E+01	2.8E+01	3.3E+01	4.4E+01	5.9E+01	1.0E+02	1.4E+02	1.8E+02
50	2.9E+01	2.9E+01	2.9E+01	2.9E+01	2.9E+01	2.9E+01	3.3E+01	4.4E+01	5.9E+01	1.0E+02	1.4E+02	2.0E+02
70	1.4E+02	1.4E+02	1.4E+02	1.4E+02	1.4E+02	1.4E+02	1.4E+02	1.8E+02	2.3E+02	3.4E+02	4.3E+02	6.4E+02
100	3.0E+02	3.0E+02	3.0E+02	3.0E+02	3.0E+02	3.0E+02	3.0E+02	3.0E+02	3.5E+02	5.2E+02	6.8E+02	8.2E+02
Stack Diameter = 3.0 m												
Stack Height (m)	30	50	70	100	200	300	500	700	1000	2000	3000	5000
10	8.5E+00	8.9E+00	7.7E+00	9.8E+00	2.2E+01	3.4E+01	5.4E+01	7.4E+01	9.8E+01	1.3E+02	1.6E+02	1.6E+02
20	1.6E+01	1.6E+01	1.7E+01	2.0E+01	2.5E+01	3.7E+01	5.6E+01	7.4E+01	9.8E+01	1.5E+02	2.1E+02	3.0E+02
30	2.0E+01	2.0E+01	2.0E+01	2.0E+01	2.5E+01	3.7E+01	5.6E+01	7.4E+01	9.8E+01	1.7E+02	2.2E+02	3.0E+02
50	4.2E+01	4.2E+01	4.2E+01	4.2E+01	4.4E+01	5.1E+01	5.6E+01	7.4E+01	9.8E+01	1.7E+02	2.2E+02	3.0E+02
70	2.3E+02	2.3E+02	2.3E+02	2.3E+02	2.3E+02	2.4E+02	2.4E+02	2.9E+02	3.6E+02	4.1E+02	5.0E+02	7.0E+02
100	3.5E+02	3.5E+02	3.5E+02	3.5E+02	3.5E+02	3.5E+02	3.5E+02	3.5E+02	3.9E+02	6.3E+02	7.5E+02	8.7E+02
Stack Diameter = 4.0 m												
Stack Height (m)	30	50	70	100	200	300	500	700	1000	2000	3000	5000
30	2.5E+01	2.5E+01	2.5E+01	2.5E+01	3.4E+01	5.6E+01	8.1E+01	1.1E+02	1.4E+02	2.2E+02	2.6E+02	4.3E+02
50	5.1E+01	5.1E+01	5.1E+01	5.1E+01	5.3E+01	8.2E+01	8.1E+01	1.1E+02	1.4E+02	2.4E+02	3.1E+02	4.4E+02
70	2.6E+02	2.6E+02	2.6E+02	2.6E+02	2.7E+02	2.8E+02	3.3E+02	4.6E+02	4.8E+02	5.0E+02	5.7E+02	7.7E+02
100	5.7E+02	5.7E+02	5.7E+02	5.7E+02	5.7E+02	5.7E+02	5.7E+02	5.7E+02	5.8E+02	8.6E+02	9.3E+02	1.1E+03

Table 2 of §63.1215: Annual Average HCl-Equivalent Emission Rate Limits (lbs/hr)--Simple Elevated Terrain

	Distance to property boundary (m)										
Stack Diameter = 0.3 m											
Stack height (m)	30	50	70	100	200	300	500	700	1000	2000	3000	5000
5	1.3E-01	1.8E-01	2.5E-01	3.7E-01	6.4E-01	8.9E-01	1.4E+00	2.0E+00	3.1E+00	7.7E+00	1.3E+01	2.6E+01
10	3.8E-01	3.8E-01	4.4E-01	6.1E-01	6.4E-01	8.9E-01	1.4E+00	2.0E+00	3.1E+00	7.7E+00	1.3E+01	2.6E+01
20	1.1E+00	1.1E+00	1.1E+00	1.2E+00	1.2E+00	1.5E+00	2.3E+00	3.4E+00	5.2E+00	1.2E+01	2.0E+01	3.9E+01
30	2.4E+00	2.4E+00	2.4E+00	2.4E+00	2.7E+00	3.5E+00	4.2E+00	5.2E+00	7.0E+00	1.5E+01	2.6E+01	4.9E+01
50	7.7E+00	7.7E+00	7.7E+00	7.7E+00	7.7E+00	8.6E+00	8.6E+00	8.6E+00	8.6E+00	2.0E+01	3.4E+01	6.5E+01
Stack Diameter = 0.5 m											
Stack height (m)	30	50	70	100	200	300	500	700	1000	2000	3000	5000
5	1.8E-01	2.6E-01	3.5E-01	5.6E-01	1.4E+00	1.6E+00	2.3E+00	3.4E+00	5.2E+00	9.6E+00	1.5E+01	2.8E+01
10	5.3E-01	5.3E-01	6.1E-01	8.5E-01	1.4E+00	1.6E+00	2.3E+00	3.4E+00	5.2E+00	9.6E+00	1.5E+01	2.8E+01
20	1.5E+00	1.5E+00	1.5E+00	1.5E+00	1.5E+00	1.6E+00	2.3E+00	3.4E+00	5.2E+00	1.2E+01	2.0E+01	3.9E+01
30	2.9E+00	2.9E+00	2.9E+00	2.9E+00	2.9E+00	3.5E+00	4.2E+00	5.5E+00	8.1E+00	1.7E+01	2.8E+01	5.2E+01
50	8.0E+00	8.0E+00	8.0E+00	8.0E+00	8.0E+00	8.8E+00	1.2E+01	1.2E+01	1.2E+01	2.3E+01	3.7E+01	6.9E+01
Stack Diameter = 1.0 m											
Stack height (m)	30	50	70	100	200	300	500	700	1000	2000	3000	5000
10	9.7E-01	9.7E-01	1.1E+00	1.7E+00	3.7E+00	3.7E+00	4.2E+00	5.5E+00	7.5E+00	1.5E+01	2.3E+01	4.1E+01
20	2.7E+00	2.7E+00	2.7E+00	3.0E+00	3.7E+00	3.7E+00	4.2E+00	5.5E+00	7.5E+00	1.5E+01	2.3E+01	4.3E+01
30	4.3E+00	4.3E+00	4.3E+00	4.3E+00	4.3E+00	4.3E+00	4.3E+00	5.5E+00	8.1E+00	1.7E+01	2.8E+01	5.2E+01
50	9.5E+00	9.5E+00	9.5E+00	9.5E+00	9.5E+00	9.5E+00	1.2E+01	1.4E+01	1.6E+01	3.1E+01	4.8E+01	8.3E+01
70	4.0E+01	4.0E+01	4.0E+01	4.0E+01	4.0E+01	4.0E+01	4.0E+01	4.1E+01	4.1E+01	4.1E+01	5.8E+01	9.8E+01
Stack Diameter = 1.5 m											
Stack height (m)	30	50	70	100	200	300	500	700	1000	2000	3000	5000
10	2.0E+00	2.0E+00	2.3E+00	3.4E+00	5.1E+00	6.0E+00	6.0E+00	6.6E+00	9.3E+00	1.9E+01	3.0E+01	5.4E+01
20	3.5E+00	3.5E+00	3.5E+00	3.9E+00	5.1E+00	6.0E+00	6.0E+00	6.6E+00	9.3E+00	1.9E+01	3.0E+01	5.4E+01
30	6.0E+00	6.0E+00	6.0E+00	6.0E+00	6.0E+00	6.0E+00	6.0E+00	6.6E+00	9.3E+00	1.9E+01	3.0E+01	5.5E+01
50	1.1E+01	1.1E+01	1.1E+01	1.1E+01	1.1E+01	1.1E+01	1.2E+01	1.4E+01	1.6E+01	3.1E+01	4.8E+01	8.3E+01
70	5.1E+01	5.1E+01	5.1E+01	5.1E+01	5.1E+01	5.1E+01	5.1E+01	5.1E+01	5.1E+01	6.2E+01	7.8E+01	1.2E+02
Stack Diameter = 2.0 m											
Stack height (m)	30	50	70	100	200	300	500	700	1000	2000	3000	5000
10	2.6E+00	2.6E+00	3.0E+00	4.2E+00	6.3E+00	9.2E+00	9.2E+00	1.0E+01	1.4E+01	2.5E+01	3.7E+01	6.3E+01
20	4.2E+00	4.2E+00	4.2E+00	4.7E+00	6.3E+00	9.2E+00	9.2E+00	1.0E+01	1.4E+01	2.5E+01	3.7E+01	6.3E+01
30	8.4E+00	8.4E+00	8.4E+00	8.4E+00	9.2E+00	9.2E+00	9.2E+00	1.0E+01	1.4E+01	2.5E+01	3.7E+01	6.3E+01
50	1.4E+01	1.4E+01	1.4E+01	1.4E+01	1.4E+01	1.4E+01	1.4E+01	1.5E+01	1.6E+01	3.1E+01	4.8E+01	8.3E+01
70	5.9E+01	5.9E+01	5.9E+01	5.9E+01	5.9E+01	5.9E+01	5.9E+01	5.9E+01	5.9E+01	7.0E+01	1.0E+02	1.5E+02
100	8.2E+01	8.2E+01	8.2E+01	8.2E+01	8.2E+01	8.2E+01	8.2E+01	8.2E+01	8.2E+01	8.2E+01	1.1E+02	1.7E+02
Stack Diameter = 3.0 m											
Stack height (m)	30	50	70	100	200	300	500	700	1000	2000	3000	5000
10	3.3E+00	3.4E+00	3.9E+00	5.5E+00	1.1E+01	1.7E+01	1.7E+01	1.7E+01	1.7E+01	3.3E+01	5.0E+01	8.6E+01
20	6.5E+00	6.5E+00	6.5E+00	7.6E+00	1.1E+01	1.7E+01	1.7E+01	1.7E+01	1.7E+01	3.3E+01	5.0E+01	8.6E+01
30	1.1E+01	1.1E+01	1.1E+01	1.1E+01	1.2E+01	1.7E+01	1.7E+01	1.7E+01	1.7E+01	3.3E+01	5.0E+01	8.6E+01
50	1.7E+01	1.7E+01	1.7E+01	1.7E+01	1.7E+01	1.7E+01	1.7E+01	1.7E+01	1.7E+01	3.3E+01	5.0E+01	8.6E+01
70	8.0E+01	8.0E+01	8.0E+01	8.0E+01	8.0E+01	8.0E+01	8.0E+01	8.0E+01	8.0E+01	8.5E+01	1.2E+02	1.9E+02
100	1.3E+02	1.3E+02	1.3E+02	1.3E+02	1.3E+02	1.3E+02	1.3E+02	1.3E+02	1.3E+02	1.3E+02	1.9E+02	2.4E+02
Stack Diameter = 4.0 m											
Stack height (m)	30	50	70	100	200	300	500	700	1000	2000	3000	5000
30	1.3E+01	1.3E+01	1.3E+01	1.3E+01	1.5E+01	2.1E+01	2.1E+01	2.1E+01	2.1E+01	4.0E+01	6.0E+01	9.8E+01
50	2.1E+01	2.1E+01	2.1E+01	2.1E+01	2.1E+01	2.1E+01	2.1E+01	2.1E+01	2.1E+01	4.0E+01	6.0E+01	9.8E+01
70	1.1E+02	1.1E+02	1.1E+02	1.1E+02	1.1E+02	1.1E+02	1.1E+02	1.1E+02	1.1E+02	1.1E+02	1.5E+02	2.3E+02
100	1.5E+02	1.5E+02	1.5E+02	1.5E+02	1.5E+02	1.5E+02	1.5E+02	1.5E+02	1.5E+02	1.5E+02	2.2E+02	3.4E+02

Table 3 of §63.1215: 1-Hour Average HCl-Equivalent Emission Rates (lb/hr)--Flat Terrain												
	Distance to property boundary (m)											
Stack Diameter = 0.3 m												
Stack Height (m)	30	50	70	100	200	300	500	700	1000	2000	3000	5000
5	3.9E+00	5.1E+00	7.6E+00	9.6E+00	1.6E+01	2.4E+01	4.3E+01	5.3E+01	6.2E+01	1.1E+02	1.7E+02	3.1E+02
10	9.7E+00	9.8E+00	1.1E+01	1.4E+01	2.0E+01	2.6E+01	4.6E+01	5.3E+01	6.2E+01	1.1E+02	1.7E+02	3.1E+02
20	2.2E+01	2.2E+01	2.2E+01	2.2E+01	2.5E+01	3.5E+01	5.3E+01	7.0E+01	9.5E+01	1.8E+02	2.8E+02	4.9E+02
30	3.9E+01	3.9E+01	3.9E+01	4.0E+01	4.4E+01	5.7E+01	9.0E+01	1.2E+02	1.7E+02	3.1E+02	4.5E+02	7.5E+02
50	1.2E+02	1.2E+02	1.2E+02	1.2E+02	1.2E+02	1.4E+02	1.9E+02	2.6E+02	3.6E+02	6.7E+02	9.7E+02	1.5E+03
Stack Diameter = 0.5 m												
Stack Height (m)	30	50	70	100	200	300	500	700	1000	2000	3000	5000
5	6.9E+00	9.8E+00	1.5E+01	1.8E+01	3.2E+01	4.6E+01	7.5E+01	9.7E+01	1.2E+02	1.6E+02	2.1E+02	3.6E+02
10	1.3E+01	1.4E+01	1.5E+01	2.0E+01	3.7E+01	5.1E+01	7.9E+01	9.7E+01	1.2E+02	1.6E+02	2.2E+02	3.6E+02
20	3.5E+01	3.5E+01	3.5E+01	3.6E+01	4.6E+01	6.2E+01	8.1E+01	9.7E+01	1.2E+02	2.1E+02	3.0E+02	5.2E+02
30	5.2E+01	5.2E+01	5.2E+01	5.2E+01	5.3E+01	6.4E+01	9.8E+01	1.3E+02	1.8E+02	3.2E+02	4.7E+02	7.7E+02
50	1.3E+02	1.3E+02	1.3E+02	1.3E+02	1.3E+02	1.4E+02	2.0E+02	2.7E+02	3.7E+02	6.8E+02	9.7E+02	1.5E+03
Stack Diameter = 1.0 m												
Stack Height (m)	30	50	70	100	200	300	500	700	1000	2000	3000	5000
10	3.0E+01	3.4E+01	3.8E+01	5.1E+01	9.0E+01	1.2E+02	1.7E+02	2.2E+02	2.7E+02	4.3E+02	5.0E+02	6.1E+02
20	5.5E+01	5.5E+01	5.5E+01	5.6E+01	9.0E+01	1.2E+02	1.7E+02	2.2E+02	2.7E+02	4.3E+02	6.0E+02	7.1E+02
30	9.6E+01	9.6E+01	9.6E+01	9.6E+01	1.1E+02	1.2E+02	1.7E+02	2.2E+02	2.7E+02	4.3E+02	6.8E+02	8.8E+02
50	1.7E+02	1.7E+02	1.7E+02	1.7E+02	1.7E+02	1.7E+02	2.2E+02	2.9E+02	4.0E+02	7.3E+02	1.0E+03	1.6E+03
70	7.0E+02	7.0E+02	7.0E+02	7.0E+02	7.0E+02	7.0E+02	7.6E+02	9.9E+02	1.3E+03	2.0E+03	2.6E+03	3.8E+03
Stack Diameter = 1.5 m												
Stack Height (m)	30	50	70	100	200	300	500	700	1000	2000	3000	5000
10	3.9E+01	5.0E+01	6.1E+01	7.5E+01	1.2E+02	2.0E+02	2.5E+02	3.4E+02	4.6E+02	7.2E+02	8.6E+02	1.0E+03
20	7.1E+01	7.1E+01	7.2E+01	7.5E+01	1.2E+02	2.0E+02	2.5E+02	3.4E+02	4.6E+02	7.2E+02	8.6E+02	1.1E+03
30	1.2E+02	1.2E+02	1.2E+02	1.2E+02	1.5E+02	2.0E+02	2.5E+02	3.4E+02	4.6E+02	7.2E+02	8.6E+02	1.1E+03
50	2.2E+02	2.2E+02	2.2E+02	2.2E+02	2.2E+02	2.2E+02	2.5E+02	3.4E+02	4.6E+02	8.1E+02	1.1E+03	1.7E+03
70	9.6E+02	9.6E+02	9.6E+02	9.6E+02	9.6E+02	9.6E+02	1.0E+03	1.3E+03	1.7E+03	2.9E+03	3.8E+03	5.5E+03
Stack Diameter = 2.0 m												
Stack Height (m)	30	50	70	100	200	300	500	700	1000	2000	3000	5000
10	4.7E+01	6.0E+01	7.3E+01	9.2E+01	1.7E+02	2.6E+02	3.2E+02	4.2E+02	5.6E+02	9.7E+02	1.3E+03	1.5E+03
20	8.6E+01	8.6E+01	8.6E+01	9.4E+01	1.7E+02	2.6E+02	3.2E+02	4.2E+02	5.6E+02	9.7E+02	1.3E+03	1.7E+03
30	1.5E+02	1.5E+02	1.5E+02	1.5E+02	1.8E+02	2.6E+02	3.2E+02	4.2E+02	5.6E+02	9.7E+02	1.3E+03	1.7E+03
50	2.7E+02	2.7E+02	2.7E+02	2.7E+02	2.7E+02	2.7E+02	3.2E+02	4.2E+02	5.6E+02	9.7E+02	1.3E+03	1.9E+03
70	1.3E+03	1.3E+03	1.3E+03	1.3E+03	1.3E+03	1.3E+03	1.4E+03	1.7E+03	2.2E+03	3.2E+03	4.1E+03	5.9E+03
100	2.8E+03	2.8E+03	2.8E+03	2.8E+03	2.8E+03	2.8E+03	2.8E+03	2.8E+03	3.3E+03	5.0E+03	6.5E+03	7.7E+03
Stack Diameter = 3.0 m												
Stack Height (m)	30	50	70	100	200	300	500	700	1000	2000	3000	5000
10	6.2E+01	6.5E+01	7.3E+01	9.2E+01	2.1E+02	3.3E+02	5.1E+02	7.0E+02	9.3E+02	1.2E+03	1.5E+03	1.5E+03
20	1.5E+02	1.5E+02	1.6E+02	1.9E+02	2.4E+02	3.5E+02	5.3E+02	7.0E+02	9.3E+02	1.4E+03	2.0E+03	2.8E+03
30	1.9E+02	1.9E+02	1.9E+02	1.9E+02	2.4E+02	3.5E+02	5.9E+02	7.0E+02	9.3E+02	1.6E+03	2.1E+03	2.8E+03
50	4.0E+02	4.0E+02	4.0E+02	4.0E+02	4.2E+02	4.8E+02	5.3E+02	7.0E+02	9.3E+02	1.6E+03	2.1E+03	2.8E+03
70	2.2E+03	2.2E+03	2.2E+03	2.2E+03	2.2E+03	2.3E+03	2.3E+03	2.8E+03	3.4E+03	3.9E+03	4.7E+03	6.6E+03
100	3.3E+03	3.3E+03	3.3E+03	3.3E+03	3.3E+03	3.3E+03	3.3E+03	3.3E+03	3.7E+03	6.0E+03	7.1E+03	8.2E+03
Stack Diameter = 4.0 m												
Stack Height (m)	30	50	70	100	200	300	500	700	1000	2000	3000	5000
30	2.3E+02	2.3E+02	2.3E+02	2.4E+02	3.2E+02	5.3E+02	7.7E+02	1.0E+03	1.3E+03	2.1E+03	2.6E+03	4.1E+03
50	4.8E+02	4.8E+02	4.8E+02	4.8E+02	5.0E+02	5.8E+02	7.7E+02	1.0E+03	1.3E+03	2.3E+03	3.0E+03	4.2E+03
70	2.4E+03	2.4E+03	2.4E+03	2.4E+03	2.6E+03	2.6E+03	3.2E+03	4.3E+03	4.5E+03	4.7E+03	5.4E+03	7.2E+03
100	5.4E+03	5.4E+03	5.4E+03	5.4E+03	5.4E+03	5.4E+03	5.4E+03	5.4E+03	5.5E+03	8.1E+03	8.8E+03	1.0E+04

Table 4 of §63.1215: 1-Hour Average HCl-Equivalent Emission Rate Limits (lb/hr)--Simple Elevated Terrain

Stack Diameter = 0.3 m	Distance to property boundary (m)												
Stack Height (m)	30	50	70	100	200	300	500	700	1000	2000	3000	5000
5	1.4E+00	1.9E+00	2.6E+00	3.8E+00	6.8E+00	9.4E+00	1.5E+01	2.1E+01	3.3E+01	6.1E+01	1.4E+02	2.7E+02
10	4.0E+00	4.0E+00	4.6E+00	6.4E+00	6.8E+00	9.4E+00	1.5E+01	2.1E+01	3.3E+01	6.1E+01	1.4E+02	2.7E+02
20	1.1E+01	1.1E+01	1.1E+01	1.1E+01	1.2E+01	1.5E+01	2.4E+01	3.5E+01	5.4E+01	1.3E+02	2.1E+02	4.0E+02
30	2.3E+01	2.3E+01	2.3E+01	2.3E+01	2.5E+01	3.3E+01	4.4E+01	5.5E+01	7.3E+01	1.6E+02	2.7E+02	6.2E+02
50	7.3E+01	7.3E+01	7.3E+01	7.3E+01	7.3E+01	8.3E+01	9.0E+01	9.0E+01	9.0E+01	2.1E+02	3.5E+02	6.8E+02
Stack Diameter = 0.5 m												
Stack Height (m)	30	50	70	100	200	300	500	700	1000	2000	3000	5000
5	1.9E+00	2.7E+00	3.7E+00	5.9E+00	1.4E+01	1.7E+01	2.4E+01	3.5E+01	5.4E+01	1.0E+02	1.6E+02	3.0E+02
10	5.6E+00	5.6E+00	6.4E+00	8.9E+00	1.4E+01	1.7E+01	2.4E+01	3.5E+01	5.4E+01	1.0E+02	1.8E+02	3.0E+02
20	1.6E+01	1.6E+01	1.6E+01	1.6E+01	1.6E+01	1.7E+01	2.4E+01	3.5E+01	5.4E+01	1.3E+02	2.1E+02	4.0E+02
30	2.7E+01	2.7E+01	2.7E+01	2.7E+01	2.7E+01	3.3E+01	4.4E+01	5.8E+01	8.5E+01	1.8E+02	2.9E+02	5.5E+02
50	7.6E+01	7.6E+01	7.6E+01	7.6E+01	7.6E+01	8.3E+01	1.1E+02	1.3E+02	1.3E+02	2.4E+02	3.9E+02	7.2E+02
Stack Diameter = 1.0 m												
Stack Height (m)	30	50	70	100	200	300	500	700	1000	2000	3000	5000
10	1.0E+01	1.0E+01	1.2E+01	1.7E+01	3.9E+01	3.9E+01	4.5E+01	5.8E+01	7.9E+01	1.6E+02	2.4E+02	4.4E+02
20	2.6E+01	2.6E+01	2.6E+01	2.8E+01	3.9E+01	3.9E+01	4.5E+01	5.8E+01	7.9E+01	1.6E+02	2.4E+02	4.5E+02
30	4.2E+01	4.2E+01	4.2E+01	4.2E+01	4.2E+01	4.2E+01	4.5E+01	5.8E+01	8.5E+01	1.6E+02	2.9E+02	5.5E+02
50	8.9E+01	8.9E+01	8.9E+01	8.9E+01	8.9E+01	8.9E+01	1.1E+02	1.4E+02	1.7E+02	3.3E+02	5.0E+02	8.7E+02
70	3.8E+02	3.8E+02	3.8E+02	3.8E+02	3.8E+02	3.8E+02	3.8E+02	4.0E+02	4.1E+02	4.3E+02	6.1E+02	1.0E+03
Stack Diameter = 1.5 m												
Stack Height (m)	30	50	70	100	200	300	500	700	1000	2000	3000	5000
10	2.1E+01	2.1E+01	2.5E+01	3.8E+01	5.4E+01	6.3E+01	6.3E+01	6.9E+01	9.8E+01	2.0E+02	3.2E+02	5.7E+02
20	3.3E+01	3.3E+01	3.3E+01	3.7E+01	5.4E+01	6.3E+01	6.3E+01	6.9E+01	9.8E+01	2.0E+02	3.2E+02	5.7E+02
30	6.3E+01	6.3E+01	6.3E+01	6.3E+01	6.3E+01	6.3E+01	6.3E+01	6.9E+01	9.8E+01	2.0E+02	3.2E+02	5.8E+02
50	1.0E+02	1.0E+02	1.0E+02	1.0E+02	1.0E+02	1.0E+02	1.2E+02	1.4E+02	1.7E+02	3.3E+02	5.0E+02	8.7E+02
70	4.8E+02	4.8E+02	4.8E+02	4.8E+02	4.8E+02	4.8E+02	4.8E+02	4.8E+02	4.8E+02	6.5E+02	8.2E+02	1.3E+03
Stack Diameter = 2.0 m												
Stack Height (m)	30	50	70	100	200	300	500	700	1000	2000	3000	5000
10	2.7E+01	2.7E+01	3.2E+01	4.4E+01	6.6E+01	9.7E+01	9.7E+01	1.1E+02	1.5E+02	2.6E+02	3.9E+02	6.6E+02
20	4.0E+01	4.0E+01	4.0E+01	4.4E+01	6.6E+01	9.7E+01	9.7E+01	1.1E+02	1.5E+02	2.6E+02	3.9E+02	6.6E+02
30	7.9E+01	7.9E+01	7.9E+01	7.9E+01	9.1E+01	9.7E+01	9.7E+01	1.1E+02	1.5E+02	2.6E+02	3.9E+02	6.6E+02
50	1.3E+02	1.3E+02	1.3E+02	1.3E+02	1.3E+02	1.3E+02	1.3E+02	1.4E+02	1.7E+02	3.3E+02	5.0E+02	8.7E+02
70	8.6E+02	5.6E+02	5.6E+02	5.6E+02	5.6E+02	5.6E+02	5.6E+02	5.6E+02	5.6E+02	7.3E+02	1.1E+03	1.5E+03
100	8.6E+02	8.6E+02	8.6E+02	8.6E+02	8.6E+02	8.6E+02	8.6E+02	8.6E+02	8.6E+02	1.2E+03	1.7E+03	
Stack Diameter = 3.0 m												
Stack Height (m)	30	50	70	100	200	300	500	700	1000	2000	3000	5000
10	3.5E+01	3.5E+01	4.1E+01	5.8E+01	1.2E+02	1.6E+02	1.8E+02	1.8E+02	1.8E+02	3.5E+02	5.2E+02	9.0E+02
20	6.2E+01	6.2E+01	6.2E+01	7.2E+01	1.2E+02	1.6E+02	1.8E+02	1.8E+02	1.8E+02	3.5E+02	5.2E+02	9.0E+02
30	1.0E+02	1.0E+02	1.0E+02	1.0E+02	1.2E+02	1.6E+02	1.8E+02	1.8E+02	1.8E+02	3.5E+02	5.2E+02	9.0E+02
50	1.8E+02	1.8E+02	1.8E+02	1.8E+02	1.8E+02	1.8E+02	1.8E+02	1.8E+02	1.8E+02	3.5E+02	5.2E+02	9.0E+02
70	7.5E+02	7.5E+02	7.5E+02	7.6E+02	7.5E+02	7.5E+02	7.5E+02	7.5E+02	7.5E+02	8.9E+02	1.3E+03	2.0E+03
100	1.4E+03	1.4E+03	1.4E+03	1.4E+03	1.4E+03	1.4E+03	1.4E+03	1.4E+03	1.4E+03	1.4E+03	2.0E+03	2.6E+03
Stack Diameter = 4.0 m												
Stack Height (m)	30	50	70	100	200	300	500	700	1000	2000	3000	5000
30	1.2E+02	1.2E+02	1.2E+02	1.2E+02	1.4E+02	2.0E+02	2.2E+02	2.2E+02	2.2E+02	4.2E+02	6.3E+02	1.0E+03
50	2.2E+02	2.2E+02	2.2E+02	2.2E+02	2.2E+02	2.2E+02	2.2E+02	2.2E+02	2.2E+02	4.2E+02	6.3E+02	1.0E+03
70	1.0E+03	1.0E+03	1.0E+03	1.0E+03	1.0E+03	1.0E+03	1.0E+03	1.0E+03	1.0E+03	1.1E+03	1.6E+03	2.4E+03
100	1.6E+03	1.6E+03	1.6E+03	1.6E+03	1.6E+03	1.6E+03	1.6E+03	1.6E+03	1.6E+03	1.6E+03	2.3E+03	3.6E+03

■ 17. Section 63.1216 and an undesignated center heading are added to subpart EEE to read as follows:

Emissions Standards and Operating Limits for Solid Fuel Boilers, Liquid Fuel Boilers, and Hydrochloric Acid Production Furnaces

§ 63.1216 What are the standards for solid fuel boilers that burn hazardous waste?

(a) *Emission limits for existing sources.* You must not discharge or cause combustion gases to be emitted into the atmosphere that contain:

(1) For dioxins and furans, either carbon monoxide or hydrocarbon emissions in excess of the limits provided by paragraph (a)(5) of this section;

(2) Mercury in excess of 11 µg/dscm corrected to 7 percent oxygen;

(3) For cadmium and lead combined, except for an area source as defined under § 63.2, emissions in excess of 180 µg/dscm, corrected to 7 percent oxygen;

(4) For arsenic, beryllium, and chromium combined, except for an area source as defined under § 63.2, emissions in excess of 380 µg/dscm, corrected to 7 percent oxygen;

(5) For carbon monoxide and hydrocarbons, either:

(i) Carbon monoxide in excess of 100 parts per million by volume, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis and corrected to 7 percent oxygen. If

you elect to comply with this carbon monoxide standard rather than the hydrocarbon standard under paragraph (a)(5)(ii) of this section, you must also document that, during the destruction and removal efficiency (DRE) test runs or their equivalent as provided by § 63.1206(b)(7), hydrocarbons do not exceed 10 parts per million by volume during those runs, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis, corrected to 7 percent oxygen, and reported as propane; or

(ii) Hydrocarbons in excess of 10 parts per million by volume, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis, corrected to 7 percent oxygen, and reported as propane;

(6) For hydrogen chloride and chlorine combined, except for an area source as defined under § 63.2, emissions in excess of 440 parts per million by volume, expressed as a chloride ($Cl^{(-)}$) equivalent, dry basis and corrected to 7 percent oxygen; and

(7) For particulate matter, except for an area source as defined under § 63.2 or as provided by paragraph (e) of this section, emissions in excess of 68 mg/dscm corrected to 7 percent oxygen.

(b) *Emission limits for new sources.* You must not discharge or cause combustion gases to be emitted into the atmosphere that contain:

(1) For dioxins and furans, either carbon monoxide or hydrocarbon emissions in excess of the limits provided by paragraph (b)(5) of this section;

(2) Mercury in excess of 11 µg/dscm corrected to 7 percent oxygen;

(3) For cadmium and lead combined, except for an area source as defined under § 63.2, emissions in excess of 180 µg/dscm, corrected to 7 percent oxygen;

(4) For arsenic, beryllium, and chromium combined, except for an area source as defined under § 63.2, emissions in excess of 190 µg/dscm, corrected to 7 percent oxygen;

(5) For carbon monoxide and hydrocarbons, either:

(i) Carbon monoxide in excess of 100 parts per million by volume, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis and corrected to 7 percent oxygen. If you elect to comply with this carbon monoxide standard rather than the hydrocarbon standard under paragraph (b)(5)(ii) of this section, you must also document that, during the destruction and removal efficiency (DRE) test runs or their equivalent as provided by § 63.1206(b)(7), hydrocarbons do not exceed 10 parts per million by volume during those runs, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis, corrected to 7 percent oxygen, and reported as propane; or

(ii) Hydrocarbons in excess of 10 parts per million by volume, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis, corrected to 7 percent oxygen, and reported as propane;

(6) For hydrogen chloride and chlorine combined, except for an area source as defined under § 63.2, emissions in excess of 73 parts per million by volume, expressed as a chloride ($Cl^{(-)}$) equivalent, dry basis and corrected to 7 percent oxygen; and

(7) For particulate matter, except for an area source as defined under § 63.2 or as provided by paragraph (e) of this section, emissions in excess of 34 mg/dscm corrected to 7 percent oxygen.

(c) *Destruction and removal efficiency (DRE) standard.* (1) *99.99% DRE.* Except as provided in paragraph (c)(2) of this section, you must achieve a DRE of 99.99% for each principle organic hazardous constituent (POHC) designated under paragraph (c)(3) of this section. You must calculate DRE for each POHC from the following equation:

$$DRE = [1 - (W_{out} + W_{in})] \times 100\%$$

Where:

W_{in} = mass feedrate of one POHC in a waste feedstream; and

W_{out} = mass emission rate of the same POHC present in exhaust emissions prior to release to the atmosphere.

(2) *99.9999% DRE.* If you burn the dioxin-listed hazardous wastes F020, F021, F022, F023, F026, or F027 (see § 261.31 of this chapter), you must achieve a DRE of 99.9999% for each POHC that you designate under paragraph (c)(3) of this section. You must demonstrate this DRE performance on POHCs that are more difficult to incinerate than tetra-, penta-, and hexachlorodibenzo-*p*-dioxins and dibenzofurans. You must use the equation in paragraph (c)(1) of this section to calculate DRE for each POHC. In addition, you must notify the Administrator of your intent to incinerate hazardous wastes F020, F021, F022, F023, F026, or F027.

(3) *Principal organic hazardous constituents (POHCs).* (i) You must treat the POHCs in the waste feed that you specify under paragraph (c)(3)(ii) of this section to the extent required by paragraphs (c)(1) and (c)(2) of this section.

(ii) You must specify one or more POHCs that are representative of the most difficult to destroy organic compounds in your hazardous waste feedstream. You must base this specification on the degree of difficulty of incineration of the organic constituents in the hazardous waste and on their concentration or mass in the hazardous waste feed, considering the results of hazardous waste analyses or other data and information.

(d) *Significant figures.* The emission limits provided by paragraphs (a) and (b) of this section are presented with two significant figures. Although you must perform intermediate calculations using at least three significant figures, you may round the resultant emission levels to two significant figures to document compliance.

(e) *Alternative to the particulate matter standard.* (1) *General.* In lieu of complying with the particulate matter standards of this section, you may elect to comply with the following alternative metal emission control requirement:

(2) *Alternative metal emission control requirements for existing solid fuel boilers.* (i) You must not discharge or cause combustion gases to be emitted into the atmosphere that contain cadmium, lead, and selenium in excess of 180 µg/dscm, combined emissions, corrected to 7 percent oxygen; and,

(ii) You must not discharge or cause combustion gases to be emitted into the atmosphere that contain antimony, arsenic, beryllium, chromium, cobalt, manganese, and nickel in excess of 380 µg/dscm, combined emissions, corrected to 7 percent oxygen.

(3) Alternative metal emission control requirements for new solid fuel boilers. (i) You must not discharge or cause combustion gases to be emitted into the atmosphere that contain cadmium, lead, and selenium in excess of 180 µg/dscm, combined emissions, corrected to 7 percent oxygen; and,

(ii) You must not discharge or cause combustion gases to be emitted into the atmosphere that contain antimony, arsenic, beryllium, chromium, cobalt, manganese, and nickel in excess of 190 µg/dscm, combined emissions, corrected to 7 percent oxygen.

(4) *Operating limits.* Semivolatile and low volatile metal operating parameter limits must be established to ensure compliance with the alternative emission limitations described in paragraphs (e)(2) and (e)(3) of this section pursuant to § 63.1209(n), except that semivolatile metal feedrate limits apply to lead, cadmium, and selenium, combined, and low volatile metal feedrate limits apply to arsenic,

beryllium, chromium, antimony, cobalt, manganese, and nickel, combined.

(f) *Elective standards for area sources.* Area sources as defined under § 63.2 are subject to the standards for cadmium and lead, the standards for arsenic, beryllium, and chromium, the standards for hydrogen chloride and chlorine, and the standards for particulate matter under this section if they elect under § 266.100(b)(3) of this chapter to comply with those standards in lieu of the standards under 40 CFR 266.105, 266.106, and 266.107 to control those pollutants.

■ 18. Section 63.1217 is added to read as follows:

§ 63.1217 What are the standards for liquid fuel boilers that burn hazardous waste?

(a) *Emission limits for existing sources.* You must not discharge or cause combustion gases to be emitted into the atmosphere that contain:

(1)(i) Dioxins and furans in excess of 0.40 ng TEQ/dscm, corrected to 7 percent oxygen, for liquid fuel boilers equipped with a dry air pollution control system; or

(ii) Either carbon monoxide or hydrocarbon emissions in excess of the limits provided by paragraph (a)(5) of this section for sources not equipped with a dry air pollution control system;

(iii) A source equipped with a wet air pollution control system followed by a dry air pollution control system is not considered to be a dry air pollution control system, and a source equipped with a dry air pollution control system followed by a wet air pollution control system is considered to be a dry air pollution control system for purposes of this emission limit;

(2) For mercury, except as provided for in paragraph (a)(2)(iii) of this section:

(i) When you burn hazardous waste with an as-fired heating value less than 10,000 Btu/lb, emissions in excess of 19 µg/dscm, corrected to 7 percent oxygen, on an (not-to-exceed) annual averaging period;

(ii) When you burn hazardous waste with an as-fired heating value 10,000 Btu/lb or greater, emissions in excess of 4.2×10^{-5} lbs mercury attributable to the hazardous waste per million Btu heat input from the hazardous waste on an (not-to-exceed) annual averaging period;

(iii) The boiler operated by Diversified Scientific Services, Inc. with EPA identification number TND982109142, and which burns radioactive waste mixed with hazardous waste, must comply with the mercury emission standard under § 63.1219(a)(2);

(3) For cadmium and lead combined, except for an area source as defined under § 63.2,

(i) When you burn hazardous waste with an as-fired heating value less than 10,000 Btu/lb, emissions in excess of 150 µg/dscm, corrected to 7 percent oxygen, on an (not-to-exceed) annual averaging period;

(ii) When you burn hazardous waste with an as-fired heating value of 10,000 Btu/lb or greater, emissions in excess of 8.2×10^{-5} lbs combined cadmium and lead emissions attributable to the hazardous waste per million Btu heat input from the hazardous waste on an (not-to-exceed) annual averaging period;

(4) For chromium, except for an area source as defined under § 63.2:

(i) When you burn hazardous waste with an as-fired heating value less than 10,000 Btu/lb, emissions in excess of 370 µg/dscm, corrected to 7 percent oxygen;

(ii) When you burn hazardous waste with an as-fired heating value of 10,000 Btu/lb or greater, emissions in excess of 1.3×10^{-4} lbs chromium emissions attributable to the hazardous waste per million Btu heat input from the hazardous waste;

(5) For carbon monoxide and hydrocarbons, either:

(i) Carbon monoxide in excess of 100 parts per million by volume, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis and corrected to 7 percent oxygen. If you elect to comply with this carbon monoxide standard rather than the hydrocarbon standard under paragraph (a)(5)(ii) of this section, you must also document that, during the destruction and removal efficiency (DRE) test runs or their equivalent as provided by § 63.1206(b)(7), hydrocarbons do not exceed 10 parts per million by volume during those runs, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis, corrected to 7 percent oxygen, and reported as propane; or

(ii) Hydrocarbons in excess of 10 parts per million by volume, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis, corrected to 7 percent oxygen, and reported as propane;

(6) For hydrogen chloride and chlorine, except for an area source as defined under § 63.2:

(i) When you burn hazardous waste with an as-fired heating value less than 10,000 Btu/lb, emissions in excess of 31 parts per million by volume, combined emissions, expressed as a chloride ($Cl^{\ominus}$) equivalent, dry basis and corrected to 7 percent oxygen;

(ii) When you burn hazardous waste with an as-fired heating value of 10,000 Btu/lb or greater, emissions in excess of 5.08×10^{-2} lbs combined emissions of hydrogen chloride and chlorine gas attributable to the hazardous waste per million Btu heat input from the hazardous waste;

(7) For particulate matter, except for an area source as defined under § 63.2 or as provided by paragraph (e) of this section, emissions in excess of 80 mg/dscm corrected to 7 percent oxygen.

(b) *Emission limits for new sources.* You must not discharge or cause combustion gases to be emitted into the atmosphere that contain:

(1)(i) Dioxins and furans in excess of 0.40 ng TEQ/dscm, corrected to 7 percent oxygen, for liquid fuel boilers equipped with a dry air pollution control system; or

(ii) Either carbon monoxide or hydrocarbon emissions in excess of the limits provided by paragraph (b)(5) of this section for sources not equipped with a dry air pollution control system;

(iii) A source equipped with a wet air pollution control system followed by a dry air pollution control system is not considered to be a dry air pollution control system, and a source equipped with a dry air pollution control system followed by a wet air pollution control system is considered to be a dry air pollution control system for purposes of this emission limit;

(2) For mercury:

(i) When you burn hazardous waste with an as-fired heating value less than 10,000 Btu/lb, emissions in excess of 6.8 µg/dscm, corrected to 7 percent oxygen, on an (not-to-exceed) annual averaging period;

(ii) When you burn hazardous waste with an as-fired heating value of 10,000 Btu/lb or greater, emissions in excess of 1.2×10^{-6} lbs mercury emissions attributable to the hazardous waste per million Btu heat input from the hazardous waste on an (not-to-exceed) annual averaging period;

(3) For cadmium and lead combined, except for an area source as defined under § 63.2:

(i) When you burn hazardous waste with an as-fired heating value less than 10,000 Btu/lb, emissions in excess of 78 µg/dscm, corrected to 7 percent oxygen, on an (not-to-exceed) annual averaging period;

(ii) When you burn hazardous waste with an as-fired heating value greater than or equal to 10,000 Btu/lb, emissions in excess of 6.2×10^{-6} lbs combined cadmium and lead emissions attributable to the hazardous waste per

million Btu heat input from the hazardous waste on an (not-to-exceed) annual averaging period;

(4) For chromium, except for an area source as defined under § 63.2:

(i) When you burn hazardous waste with an as-fired heating value less than 10,000 Btu/lb, emissions in excess of 12 µg/dscm, corrected to 7 percent oxygen;

(ii) When you burn hazardous waste with an as-fired heating value of 10,000 Btu/lb or greater, emissions in excess of 1.4×10^{-5} lbs chromium emissions attributable to the hazardous waste per million Btu heat input from the hazardous waste;

(5) For carbon monoxide and hydrocarbons, either:

(i) Carbon monoxide in excess of 100 parts per million by volume, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis and corrected to 7 percent oxygen. If you elect to comply with this carbon monoxide standard rather than the hydrocarbon standard under paragraph (b)(5)(ii) of this section, you must also document that, during the destruction and removal efficiency (DRE) test runs or their equivalent as provided by § 63.1206(b)(7), hydrocarbons do not exceed 10 parts per million by volume during those runs, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis, corrected to 7 percent oxygen, and reported as propane; or

(ii) Hydrocarbons in excess of 10 parts per million by volume, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis, corrected to 7 percent oxygen, and reported as propane;

(6) For hydrogen chloride and chlorine, except for an area source as defined under § 63.2:

(i) When you burn hazardous waste with an as-fired heating value less than 10,000 Btu/lb, emissions in excess of 31 parts per million by volume, combined emissions, expressed as a chloride ($Cl^{(-)}$) equivalent, dry basis and corrected to 7 percent oxygen;

(ii) When you burn hazardous waste with an as-fired heating value of 10,000 Btu/lb or greater, emissions in excess of 5.08×10^{-2} lbs combined emissions of hydrogen chloride and chlorine gas attributable to the hazardous waste per million Btu heat input from the hazardous waste;

(7) For particulate matter, except for an area source as defined under § 63.2 or as provided by paragraph (e) of this section, emissions in excess of 20 mg/dscm corrected to 7 percent oxygen.

(c) *Destruction and removal efficiency (DRE) standard.* (1) *99.99% DRE.* Except as provided in paragraph (c)(2) of this section, you must achieve a DRE of 99.99% for each principle organic hazardous constituent (POHC) designated under paragraph (c)(3) of this section. You must calculate DRE for each POHC from the following equation:

$$DRE = [1 - (W_{out} + W_{in})] \times 100\%$$

Where:

W_{in} = mass feedrate of one POHC in a waste feedstream; and

W_{out} = mass emission rate of the same POHC present in exhaust emissions prior to release to the atmosphere.

(2) *99.9999% DRE.* If you burn the dioxin-listed hazardous wastes F020, F021, F022, F023, F026, or F027 (see § 261.31 of this chapter), you must achieve a DRE of 99.9999% for each POHC that you designate under paragraph (c)(3) of this section. You must demonstrate this DRE performance on POHCs that are more difficult to incinerate than tetra-, penta-, and hexachlorodibenzo-*p*-dioxins and dibenzofurans. You must use the equation in paragraph (c)(1) of this section to calculate DRE for each POHC. In addition, you must notify the Administrator of your intent to incinerate hazardous wastes F020, F021, F022, F023, F026, or F027.

(3) *Principal organic hazardous constituents (POHCs).* (i) You must treat the POHCs in the waste feed that you specify under paragraph (c)(3)(ii) of this section to the extent required by paragraphs (c)(1) and (c)(2) of this section.

(ii) You must specify one or more POHCs that are representative of the most difficult to destroy organic compounds in your hazardous waste feedstream. You must base this specification on the degree of difficulty of incineration of the organic constituents in the hazardous waste and on their concentration or mass in the hazardous waste feed, considering the results of hazardous waste analyses or other data and information.

(d) *Significant figures.* The emission limits provided by paragraphs (a) and (b) of this section are presented with two significant figures. Although you must perform intermediate calculations using at least three significant figures, you may round the resultant emission levels to two significant figures to document compliance.

(e) *Alternative to the particulate matter standard.* (1) *General.* In lieu of complying with the particulate matter standards of this section, you may elect to comply with the following alternative metal emission control requirement:

(2) *Alternative metal emission control requirements for existing liquid fuel boilers.* (i) When you burn hazardous waste with a heating value less than 10,000 Btu/lb:

(A) You must not discharge or cause combustion gases to be emitted into the atmosphere that contain cadmium, lead, and selenium, combined, in excess of 150 µg/dscm, corrected to 7 percent oxygen; and

(B) You must not discharge or cause combustion gases to be emitted into the atmosphere that contain antimony, arsenic, beryllium, chromium, cobalt, manganese, and nickel, combined, in excess of 370 µg/dscm, corrected to 7 percent oxygen;

(ii) When you burn hazardous waste with a heating value of 10,000 Btu/lb or greater:

(A) You must not discharge or cause combustion gases to be emitted into the atmosphere that contain in excess of 8.2×10^{-5} lbs combined emissions of cadmium, lead, and selenium attributable to the hazardous waste per million Btu heat input from the hazardous waste; and

(B) You must not discharge or cause combustion gases to be emitted into the atmosphere that contain either in excess of 1.3×10^{-4} lbs combined emissions of antimony, arsenic, beryllium, chromium, cobalt, manganese, and nickel attributable to the hazardous waste per million Btu heat input from the hazardous waste;

(3) *Alternative metal emission control requirements for new liquid fuel boilers.* (i) When you burn hazardous waste with a heating value less than 10,000 Btu/lb:

(A) You must not discharge or cause combustion gases to be emitted into the atmosphere that contain cadmium, lead, and selenium, combined, in excess of 78 µg/dscm, corrected to 7 percent oxygen; and

(B) You must not discharge or cause combustion gases to be emitted into the atmosphere that contain antimony, arsenic, beryllium, chromium, cobalt, manganese, and nickel, combined, in excess of 12 µg/dscm, corrected to 7 percent oxygen;

(ii) When you burn hazardous waste with a heating value greater than or equal to 10,000 Btu/lb:

(A) You must not discharge or cause combustion gases to be emitted into the atmosphere that contain in excess of 6.2×10^{-6} lbs combined emissions of cadmium, lead, and selenium attributable to the hazardous waste per million Btu heat input from the hazardous waste; and

(B) You must not discharge or cause combustion gases to be emitted into the

atmosphere that contain either in excess of 1.4×10^{-5} lbs combined emissions of antimony, arsenic, beryllium, chromium, cobalt, manganese, and nickel attributable to the hazardous waste per million Btu heat input from the hazardous waste;

(4) *Operating limits.* Semivolatile and low volatile metal operating parameter limits must be established to ensure compliance with the alternative emission limitations described in paragraphs (e)(2) and (e)(3) of this section pursuant to § 63.1209(n), except that semivolatile metal feedrate limits apply to lead, cadmium, and selenium, combined, and low volatile metal feedrate limits apply to arsenic, beryllium, chromium, antimony, cobalt, manganese, and nickel, combined.

(f) *Elective standards for area sources.* Area sources as defined under § 63.2 are subject to the standards for cadmium and lead, the standards for chromium, the standards for hydrogen chloride and chlorine, and the standards for particulate matter under this section if they elect under § 266.100(b)(3) of this chapter to comply with those standards in lieu of the standards under 40 CFR 266.105, 266.106, and 266.107 to control those pollutants.

■ 19. Section 63.1218 is added to read as follows:

§ 63.1218 What are the standards for hydrochloric acid production furnaces that burn hazardous waste?

(a) *Emission limits for existing sources.* You must not discharge or cause combustion gases to be emitted into the atmosphere that contain:

(1) For dioxins and furans, either carbon monoxide or hydrocarbon emissions in excess of the limits provided by paragraph (a)(5) of this section;

(2) For mercury, hydrogen chloride and chlorine gas emissions in excess of the levels provided by paragraph (a)(6) of this section;

(3) For lead and cadmium, except for an area source as defined under § 63.2, hydrogen chloride and chlorine gas emissions in excess of the levels provided by paragraph (a)(6) of this section;

(4) For arsenic, beryllium, and chromium, except for an area source as defined under § 63.2, hydrogen chloride and chlorine gas emissions in excess of the levels provided by paragraph (a)(6) of this section;

(5) For carbon monoxide and hydrocarbons, either:

(i) Carbon monoxide in excess of 100 parts per million by volume, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis and corrected to 7 percent oxygen. If you elect to comply with this carbon monoxide standard rather than the hydrocarbon standard under paragraph (a)(5)(ii) of this section, you must also document that, during the destruction and removal efficiency (DRE) test runs or their equivalent as provided by § 63.1206(b)(7), hydrocarbons do not exceed 10 parts per million by volume during those runs, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis, corrected to 7 percent oxygen, and reported as propane; or

(ii) Hydrocarbons in excess of 10 parts per million by volume, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis, corrected to 7 percent oxygen, and reported as propane;

(6) For hydrogen chloride and chlorine gas, either:

(i) Emission in excess of 150 parts per million by volume, combined emissions, expressed as a chloride ($Cl^{(-)}$ equivalent, dry basis and corrected to 7 percent oxygen; or

(ii) Emissions greater than the levels that would be emitted if the source is achieving a system removal efficiency (SRE) of less than 99.923 percent for total chlorine and chloride fed to the combustor. You must calculate SRE from the following equation:

$$SRE = [1 - (Cl_{out} / Cl_{in})] \times 100\%$$

Where:

Cl in = mass feedrate of total chlorine or chloride in all feedstreams, reported as chloride; and

Cl out = mass emission rate of hydrogen chloride and chlorine gas, reported as chloride, in exhaust emissions prior to release to the atmosphere.

(7) For particulate matter, except for an area source as defined under § 63.2, hydrogen chloride and chlorine gas emissions in excess of the levels provided by paragraph (a)(6) of this section.

(b) *Emission limits for new sources.* You must not discharge or cause combustion gases to be emitted into the atmosphere that contain:

(1) For dioxins and furans, either carbon monoxide or hydrocarbon emissions in excess of the limits provided by paragraph (b)(5) of this section;

(2) For mercury, hydrogen chloride and chlorine gas emissions in excess of the levels provided by paragraph (b)(6) of this section;

(3) For lead and cadmium, except for an area source as defined under § 63.2, hydrogen chloride and chlorine gas emissions in excess of the levels provided by paragraph (b)(6) of this section;

(4) For arsenic, beryllium, and chromium, except for an area source as defined under § 63.2, hydrogen chloride and chlorine gas emissions in excess of the levels provided by paragraph (b)(6) of this section;

(5) For carbon monoxide and hydrocarbons, either:

(i) Carbon monoxide in excess of 100 parts per million by volume, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis and corrected to 7 percent oxygen. If you elect to comply with this carbon monoxide standard rather than the hydrocarbon standard under paragraph (b)(5)(ii) of this section, you must also document that, during the destruction and removal efficiency (DRE) test runs or their equivalent as provided by § 63.1206(b)(7), hydrocarbons do not exceed 10 parts per million by volume during those runs, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis, corrected to 7 percent oxygen, and reported as propane; or

(ii) Hydrocarbons in excess of 10 parts per million by volume, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis, corrected to 7 percent oxygen, and reported as propane;

(6) For hydrogen chloride and chlorine gas, either:

(i) Emission in excess of 25 parts per million by volume, combined emissions, expressed as a chloride ($Cl^{(-)}$ equivalent, dry basis and corrected to 7 percent oxygen; or

(ii) Emissions greater than the levels that would be emitted if the source is achieving a system removal efficiency (SRE) of less than 99.987 percent for total chlorine and chloride fed to the combustor. You must calculate SRE from the following equation:

$$SRE = [1 - (Cl_{out} / Cl_{in})] \times 100\%$$

Where:

Cl in = mass feedrate of total chlorine or chloride in all feedstreams, reported as chloride; and

Cl out = mass emission rate of hydrogen chloride and chlorine gas, reported as chloride, in exhaust emissions prior to release to the atmosphere.

(7) For particulate matter, except for an area source as defined under § 63.2, hydrogen chloride and chlorine gas

emissions in excess of the levels provided by paragraph (b)(6) of this section.

(c) *Destruction and removal efficiency (DRE) standard.* (1) *99.99% DRE.* Except as provided in paragraph (c)(2) of this section, you must achieve a DRE of 99.99% for each principle organic hazardous constituent (POHC) designated under paragraph (c)(3) of this section. You must calculate DRE for each POHC from the following equation:

$$DRE = [1 - (W_{out} / W_{in})] \times 100\%$$

Where:

Win = mass feedrate of one POHC in a waste feedstream; and

Wout = mass emission rate of the same POHC present in exhaust emissions prior to release to the atmosphere.

(2) *99.9999% DRE.* If you burn the dioxin-listed hazardous wastes F020, F021, F022, F023, F026, or F027 (see § 261.31 of this chapter), you must achieve a DRE of 99.9999% for each POHC that you designate under paragraph (c)(3) of this section. You must demonstrate this DRE performance on POHCs that are more difficult to incinerate than tetra-, penta-, and hexachlorodibenzo-*p*-dioxins and dibenzofurans. You must use the equation in paragraph (c)(1) of this section to calculate DRE for each POHC. In addition, you must notify the Administrator of your intent to incinerate hazardous wastes F020, F021, F022, F023, F026, or F027.

(3) *Principal organic hazardous constituents (POHCs).* (i) You must treat the POHCs in the waste feed that you specify under paragraph (c)(3)(ii) of this section to the extent required by paragraphs (c)(1) and (c)(2) of this section.

(ii) You must specify one or more POHCs that are representative of the most difficult to destroy organic compounds in your hazardous waste feedstream. You must base this specification on the degree of difficulty of incineration of the organic constituents in the hazardous waste and on their concentration or mass in the hazardous waste feed, considering the results of hazardous waste analyses or other data and information.

(d) *Significant figures.* The emission limits provided by paragraphs (a) and (b) of this section are presented with two significant figures. Although you must perform intermediate calculations using at least three significant figures, you may round the resultant emission levels to two significant figures to document compliance.

(e) *Elective standards for area sources.* Area sources as defined under § 63.2 are subject to the standards for cadmium and lead, the standards for arsenic, beryllium, and chromium, the standards for hydrogen chloride and chlorine, and the standards for particulate matter under this section if they elect under § 266.100(b)(3) of this chapter to comply with those standards in lieu of the standards under 40 CFR 266.105, 266.106, and 266.107 to control those pollutants.

■ 20. Section 63.1219 and a new undesignated center heading are added to subpart EEE to read as follows:

Replacement Emissions Standards and Operating Limits for Incinerators, Cement Kilns, and Lightweight Aggregate Kilns

§ 63.1219 What are the replacement standards for hazardous waste incinerators?

(a) *Emission limits for existing sources.* You must not discharge or cause combustion gases to be emitted into the atmosphere that contain:

(1) For dioxins and furans:

(i) For incinerators equipped with either a waste heat boiler or dry air pollution control system, either:

(A) Emissions in excess of 0.20 ng TEQ/dscm, corrected to 7 percent oxygen; or

(B) Emissions in excess of 0.40 ng TEQ/dscm, corrected to 7 percent oxygen, provided that the combustion gas temperature at the inlet to the initial particulate matter control device is 400°F or lower based on the average of the test run average temperatures. (For purposes of compliance, operation of a wet particulate matter control device is presumed to meet the 400°F or lower requirement);

(ii) Emissions in excess of 0.40 ng TEQ/dscm, corrected to 7 percent oxygen, for incinerators not equipped with either a waste heat boiler or dry air pollution control system;

(iii) A source equipped with a wet air pollution control system followed by a dry air pollution control system is not considered to be a dry air pollution control system, and a source equipped with a dry air pollution control system followed by a wet air pollution control system is considered to be a dry air pollution control system for purposes of this standard;

(2) Mercury in excess of 130 µg/dscm, corrected to 7 percent oxygen;

(3) Cadmium and lead in excess of 230 µg/dscm, combined emissions, corrected to 7 percent oxygen;

(4) Arsenic, beryllium, and chromium in excess of 92 µg/dscm, combined emissions, corrected to 7 percent oxygen;

(5) For carbon monoxide and hydrocarbons, either:

(i) Carbon monoxide in excess of 100 parts per million by volume, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis and corrected to 7 percent oxygen. If you elect to comply with this carbon monoxide standard rather than the hydrocarbon standard under paragraph (a)(5)(ii) of this section, you must also document that, during the destruction and removal efficiency (DRE) test runs or their equivalent as provided by § 63.1206(b)(7), hydrocarbons do not exceed 10 parts per million by volume during those runs, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis, corrected to 7 percent oxygen, and reported as propane; or

(ii) Hydrocarbons in excess of 10 parts per million by volume, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis, corrected to 7 percent oxygen, and reported as propane;

(6) Hydrogen chloride and chlorine gas (total chlorine) in excess of 32 parts per million by volume, combined emissions, expressed as a chloride ($Cl^{(-)}$) equivalent, dry basis and corrected to 7 percent oxygen; and

(7) Except as provided by paragraph (e) of this section, particulate matter in excess of 0.013 gr/dscf corrected to 7 percent oxygen.

(b) *Emission limits for new sources.* You must not discharge or cause combustion gases to be emitted into the atmosphere that contain:

(1)(i) Dioxins and furans in excess of 0.11 ng TEQ/dscm corrected to 7 percent oxygen for incinerators equipped with either a waste heat boiler or dry air pollution control system; or

(ii) Dioxins and furans in excess of 0.20 ng TEQ/dscm corrected to 7 percent oxygen for sources not equipped with either a waste heat boiler or dry air pollution control system;

(iii) A source equipped with a wet air pollution control system followed by a dry air pollution control system is not considered to be a dry air pollution control system, and a source equipped with a dry air pollution control system followed by a wet air pollution control system is considered to be a dry air pollution control system for purposes of this standard;

(2) Mercury in excess of 8.1 µg/dscm, corrected to 7 percent oxygen;

(3) Cadmium and lead in excess of 10 µg/dscm, combined emissions, corrected to 7 percent oxygen;

(4) Arsenic, beryllium, and chromium in excess of 23 µg/dscm, combined

emissions, corrected to 7 percent oxygen;

(5) For carbon monoxide and hydrocarbons, either:

(i) Carbon monoxide in excess of 100 parts per million by volume, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis and corrected to 7 percent oxygen. If you elect to comply with this carbon monoxide standard rather than the hydrocarbon standard under paragraph (b)(5)(ii) of this section, you must also document that, during the destruction and removal efficiency (DRE) test runs or their equivalent as provided by § 63.1206(b)(7), hydrocarbons do not exceed 10 parts per million by volume during those runs, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis, corrected to 7 percent oxygen, and reported as propane; or

(ii) Hydrocarbons in excess of 10 parts per million by volume, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis, corrected to 7 percent oxygen, and reported as propane;

(6) Hydrogen chloride and chlorine gas in excess of 21 parts per million by volume, combined emissions, expressed as a chloride ($Cl^{(-)}$) equivalent, dry basis and corrected to 7 percent oxygen; and

(7) Except as provided by paragraph (e) of this section, particulate matter in excess of 0.0015 gr/dscf, corrected to 7 percent oxygen.

(c) *Destruction and removal efficiency (DRE) standard.* (1) *99.99% DRE.* Except as provided in paragraph (c)(2) of this section, you must achieve a destruction and removal efficiency (DRE) of 99.99% for each principle organic hazardous constituent (POHC) designated under paragraph (c)(3) of this section. You must calculate DRE for each POHC from the following equation:

$$DRE = [1 - (W_{out} / W_{in})] \times 100\%$$

Where:

W_{in} = mass feedrate of one POHC in a waste feedstream; and

W_{out} = mass emission rate of the same POHC present in exhaust emissions prior to release to the atmosphere.

(2) *99.9999% DRE.* If you burn the dioxin-listed hazardous wastes F020, F021, F022, F023, F026, or F027 (see § 261.31 of this chapter), you must achieve a DRE of 99.9999% for each POHC that you designate under paragraph (c)(3) of this section. You must demonstrate this DRE performance on POHCs that are more difficult to incinerate than tetra-, penta-, and hexachlorodibenzo-p-dioxins and dibenzofurans. You must use the equation in paragraph (c)(1) of this section to calculate DRE for each POHC. In addition, you must notify the Administrator of your intent to incinerate hazardous wastes F020, F021, F022, F023, F026, or F027.

(3) *Principal organic hazardous constituent (POHC).* (i) You must treat each POHC in the waste feed that you specify under paragraph (c)(3)(ii) of this section to the extent required by paragraphs (c)(1) and (c)(2) of this section.

(ii) You must specify one or more POHCs that are representative of the most difficult to destroy organic compounds in your hazardous waste feedstream. You must base this specification on the degree of difficulty of incineration of the organic constituents in the hazardous waste and on their concentration or mass in the hazardous waste feed, considering the results of hazardous waste analyses or other data and information.

(d) *Significant figures.* The emission limits provided by paragraphs (a) and (b) of this section are presented with two significant figures. Although you must perform intermediate calculations using at least three significant figures, you may round the resultant emission levels to two significant figures to document compliance.

(e) *Alternative to the particulate matter standard.* (1). *General.* In lieu of complying with the particulate matter standards of this section, you may elect to comply with the following alternative metal emission control requirement:

(2) *Alternative metal emission control requirements for existing incinerators.* (i) You must not discharge or cause combustion gases to be emitted into the atmosphere that contain cadmium, lead, and selenium in excess of 230 μg/dscm, combined emissions, corrected to 7 percent oxygen; and,

(ii) You must not discharge or cause combustion gases to be emitted into the atmosphere that contain antimony, arsenic, beryllium, chromium, cobalt, manganese, and nickel in excess of 92 μg/dscm, combined emissions, corrected to 7 percent oxygen.

(3) *Alternative metal emission control requirements for new incinerators.* (i) You must not discharge or cause combustion gases to be emitted into the atmosphere that contain cadmium, lead, and selenium in excess of 10 μg/dscm, combined emissions, corrected to 7 percent oxygen; and,

(ii) You must not discharge or cause combustion gases to be emitted into the atmosphere that contain antimony, arsenic, beryllium, chromium, cobalt, manganese, and nickel in excess of 23 μg/dscm, combined emissions, corrected to 7 percent oxygen.

(4) *Operating limits.* Semivolatile and low volatile metal operating parameter limits must be established to ensure compliance with the alternative emission limitations described in paragraphs (e)(2) and (e)(3) of this section pursuant to § 63.1209(n), except that semivolatile metal feedrate limits apply to lead, cadmium, and selenium, combined, and low volatile metal feedrate limits apply to arsenic, beryllium, chromium, antimony, cobalt, manganese, and nickel, combined.

■ 21. Section 63.1220 is added to subpart EEE to read as follows:

§ 63.1220 What are the replacement standards for hazardous waste burning cement kilns?

(a) *Emission and hazardous waste feed limits for existing sources.* You must not discharge or cause combustion gases to be emitted into the atmosphere or feed hazardous waste that contain:

(1) For dioxins and furans, either:

(i) Emissions in excess of 0.20 ng TEQ/dscm corrected to 7 percent oxygen; or

(ii) Emissions in excess of 0.40 ng TEQ/dscm corrected to 7 percent oxygen provided that the combustion gas temperature at the inlet to the initial dry particulate matter control device is 400 °F or lower based on the average of the test run average temperatures;

(2) For mercury, both:

(i) An average as-fired concentration of mercury in all hazardous waste feedstreams in excess of 3.0 parts per million by weight; and

(ii) Emissions in excess of 120 μg/dscm, corrected to 7 percent oxygen; or

(iii) A hazardous waste feedrate corresponding to a maximum theoretical emission concentration (MTEC) in excess of 120 μg/dscm;

(3) For cadmium and lead, both:

(i) Emissions in excess of 7.6×10^{-4} lbs combined emissions of cadmium and lead attributable to the hazardous waste per million Btu heat input from the hazardous waste; and

(ii) Emissions in excess of 330 μg/dscm, combined emissions, corrected to 7 percent oxygen;

(4) For arsenic, beryllium, and chromium, both:

(i) Emissions in excess of 2.1×10^{-5} lbs combined emissions of arsenic, beryllium, and chromium attributable to the hazardous waste per million Btu heat input from the hazardous waste; and

(ii) Emissions in excess of 56 μg/dscm, combined emissions, corrected to 7 percent oxygen;

(5) *Carbon monoxide and hydrocarbons.* (i) For kilns equipped with a by-pass duct or midkiln gas sampling system, either:

(A) Carbon monoxide in the by-pass duct or mid-kiln gas sampling system in excess of 100 parts per million by volume, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis and corrected to 7 percent oxygen. If you elect to comply with this carbon monoxide standard rather than the hydrocarbon standard under paragraph (a)(5)(i)(B) of this section, you must also document that, during the destruction and removal efficiency (DRE) test runs or their equivalent as provided by § 63.1206(b)(7), hydrocarbons in the by-pass duct or mid-kiln gas sampling system do not exceed 10 parts per million by volume during those runs, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis, corrected to 7 percent oxygen, and reported as propane; or

(B) Hydrocarbons in the by-pass duct or midkiln gas sampling system in excess of 10 parts per million by volume, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis, corrected to 7 percent oxygen, and reported as propane;

(ii) For kilns not equipped with a by-pass duct or midkiln gas sampling system, either:

(A) Hydrocarbons in the main stack in excess of 20 parts per million by volume, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis, corrected to 7 percent oxygen, and reported as propane; or

(B) Carbon monoxide in the main stack in excess of 100 parts per million by volume, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis and corrected to 7 percent oxygen. If you elect to comply with this carbon monoxide standard rather than the hydrocarbon standard under paragraph (a)(5)(ii)(A) of this section, you also must document that, during the destruction and removal efficiency (DRE) test runs or their equivalent as provided by § 63.1206(b)(7), hydrocarbons in the main stack do not exceed 20 parts per million by volume during those runs, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis, corrected to 7 percent oxygen, and reported as propane.

(6) Hydrogen chloride and chlorine gas in excess of 120 parts per million by volume, combined emissions, expressed as a chloride ($Cl^{(-)}$) equivalent, dry basis, corrected to 7 percent oxygen; and

(7) For particulate matter, both:

(i) Emissions in excess of 0.028 gr/dscf corrected to 7 percent oxygen; and

(ii) Opacity greater than 20 percent, unless your source is equipped with a bag leak detection system under § 63.1206(c)(8) or a particulate matter detection system under § 63.1206(c)(9).

(b) *Emission and hazardous waste feed limits for new sources.* You must not discharge or cause combustion gases to be emitted into the atmosphere or feed hazardous waste that contain:

(1) For dioxins and furans, either:

(i) Emissions in excess of 0.20 ng TEQ/dscm corrected to 7 percent oxygen; or

(ii) Emissions in excess of 0.40 ng TEQ/dscm corrected to 7 percent oxygen provided that the combustion gas temperature at the inlet to the initial dry particulate matter control device is 400 °F or lower based on the average of the test run average temperatures;

(2) For mercury, both:

(i) An average as-fired concentration of mercury in all hazardous waste feedstreams in excess of 1.9 parts per million by weight; and

(ii) Emissions in excess of 120 µg/dscm, corrected to 7 percent oxygen; or

(iii) A hazardous waste feedrate corresponding to a maximum theoretical emission concentration (MTEC) in excess of 120 µg/dscm;

(3) For cadmium and lead, both:

(i) Emissions in excess of 6.2×10^{-5} lbs combined emissions of cadmium and lead attributable to the hazardous waste per million Btu heat input from the hazardous waste; and

(ii) Emissions in excess of 180 µg/dscm, combined emissions, corrected to 7 percent oxygen;

(4) For arsenic, beryllium, and chromium, both:

(i) Emissions in excess of 1.5×10^{-5} lbs combined emissions of arsenic, beryllium, and chromium attributable to the hazardous waste per million Btu heat input from the hazardous waste; and

(ii) Emissions in excess of 54 µg/dscm, combined emissions, corrected to 7 percent oxygen;

(5) *Carbon monoxide and hydrocarbons.* (i) For kilns equipped with a by-pass duct or midkiln gas sampling system, carbon monoxide and hydrocarbons emissions are limited in both the bypass duct or midkiln gas sampling system and the main stack as follows:

(A) Emissions in the by-pass or midkiln gas sampling system are limited to either:

(1) Carbon monoxide in excess of 100 parts per million by volume, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis and corrected to 7 percent oxygen. If you elect to comply with this carbon monoxide standard rather than the hydrocarbon standard under paragraph (b)(5)(i)(A)(2) of this section, you also must document that, during the destruction and removal efficiency (DRE) test runs or their equivalent as provided by § 63.1206(b)(7), hydrocarbons do not exceed 10 parts per million by volume during those runs, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis, corrected to 7 percent oxygen, and reported as propane; or

(2) Hydrocarbons in the by-pass duct or midkiln gas sampling system in excess of 10 parts per million by volume, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis, corrected to 7 percent oxygen, and reported as propane; and

(B) Hydrocarbons in the main stack are limited, if construction of the kiln commenced after April 19, 1996 at a plant site where a cement kiln (whether burning hazardous waste or not) did not previously exist, to 50 parts per million by volume, over a 30-day block average (monitored continuously with a continuous monitoring system), dry basis, corrected to 7 percent oxygen, and reported as propane.

(ii) For kilns not equipped with a by-pass duct or midkiln gas sampling system, hydrocarbons and carbon monoxide are limited in the main stack to either:

(A) Hydrocarbons not exceeding 20 parts per million by volume, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis, corrected to 7 percent oxygen, and reported as propane; or

(B)(1) Carbon monoxide not exceeding 100 parts per million by volume, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis, corrected to 7 percent oxygen; and

(2) Hydrocarbons not exceeding 20 parts per million by volume, over an hourly rolling average (monitored continuously with a continuous

monitoring system), dry basis, corrected to 7 percent oxygen, and reported as propane at any time during the destruction and removal efficiency (DRE) test runs or their equivalent as provided by § 63.1206(b)(7); and

(3) If construction of the kiln commenced after April 19, 1996 at a plant site where a cement kiln (whether burning hazardous waste or not) did not previously exist, hydrocarbons are limited to 50 parts per million by volume, over a 30-day block average (monitored continuously with a continuous monitoring system), dry basis, corrected to 7 percent oxygen, and reported as propane.

(6) Hydrogen chloride and chlorine gas in excess of 86 parts per million by volume, combined emissions, expressed as a chloride ($Cl^{(-)}$) equivalent, dry basis and corrected to 7 percent oxygen; and

(7) For particulate matter, both:

(i) Emissions in excess of 0.0023 gr/dscf corrected to 7 percent oxygen; and

(ii) Opacity greater than 20 percent, unless your source is equipped with a bag leak detection system under § 63.1206(c)(8) or a particulate matter detection system under § 63.1206(c)(9).

(c) *Destruction and removal efficiency (DRE) standard.* (1) *99.99% DRE.* Except as provided in paragraph (c)(2) of this section, you must achieve a destruction and removal efficiency (DRE) of 99.99% for each principle organic hazardous constituent (POHC) designated under paragraph (c)(3) of this section. You must calculate DRE for each POHC from the following equation:

$$DRE = [1 - (W_{out}/W_{in})] \times 100\%$$

Where:

W_{in} = mass feedrate of one POHC in a waste feedstream; and

W_{out} = mass emission rate of the same POHC present in exhaust emissions prior to release to the atmosphere.

(2) *99.9999% DRE.* If you burn the dioxin-listed hazardous wastes F020, F021, F022, F023, F026, or F027 (see § 261.31 of this chapter), you must achieve a DRE of 99.9999% for each POHC that you designate under paragraph (c)(3) of this section. You must demonstrate this DRE performance on POHCs that are more difficult to incinerate than tetra-, penta-, and hexachlorodibenzo-*p*-dioxins and dibenzofurans. You must use the equation in paragraph (c)(1) of this section to calculate DRE for each POHC. In addition, you must notify the Administrator of your intent to incinerate hazardous wastes F020, F021, F022, F023, F026, or F027.

(3) *Principal organic hazardous constituent (POHC).* (i) You must treat each POHC in the waste feed that you specify under paragraph (c)(3)(ii) of this section to the extent required by paragraphs (c)(1) and (c)(2) of this section.

(ii) You must specify one or more POHCs that are representative of the most difficult to destroy organic compounds in your hazardous waste feedstream. You must base this specification on the degree of difficulty of incineration of the organic constituents in the hazardous waste and on their concentration or mass in the hazardous waste feed, considering the results of hazardous waste analyses or other data and information.

(d) *Cement kilns with in-line kiln raw mills.* (1) *General.* (i) You must conduct performance testing when the raw mill is on-line and when the mill is off-line to demonstrate compliance with the emission standards, and you must establish separate operating parameter limits under § 63.1209 for each mode of operation, except as provided by paragraphs (d)(1)(iv) and (d)(1)(v) of this section.

(ii) You must document in the operating record each time you change from one mode of operation to the alternate mode and begin complying with the operating parameter limits for that alternate mode of operation.

(iii) You must calculate rolling averages for operating parameter limits as provided by § 63.1209(q)(2).

(iv) If your in-line kiln raw mill has dual stacks, you may assume that the dioxin/furan emission levels in the by-pass stack and the operating parameter limits determined during performance testing of the by-pass stack when the raw mill is off-line are the same as when the mill is on-line.

(v) In lieu of conducting a performance test to demonstrate compliance with the dioxin/furan emission standards for the mode of operation when the raw mill is on-line, you may specify in the performance test workplan and Notification of Compliance the same operating parameter limits required under § 63.1209(k) for the mode of operation when the raw mill is on-line as you establish during performance testing for the mode of operation when the raw mill is off-line.

(2) *Emissions averaging.* You may comply with the mercury, semivolatile metal, low volatile metal, and hydrogen chloride/chlorine gas emission standards on a time-weighted average basis under the following procedures:

(i) *Averaging methodology.* You must calculate the time-weighted average emission concentration with the following equation:

$$C_{total} = \{C_{mill\text{-}off} \times (T_{mill\text{-}off}/(T_{mill\text{-}off} + T_{mill\text{-}on}))\} + \{C_{mill\text{-}on} \times (T_{mill\text{-}on}/(T_{mill\text{-}off} + T_{mill\text{-}on}))\}$$

Where:

C_{total} = time-weighted average concentration of a regulated constituent considering both raw mill on time and off time;

$C_{mill\text{-}off}$ = average performance test concentration of regulated constituent with the raw mill off-line;

$C_{mill\text{-}on}$ = average performance test concentration of regulated constituent with the raw mill on-line;

$T_{mill\text{-}off}$ = time when kiln gases are not routed through the raw mill; and

$T_{mill\text{-}on}$ = time when kiln gases are routed through the raw mill.

(ii) *Compliance.* (A) If you use this emission averaging provision, you must document in the operating record compliance with the emission standards on an annual basis by using the equation provided by paragraph (d)(2) of this section.

(B) Compliance is based on one-year block averages beginning on the day you submit the initial notification of compliance.

(iii) *Notification.* (A) If you elect to document compliance with one or more emission standards using this emission averaging provision, you must notify the Administrator in the initial comprehensive performance test plan submitted under § 63.1207(e).

(B) You must include historical raw mill operation data in the performance test plan to estimate future raw mill down-time and document in the performance test plan that estimated emissions and estimated raw mill down-time will not result in an exceedance of an emission standard on an annual basis.

(C) You must document in the notification of compliance submitted under § 63.1207(j) that an emission standard will not be exceeded based on the documented emissions from the performance test and predicted raw mill down-time.

(e) *Preheater or preheater/precalciner kilns with dual stacks.* (1) *General.* You must conduct performance testing on each stack to demonstrate compliance with the emission standards, and you must establish operating parameter limits under § 63.1209 for each stack, except as provided by paragraph (d)(1)(iv) of this section for dioxin/furan emissions testing and operating parameter limits for the by-pass stack of in-line raw mills.

(2) *Emissions averaging.* You may comply with the mercury, semivolatile metal, low volatile metal, and hydrogen

chloride/chlorine gas emission standards specified in this section on a gas flowrate-weighted average basis under the following procedures:

(i) *Averaging methodology.* You must calculate the gas flowrate-weighted average emission concentration using the following equation:

$$C_{tot} = \{C_{main} \times (Q_{main} / (Q_{main} + Q_{bypass}))\} + \{C_{bypass} \times (Q_{bypass} / (Q_{main} + Q_{bypass}))\}$$

Where:

C_{tot} = gas flowrate-weighted average concentration of the regulated constituent;

C_{main} = average performance test concentration demonstrated in the main stack;

C_{bypass} = average performance test concentration demonstrated in the bypass stack;

Q_{main} = volumetric flowrate of main stack effluent gas; and

Q_{bypass} = volumetric flowrate of bypass effluent gas.

(ii) *Compliance.* (A) You must demonstrate compliance with the emission standard(s) using the emission concentrations determined from the performance tests and the equation provided by paragraph (e)(1) of this section; and

(B) You must develop operating parameter limits for bypass stack and main stack flowrates that ensure the emission concentrations calculated with the equation in paragraph (e)(1) of this section do not exceed the emission standards on a 12-hour rolling average basis. You must include these flowrate limits in the Notification of Compliance.

(iii) *Notification.* If you elect to document compliance under this emissions averaging provision, you must:

(A) Notify the Administrator in the initial comprehensive performance test plan submitted under § 63.1207(e). The performance test plan must include, at a minimum, information describing the flowrate limits established under paragraph (e)(2)(ii)(B) of this section; and

(B) Document in the Notification of Compliance submitted under § 63.1207(j) the demonstrated gas flowrate-weighted average emissions that you calculate with the equation provided by paragraph (e)(2) of this section.

(f) *Significant figures.* The emission limits provided by paragraphs (a) and (b) of this section are presented with two significant figures. Although you must perform intermediate calculations using at least three significant figures, you may round the resultant emission levels to two significant figures to document compliance.

(g) [Reserved].

(h) When you comply with the particulate matter requirements of paragraphs (a)(7) or (b)(7) of this section, you are exempt from the New Source Performance Standard for particulate matter and opacity under § 60.60 of this chapter.

■ 22. Section 63.1221 is added to subpart EEE to read as follows:

§ 63.1221 What are the replacement standards for hazardous waste burning lightweight aggregate kilns?

(a) *Emission and hazardous waste feed limits for existing sources.* You must not discharge or cause combustion gases to be emitted into the atmosphere or feed hazardous waste that contain:

(1) For dioxins and furans, either:

(i) Emissions in excess of 0.20 ng TEQ/dscm corrected to 7 percent oxygen; or

(ii) Rapid quench of the combustion gas temperature at the exit of the (last) combustion chamber (or exit of any waste heat recovery system that immediately follows the last combustion chamber) to 400°F or lower based on the average of the test run average temperatures. You must also notify in writing the RCRA authority that you are complying with this option;

(2) For mercury, either:

(i) Emissions in excess of 120 µg/dscm, corrected to 7 percent oxygen; or

(ii) A hazardous waste feedrate corresponding to a maximum theoretical emission concentration (MTEC) in excess of 120 µg/dscm;

(3) For cadmium and lead, both:

(i) Emissions in excess of 3.0×10^{-4} lbs combined emissions of cadmium and lead attributable to the hazardous waste per million Btu heat input from the hazardous waste; and

(ii) Emissions in excess of 250 µg/dscm, combined emissions, corrected to 7 percent oxygen;

(4) For arsenic, beryllium, and chromium, both:

(i) In excess of 9.5×10^{-5} lbs combined emissions of arsenic, beryllium, and chromium attributable to the hazardous waste per million Btu heat input from the hazardous waste;

(ii) Emissions in excess of 110 µg/dscm, combined emissions, corrected to 7 percent oxygen;

(5) *Carbon monoxide and hydrocarbons.* (i) Carbon monoxide in excess of 100 parts per million by volume, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis and corrected to 7 percent oxygen. If you elect to comply with this carbon monoxide standard rather than the hydrocarbon standard under paragraph (a)(5)(ii) of this section, you also must document that, during the destruction and removal efficiency (DRE) test runs or their equivalent as provided by § 63.1206(b)(7), hydrocarbons do not exceed 20 parts per million by volume during those runs, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis, corrected to 7 percent oxygen, and reported as propane; or

(ii) Hydrocarbons in excess of 20 parts per million by volume, over an hourly rolling average, dry basis, corrected to 7 percent oxygen, and reported as propane;

(6) Hydrogen chloride and chlorine gas in excess of 600 parts per million by volume, combined emissions, expressed as a chloride ($Cl^{(-)}$) equivalent, dry basis and corrected to 7 percent oxygen; and

(7) Particulate matter emissions in excess of 0.025 gr/dscf, corrected to 7 percent oxygen.

(b) *Emission and hazardous waste feed limits for new sources.* You must not discharge or cause combustion gases to be emitted into the atmosphere or feed hazardous waste that contain:

(1) For dioxins and furans, either:

(i) Emissions in excess of 0.20 ng TEQ/dscm corrected to 7 percent oxygen; or

(ii) Rapid quench of the combustion gas temperature at the exit of the (last) combustion chamber (or exit of any waste heat recovery system that immediately follows the last combustion chamber) to 400°F or lower based on the average of the test run average temperatures. You must also notify in writing the RCRA authority that you are complying with this option;

(2) For mercury, either:

(i) Emissions in excess of 120 µg/dscm, corrected to 7 percent oxygen; or

(ii) A hazardous waste feedrate corresponding to a maximum theoretical emission concentration (MTEC) in excess of 120 µg/dscm;

(3) For cadmium and lead, both:

(i) Emissions in excess of 3.7×10^{-5} lbs combined emissions of cadmium and lead attributable to the hazardous waste per million Btu heat input from the hazardous waste; and

(ii) Emissions in excess of 43 µg/dscm, combined emissions, corrected to 7 percent oxygen;

(4) For arsenic, beryllium, and chromium, both:

(i) In excess of 3.3×10^{-5} lbs combined emissions of arsenic, beryllium, and chromium attributable to the hazardous waste per million Btu heat input from the hazardous waste;

(ii) Emissions in excess of 110 μg/dscm, combined emissions, corrected to 7 percent oxygen;

(5) *Carbon monoxide and hydrocarbons.* (i) Carbon monoxide in excess of 100 parts per million by volume, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis and corrected to 7 percent oxygen. If you elect to comply with this carbon monoxide standard rather than the hydrocarbon standard under paragraph (b)(5)(ii) of this section, you also must document that, during the destruction and removal efficiency (DRE) test runs or their equivalent as provided by § 63.1206(b)(7), hydrocarbons do not exceed 20 parts per million by volume during those runs, over an hourly rolling average (monitored continuously with a continuous emissions monitoring system), dry basis, corrected to 7 percent oxygen, and reported as propane; or

(ii) Hydrocarbons in excess of 20 parts per million by volume, over an hourly rolling average, dry basis, corrected to 7 percent oxygen, and reported as propane;

(6) Hydrogen chloride and chlorine gas in excess of 600 parts per million by volume, combined emissions, expressed as a chloride ($Cl^{(-)}$) equivalent, dry basis and corrected to 7 percent oxygen; and

(7) Particulate matter emissions in excess of 0.0098 gr/dscf corrected to 7 percent oxygen.

(c) *Destruction and removal efficiency (DRE) standard.* (1) *99.99% DRE.* Except as provided in paragraph (c)(2) of this section, you must achieve a destruction and removal efficiency (DRE) of 99.99% for each principal organic hazardous constituent (POHC) designated under paragraph (c)(3) of this section. You must calculate DRE for each POHC from the following equation:

$$DRE = [1 - (W_{out} / Win)] \times 100\%$$

Where:

W_{in} = mass feedrate of one POHC in a waste feedstream; and

W_{out} = mass emission rate of the same POHC present in exhaust emissions prior to release to the atmosphere.

(2) *99.9999% DRE.* If you burn the dioxin-listed hazardous wastes F020, F021, F022, F023, F026, or F027 (see § 261.31 of this chapter), you must achieve a destruction and removal efficiency (DRE) of 99.9999% for each POHC that you designate under paragraph (c)(3) of this section. You must demonstrate this DRE performance on POHCs that are more difficult to incinerate than tetra-, penta-, and hexachlorodibenzo-dioxins and dibenzofurans. You must use the equation in paragraph (c)(1) of this section to calculate DRE for each POHC. In addition, you must notify the Administrator of your intent to burn hazardous wastes F020, F021, F022, F023, F026, or F027.

(3) *Principal organic hazardous constituents (POHCs).* (i) You must treat each POHC in the waste feed that you specify under paragraph (c)(3)(ii) of this section to the extent required by paragraphs (c)(1) and (c)(2) of this section.

(ii) You must specify one or more POHCs that are representative of the most difficult to destroy organic compounds in your hazardous waste feedstream. You must base this specification on the degree of difficulty of incineration of the organic constituents in the hazardous waste and on their concentration or mass in the hazardous waste feed, considering the results of hazardous waste analyses or other data and information.

(d) *Significant figures.* The emission limits provided by paragraphs (a) and (b) of this section are presented with two significant figures. Although you must perform intermediate calculations using at least three significant figures, you may round the resultant emission levels to two significant figures to document compliance.

PART 260—HAZARDOUS WASTE MANAGEMENT SYSTEM: GENERAL

■ 1. The authority citation for part 260 continues to read as follows:

Authority: 42 U.S.C. 6905, 6912(a), 6921–6927, 6930, 6934, 6935, 6937, 6938, 6939, and 6974.

■ 2. Section 260.11 is amended by

■ a. Revising the first sentence in paragraph (a).

■ b. Revising paragraph (c)(1).

The revisions and additions read as follows:

§ 260.11 References.

(a) When used in parts 260 through 268 of this chapter, the following publications are incorporated by reference. * * *

* * * * *

(c) * * *

(1) "APTI Course 415: Control of Gaseous Emissions," EPA Publication EPA–450/2–81–005, December 1981, IBR approved for §§ 264.1035 and 265.1035.

* * * * *

PART 264—STANDARDS FOR OWNERS AND OPERATORS OF HAZARDOUS WASTE TREATMENT, STORAGE, AND DISPOSAL FACILITIES

■ 1. The authority citation for part 264 continues to read as follows:

Authority: 42 U.S.C. 6905, 6912(a), 6924, 6925, 6927, 6928(h), and 6974.

■ 2. Section 264.340 is amended by revising the first sentence of paragraph (b)(1) and adding paragraph (b)(5) to read as follows:

§ 264.340 Applicability.

* * * * *

(b) * * * (1) Except as provided by paragraphs (b)(2) through (b)(5) of this section, the standards of this part do not apply to a new hazardous waste incineration unit that becomes subject to RCRA permit requirements after October 12, 2005; or no longer apply when an owner or operator of an existing hazardous waste incineration unit demonstrates compliance with the maximum achievable control technology (MACT) requirements of part 63, subpart EEE, of this chapter by conducting a comprehensive performance test and submitting to the Administrator a Notification of Compliance under §§ 63.1207(j) and 63.1210(d) of this chapter documenting compliance with the requirements of part 63, subpart EEE, of this chapter.

* * *

* * * * *

(5) The particulate matter standard of § 264.343(c) remains in effect for incinerators that elect to comply with the alternative to the particulate matter standard of §§ 63.1206(b)(14) and 63.1219(e) of this chapter.

* * * * *

PART 265—INTERIM STATUS STANDARDS FOR OWNERS AND OPERATORS OF HAZARDOUS WASTE TREATMENT, STORAGE, AND DISPOSAL FACILITIES

■ 1. The authority citation for part 265 continues to read as follows:

Authority: 42 U.S.C. 6905, 6906, 6912, 6922, 6923, 6924, 6925, 6935, 6936, and 6937.

■ 2. Section 265.340 is amended by revising paragraph (b)(1) to read as follows:

§ 265.340 Applicability.

* * * * *

(b) * * * (1) Except as provided by paragraphs (b)(2) and (b)(3) of this section, the standards of this part no longer apply when an owner or operator

demonstrates compliance with the maximum achievable control technology (MACT) requirements of part 63, subpart EEE, of this chapter by conducting a comprehensive performance test and submitting to the Administrator a Notification of Compliance under §§ 63.1207(j) and 63.1210(d) of this chapter documenting compliance with the requirements of part 63, subpart EEE, of this chapter.

* * * * *

PART 266—STANDARDS FOR THE MANAGEMENT OF SPECIFIC HAZARDOUS WASTES AND SPECIFIC TYPES OF HAZARDOUS WASTE MANAGEMENT FACILITIES

■ 1. The authority citation for part 266 continues to read as follows:

Authority: 42 U.S.C. 1006, 2002(a), 3001–3009, 3014, 6905, 6906, 6912, 6921, 6922, 6924–6927, 6934, and 6937.

■ 2. Section 266.100 is amended by revising the first sentence of paragraph (b)(1) and adding paragraphs (b)(3) and (b)(4) to read as follows:

§ 266.100 Applicability.

* * * * *

(b) * * * (1) Except as provided by paragraphs (b)(2), (b)(3), and (b)(4) of this section, the standards of this part do not apply to a new hazardous waste boiler or industrial furnace unit that becomes subject to RCRA permit requirements after October 12, 2005; or no longer apply when an owner or operator of an existing hazardous waste boiler or industrial furnace unit demonstrates compliance with the maximum achievable control technology (MACT) requirements of part 63, subpart EEE, of this chapter by conducting a comprehensive performance test and submitting to the Administrator a Notification of Compliance under §§ 63.1207(j) and 63.1210(d) of this chapter documenting compliance with the requirements of part 63, subpart EEE, of this chapter.

* * *

* * * * *

(3) If you own or operate a boiler or hydrochloric acid production furnace that is an area source under § 63.2 of this chapter and you elect not to comply with the emission standards under §§ 63.1216, 63.1217, and 63.1218 of this chapter for particulate matter, semivolatile and low volatile metals, and total chlorine, you also remain subject to:

(i) Section 266.105—Standards to control particulate matter;

(ii) Section 266.106—Standards to control metals emissions, except for mercury; and

(ii) Section 266.107—Standards to control hydrogen chloride and chlorine gas.

(4) The particulate matter standard of § 266.105 remains in effect for boilers that elect to comply with the alternative to the particulate matter standard under §§ 63.1216(e) and 63.1217(e) of this chapter.

* * * * *

PART 270—EPA ADMINISTERED PERMIT PROGRAMS: THE HAZARDOUS WASTE PERMIT PROGRAM

■ 1. The authority citation for part 270 continues to read as follows:

Authority: 42 U.S.C. 6905, 6912, 6924, 6925, 6927, 6939, and 6974.

■ 2. Section 270.6 is revised to read as follows:

§ 270.6 References.

(a) When used in part 270 of this chapter, the following publications are incorporated by reference. These incorporations by reference were approved by the Director of the Federal Register pursuant to 5 U.S.C. 552(a) and 1 CFR part 51. These materials are incorporated as they exist on the date of approval and a notice of any change in these materials will be published in the Federal Register. Copies may be inspected at the Library, U.S. Environmental Protection Agency, 1200 Pennsylvania Ave., NW., (3403T), Washington, DC 20460, *libraryhq@epa.gov*; or at the National Archives and Records Administration (NARA). For information on the availability of this material at NARA, call 202–741–6030, or go to: *http://www.archives.gov/federal_register/code_of_federal_regulations/ibr_locations.html*.

(b) The following materials are available for purchase from the National Technical Information Service (NTIS), 5285 Port Royal Road, Springfield, VA 22161, (703) 605–6000 or (800) 553–6847; or for purchase from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402, (202) 512–1800:

(1) "APTI Course 415: Control of Gaseous Emissions," EPA Publication EPA–450/2–81–005, December 1981, IBR approved for §§ 270.24 and 270.25.

(2) [Reserved].

■ 3. Section 270.10 is amended by adding paragraph (l) to read as follows:

§ 270.10 General application requirements.

* * * * *

(l) If the Director concludes, based on one or more of the factors listed in paragraph (l)(1) of this section that compliance with the standards of 40 CFR part 63, subpart EEE alone may not be protective of human health or the environment, the Director shall require the additional information or assessment(s) necessary to determine whether additional controls are necessary to ensure protection of human health and the environment. This includes information necessary to evaluate the potential risk to human health and/or the environment resulting from both direct and indirect exposure pathways. The Director may also require a permittee or applicant to provide information necessary to determine whether such an assessment(s) should be required.

(1) The Director shall base the evaluation of whether compliance with the standards of 40 CFR part 63, subpart EEE alone is protective of human health or the environment on factors relevant to the potential risk from a hazardous waste combustion unit, including, as appropriate, any of the following factors:

(i) Particular site-specific considerations such as proximity to receptors (such as schools, hospitals, nursing homes, day care centers, parks, community activity centers, or other potentially sensitive receptors), unique dispersion patterns, etc.;

(ii) Identities and quantities of emissions of persistent, bioaccumulative or toxic pollutants considering enforceable controls in place to limit those pollutants;

(iii) Identities and quantities of nondioxin products of incomplete combustion most likely to be emitted and to pose significant risk based on known toxicities (confirmation of which should be made through emissions testing);

(iv) Identities and quantities of other off-site sources of pollutants in proximity of the facility that significantly influence interpretation of a facility-specific risk assessment;

(v) Presence of significant ecological considerations, such as the proximity of a particularly sensitive ecological area;

(vi) Volume and types of wastes, for example wastes containing highly toxic constituents;

(vii) Other on-site sources of hazardous air pollutants that significantly influence interpretation of the risk posed by the operation of the source in question;

(viii) Adequacy of any previously conducted risk assessment, given any subsequent changes in conditions likely to affect risk; and

(ix) Such other factors as may be appropriate.

(2) [Reserved]

■ 4. Section 270.19 is amended by revising paragraph (e) to reads as follows:

§ 270.19 Specific part B information requirements for incinerators.

* * * * *

(e) When an owner or operator of a hazardous waste incineration unit becomes subject to RCRA permit requirements after October 12, 2005, or when an owner or operator of an existing hazardous waste incineration unit demonstrates compliance with the air emission standards and limitations in part 63, subpart EEE, of this chapter (*i.e.*, by conducting a comprehensive performance test and submitting a Notification of Compliance under §§ 63.1207(j) and 63.1210(d) of this chapter documenting compliance with all applicable requirements of part 63, subpart EEE, of this chapter), the requirements of this section do not apply, except those provisions the Director determines are necessary to ensure compliance with §§ 264.345(a) and 264.345(c) of this chapter if you elect to comply with § 270.235(a)(1)(i) to minimize emissions of toxic compounds from startup, shutdown, and malfunction events. Nevertheless, the Director may apply the provisions of this section, on a case-by-case basis, for purposes of information collection in accordance with §§ 270.10(k), 270.10(l), 270.32(b)(2), and 270.32(b)(3).

■ 5. Section 270.22 is amended by revising the introductory text to read as follows:

§ 270.22 Specific part B information requirements for boilers and industrial furnaces burning hazardous waste.

When an owner or operator of a cement kiln, lightweight aggregate kiln, solid fuel boiler, liquid fuel boiler, or hydrochloric acid production furnace becomes subject to RCRA permit requirements after October 12, 2005, or when an owner or operator of an existing cement kiln, lightweight aggregate kiln, solid fuel boiler, liquid fuel boiler, or hydrochloric acid production furnace demonstrates compliance with the air emission standards and limitations in part 63, subpart EEE, of this chapter (*i.e.*, by conducting a comprehensive performance test and submitting a Notification of Compliance under §§ 63.1207(j) and 63.1210(d) of this chapter documenting compliance with all applicable requirements of part 63, subpart EEE, of this chapter), the requirements of this section do not apply. The requirements of this section do apply, however, if the Director determines certain provisions are necessary to ensure compliance with §§ 266.102(e)(1) and 266.102(e)(2)(iii) of this chapter if you elect to comply with § 270.235(a)(1)(i) to minimize emissions of toxic compounds from startup, shutdown, and malfunction events; or if you are an area source and elect to comply with the §§ 266.105, 266.106, and 266.107 standards and associated requirements for particulate matter, hydrogen chloride and chlorine gas, and non-mercury metals; or the Director determines certain provisions apply, on a case-by-case basis, for purposes of information collection in accordance with §§ 270.10(k), 270.10(l), 270.32(b)(2), and 270.32(b)(3).

* * * * *

■ 6. Section 270.24 is amended by revising paragraph (d)(3) to read as follows:

§ 270.24 Specific part B information requirements for process vents.

* * * * *

(d) * * *

(3) A design analysis, specifications, drawings, schematics, and piping and instrumentation diagrams based on the appropriate sections of "APTI Course 415: Control of Gaseous Emissions" (incorporated by reference as specified in § 270.6) or other engineering texts acceptable to the Regional Administrator that present basic control device information. The design analysis shall address the vent stream characteristics and control device operation parameters as specified in § 264.1035(b)(4)(iii).

* * * * *

■ 7. Section 270.25 is amended by revising paragraph (e)(3) to read as follows:

§ 270.25 Specific part B information requirements for equipment.

* * * * *

(e) * * *

(3) A design analysis, specifications, drawings, schematics, and piping and instrumentation diagrams based on the appropriate sections of "APTI Course 415: Control of Gaseous Emissions" (incorporated by reference as specified in § 270.6) or other engineering texts acceptable to the Regional Administrator that present basic control device information. The design analysis shall address the vent stream characteristics and control device operation parameters as specified in § 264.1035(b)(4)(iii).

* * * * *

■ 8. Section 270.32 is amended by adding paragraph (b)(3) to read as follows:

§ 270.32 Establishing permit conditions.

* * * * *

(b) * * *

(3) If, as the result of an assessment(s) or other information, the Administrator or Director determines that conditions are necessary in addition to those required under 40 CFR parts 63, subpart EEE, 264 or 266 to ensure protection of human health and the environment, he shall include those terms and conditions in a RCRA permit for a hazardous waste combustion unit.

* * * * *

■ 9. Section 270.42 is amended by:
■ a. Revising paragraph (j)(1).
■ b. Redesignating paragraph (j)(2) as (j)(3).
■ c. Adding new paragraph (j)(2).
■ d. Adding new paragraph (k); and
■ e. Adding a new entry 10 in numerical order in the table under section L of Appendix I.

The revisions and additions read as follows:

§ 270.42 Permit modification at the request of the permittee.

* * * * *

(j) * * *

(1) Facility owners or operators must have complied with the Notification of Intent to Comply (NIC) requirements of 40 CFR 63.1210 that were in effect prior to October 11, 2000, (See 40 CFR part 63 §§ 63.1200–63.1499 revised as of July 1, 2000) in order to request a permit modification under this section for the purpose of technology changes needed to meet the standards under 40 CFR 63.1203, 63.1204, and 63.1205.

(2) Facility owners or operators must comply with the Notification of Intent to Comply (NIC) requirements of 40 CFR 63.1210(b) and 63.1212(a) before a permit modification can be requested under this section for the purpose of technology changes needed to meet the 40 CFR 63.1215, 63.1216, 63.1217, 63.1218, 63.1219, 63.1220, and 63.1221 standards promulgated on October 12, 2005.

* * * * *

(k) *Waiver of RCRA permit conditions in support of transition to the part 63 MACT standards.* (1) You may request to have specific RCRA operating and emissions limits waived by submitting a Class 1 permit modification request under Appendix I of this section, section L(10). You must:

(i) Identify the specific RCRA permit operating and emissions limits which you are requesting to waive;

(ii) Provide an explanation of why the changes are necessary in order to minimize or eliminate conflicts between the RCRA permit and MACT compliance; and

(iii) Discuss how the revised provisions will be sufficiently protective.

(iv) The Director shall approve or deny the request within 30 days of receipt of the request. The Director may, as his or her discretion, extend this 30 day deadline one time for up to 30 days by notifying the facility owner or operator.

(2) To request this modification in conjunction with MACT performance testing where permit limits may only be waived during actual test events and pretesting, as defined under 40 CFR 63.1207(h)(2)(i) and (ii), for an aggregate time not to exceed 720 hours of operation (renewable at the discretion of the Administrator) you must:

(i) Submit your modification request to the Director at the same time you submit your test plans to the Administrator; and

(ii) The Director may elect to approve or deny the request continent upon approval of the test plans.

* * * * *

Appendix I to § 270.42—Classification of Permit Modification

Modifications	Class
* * * * * * *	
L * * *	[1] 1
10. Changes to RCRA permit provisions needed to support transition to 40 CFR part 63 (Subpart EEE—National Emission Standards for Hazardous Air Pollutants From Hazardous Waste Combustors), provided the procedures of § 270.42(k) are followed..	
* * * * * * *	

[1] Class 1 modifications requiring prior Agency approval.

* * * * *

■ 10. Section 270.62 is amended by revising the introductory text to read as follows:

§ 270.62 Hazardous waste incinerator permits.

When an owner or operator of a hazardous waste incineration unit becomes subject to RCRA permit requirements after October 12, 2005, or when an owner or operator of an existing hazardous waste incineration unit demonstrates compliance with the air emission standards and limitations in part 63, subpart EEE, of this chapter (*i.e.*, by conducting a comprehensive performance test and submitting a Notification of Compliance under §§ 63.1207(j) and 63.1210(d) of this chapter documenting compliance with all applicable requirements of part 63, subpart EEE, of this chapter), the requirements of this section do not apply, except those provisions the Director determines are necessary to ensure compliance with §§ 264.345(a) and 264.345(c) of this chapter if you elect to comply with § 270.235(a)(1)(i) to minimize emissions of toxic compounds from startup, shutdown, and malfunction events. Nevertheless, the Director may apply the provisions of this section, on a case-by-case basis, for purposes of information collection in accordance with §§ 270.10(k), 270.10(l), 270.32(b)(2), and 270.32(b)(3).

* * * * *

■ 11. Section 270.66 is amended by revising the introductory text to read as follows:

§ 270.66 Permits for boilers and industrial furnaces burning hazardous waste.

When an owner or operator of a cement kiln, lightweight aggregate kiln, solid fuel boiler, liquid fuel boiler, or hydrochloric acid production furnace becomes subject to RCRA permit requirements after October 12, 2005 or when an owner or operator of an existing cement kiln, lightweight aggregate kiln, solid fuel boiler, liquid fuel boiler, or hydrochloric acid production furnace demonstrates compliance with the air emission standards and limitations in part 63, subpart EEE, of this chapter (*i.e.*, by conducting a comprehensive performance test and submitting a Notification of Compliance under §§ 63.1207(j) and 63.1210(d) of this chapter documenting compliance with all applicable requirements of part 63, subpart EEE, of this chapter), the requirements of this section do not apply. The requirements of this section do apply, however, if the Director determines certain provisions are necessary to ensure compliance with §§ 266.102(e)(1) and 266.102(e)(2)(iii) of this chapter if you elect to comply with § 270.235(a)(1)(i) to minimize emissions of toxic compounds from startup, shutdown, and malfunction events; or if you are an area source and elect to comply with the §§ 266.105, 266.106, and 266.107 standards and associated requirements for particulate matter, hydrogen chloride and chlorine gas, and non-mercury metals; or the Director determines certain provisions apply, on a case-by-case basis, for purposes of information collection in accordance with §§ 270.10(k), 270.10(l), 270.32(b)(2), and 270.32(b)(3).

* * * * *

■ 12. Section 270.235 is amended by:

■ a. Revising the section heading and paragraphs (a)(1) introductory text and (a)(2) introductory text.

■ b. Revising paragraphs (b)(1) introductory text and (b)(2).

■ c. Adding new paragraph (c).

The revisions read as follows:

* * * * *

§ 270.235 Options for incinerators, cement kilns, lightweight aggregate kilns, solid fuel boilers, liquid fuel boilers and hydrochloric acid production furnaces to minimize emissions from startup, shutdown, and malfunction events.

(a) * * * (1) *Revisions to permit conditions after documenting compliance with MACT.* The owner or operator of a RCRA-permitted incinerator, cement kiln, lightweight aggregate kiln, solid fuel boiler, liquid fuel boiler, or hydrochloric acid production furnace may request that the Director address permit conditions that minimize emissions from startup, shutdown, and malfunction events under any of the following options when requesting removal of permit conditions that are no longer applicable according to §§ 264.340(b) and 266.100(b) of this chapter:

* * * * *

(2) *Addressing permit conditions upon permit reissuance.* The owner or operator of an incinerator, cement kiln, lightweight aggregate kiln, solid fuel boiler, liquid fuel boiler, or hydrochloric acid production furnace that has conducted a comprehensive performance test and submitted to the Administrator a Notification of Compliance documenting compliance with the standards of part 63, subpart EEE, of this chapter may request in the application to reissue the permit for the combustion unit that the Director control emissions from startup,

shutdown, and malfunction events under any of the following options:

* * * * *

(b) * * * (1) *Interim status operations.* In compliance with §§ 265.340 and 266.100(b), the owner or operator of an incinerator, cement kiln, lightweight aggregate kiln, solid fuel boiler, liquid fuel boiler, or hydrochloric acid production furnace that is operating under the interim status standards of part 265 or 266 of this chapter may control emissions of toxic compounds during startup, shutdown, and malfunction events under either of the following options after conducting a comprehensive performance test and submitting to the Administrator a Notification of Compliance documenting compliance with the standards of part 63, subpart EEE, of this chapter.

* * * * *

(2) *Operations under a subsequent RCRA permit.* When an owner or operator of an incinerator, cement kiln, lightweight aggregate kiln, solid fuel boiler, liquid fuel boiler, or hydrochloric acid production furnace that is operating under the interim status standards of parts 265 or 266 of this chapter submits a RCRA permit application, the owner or operator may request that the Director control emissions from startup, shutdown, and malfunction events under any of the options provided by paragraphs (a)(2)(i), (a)(2)(ii), or (a)(2)(iii) of this section.

(c) *New units.* Hazardous waste incinerator, cement kiln, lightweight aggregate kiln, solid fuel boiler, liquid fuel boiler, or hydrochloric acid production furnace units that become subject to RCRA permit requirements after October 12, 2005 must control emissions of toxic compounds during startup, shutdown, and malfunction events under either of the following options:

(1) Comply with the requirements specified in § 63.1206(c)(2) of this chapter; or

(2) Request to include in the RCRA permit, conditions that ensure emissions of toxic compounds are minimized from startup, shutdown, and malfunction events, including releases from emergency safety vents, based on review of information including the source's startup, shutdown, and malfunction plan and design. The director will specify that these permit conditions apply only when the facility is operating under its startup, shutdown, and malfunction plan.

PART 271—REQUIREMENTS FOR AUTHORIZATION OF STATE HAZARDOUS WASTE PROGRAMS

■ 1. The authority citation for part 271 continues to read as follows:

Authority: 42 U.S.C. 6905, 6912(a), and 6926.

■ 2. Section 271.1(j) is amended by adding the following entries to Table 1 in chronological order by date of publication in the Federal Register, to read as follows:

§ 271.1 Purpose and scope.

* * * * *

(j) * * *

TABLE 1.—REGULATIONS IMPLEMENTING THE HAZARDOUS AND SOLID WASTE AMENDMENTS OF 1984

Promulgation date	Title of Reglation	Federal Register reference	Effective date
*	*	*	*
Oct. 12, 2005	Standards for Hazardous Air Pollutants for Hazardous Waste Combustors.	[Insert FR page numbers]	Oct. 12, 2005.

[FR Doc. 05–18824 Filed 10–11–05; 8:45 am]

BILLING CODE 6560–50–P

Federal Register

Tuesday,
April 4, 2006

Part II

Environmental Protection Agency

40 CFR Parts 260, 261 et al.
Resource Conservation and Recovery Act Burden Reduction Initiative; Final Rule

ENVIRONMENTAL PROTECTION AGENCY

40 CFR Parts 260, 261, 264, 265, 266, 268, 270, and 271

[RCRA–2001–0039; FRL–8047–3]

RIN 2050–AE50

Resource Conservation and Recovery Act Burden Reduction Initiative

AGENCY: Environmental Protection Agency.

ACTION: Final rule.

SUMMARY: The Environmental Protection Agency (EPA), in accordance with the goals of the Paperwork Reduction Act (PRA), is promulgating changes to the regulatory requirements of the Resource Conservation and Recovery Act (RCRA) hazardous waste program to reduce the paperwork burden these requirements impose on the states, EPA, and the regulated community. EPA has estimated that the total annual hour savings under the final rule ranges from 22,000 hours to 37,500 hours per year. The total annual cost savings under the final rule ranges from approximately $2 million to $3 million. This rulemaking will streamline our information collection requirements, ensuring that only the information that is actually needed and used to implement the RCRA program is collected and the goals of protection of human health and the environment are retained.

DATES: This final rule is effective on May 4, 2006.

ADDRESSES: EPA has established a docket for this action under Docket ID No. EPA–HQ–RCRA–1999–0031. All documents in the docket are listed on the *http://www.regulations.gov* Web site. Although listed in the index, some information is not publicly available, e.g., CBI or other information whose disclosure is restricted by statute. Certain other material, such as copyrighted material, is not placed on the Internet and will be publicly available only in hard copy form. Publicly available docket materials are available either electronically through *http://www.regulations.gov* or in hard copy at the RCRA Docket, EPA/DC, EPA West, Room B102, 1301 Constitution Ave., NW., Washington, DC. This Docket Facility is open from 8:30 a.m. to 4:30 p.m., Monday through Friday, excluding legal holidays. The telephone number for the Public Reading Room is (202) 566–1744, and the telephone number for the RCRA docket is (202) 566–0270.

FOR FURTHER INFORMATION CONTACT: Elaine Eby, Waste Minimization Branch, Hazardous Waste Minimization and Management Division, Office of Solid Waste (5302W), Environmental Protection Agency, 1200 Pennsylvania Ave., NW., Washington, DC 20460; telephone number: (703) 308–8449, fax number: (703) 308–8443, e-mail address: *eby.elaine@epa.gov.*

SUPPLEMENTARY INFORMATION:

General Information

A. Does This Action Apply to Me?

This rule applies to entities regulated under the Resource Conservation and Recovery Act, including manufacturing, transportation, utilities, the waste treatment industry, and the mineral processing industry. This list is not intended to be exhaustive, but rather provides a guide for readers regarding entities likely to be affected by this action. To determine whether your facility, company, or business is regulated by this action, you should carefully examine 40 CFR parts 260 through 273. If you have questions regarding the applicability of this action to a particular entity, consult the person listed in the preceding **FOR FURTHER INFORMATION CONTACT** section.

B. Table of Contents

I. Statutory Authority
II. Background, Purpose, and Summary of Today's Action
III. What Burden Reduction Changes Are We Making?
A. Changes to the Amount of Time Records Must Be Kept
1. We Are Reducing the Retention Time for Certain Information Kept in a Facility's Operating Record
2. We Are Increasing the Retention Time for Certain Information Kept in an Interim Status Facility's Operating Record
3. We Are Establishing a Five Year Record Retention Time for Information Kept on the Operation of Incinerators, Boilers, and Industrial Furnaces
B. Changes to the Professional Engineer Certification Requirements
1. We Are Removing the "Independent and "Registered" Requirements for Selected Certifications
2. We Are Also Changing the Closure and Post-Closure Certification Requirements
C. Owners and Operators of Hazardous Waste Treatment, Storage, and Disposal Facilities Have an Option of Following the Integrated Contingency Plan Guidance
D. Owners and Operators of Hazardous Waste Treatment, Storage, and Disposal Facilities Have an Option to Follow the RCRA or Equivalent Occupational Safety and Health Administration (OSHA) Standard for Emergency Response Training
E. We Are Clarifying Selected Requirements Under RCRA's Land Disposal Restrictions and Eliminating Obsolete Regulatory Language
1. We Are Clarifying the Regulatory Language on the Land Disposal Restrictions Generator Waste Determination
2. We Are Clarifying the Regulatory Language on the Land Disposal Restrictions Characteristic Waste Determination
3. We Are Removing Obsolete Regulatory Language
F. We Are Eliminating Selected Recordkeeping and Reporting Requirements That We Believe Provide Duplicative Information to EPA
1. We Are Eliminating the Requirement for Facilities To Notify That They Are in Compliance After a Release
2. We Are Eliminating the Requirement for Facilities To Notify of Their Intent to Burn F020, F021, F022, F023, F026, and F027 Wastes
3. We Are Eliminating the Requirement for Facilities to Notify if They Employ or Discontinue Use of the Alternative Valve Standard
4. We Are Eliminating the Requirement for Facilities To Notify If They Are Using Alternative Valve Work Practices.
G. We Are Permitting Decreased Inspection Frequency for Certain Hazardous Waste Management Units
1. We Are Establishing Weekly Inspections for Certain Hazardous Waste Tank Systems at Permitted and Interim Status Facilities, and at Large Quantity Generator Sites
2. We Are Establishing Weekly Inspections for SQG Hazardous Waste Tanks Systems With Secondary Containment
3. We Are Allowing Members of the National Environmental Performance Track Program To Apply for an Adjustment to the Frequency of Their Inspections for Certain Hazardous Waste Management Units and Areas.
a. Performance Track: Reduced Inspection Frequency for Areas Subject to Spills.
b. Performance Track: Reduced Inspection Frequency for Containers.
c. Performance Track: Reduced Inspection Frequency for Tank Systems.
d. Performance Track: Reduced Inspection Frequency for Containment Buildings
H. We Are Making Selected Changes to the Requirements for Record Retention and Submittal of Records
1. We Are Removing the Requirement To Submit a One-time Notification for Recycled Wood Wastewater and Spent Wood-Preserving Solutions and Clarifying an Unintentional Elimination Made in the Proposal
2. We Are Eliminating the Requirement for Interim Status Facilities To Submit Specific Ground-Water Monitoring Plans and Ground-Water Assessment Reports
3. We Are Eliminating the Requirement for Interim Status Surface Impoundments, Waste Piles, and Landfills To Submit a Response Action Plan
4. We Are Eliminating the Requirement for Facilities To Submit a Tank System Certification of Completion of Major Repairs

5. We Are Eliminating the Requirement for a Recycler To Submit a Notification and Certification
6. We Are Eliminating the Requirement To Submit an LDR Notification and Certification
I. We Are Making Selected Changes To the Requirements for Document Submittal
1. We Are Streamlining the Procedure for Obtaining a Variance From Classification as a Solid Waste
2. We Are Streamlining the Requirements for Treatability Study Reports for Testing Facilities
3. We Are Streamlining the Requirements for Ground-Water Monitoring
J. We Are Making Selected Changes to the Requirements for Semi-Annual Reports to Annual Reports
1. We Are Changing the Requirement for a Semi-Annual Report Detailing the Effectiveness of the Corrective Action Program
2. We Are Changing the Requirement for a Semi-Annual Report Detailing the Progress of the Corrective Action Program
IV. What Regulatory Requirements Will Remain in the CFR?
V. We Will Implement this Rule via the Class I Permit Modification Process Without Prior Approval
VI. How Will Today's Regulatory Changes Be Administered and Enforced in the States?
A. Applicability of Federal Rules in Authorized States
B. Authorization of States for Today's Rule
VII. Statutory and Executive Reviews
A. Executive Order 12866: Regulatory Planning and Review
B. Paperwork Reduction Act
C. Regulatory Flexibility Act
D. Unfunded Mandates Reform Act
E. Executive Order 13132: Federalism
F. Executive Order 13175: Consultation and Coordination with Indian Tribal Governments
G. Executive Order 13045: Protection of Children from Environmental Health and Safety Risks
H. Executive Order 13211: Actions That Significantly Affect Energy Supply, Distribution or Use
I. National Technology Transfer and Advancement Act of 1995
J. Executive Order 12898: Federal Actions To Address Environmental Justice in Minority Populations and Low-Income Populations
K. Congressional Review Act
VIII. Regulatory Language

I. Statutory Authority

The U.S. Environmental Protection Agency (EPA) regulates the generation and management of hazardous waste under 40 CFR parts 260 through 273 using the authority of the Resource Conservation and Recovery Act of 1976 (RCRA), as amended, 42 U.S.C. 6901 *et seq.*

II. Background, Purpose, and Summary of Today's Action

As part of its hazardous waste regulations, EPA has established recordkeeping and reporting requirements that allow the Agency to enforce and ensure compliance with these regulations. In the Paperwork Reduction Act (PRA) 44 U.S.C. 3501, et seq, Congress directs all federal agencies to become more responsible and publicly accountable for reducing the burden of federal paperwork on the public. "Burden" is defined as the total time, effort, or financial resources expended by persons to generate, maintain, retain, or disclose or provide information to or for a federal agency (44 U.S.C. 3502(2))t

Over the past five years, EPA has continued to assess and evaluate the need for the many recordkeeping and reporting requirements found in the RCRA hazardous waste program. In the course of this effort, we have identified numerous opportunities to eliminate or streamline RCRA requirements, while continuing to fulfill our mission of protecting human health and the environment.

Today's final rule changes a number of the regulatory requirements found in 40 CFR parts 260 through 271. These changes will bring about burden reductions to both the regulated community and the regulators and is a direct result of our consultations with a number of state experts on potential burden reduction ideas, as well as public input through two Notices of Data Availability and a Proposed Rulemaking.[1]

The regulatory changes contained in the Burden Reduction final rule will have no practical impact on the many protections that EPA has established over the years for human health and the environment. At the same time, this rule strives to relieve stakeholders of the burden of nonessential paperwork. The final rule clarifies certain requirements and eliminates or simplifies other requirements. We have eliminated paperwork requirements if they entail information that is obscure, inconsequential, or infrequently submitted to or used by regulators. Note, however, that the final rule does not curtail the right of regulatory agencies to request any information desired. Waste handlers must continue to keep on-site records of their waste management activities and make them available to regulators when requested. As such, the rule does not limit regulators' or the public's ability to learn what is happening at a facility.

To effectively present the large number of regulatory changes we are finalizing, we have divided these changes into ten categories or groups of changes; they are: (1) The amount of time records must be kept; (2) certification by a professional engineer; (3) option to follow the Integrated Contingency Plan Guidance; (4) option to follow the Occupational Safety and Health Administration (OSHA) regulations for emergency training; (5) clarifications and elimination of obsolete regulatory language; (6) elimination of selected recordkeeping and reporting requirements; (7) decreased self-inspection frequency for selected hazardous waste management units; (8) selected changes to the requirements for record retention and submittal of records; (9) changes to the requirements for document submittal; and (10) reduced frequency for report submittals. A summary of the major components of the final rule is presented in Table 1.

The preamble discussion follows the set of categories presented above (see also Table 1, "Summary of the Major Components and a Description of the Regulatory Changes Being Promulgated in Today's Burden Reduction Final Rule"). Within each category, we present the changes we are promulgating, along with a discussion of the comments received and our resolution of the major issues or concerns. At the conclusion of each section, we present comparative tables showing both the current regulatory requirement and the new requirement for the affected group, *i.e.*, generators; permitted hazardous waste treatment, storage, and disposal facilities; and interim status treatment, storage, and disposal facilities. Interim status regulations at 40 CFR Part 265 provide for the continued operation of an existing facility that meets certain conditions until final administrative disposition of the owner and operator permit application is made. Regulations for permit applications are found in 40 CFR part 270 and general standards for permitted facilities are found in 40 CFR part 264.

[1] The Notices of Data Availability were published in the Federal Register on June 18, 1999 (64 FR 32859) and October 29, 2003 (68 FR 61662). The Proposed Rulemaking was published in the Federal Register on January 17, 2002 (67 FR 2518).

TABLE 1.—SUMMARY OF THE MAJOR COMPONENTS AND A DESCRIPTION OF THE REGULATORY CHANGES BEING PROMULGATED IN TODAY'S BURDEN REDUCTION FINAL RULE

Regulatory change	Description of regulatory change
The amount of time records must be kept	Many of the recordkeeping requirements for treatment, storage and disposal facilities (TSDFs) mandate record retention for the life of the facility. In this final rule, we have reduced the length of time waste handlers must retain certain records on site to three years or five years for hazardous waste combustion units (e.g., operating record requirements at 40 CFR 264.73 and 265.73). We have also increased the record retention time for a selected number of documents for interim status facilities in cases where the notification requirement has been eliminated.
Certification by a professional engineer	Numerous regulations require generators and TSDFs to obtain an independent, qualified, registered, professional engineer's certification, as specified. We have changed certain RCRA certification requirements by taking out the terms "independent" and "registered."
Option to follow the Integrated Contingency Plan Guidance	Large Quantity Generators (LQGs) and TSDFs must have contingency plans to minimize hazards to human health and the environment from fires, explosions, or any unplanned release of hazardous waste to the environment. We have modified our RCRA regulations to indicate that these waste handlers may consider developing one comprehensive contingency plan based on the Integrated Contingency Guidance. This guidance provides a mechanism for consolidating the multiple contingency plans that waste handlers have to prepare to comply with various government regulations.
Option to follow Occuputional Safety and Health Administration (OSHA) regulations for emergency training.	LQGs and TSDFs must train their employees in emergency procedures. We have modified the RCRA regulations to allow waste handlers to have the option of complying with either the RCRA or OSHA requirements for emergency response procedures.
Clarifications and elimination of obsolete regulatory language	We are modifying specified regulatory language by and eliminating obsolete terms and/or rewording language to make it clearer. We are also providing regulatory clarifications to several LDR requirements.
Elimination of selected recordkeeping and reporting requirements	We have eliminated certain recordkeeping and reporting requirements in the RCRA regulations in order to eliminate submission of duplicative information and/or reporting unnecessary burden to waste handlers.
Decreased inspection frequency for hazardous waste management units.	Under many RCRA inspection requirements, we specify a frequency at which waste handlers must inspect their frequency for facility and equipment. We have reduced the self-inspection frequency for hazardous waste tank systems from daily to weekly, under certain conditions. In addition, EPA is allowing facilities in the National Performance Track Program to reduce their inspection frequencies, under certain conditions, up to monthly, on a case-by-case basis, for tank systems, containers, containment buildings, and areas subject to spills.
Selected changes to the requirements for record retention and submittal of records.	We are modifying certain requirements under which waste handlers must keep records on-site and submit these same records to EPA. We are specifying certain records that waste handlers need to keep only on-site.
Changes to the requirements for document submittal	We have eliminated several requirements to reduce the number of documents that are submitted to the Agency document for review.
Reduced frequency for report submittal	We have reduced the submittal frequency of certain documents (e.g., from semi-annual to annual).

III. What Burden Reduction Changes Are We Making?

A. Changes to the Amount of Time Records Must Be Kept

As a precautionary measure in promulgating the hazardous waste requirements in 1980, we mandated the retention of many kinds of records until facility closure, resulting in a tremendous volume of stored paperwork. Our experience in implementing the RCRA program has shown that this retention time is excessive, and a priority item for reduction.

1. We Are Reducing the Retention Time for Certain Information Kept in a Facility's Operating Record

We are changing a number of the operating record requirements under §§ 264.73 and 265.73 to reduce the record retention time to three years. Among other things, we are modifying the retention time limit for records on waste analyses; certain monitoring, testing and analytical data; waste determinations; selected certifications; and notifications.

We believe that these changes establish a more reasonable record retention time than the requirement to keep this information until closure of the facility.[2] The three-year record retention period is sufficient to enable regulators to monitor industry compliance and take enforcement actions as needed. In any event,

[2] Record retention times for all Agency programs vary, but in numerous instances have retention times shorter than the life of the facility. For example, the National Primary Drinking Water Regulations require records retention times of one, five, and twelve years (depending on the record). The National Emission Standards for Hazardous Air Pollutants, Subpart FF—National Emission Standards for Benzene Waste Operations requires a two-year records retention time.

§§ 264.74(b) and 265.74(b) require the retention period of any records to be extended automatically during the course of any unresolved enforcement action regarding the facility, or as requested by the Administrator.

We are not modifying the retention limit for records that contain the following information: (1) Description and quantity of each hazardous waste received and what was done with it; (2) location of each hazardous waste; (3) closure estimates; or (4) quantities of waste placed in land disposal units under an extension to the effective date of any land disposal restriction. The retention of this information is necessary to ensure protection of human health and the environment through the life of the facility, and until closure of the facility.

We believe that these changes will not affect the government's or the public's ability to know what is happening at a hazardous waste facility because a basic set of compliance information will still be available in the facility's records. The Agency will have access to the facility's operating record, which will contain many of the documents previously submitted to the Agency. Although the public does not generally have access to the facility's operating record, the Agency Director can require permitted facilities to establish and maintain a publicly accessible information repository at any time (see § 270.30 (m)). Similarly, facilities that are applying for permits may be required to establish and maintain an information repository. (See 124.33.)

In today's rule, we are also amending the regulatory language proposed for maintaining these records. In the proposed rule, we used the language, "maintain for three years after entry into the operating record." A commenter pointed out that some records, such as laboratory analytical results, stand alone in the laboratory records and are not actually "entered into the operating record." We recognize that this is an important distinction and are changing the regulatory language from the proposal to say "maintain for three years" instead of "maintain for three years after entry into the operating record." Also, a commenter pointed out that since monitoring and ground-water clean up is a multi-year or multi-decade task, these records should be kept until closure of the facilities. We agree, and are changing § 264.73(b)(6) and § 265.73(b)(6) accordingly.

We also received comments stating that we should not reduce our record retention requirements, because any particular record might be useful at some future point. This could be said of any requirement. In the Paperwork Reduction Act, Congress instructed us to set a higher standard for imposing an information collection requirement. We believe that information must have a demonstrable value. Based on our experience, we believe that we have identified those records that have the greatest potential impact on the protection of human health and the environment. Such records must be maintained until closure of the facility.

We also received questions in response to the proposed rule asking whether facilities must keep existing records, once generated and stored, until the date that was initially established for their disposal, even though we are changing that date with this rule. It would be burdensome for facilities to have two different sets of recordkeeping requirements, and difficult for EPA and the states to enforce a phase-out of recordkeeping. Therefore, we believe it is appropriate to maintain consistency and retain records until the date established by today's rule (or if the date is unchanged by this rule, to the original date (i.e., until closure of the facility)). Therefore, facilities may dispose of existing records consistent with today's rule, once the retention date established by today's rule becomes effective.

2. We Are Increasing the Retention Time for Certain Information Kept in an Interim Status Facility's Operating Record

In response to comments received, EPA is amending § 265.73(b)(6) and creating a new § 265.73(b)(15) to require retention in the operating record until closure of the facility, the ground-water quality assessment plans required under § 265.90 and § 265.93(d)(2), and ground-water quality assessment reports required under § 265.93(d)(5). Under today's rule, these plans are no longer required to be submitted to the Regional Administrator. Accordingly, EPA has decided that, in order to ensure protection of health and the environment, these records need to be available and, therefore, has amended the regulation to require that the information be maintained in the operating record until closure of the facility. EPA believes today's changes would result in no more burden to facility owners or operators for storage, since it is likely that any report submitted to the Agency would also be kept on-site by the facility. In other words, there would be no increase in burden over what is already being done.

3. We Are Establishing a Five-Year Record Retention Time for Information Kept on the Operation of Incinerators, Boilers, and Industrial Furnaces

Owners and/or operators of boilers and industrial furnaces (BIFs) are subject to compliance-related recordkeeping regulations. For example, BIFs must conduct emission tests to demonstrate compliance with the RCRA emission standards (such as certification of compliance tests), performance tests for their continuous emissions monitors, and retain these test reports on-site until closure of the facility. As a result of the emissions tests, BIFs also establish enforceable operating limits that must be achieved on a daily basis (such as hourly rolling average feed rate limits). BIFs are also required to record the daily operating data in their operating record for compliance purposes and make them available for inspection.

In the October 29, 2003 NODA (68 FR 61662), we solicited comment on amending the current record retention requirement for incinerator monitoring, testing and analytical data, from "for the life of the facility" to three years. We took this action because we had overlooked incinerators in the original proposal and maintain that their record retention requirements should be consistent with those for BIFs. This change for incinerators was supported by a majority of the commenters; however, some pointed out that the recordkeeping requirements for incinerators and BIFs should be consistent with those that the Agency promulgated on October 12, 2005 (70 FR 59402) for incinerators and the majority of BIFs under the Clean Air Act (CAA).[3]

We agree with these commenters and have decided for reasons of consistency with the CAA requirements, to finalize a five year record retention time for incinerators and BIFs. We are also promulgating the five year record retention time for BIFs (such as sulfur recovery furnaces) that will not be subject to the recently promulgated MACT standards.

One commenter that opposed any change to the record retention time stated that incinerators should keep all their data points for the life of the facility. The commenter asserted that the only information that a state inspector has to use during a violation are the data on the incinerator's parametric monitoring. They argued

[3] The Clean Air Act requires the Agency to develop rules to reduce Hazardous Air Pollutant emissions. The rules require the application of strict air emission controls based on performance of best technologies, the overall approach usually being referred to as maximum achievable control technology, or MACT.

that, in no case, should record retention be reduced if there are outstanding enforcement, non-compliance or legal issues pending.

For reasons cited earlier, we believe that modifying the record retention period for incinerators and BIFs to five years is appropriate. Regarding the commenter's point that records should be retained if there is an outstanding enforcement, non-compliance or legal action pending, the regulations already provide for this and nothing in today's rule would amend this provision. See §§ 264.74 and 265.74 which state:

The record retention period for all records required under this part is extended automatically during the course of any unresolved enforcement action regarding the facility or as requested by the Administrator.

The following tables show the new retention times by facility for selected records. We have also included the recordkeeping requirements found in: (1) Section 264.73, Operating record; (2) Section 264.347, Monitoring and inspections; (3) Section 265.73, Operating record; (4) Section 266.102(e)(10), Permit standards for burners; and (5) Section 266.103(d) and (k), Interim status standards for burners.

TABLE 2.—REVISED RECORD RETENTION TIMES FOR PERMITTED TREATMENT, STORAGE, AND DISPOSAL FACILITIES

CFR section	Record summary	Current retention time New retention time as amended by the burden reduction rule
264.73(b)(1)	Description and quantity of each hazardous waste received and the method(s) and date(s) of its treatment, storage or disposal at the facility.	Maintain until closure of the facility. No change in regulatory requirement.
264.73(b)(2)	The location of each hazardous waste within the facility and the quantity at each location.	Maintain until closure of the facility. No change in regulatory requirement.
264.73(b)(3)	Records and results of waste analyses and waste determinations.	Maintain until closure of the facility. Maintain for three years.
264.73(b)(4)	Summary reports and details of all incidents that require implementing the contingency plan.	Maintain until closure of the facility. Maintain for three years.
264.73(b)(5)	Records and results of inspections	Maintain for three years. No change in requirement.
264.73(b)(6)	Monitoring, testing, or analytical data corrective action	Maintain until closure of the facility. Maintain for three years, except for records and results pertaining to ground-water monitoring and cleanup, which must be maintained until closure of the facility.
264.73(b)(7)	For off-site facilities, notices to generators as specified in § 264.12(b).	Maintain until closure of the facility. Maintain for three years.
264.73(b)(8)	All closure cost estimates for disposal facilities, all post-closure cost estimates.	Maintain until closure of the facility. No change in regulatory requirement.
264.73(b)(9)	Waste minimization certification	Maintain until closure of the facility. Maintain for three years.
264.73(b)(10)	Records of the quantities and date of placement for each shipment of hazardous waste place in land disposal units under an extension to the effective date of any land disposal restriction granted.	Maintain until closure of the facility. No change in regulatory requirement.
264.73(b)(11)	For off-site treatment facility, notices and certifications from generator.	Maintain until closure of the facility. Maintain for three years.
264.73(b)(12)	For on-site treatment facility, notices and certifications	Maintain until closure of the facility. Maintain for three years.
264.73(b)(13)	For off-site land disposal facility, notices and certifications from generator.	Maintain until closure of the facility. Maintain for three years.
264.73(b)(14)	For on-site land disposal facility, notices and certifications.	Maintain until closure of the facility. Maintain for three years.
264.73(b)(15)	For off-site storage facility, notices and certifications from generator.	Maintain until closure of the facility. Maintain for three years.
264.73(b)(16)	For on-site storage facility, notices and certifications	Maintain until closure of the facility. Maintain for three years.
264.73(b)(17)	Records required under § 264.1(j)(13)	Maintain until closure of the facility. Maintain for three years.
264.73(b)(18)	Monitoring, testing or analytical data where required by § 264.347.	Maintain until closure of the facility. Maintain for five years.
264.73(b)(19)	Certification as required by § 264.196(f)	No specified requirement. Maintain until closure of the facility.
264.347(d)	For incinerators: monitoring and inspection data	Maintain until closure of the facility. Maintain for five years.
266.102(e)(10)	For burners: recordkeeping	Maintain until closure of the facility. Maintain for five years.

TABLE 3.—REVISED RECORD RETENTION TIMES FOR INTERIM STATUS TREATMENT, STORAGE, AND DISPOSAL FACILITIES

CFR section	Summary record	Current retention time / New retention time as amended by the burden reduction rule
265.73(b)(1)	Description and quantity of each hazardous waste received and the method(s) and date(s) of its treatment, storage or disposal at the facility.	Maintain until closure of the facility. No change in regulatory requirement.
265.73(b)(2)	The location of each hazardous waste within the facility and the quantity at each location.	Maintain until closure of the facility. No change in regulatory requirement.
265.73(b)(3)	Records and results of waste analyses and waste determinations.	Maintain until closure of the facility. Maintain for three years.
265.73(b)(4)	Summary reports and details of all incidents that require implementing the contingency plan.	Maintain until closure of the facility. Maintain for three years.
265.73(b)(5)	Records and results of inspections	Maintain for three years. No change in regulatory requirement.
265.73(b)(6)	Monitoring, testing, or analytical data and corrective action.	Maintain until closure of the facility. Maintain for three years, except for records and results pertaining to ground-water monitoring and cleanup, and response action plans for surface impoundments, waste piles, and landfills which must be maintained until closure of the facility.
265.73(b)(7)	All closure cost estimates for disposal facilities, all post-closure cost estimates.	Maintain until closure of the facility. No change in regulatory requirement.
265.73(b)(8)	Records of the quantities and date of placement for each shipment of the hazardous waste place in land disposal units under an extension to the effective date of any land disposal restriction granted.	Maintain until closure of the facility. No change in regulatory requirement.
265.73(b)(9)	For off-site treatment facility, notices and certifications from generator.	Maintain until closure of the facility. Maintain for three years.
265.73(b)(10)	For on-site treatment facility, notices and certifications.	Maintain until closure of the facility. Maintain for three years.
265.73(b)(11)	For off-site land disposal facility, notices and certifications from the generator.	Maintain until closure of the facility. Maintain for three years.
265.73(b)(12)	For on-site land disposal facility, notices and certifications.	Maintain until closure of the facility. Maintain for three years.
265.73(b)(13)	For off-site storage facility, notices and certifications from generator.	Maintain until closure of the facility. Maintain for three years.
265.73(b)(14)	For on-site storage facility, notices and certifications.	Maintain until closure of the facility. Maintain for three years.
265.73(b)(15)	Monitoring, testing, or analytical data, and corrective action where required by §§ 265.90, 265.93(d)(2), and 265.93(d)(5) of this part and certifications as required by § 265.196(f).	Maintain until closure of the facility. No change in regulatory requirement.
266.103(d)	*Periodic Recertifications.* The owner or operator must conduct compliance testing and submit to the Director a recertification of compliance under provisions of paragraph (c) of this section within five years from submitting the previous certification or recertification. If the owner or operator seeks to recertify compliance under new operating conditions, he/she must comply with the requirements of paragraph (c)(8) of this section.	Every three years. Every five years.
266.103(k)	Interim status standards for burners: recordkeeping.	Maintain until closure of the facility. Maintain for five years.

B. Changes to the Professional Engineer Certification Requirements

Throughout the RCRA regulations, there are various requirements for the services of an independent, qualified, registered, professional engineer to certify the effectiveness of the design and operation of various hazardous waste management units. We proposed to add Certified Hazardous Materials Managers (CHMMs) as professionals qualified to make selected certifications. This proposed change was a result of comments received on our June 18, 1999 NODA (64 FR 32859). In response to this proposal, the Agency received significant comment, primarily requesting that we expand the category of persons allowed to provide the various certifications. Commenters argued that we were being arbitrary in proposing to allow only two professional disciplines (i.e., CHMMs and professional engineers) to certify hazardous waste management operations. Conversely, professional engineers strongly opposed the proposed change in the regulatory requirements. They suggested that

CHMMs were not qualified to certify the design, construction, and structural integrity of hazardous waste management units.

In addition, numerous states opposed the change on the grounds that their state laws allow only licensed engineers to make these certifications. State comments also pointed out that state licensing boards can investigate complaints of negligence or incompetence, on the part of professional engineers, and may impose fines and other disciplinary actions such as cease-and-desist orders or license revocation. According to commenters, similar controls do not exist for other professions. This personal liability of the professional engineer is one of the reasons why state commenters supported the idea that RCRA certifications should only be done by licensed professional engineers.

Other commenters suggested that, rather than deciding which professions are qualified to make certifications, we should establish an environmental professional performance standard based on membership in a recognized professional organization. In response to these comments, we solicited comment in our October 29, 2003 NODA to allow professionals accredited by organizations meeting the American Society for Testing and Materials (ASTM) E1929–98, Standard Practice for the Assessment of Certification Programs for Environmental Engineers: Accreditation Criteria to conduct a limited number of certifications, including: (1) Section 264.573(a)(4)(ii)(g), Drip Pads, Design and operating requirements; (2) Section 265.443(a)(4)(ii)(g), Drip Pads, Design and operating requirements; (3) Section 264.574(a), Drip Pads, Inspections; (4) Section 265.444(a), Drip Pads, Inspections; and (5) Section 266.111(e)(2), Boilers and Industrial Furnaces, Direct transfer equipment—requirements prior to meeting secondary containment requirements.[4]

Comments to the change described in the NODA were mixed. Some commenters supported this change in qualifications for selected certifications, while a number of states and professional organizations still strongly opposed allowing anyone other than a professional engineer to perform these certifications. While the Agency believes that added flexibility to the RCRA regulations is a goal worth pursuing, in this case, we are persuaded by the arguments presented by states with regard to these certifications and are not going forward with these changes at this time. Certifications for drip pads involve certifying engineering designs, drawings, plans and other engineering details, involving structural and hydraulic and other functions. As such, we believe that while there may be professionals other than professional engineers qualified to make these certifications, it is imperative that the goals of human health and the environmental protection are maintained. In reviewing the comments, we are not convinced that all environmental professionals certified by the ASTM standard would be qualified to perform these engineering evaluations. To this end, we are not going forward with allowing the changes to the drip pad certification requirements that would allow environmental professionals recognized by a certification program that is compliant with ASTM E–1929–98 Standard Practice for the Assessment of Certification Programs for Environmental Professionals: Accreditation Criteria.

Although the Agency was not persuaded that ASTM board certified environmental professionals, including CHMMs, should be allowed to make the required RCRA certifications that were the subject of this rulemaking, the Agency wants to make it clear that facilities are still permitted to utilize qualified professionals who may not be professional engineers in performing the analyses that underlie these certifications. Facilities can potentially lower their costs by utilizing the flexibility to employ others as part of the certification requirement. For example, as part of the closure and post closure requirements, some CHMMs may be qualified to make certain determinations associated with these certifications to determine whether operations at the site will minimize hazards.

The Agency is sympathetic to the large number of comments by the CHMMs and other environmental professionals about unnecessary restrictions in the marketplace. However, EPA is retaining the professional engineering certification, in part, to allay state concerns about the need to monitor and control the activities of personnel that are now subject to state licensure control. Given, however, additional experience by the Agency with the utilization of other environmental professionals, EPA may re-examine this issue in the future.[5]

1. We Are Removing the "Independent" and "Registered" Requirements for Selected Certifications

Some commenters to the proposed rule suggested that we change the certification requirements by amending the qualifications required for the certification from "independent, qualified, registered, professional engineer" to "qualified professional engineer." That is, the commenters suggested it was not necessary for the professional engineer to be independent or registered. Commenters argued that the term "qualified professional engineer" retains the most important components of the requirement: (1) That the engineer be *qualified* to perform the task; and (2) that she or he be a professional engineer (following a code of ethics and the potential of losing his/her license for negligence).

In the October 29, 2003 NODA (68 FR 61662), EPA also solicited comment on changing the qualifications for who can certify the design, operation and closure of specific hazardous waste management units from "independent, qualified, registered, professional engineer" to "qualified professional engineer." We solicited comment on eliminating the requirement that the certifier be "independent," reasoning that we could rely on the professional standards of the certifier to ensure accurate certifications. This could potentially save expenses for companies with in-house engineers, since they would not have to hire outside consultants. State commenters strongly argued that the word "independent" should be retained because an independent review and certification avoids any potential of conflict of interest. Commenters stated that an employee of a facility would more likely have a biased approach to review and certification, and that state agencies would have less confidence in the accuracy and quality of review and

[4] After publication of the October 29, 2003 NODA, (see 68 FR 61662), EPA determined that the certification required by § 266.111(e)(2) had to be made by August 21, 1992. As such the Agency is not pursuing a change to this requirement in today's rulemaking, obviously because the date has passed.

[5] For example, in the All Appropriate Inquiries (AAI) rule published on November 1, 2005, (70 CFR 66070) EPA sets standards for CERCLA liability protection by establishing criteria that prospective property owners must use in the inquiries they conduct into the previous ownership, uses, and environmental conditions of a property prior to acquiring the property. The AAI rule differs from the RCRA burden reduction rule in that AAI does not in any way require the environmental professional to render any judgment or opinion regarding RCRA or CERCLA compliance or liability. AAI requirements include research activities and a site investigation similar to a Phase I environmental site assessment. It does not include compliance evaluation or an assessment of engineering or technical requirements (which may inherently require the expertise of an engineer or geologist).

certification. Furthermore, the commenters argued that the public would have reduced confidence in the accuracy and meaning of the engineering review and certification if it was conducted by an employee of the facility. The public would more likely suspect a conflict of interest and demand a more rigorous review by state agencies. Commenters also noted that a similar change, regarding whether to retain the term "independent" for professional engineers certifying closure, was proposed by EPA on March 19, 1985 (50 FR 11074). After receiving public comment, a final rule was issued on May 2,1986 with the term "independent" retained. In the preamble to the May 2, 1986 final rule, we stated that, because certification of final closure is the final step in the closure process and triggers the release of the owner or operator from financial responsibility requirements for closure and third party liability coverage requirements, we believed that the certification should be made by a person who is least subject to pressures to certify to the adequacy of a closure that, in fact, is not in accordance with the approved closure plan. Commenters also noted that in the October 9, 1991 **Federal Register**, EPA addressed concerns regarding proposed language that would have allowed a "qualified party" to perform closure and post closure certification. In that FR notice, we stated on page 51103:

> The Agency agrees with commenters that objective closure and post-closure certifications are essential for avoiding any potential conflicts of interest and ensuring protection of human health and the environment and that more specific requirements concerning the qualification of the certifying party are necessary to ensure the adequacy of the certification. We, therefore, are requiring in this final rule that certifications be obtained from independent, registered, professional engineers (i.e., registered professional engineers not in the employ of the owner or operator), consistent with requirements under subtitle C and other federally mandated certification programs (e.g., Clean Water Act grants).

Upon further analysis and reflection, we have decided to delete the independent qualification for certification made by a professional engineer. EPA continues to believe that this proposed modification retains the most important requirements: That the engineer is *qualified* to perform the task and is a professional engineer (i.e., licensed to practice engineering under the title Professional Engineer.) We believe that a professional engineer, regardless of whether he/she is independent is able to give fair and technical review because of the programs established by the state licensing boards. It is not clear to us that an in-house engineer faces a greater economic temptation than an independent engineer seeking to cultivate an ongoing relationship with a client. This is a central mission of state licensing boards. If certifications are provided when the facts do not warrant certification, the professional engineer is subject to penalties, including the loss of license and the possibility of fines. Furthermore, we are convinced that the change to the certification requirements will allow facilities to reduce burden without compromising environmental safety by using in-house expertise. Professional engineers employed by a facility are more familiar with its own particular situation and are in a position to provide more on-site review and oversight of the activity being certified.

We also solicited comment on removing the term "registered," explaining that based on our understanding of the term "registered" (one who is licensed by a state) the terms "registered," "licensed" and "professional" mean the same thing in the case of certifying the design, operation and closure of hazardous waste management units. Thus, using the terms "registered" and "professional" when defining the qualification of an engineer, in this context, is redundant. While the majority of the comments supported the change, agreeing that the term "registered" appears to be redundant and could be removed, several commenters were opposed to making the change. These commenters argued that the word "registered" is necessary to prevent confusion in the field, particularly among generators, that a license or registration is required. The Agency is unconvinced by this argument and maintains that the use of "registered" and "professional" as qualifications for engineers making these certifications is redundant and should be simplified.

As a final matter, we unintentionally failed to identify eight additional certification requirements that are part of this regulatory change, i.e., each contains one or a combination of the terms: independent, registered and/or professional when describing the qualifications of the engineer. These certifications include: (1) Section 264.193(h)(4)(i)(2), Tank Systems, Containment and detection of releases; (2) Section 265.193(h)(5)(i)(2), Tank Systems, Containment and detection of releases; (3) Section 264.554(c)(2), Staging Piles; (4) Section 264.1101(c)(2), Containment Buildings, Design and operating standards; (5) Section 265.1101(c)(2), Containment Buildings, Design and operating standards; (6) Section 270.14(a), Permit Application, Content of part B. General requirements; (7) Section 270.17(d) Permit Application, Specific part B information requirements for surface impoundments; and (8) Section 270.26(c)(15), Permit Application, Special part B information requirements for drip pads. EPA believes today's changes provide consistency to the certification requirements, i.e., removing the terms independent and registered. As such, we are finalizing these eight additional certification changes.

2. We Are Also Changing the Closure and Post-Closure Certification Requirements

In the October 29, 2003 NODA (68 FR 61662), we also solicited comment on amending the qualifications for selected closure and post-closure certifications to "qualified professional engineer." These certifications included: (1) Section 264.115, Closure and Post-Closure, Certification of closure; (2) Section 265.115, Closure and Post-Closure, Certification of closure; (3) Section 264.120, Closure and Post-Closure, Certification of completion of post-closure care; (4) Section 265.120, Closure and Post-Closure, Certification of completion of post-closure care; and (5) Section 264.280(b), Land Treatment, Closure and post-closure care.

During the development of today's final rule, we discovered that we incorrectly stated the required qualifications for engineers providing the closure and post-closure certifications, and we failed to identify one additional certification, § 265.280(e) Land Treatment, Closure and post-closure care, and six cross-reference citations to the original closure and post-closure certifications. These cross-references are: (1) Section 264.143(i), Financial Assurance for Closure, Release of the owner or operator from the requirements of this section; (2) Section 265.143(h), Financial Assurance for Closure, Release of the owner or operator from the requirements of this section; (3) Section 264.145(i), Financial Assurance for Post-Closure, Release of the owner or operator from the requirements of this section; (4) Section 265.145(h), Financial Assurance for Post-Closure, Release of the owner or operator from the requirements of this section; (5) Section 264.147(e), Liability Requirements, Period of coverage; and (6) Section 265.147(e), Liability Requirements, Period of coverage.

We incorrectly stated, in both the proposed rule and the October 29, 2003

NODA (68 FR 61662), the regulatory requirements for these certifications. In both these notices, we stated that the regulatory language for closure and post-closure certifications require an "independent, qualified, registered, professional engineer" to make the certifications. This is incorrect. The regulatory language for these certifications does not include the word "qualified;" the certifications language states that the certification must be made by an "independent, registered, professional engineer." Hence our proposed regulatory change to "qualified professional engineer" for these certifications was inaccurate and inconsistent with our other proposed certification requirements. In our view, this error was minor and does not change our position regarding the redundancy of using both "registered" and "professional," when defining the necessary certification qualifications. This error also does not change our position that all certifications should be conducted by a "qualified professional engineer" i.e., one that is qualified to perform the task and is a professional engineer (licensed/registered by the state and following a code of ethics and the potential of losing his/her license for negligence). As such, we are today amending all the closure and post-closure certification requirements to require qualified professional engineers to certify closure and post-closure.

Tables 4 and 5 identify the certifications that we are amending in today's rule for permitted and interim status treatment, storage and disposal facilities as needing a qualified (as in "qualified to perform the task") professional engineer.[6]

TABLE 4.—PERMITTED TREATMENT, STORAGE, AND DISPOSAL FACILITIES NEEDING RCRA CERTIFICATIONS BY A QUALIFIED PROFESSIONAL ENGINEER

CFR section	New RCRA certification requirement (i.e., dropping "registered")
264.115	Closure and Post-Closure. Certification of closure.
264.120	Closure and Post-Closure. Certification of completion of post-closure care.
264.143(i)	Financial Assurance for Closure. Release of the owner or operator from the requirements of this section.
264.145(i)	Financial Assurance for Post-Closure. Release of the owner or operator from the requirements of this section.
264.147(e)	Liability Requirements. Period of coverage.
264.191(a), (b)(5)(ii)	Tank Systems. Assessment of existing tank system's integrity.
264.192(a), (b)	Tank Systems. Design and installation of new tank systems or components.
264.193(h)(4)(i)(2)	Tank Systems. Containment and detection of releases.
264.196(f)	Tank systems. Response to leaks or spills and disposition of leaking or unfit-for-use tank systems.
264.280(b)	Land Treatment. Closure and post closure care.
264.554(c)(2)	Staging Piles.
264.571(a),(b),(c)	Drip Pads. Assessment of existing drip pad integrity.
264.573(a)(4)(ii)	Drip Pads. Design and Operating Requirements.
264.573(g)	Drip Pads. Design and Operating Requirements.
264.574(a)	Drip Pads. Inspections.
264.1101(c)(2)	Containment Buildings. Design and operating standards.
270.14(a)	Permit Application. Content of part B. General requirements.
270.16(a)	Permit Application. Specific part B information requirements for tank systems.
270.26(c)(15)	Permit Application. Specific part B information requirements for drip pads.

TABLE 5.—INTERIM STATUS TREATMENT, STORAGE AND DISPOSAL FACILITIES NEEDING RCRA CERTIFICATIONS BY A QUALIFIED PROFESSIONAL ENGINEER

CFR section	New RCRA certification requirement (i.e., dropping "registered")
265.115	Closure and Post-Closure. Certification of closure.
265.120	Closure and Post-Closure. Certification of completion of post-closure care.
265.143(h)	Financial Assurance for Closure. Release of the owner or operator from the requirements of this section.
265.145(h)	Financial Assurance for Post-Closure. Release of the owner or operator from the requirements of this section.
265.147(e)	Liability Requirements. Period of coverage.
265.191(a), (b)(5)(ii)	Tank Systems. Assessment of existing tank system's integrity.
265.192(a), (b)	Tank Systems. Design and installation of new tank systems or components.
265.193(h)(5)(i)(2)	Tank Systems. Containment and detection of releases.
265.196(f)	Tank Systems. Response to leaks or spills and disposition of leaking or unfit-for-use tank systems.
265.280(e)	Land Treatment. Closure and post closure care.
265.441(a), (b),(c)	Drip Pads. Assessment of existing drip pad integrity.
265.443(a)(4)(ii)	Drip Pads. Design and Operating Requirements.
265.443(g)	Drip Pads. Design and Operating Requirements.
265.444(a)	Drip Pads. Inspections.
265.1101(c)(2)	Containment Buildings. Design and operating standards.
270.14(a)	Permit Application. Content of part B. General requirements.
270.16(a)	Permit Application. Specific part B information requirements for tank systems.
270.26(c)(15)	Permit Application. Special part B information requirements for drip pads.

[6] In §§ 264.192(b) and 265.192(b), certifications may also be done by an independent, qualified installation inspector. Similarly, in § 264.280(b), this certification may be done by an independent, qualified soil scientist, in lieu of a qualified professional engineer.

C. Owners and Operators of Hazardous Waste Treatment, Storage, and Disposal Facilities Have an Option of Following the Integrated Contingency Plan Guidance

We are amending §§ 264.52(b) and 265.52(b) of the RCRA regulations to provide owners and operators of hazardous waste treatment, storage, and disposal facilities the option of developing one contingency plan. EPA recommends that the plan be based on the integrated contingency plan guidance.[7] This guidance provides an excellent set of considerations for consolidating the multiple contingency plans that facilities have to prepare to comply with various government regulations. The use of a single plan per facility will eliminate the confusion for facilities that must decide which of the contingency plans is applicable to a particular emergency. In addition, a single plan will provide "first responders" (e.g., firemen) with a mechanism for complying with multiple regulatory requirements. The adoption of a standard plan should ease the burden of coordination with local emergency planning committees.

Today's rule clarifies our regulations (see §§ 264.52 and 265.52) by specifically authorizing combined plans, as well as clarifying that when modifications are made to non-RCRA provisions in an integrated contingency plan, the changes do not trigger the need for a RCRA permit modification.

D. Owners and Operators of Hazardous Waste Treatment, Storage, and Disposal Facilities Have an Option To Follow the RCRA or the Occupational Safety and Health Administration (OSHA) Standards for Emergency Response Training

We are revising §§ 264.16 and 265.16 to eliminate redundant emergency response training requirements under OSHA and RCRA regulations while still ensuring protectiveness.

EPA and the Occupational Safety and Health Administration (OSHA) have both promulgated regulations addressing worker activities and training at hazardous waste management facilities. While EPA's hazardous waste regulations focus on facility operations, worker training, OSHA focuses on worker safety. Both agencies require worker training.

While we were conducting our own review of potential overlaps between EPA and OSHA regulations, the Government Accountability Office [8] published in October 2000 a study on the issue. GAO suggested that the overlap in emergency training requirements diminishes the efficiency of the facility and creates unnecessary compliance costs. The GAO study pointed out that OSHA's regulations have specific training requirements for RCRA-permitted facilities to teach hazardous waste workers how to respond to emergencies under 29 CFR 1910.120(p). With the support of the GAO findings, EPA proposed to eliminate the RCRA emergency response training requirements in favor of the OSHA requirements.

While we received comments in support of the proposal, other commenters expressed particular concern that two of the RCRA emergency response training requirements are not covered in OSHA's requirements. (1) understanding key parameters for automatic waste feed cut-off systems; and (2) how to respond to ground-water contamination incidents. These commenters believe that the deletion of these two requirements would endanger the environment and human health in the area of RCRA facilities, in that adhering only to the OSHA requirements would mean that workers would not be trained in these areas.

This, however, is not EPA's intention. The final rule has been written to ensure that RCRA facilities are not required to provide separate training. We also note that facilities exempted from RCRA emergency response training would still have to comply with §§ 264.16(a)(1) and 265.16(a)(1), which state: "Facility personnel must successfully complete a program of classroom instruction or on-the-job-training that teaches them to perform their duties in a way that ensures the facility's compliance with the requirements of this part."

OSHA's 29 CFR 1910.120 regulations require that employees understand and be able to perform the standard operating procedures that are part of their daily work. OSHA's 29 CFR 1910.38 Emergency Action Plan requirements include mandated training in procedures to be followed by employees who operate critical plant operations (such as responding to ground-water contamination incidents) during a spill or other emergency.

Other commenters opposed the proposal because OSHA's 29 CFR 1910 requirements are not as comprehensive as the RCRA requirements regarding the universe of facilities. Specifically, they stated that OSHA's regulations are not required for all hazardous waste generators (e.g., conditionally exempt small quantity generators under § 261.5 and small quantity generators under § 262.34) and certain treatment, storage, disposal facilities (e.g., municipal, state and federal owned and operated facilities.) We agree, and facilities not subject to OSHA training requirements would have to comply with the RCRA training requirements.

To ensure that all facilities are covered and that there are no gaps in the emergency response training requirements, we are providing flexibility by allowing facilities to eliminate redundant emergency response training requirements under RCRA and OSHA requirements (as opposed to the proposed rule's approach of requiring facilities to follow only the OSHA regulations). For example, if a facility can meet all of the RCRA emergency response training requirements through an OSHA training course, we would consider the facility in compliance with the regulation. On the other hand, if a facility cannot meet the emergency response training requirements through an OSHA training course, then it would be incumbent upon that facility to address any gaps (for example, if OSHA did not include automatic waste feed cut-off training, there would not be a problem as long as appropriate training occurs, such as combustor staff receives this training as part of its RCRA training.) Facilities not subject to OSHA training requirements would have to comply with the RCRA training requirements. We believe that this is a reasonable accommodation for all facilities.

Generators and owners/operators of treatment, storage, and disposal facilities should work with the appropriate permitting and/or enforcement authority to ensure that the approach they take in developing an emergency response training program is in compliance with the requirements of §§ 264.16 and 265.16.

[7] In 1996, EPA, in conjunction with the Department of Transportation, the Department of the Interior, and the Department of Labor, issued the Integrated Contingency Plan Guidance. This guidance provides a mechanism for consolidating the multiple contingency plans that facilities have to prepare to comply with various government regulations. Owners and operators of hazardous waste facilities can develop one contingency plan based on this Guidance. The Integrated Contingency Plan can be found at 61 FR 28641, June 5, 1996 or on the Internet at *http://yosemite.epa.gov/oswer/ceppoweb.nsf/content/serc-lepc-publications.htm.*

[8] Formerly the United States General Accounting Office.

E. We Are Clarifying Selected Requirements Under RCRA's Land Disposal Restrictions and Eliminating Obsolete Regulatory Language

1. We Are Clarifying the Regulatory Language on the Land Disposal Restrictions Generator Waste Determination

We proposed eliminating § 268.7(a)(1) that requires, among other things, that generators conduct a waste determination for purposes of complying with the Land Disposal Restrictions (LDRs). Section 268.7(a)(1) requires generators to determine if hazardous waste must be treated prior to land disposal. This determination can be made either through testing or using the generator's knowledge of the waste's properties and constituents. We suggested that a combination of two other requirements provided the same safeguards as § 268.7(a)(1), making it redundant. First, a determination of whether a waste is hazardous is required by 40 CFR 262.11, which says that generators of solid waste must determine whether a waste is hazardous. Second, § 264.13(a)(1) requires treatment, storage, and disposal facilities (TSDFs) to perform a general waste analysis to determine "all of the information which must be known to treat, store, or dispose of the waste in accordance with this Part and Part 268 of this chapter". We suggested that these other determinations are sufficient to assure that a waste is properly characterized for achieving compliance with the LDRs.

Some commenters supported deleting this waste analysis requirement, stating, generally, that they supported the Agency's efforts to reduce redundant testing requirements. We agree with these comments with respect to reducing redundant testing requirements and are adding a cross reference in § 268.7(a)(1) to § 262.11, in order to clarify that these two generator waste analysis functions can be performed concurrently, thus avoiding redundant waste analysis.

Commenters who opposed deleting the generator LDR waste analysis requirement, however, were persuasive in their argument that the deletion of § 268.7(a)(1) would not really result in burden reduction. Rather, it would merely shift the burden from the generator to the TSDF. While TSDFs have a separate LDR waste analysis requirement under § 264.13(a)(1), they often rely—at least in part—on determinations or information provided by the generator.

Commenters further asserted that if TSDFs have to assume full responsibility for the LDR waste analysis requirement, it would be more expensive overall, because generators can use their knowledge of the waste in determining how LDRs apply to a waste, while the TSDF would not have that background and would have to perform much more extensive waste analysis.

We agree with these comments, and have determined that we need to maintain the LDR generator waste analysis requirement of § 268.7(a)(1). Thus, today's rule, rather than eliminating paragraph § 268.7(a)(1), amends paragraph § 268.7(a)(1), to avoid duplication and clarify that the two generator waste analysis functions can be performed concurrently. However, in order to provide maximum flexibility to generators, we also are clarifying that if a generator does not want to determine, based on waste analysis or knowledge of the waste, whether the waste must be treated, he may assume that he is subject to the full array of LDR requirements. The generator then must send the waste to a RCRA-permitted hazardous waste treatment facility where the treatment facility must make the determination when the waste has met the treatment standards of LDR (possibly even upon receipt as generated.) A conforming change is also being made to the notification in § 268.7(a)(2) for such cases.

2. We Are Clarifying the Regulatory Language on the Land Disposal Restrictions Characteristic Waste Determination Requirement

We proposed to eliminate the separate waste analysis requirement (§ 268.9(a)) for generators of characteristic hazardous wastes under the land disposal restrictions, in order to parallel the proposed changes to § 268.7(a)(1) that are discussed above.

Some commenters supported deleting this waste analysis requirement, stating, generally, that they supported the Agency's efforts to reduce redundant testing requirements. We agree with these comments with respect to reducing redundant testing requirements and are adding a cross reference in § 268.9(a) to § 262.11, in order to clarify that these two generator waste analysis functions can be performed concurrently, thus avoiding redundant waste analysis.

Commenters who opposed deleting the generator LDR waste analysis requirement, however, were persuasive in their argument that the deletion of § 268.9(a) would not really result in burden reduction. Rather, it would merely shift the burden from the generator to the TSDF. While TSDFs have a separate LDR waste analysis requirement under § 264.13(a)(1), they often rely—at least in part—on determinations or information provided by the generator. Commenters further asserted that if TSDFs have to assume full responsibility for the LDR waste analysis requirement, it would be more expensive overall, because generators can use their knowledge of the waste in determining how LDRs apply to a waste, while the TSDF would not have that background and would have to perform much more extensive waste analysis. We agree with these comments, and have determined that we need to maintain the LDR generator waste analysis requirement of § 268.9(a). Thus, today's rule, rather than eliminating paragraph § 268.9(a), amends paragraph § 268.9(a), to avoid duplication and clarify that the two generator waste analysis functions can be performed concurrently.

3. We Are Removing Obsolete Regulatory Language

We are deleting seventeen RCRA requirements because they are no longer applicable or have an expiration date that has passed. Except as noted below, we received no negative comments on these proposed changes.

In the proposed rule, we suggested amending §§ 264.193(a) and 265.193(a), arguing that the language was obsolete. However, the proposal inadvertently deleted paragraphs (1) and (5) of §§ 264.193(a) and 265.193(a). These paragraphs specify what tanks are required to have secondary containment, and in the case of tanks managing newly regulated waste, how soon secondary containment must be provided. We are correcting this mistake by finalizing the deletion of only §§ 264.193 (a)(2),(3), and (4) and 265.193(a)(2), (3), and (4) and clarifying the requirements in §§ 264.193(a)(5) and 265.193(a)(5). Tables 6, 7, and 8 summarize the changes being finalized today.

TABLE 6.—REGULATORY CLARIFICATION BEING MADE FOR LAND DISPOSAL RESTRICTIONS TESTING, TRACKING, AND RECORDKEEPING REQUIREMENTS FOR GENERATORS, TREATERS, AND DISPOSAL FACILITIES

CFR section	Current regulatory language New regulatory language as amended by the Burden Reduction Rule
268.7(a)(1)	(a) Requirements for generators: (1) A generator of hazardous waste must determine if the waste has to be treated before it can be land disposed. This is done by determining if the hazardous waste meets the treatment standards in §268.40, §268.45, or §268.49. This determination can be made in either of two ways: testing the waste or using knowledge of the waste. If the generator tests the waste, testing would normally determine the total concentration of hazardous constituents, or the concentration of hazardous constituents in an extract of the waste obtained using test method 1311 in "Test Methods of Evaluating Solid Waste, Physical/Chemical Methods," EPA Publication SW–846, as referenced in §260.11 of this chapter, depending on whether the treatment standard for the waste is expressed as a total concentration or concentration of hazardous constituent in the waste's extract. In addition, some hazardous wastes must be treated by particular treatment methods before they can be land disposed and some soils are contaminated by such hazardous wastes. These treatment standards are also found in §268.40, and are described in detail in §268.42, Table 1. These wastes, and solids contaminated with such wastes, do not need to be tested (however, if they are in a waste mixture, other wastes with concentration level treatment standards would have to be tested). If a generator determines they are managing a waste or soil contamination with a waste, that displays a hazardous characteristic of ignitability, corrosivity, reactivity, or toxicity, they must comply with the special requirements of §268.9 of this part in addition to any applicable requirements in this section.
	(a) Requirements for generators: (1) A generator of hazardous waste must determine if the waste has to be treated before it can be land disposed. This is done by determining if the hazardous waste meets the treatment standards in §268.40, §268.45, or §268.49. This determination can be made concurrently with the hazardous waste determination required in §262.11 of this chapter, in either of two ways: testing the waste or using knowledge of the waste. If the generator tests the waste, testing would normally determine the total concentration of hazardous constituents, or the concentration of hazardous constituents in an extract of the waste obtained using test method 1311 in "Test Methods of Evaluating Solid Waste, Physical/Chemical Methods," EPA Publication SW–846, incorporated by reference (see §260.11 of this chapter), depending on whether the treatment standard for the waste is expressed as a total concentration or concentration of hazardous constituent in the waste's extract. (Alternatively, the generator must send the waste to a RCRA-permitted hazardous waste treatment facility, where the waste treatment facility must comply with the requirements of §264.13 of this chapter and §268.7(b) of this part.) In addition, some hazardous wastes must be treated by particular treatment methods before they can be land disposed and some soils are contaminated by such hazardous wastes. These treatment standards are also found in §268.40, and are described in detail in §268.42, Table 1. These wastes, and solids contaminated with such wastes, do not need to be tested (however, if they are in a waste mixture, other wastes with concentration level treatment standards would have to be tested). If a generator determines they are managing a waste or soil with a waste, that displays a hazardous characteristic of ignitability, corrosivity, reactivity, or toxicity, they must comply with the special requirements of §268.9 of this part in addition to any applicable requirements in this section.
268.7(a)(2)	If the waste or contaminated soil does not meet the treatment standards: With the initial shipment of waste to each treatment or storage facility, the generator must send a one-time written notice to each treatment or storage facility receiving the waste, and place a copy in the file. The notice must include the information in column "268.7(a)(2)" of the Generator Paperwork Requirements Table in 268.7(a)(4). No further notification is necessary until such time that the waste or facility change, in which case a new notification must be sent and a copy placed in the generator's file.
	If the waste or contaminated soil does not meet the treatment standards, or if the generator chooses not to make the determination of whether his waste must be treated, with the initial shipment of waste to each treatment or storage facility, the generator must send a one-time written notice to each treatment or storage facility receiving the waste, and place a copy in the file. The notice must include the information in column "268.7(a)(2)" of the Generator Paperwork Requirements Table in 268.7(a)(4). (Alternatively, if the generator chooses not to make the determination of whether the waste must be treated, the notification must include the EPA Hazardous Waste Numbers and Manifest Number of the first shipment and must state "This hazardous waste may or may not be subject to the LDR treatment standards. The treatment facility must make the determination.") No further notification is necessary until such time that the waste or facility change, in which case a new notification must be sent and a copy placed in the generator's file.
268.9(a)	(a) The initial generator of a solid waste must determine each EPA Hazardous Waste Number (waste code) applicable to the waste in order to determine the applicable treatment standards under subpart D of this part. For purposes of part 268, the waste will carry the waste code for any applicable listed waste (Part 261, Subpart D). In addition, where the waste exhibits a characteristic, the waste will carry one or more of the characteristic waste codes (Part 261, Subpart C), except when the treatment standard for the listed waste operates in lieu of the treatment standard for the characteristic waste, as specified in paragraph (b) of this section. If the generator determines that their waste displays a hazardous characteristic (and is not D001 nonwastewaters treated by CMBST, RORGS, OR POLYM of §268.42, Table 1), the generator must determine the underlying hazardous constituents (as defined at §268.2(i)) in the characteristic waste.

TABLE 6.—REGULATORY CLARIFICATION BEING MADE FOR LAND DISPOSAL RESTRICTIONS TESTING, TRACKING, AND RECORDKEEPING REQUIREMENTS FOR GENERATORS, TREATERS, AND DISPOSAL FACILITIES—Continued

CFR section	Current regulatory language New regulatory language as amended by the Burden Reduction Rule
	(a) The initial generator of a solid waste must determine each EPA Hazardous Waste Number (waste code) applicable to the waste in order to determine the applicable treatment standards under subpart D of this part. This determination may be made concurrently with the hazardous waste determination required in §262.11 of this chapter. For purposes of part 268, the waste will carry the waste code for any applicable listed waste (Part 261, Subpart D). In addition, where the waste exhibits a characteristic, the waste will carry one or more of the characteristic waste codes (Part 261, Subpart C), except when the treatment standard for the listed waste operates in lieu of the treatment standard for the characteristic waste, as specified in paragraph (b) of this section. If the generator determines that their waste displays a hazardous characteristic (and is not D001 nonwastewaters treated by CMBST, RORGS, OR POLYM of §268.42, Table 1), the generator must determine the underlying hazardous constituents (as defined at §268.2(i)) in the characteristic waste.

TABLE 7.—OBSOLETE REGULATORY LANGUAGE BEING DELETED FOR PERMITTED TREATMENT, STORAGE, AND DISPOSAL FACILITIES

CFR section	Regulatory requirement	Current regulatory language New regulatory requirement as amended by the Burden Reduction Rule
264.193(a)(2)	Tank Systems: Containment and detection of releases.	For all existing tank systems used to store or treat EPA Hazardous Waste Nos. F020, F021, F022, F023, F026, and F027, within two years after January 12, 1987. Section 264.193(a)(2) is being deleted.
264.193(a)(3)	Tank Systems: Containment and detection of releases.	For those existing tank systems of known and documented age, within two years after January 12, 1987 or when the tank system has reached 15 years of age, whichever comes later. Section 264.193(a)(3) is being deleted.
264.193(a)(4)	Tank Systems: Containment and detection of releases.	For those existing tank systems for which the age cannot be documented, within eight years of January 12, 1987; but if the age of the facility is greater than seven years, secondary containment must be provided by the time the facility reaches 15 years of age, or within two years of January 12, 1987, whichever comes later. Section 264.193(a)(4) is being deleted.
264.251(c)	Waste Piles: Design and operating requirements.	The owner or operator of each new waste pile unit on which construction operating commences after January 29, 1992, each lateral expansion of a waste pile unit on which construction commences after July 29, 1992, and each replacement of an existing waste pile unit that is to commence reuse after July 29, 1992 must install two or more liners and a leachate collection and removal system above and between such liners. "Construction commences" is as defined in section 260.10 under "existing facility". The owner or operator of each new waste pile unit, each lateral expansion of a waste pile unit, and each replacement of an existing waste pile unit must install two or more liners and a leachate collection and removal system above and between such liners.
264.314(a)	Land fills: Special requirements for bulk and containerized liquids.	Bulk or non-containerized liquid waste or waste containing free liquids may be placed in a landfill prior to May 8, 1985. Section 264.314(a) is being deleted.
264.314(b)	Landfills: Special requirements for bulk and containerized liquids.	Effective May 8, 1995, the placement of bulk or non-containerized liquid hazardous waste or hazardous waste containing free liquids (whether or not sorbents have been added) in any landfill is prohibited. The placement of bulk or non-containerized liquid hazardous waste or hazardous waste containing free liquids (whether or not sorbents have been added) in any landfill is prohibited.
264.314(f)	Land Fills: Special requirements for bulk and containerized liquids.	Effective November 8, 1985, the placement of any liquid which is not a hazardous waste in a landfill is prohibited unless the owner or operator of such landfill demonstrates to the Regional Administrator, or the Regional Administrator determines that: The placement of any liquid which is not a hazardous waste in a landfill is prohibited unless the owner or operator of such landfill demonstrates to the Regional Administrator, or the Regional Administrator determines that:
264.1100	Containment Buildings. Applicability.	The requirements of ths subpart apply to owners or operators who store or treat hazardous waste in units designed and operated under §264.1101 of this subpart. These provisions will become effective on February 18, 1993, although owner or operator may notify the Regional Administrator of his intent to be bound by this subpart at an earlier time. The owner or operator is not subject to the definition of land disposal in RCRA §3004(k) provided that the unit: The requirements of this subpart apply to owners or operators who store or treat hazardous waste in units designed and operated under §264.1101 of this subpart. The owner or operator is not subject to the definition of land disposal in RCRA §3004(k) provided that the unit:

TABLE 7.—OBSOLETE REGULATORY LANGUAGE BEING DELETED FOR PERMITTED TREATMENT, STORAGE, AND DISPOSAL FACILITIES—Continued

CFR section	Regulatory requirement	Current regulatory language New regulatory requirement as amended by the Burden Reduction Rule
264.1101(c)(2)	Containment Buildings. Design and Operating Standards.	Obtain certification by a qualified registered professional engineer that the containment building design meets the requirements of paragraphs (a) through (c) of this section. For units placed into operation prior to February 18, 1993, this certification must be placed in the facility's operating record (on-site files for generators who are not formally required to have operating records) no later than 60 days after the date of initial operation of the unit. After February 18, 1993, PE certification will be required prior to operation of the unit. Obtain and keep on-site a certification by a qualified professional engineer that the containment building design meets the requirements of paragraphs (a), (b), and (c) of this section.

TABLE 8.—OBSOLETE REGULATORY LANGUAGE BEING DELETED FOR INTERIM STATUS TREATMENT, STORAGE, AND DISPOSAL FACILITIES

CFR section	Regulatory requirement	Current regulatory language New regulatory requirement as amended by the Burden Reduction Rule
265.193(a)(2)	Tank, Systems: Containment and detection of releases.	For all existing tank systems used to and store or treat EPA Hazardous Waste Nos. F020, F021, F022, F023, F026, and F027, within two years after January 12, 1987. Section 265.193(a)(2) is being deleted.
265.193(a)(3)	Tank Systems: Containment and detection of releases.	For those existing tank systems of known and documentable age, within two years after January 12, 1987, or when the tank system has reached 15 years of age, whichever comes later. Section 265.193(a)(3) is being deleted.
265.193(a)(4)	Tank Systems: Containment and detection of releases.	For those existing tank systems for which the age cannot be documented, within eight years of January 12, 1987; but if the age of the facility is greater than seven years, secondary containment must be provided by the time the facility reaches 15 years of age, or within two years of January 12, 1987, whichever comes later. Section 265.193(a)(4) is being deleted.
265.314(a)	Land Fills: Special requirements for bulk and containerized liquids.	Bulk or non-containerized liquid waste or waste containing free liquids may be placed in a landfill prior to May 8, 1985. Section 265.314(a) is being deleted.
265.314(b)	Land Fills: Special requirements for bulk and containerized liquids.	Effective May 8, 1995, the placement of bulk or non-containerized liquid hazardous waste or hazardous waste containing free liquids (whether or not sorbents have been added) in any landfill is prohibited. The placement of bulk or non-containerized liquid hazardous waste or hazardous waste containing free liquids (whether or not sorbents have been added) in any landfill is prohibited.
265.314(g)	Land Fills: Special requirements for bulk and containerized liquids.	Effective November 8, 1985, the placement of any liquid which is not a hazardous waste in a landfill is prohibited unless the owner or operator of such landfill demonstrates to the Regional Administrator, or the Regional Administrator determines that: The placement of any liquid which is not a hazardous waste in a landfill is prohibited unless the owner or operator of such landfill demonstrates to the Regional Administrator, or the Regional Administrator determines that:
265.1100	Containment Buildings. Applicability.	The requirements of ths subpart apply to owners or operators who store or treat hazardous waste in units designed and operated under §265.1101 of this subpart. These provisions will become effective on February 18, 1993, although owner or operator may notify the Regional Administrator of his intent to be bound by this subpart at an earlier time. The owner or operator is not subject to the definition of land disposal in RCRA §3004(k) provided that the unit: The requirements of this subpart apply to owners or operators who store or treat hazardous waste in units designed and operated under §265.1101 of this subpart. The owner or operator is not subject to the definition of land disposal in RCRA §3004(k) provided that the unit:
265.1101(c)(2)	Containment Buildings. Design and Operating Standards.	Obtain certification by a qualified registered professional engineer that the containment building design meets the requirements of paragraphs (a) through (c) of this section. For units placed into operation prior to February 18, 1993, this certification must be placed in the facility's operating record (on-site files for generators who are not formally required to have operating records) no later than 60 days after the date of initial operation of the unit. After February 18, 1993, PE certification will be required prior to operation of the unit. Obtain and keep on-site a certification by a qualified professional engineer that the containment building design meets the requirements of paragraphs (a), (b), and (c) of this section.

TABLE 8.—OBSOLETE REGULATORY LANGUAGE BEING DELETED FOR INTERIM STATUS TREATMENT, STORAGE, AND DISPOSAL FACILITIES—Continued

CFR section	Regulatory requirement	Current regulatory language New regulatory requirement as amended by the Burden Reduction Rule
265.221(a)	Surface Impoundments: Design and operating requirements.	The owner or operator of each new surface impoundment unit on which construction commences after January operating 29, 1992, each lateral expansion of a surface impoundment unit on which construction commences after July 29, 1992, and each replacement of an existing surface impoundment unit that is to commence reuse after July 29, 1992 must install two or more liners and a leachate collection and removal system above and between such liners, and operate the leachate collection and removal systems, in accordance with §264.221(c), unless exempted under §264.221 (d), (e), or (f) of this chapter. "Construction commences" is as defined in §260.10 under "existing facility". The owner or operator of each new surface impoundment unit, each lateral expansion of a surface impoundment unit, and each replacement of an existing surface impoundment unit must install two or more liners and a leachate collection and removal system above and between such liners, and operate the leachate collection and removal systems, in accordance with §264.221(c), unless exempted under §264.221(d), (e), or (f) of this chapter.
265.301(a)	Land Fills: Design and operating requirements.	The owner or operator of each new and operating landfill unit on which construction commences after January 29, 1992, each lateral expansion of a landfill unit on which construction commences after July 29, 1992, and each replacement of an existing landfill unit that is to commence reuse after July 29, 1992 must install two or more liners and a leachate collection and removal system above and between such liners, and operate the leachate collection and removal systems, in accordance with §264.301 (d), (e), or (f) of this chapter. "Construction commences" is as defined in §260.10 under "existing facility." The owner or operator of each new landfill unit, each lateral expansion of a landfill unit, and each replacement of an existing landfill unit must install two or more liners and a leachate collection and removal system above and between such liners, and operate the leachate collection and removal system, in accordance with §264.301 (d), (e), or (f) of this chapter.

F. We Are Eliminating Selected Recordkeeping and Reporting Requirements That We Believe Provide Duplicative Information to EPA

1. We Are Eliminating the Requirement for Facilities To Notify That They Are in Compliance After a Release

We received comments that both supported and opposed the elimination of the notifications required by §§ 264.56(i) and 265.56(i). These notifications require the facility owner or operator to notify the Regional Administrator and appropriate state and local authorities after an emergency action has taken place, and that the facility is in compliance with §§ 264.56(h) and 265.56(h), respectively. Sections 264.56(h) and 265.56(h) require the facility emergency coordinator to ensure that no wastes that may be incompatible with the released material is treated, stored, or disposed of until cleanup procedures are completed, and that emergency equipment listed in the contingency plan is cleaned and fit for its intended use before operations are resumed. Several commenters generally supported the elimination of these notification provisions. Other commenters were opposed to eliminating these provisions because they thought that it was prudent for the regulatory agency to receive notification that a facility was ready to again manage hazardous waste after emergency measures were implemented and releases were cleaned up.

We have decided to finalize the elimination of this notification provision. The Regional Administrator and appropriate state and local authorities will still be getting a report 15 days after the emergency incident (as required in §§ 264.56(j) and 265.56(j)). This report will specify the details of the incident that required implementation of the contingency plan. In most cases, the incident is likely to be relatively minor, and operations may even be ready for resumption with the 15 days. The actions to be taken (*i.e.*, not handling incompatible waste and cleaning emergency equipment) are straightforward and it is not clear what value a simple notification would add. On the other hand, in major incidents the state would likely send personnel on-site and would be in a position to ensure that an appropriate response was taken before operations resumed. Therefore, we have decided to eliminate this notification requirement.

2. We Are Eliminating the Requirement for Facilities To Notify of Their Intent To Burn F020, F021, F022, F023, F026, and F027 Wastes

We proposed to eliminate the notification of intent to burn hazardous dioxin/furan wastes listed as F020, F021, F022, F023, F026 and F027. We viewed this as an unnecessary requirement because the facility is already permitted to burn these wastes, and there are already regulatory standards governing how the waste is burned.

Commenters generally supported our proposed change. Therefore, we are removing the notification requirement.

We inadvertently proposed to remove the entire paragraph (a)(2) of §264.343. We are merely removing the last sentence that referred to the notification of intent to burn listed dioxin/furan wastes.

3. We Are Eliminating the Requirement for Facilities To Notify if They Employ or Discontinue Use of the Alternative Valve Standard

The regulations in Subpart BB of RCRA deal with air emission standards for equipment leaks. They apply to owners and operators of facilities that treat, store, or dispose of hazardous waste with equipment that contains or

contacts hazardous waste with organic concentrations of at least 10 percent by weight. We proposed to eliminate the requirement for submitting notifications to the Regional Administrator with regard to the implementation of the alternative standards for valves in gas/vapor service or in light liquid service. Under the current regulations in §§ 264.1061(b)(1), (d) and 265.1061(b)(1) and (d), if an owner or operator decides to either: (1) Implement the alternative standard or (2) discontinue the use of the alternative standard, a written notification must be sent to the Regional Administrator. In the proposed rule, we stated that these notifications were an unnecessary requirement because §§ 264.1061(b)(2) and 265.1061(b)(2) require performance tests to be conducted (upon designation, annually, and as requested by the Regional Administrator) and their results kept on site once a decision is made to use the alternative valve standard. Several commenters disagreed with our position and suggested that facilities need to notify regulators when they elect to use alternative standards. Commenters further stated that without knowledge of the specification that facilities are using, regulators may not be able to effectively administer the standards and that this information may be required for regulators to address various permitting, compliance and enforcement actions at the facility. We remain unconvinced that these notifications are an essential element in our regulatory compliance regime. While we understand the commenters concerns, we believe that sufficient information and data will be available to the regulatory authority to monitor compliance with an alternative standard without these notifications.

4. We Are Eliminating the Requirement for Facilities To Notify if They Are Using Alternative Valve Work Practices

We proposed to eliminate the requirement to submit a notification to the Regional Administrator before implementing one of the alternative work practices specified in §§ 264.1062(b)(2) and (3) and 265.1062(b)(2) and (3). Under the current regulations, an owner or operator may elect to comply with one of two alternative work practices specified in the regulations. These alternatives are: (1) After two consecutive quarterly leak detection periods with the percentage of valves leaking equal to or less than 2 percent, an owner or operator may begin to skip one of the quarterly leak detection periods (*i.e.*, monitor for leaks once every six months) for the valves; or (2) after five consecutive quarterly leak detection periods with the percentage of valves leaking equal to or less than 2 percent, an owner or operator may be begin to skip three of the quarterly leak detection periods (*i.e.*, monitor for leaks once every year) for the valves.

The majority of the commenters agreed with the proposal. One commenter, however, argued that some technical review by the Agency should be warranted to approve this alternative standard. Upon review of the comment, we are unconvinced that the implementation of this alternative work practice needs technical review or oversight by the regulated authority. The alternative work practices described in the regulations are straightforward and the results of the leak detection periods will be maintained in the facility files as required under the recordkeeping requirements found in § 264.1064. Therefore, we are eliminating the need for these notifications.

TABLE 9.—RECORDKEEPING AND REPORTING REQUIREMENTS BEING DELETED FOR PERMITTED TREATMENT, STORAGE, AND DISPOSAL, FACILITIES

CFR section	Regulatory requirement
Deletion to 264.56	Contingency Plan and Emergency Procedures. Emergency Procedures.
264.56(i)	Notify Regional Administrator that facility is in compliance with § 265.56(h) (which requires that no waste that may be incompatible with the released material will be treated, stored, or disposed until cleanup is completed, and emergency equipment is made ready for use again) before resuming operations.
Deletion to 264.343	Incinerators. Performance standards.
264.343(a)(2)	Submit notification of intent to burn hazardous wastes F020, F021, F022, F023, F026, and F027.
Deletions to 264.1061	Air Emission Standards for Equipment Leaks. Alternative standards for valves in gas/vapor service or in light liquid service: percentage of valves allowed to leak.
264.1061(b)(1)	Submit notification to implement the alternative valve standard
264.1061(d)	Submit notification to discontinue the alternative valve standard.
Deletion to 264.1062	Air Emission Standards for Equipment Leaks. Alternative standards for valves in gas/vapor service or in light liquid service; skip period leak detection and repair.
264.1062(a)(2)	Submit notification to implement alternative work practices for valves.

TABLE 10.—RECORDKEEPING AND REPORTING REQUIREMENTS BEING DELETED FOR INTERIM STATUS TREATMENT, STORAGE, AND DISPOSAL FACILITIES

CFR section	Regulatory requirement
Deletion to 265.56	Contingency Plan and Emergency Procedures. Emergency Procedures.
265.56(i)	Notify Regional Administrator that facility is in compliance with § 265.56(h) (which requires that no waste that may be incompatible with the released material will be treated, stored, or disposed until cleanup is completed, and emergency equipment is made ready for use again) before resuming operations.
Deletions to 265.1061	Air Emission Standards for Equipment Leaks. Alternative standards for valves in gas/vapor service or in light liquid service: percentage of valves allowed to leak.
265.1061(b)(1)	Submit notification to implement the alternative valve standard.
265.1061(d)	Submit notification to discontinue the alternative valve standard.
Deletion to 265.1062	Air Emission Standards for Equipment Leaks. Alternative standards for valves in gas/vapor service or in light liquid service; skip period leak detection and repair.
265.1062(a)(2)	Submit notification to implement alternative work practices for valves.

G. We Are Permitting Decreased Inspection Frequency for Certain Hazardous Waste Management Units

RCRA regulations require generators and treatment, storage and disposal facilities to self-inspect their facilities to ensure that they are in compliance. The regulations include both facility-wide and unit- and equipment-specific inspection standards. Some of RCRA's regulations specify the inspection frequency.

Self-inspections are a vital component of an effective regulatory system. We recognize however, that the frequency of inspections has been a concern, and that in most cases (particularly where alternative approaches are employed) facilities are able to carry out formal inspections less frequently without sacrificing human health and environmental protection.

The Agency proposed a reduction in tank self-inspection frequency from daily to weekly for large quantity generator tanks and treatment, storage and disposal facilities. We also solicited comment on allowing further reduced inspection frequencies, on a case-by-case basis (as approved by the Regional Administrator or the state Director, as the context requires, or an authorized representative), for containers, containment buildings, and tanks. However, this proposal required that these inspections occur at least monthly. In proposing these changes, we suggested that decreased inspection frequencies should be based on factors such as: (1) A demonstrated commitment by facility management to sound environmental practices; (2) achievement of good management practices over the history of the facility—that is, having a record of sustained compliance with environmental laws and permit requirements; (3) a demonstrated commitment to continued environmental improvement; (4) a demonstrated commitment to public outreach and performance reporting; (5) the installation of automatic monitoring devices at the facility; and (6) the risk posed by the waste managed in the unit.

Many commenters supported the change from a daily to weekly inspection frequency for tanks. Commenters pointed out that the integrity and safety of hazardous waste tanks would not be compromised by reducing the daily inspection requirement to a weekly frequency. Several other commenters pointed out that hazardous waste storage tanks, which have secondary containment, are even more protectively designed than process tanks which handle the same chemicals. Other commenters, however, did not support any decrease in inspection frequency because of concerns that if inspection frequencies were decreased, the amount of time between a leak and its discovery would increase.

With regard to extending even further the inspection frequency, to at least once each month on a case-by-case basis, we received comments from the states expressing concern over the added administrative burden in implementing case-by-case changes to inspection frequencies.

Based on the comments from the proposed rule, we reconsidered whether to make case-by-case reduced inspections available to all generators because of the burden it might impose on authorized states to evaluate compliance with the criteria. In the October 29, 2003 NODA (68 FR 61662), we proposed reduced inspection frequencies, granted on a case-by-case basis, only for members of the National Environmental Performance Track Program, stating that, at a minimum, we believe that providing relief is appropriate for companies that are demonstrated "good performers." [9]

In the NODA, we also clarified that the reduced inspection frequency for tanks was intended to apply not just to the tanks, but to the complete tank systems, which include piping, pumps, valves and other associated equipment, also known as ancillary equipment (see §§ 264.193(f) and 265.193(f)). We also asked for comment on expanding the change to include tanks, not only at large quantity generator sites, but small quantity generator sites as well (see § 265.201(c)). Furthermore, we solicited comment on extending the reduced inspection frequencies, granted on a case-by-case basis, to areas subject to spills (see §§ 264.15(b)(4) and 265.15(b)(4)). We solicited comment on whether to grant this relief only to members of the National Environmental Performance Track Program in that we believe the risk from this change would be minimal at facilities that have met the requirements to be accepted into this program.

1. We Are Establishing Weekly Inspections for Certain Hazardous Waste Tank Systems at Permitted and Interim Status Facilities and at Large Quantity Generator Sites

We are changing the self-inspection frequencies for tank systems from daily to weekly at permitted and interim status treatment, storage and disposal facilities, as well as for large quantity generator (LQG) tank systems that are operated under certain conditions. Changing inspections for small quantity generator (SQG) tanks is discussed in section III.G.2 of this preamble. Tank system, as defined in § 260.10, means a hazardous waste storage or treatment tank and its associated ancillary equipment and containment system. The requirements for permitted, interim status, and LQG tank systems appear in §§ 264 and 265, subpart J. Daily inspections enable tank systems, subject to subpart J, to comply with the §§ 264.193(c) and 265.193(c) requirements to detect leaks and spills within 24 hours.

Our rule reduces inspections for: (1) Above ground portions of the tank system, if any, to detect corrosion or releases of waste; and (2) the construction materials and the area immediately surrounding the externally accessible portion of the tank system, including the secondary containment system (e.g., dikes) to detect erosion or signs of releases of hazardous waste (e.g., wet spots, dead vegetation). Reduced inspections will be allowed when either of two conditions are met: (1) Tank owners and operators employ leak detection equipment; or (2) in the absence of leak detection equipment, tank owners and operators employ established workplace practices that ensure that when any leaks or spills occur, they will be promptly identified, and promptly remediated. Owners and operators choosing one of these options to reduce inspection frequencies should document the option selected in their operating record. If the option selected is "established workplace practices," the owner and/or operator should document those practices in the facility's operating record.

Leak detection equipment must meet the respective requirements of §§ 264.193(c)(3) and 265.193(c)(3). It should be designed to alert facility personnel promptly to the presence of any leaks or spills (e.g., alarm systems) so that emergency and/or remedial action can be taken. (The existing subpart J tank regulations require secondary containment systems to be

[9] The National Environmental Performance Track Program is a voluntary EPA program that recognizes and rewards private and public facilities that demonstrate strong environmental performance beyond current requirements. The program is based on the premise that government should complement its existing programs and regulations with new tools and strategies that not only protect people and the environment, but also capture opportunities for reducing cost and spurring innovation. For more information and a closer look at the activities and accomplishments of Performance Track members to date, as well as member's goals for future achievements, please refer to the program Web site at *http://www.epa.gov/performancetrack.*

designed and operated to detect releases within 24 hours.) Leak detection systems were described in the proposed rule (67 FR 2527). But, while subpart J requires releases to be detected within 24 hours, the regulations do not specify the method of leak detection systems that must be used. For example, some facilities use daily visual inspections as a method of leak detection for their aboveground tanks, which is an acceptable practice. However, under the current tank system regulations, absent daily visual inspections, leak detection equipment that promptly notifies facility personnel of leaks or spills, must be used.

In the absence of leak detection equipment, established workplace practices must ensure that when any leaks or spills occur, they will be promptly identified and promptly remediated in compliance with §§ 264.193(c)(3) and (4) and 265.193(c)(3) and (4). When we say "established workplace practices," we mean practices that are documented and that describe how the facility is operated. (An example of established workplace practices could be the presence of an Environmental Management System that includes plans and practices to ensure that any releases are promptly identified, contained, and cleaned up.) Established workplace practices will most likely be put in place in situations, like that described by a state commenter, where aboveground tanks without leak detection exist and daily visual monitoring is the most common method of leak detection used. In cases such as these, lacking leak detection equipment, owners or operators would need to use workplace practices to identify releases, if they choose to reduce their inspection frequency.

A number of commenters noted that reducing inspection frequencies of §§ 264.195 and 265.195 should only be done if secondary containment is equipped with leak detection that notifies response personnel if releases occur. We partially agree with the commenters; however, as noted earlier, the rule also allows the facility operator to institute work practices to ensure prompt detection of a release. For example, if the tank system is in an area frequented by employees, where releases will be immediately obvious, all employees might be trained to watch for releases and report them. In other situations, an employee might be assigned to check secondary containment on a daily basis without conducting a full tank system "inspection."

We received several comments from industry that the current daily inspection requirements are a large burden for the regulated community, and that weekly inspections would provide welcome relief. One commenter noted that the majority of printers that have tanks for collecting hazardous waste have small tanks and they are generally located indoors. Any release from the tank would be detected almost immediately and the extension of mandatory inspection frequency would greatly reduce the administrative burden associated with using these types of collection tanks. In this case, the facility might not have leak detection equipment, but standard work practices might require all employees to notify appropriate facility personnel if they observe a release from the tanks. Given the nature of the facility described by the commenter, this would likely constitute a work practice sufficient to ensure prompt detection of a release. Conversely, we also received other industry comments suggesting that while they liked the flexibility of the reduced inspections, they offered that they probably would not reduce their own inspection frequency.

A state commenter argued that a basic principle of RCRA is prevention, including preventing a major release from a waste management unit and that the proposed rule appears primarily guided by a desire to project an image of providing a "burden reduction" for the regulated community, while disregarding prevention mechanisms. The commenter further stated that the chance of a release occurring and going undetected is greatly increased by allowing for weekly inspections of tank systems. The commenter believes the current requirement for daily inspections of tank systems provides a reasonable means to detect and minimize release of hazardous waste in a timely manner and the commenter further stated that the requirement for daily inspection of tank systems has not been a significant burden on the regulated community. We question this commenter's conclusion. By requiring owners and operators who wish to change the self-inspection frequencies for tanks, to use either leak detection or work place practices, we believe it is unlikely that releases from tanks will go undetected. The use of either leak detection systems or established workplace practices should assure that releases are promptly detected, and that the appropriate personnel are notified so that releases can be stopped and cleaned up. According to § 264.196, upon detection of a leak, either through the leak detection system or visual observation, the owner or operator of the tank system must immediately stop the flow of hazardous waste, determine and rectify the cause of the leak, remove the waste, and contain releases to the environment.

It is important to note that we are not changing the existing requirement, found in § 264.195(a)(2) and § 265.195(a)(3)), that data gathered from monitoring and leak detection equipment (e.g., pressure or temperature gauges, monitoring wells) must be inspected at least once each operating day to ensure that the tank system is being operated according to its design. We believe that this requirement is necessary in order to ensure compliance with § 264.193(c) and § 265.193(c), which require the detection of leaks and spills within 24 hours. In addition, keeping this requirement supports the new reduced inspection requirements that we are putting in place today, by providing further information about any releases that may occur.

As a final matter, several commenters to the proposed rule suggested changing the inspection frequencies for ancillary equipment, specifically citing §§ 264.193(f) and 265.193(f). (These requirements specify that ancillary equipment must have secondary containment, except in four instances, each involving daily visual inspections for leaks.) While most commenters provided little information to support making the change, one commenter did argue that if the proposed changes to §§ 264.195 and 265.195 were finalized, the existing provisions in §§ 264.193(f) and 265.193(f), if not also changed, would be inconsistent.

As background, the October 29, 2003 NODA requested comment on expanding the proposed rule to include ancillary equipment at LQG and SQG sites. The NODA referenced the regulations at §§ 264.193(f) and 265.193(f), suggesting making the change would be consistent with our intent, as discussed in the proposed rule. Because today's rule changes the inspection frequencies for tank systems provided with secondary containment, where leak detection equipment or workplace practices are used, as discussed previously, any ancillary equipment associated with such tank systems would, therefore, be eligible for reduced inspections.

We considered allowing ancillary equipment without secondary containment, as described at §§ 264.193(f)(1)–(4) and 265.193(f)(1)–(4), to be visually inspected weekly instead of daily. While most of the commenters supported this change,

upon further analysis we now conclude that expanding the rule to include ancillary equipment without secondary containment is not consistent with how the final rule addresses reduced inspection frequency for tank systems. The proposed rule discussed reducing inspection frequencies for tanks and tank systems because of, among other reasons, the presence of secondary containment. Allowing ancillary equipment without secondary containment to change from daily visual inspections to weekly visual inspections would not be consistent with our approach. We are including regulatory language in §§ 264.194(d) and 265.195(c) to say that ancillary equipment that is not provided with secondary containment, as described in §§ 264.193(f)(1)–(4), must be inspected at least once each operating day.

We would like to note that there are instances where tanks and tanks systems are located within buildings, and where the building itself provides secondary containment. In cases where ancillary equipment is located inside a building that has been determined to provide secondary containment, and either leak detection systems or established workplace practices exist to identify leaks and spills, then the regulatory criteria are met and that ancillary equipment may be inspected weekly. For example, in a case where ancillary equipment inside a building does not have double walls or leak detection, this ancillary equipment would still be eligible for weekly inspections if the building serves as secondary containment, and if the area is frequented by employees whereby releases will be immediately obvious and the employees will promptly identify and remediate leaks and spills.

In cases involving buildings serving as secondary containment, authorized states necessarily have the ultimate authority to make the determination that secondary containment requirements are met (taking into account all relevant site-specific considerations).

2. We Are Establishing Weekly Inspections for SQG Hazardous Waste Tank Systems With Secondary Containment

While the previous discussion addressed changes in the inspection frequency for certain tank systems at permitted and interim status facilities, and LQG sites, today's rule also changes the inspection frequency for certain tank systems at SQG sites. The requirements for SQG tanks are found in 40 CFR 265.201(b).[10]

Under the current regulations, generators of between 100 and 1,000 kg/mo accumulating hazardous waste in tanks must inspect at least once each operating day, if applicable; (1) discharge control equipment (e.g., waste feed cutoff systems, by-pass systems, and drainage systems); (2) data gathered from monitoring equipment (*e.g.*, pressure and temperature gauges); and (3) the level of waste in the tank. In addition, at least weekly, generators must also inspect: (1) The construction materials of the tank to detect corrosion or leaking of fixtures or seams; and (2) the construction materials of, and the area immediately surrounding, discharge confinement structures (e.g., dikes) to detect erosion or obvious signs of leakage (e.g., wet spots or dead vegetation).

While § 265.201 does not require SQGs to be equipped with secondary containment, nor leak detection, under today's rule, SQG tank system owners and operators who wish to reduce their inspection frequency may do so if these tank systems are provided with secondary containment with either leak detection equipment or established workplace practices that ensure prompt detection of releases, as described above for other tank systems. Owners and operators choosing one of these options to reduce inspection frequencies should document the option selected in their operating record. If the option selected is "established workplace practices," the owner and/or operator should document those practices in the facility's operating record.

In the proposal, we received comments suggesting that we expand the proposed reduction in tank self-inspection frequency to include tanks located at small quantity generator sites (see § 265.201(c)) and ancillary equipment (see § 265.193(f)[11]). This change would affect only three of the five SQG inspection requirements: for discharge control equipment (§ 265.201(c)(1)); data gathered from monitoring equipment (§ 265.201(c)(2)); and monitoring the level of waste in the tank (§ 265.201(c)(3)), since the last two inspection requirements (§§ 265.201(c)(4) and (c)(5)) are already done on a weekly basis. We stated in the NODA that changing these inspection frequencies would be consistent with our intent to establish weekly inspections for all tank systems.

One state commenter argued that tanks can and frequently do fail abruptly and with little or no warning, losing most or all of their contents in a very short period of time and if the rule were promulgated as proposed, it might be a week or longer before leaks of any size were discovered and remediation begun. The commenter further reasoned that for those tanks without secondary containment (e.g., SQGs), waiting such a long time for remediation efforts may lead to extensive environmental damage. We acknowledge the commenter's concerns and support the rapid remediation of leaks; we believe that the controls we are promulgating today will adequately prevent such an occurrence, even for SQGs.

One commenter did state that, although he did not object to allowing small quantity generators reduced tank inspection frequencies, he noted that reducing inspection frequencies will not provide any additional reduction in the recordkeeping/reporting burden for small quantity generators who are not subject to §§ 264.15 and 265.15 and are not required to maintain a schedule or a record of inspections. We agree that § 265.201 does not require SQGs to record inspections. Burden reduction would come from the time saved (person-hours) from reduced inspections.

Several states were not in favor of reduced inspection frequency for small quantity generators. One commenter stated that EPA has not provided any data that suggest that the reduced frequency of tank inspections is as protective as the intent of the current standard which as stated in 51 FR 25454, July 14, 1986 is to "* * * enable the detection of releases or potential

[10] The requirements for SQG tanks were finalized on March 24, 1986 (51 FR 10146), and with the July 14, 1986 final tank regulations (51 FR 25422), codified at § 265.201. Discussion in the March 1986 rule explains how the SQG requirements were developed, as distinct from the requirements for tanks at LQG sites. The rule states: "Congress anticipated reducing administrative requirements, such as reporting and recordkeeping, as a means to reduce impacts on the 100–1000 kg/mo generators. Thus, EPA proposed to relieve these generators of some Part 262 standards that are administrative in nature, while retaining all existing technical standards. The relief was only provided to generators who accumulate on-site for the statutorily prescribed periods, because, given that the amount of waste accumulated would necessarily be limited, the relative risk from releases of such waste would be less than that from the unlimited amounts of waste accumulated by off-site facilities." (51 FR 10149).

[11] While the Agency solicited comment on reducing the inspection frequency for ancillary equipment for SQGs, the referenced regulation, § 265.193(f) does not apply to tank systems at SQG sites, only the requirements found in § 265.201(c) apply to SQG tank systems. Therefore, the Agency is not pursuing changes to § 265.193(f) that would affect SQGs. As discussed above, the regulatory changes we are making today apply to SQG tank systems, which include ancillary equipment.

releases at the earliest possible time." Another commenter further argued that reduced tank inspection frequency should not be afforded to small quantity generators unless their tank systems are upgraded to meet additional standards and that currently SQGs only have to inspect their tank systems for proper operations controls daily. SQGs are not required to do any type of additional leak detection, except for the weekly requirements already in place. Since SQGs are not required to provide secondary containment, the operating day inspections assist in protecting from a release or potential release. Other commenters argued that if SQGs wish to receive this reduced inspection frequency, they should comply with the same secondary containment requirements as large quantity generators and install an automated leak detection equipment that alerts a person designated to respond. We agree, in part, with the commenters. SQG tanks historically have less stringent requirements than LQGs, permitted, and interim status tanks. But, while existing SQG tanks are not required to have secondary containment, in order to enjoy reduced inspection frequencies under today's rule, tanks must have secondary containment with leak detection, or have secondary containment and workplace practices in use that promptly identify leaks and spills.

3. We Are Allowing Members of the National Environmental Performance Track Program To Apply for an Adjustment to the Frequency of Inspections for Certain Hazardous Waste Units and Areas

In addition to allowing a change in the inspection frequency for selected tank systems, we also proposed to allow on a case-by-case basis, less frequent self-inspections for tank systems, container storage areas, and containment buildings. Under our current regulations, container storage areas and containment buildings must be inspected weekly. (See §§ 264.174, 265.174, 264.1101(c)(4), and 265.1101(c)(4).)

Based on comments received on the proposal, we reconsidered whether to make such a change available to all generators because of the burden it would impose on authorized states to evaluate compliance with the criteria. As stated in the October 29, 2003 NODA (68 FR 61662), we believe that providing relief is appropriate for companies that are demonstrated "good performers" and we solicited comment on limiting this provision to member companies of the National Environmental Performance Track Program, as well as extending reduced inspection frequencies, granted on a case-by-case basis, to areas subject to spills (see § 264.15(b)(4)).

In today's rule we are finalizing this provision—the ability to file a case-by-case application for further reduced self-inspection frequencies—to facilities that are members of the National Environmental Performance Track Program. Performance Track member facilities are provided the opportunity to reduce self-inspections of tank systems, containers, containment buildings, and areas subject to spills to a frequency of at least once each month.

Performance Track members must apply to the regulatory agency for approval before implementing a reduced inspection frequency schedule.[12] The Performance Track facility must submit an application to the regulatory authority identifying itself as a member of the National Environmental Performance Track Program and request a reduction in self inspection frequency. For those members that are also permitted treatment, storage and disposal facilities, the application must be in the form of a Class 1 permit modification with prior approval. The Performance Track member facility must request reduced inspections, for no less than once each month, for any of the waste management units identified in today's rule (including tank systems, containers, containment buildings, and areas subject to spills). (Only one application per Performance Track member facility is required.) After the application is received, the Director has 60 days to approve or deny the application, in writing. The Director also may choose to extend this 60 day deadline, if more time is needed to review the application (e.g., in the case where an on-site inspection is needed or a more in-depth analysis of the application is warranted.) If the application is approved, the notification will identify the management units approved for reduced frequency of inspections, as well as the time interval between inspections (at a minimum of one inspection each month.) This notice must be placed in the facility's operating record.

The Performance Track member facility should consider the application approved after 60 days if the Director does not: (1) Deny the application, in writing; or (2) notify, in writing, the Performance Track member facility of an extension to the 60-day deadline. In these situations, the Performance Track member facility must adhere to the revised inspection schedule outlined in their application and keep a copy of the application in the facility's operating record.

It is expected that Performance Track facilities would have an EMS providing sufficient oversight to prevent and detect leaks and spills. In addition, facilities that applied for Performance Track would have conducted an Environmental Management System (EMS) Independent Assessment.[13] The assessment must determine whether the facility regularly monitors and measures its key operations that can have a significant impact on the environment, and records this information. Therefore, through the use of EMSs and workplace practices, we would expect Performance Track facilities to be able to prevent and detect leaks and spills. Providing Performance Track member facilities with the option for reduced inspection frequencies does not mean we are reducing the requirements for the owner or operator to detect leaks and spills; providing reduced inspection for Performance Track member facilities acknowledges that these facilities have established controls and procedures to prevent releases and to respond promptly if and when they occur. The Agency believes it is important to recognize the difference in the need for oversight of facilities that are top environmental performers which have developed comprehensive environmental management systems and who have a track record of effective self-oversight.

Any Performance Track member facility that discontinues its membership in Performance Track or is terminated from the program must immediately notify the Director, in writing of its change in status (i.e., they are no longer a Performance Track member facility). These facilities must revert back to the "non-Performance

[12] In the proposed rule (67 FR at 2527), the Agency made reference to a commenter's suggestion that inspection frequency changes should be self-implementing. The example given by the commenter outlined an option where an inspection schedule should be deemed approved if EPA does not specifically deny the request in writing within 30 days. At that time, we stated that one of our principle objectives for this burden reduction change, was to ensure that the regulatory agencies made the decision to decrease inspection frequencies and as such, we were not considering self-implementing alternatives. While we still maintain that regulatory agencies should make these decisions on a case-by-case basis, upon further consideration, we believe it is also important to streamline the application process by establishing a timetable for application/permit modification review.

[13] For more information on the Independent Assessment Criteria for EMSs, see *http://www.epa.gov/performancetrack/ind_assessment.htm.*

Track member" inspection frequency within seven calendar days. The facility must place in their operating record a dated copy of this notification. In cases where the Performance Track member is a permitted TSDF, the Agency is requiring that the permit modification to allow the reduced inspection frequency contain a "sunset" clause, in case the facility's membership in Performance Track ends. If written without a "sunset" clause, an approved permit modification allowing a reduced inspection frequency could otherwise "shield" the facility from violation if it ceases to be a Performance Track member. Therefore, we are requiring that the Class 1 modification request contain specific language stating that the reduced frequency is for as long as the facility remains a Performance Track member. The language must say that if the facility ceases to be a Performance Track member facility, it must revert to the "non-Performance Track" inspection frequency within seven calendar days after membership in Performance Track ends.

Sections a. through d. below discuss in more detail the Agency's basis for decisions on inspection frequency for areas subject to spills, containers, tank systems, and containment buildings at Performance Track member facilities.

a. *Performance Track: Reduced Inspection Frequency for Areas Subject to Spills.* The general inspection requirements of §§ 264.15 and 265.14, require that areas subject to spills, such as loading and unloading areas, must be inspected daily, while in use. These inspections are to identify malfunctions and deterioration, operator errors, and discharges which may be causing—or be leading to—(1) a release of hazardous waste constituents to the environment, or (2) a threat to human health. In response to a comment in the 2002 proposal, the October 29, 2003 NODA (68 FR 61662) considered reducing inspection frequencies, granted on a case-by-case basis, for areas subject to spills. We also solicited comment on whether to grant this relief only to Performance Track member facilities, stating that the risk from this change is minimal at facilities that have met the requirements to be accepted into the Performance Track Program. We received two comments on this issue; one commenter supported the proposal, and one did not . The commenter that opposed the proposal provided no explanation or justification for its position. The supporting commenter stated that activities that may cause spills "usually allow for the spills to be easily detected and quickly cleaned up. More frequent inspections are unlikely to result in quicker spill detection."

In general, we do not believe that such a change to the regulation is appropriate for all facilities, for the reasons laid out above. However, we believe the risk from this change is minimal at facilities that have met the requirements to be accepted into the National Environmental Performance Track Program. Therefore, we have decided to extend inspection frequencies for no less than once each month, at areas subject to spills, but only for facilities that are members of the National Environmental Performance Track Program that have received prior approval from the regulatory agency.

b. *Performance Track: Reduced Inspection Frequency for Containers.* Sections 264.174 and 265.174 require owners or operators to inspect, at least weekly, areas where containers holding hazardous waste are stored, looking for leaking containers and for deterioration of containers and the containment system caused by corrosion or other factors. We proposed to allow case-by-case decreased inspection frequencies for containers.

The October 29, 2003 NODA (68 FR 61662) addressed comments received on the 2002 proposal. Based on the comments from the proposal, the NODA reconsidered whether to make case-by-case reduced self-inspections available to all generators because of the burden it might impose on authorized states to evaluate compliance with the criteria. That is, making such a change available to all generators would likely impose a substantial burden on the states or EPA in order to evaluate whether an applicant facility met the criteria. Such a burden is clearly in opposition to the intent of today's rule. Finally, the Agency stated clearly that "at a minimum, we believe that providing relief is appropriate for companies that are demonstrated good performers." (68 FR 61665.)

The Agency received comments on this issue that supported the application of this provision to Performance Track members. Other comments stated that this provision should be made available to all facilities with a demonstrated record of good compliance, with some type of demonstrated top performance, or by meeting the proposed criteria.

The Agency considered all comments received on this issue and has decided to finalize a reduced self-inspection requirement to §§ 264.174 and 265.174 available only to members of the National Environmental Performance Track Program. The reason for this decision is that case-by-case determinations for all hazardous waste facilities would significantly increase the burden associated with providing this benefit to all facilities. Performance Track member facilities may apply to their regulatory agency for a reduction in self-inspection frequency, for no less thanonce each month, for containers and for areas where containers holding hazardous waste are stored.

c. *Performance Track: Reduced Inspection Frequency for Tank Systems.* Today, we are changing the self-inspection frequencies for tank systems from daily to no less than once each month for tank systems, granted on a case-by-case basis, for members of the National Environmental Performance Track Program when operating under certain conditions.[14] This includes Performance Track member facilities that are either permitted TSDFs, interim status TSDFs, large quantity generators (LQGs), and/or small quantity generators (SQGs).

Today's rule allows Performance Track member facilities to apply to the regulatory agency for reduced tank system self-inspection frequency, of no less than once each month when either of two conditions are met: (1) When tank owners and operators employ leak detection equipment, or (2) when in the absence of leak detection equipment, owners and operators of tank systems employ workplace practices that ensure that when any leaks or spills occur, they will be promptly identified and remediated. Performance Track member facilities choosing one of these options to reduce inspection frequencies, should identify the option selected as part of its application to the regulatory agency.

Small quantity generator (SQG) tank systems are subject to separate requirements, found in 40 CFR 265.201. Today's rulemaking also allows National Environmental Performance Track members to apply to the regulatory agency for reduced self-inspection frequencies for SQG tank systems under § 265.201(b) when they meet either one of the two conditions described above.

d. *Performance Track: Reduced Inspection Frequency for Containment*

[14] As previously discussed, we intended to include a broad applicability for tank systems in our proposed rule; however, the proposal did not clearly address the point. We clarified in the October 29, 2003 NODA (68 FR 61662) that the proposal was meant to apply not just to the tanks, but to the complete tank systems (i.e., ancillary equipment). Complete tank systems were defined as including piping, pumps, valves and other associated equipment. Commenters were generally supportive of this change. Therefore, we are applying this provision to complete tank systems, except to ancillary equipment without secondary containment as described at §§ 264.193(f)(1)–(4) and 265.193(f)(1)–(4).

Buildings. We proposed to allow case-by-case decreased inspection frequencies for containment buildings. As stated generally above, the intent was to offer this provision only to the safest and best performing facilities. In the October 29, 2003 NODA (68 FR 61662), we solicited comment on whether to limit the reduced inspection frequency for containment buildings to member facilities of the National Environmental Performance Track Program. Again, for the same reasons stated above, we decided to limit §§ 264.1101 and 265.1101 to Performance Track member facilities.

TABLE 11.—DECREASED INSPECTION FREQUENCIES FOR HAZARDOUS WASTE MANAGEMENT UNITS AT PERMITTED HAZARDOUS WASTE FACILITIES

CFR section	Regulatory requirement	Current regulatory language New regulatory language as amended by the Burden Reduction Rule
260.10	Hazardous Waste Management System: Definitions.	No regulatory definition currently exists. Performance Track member facility means a facility which has been accepted by EPA for membership in the National Environmental Performance Track Program and is still a member of the Program. The National Environmental Performance Track Program is a voluntary, facility based, program for top environmental performers. Facility members must demonstrate a good record of compliance, past success in achieving environmental goals, and commit to future specific quantified environmental goals, environmental management systems, local community outreach, and annual reporting of measurable results.
264.15(b)(4)	General Facility Standards: General Inspection Requirements.	The frequency of inspection may vary for the items on the schedule. However, the frequency should be based on the rate of deterioration of the equipment and the probability of an environmental or human health incident if the deterioration, malfunction, or any operator error goes undetected between inspections. Areas subject to spills, such as loading and unloading areas, must be inspected daily when in use. At a minimum, the inspection schedule must include the items and frequencies called for in §§ 264.174, 264.193, 264.195, 264.226, 264.254, 264.278, 264.303, 264.347, 264.602, 264.1033, 264.1052, 264.1053, 264.1058, and 264.1083 through 264.1089 of this part, where applicable. The frequency of inspection may vary for the items on the schedule. However, the frequency should be based on the rate of deterioration of the equipment and the probability of an environmental or human health incident if the deterioration, malfunction, or operator error goes undetected between inspections. Areas subject to spills, such as loading and unloading areas, must be inspected daily when in use, except for Performance Track member facilities, that may inspect at least once each month, upon approval by the Director, as described in paragraph (b)(5) of this section. At a minimum, the inspection schedule must include the items and frequencies called for in §§ 264.174, 264.193, 264.195, 264.226, 264.254, 264.278, 264.303, 264.347, 264.602, 264.1033, 264.1052, 264.1053, 264.1058, and 264.1083 through 264.1089 of this part, where applicable.
264.15(b)(5)	General Facility Standards: General Inspection Requirements.	No regulatory language currently exists. Performance Track member facilities that choose to reduce their inspection frequency must: (i) Submit a request for a Class I permit modification with prior approval to the Director. The modification request must identify the facility as a member of the National Environmental Performance Track Program and identify the management units for reduced inspections and the proposed frequency of inspections. The modification request must also specify, in writing, that the reduced inspection frequency will apply for as long as the facility is a Performance Track member facility, and that within seven calendar days of ceasing to be a Performance Track member, the facility will revert to the non-Performance Track inspection frequency. Inspections must be conducted at least once each month. (ii) Within 60 days, the Director will notify the Performance Track member facility, in writing, if the request is approved, denied, or if an extension to the 60-day deadline is needed. This notice must be placed in the facility's operating record. The Performance Track member facility should consider the application approved if the Director does not: (1) deny the application; or (2) notify the Performance Track member facility of an extension to the 60 day deadline. In these situations, the Performance Track member facility must adhere to the revised inspection schedule outlined in its request for a Class I permit modification and keep a copy of the application in the facility's operating record. (iii) Any Performance Track member facility that discontinues its membership or is terminated from the program must immediately notify the Director of its change in status. The facility must place in the operating record a dated copy of this notification and revert back to the non-Performance Track inspection frequencies within seven calendar days.
264.174	Use and Management of Containers: Inspections.	At least weekly, the owner or operator must inspect areas where containers are stored, looking for leaking containers, and for deterioration of containers and the containment system caused by corrosion or other factors.

TABLE 11.—DECREASED INSPECTION FREQUENCIES FOR HAZARDOUS WASTE MANAGEMENT UNITS AT PERMITTED HAZARDOUS WASTE FACILITIES—Continued

CFR section	Regulatory requirement	Current regulatory language New regulatory language as amended by the Burden Reduction Rule
264.195	Tank Systems: Inspections	At least weekly, the owner or operator must inspect areas where containers are stored, except for Performance Track member facilities, that may conduct inspections at least once each month, upon approval by the Director. To apply for reduced inspection frequencies, the Performance Track member facility must follow the procedures described in §264.15(b)(5) of this part. The owner or operator must look for leaking containers and for deterioration of containers and the containment system caused corrosion or other factors. (b) The owner or operator must inspect at least once each operating day: (1) Above ground portions of the tank system, if any to detect corrosion or releases of waste; (2) Data gathered from monitoring and leak detection equipment (e.g., pressure or temperature gauges, monitoring wells) to ensure that the tank system is being operated according to its design; and (3) The construction materials and the area immediately surrounding the externally accessible portion of the tank system, including the secondary containment system (e.g., dikes) to detect erosion or signs of releases of hazardous waste (e.g., wet spots, dead vegetation). [**Note:** Section 264.15(c) requires the owner or operator to remedy any deterioration or malfunction he finds. Section 264.196 requires the owner or operator to notify the Regional Administrator within 24 hours of confirming a leak. Also, 40 CFR part 302 may require the owner or operator to notify the National Response Center of a release.] (b) The owner or operator must inspect at least once each operating day data gathered from monitoring and leak detection equipment (e.g., pressure or temperature gauges, monitoring wells) to ensure that the tank system is being operated according to its design; (c) In addition, except as noted under paragraph (d) of this section, the owner or operator must inspect at least once each operating day: (1) Above ground portions of the tank system, if any to detect corrosion or releases of waste; (2) The construction materials and the area immediately surrounding the externally accessible portion of the tank system, including the secondary containment system (e.g., dikes) to detect erosion or signs of releases of hazardous waste (e.g., wetspots, dead vegetation). (d) Owners or operators of tank systems that either use leak detection equipment to alert facility personnel to leaks, or implement established workplace practices to ensure leaks are promptly identified, must inspect at least weekly those areas described in paragraphs (c)(1) and (c)(2) of this section. Use of the alternate inspection schedule must be documented in the facility's operating record. This documentation must include a description of the established workplace practices at the facility. (e) Performance Track member facilities may inspect on a less frequent basis, upon approval by the Director, but must inspect at least once each month. To apply for a less than weekly inspection frequency, the Performance Track member facility must follow the procedures described in §264.15(b)(5). (f) Ancillary equipment that is not provided with secondary containment, as described in §264.193(f)(1)–(4), must be inspected at least once each operating day. [**Note:** Section 264.15(c) requires the owner or operator to remedy any deterioration or malfunction he finds. Section 264.196 requires the owner or operator to notify the Regional Administrator within 24 hours of confirming a leak. Also, 40 CFR part 302 may require the owner or operator to notify the National Response Center of a release.]
264.1101(c)(4)	Containment Buildings: Design and Operating Standards.	Inspect and record in the facility's operating record, at least once every seven days, data gathered from monitoring and leak detection equipment as well as the containment building and the area immediately surrounding the containment building to detect signs of releases of hazardous waste. Inspect and record in the facility's operating record, at least once every seven days, except for Performance Track member facilities that must inspect at least once each month, upon approval by the Director, data gathered from monitoring and leak detection equipment as well as the containment building and the area immediately surrounding the containment building to detect signs of releases of hazardous waste. To apply for reduced inspection frequency, the Performance Track member facility must follow the procedures described in §264.15(b)(5) of this part.

TABLE 12.—DECREASED INSPECTION FREQUENCIES FOR HAZARDOUS WASTE MANAGEMENT UNITS AT INTERIM STATUS FACILITIES

CFR section	Regulatory requirement	Current regulatory language New regulatory language as amended by the Burden Reduction Rule
260.10	Hazardous Waste Management System: Definitions.	No regulatory definition currently exists. Performance Track member facility means a facility that has been accepted by EPA for membership in the National Environmental Performance Track Program and is still a member of the Program. The National Environmental Performance Track Program is a voluntary, facility based, program for top environmental performers. Facility members must demonstrate a good record of compliance, past success in achieving environmental goals, and commit to future specific quantified environmental goals, environmental management systems, local community outreach, and annual reporting of measurable results.
265.15(b)(4)	General Facility Standards: General Inspection Requirements.	The frequency of inspection may vary for the items on the schedule. However, the frequency should be based on the rate of deterioration of the equipment and the probability of an environmental or human health incident if the deterioration, malfunction, or any operator error goes undetected between inspections. Areas subject to spills, such as loading and unloading areas, must be inspected daily when in use. At a minimum, the inspection schedule must include the items and frequencies called for in §§ 265.174, 265.193, 265.195, 265.226, 265.260, 265.278, 265.304, 265.347, 265.377, 265.403, 265.1033, 265.1052, 265.1053, 265.1058 and 265.1084 through 265.1090 of this part, where applicable. The frequency of inspection may vary for the items on the schedule. However, the frequency should be based on the rate of deterioration of the equipment and the probability of an environmental or human health incident if the deterioration, malfunction, or operator error goes undetected between inspections. Areas subject to spills, such as loading and unloading areas, must be inspected daily when in use, except for Performance Track member facilities, that must inspect at least once each month, upon approval by the Director, as described in paragraph (b)(5) of this section. At a minimum, the inspection schedule must include the items and frequencies called for in §§ 265.174, 265.193, 265.195, 265.226, 265.260, 265.278, 265.304, 265.347, 265.377, 265.403, 265.1033, 265.1052, 265.1053, 265.1058 and 265.1084 through 265.1090 of this part, where applicable.
265.15(b)(5)	General Facility Standards: General Inspection Requirements..	No regulatory language currently exists. Performance Track member facilities that choose to reduce their inspection frequency must: (i) Submit an application to the Director. The application must identify the facility as a member of the National Environmental Performance Track Program and identify the management units for reduced inspections and the proposed frequency of inspections. Inspections must be conducted at least once each month. (ii) Within 60 days, the Director will notify the Performance Track member facility, in writing, if the application is approved, denied, or if an extension to the 60-day deadline is needed. This notice must be placed in the facility's operating record. The Performance Track member facility should consider the application approved if the Director does not: (1) deny the application; or (2) notify the Performance Track member facility of an extension to the 60-day deadline. In these situations, the Performance Track member facility must adhere to the revised inspection schedule outlined in its application and keep a copy of the application in the facility's operating record. (iii) Any Performance Track member facility that discontinues its membership or is terminated from the program must immediately notify the Director of its change in status. The facility must place in the operating record a dated copy of this notification and revert back to the non-Performance Track inspection frequencies within seven calender days.
265.174	Use and Management of Containers: Inspections.	The owner or operator must inspect areas where containers are stored, at least weekly, looking for leaks and for deterioration caused by corrosion or other factors. At least weekly, the owner or operator must inspect areas where containers are stored, except Performance Track member facilities, that must conduct inspections at least once each month, upon approval by the Director. To apply for reduced inspection frequency, the Performance Track member facility must follow the procedures described in §265.15(b)(5) of this part. The owner or operator must look for leaking containers and for deterioration of containers and the containment system caused by corrosion or other factors.
265.195	Tank Systems: Inspections.	(a) The owner or operator must inspect, where present, at least once each operating day: (1) Overfill/spill control equipment (e.g., waste-feed cutoff systems, bypass systems, and drainage systems) to ensure that it is in good working order; (2) Above ground portions of the tank system, if any to detect corrosion or releases of waste; (3) Data gathered from monitoring and leak detection equipment (e.g., pressure or temperature gauges, monitoring wells) to ensure that the tank system is being operated according to its design; and

TABLE 12.—DECREASED INSPECTION FREQUENCIES FOR HAZARDOUS WASTE MANAGEMENT UNITS AT INTERIM STATUS FACILITIES—Continued

CFR section	Regulatory requirement	Current regulatory language / New regulatory language as amended by the Burden Reduction Rule
		(4) The construction materials and the area immediately surrounding the externally accessible portion of the tanks system, including the secondary containment system (e.g., dikes) to detect erosion or signs of releases of hazardous waste (e.g., wet spots, dead vegetation). **Note:** Section 265.15(c) requires the owner or operator to remedy any deterioration or malfunction he finds. Section 265.196 requires the owner or operator to notify the Regional Administrator within 24 hours of confirming a release. Also, 40 CFR part 302 may require the owner or operator to notify the National Response Center of a release. (a) The owner or operator must inspect, where present, at least once each operating day, data gathered from monitoring and leak detection equipment (e.g., pressure or temperature gauges, monitoring wells) to ensure that the tank system is being operated according to its design. (b) Except as noted under paragraph (c) of this section, the owner or operator must inspect at least once each operating day: (1) Overfill/spill control equipment (e.g., waste-feed cutoff systems, bypass systems, and drainage systems) to ensure that it is in good working order; (2) Above ground portions of the tank system, if any, to detect corrosion or releases of waste; and (3) The construction materials and the area immediately surrounding the externally accessible portion of the tank system, including the secondary containment system (e.g., dikes) to detect erosion or signs of releases of hazardous waste (e.g., wet spots, dead vegetation). (c) Owners or operators of tank systems that either use leak detection equipment to alert facility personnel to leaks, or implement established workplace practices to ensure leaks are promptly identified, must inspect at least weekly those areas described in paragraphs (b)(1)–(3) of this section. Use of the alternate inspection schedule must be documented in the facility's operating record. This documentation must include a description of the established workplace practices at the facility. (d) Performance Track member facilities may inspect on a less frequent basis, upon approval by the Director, but must inspect at least once each month. To apply for a less than weekly inspection frequency, the Performance Track member facility must follow the procedures described in § 265.15(b)(5). (e) Ancillary equipment that is not provided with secondary containment, as described in § 265.193(f)(1)–(4), must be inspected at least once each operating day. **Note:** Section 265.15(c) requires the owner or operator to remedy any deterioration or malfunction he finds. Section 265.196 requires the owner or operator to notify the Regional Administrator within 24 hours of confirming a release. Also, 40 CFR part 302 may require the owner or operator to notify the National Response Center of a release.
265.1101(c)(4)	Containment Buildings: Design and Operating Standards.	Inspect and record in the facility's operating record, at least once every seven days, data gathered from monitoring and leak detection equipment as well as the containment building and the area immediately surrounding the containment building to detect signs of releases of hazardous waste. Inspect and record in the facility's operating record, at least once every seven days, except for Performance Track member facilities, that must inspect at least once each month, upon approval by the Director, data gathered from monitoring and leak detection equipment as well as the containment building and the area immediately surrounding the containment building to detect signs of releases of hazardous waste. To apply for reduced inspection frequency, the Performance Track member facility must follow the procedures described in § 265.15(b)(5).

TABLE 13.—DECREASED INSPECTION FREQUENCIES FOR SMALL QUANTITY GENERATOR HAZARDOUS WASTE MANAGEMENT UNITS

CFR section	Regulatory requirement	Current regulatory language / New regulatory language as amended by the Burden Reduction Rule
265.201(c)	Tank Systems: Special requirements for generators of between 100 and 1,000 kg/mo that accumulate hazardous waste in tanks.	(c) Generators of between 100 and 1,000 kg/mo of hazardous waste in tanks must inspect, where present: (1) Discharge control equipment (e.g., waste feed cutoff systems, by-pass systems, and drainage systems) at least once each operating day, to ensure that it is in good working order; (2) Data gathered from monitoring equipment (e.g., pressure and temperature gauges) at least once each operating day, to ensure that the tank is being operated according to its design;

TABLE 13.—DECREASED INSPECTION FREQUENCIES FOR SMALL QUANTITY GENERATOR HAZARDOUS WASTE MANAGEMENT UNITS—Continued

CFR section	Regulatory requirement	Current regulatory language New regulatory language as amended by the Burden Reduction Rule
		(3) The level of waste in the tank at least once each operating day to ensure compliance with §265.201(b)(3); (4) The construction materials of the tank at least weekly to detect corrosion or leaking of fixtures or seams; and (5) The construction materials of, and the area immediately surrounding, discharge confinement structures (e.g., dikes) at least weekly to detect erosion or obvious signs of leakage (e.g., wet spots or dead vegetation). (c) Except as noted in paragraph (d) of this section, generators who accumulate between 100 and 1,000 kg/mo of hazardous waste in tanks must inspect, where present: (1) Discharge control equipment (e.g., waste feed cutoff systems, by-pass systems, and drainage systems) at least once each operating day, to ensure that it is in good working order; (2) Data gathered from monitoring equipment (e.g., pressure and temperature gauges) at least once each operating day, to ensure that the tank is being operated according to its design; (3) The level of waste in the tank at least once each operating day to ensure compliance with §265.201(b)(3); (4) The construction materials of the tank at least weekly to detect corrosion or leaking of fixtures or seams; and (5) The construction materials of, and the area immediately surrounding, discharge confinement structures (e.g., dikes) at least weekly to detect erosion or obvious signs of leakage (e.g., wet spots or dead vegetation). (d) Generators who accumulate between 100 and 1,000 kg/mo of hazardous waste in tanks or tank systems that have full secondary containment and that either use leak detection equipment to alert facility personnel to leaks, or implement established workplace practices to ensure leaks are promptly identified, must inspect at least weekly, where applicable, the areas identified in paragraphs (c)(1)–(5) of this section. Use of the alternate inspection schedule must be documented in the facility's operating record. This documentation must include a description of the established workplace practices at the facility. (e) Performance Track member facilities may inspect on a less frequent basis, upon approval by the Director, but must inspect at least once each month. To apply for a less than weekly inspection frequency, the Performance Track member facility must follow the procedures described in §265.15(b)(5).

H. We Are Making Selected Changes to the Requirements for Record Retention and Submittal of Records

EPA is modifying certain requirements for hazardous waste handlers who keep records on site and submit these same records to EPA. We will now require waste handlers only to keep these selected records on site.

EPA believes that many of the various notices required do not add much in protection and some are simply redundant. We believe that reporting to EPA on the majority of the day-to-day functions of a facility does not need to occur. Because a basic set of compliance information will still be kept in the facility's operating record, we believe the regulatory agency has an ample opportunity for effective oversight.

1. We Are Removing the Requirement To Submit a One-Time Notification for Recycled Wood Wastewaters and Spent Wood-Preserving Solutions and Clarifying an Unintentional Elimination Made in the Proposal

Currently under 40 CFR 261.4(a)(9), spent wood preserving solutions and wastewaters from wood preserving processes are excluded from classification as a solid waste if they are reclaimed and reused for their original intended purpose, and if five conditions specified in subparagraphs (iii)(A) through (iii)(E) are met. Paragraph (E) required that the plant owner or operator submit a one-time notification that the plant intends to claim the exclusion.[15] Paragraph (E) also requires the owner or operator to maintain a copy of the notification on-site for no less than three years. Finally, paragraph (E) explains that the exclusion applies only so long as the plant meets all of the conditions, and sets forth procedures for what to do to retain the exclusion if the facility goes out of compliance with a condition.

The proposed rule (see 67 FR 2521) was to reduce the burden on wood preservers/treaters by eliminating the requirement to submit the one-time notification. The proposal stated that the requirement is unnecessary and has limited use for regulators. However, the change to the regulations specified in the regulatory text of the proposal unintentionally eliminated the entire paragraph (E) of 40 CFR 261.4(a)(9),(iii)

[15] The four other conditions found in 40 CFR 261.4(a)(9)(iii)(A)–(D) are: (A) The wood preserving wastewaters and spent wood preserving solutions are reused on-site at water borne plants in the production process for their original intended purpose; (B) Prior to reuse, the wastewaters and spent wood preserving solutions are managed to prevent release to either land or groundwater or both; (C) Any unit used to manage wastewaters and/or spent wood preserving solutions prior to reuse can be visually or otherwise be determined to prevent such releases; and (D) Any drip pad used to manage the wastewaters and/or spent wood preserving solutions prior to reuse complies with the standard in part 265, subpart W of this chapter, regardless of whether the plant generates a total of less than 100 kg/month of hazardous waste.

thus eliminating the one-time notification requirement and also eliminating the two other requirements in that paragraph: (1) The requirement to maintain the notification on-site for three years, and (2) the implementation discussion for compliance with the conditions.

Three state commenters did not agree with the proposal. These commenters argued that the notification is useful for identifying facilities that are claiming the exclusion, identifying potential problems before they occur, allowing the regulating agency to verify compliance, and workload planning. Several state commenters, however, agreed with the proposal to eliminate the requirement to submit the notification. Based on their comments, these commenters appeared to understand that only the requirement to submit the one-time notification was proposed for elimination. None mentioned the requirement to retain the notification on-site or the compliance implementation procedures.

While we understand the concern of some of the commenters, we still do not believe that arguments put forth were sufficient to change the proposed approach. We believe that the submittal of this notification is unnecessary because the facilities are engaged in limited activities to return materials to their intended use in the wood treating industry. Many comparable activities occur without notification, including direct reuse of the same material. These activities will occur at generator sites subject to EPA or state inspection (and in some case at treatment, storage, and disposal facilities), so EPA or the state will have an opportunity to review the activity. Note that in the final change to the regulatory text, we are only eliminating the requirement to submit the one-time notification; we are not eliminating the requirement to keep the document on-site, or the discussion of compliance implementation procedures.

2. We Are Eliminating the Requirement for Interim Status Facilities To Submit Specific Ground-Water Monitoring Plans and Ground-Water Assessment Reports

In today's final rule, we are reducing some of the burden on interim status facilities by eliminating the need to submit specific ground-water monitoring plans and ground-water assessment reports to the Regional Administrator. These reports include: (1) Plans for an alternative ground-water monitoring system under § 265.90(d)(1) that are implemented when the owner or operator assumes (or knows) that ground-water monitoring of indicator parameters in accordance with §§ 265.91 and 265.92 would show statistically significant increases when evaluated under § 265.93(b); (2) records of the analyses and evaluations specified in the plan under § 265.93(d)(2); and (3) ground-water quality assessment reports required under § 265.93(d)(5). These plans are not being eliminated, but are to be placed in the facility's operating record until closure of the facility. We consider today's changes to be a common sense approach to reducing burden at regulated facilities without compromising environmental protection.

Numerous states objected to these proposed changes to the interim status reporting and recordkeeping requirements, asserting that the regulatory agency should continue to receive a copy of these reports to assess the effectiveness and appropriateness of the ground-water monitoring system. Other states asserted that EPA's approach places an undue burden on the regulatory authority and makes it difficult for states to fully evaluate ground water across the state.

We believe that self-implementing ground-water monitoring plans for interim status facilities can be protective of human health and the environment; we disagree with the assertion that our rationale places a burden on the regulating authority. These reports must be kept in the facility's operating record until closure of the facility and will be available for inspection when the state or EPA visits the facility. Nothing in today's rulemaking prevents the regulating authority from requesting reports from interim status facilities for ground-water quality assessment or indicator parameter concentrations.

EPA is retaining many requirements for interim status facilities. For example, we are not changing the ground-water reporting requirements of §§ 265.93(c)(1), (d)(1), (e) and (f) and 265.94(a)(2)(i), (ii) and (iii), that deal with submitting notifications of increased indicator parameter concentrations and the development and submittal of: (1) Ground-water quality assessment reports; (2) preparation and submittal of quarterly reports on drinking water suitability parameters; indicator parameter concentrations and evaluations; and (3) ground-water surface elevations. Stakeholders have convinced us of the importance of this information. Without the knowledge of the status of the facility ground-water monitoring system, it may be difficult for regulators to conduct effective inspections, address compliance issues, and address enforcement issues regarding the ground water at interim status facilities.

3. We Are Eliminating the Requirement for Interim Status Surface Impoundments, Waste Piles, and Landfills To Submit a Response Action Plan

Response action plans are generated by the owner or operator of a specified hazardous waste management unit (e.g., surface impoundment, waste pile, and/or landfill), and document actions to be taken if the action leakage rate in the unit's leak detection system has been exceeded.[16] These actions are listed in §§ 265.223, 265.259 and 265.303.[17] The Agency proposed eliminating the need to submit to the Regional Administrator response action plans for interim status surface impoundments, waste piles, and landfills. We are eliminating the submission of the response action plan to the Regional Administrator. The facility must still prepare and retain these plans on-site.

Several state commenters agreed with the proposal; however, several others did not. One commenter argued that a release from a land-based unit is a significant noncompliance and could pose serious impacts to the people and the environment, and it is important for the facility to have a clear plan in advance to respond to releases. Because of the importance of controlling these releases, it is appropriate for the response action plan to be submitted to EPA or the state permit agency. While we agree with the commenter that any release from a land-based unit is a serious matter, and that controlling these releases is of the utmost importance, we are not convinced that these plans need to be submitted to the regulatory agency. EPA is retaining all requirements to submit notices to the regulatory authority when an action leakage rate is exceeded (see §§ 265.224(b)(2) and (6); 265.259(b)(2) and (6); and 265.303(b)(2) and (6)); we

[16] The action leakage rate is the maximum design flow rate that the leak detection system (LDS) can remove without the fluid head on the bottom liner exceeding one foot. The action leakage rate must include an adequate margin of safety to allow for uncertainties in the design (e.g., slope, hydraulic conductivity, thickness of drainage material), construction, operation, and location of the LDS, waste and leachate characteristics, likelihood and amounts of other sources of liquids in the LDS, and proposed response actions (e.g., the action leakage rate must consider decreases in the flow capacity of the system over time resulting from siltation and clogging, rib layover and creep of synthetic components of the system, overburden pressures, etc.).

[17] In the CFR there are two sections identified as § 265.223, the first titled "Containment system" and the second titled "Response actions". In today's rule we are redesignating § 265.223 titled "Response actions" as § 265.224.

believe that the need to submit the response action plan which merely reiterates these requirements is an overly burdensome requirement that can be removed.

4. We Are Eliminating the Requirement for Facilities To Submit a Tank System Certification of Completion of Major Repairs

We are amending the requirement for submitting to the Regional Administrator a certification of completion of major repairs to a tank system by an independent, qualified, professional engineer. This certification need only be kept on-site in the operating record through the intended life of the system. This change will eliminate the submission of duplicative information to the regulatory authority. Sections 264.196(d) and 265.196(d) already require that certain notifications be submitted that include descriptions of response actions taken or planned.

Several commenters did not support the proposed change, noting that submission of the certification helps to ensure that the regulatory authority is made aware of any potentially significant repairs that were conducted. One commenter argued that the elimination of these notices or notations in the operating record will adversely affect oversight. Another commenter argued that, while supportive of the proposed change, the certification of major repairs must be kept with the facility record, and be available for review by regulatory inspectors. We believe that information provided by the certification of major repairs is already provided through the notification mechanisms described in §§ 264.196(d) and 265.196(d), which require notification when releases occur, and a description of response actions taken or planned. While we are not eliminating the certification, we are requiring the certification be kept on site in the operating record, and we are requiring the certification be signed by a qualified professional engineer.

5. We Are Eliminating the Requirement for a Recycler To Submit a Notification and Certification

Under 40 CFR 268.7(b)(3), a treatment facility must send a one-time notice to the receiving land disposal facility with the initial shipment of waste or contaminated soil. Also, in § 268.7(b)(4), the treatment facility must submit a one-time certification with the initial shipment of waste or contaminated soil to the land disposal facility.

Under § 268.7(b)(6), however, if the wastes are recyclable materials used in a manner constituting disposal, the owner or operator of the treatment facility (i.e., the recycler) is not required to send the one-time (b)(3) notice to the receiving facility. For each shipment, however, the owner or operator of the treatment facility (i.e., recycler) must submit a (b)(4) certification and a notice with the information listed in (b)(3) to the Regional Administrator. These notifications and certifications are to assure and document that treatment standards are being met. The preamble to the proposed rule described a proposal that would reduce burden on the regulated industry by eliminating the requirement to send the notifications and certifications to EPA, and instead require that the treatment facility (i.e., recycler) place these documents in its on-site files.

Five commenters, including three states, agreed that notifying the regulatory agency is not necessary as long as the information is maintained at the facility. Only one commenter did not support the elimination of the requirement. This commenter argued that it is important to track hazardous wastes used in the manufacture of fertilizers because it believes there are problems with compliance in this industry. It believes that notification to the regulatory agency allows such tracking. We, however, do not agree with this commenter, for the reasons presented below.

Based on the majority of comments received, we are amending § 268.7(b)(6) to eliminate the requirement to submit notifications and certifications to EPA, and instead require that the information be placed in the treating/recycling facility's on-site files. All but one commenter confirmed that maintaining these records on-site provides sufficient documentation of waste treatment in these cases. We also point out that regulating agencies have a great deal of information about these facilities already since, in most cases, they would be permitted facilities. Retaining these notices on-site does not eliminate the regulating agency's knowledge of the existence of the facility. We also note that if a state has concerns about compliance in a particular use constituting disposal industry in their state, they may choose to be more stringent than the federal program, and choose to retain these notifications.

It should be noted that the preamble to the proposal incorrectly indicated that the current regulations only require one-time notifications and certifications for these materials. This is not accurate. As discussed earlier, the existing regulations actually require that certifications and notifications be sent to the regulating agency with each shipment. One commenter suggested that we change the requirement so that these notifications and certifications are only required to be prepared once and maintained in the facility's records, unless there are changes to the treatment process. The commenter pointed out that it would greatly reduce the burden for the facility if they were only required to prepare these documents once, and then again any time the treatment process changes. We agree with this commenter's point. As long as these notifications and certifications are required to be maintained in the facility's files and be available for inspection, there is no reason for the facility to prepare and maintain multiple copies for each shipment. The information will be available for inspection at all times. Whereas the proposal did address the burden of sending notifications and certifications to the regulatory agency, it did not address the burden associated with the requirement to send those documents with each waste shipment. This final rule corrects that omission. Thus, this final rule only requires facilities (i.e., recyclers) to prepare and maintain notifications and certifications with the initial shipment of waste, and then to prepare new documentation only if the waste, the treatment process, or the receiving facility changes.

6. We Are Eliminating the Requirement to Submit an LDR Notification and Certification

Under § 268.9(d), once a characteristic waste is treated so it is no longer characteristic, a one-time notification and certification of this fact have to be placed in the generator's or treater's files, and also sent to EPA or the authorized state. We proposed to eliminate the requirement to submit the notification to EPA or the authorized state (the notification and certification would continue to be required to be kept in the facility's files).

Almost all commenters supported the proposal to delete the one-time requirement that the § 268.9(d) notification and certification be sent to EPA or the authorized state. This is because the notification and the certification must be placed in the on-site files and would thus be available for inspection. However, a few commenters opposed the deletion of these submittals, stating that this information is valuable. While we agree that the information is valuable, we do not believe that submitting these documents to the regulatory agency is necessary to protect human health and the environment. For a number of years, other LDR notifications and

certifications have not been required to be submitted to the regulatory agency, but are available for inspection in the facility's on-site files. Therefore, we believe that this system of recordkeeping is sufficient and are deleting the notification and certification submission requirement as proposed.

TABLE 14.—CHANGES TO THE REQUIREMENTS FOR RECORD RETENTION AND SUBMITTAL OF RECORDS FOR PERMITTED TREATMENT, STORAGE, AND DISPOSAL FACILITIES

CFR section	Regulatory requirement	Current regulatory language New regulatory language as amended by the Burden Reduction Rule
264.196(f)	Tank Systems. Response to leaks or spills and disposition of leaking or unfit-for-use tank systems.	Certification of major repairs. If the owner/operator has repaired a tank system in accordance with paragraph (e) of this section, and the repair has been extensive (e.g., installation of an internal liner; repair of a ruptured primary containment or secondary containment vessel), the tank system must not be returned to service unless the owner/operator has obtained a certification by an independent, qualified, registered, professional engineer in accordance with § 270.11(d) that the repaired system is capable of handling hazardous wastes without release for the intended life of the system. This certification must be submitted to the Regional Administrator within seven days after returning the tank system to use. Certification of major repairs. If the owner/operator has repaired a tank system in accordance with paragraph (e) of this section, and the repair has been extensive (e.g., installation of an internal liner; repair of a ruptured primary containment or secondary containment vessel), the tank system must not be returned to service unless the owner/operator has obtained a certification by a qualified professional engineer in accordance with § 270.11(d) that the repaired system is capable of handling hazardous wastes without release for the intended life of the system. This certification must be placed in the operating record and maintained until closure of the facility.[18]

[18] The reader is referred to Section III. B. of today's preamble for a discussion of the change from "independent, qualified, registered, professional" to "qualified professional engineer".

TABLE 15.—CHANGES TO THE REQUIREMENTS FOR RECORD RETENTION AND SUBMITTAL OF RECORDS FOR INTERIM STATUS TREATMENT, STORAGE, AND DISPOSAL FACILITIES

CFR section	Regulatory requirement	Current regulatory language New regulatory language as amended by the Burden Reduction Rule
265.90(d)(1)	Ground-Water Monitoring. Applicability.	Within one year after the effective date of these regulations, submit to the Regional Administrator a specific plan, certified by a qualified geologist or geotechnical engineer, which satisfies the requirements of § 265.93(d)(3), for an alternate ground-water monitoring system. Within one year after the effective date of these regulations, develop a specific plan, certified by a qualified geologist or geotechnical engineer, which satisfies the requirements of § 265.93(d)(3), for an alternate ground-water monitoring system. This plan is to be placed in the facility's operating record and maintained until closure of the facility.
265.90(d)(3)	Ground-Water Monitoring. Applicability.	Prepare and submit a written report in accordance with § 265.93(d)(5). Prepare a report in accordance with § 265.93(d)(5) and place it in the facility's operating record and maintain until closure of the facility.
265.93(d)(2)	Ground-Water Monitoring. Preparation, evaluation, and response.	Within 15 days after the notification under paragraph (d)(1) of this section, the owner or operator must develop and submit to the Regional Administrator a specific plan, based on the outline required under paragraph (a) of this section and certified by a qualified geologist or geotechnical engineer, for a ground-water quality assessment at the facility. Within 15 days after the notification under paragraph (d)(1) of this section, the owner or operator must develop a specific plan, based on the outline required under paragraph (a) of this section and certified by a qualified geologist or geotechnical engineer, for a ground-water quality assessment at the facility. This plan must be placed in the facility operating record and be maintained until closure of the facility.
265.93(d)(5)	Ground-Water Monitoring. Preparation, evaluation, and response.	The owner or operator must make his first determination under paragraph (d)(4) of this section, as soon as technically feasible, and, within 15 days after that determination, submit to the Regional Administrator a written report containing an assessment of the ground-water quality. The owner or operator must make his first determination under paragraph (d)(4) of this section as soon as technically feasible, and prepare a report containing an assessment of the ground-water quality. This report must be placed in the facility operating record and be maintained until closure of the facility.

TABLE 15.—CHANGES TO THE REQUIREMENTS FOR RECORD RETENTION AND SUBMITTAL OF RECORDS FOR INTERIM STATUS TREATMENT, STORAGE, AND DISPOSAL FACILITIES—Continued

CFR section	Regulatory requirement	Current regulatory language New regulatory language as amended by the Burden Reduction Rule
265.196(f)	Tank Systems. Response to leaks or spills and disposition of leaking or unfit-for-use tank systems.	Certification of major repairs. If the owner/operator has repaired a tank system in accordance with paragraph (e) of this section, and the repair has been extensive (*e.g.*, installation of an internal liner; repair of a ruptured primary containment or secondary containment vessel), the tank system must not be returned to service unless the owner/operator has obtained a certification by an independent, qualified, registered, professional engineer in accordance with § 270.11(d) that the repaired system is capable of handling hazardous wastes without release for the intended life of the system. This certification must be submitted to the Regional Administrator within seven days after returning the tank system to use. Certification of major repairs. If the owner/operator has repaired a tank system in accordance with paragraph (e) of this section, and the repair has been extensive (*e.g.*, installation of an internal liner; repair of a ruptured primary containment or secondary containment vessel), the tank system must not be returned to service unless the owner/operator has obtained a certification by a qualified professional engineer in accordance with § 270.11(d) that the repaired system is capable of handling hazardous wastes without release for the intended life of the system. This certification must be placed in the operating record until closure of the facility.[19]
265.223(a)	Surface Impoundments. Response actions.	The owner or operator of surface impoundment units subject to § 265.221(a) must submit a response action plan to the Regional Administrator when submitting the proposed action leakage rate under § 265.222. The response action plan must set forth the actions to be taken if the action leakage rate has been exceeded. At a minimum, the response action plan must describe the actions specified in paragraph (b) of this section. (Now § 265.224(a)) The owner or operator of surface impoundment units subject to § 265.221(a) must develop and keep on-site until closure of the facility a response action plan. The response action plan must set forth the actions to be taken if the action leakage rate has been exceeded. At a minimum, the response action plan must describe the actions specified in paragraph (b) of this section.
265.259(a)	Waste Piles. Response actions	The owner or operator of waste pile units subject to § 265.254 must submit a response action plan to the Regional Administrator when submitting the proposed action leakage rate under § 265.255. The response action plan must set forth the actions to be taken if the action leakage rate has been exceeded. At a minimum, the response action plan must describe the action specified in paragraph (b) of this section. The owner or operator of waste pile units subject to § 265.254 must develop and keep on-site until closure of the facility a response action plan. The response action plan must set forth the actions to be taken if the action leakage rate has been exceeded. At a minimum, the response action plan must describe the actions specified in paragraph (b) of this section.
265.303(a)	Landfills. Response actions	The owner or operator of landfill units subject to § 265.301(a) must submit a response action plan to the Regional Administrator when submitting the proposed action leakage rate under § 265.302. The response action plan must set forth the actions to be taken if the action leakage rate has been exceeded. At a minimum, the response action plan must describe the action specified in paragraph (b) of this section. The owner or operator of landfill units subject to § 265.301(a) must develop and keep on-site until closure of the facility a response action plan. The response action plan must set forth the actions to be taken if the action leakage rate has been exceeded. At a minimum, the response action plan must describe the actions specified in paragraph (b) of this section.

[19] The reader is referred to today's preamble for a discussion of the change from "independent, qualified, registered, professional engineer" to "qualified professional engineer." We are also requiring that this certification be retained in the operating record until closure of the facility.

TABLE 16.—CHANGES TO THE REQUIREMENTS FOR RECORD RETENTION AND SUBMITTAL OF RECORDS FOR HAZARDOUS WASTE GENERATORS

CFR section	Regulatory requirement	Current regulatory language New regulatory language as amended by the Burden Reduction Rule
261.4(a)(9)(iii)(E)	General. Exclusions. Materials which are not solid wastes.	Prior to operating pursuant to this exclusion, the plant owner or operator submits to the appropriate Regional Administrator or state Director a one-time notification stating that the plant intends to claim the exclusion, giving the date on which the plant intends to begin operating under the exclusion, and containing the following language: "I have read the applicable regulation establishing an exclusion for wood preserving wastewaters and spent wood preserving wastewater and spent wood preserving solutions and understand it requires me to comply at all times with the conditions set out in the regulation." The plant must maintain a copy of that document in its on-site records for a period of no less than 3 years from the date specified in the notice. The exclusion applies only so long as the plant meets all of the conditions. If the plant goes out of compliance with any condition, it may apply to the appropriate Regional Administrator or state Director for reinstatement The Regional Administrator or state Director may reinstate the exclusion upon finding that the plant has returned to compliance with all conditions and that violations are not likely to recur. Prior to operating pursuant to this exclusion, the plant owner or operator prepares a one-time notification stating that the plant intends to claim the exclusion, giving the date on which the plant intends to begin operating under the exclusion, and containing the following language: "I have read the applicable regulation establishing an exclusion for wood preserving wastewaters and spent wood preserving solutions and understand it requires me to comply at all times with the conditions set out in the regulation." The plant must maintain a copy of that document in its on-site records until closure of the facility. The exclusion applies only so long as the plant meets all of the conditions. If the plant goes out of compliance with any condition, it may apply to the appropriate Regional Administrator or state Director for reinstatement. The Regional Administrator or state Director may reinstate the exclusion upon finding that the plant has returned to compliance with all conditions and that violations are not likely to recur.
268.7(b)(6)	Land Disposal Restrictions. Testing, tracking, and record-keeping requirements for generators, treaters, and disposal facilities.	Where the wastes are recyclable materials used in a manner constituting disposal subject to the and provisions of §268.20(b) regarding requirements for treatment standards and prohibition levels, the owner or operator of a treatment facility (i.e., the recycler) is not required to notify the receiving facility, pursuant to paragraph (b)(3) of this section. With each shipment of such wastes, the owner or operator of the recycling facility must submit a certification described in paragraph (b)(4) of this section, and a notice which includes the information listed in paragraph (b)(3) of this section (except the manifest number) to the Regional Administrator, or his delegated representative. The recycling facility also must keep records of the name and location of each entity receiving the hazardous waste-derived product. Where the wastes are recyclable materials used in a manner constituting disposal subject to the provisions of §266.20(b)[20] of this chapter regarding treatment standards and prohibition levels, the owner or operator of a treatment facility (i.e., the recycler) must, for the initial shipment of waste, prepare a one-time certification described in paragraph (b)(4) of this section, and a one-time notice which includes the information in paragraph (b)(3) of this section (except the manifest number). The certification and notification must be placed in the facility's on-site files. If the waste or the receiving facility changes, a new certification and notification must be prepared and placed in the on-site files. In addition, the recycling facility must also keep records of the name and location of each entity receiving the hazardous waste-derived product.
268.9(d)	Land Disposal Restrictions. Special rules regarding wastes that exhibit a characteristic.	Wastes that exhibit a characteristic are also subject to §268.7 requirements, except that once the waste is no longer hazardous, a one-time notification and certification must be placed in the generators or treaters files and sent to the EPA region or authorized state. The notification and certification that is placed in the generators or treaters files must be updated if the process or operation generating the waste changes and/or if the subtitle D facility receiving the waste changes. However, the generator or treater need only notify the EPA region or an authorized state on an annual basis if such changes occur. Such notification and certification should be sent to the EPA region or authorized state by the end of the calendar year, but no later than December 31. Wastes that exhibit a characteristic are also subject to §268.7 requirements, except that once the waste is no longer hazardous, a one-time notification and certification must be placed in the generator's or treater's files. The notification and certification must be updated if the process or operation generating the waste changes and/or if the subtitle D facility receiving the waste changes.

[20] In the previous regulatory language, the citation referred to §268.20(b), however, this was an error. In today's rule, we are correcting this error by referring to the correct citation which is §266.20(b).

I. We Are Making Selected Changes to the Requirements for Document Submittal

1. We Are Streamlining the Procedure for Obtaining a Variance From Classification as a Solid Waste

A regulatory agency may grant a variance from classification as a solid waste for materials that are reclaimed and then reused as feedstock within the original production process in which the materials were generated. The regulation lists eight criteria that are to be used in determining if the request for a variance is to be granted. One of the criteria is a requirement to demonstrate the prevalence of the practice on an industry-wide basis.

The proposed rule described a proposal to eliminate the requirement that applicants for this variance submit information on the prevalence of the practice on an industry-wide basis. The Agency found that this information was less important in making the decision than the other factors and could be difficult for a facility to provide.

Four commenters agreed with the proposal to eliminate the requirement. One pointed out the difficulty of obtaining such information, particularly in the batch and speciality chemical industry. Three states also supported eliminating the requirement. Three other commenters opposed eliminating the requirement, arguing that the information is important in determining whether the reclamation process is an essential part of the production process.

While the Agency believes that this information can be useful in some cases, we also believe that such industry-wide information about these practices is not critical in demonstrating or determining that reclamation is an essential part of production. We believe that a successful demonstration can be made without this information. We also acknowledge that this information may be very difficult, and in some cases, impossible for one company to obtain. We are, therefore, eliminating the requirement in § 260.31(b)(2) that applicants provide industry-wide information.

2. We Are Streamlining the Requirements for Treatability Study Reports for Testing Facilities

Treatability studies are studies at laboratories and testing facilities in which hazardous waste is tested to evaluate the effectiveness of a treatment process. (See definition in 40 CFR 260.) Facilities conducting treatability studies are excluded from the standard hazardous waste management requirements if they comply with certain requirements described in § 261.4(f). Paragraph (9) requires the facility to submit to the regulatory agency an annual report that includes: (1) An estimate of the number of studies and the amount of waste expected to be used in treatability studies during the current year; and (2) information on the treatability studies conducted during the previous year.

We proposed to reduce burden by eliminating the requirement to submit an estimate of the number of treatability studies and amount of waste expected to be used in treatability studies in the upcoming year. The proposal explained that the requirement is duplicative because the same information is submitted in the annual report at a later date. However, the change to the regulations specified in the regulatory text of the proposal unintentionally eliminated the entire paragraph (9) of § 261.4(f), thus proposing to eliminate both the requirement to submit estimates for the current year, as well as information for the previous year.

The majority of commenters (seven) supported elimination of the estimates. They did so with the apparent understanding that only the requirement to provide estimates for the coming year was to be eliminated, and that the requirement to submit information for the previous year would remain in place. Most agreed with the proposal to eliminate the estimates based on the rationale in the preamble that the information would be provided at a later date. Two commenters did point out that eliminating all of § 261.4(f)(9) also eliminates the requirement for providing any report, including the submittal of information from the previous year.

We agree with commenters that the estimate of upcoming activities are unnecessary since the same information will be provided later in the annual report, and the information provided on past activities will be more accurate than estimates of the future. We are, therefore, eliminating the requirement in § 261.4(f)(9) to submit estimates of the number of studies and the amount of waste to be used in treatability studies for the current year, but are retaining the requirement for preparing and submitting an annual report providing information for the previous year.

3. We Are Streamlining the Requirements for Ground-Water Monitoring

As previously discussed in the October 29, 2003 NODA (68 FR 61662), hazardous waste treatment, storage, and disposal facilities must implement ground-water monitoring as a condition for receiving a RCRA permit. EPA requires a phased approach to ground-water monitoring (detection monitoring, compliance monitoring, corrective action). Ground-water monitoring systems must consist of a sufficient number of wells, properly located and constructed, and capable of ensuring that the ground-water impacts of a treatment, storage, or disposal unit can be determined. Sampling and analysis procedures must also be capable of determining both background quality of ground water and quality at the point of compliance.

If hazardous constituents are detected in ground water, more detailed monitoring may be required. In this case, a facility would need additional wells, sampling, and analysis to determine the extent and rate of contaminant migration, to determine if the ground-water protection standard is violated, and to indicate the need for, or effectiveness of, corrective action.

Detection monitoring is the first phase of ground-water monitoring, and is designed to detect a change in ground-water quality in wells surrounding a regulated unit. A potential release from the unit, or impacts from activities up gradient of the unit, may cause this change. For detection monitoring, ground-water monitoring wells are installed up-gradient of the unit and at the point of compliance. Facilities then monitor for each indicator parameter or hazardous constituent specified in the permit.

Compliance monitoring occurs when hazardous waste constituents are detected down-gradient of the unit. The permitting authority will establish hazardous constituent standards for facilities undergoing compliance monitoring.

The third phase of ground-water monitoring, corrective action, is required when hazardous constituents exceed the ground-water protection standards at the point of compliance. Once this has occurred, the owner or operator must remedy the situation by removing the hazardous constituents or treating them in place.

We are modifying the § 264.99(g) requirement that facilities performing compliance monitoring conduct an annual 40 CFR Part 264 Appendix IX (the ground-water monitoring chemical list) analysis of all monitoring wells. We are allowing, on a case-by-case basis, as authorized by a permit authority, sampling from a subset of the wells. Appendix IX analyses are costly at large facilities, and analyzing all wells does not necessarily contribute to protection of human health and the environment. This is especially the case if there are

multiple units and wells at a facility, and only one unit shows signs of contamination.

In addition, monitoring for constituents that are not likely to be found at a site is wasteful and does not increase the protection of monitoring programs. We, therefore, are also modifying § 264.98(g)(2) to give the Regional Administrator discretion on a case-by-case basis to allow sampling for a subset of the Appendix IX constituents. While this change was proposed for § 264.98(c), upon re-evaluation, we decided it is more appropriate to amend § 264.98(g)(2) and leave § 264.98(c) unchanged. Decisions on what constituents must be sampled will be based on the regulatory agencies' judgment of what amount of sampling supports the protection of human health and the environment, as well as the level of knowledge of what contaminants could be present at a site. As a commenter pointed out, this subsection prior to today did not require that all samples must be analyzed for every chemical parameter and hazardous constituent listed in Appendix IX. Today's rule eliminates ambiguity by specifically confirming that sampling for a site-specific subset of constituents is allowable.

Based on a comment we received, we also are revising § 264.98(d) to allow for alternative sampling procedures as provided in § 264.97(g)(2). Under § 264.98(d), a facility must collect at least four samples from each well at least semi-annually. This provision has resulted in sites being required to sample four times within a single monitoring event, despite the contradiction with § 264.97(g)(2) which allows for an alternate sampling procedure. To reduce some of the burden related to this sampling and reporting, we are removing the last sentence from § 264.98(d) (requiring a facility to collect at least four samples from each well at least semi-annually). We are also eliminating the last sentence in § 264.99(f) (requiring a facility to collect at least four samples from each well at least semi-annually). These changes will prevent § 264.98(d) and § 264.99(f) from unintentionally trumping the flexibility granted by § 264.97(g)(2).

Finally, based on another comment received, we are also changing the re-sampling requirements in § 264.98(g)(3) and § 264.99(g) from "may resample within one month" to "may resample within one month or at an alternative site-specific time frame approved by the Administrator." This change allows for sampling to be based on site-specific hydrogeologic conditions. It also can be burdensome for facilities to resample wells within 30 days, because this time frame can allow, in some circumstances, insufficient time to evaluate the original data set, perform quality assurance evaluations, and re-mobilize the sampling team.

TABLE 17.—CHANGES TO THE REQUIREMENTS FOR DOCUMENT SUBMITTAL FOR VARIANCES FROM CLASSIFICATION AS A SOLID WASTE AND FOR TESTING FACILITIES REGARDING TREATABILITY STUDY REPORTS

CFR section	Regulatory requirement	Current regulatory language New regulatory language as amended by the Burden Reduction Rule
260.31(b)(2)	Rulemaking Petitions. Standards and criteria for variances from classification as a solid waste.	The prevalence of the practice on an industry-wide basis. Section 260.31(b)(2) has been deleted from the regulatory text.
261.4(f)(9)	General. Exclusions. Samples undergoing treatability studies at laboratories and testing facilities.	The facility prepares and submits a report to the Regional Administrator, or state Director (if located in an authorized state), by March 15 of each year that estimates the number of studies at studies and the amount of waste laboratories and expected to be used in treatability testing studies during the current year, and facilities, includes the following information for the previous calendar year: The facility prepares and submits a report to the Regional Administrator, or state Director (if located in an authorized state), by March 15 of each year, that includes the following information for the previous calendar year:

TABLE 18.—CHANGES TO THE REQUIREMENTS FOR DOCUMENT SUBMITTAL FOR PERMITTED TREATMENT, STORAGE AND DISPOSAL FACILITIES

CFR section	Regulatory requirement	Current regulatory language New regulatory language as amended by the Burden Reduction Rule
264.98(d)	Releases from Solid Waste Management Units. Detection monitoring program.	The Regional Administrator will specify the frequencies for collecting samples and conducting statistical tests to determine whether there is statistically significant evidence of contamination for any parameter or hazardous constituent specified in the permit under paragraph (a) of this section in accordance with § 264.97(g). A sequence of at least four samples from each well (background and compliance wells) must be collected at least semi-annually during detection monitoring. The Regional Administrator will specify the frequencies for collecting samples and conducting statistical tests to determine whether there is statistically significant evidence of contamination for any parameter or hazardous constituent specified in the permit conditions under paragraph (a) of this section in accordance with § 264.97(g).
264.98(g)(2)	Releases from Solid Waste Management Units. Detection monitoring program.	Immediately sample the ground water in all monitoring wells and determine whether constituents in the list of appendix IX of part 264 are present, and if so, in what concentration.

TABLE 18.—CHANGES TO THE REQUIREMENTS FOR DOCUMENT SUBMITTAL FOR PERMITTED TREATMENT, STORAGE AND DISPOSAL FACILITIES—Continued

CFR section	Regulatory requirement	Current regulatory language New regulatory language as amended by the Burden Reduction Rule
		Immediately sample the ground water in all monitoring wells and determine whether constituents in the list of appendix IX of part 264 are present, and if so, in what concentration. However, the Regional Administrator, on a discretionary basis, may allow sampling for a site-specific subset of constituents from the Appendix IX list of this part and other representative/related waste constituents.
264.98(g)(3)	Releases from Solid Waste Management Units. Detection monitoring program.	For any appendix IX compounds found in the analysis pursuant to paragraph (g)(2) of this section, the owner or operator may resample within one month and repeat the analysis for those compounds detected. If the results of the second analysis confirm the initial results, then these constituents will form the basis for compliance monitoring. If the owner or operator does not resample for the compounds found pursuant to paragraph (g)(2) of this section, the hazardous constituents found during this initial appendix IX analysis will form the basis for compliance monitoring. For any appendix IX compounds found in the analysis pursuant to paragraph (g)(2) of this section, the owner or operator may resample within one month or at an alternative site-specific schedule approved by the Administrator and repeat the analysis for those compounds detected. If the results of the second analysis confirm the initial results, then these constituents will form the basis for compliance monitoring. If the owner or operator does not resample for the compounds in paragraph (g)(2) of this section, the hazardous constituents found during this initial appendix IX analysis will form the basis for compliance monitoring.
264.99(f)	Releases from Solid Waste Management Units. Compliance monitoring program.	The Regional Administrator will specify the frequencies for collecting samples and conducting statistical tests to determine statistically significant evidence of increased contamination in accordance with § 264.97(g). A sequence of at least four samples from each well (background and compliance wells) must be collected at least semi-annually during the compliance period of the facility. The Regional Administrator will specify the frequencies for collecting samples and conducting statistical tests to determine statistically significant evidence of increased contamination in accordance with § 264.97(g).
264.99(g)	Releases from Solid Waste Management Units. Compliance monitoring program.	The owner or operator must analyze samples from all monitoring wells at the compliance point for all constituents contained in appendix IX of part 264 at least annually to determine whether additional hazardous constituents are present in the uppermost aquifer and, if so at what concentrations, pursuant to procedures in § 264.98(f). If the owner or operator finds appendix IX constituents in the ground water that are not already identified in the permit as monitoring constituents, the owner or operator may resample within one month and repeat the appendix IX analysis. If the second analysis confirms the presence of new constituents, the owner or operator must report the concentration of these additional constituents to the Regional Administrator within seven days after the completion of the second analysis and add them to the monitoring list. If the owner or operator chooses not to resample, then he or she must report the concentrations of these additional constituents to the Regional Administrator within seven days after completion of the initial analysis and add them to the monitoring list. Annually, the owner or operator must determine whether additional hazardous constituents from appendix IX of this 264, which could possibly be present but are not on the detection monitoring list in the permit, are actually present in the uppermost aquifer and, if so, at what concentration, pursuant to procedures in § 264.98(f). To accomplish this, the owner or operator must consult with the Regional Administrator to determine on a case-by-case basis: (1) Which sample collection event during the year will involve enhanced sampling; (2) the number of monitoring wells at the compliance point to undergo enhanced sampling; (3) the number of samples to be collected from each of these monitoring wells; and, (4) the specific constituents from Appendix IX of this 264 for which these samples must be analyzed. If the enhanced sampling event indicates that appendix IX constituents are present in the ground water that are not already identified in the permit as monitoring constituents, the owner or operator may resample within one month or at an alternative site-specific schedule approved by the Regional Administrator, and repeat the analysis. If the second analysis confirms the presence of new constituents, the owner or operator must report the concentration of these additional constituents to the Regional Administrator within seven days after the completion of the second analysis and add them to the monitoring list. If the owner or operator chooses not to resample, then he or she must report the concentrations of these additional constituents to the Regional Administrator within seven days after completion of the initial analysis, and add them to the monitoring list.

J. We Are Making Selected Changes to the Requirements for Semi-Annual Reports to Annual Reports

1. We Are Changing the Requirement for a Semi-Annual Report Detailing the Effectiveness of the Corrective Action Program

Section 264.100(g) requires the owner or operator of a permitted facility to report in writing to the Regional Administrator on the effectiveness of the corrective action program. These reports must be submitted semi-annually. We are now requiring an annual report instead of a semi-annual report. While this change was not in the proposed rule, it was identified in the comments received and was discussed in the October 29, 2003 NODA (68 FR 61668). It is a change that conforms to the change we are making to § 264.113(e)(5) and was supported by a majority of the commenters.

2. We Are Changing the Requirement for a Semi-Annual Report Describing the Progress of the Corrective Action Program

We proposed lengthening the reporting frequency for corrective action effectiveness reports required by §§ 264.113(e)(5) and 265.113(e)(5). These reports are currently required to be submitted semi-annually and include a description of the progress of the corrective action program, all ground-water monitoring data, and an evaluation of the effect of the continued receipt of non-hazardous wastes on the effectiveness of the corrective action. We received comments, mainly from the states, on this proposed regulatory change. Several states suggested giving the regulatory agency the flexibility of establishing report submittals on a case-by-case basis. Other states suggested the reports be submitted at least annually. Still another state suggested that the semi-annual submittal of reports is preferred because it allows the state to identify inadequate monitoring systems earlier, which in turn, could save the facilities needless ground-water monitoring expenses.

After reviewing the comments submitted, we have decided to promulgate the changes as proposed. Ground-water cleanup is generally a multi-year effort. Thus, we believe that annual submittal of these reports will not jeopardize the protection of human health and the environment.

TABLE 19.—REDUCED FREQUENCY FOR SUBMITTAL OF REPORTS FOR PERMITTED TREATMENT, STORAGE AND DISPOSAL FACILITIES

CFR section	Regulatory requirement	Current regulatory language New regulatory language as amended by the Burden Reduction Rule
264.100(g)	Releases from Solid Waste Management Units. Corrective action program.	The owner or operator must report in writing to the Regional Administrator on the effectiveness of the corrective action program. The owner or operator must submit these reports semi-annually. The owner or operator must report in writing to the Regional Administrator on the effectiveness of the corrective action program. The owner or operator must submit these reports annually.
264.113(e)(5)	Closure and Post-Closure. Closure; time allowed for closure.	During the period of corrective action, the owner or operator shall provide semi-annual reports to the Regional Administrator that describe the progress of the corrective action program, compile all ground-water monitoring data, and evaluate the effect of the continued receipt of non-hazardous wastes on the effectiveness of the corrective action. During the period of corrective action, the owner or operator shall provide annual reports to the Regional Administrator describing the progress of the corrective action program, compile all ground-water monitoring data, and evaluate the effect of the continued receipt of non-hazardous wastes on the effectiveness of the corrective action.

TABLE 20.—REDUCED FREQUENCY FOR SUBMITTAL OF REPORTS FOR INTERIM STATUS TREATMENT, STORAGE AND DISPOSAL FACILITIES

CFR section	Regulatory requirement	Current regulatory language New regulatory language as amended by the Burden Reduction Rule
265.113(e)(5)	Closure and Post-Closure. Closure; time allowed for closure.	During the period of corrective action, the owner or operator shall provide semi-annual reports to the Regional Administrator that describe the progress of the corrective action program, compile all ground-water monitoring data, and evaluate the effect of the continued receipt of non-hazardous wastes on the effectiveness of the corrective action. During the period of corrective action, the owner or operator shall provide annual reports to the Regional Administrator describing the progress of the corrective action program, compile all ground-water monitoring data, and evaluate the effect of the continued receipt of non-hazardous wastes on the effectiveness of the corrective action.

IV. What Regulatory Requirements Will Remain in the CFR?

Commenters opposed a number of the burden reduction changes that we either proposed or noticed in our October 29, 2003 NODA. After thorough analysis of the comments, and in consultation with state representatives, we have decided (at least for the present time) to retain these regulatory requirements. Stakeholders persuaded us that these changes could delete important recordkeeping and reporting requirements that were necessary in order to protect human health and the environment. Stakeholders, particularly the states, also provided arguments as to

the importance of retaining their oversight role when dealing with leaks and spills of hazardous waste. Table 21—Regulatory Requirements That Will Remain in the CFR, identifies those proposed regulatory sections that we are not promulgating in today's rule.

For information on what commenters said regarding particular provisions and the Agency's response, the reader is referred to the following document, Response to Comments Background Document that can be found in the rulemaking docket.

TABLE 21.—REGULATORY REQUIREMENTS THAT WILL REMAIN IN THE CFR

CFR section	Regulatory requirement
261.38	Lists of Hazardous Wastes. Comparable/syngas fuel exclusion.
261.38(c)(1)(i)(A)	Submit a one-time comparable/syngas fuel notice to the permitting agency.
264/5.16	General Facility Standards. Personnel training.
264/5.16(d)(1)	Record the job title.
264/5.16(d)(2)	Record job description.
264/5.16(d)(3)	Record type and amount of training employees will be provided.
264.90	Releases From Solid Waste Management Units. Applicability.
264.90(a)(2)	Comply with the requirements of 264.101 with exceptions for surface impoundments, waste piles, land treatment unit, or landfills.
264/5.98	Releases From Solid Waste Management Units. Detection monitoring program.
264.98(c)	Conduct and maintain ground-water monitoring.
264.98(g)(1)	Prepare and submit a notification of contamination.
264.98(g)(5)(ii)	Prepare and submit an engineering feasibility plan for corrective action.
264.98(g)(6)(i)–(ii)	Prepare and submit a notification of intent to make a demonstration.
264.99	Releases From Solid Waste Management Units. Compliance monitoring program.
264.99(h)(1)	Prepare and submit a notification of exceeded concentration limits.
264.99(i)(1)–(2)	Prepare and submit a notification of intent to make a demonstration.
264/5.174	Use and Management of Containers. Inspections.
264/5.174	Inspect containers weekly.
264/5.193	Tank Systems. Leak detection systems for tanks.
264.193(c)(3)	Demonstration.
264.193 (c)(4)	Demonstration.
264/5.193(e)(3)(iii)	Demonstrate to EPA that technology and site conditions do not allow detection of release within 24 hours.
264/5.193(g)	Variance from leak detection systems for tanks.
264/5.193(h)	Variance from leak detection systems for tanks.
264.196	Tank Systems. Response to leaks or spills and disposition of leaking or unfit-to use tank systems.
264.196(d)(1)	Notify EPA of release.
264.196(d)(2)	Notify EPA of release.
264.196(d)(3)	Submit report describing release.
264/5.223	Surface Impoundments. Response actions.
264/5.223(b)(1)	Notify EPA in writing if flow rate exceeds Action Leakage Rate for any sump within 7 days.
264/5.223(b)(2)	Submit a written assessment to the Regional Administrator within 14 days of determination of leakage.
264/5.223(b)(6)	Compile and submit information to EPA each month the Action Leakage Rate is exceeded.
264.253	Waste Piles. Response actions.
264.253(b)(1)	Notify EPA in writing of the exceedence within 7 days of the determination.
264.253(b)(2)	Submit a written assessment to the Regional Administrator within 14 days of determining leakage.
264.253(b)(6)	Compile and submit information to the EPA each month that the Action Leakage Rate is exceeded.
264.278	Land Treatment. Unsaturated zone monitoring.
264.278(g)(1)	Prepare and submit a notice of statistically significant increases in hazardous constituents below treatment zone.
264.278(h)(1)–(2)	Prepare and submit a notice of intent to make a demonstration that other sources or error led to increases below treatment zone.
264.304	Landfills. Response actions.
264.304(b)(1)	Notify EPA if Action Leakage Rate is exceeded within 7 days of determination.
264.304(b)(2)	Submit a written assessment to the Regional Administrator within 14 days of determination of leakage.
264.304(b)(6)	Submit information to EPA each month the Action Leakage Rate is exceeded.
264.573	Drip Pads. Design and operating standards.
264.573(m)(1)(iv)	Notify EPA in writing of release.
264.573(m)(2)	Regional Administrator will make a determination and will notify owner/operator of the determination.
264.573(m)(3)	Notify EPA and certify completion of repairs.
264.1036	Air Emission Standards for Process Vents. Reporting requirements.
264.1036(a)	Notify EPA semi-annually of exceedences.
264.1065	Air Emission Standards for Equipment Leaks. Reporting requirements.
264.1065(a)	Notify EPA semi-annually of exceedences.
264/5.1101	Containment Buildings. Design and operating standards.
265.1101(c)(2)	Certify by qualified professional engineer.
264/5.1101(c)(3)(i)(D)	Notify EPA in writing of release.
264/5.1101(c)(3)(ii)–(iii)	Notify EPA and verify in writing that the cleanup and repairs have been completed after a release.
264/5.1101(c)(4)	Inspection frequency.
265.1(b)	Purpose, scope, and applicability.
265.93	Ground-Water Monitoring. Preparation, evaluation, and response.
265.93(c)(1)	Notify of increased indicator parameter concentrations.
265.93(d)(1)	Notify of increased indicator parameter concentrations.
265.93(e)	Any ground-water assessment to satisfy the requirements of §265.93(d)(4) which is initiated prior to final closure must be completed and reported in accordance with §265.93(d)(5).

TABLE 21.—REGULATORY REQUIREMENTS THAT WILL REMAIN IN THE CFR—Continued

CFR section	Regulatory requirement
265.93(f)	Evaluate data and if §265.91(a) are not satisfied, immediately modify the number, location, or depth of the monitoring wells.
265.94	Ground-Water Monitoring. Recordkeeping and reporting.
265.94(a)(2)(i)	Prepare and submit a quarterly report of concentrations of values of the drinking water suitability parameters.
265.94(a)(2)(ii)	Prepare and submit a report on indicator parameter concentrations and evaluations.
265.94(a)(2)(iii)	Prepare and submit a report on ground-water surface elevations.
265.94(b)(2)	Prepare and submit a report on the results of the ground-water quality assessment program.
265.259	Waste Piles. Response actions.
265.259(b)(1)	Notify EPA in writing within 7 days of determination.
265.259(b)(2)	Submit a written assessment to the Regional Administrator within 14 days of determination of leakage.
265.259(b)(6)	Submit information to EPA each month that the Action Leakage Rate is exceeded.
265.276	Land Treatment. Food-chain crops.
265.276(a)	Submit notification for food-chain crops at land treatment facility.
265.303	Landfills. Response actions.
265.303(b)(1)	Notify EPA if Action Leakage Rate is exceeded within 7 days of determination.
265.303(b)(2)	Submit a written assessment to the Regional Administrator within 14 days of determination of leakage.
265.303(b)(6)	Submit information to EPA each month the Action Leakage Rate is exceeded.
265.443	Drip Pads. Design and operating requirements.
265.443(m)(1)(iv)(2)	Notify EPA of release and provide written notice of procedures and schedule for cleanup.
265.443(m)(2)	Regional Administrator will make a determination and notify the owner/operator of the determination.
265.443(m)(3)	Notify Regional Administrator and certify completion of repairs.
266.103	Hazardous Waste Burned in Boilers and Industrial Furnaces. Interim status standards for burners.
266.103(b)(2)(ii)(D)	Certification of pre-compliance.
268.7	Land Disposal Restrictions. General. Testing, tracking, and recordkeeping requirements for generators, treaters, and disposal facilities.
268.7(a)(6)	Requirement to keep in the facility's files all supporting data and waste analysis data for "knowledge of the waste" determinations and for testing determinations.
268.7(d)(1)	Requirement to submit to the regulatory authority one-time notifications that hazardous debris is excluded form the definition of hazardous waste,
270.17(d)	Permit Application. Specific part B information requirements for surface impoundments.

V. We Will Implement This Rule Via the Class 1 Permit Modification Process Without Prior Approval

Several comments on the proposed rule pointed out that implementing many of the changes in the proposal would require a Class 2 Permit modification for facilities with permits (see the following Web site for information about Permit modifications: *http://www.epa.gov/epaoswer/hotline/training/perm.pdf*). Obtaining a Class 2 Permit modification requires a substantial effort on the part of a regulated facility, which is contrary to the intent of today's rule. We believe the changes in this rule will provide no significant risk to human health or the environment, and thus, we prefer that these changes become effective as quickly as possible so that the paperwork reduction benefits from the rule can be realized.

Therefore, in our October 29, 2003 NODA, we requested comment on allowing permitted facilities to use the Class 1 permit modification procedure, with prior Agency approval, to implement the changes arising from this rulemaking. We also requested comment on whether the Class 1 permit modifications should be without prior Agency approval.

States represented by the Association of State and Territorial Solid Waste Management Officials (ASTSWMO) requested that we use the Class 1 permit modification procedure with prior Agency approval. They expressed an interest in retaining oversight in the implementation of our burden reductions. After weighing this interest against the interest in achieving savings as soon as possible, we have decided in favor of not delaying the benefits of this rule. This is based on our judgment that, in general, the risks associated with these changes are negligible. We will allow the changes in today's rule to be implemented as Class 1 permit modifications without prior approval, except for a permit modification for reduced inspection frequency for Performance Track member facilities which will be implemented as a Class 1 permit modification with prior approval. To implement this approach, we are adding regulatory language and an entry to the permit modification classification table in Appendix I to 270.42, denoting modifications pursuant to the burden reduction rule. However, we wish to point out that, unless state law prevents it, states can be more stringent than the EPA rules if there are specific concerns with the consequences of these changes in any state. All states also can use the omnibus authority of RCRA Section 3005(c) for specific facilities where they believe there is risk due to site-specific circumstances not identified in our rulemaking process. This will allow states to retain oversight where they choose to do so.

VI. How Will Today's Regulatory Changes Be Administered and Enforced in the States?

A. Applicability of Federal Rules in Authorized States

Under section 3006 of RCRA, EPA may authorize qualified states to administer their own hazardous waste programs in lieu of the federal program within the state. Following authorization, EPA retains enforcement authority under sections 3008, 3013, and 7003 of RCRA, although authorized states have primary enforcement responsibility. The standards and requirements for state authorization are found at 40 CFR Part 271.

Prior to enactment of the Hazardous and Solid Waste Amendments of 1984 (HSWA), a state with final RCRA authorization administered its hazardous waste program entirely in lieu of EPA administering the federal program in that state. The federal requirements no longer applied in the authorized state, and EPA could not issue permits for any facilities in that state, since only the state was authorized to issue RCRA permits. When new, more stringent federal

requirements were promulgated, the state was obligated to enact equivalent authorities within specified time frames. However, the new federal requirements did not take effect in an authorized state until the state adopted the federal requirements as state law.

In contrast, under RCRA section 3006(g) (42 U.S.C. 6926(g)), which was added by HSWA, new requirements and prohibitions imposed under HSWA authority take effect in authorized states at the same time that they take effect in unauthorized states. EPA is directed by the statute to implement these requirements and prohibitions in authorized states, including the issuance of permits, until the state is granted authorization to do so. While states must still adopt HSWA related provisions as state law to retain final authorization, EPA implements the HSWA provisions in authorized states until the states do so.

Authorized states are required to modify their programs only when EPA enacts federal requirements that are more stringent or broader in scope than existing federal requirements. RCRA section 3009 allows the states to impose standards more stringent than those in the federal program (see also 40 CFR 271.1). Therefore, authorized states may, but are not required to, adopt federal regulations, both HSWA and non-HSWA, that are considered less stringent than previous federal regulations.

B. Authorization of States for Today's Rule

Today's rule affects many aspects of the RCRA program and is promulgated pursuant to both HSWA and non-HSWA statutory authority. Today's rule amends a number of provisions in the RCRA regulations which were promulgated pursuant to HSWA. These provisions include, among others, the land disposal restrictions and the regulation of air emissions from hazardous waste facilities, which were promulgated pursuant to authority in sections 3004(m) and (o) respectively, of RCRA. Therefore, the Agency is adding the rule to Table 1 in 40 CFR 271.1(j), which identifies the Federal program requirements that are promulgated pursuant to the statutory authority that was added by HSWA.

Other sections of today's rule are being promulgated pursuant to non-HSWA authority. All of the HSWA and non-HSWA requirements in today's rulemaking are equivalent to, or less stringent than, the existing provisions in the Federal regulations which they would amend. Authorized states are required to modify their program only when EPA promulgates Federal regulations that are more stringent or broader in scope than the authorized state regulations. For those changes that are less stringent or reduce the scope of the Federal program, states are not required to modify their program. This is a result of section 3009 of RCRA, which allows states to impose more stringent regulations than the Federal program. Therefore, states are not required to adopt and seek authorization for this rulemaking. EPA will implement this rulemaking only in those states which are not authorized for the RCRA program, and will implement provisions promulgated pursuant to HSWA only in those states which have not received authorization for the HSWA provision that is amended today.

Nevertheless, this rule will provide significant benefits to EPA, states, and the regulated community, without compromising human health or environmental protection. Because this rulemaking will not become effective in authorized states until they have adopted and are authorized for it, we strongly encourage states to amend their programs and seek authorization for today's rule. EPA will try to act promptly on any such requests for authorization.

VII. Statutory and Executive Reviews

A. Executive Order 12866: Regulatory Planning and Review

Under Executive Order 12866 (58 FR 51735, October 4, 1993), the Agency must determine whether a regulatory action is significant and therefore subject to OMB review and the requirements of the Executive Order. The Order defines significant regulatory action as one that is likely to result in a rule that may: (1) Have an annual effect on the economy of $100 million or more or adversely affect in a material way the economy, a sector of the economy, productivity, competition, jobs, the environment, public health or safety, or state, local, or tribal governments or communities; (2) create a serious inconsistency or otherwise interfere with an action taken or planned by another agency; (3) materially alter the budgetary impact of entitlements, grants, user fees, or loan programs or the rights and obligations of recipients thereof; or (4) raise novel legal or policy issues arising out of legal mandates, the President's priorities, or the principles set forth in the Executive Order.

Although this rule clarifies inconsistencies in the regulations and decreases burden, it is still considered a significant regulatory action under the terms of Executive Order 12866 since it addresses one of the President's priorities of reducing burden.

B. Paperwork Reduction Act

This action does not impose any new information collection burden. This rule is promulgating changes to the regulatory requirements of the RCRA hazardous waste program to reduce the paperwork burden certain requirements impose on the States, EPA, and the regulated community. EPA estimates that the reporting and recordkeeping hour burden reduction for this rule ranges from 22,000 hours to 37,500 hours. EPA also estimates that the reporting and recordkeeping cost burden reduction for this rule ranges from approximately $2 million to $3 million. The Office of Management and Budget (OMB) has previously approved the information collection requirements contained in the existing regulations 40 CFR parts 260, 261, 264, 265, 266, 268, 270, and 271, under the provisions of the Paperwork Reduction Act, 44 U.S.C. 3501 *et seq.* The burden reduction resulting from this rulemaking will affect the following seven existing Information Collection Requests (ICRs): OMB control number 2050–0033, Facility Groundwater Monitoring Requirements, EPA ICR number 0959.12; OMB control number 2050–0035, Hazardous Waste Generator Standards, EPA ICR number 0820.09; OMB control number 2050–0050, Hazardous Waste Specific Unit Requirements and Special Waste Processes and Types, EPA ICR number 1572.06; OMB control number 2050–0053, Identification, Listing and Rulemaking Petitions, EPA ICR number 1189.14; OMB control number 2050–0073, Boilers and Industrial Furnaces: General Hazardous Waste Facility Standards, Specific Unit Requirements and Part B Permit Application and Modifications Requirements, EPA ICR number 1361.10; OMB control number 2050–0085, Land Disposal Restrictions, EPA ICR number 1442.18; OMB control number 2050–0120, General Hazardous Waste Facility Standards, EPA ICR number 1571.07. A copy of these OMB approved Information Collection Requests (ICR) may be obtained from Susan Auby, Collection Strategies Division; U.S. Environmental Protection Agency (2822T); 1200 Pennsylvania Ave., NW., Washington, DC 20460 or by calling (202) 566–1672.

Burden means the total time, effort, or financial resources expended by persons to generate, maintain, retain, or disclose or provide information to or for a Federal agency. This includes the time needed to review instructions; develop,

acquire, install, and utilize technology and systems for the purposes of collecting, validating, and verifying information, processing and maintaining information, and disclosing and providing information; adjust the existing ways to comply with any previously applicable instructions and requirements; train personnel to be able to respond to a collection of information; search data sources; complete and review the collection of information; and transmit or otherwise disclose the information.

An agency may not conduct or sponsor, and a person is not required to respond to a collection of information unless it displays a currently valid OMB control number. The OMB control numbers for EPA's regulations in 40 CFR are listed in 40 CFR part 9.

C. Regulatory Flexibility Act

The Regulatory Flexibility Act (RFA), generally requires an agency to prepare a regulatory flexibility analysis of any rule subject to notice and comment rulemaking requirements under the Administrative Procedure Act or any other statute unless the agency certifies that the rule will not have a significant economic impact on a substantial number of small entities. Small entities include small businesses, small organizations, and small governmental jurisdictions.

For purposes of assessing the impacts of the final rule on small entities, a "small entity" is defined as: (1) A small business as defined by the Small Business Administration's (SBA) regulations at 13 CFR 121.201; (2) a small governmental jurisdiction that is a government of a city, county, town, school district or special district with a population of less than 50,000; and (3) a small organization that is any not-for-profit enterprise which is independently owned and operated and is not dominant in its field.

After considering the economic impacts of today's final rule on small entities, I certify that this action will not have a significant economic impact on a substantial number of small entities. In determining whether a rule has a significant economic impact on a substantial number of small entities, the impact of concern is any significant adverse economic impact on small entities, since the primary purpose of the regulatory flexibility analyses is to identify and address regulatory alternatives "which minimize any significant economic impact of the rule on small entities." 5 U.S.C. 603 and 604. Thus, an agency may certify that a rule will not have a significant economic impact on a substantial number of small entities if the rule relieves regulatory burden, or otherwise has a positive economic effect on all of the small entities subject to the rule.

The final rule is specifically intended to reduce, not increase, the paperwork and related burdens of the RCRA hazardous waste program. For businesses in general, including all small businesses, the regulatory changes will reduce the labor time and other costs of preparing, keeping records of, and submitting reports to the Agency. The final rule, for example, reduces the frequency by which businesses must conduct specified recordkeeping and reporting activities (*e.g.*, decreased inspection frequency for hazardous waste tanks from daily to weekly). It also eliminates certain recordkeeping and reporting requirements altogether, *i.e.*, in cases where the documents are little used by the public or regulators. In addition, the rule eliminates redundancies between the RCRA regulations and other regulatory programs (*e.g.*, RCRA and OSHA requirements for personnel training), thereby streamlining facilities' compliance activities. Finally, the rule provides increased flexibility in how waste handlers may comply with the regulations (*e.g.*, establishment of decreased inspection frequencies for facilities in the National Performance Track Program). We have therefore concluded that today's final rule will relieve regulatory burden for all affected small entities.

D. Unfunded Mandates Reform Act

Title II of the Unfunded Mandates Reform Act of 1995 (UMRA) establishes requirements for Federal agencies to assess the effects of their regulatory actions on state, local, and tribal governments and the private sector. Under Section 202 of the UMRA, EPA must prepare a written statement for rules with Federal mandates that may result in the expenditure by state, local, and tribal governments, in the aggregate, or by the private sector, of $100 million or more in any one year. Before promulgating a rule for which a written statement is needed, Section 205 of the UMRA requires EPA to identify and consider a reasonable number of regulatory alternatives and adopt the least costly, most cost-effective or least burdensome alternative that achieves the objectives of the rule. The provisions of Section 205 do not apply when they are inconsistent with applicable law. Moreover, Section 205 allows EPA to adopt an alternative other than the least costly, most cost-effective or least burdensome alternative if the Administrator publishes with the final rule an explanation of why that alternative was not adopted.

Before EPA establishes any regulatory requirements that may significantly or uniquely affect small governments, including tribal governments, it must have developed, under Section 203 of the UMRA, a small government agency plan. The plan must provide for notifying potentially affected small governments; enabling officials of affected small governments to provide meaningful and timely input in the development of EPA regulatory proposals with significant federal intergovernmental mandates; and informing, educating, and advising small governments on compliance with the regulatory requirements.

EPA has determined that the final rule does not contain a federal mandate that may result in expenditures of $100 million or more by State, local, and tribal governments, in the aggregate, or by the private sector, in any one year. In addition, the rule contains no regulatory requirements for small governments. Thus, the final rule is not subject to the requirements of Sections 202, 203, and 205 of the UMRA.

E. Executive Order 13132: Federalism

Executive Order 13132 requires EPA to develop an accountable process to ensure "meaningful and timely input by state and local officials in the development of regulatory policies that have Federalism implications." As defined in Executive Order 13132, "policies that have Federalism implications" include regulations, legislative comments or proposed legislation, and other policy statements or actions that have substantial direct effects on the states, on the relationship between the National Government and the states, or on the distribution of power and responsibilities among the various levels of government.

Under Section 6 of Executive Order 13132, EPA may not issue a regulation that has federalism implications, that imposes substantial direct compliance costs, and that is not required by statute, unless the Federal Government provides the funds necessary to pay the direct compliance costs incurred by state and local governments, or EPA consults with state and local officials early in the process of developing the proposed regulation. EPA may not issue a regulation that has federalism implications and that preempts state law, unless the Agency consults with state and local officials early in the process of developing the proposed regulation.

The final rule does not have federalism implications. It will not have

substantial direct effects on the states, on the relationship between the National Government and the states, or on the distribution of power and responsibilities among the various levels of government, as specified in Executive Order 13132, because it will not impose any requirements on states or any other level of government. As explained above, the final rule eliminates or relaxes many of the paperwork requirements in the regulations. Because these changes are equivalent to or less stringent than the existing federal program, states will not be required to adopt and seek authorization for them. Thus, the requirements of Section 6 of the Executive Order do not apply to this rule.

F. Executive Order 13175: Consultation and Coordination With Indian Tribal Governments

Executive Order 13175 requires EPA to develop an accountable process to ensure "meaningful and timely input by Tribal officials in the development of regulatory policies that have Tribal implications." As defined in Executive Order 13175, "policies that have Tribal implications" include regulations, legislative comments or proposed legislation, and other policy statements or actions that have substantial direct effects on one or more Indian Tribes, on the relationship between the Federal Government and Indian Tribes, or on the distribution of power and responsibilities between the Federal Government and Indian Tribes.

The final rule does not have tribal implications. It will not have substantial direct effects on Tribal governments, on the relationship between the Federal Government and Indian Tribes, or on the distribution of power and responsibilities between the Federal Government and Indian Tribes, as specified in Executive Order 13175. As explained above, the final rule eliminates or relaxes many of the paperwork requirements in the regulations. Thus, Executive Order 13175 does not apply to this rule.

G. Executive Order 13045: Protection of Children From Environmental Health & Safety Risks

Executive Order 13045 applies to any rule that may: (1) Be "economically significant" under Executive Order 12866 (*i.e.*, a rulemaking that has an annual effect on the economy of $100 million or more or would adversely affect in a material way the economy, a sector of the economy, productivity, competition, jobs, the environment, public health or safety, or state, local, or tribal governments or communities), and (2) concern an environmental health or safety risk that EPA has reason to believe may have a disproportionate effect on children. If the regulatory action meets both criteria, the Agency must evaluate the environmental health or safety effects of the planned rule on children, and explain why the planned regulation is preferable to other potentially effective and reasonably feasible alternatives considered by the Agency.

EPA has determined that the final rule is not subject to Executive Order 13045 because it is not an "economically significant" rule as defined by Executive Order 12866. EPA also expects the rule does not have a disproportionate effect on children's health. The basic reason for this finding is that the rule modifies or eliminates paperwork requirements that were deemed unnecessary or infrequently used by regulators. However, the rule preserves the technical requirements underlying these paperwork requirements. In addition, regulators continue to have access to all facility paperwork held on site, should the need arise.

In addition, EPA has reduced the inspection frequency of tank systems from each operating day to at least weekly, provided that the tank systems have full secondary containment with leak detection equipment or established workplace practices that will alert facility personnel. SQG tank systems are required to have secondary containment with leak detection equipment or established workplace practices to adopt the weekly inspections.

H. Executive Order 13211: Actions That Significantly Affect Energy Supply, Distribution, or Use

Executive Order 13211 requires EPA to prepare and submit a Statement of Energy Effects to OMB for those matters identified as significant energy actions. As defined in Executive Order 13211, a "significant energy action" is any action by an agency (normally published in the **Federal Register**) that promulgates or is expected to lead to the promulgation of a final rule or regulation, including notices of inquiry, advance notices of proposed rulemaking, and notices of proposed rulemaking that: (1) Is a significant regulatory action under Executive Order 12866 or any successor order and is likely to have a significant adverse effect on the supply, distribution, or use of energy; or (2) is designated by OMB as a significant energy action.

The final rule does not involve the supply, distribution, or use of energy. Thus, Executive Order 13211 does not apply to this rule.

I. National Technology Transfer and Advancement Act of 1995

Section 12(d) of the National Technology Transfer and Advancement Act of 1995 (NTTAA), Public Law 104–113, directs EPA to use voluntary consensus standards in its regulatory activities unless to do so would be inconsistent with applicable law or otherwise impractical. Voluntary consensus standards are technical standards (*e.g.*, materials specifications, test methods, sampling procedures) that are developed or adopted by voluntary consensus standards bodies. The NTTAA also directs EPA to provide Congress, through OMB, explanations when the Agency decides not to use available and applicable voluntary consensus standards.

The final rule does not involve technical standards. Therefore, EPA did not consider the use of any voluntary consensus standards.

J. Executive Order 12898: Federal Actions To Address Environmental Justice in Minority Populations and Low-Income Populations

Under Executive Order 12898, as well as through EPA's April 1995 "Environmental Justice Strategy, OSWER Environmental Justice Task Force Action Agency Report" and National Environmental Justice Advisory Council, EPA has undertaken to incorporate environmental justice into its policies and programs. EPA is committed to addressing environmental justice concerns, and is assuming a leadership role in environmental justice initiatives to enhance environmental quality for all residents of the U.S. The Agency's goals are to ensure that no segment of the population, regardless of race, color, national origin, or income, bears disproportionately high and adverse human health and environmental effects as a result of EPA's policies, programs, and activities.

EPA has considered the impacts of the final rule on low-income populations and minority populations and concluded that there are no disproportionately high impacts under the rule. The basic reason for this finding is that the rule modifies or eliminates paperwork requirements that were deemed unnecessary or infrequently used by regulators. However, the rule preserves the technical requirements underlying these paperwork requirements. In addition, regulators continue to have access to all facility paperwork held on site, should the need arise.

In addition, EPA has reduced the inspection frequency of tank systems from each operating day to at least weekly, provided that the tank systems have full secondary containment with leak detection equipment or workplace practices that will alert facility personnel.

K. Congressional Review Act

The Congressional Review Act, 5 U.S.C. 801 *et seq.*, as added by the Small Business Regulatory Enforcement Fairness Act of 1996, generally provides that before a rule may take effect, the agency promulgating the rule must submit a rule report, which includes a copy of the rule, to each House of the Congress and to the Comptroller General of the United States. EPA will submit a report containing this rule and other required information to the U.S. Senate, the U.S. House of Representatives, and the Comptroller General of the United States prior to publication of the rule in the **Federal Register**. A major rule cannot take effect until 60 days after it is published in the **Federal Register**. This action is not a "major rule" as defined by 5 U.S.C. 804(2). This rule will be effective May 4, 2006.

List of Subjects

40 CFR Part 260

Environmental protection, Administrative practice and procedure, Confidential business information, Hazardous waste Reporting and recordkeeping requirements.

40 CFR Part 261

Excluded hazardous waste, Hazardous waste, Reporting and recordkeeping requirements.

40 CFR Part 264

Air pollution control, Hazardous waste, Insurance, Packaging and containers, Reporting and recordkeeping requirements, Security measures, Surety bonds.

40 CFR Part 265

Air pollution control, Hazardous waste, Insurance, Packaging and containers, Reporting and recordkeeping requirements, Security measures, Surety bonds, Water supply.

40 CFR Part 266

Energy, Hazardous waste, Recycling, Reporting and recordkeeping requirements.

40 CFR Part 268

Hazardous waste, Reporting and recordkeeping requirements.

40 CFR Part 270

Administrative practice and procedure, Confidential business information, Hazardous materials transportation, Hazardous waste, Reporting and recordkeeping requirements, Water pollution control, Water supply.

40 CFR Part 271

Administrative practice and procedure, Confidential business information, Hazardous materials transportation, Hazardous waste, Indians-lands, Intergovernmental relations, Penalties, Reporting and recordkeeping requirements, Water pollution control, Water supply.

Dated: March 15, 2006.

Stephen L. Johnson,

Administrator.

■ For the reasons set out in the preamble, title 40 of the Code of Federal Regulations is amended as follows:

PART 260—HAZARDOUS WASTE MANAGEMENT SYSTEM: GENERAL

■ 1. The authority citation for part 260 continues to read as follows:

Authority: 42 U.S.C. 6905, 6912(a), 6921–6927, 6930, 6934, 6935, 6937, 6938, 6939, and 6974.

Subpart B—Definitions

■ 2. Section 260.10 is amended by adding in alphabetical order the definition of "Performance Track member facility" to read as follows:

§ 260.10 Definitions.

* * * * *

Performance Track member facility means a facility that has been accepted by EPA for membership in the National Environmental Performance Track Program and is still a member of the Program. The National Environmental Performance Track Program is a voluntary, facility based, program for top environmental performers. Facility members must demonstrate a good record of compliance, past success in achieving environmental goals, and commit to future specific quantified environmental goals, environmental management systems, local community outreach, and annual reporting of measurable results.

* * * * *

Subpart C—Rulemaking Petitions

§ 260.31 [Amended]

■ 3. Section 260.31 is amended by removing paragraph (b)(2) and redesignating paragraphs (b)(3) through (b)(8) as (b)(2) through (b)(7).

PART 261—IDENTIFICATION AND LISTING OF HAZARDOUS WASTE

■ 4. The authority citation for part 261 continues to read as follows:

Authority: 42 U.S.C. 6905, 6912(a), 6921, 6922, 6924(y), and 6938.

Subpart A—General

■ 5. Section 261.4 is amended by revising paragraphs (a)(9)(iii)(E) and (f)(9) introductory text to read as follows:

§ 261.4 Exclusions.

(a) * * *

(9) * * *

(iii) * * *

(E) Prior to operating pursuant to this exclusion, the plant owner or operator prepares a one-time notification stating that the plant intends to claim the exclusion, giving the date on which the plant intends to begin operating under the exclusion, and containing the following language: "I have read the applicable regulation establishing an exclusion for wood preserving wastewaters and spent wood preserving solutions and understand it requires me to comply at all times with the conditions set out in the regulation." The plant must maintain a copy of that document in its on-site records until closure of the facility. The exclusion applies so long as the plant meets all of the conditions. If the plant goes out of compliance with any condition, it may apply to the appropriate Regional Administrator or state Director for reinstatement. The Regional Administrator or state Director may reinstate the exclusion upon finding that the plant has returned to compliance with all conditions and that the violations are not likely to recur.

* * * * *

(f) * * *

(9) The facility prepares and submits a report to the Regional Administrator, or state Director (if located in an authorized state), by March 15 of each year, that includes the following information for the previous calendar year:

* * * * *

PART 264—STANDARDS FOR OWNERS AND OPERATORS OF HAZARDOUS WASTE TREATMENT, STORAGE, AND DISPOSAL FACILITIES

■ 6. The authority citation for part 264 continues to read as follows:

Authority: 42 U.S.C. 6905, 6912(a), 6924, and 6925.

Subpart B—General Facility Standards

■ 7. Section 264.15 is amended by revising paragraph (b)(4) (the comment to paragraph (b)(4) is unchanged), and adding paragraph (b)(5) to read as follows:

§ 264.15 General inspection requirements.

* * * * *

(b) * * *

(4) The frequency of inspection may vary for the items on the schedule. However, the frequency should be based on the rate of deterioration of the equipment and the probability of an environmental or human health incident if the deterioration, malfunction, or operator error goes undetected between inspections. Areas subject to spills, such as loading and unloading areas, must be inspected daily when in use, except for Performance Track member facilities, that must inspect at least once each month, upon approval by the Director, as described in paragraph (b)(5) of this section. At a minimum, the inspection schedule must include the items and frequencies called for in §§ 264.174, 264.193, 264.195, 264.226, 264.254, 264.278, 264.303, 264.347, 264.602, 264.1033, 264.1052, 264.1053, 264.1058, and 264.1083 through 264.1089 of this part, where applicable.

* * * * *

(5) Performance Track member facilities that choose to reduce their inspection frequency must:

(i) Submit a request for a Class I permit modification with prior approval to the Director. The modification request must identify the facility as a member of the National Environmental Performance Track Program and identify the management units for reduced inspections and the proposed frequency of inspections. The modification request must also specify, in writing, that the reduced inspection frequency will apply for as long as the facility is a Performance Track member facility, and that within seven calendar days of ceasing to be a Performance Track member, the facility will revert to the non-Performance Track inspection frequency. Inspections must be conducted at least once each month.

(ii) Within 60 days, the Director will notify the Performance Track member facility, in writing, if the request is approved, denied, or if an extension to the 60-day deadline is needed. This notice must be placed in the facility's operating record. The Performance Track member facility should consider the application approved if the Director does not: deny the application; or notify the Performance Track member facility of an extension to the 60-day deadline. In these situations, the Performance Track member facility must adhere to the revised inspection schedule outlined in its request for a Class 1 permit modification and keep a copy of the application in the facility's operating record.

(iii) Any Performance Track member facility that discontinues their membership or is terminated from the program must immediately notify the Director of their change in status. The facility must place in its operating record a dated copy of this notification and revert back to the non-Performance Track inspection frequencies within seven calendar days.

* * * * *

■ 8. Section 264.16 is amended by adding new paragraph (a)(4) to read as follows:

§ 264.16 Personnel training.

(a)(1) * * *

(4) For facility employees that receive emergency response training pursuant to Occupational Safety and Health Administration (OSHA) regulations 29 CFR 1910.120(p)(8) and 1910.120(q), the facility is not required to provide separate emergency response training pursuant to this section, provided that the overall facility training meets all the requirements of this section.

* * * * *

Subpart D—Contingency Plan and Emergency Procedures

■ 9. Section 264.52 is amended by revising paragraph (b) to read as follows:

§ 264.52 Content of contingency plan.

* * * * *

(b) If the owner or operator has already prepared a Spill Prevention, Control, and Countermeasures (SPCC) Plan in accordance with part 112 of this chapter, or part 1510 of chapter V, or some other emergency or contingency plan, he need only amend that plan to incorporate hazardous waste management provisions that are sufficient to comply with the requirements of this part. The owner or operator may develop one contingency plan which meets all regulatory requirements. EPA recommends that the plan be based on the National Response Team's Integrated Contingency Plan Guidance ("One Plan"). When modifications are made to non-RCRA provisions in an integrated contingency plan, the changes do not trigger the need for a RCRA permit modification.

* * * * *

§ 264.56 [Amended]

■ 10. Section 264.56 is amended by removing paragraph (i) and redesignating paragraph (j) as paragraph (i).

Subpart E—Manifest System, Recordkeeping, and Reporting

■ 11. Section 264.73 is amended by revising paragraphs (b) introductory text, (b)(1), (b)(2) (the comment to (b)(2) remains unchanged), (b)(6), (b)(8), and (b)(10), and by adding paragraphs (b)(18) and (b)(19) to read as follows:

§ 264.73 Operating record.

* * * * *

(b) The following information must be recorded, as it becomes available, and maintained in the operating record for three years unless noted as follows:

(1) A description and the quantity of each hazardous waste received, and the method(s) and date(s) of its treatment, storage, or disposal at the facility as required by appendix I of this part. This information must be maintained in the operating record until closure of the facility;

(2) The location of each hazardous waste within the facility and the quantity at each location. For disposal facilities, the location and quantity of each hazardous waste must be recorded on a map or diagram that shows each cell or disposal area. For all facilities, this information must include cross-references to manifest document numbers if the waste was accompanied by a manifest. This information must be maintained in the operating record until closure of the facility.

* * * * *

(6) Monitoring, testing or analytical data, and corrective action where required by subpart F of this part and §§ 264.19, 264.191, 264.193, 264.195, 264.222, 264.223, 264.226, 264.252–264.254, 264.276, 264.278, 264.280, 264.302–264.304, 264.309, 264.602, 264.1034(c)–264.1034(f), 264.1035, 264.1063(d)–264.1063(i), 264.1064, and 264.1082 through 264.1090 of this part. Maintain in the operating record for three years, except for records and results pertaining to ground-water monitoring and cleanup which must be maintained in the operating record until closure of the facility.

* * * * *

(8) All closure cost estimates under § 264.142, and for disposal facilities, all post-closure cost estimates under § 264.144 of this part. This information must be maintained in the operating record until closure of the facility.

* * * * *

(10) Records of the quantities and date of placement for each shipment of hazardous waste placed in land disposal units under an extension to the effective date of any land disposal restriction granted pursuant to § 268.5 of this chapter, a petition pursuant to § 268.6 of this chapter, or a certification under § 268.8 of this chapter, and the applicable notice required by a generator under § 268.7(a) of this chapter. This information must be maintained in the operating record until closure of the facility.

* * * * *

(18) Monitoring, testing or analytical data where required by § 264.347 must be maintained in the operating record for five years.

(19) Certifications as required by § 264.196(f) must be maintained in the operating record until closure of the facility.

Subpart F—Releases From Solid Waste Management Units

■ 12. Section 264.98 is amended by revising paragraphs (d), (g)(2), and (g)(3) to read as follows:

§ 264.98 Detection monitoring program.

* * * * *

(d) The Regional Administrator will specify the frequencies for collecting samples and conducting statistical tests to determine whether there is statistically significant evidence of contamination for any parameter or hazardous constituent specified in the permit conditions under paragraph (a) of this section in accordance with § 264.97(g).

* * * * *

(g) * * *

(2) Immediately sample the ground water in all monitoring wells and determine whether constituents in the list of appendix IX of this part are present, and if so, in what concentration. However, the Regional Administrator, on a discretionary basis, may allow sampling for a site-specific subset of constituents from the Appendix IX list of this part and other representative/related waste constituents.

(3) For any appendix IX compounds found in the analysis pursuant to paragraph (g)(2) of this section, the owner or operator may resample within one month or at an alternative site-specific schedule approved by the Administrator and repeat the analysis for those compounds detected. If the results of the second analysis confirm the initial results, then these constituents will form the basis for compliance monitoring. If the owner or operator does not resample for the compounds in paragraph (g)(2) of this section, the hazardous constituents found during this initial appendix IX analysis will form the basis for compliance monitoring.

* * * * *

■ 13. Section 264.99 is amended by revising paragraphs (f) and (g) to read as follows:

§ 264.99 Compliance monitoring program.

* * * * *

(f) The Regional Administrator will specify the frequencies for collecting samples and conducting statistical tests to determine statistically significant evidence of increased contamination in accordance with § 264.97(g).

(g) Annually, the owner or operator must determine whether additional hazardous constituents from Appendix IX of this part, which could possibly be present but are not on the detection monitoring list in the permit, are actually present in the uppermost aquifer and, if so, at what concentration, pursuant to procedures in § 264.98(f). To accomplish this, the owner or operator must consult with the Regional Administrator to determine on a case-by-case basis: which sample collection event during the year will involve enhanced sampling; the number of monitoring wells at the compliance point to undergo enhanced sampling; the number of samples to be collected from each of these monitoring wells; and, the specific constituents from Appendix IX of this part for which these samples must be analyzed. If the enhanced sampling event indicates that Appendix IX constituents are present in the ground water that are not already identified in the permit as monitoring constituents, the owner or operator may resample within one month or at an alternative site-specific schedule approved by the Regional Administrator, and repeat the analysis. If the second analysis confirms the presence of new constituents, the owner or operator must report the concentration of these additional constituents to the Regional Administrator within seven days after the completion of the second analysis and add them to the monitoring list. If the owner or operator chooses not to resample, then he or she must report the concentrations of these additional constituents to the Regional Administrator within seven days after completion of the initial analysis, and add them to the monitoring list.

* * * * *

■ 14. Section 264.100 is amended by revising paragraph (g) to read as follows:

§ 264.100 Corrective action program.

* * * * *

(g) The owner or operator must report in writing to the Regional Administrator on the effectiveness of the corrective action program. The owner or operator must submit these reports annually.

* * * * *

Subpart G—Closure and Post-Closure

■ 15. Section 264.113 is amended by revising paragraph (e)(5) to read as follows:

§ 264.113 Closure; time allowed for closure.

* * * * *

(e) * * *

(5) During the period of corrective action, the owner or operator shall provide annual reports to the Regional Administrator describing the progress of the corrective action program, compile all ground-water monitoring data, and evaluate the effect of the continued receipt of non-hazardous wastes on the effectiveness of the corrective action.

* * * * *

■ 16. Section 264.115 is revised to read as follows:

§ 264.115 Certification of closure.

Within 60 days of completion of closure of each hazardous waste surface impoundment, waste pile, land treatment, and landfill unit, and within 60 days of the completion of final closure, the owner or operator must submit to the Regional Administrator, by registered mail, a certification that the hazardous waste management unit or facility, as applicable, has been closed in accordance with the specifications in the approved closure plan.. The certification must be signed by the owner or operator and by a qualified Professional Engineer. Documentation supporting the Professional Engineer's certification must be furnished to the Regional Administrator upon request until he releases the owner or operator from the financial assurance requirements for closure under § 264.143(i).

■ 17. Section 264.120 is revised to read as follows:

§ 264.120 Certification of completion of post-closure care.

No later than 60 days after completion of the established post-closure care period for each hazardous waste disposal unit, the owner or operator must submit to the Regional Administrator, by registered mail, a certification that the post-closure care period for the hazardous waste disposal unit was performed in accordance with

the specifications in the approved post-closure plan. The certification must be signed by the owner or operator and a qualified Professional Engineer. Documentation supporting the Professional Engineer's certification must be furnished to the Regional Administrator upon request until he releases the owner or operator from the financial assurance requirements for post-closure care under § 264.145(i).

Subpart H—Financial Requirements

■ 18. Section 264.143 is amended by revising paragraph (i) to read as follows:

§ 264.143 Financial assurance for closure.

* * * * *

(i) *Release of the owner or operator from the requirements of this section.* Within 60 days after receiving certifications from the owner or operator and a qualified Professional Engineer that final closure has been completed in accordance with the approved closure plan, the Regional Administrator will notify the owner or operator in writing that he is no longer required by this section to maintain financial assurance for final closure of the facility, unless the Regional Administrator has reason to believe that final closure has not been in accordance with the approved closure plan. The Regional Administrator shall provide the owner or operator a detailed written statement of any such reason to believe that closure has not been in accordance with the approved closure plan.

■ 19. Section 264.145 is amended by revising paragraph (i) to read as follows:

§ 264.145 Financial assurance for post-closure care.

* * * * *

(i) *Release of the owner or operator from the requirements of this section.* Within 60 days after receiving certifications from the owner or operator and a qualified Professional Engineer that the post-closure care period has been completed for a hazardous waste disposal unit in accordance with the approved plan, the Regional Administrator will notify the owner or operator that he is no longer required to maintain financial assurance for post-closure of that unit, unless the Regional Administrator has reason to believe that post-closure care has not been in accordance with the approved post-closure plan. The Regional Administrator shall provide the owner or operator a detailed written statement of any such reason to believe that post-closure care has not been in accordance with the approved post-closure plan.

■ 20. Section 264.147 is amended by revising paragraph (e) to read as follows:

§ 264.147 Liability requirements.

* * * * *

(e) *Period of coverage.* Within 60 days after receiving certifications from the owner or operator and a qualified Professional Engineer that final closure has been completed in accordance with the approved closure plan, the Regional Administrator will notify the owner or operator in writing that he is no longer required by this section to maintain liability coverage for that facility, unless the Regional Administrator has reason to believe that closure has not been in accordance with the approved closure plan.

* * * * *

Subpart I—Use and Management of Containers

■ 21. Section 264.174 is revised to read as follows:

§ 264.174 Inspections.

At least weekly, the owner or operator must inspect areas where containers are stored, except for Performance Track member facilities, that may conduct inspections at least once each month, upon approval by the Director. To apply for reduced inspection frequencies, the Performance Track member facility must follow the procedures identified in § 264.15(b)(5) of this part. The owner or operator must look for leaking containers and for deterioration of containers and the containment system caused by corrosion or other factors.

[Comment: See §§ 264.15(c) and 264.171 for remedial action required if deterioration or leaks are detected.]

Subpart J—Tank Systems

■ 22. Section 264.191 is amended by revising paragraphs (a) and (b)(5)(ii) (the note to paragraph (b)(5)(ii) is unchanged) to read as follows:

§ 264.191 Assessment of existing tank system's integrity.

(a) For each existing tank system that does not have secondary containment meeting the requirements of § 264.193, the owner or operator must determine that the tank system is not leaking or is unfit for use. Except as provided in paragraph (c) of this section, the owner or operator must obtain and keep on file at the facility a written assessment reviewed and certified by a qualified Professional Engineer, in accordance with § 270.11(d) of this chapter, that attests to the tank system's integrity by January 12, 1988.

(b) * * *

(5) * * *

(ii) For other than non-enterable underground tanks and for ancillary equipment, this assessment must include either a leak test, as described above, or other integrity examination that is certified by a qualified Professional Engineer in accordance with § 270.11(d) of this chapter, that addresses cracks, leaks, corrosion, and erosion.

* * * * *

■ 23. Section 264.192 is amended by revising paragraph (a) introductory text and paragraph (b) introductory text to read as follows:

§ 264.192 Design and installation of new tank systems or components.

(a) Owners or operators of new tank systems or components must obtain and submit to the Regional Administrator, at time of submittal of part B information, a written assessment, reviewed and certified by a qualified Professional Engineer, in accordance with § 270.11(d) of this chapter, attesting that the tank system has sufficient structural integrity and is acceptable for the storing and treating of hazardous waste. The assessment must show that the foundation, structural support, seams, connections, and pressure controls (if applicable) are adequately designed and that the tank system has sufficient structural strength, compatibility with the waste(s) to be stored or treated, and corrosion protection to ensure that it will not collapse, rupture, or fail. This assessment, which will be used by the Regional Administrator to review and approve or disapprove the acceptability of the tank system design, must include, at a minimum, the following information:

* * * * *

(b) The owner or operator of a new tank system must ensure that proper handling procedures are adhered to in order to prevent damage to the system during installation. Prior to covering, enclosing, or placing a new tank system or component in use, an independent, qualified, installation inspector or a qualified Professional Engineer, either of whom is trained and experienced in the proper installation of tanks systems or components, must inspect the system for the presence of any of the following items:

* * * * *

■ 24. Section 264.193 is amended by:

■ a. Removing paragraphs (a)(2) through (a)(4);

■ b. Redesignating (a)(5) as (a)(2);

■ c. Revising paragraphs (a)(1), newly designated (a)(2), and (i)(2) to read as follows:

§ 264.193 Containment and detection of releases.

(a) * * *

(1) For all new and existing tank systems or components, prior to their being put into service.

(2) For tank systems that store or treat materials that become hazardous wastes, within two years of the hazardous waste listing, or when the tank system has reached 15 years of age, whichever comes later.

* * * * *

(h) * * *

(4) * * *

(i) * * *

(2) For other than non-enterable underground tanks, the owner or operator must either conduct a leak test as in paragraph (i)(1) of this section or develop a schedule and procedure for an assessment of the overall condition of the tank system by a qualified Professional Engineer. The schedule and procedure must be adequate to detect obvious cracks, leaks, and corrosion or erosion that may lead to cracks and leaks. The owner or operator must remove the stored waste from the tank, if necessary, to allow the condition of all internal tank surfaces to be assessed. The frequency of these assessments must be based on the material of construction of the tank and its ancillary equipment, the age of the system, the type of corrosion or erosion protection used, the rate of corrosion or erosion observed during the previous inspection, and the characteristics of the waste being stored or treated.

* * * * *

■ 25. Section 264.195 is amended by:

■ a. Revising paragraph (b) (the note to paragraph (b) is unchanged);

■ b. Redesignating existing paragraphs (c) and (d), as paragraphs (g) and (h), respectively;

■ c. Adding new paragraphs (c) through (f), to read as follows:

§ 264.195 Inspections.

* * * * *

(b) The owner or operator must inspect at least once each operating day data gathered from monitoring and leak detection equipment (*e.g.*, pressure or temperature gauges, monitoring wells) to ensure that the tank system is being operated according to its design.

* * * * *

(c) In addition, except as noted under paragraph (d) of this section, the owner or operator must inspect at least once each operating day:

(1) Above ground portions of the tank system, if any, to detect corrosion or releases of waste.

(2) The construction materials and the area immediately surrounding the externally accessible portion of the tank system, including the secondary containment system (*e.g.*, dikes) to detect erosion or signs of releases of hazardous waste (*e.g.*, wet spots, dead vegetation).

(d) Owners or operators of tank systems that either use leak detection systems to alert facility personnel to leaks, or implement established workplace practices to ensure leaks are promptly identified, must inspect at least weekly those areas described in paragraphs (c)(1) and (c)(2) of this section. Use of the alternate inspection schedule must be documented in the facility's operating record. This documentation must include a description of the established workplace practices at the facility.

(e) Performance Track member facilities may inspect on a less frequent basis, upon approval by the Director, but must inspect at least once each month. To apply for a less than weekly inspection frequency, the Performance Track member facility must follow the procedures described in § 264.15(b)(5).

(f) Ancillary equipment that is not provided with secondary containment, as described in § 264.193(f)(1) through (4), must be inspected at least once each operating day.

* * * * *

■ 26. Section 264.196 is amended by revising paragraph (f) (the notes to paragraph (f) are unchanged) to read as follows:

§ 264.196 Response to leaks or spills and disposition of leaking or unfit-for-use tank systems.

* * * * *

(f) *Certification of major repairs.* If the owner/operator has repaired a tank system in accordance with paragraph (e) of this section, and the repair has been extensive (*e.g.*, installation of an internal liner; repair of a ruptured primary containment or secondary containment vessel), the tank system must not be returned to service unless the owner/operator has obtained a certification by a qualified Professional Engineer in accordance with § 270.11(d) of this chapter that the repaired system is capable of handling hazardous wastes without release for the intended life of the system. This certification must be placed in the operating record and maintained until closure of the facility.

* * * * *

Subpart L—Waste Piles

■ 27. Section 264.251 is amended by revising the introductory text to paragraph (c) to read as follows:

§ 264.251 Design and operating requirements.

* * * * *

(c) The owner or operator of each new waste pile unit, each lateral expansion of a waste pile unit, and each replacement of an existing waste pile unit must install two or more liners and a leachate collection and removal system above and between such liners.

* * * * *

Subpart M—Land Treatment

■ 28. Section 264.280 is amended by revising paragraph (b) to read as follows:

§ 264.280 Closure and post-closure care.

* * * * *

(b) For the purpose of complying with § 264.115 of this chapter, when closure is completed the owner or operator may submit to the Regional Administrator certification by an independent, qualified soil scientist, in lieu of a qualified Professional Engineer, that the facility has been closed in accordance with the specifications in the approved closure plan.

* * * * *

Subpart N—Landfills

■ 29. Section 264.314 is amended by:

■ a. Removing paragraph (a);

■ b. Redesignating paragraphs (b) through (f) as paragraphs (a) through (e); and,

■ c. Revising newly designated paragraphs (a) and newly designated paragraph (e) introductory text to read as follows:

§ 264.314 Special requirements for bulk and containerized liquids.

(a) The placement of bulk or non-containerized liquid hazardous waste or hazardous waste containing free liquids (whether or not sorbents have been added) in any landfill is prohibited.

* * * * *

(e) The placement of any liquid which is not a hazardous waste in a landfill is prohibited unless the owner or operator of such landfill demonstrates to the Regional Administrator, or the Regional Administrator determines that:

* * * * *

Subpart O—Incinerators

■ 30. Section 264.343 is amended by revising paragraph (a)(2) to read as follows:

§ 264.343 Performance standards.

* * * * *

(a)(1) * * *

(2) An incinerator burning hazardous wastes FO20, FO21, FO22, FO23, FO26,

or FO27 must achieve a destruction and removal efficiency (DRE) of 99.9999% for each principal organic hazardous constituent (POHC) designated (under § 264.342) in its permit. This performance must be demonstrated on POHCs that are more difficult to incinerate than tetra-, penta-, and hexachlorodibenzo-p-dioxins and dibenzofurans. DRE is determined for each POHC from the equation in § 264.343(a)(1).

* * * * *

■ 31. Section 264.347 is amended by revising paragraph (d) to read as follows:

§ 264.347 Monitoring and inspections.

* * * * *

(d) This monitoring and inspection data must be recorded and the records must be placed in the operating record required by § 264.73 of this part and maintained in the operating record for five years.

Subpart S—Special Provisions for Cleanup

■ 32. Section 264.554 is amended by revising paragraph (c)(2) to read as follows:

§ 264.554 Staging piles.

* * * * *

(c) * * *

(2) Certification by a qualified Professional Engineer for technical data, such as design drawings and specifications, and engineering studies, unless the Director determines, based on information that you provide, that this certification is not necessary to ensure that a staging pile will protect human health and the environment; and

* * * * *

Subpart W—Drip Pads

■ 33. Section 264.571 is amended by revising paragraphs (a), (b), and (c) to read as follows:

§ 264.571 Assessment of existing drip pad integrity.

(a) For each existing drip pad as defined in § 264.570 of this subpart, the owner or operator must evaluate the drip pad and determine whether it meets all of the requirements of this subpart, except the requirements for liners and leak detection systems of § 264.573(b). No later than the effective date of this rule, the owner or operator must obtain and keep on file at the facility a written assessment of the drip pad, reviewed and certified by a qualified Professional Engineer that attests to the results of the evaluation. The assessment must be reviewed, updated and re-certified annually until all upgrades, repairs, or modifications necessary to achieve compliance with all the standards of § 264.573 are complete. The evaluation must document the extent to which the drip pad meets each of the design and operating standards of § 264.573, except the standards for liners and leak detection systems, specified in § 264.573(b).

(b) The owner or operator must develop a written plan for upgrading, repairing, and modifying the drip pad to meet the requirements of § 264.573(b) and submit the plan to the Regional Administrator no later than 2 years before the date that all repairs, upgrades, and modifications are complete. This written plan must describe all changes to be made to the drip pad in sufficient detail to document compliance with all the requirements of § 264.573. The plan must be reviewed and certified by a qualified Professional Engineer.

(c) Upon completion of all upgrades, repairs, and modifications, the owner or operator must submit to the Regional Administrator or state Director, the as-built drawings for the drip pad together with a certification by a qualified Professional Engineer attesting that the drip pad conforms to the drawings.

* * * * *

■ 34. Section 264.573 is amended by revising paragraphs (a)(4)(ii) and (g) to read as follows:

§ 264.573 Design and operating requirements.

(a) * * *

(4) * * *

(ii) The owner or operator must obtain and keep on file at the facility a written assessment of the drip pad, reviewed and certified by a qualified Professional Engineer that attests to the results of the evaluation. The assessment must be reviewed, updated and recertified annually. The evaluation must document the extent to which the drip pad meets the design and operating standards of this section, except for paragraph (b) of this section.

* * * * *

(g) The drip pad must be evaluated to determine that it meets the requirements of paragraphs (a) through (f) of this section and the owner or operator must obtain a statement from a qualified Professional Engineer certifying that the drip pad design meets the requirements of this section.

* * * * *

■ 35. Section 264.574 is amended by revising paragraph (a) to read as follows:

§ 264.574 Inspections.

(a) During construction or installation, liners and cover systems (*e.g.*, membranes, sheets, or coatings) must be inspected for uniformity, damage and imperfections (*e.g.*, holes, cracks, thin spots, or foreign materials). Immediately after construction or installation, liners must be inspected and certified as meeting the requirements in § 264.573 of this subpart by a qualified Professional Engineer. This certification must be maintained at the facility as part of the facility operating record. After installation, liners and covers must be inspected to ensure tight seams and joints and the absence of tears, punctures, or blisters.

* * * * *

Subpart BB—Air Emission Standards for Equipment Leaks

§ 264.1061 [Amended]

■ 36. Section 264.1061 is amended by:

■ a. Removing paragraphs (b)(1) and (d); and,

■ b. Redesignating paragraphs (b)(2) and (b)(3) as paragraphs (b)(1) and (b)(2).

§ 264.1062 [Amended]

■ 37. Section 264.1062 is amended by removing paragraph (a)(2) and redesignating paragraph (a)(1) as paragraph (a).

Subpart DD—Containment Buildings

■ 38. Section 264.1100 is amended by revising the introductory text to read as follows:

§ 264.1100 Applicability.

The requirements of this subpart apply to owners or operators who store or treat hazardous waste in units designed and operated under § 264.1101 of this subpart. The owner or operator is not subject to the definition of land disposal in RCRA section 3004(k) provided that the unit:

* * * * *

■ 39. Section 264.1101 is amended by revising paragraphs (c)(2) and (c)(4) to read as follows:

§ 264.1101 Design and operating standards.

* * * * *

(c) * * *

(2) Obtain and keep on-site a certification by a qualified Professional Engineer that the containment building design meets the requirements of paragraphs (a), (b), and (c) of this section.

* * * * *

(4) Inspect and record in the facility's operating record, at least once every

seven days, except for Performance Track member facilities that must inspect at least once each month, upon approval by the Director, data gathered from monitoring and leak detection equipment as well as the containment building and the area immediately surrounding the containment building to detect signs of releases of hazardous waste. To apply for reduced inspection frequency, the Performance Track member facility must follow the procedures described in § 264.15(b)(5).

* * * * *

PART 265—INTERIM STATUS STANDARDS FOR OWNERS AND OPERATORS OF HAZARDOUS WASTE TREATMENT, STORAGE, AND DISPOSAL FACILITIES

■ 40. The authority citation for part 265 continues to read as follows:

Authority: 42 U.S.C. 6905, 6906, 6912, 6922, 6923, 6924, 6925, 6935, 6936, and 6937, unless otherwise noted.

Subpart B—General Facility Standards

■ 41. Section 265.15 is amended by revising paragraph (b)(4) and adding paragraph (b)(5) to read as follows:

§ 265.15 General inspection requirements.

* * * * *

(b) * * *

(4) The frequency of inspection may vary for the items on the schedule. However, the frequency should be based on the rate of deterioration of the equipment and the probability of an environmental or human health incident if the deterioration, malfunction, or operator error goes undetected between inspections. Areas subject to spills, such as loading and unloading areas, must be inspected daily when in use, except for Performance Track member facilities, that must inspect at least once each month, upon approval by the Director, as described in paragraph (b)(5) of this section. At a minimum, the inspection schedule must include the items and frequencies called for in §§ 265.174, 265.193, 265.195, 265.226, 265.260, 265.278, 265.304, 265.347, 265.377, 265.403, 265.1033, 265.1052, 265.1053, 265.1058, and 265.1084 through 265.1090, where applicable.

(5) Performance Track member facilities that choose to reduce inspection frequencies must:

(i) Submit an application to the Director. The application must identify the facility as a member of the National Environmental Performance Track Program and identify the management units for reduced inspections and the proposed frequency of inspections. Inspections must be conducted at least once each month.

(ii) Within 60 days, the Director will notify the Performance Track member facility, in writing, if the application is approved, denied, or if an extension to the 60-day deadline is needed. This notice must be placed in the facility's operating record. The Performance Track member facility should consider the application approved if the Director does not: (1) Deny the application; or (2) notify the Performance Track member facility of an extension to the 60-day deadline. In these situations, the Performance Track member facility must adhere to the revised inspection schedule outlined in its application and maintain a copy of the application in the facility's operating record.

(iii) Any Performance Track member facility that discontinues its membership or is terminated from the program must immediately notify the Director of its change in status. The facility must place in its operating record a dated copy of this notification and revert back to the non-Performance Track inspection frequencies within seven calendar days.

* * * * *

■ 42. Section 265.16 is amended by adding new paragraph (a)(4) to read as follows:

§ 265.16 Personnel training.

(a) * * *

(4) For facility employees that receive emergency response training pursuant to Occupational Safety and Health Administration (OSHA) regulations 29 CFR 1910.120(p)(8) and 1910.120(q), the facility is not required to provide separate emergency response training pursuant to this section, provided that the overall facility training meets all the requirements of this section.

* * * * *

Subpart D—Contingency Plans and Emergency Procedures

■ 43. Section 265.52 is amended by revising paragraph (b) to read as follows:

§ 265.52 Content of contingency plan.

* * * * *

(b) If the owner or operator has already prepared a Spill Prevention, Control, and Countermeasures (SPCC) Plan in accordance with Part 112 of this chapter, or Part 1510 of chapter V, or some other emergency or contingency plan, he need only amend that plan to incorporate hazardous waste management provisions that are sufficient to comply with the requirements of this Part. The owner or operator may develop one contingency plan which meets all regulatory requirements. EPA recommends that the plan be based on the National Response Team's Integrated Contingency Plan Guidance ("One Plan"). When modifications are made to non-RCRA provisions in an integrated contingency plan, the changes do not trigger the need for a RCRA permit modification.

* * * * *

§ 265.56 [Amended]

■ 44. Section 265.56 is amended by removing paragraph (i) and redesignating paragraph (j) as paragraph (i).

Subpart E—Manifest System, Recordkeeping, and Reporting

■ 45. Section 265.73 is amended by revising the introductory text to paragraph (b), (b)(1), (b)(2) (the comment to paragraph (b)(2) is unchanged), (b)(6) (the comment to paragraph (b)(6) is unchanged), (b)(7), and (b)(8) and adding a new (b)(15) to read as follows:

§ 265.73 Operating record.

* * * * *

(b) The following information must be recorded, as it becomes available, and maintained in the operating record for three years unless noted below:

(1) A description and the quantity of each hazardous waste received, and the method(s) and date(s) of its treatment, storage, or disposal at the facility as required by Appendix I to part 265. This information must be maintained in the operating record until closure of the facility;

(2) The location of each hazardous waste within the facility and the quantity at each location. For disposal facilities, the location and quantity of each hazardous waste must be recorded on a map or diagram of each cell or disposal area. For all facilities, this information must include cross-references to manifest document numbers if the waste was accompanied by a manifest. This information must be maintained in the operating record until closure of the facility;

* * * * *

(6) Monitoring, testing or analytical data, and corrective action where required by subpart F of this part and by §§ 265.19, 265.94, 265.191, 265.193, 265.195, 265.224, 265.226, 265.255, 265.260, 265.276, 265.278, 265.280(d)(1), 265.302, 265.304, 265.347, 265.377, 265.1034(c) through 265.1034(f), 265.1035, 265.1063(d) through 265. 265.1063(i), 265.1064, and 265.1083 through 265.1090. Maintain in

the operating record for three years, except for records and results pertaining to ground-water monitoring and cleanup, and response action plans for surface impoundments, waste piles, and landfills, which must be maintained in the operating record until closure of the facility.

* * * * *

(7) All closure cost estimates under § 265.142 and, for disposal facilities, all post-closure cost estimates under § 265.144 must be maintained in the operating record until closure of the facility.

(8) Records of the quantities (and date of placement) for each shipment of hazardous waste placed in land disposal units under an extension to the effective date of any land disposal restriction granted pursuant to § 268.5 of this chapter, monitoring data required pursuant to a petition under § 268.6 of this chapter, or a certification under § 268.8 of this chapter, and the applicable notice required by a generator under § 268.7(a) of this chapter. All of this information must be maintained in the operating record until closure of the facility.

* * * * *

(15) Monitoring, testing or analytical data, and corrective action where required by §§ 265.90, 265.93(d)(2), and 265.93(d)(5), and the certification as required by § 265.196(f) must be maintained in the operating record until closure of the facility.

Subpart F—Ground-Water Monitoring

■ 46. Section 265.90 is amended by revising paragraphs (d)(1) and (d)(3) to read as follows:

§ 265.90 Applicability.

* * * * *

(d) * * *

(1) Within one year after the effective date of these regulations, develop a specific plan, certified by a qualified geologist or geotechnical engineer, which satisfies the requirements of § 265.93(d)(3), for an alternate ground-water monitoring system. This plan is to be placed in the facility's operating record and maintained until closure of the facility.

* * * * *

(3) Prepare a report in accordance with § 265.93(d)(5) and place it in the facility's operating record and maintain until closure of the facility.

* * * * *

■ 47. Section 265.93 is amended by revising paragraphs (d)(2) and (d)(5) to read as follows:

§ 265.93 Preparation, evaluation, and response.

* * * * *

(d)(1) * * *

(2) Within 15 days after the notification under paragraph (d)(1) of this section, the owner or operator must develop a specific plan, based on the outline required under paragraph (a) of this section and certified by a qualified geologist or geotechnical engineer, for a ground-water quality assessment at the facility. This plan must be placed in the facility operating record and be maintained until closure of the facility.

* * * * *

(5) The owner or operator must make his first determination under paragraph (d)(4) of this section, as soon as technically feasible, and prepare a report containing an assessment of ground-water quality. This report must be placed in the facility operating record and be maintained until closure of the facility.

* * * * *

Subpart G—Closure and Post-Closure

■ 48. Section 265.113 is amended by revising paragraph (e)(5) to read as follows:

§ 265.113 Closure; time allowed for closure.

* * * * *

(e) * * *

(5) During the period of corrective action, the owner or operator shall provide annual reports to the Regional Administrator describing the progress of the corrective action program, compile all ground-water monitoring data, and evaluate the effect of the continued receipt of non-hazardous wastes on the effectiveness of the corrective action.

* * * * *

■ 49. Section 265.115 is revised to read as follows:

§ 265.115 Certification of closure.

Within 60 days of completion of closure of each hazardous waste surface impoundment, waste pile, land treatment, and landfill unit, and within 60 days of completion of final closure, the owner or operator must submit to the Regional Administrator, by registered mail, a certification that the hazardous waste management unit or facility, as applicable, has been closed in accordance with the specifications in the approved closure plan. The certification must be signed by the owner or operator and by a qualified Professional Engineer. Documentation supporting the Professional Engineer's certification must be furnished to the Regional Administrator upon request until he releases the owner or operator from the financial assurance requirements for closure under § 265.143(h).

■ 50. Section 265.120 is revised to read as follows:

§ 265.120 Certification of completion of post-closure care.

No later than 60 days after the completion of the established post-closure care period for each hazardous waste disposal unit, the owner or operator must submit to the Regional Administrator, by registered mail, a certification that the post-closure care period for the hazardous waste disposal unit was performed in accordance with the specifications in the approved post-closure plan. The certification must be signed by the owner or operator and a qualified Professional Engineer. Documentation supporting the Professional Engineer's certification must be furnished to the Regional Administrator upon request until he releases the owner or operator from the financial assurance requirements for post-closure care under § 265.145(h).

Subpart H—Financial Requirements

■ 51. Section 265.143 is amended by revising paragraph (h) to read as follows:

§ 265.143 Financial assurance for closure.

* * * * *

(h) *Release of the owner or operator from the requirements of this section.* Within 60 days after receiving certifications from the owner or operator and a qualified Professional Engineer that final closure has been completed in accordance with the approved closure plan, the Regional Administrator will notify the owner or operator in writing that he is no longer required by this section to maintain financial assurance for final closure of the facility, unless the Regional Administrator has reason to believe that final closure has not been in accordance with the approved closure plan. The Regional Administrator shall provide the owner or operator a detailed written statement of any such reason to believe that closure has not been in accordance with the approved closure plan.

■ 52. Section 265.145 is amended by revising paragraph (h) to read as follows:

§ 265.145 Financial assurance for post-closure care.

* * * * *

(h) *Release of the owner or operator from the requirements of this section.* Within 60 days after receiving

certifications from the owner or operator and a qualified Professional Engineer that the post-closure care period has been completed for a hazardous waste disposal unit in accordance with the approved plan, the Regional Administrator will notify the owner or operator in writing that he is no longer required to maintain financial assurance for post-closure care of that unit, unless the Regional Administrator has reason to believe that post-closure care has not been in accordance with the approved post-closure plan. The Regional Administrator shall provide the owner or operator a detailed written statement of any such reason to believe that post-closure care has not been in accordance with the approved post-closure plan.

■ 53. Section 265.147 is amended by revising paragraph (e) to read as follows:

§ 265.147 Liability requirements.

* * * * *

(e) *Period of coverage.* Within 60 days after receiving certifications from the owner or operator and a qualified Professional Engineer that final closure has been completed in accordance with the approved closure plan, the Regional Administrator will notify the owner or operator in writing that he is no longer required by this section to maintain liability coverage for that facility, unless the Regional Administrator has reason to believe that closure has not been in accordance with the approved closure plan.

* * * * *

Subpart I—Use and Management of Containers

■ 54. Section 265.174 is revised to read as follows:

§ 265.174 Inspections.

At least weekly, the owner or operator must inspect areas where containers are stored, except for Performance Track member facilities, that must conduct inspections at least once each month, upon approval by the Director. To apply for reduced inspection frequency, the Performance Track member facility must follow the procedures described in § 265.15(b)(5) of this part. The owner or operator must look for leaking containers and for deterioration of containers and the containment system caused by corrosion or other factors.

[Comment: See § 265.171 for remedial action required if deterioration or leaks are detected.]

Subpart J—Tank Systems

■ 55. Section 265.191 is amended by revising paragraphs (a) and (b)(5)(ii) (the note to paragraph (b)(5)(ii) is unchanged) to read as follows:

§ 265.191 Assessment of existing tank system's integrity.

(a) For each existing tank system that does not have secondary containment meeting the requirements of § 265.193, the owner or operator must determine that the tank system is not leaking or is unfit for use. Except as provided in paragraph (c) of this section, the owner or operator must obtain and keep on file at the facility a written assessment reviewed and certified by a qualified Professional Engineer in accordance with § 270.11(d) of this chapter, that attests to the tank system's integrity by January 12, 1988.

(b) * * *

(5) * * *

(ii) For other than non-enterable underground tanks and for ancillary equipment, this assessment must be either a leak test, as described above, or an internal inspection and/or other tank integrity examination certified by a qualified Professional Engineer in accordance with § 270.11(d) of this chapter that addresses cracks, leaks, corrosion, and erosion.

* * * * *

■ 56. Section 265.192 is amended by revising paragraphs (a) introductory text and (b) introductory text to read as follows:

§ 265.192 Design and installation of new tank systems or components.

(a) Owners or operators of new tank systems or components must ensure that the foundation, structural support, seams, connections, and pressure controls (if applicable) are adequately designed and that the tank system has sufficient structural strength, compatibility with the waste(s) to be stored or treated, and corrosion protection so that it will not collapse, rupture, or fail. The owner or operator must obtain a written assessment reviewed and certified by a qualified Professional Engineer in accordance with § 270.11(d) of this chapter attesting that the system has sufficient structural integrity and is acceptable for the storing and treating of hazardous waste. This assessment must include the following information:

* * * * *

(b) The owner or operator of a new tank system must ensure that proper handling procedures are adhered to in order to prevent damage to the system during installation. Prior to covering, enclosing, or placing a new tank system or component in use, an independent, qualified installation inspector or a qualified Professional Engineer, either of whom is trained and experienced in the proper installation of tank systems, must inspect the system or component for the presence of any of the following items:

* * * * *

■ 56. Section 265.193 is amended by:
■ a. Removing paragraphs (a)(2) through (a)(4);
■ b. Redesignating (a)(5) as (a)(2);
■ c. Revising paragraphs (a)(1), newly designated (a)(2) and (i)(2) (the note to (i)(2) is unchanged) to read as follows.

§ 265.193 Containment and detection of releases.

(a) * * *

(1) For all new and existing tank systems or components, prior to their being put into service.

(2) For tank systems that store or treat materials that become hazardous wastes, within 2 years of the hazardous waste listing, or when the tank system has reached 15 years of age, whichever comes later.

* * * * *

(i) * * *

(2) For other than non-enterable underground tanks, and for all ancillary equipment, the owner or operator must either conduct a leak test as in paragraph (i)(1) of this section or an internal inspection or other tank integrity examination by a qualified Professional Engineer that addresses cracks, leaks, and corrosion or erosion at least annually. The owner or operator must remove the stored waste from the tank, if necessary, to allow the condition of all internal tanks surfaces to be assessed.

* * * * *

■ 58. Section 265.195 is amended by:
■ a. Revising paragraph (a) (the note to paragraph (a) is unchanged);
■ b. Redesignating existing paragraphs (b) and (c), as paragraphs (f) and (g), respectively; and,
■ c. Adding new paragraphs (b) through (e).

§ 265.195 Inspections.

(a) The owner or operator must inspect, where present, at least once each operating day, data gathered from monitoring and leak detection equipment (e.g., pressure or temperature gauges, monitoring wells) to ensure that the tank system is being operated according to its design.

* * * * *

(b) Except as noted under the paragraph (c) of this section, the owner or operator must inspect at least once each operating day:

(1) Overfill/spill control equipment (e.g., waste-feed cutoff systems, bypass

systems, and drainage systems) to ensure that it is in good working order;

(2) Above ground portions of the tank system, if any, to detect corrosion or releases of waste; and

(3) The construction materials and the area immediately surrounding the externally accessible portion of the tank system, including the secondary containment system (e.g., dikes) to detect erosion or signs of releases of hazardous waste (e.g., wet spots, dead vegetation).

(c) Owners or operators of tank systems that either use leak detection equipment to alert facility personnel to leaks, or implement established workplace practices to ensure leaks are promptly identified, must inspect at least weekly those areas described in paragraphs (b)(1) through (3) of this section. Use of the alternate inspection schedule must be documented in the facility's operating record. This documentation must include a description of the established workplace practices at the facility.

(d) Performance Track member facilities may inspect on a less frequent basis, upon approval by the Director, but must inspect at least once each month. To apply for a less than weekly inspection frequency, the Performance Track member facility must follow the procedures described in § 265.15(b)(5).

(e) Ancillary equipment that is not provided with secondary containment, as described in § 265.193(f)(1) through (4), must be inspected at least once each operating day.

* * * * *

■ 59. Section 265.196 is amended by revising paragraph (f) (the notes to paragraph (f) are unchanged) to read as follows:

§ 265.196 Response to leaks or spills and disposition of leaking or unfit-for-use tank systems.

* * * * *

(f) *Certification of major repairs.* If the owner/operator has repaired a tank system in accordance with paragraph (e) of this section, and the repair has been extensive (e.g., installation of an internal liner; repair of a ruptured primary containment or secondary containment vessel), the tank system must not be returned to service unless the owner/operator has obtained a certification by a qualified Professional Engineer in accordance with § 270.11(d) that the repaired system is capable of handling hazardous wastes without release for the intended life of the system. This certification is to be placed in the operating record and maintained until closure of the facility.

* * * * *

■ 60. Section 265.201 is amended by:

■ a. Revising the paragraph (c) introductory text;

■ b. Redesignating paragraph (d) through (f), as paragraphs (f) through (h), respectively; and,

■ c. Adding new paragraphs (d) and (e).

§ 265.201 Special requirements for generators of between 100 and 1,000 kg/mo. that accumulate hazardous waste in tanks.

* * * * *

(c) Except as noted in paragraph (d) of this section, generators who accumulate between 100 and 1,000 kg/mo of hazardous in tanks must inspect, where present:

* * * * *

(d) Generators who accumulate between 100 and 1,000 kg/mo of hazardous waste in tanks or tank systems that have full secondary containment and that either use leak detection equipment to alert facility personnel to leaks, or implement established workplace practices to ensure leaks are promptly identified, must inspect at least weekly, where applicable, the areas identified in paragraphs (c)(1) through (5) of this section. Use of the alternate inspection schedule must be documented in the facility's operating record. This documentation must include a description of the established workplace practices at the facility.

(e) Performance Track member facilities may inspect on a less frequent basis, upon approval by the Director, but must inspect at least once each month. To apply for a less than weekly inspection frequency, the Performance Track member facility must follow the procedures described in § 265.15(b)(5).

* * * * *

Subpart K—Surface Impoundments

■ 61. Section 265.221 is amended by revising paragraph (a) to read as follows:

§ 265.221 Design and operating requirements.

(a) The owner or operator of each new surface impoundment unit, each lateral expansion of a surface impoundment unit, and each replacement of an existing surface impoundment unit must install two or more liners, and a leachate collection and removal system above and between the liners, and operate the leachate collection and removal system, in accordance with § 264.221(c), unless exempted under § 264.221(d), (e), or (f) of this Chapter.

* * * * *

§ 265.223 [Redesignated as § 265.224]

■ 62. Section 265.223 titled "Response actions" is redesignated as § 265.224 and the newly designated § 265.224 is amended by revising paragraph (a) to read as follows:

§ 265.224 Response actions.

(a) The owner or operator of surface impoundment units subject to § 265.221(a) must develop and keep on site until closure of the facility a response action plan. The response action plan must set forth the actions to be taken if the action leakage rate has been exceeded. At a minimum, the response action plan must describe the actions specified in paragraph (b) of this section.

* * * * *

Subpart L—Waste Piles

■ 63. Section 265.259 is amended by revising the first sentence of paragraph (a) to read as follows:

§ 265.259 Response actions.

(a) The owner or operator of waste pile units subject to § 265.254 must develop and keep on-site until closure of the facility a response action plan.

* * *

* * * * *

Subpart M—Land Treatment

■ 64. Section 265.280 is amended by revising paragraph (e) to read as follows:

§ 265.280 Closure and post-closure.

* * * * *

(e) For the purpose of complying with § 265.115, when closure is completed the owner or operator may submit to the Regional Administrator certification both by the owner or operator and by an independent, qualified soil scientist, in lieu of a qualified Professional Engineer, that the facility has been closed in accordance with the specifications in the approved closure plan.

* * * * *

Subpart N—Landfills

■ 65. Section 265.301 is amended by revising paragraph (a) to read as follows:

§ 265.301 Design and operating requirements.

(a) The owner or operator of each new landfill unit, each lateral expansion of a landfill unit, and each replacement of an existing landfill unit must install two or more liners and a leachate collection and removal system above and between such liners, and operate the leachate collection and removal system, in accordance with § 264.301(d), (e), or (f) of this chapter.

* * * * *

■ 66. Section 265.303 is amended by revising paragraph (a) to read as follows:

§ 265.303 Response actions.

(a) The owner or operator of landfill units subject to § 265.301(a) must develop and keep on site until closure of the facility a response action plan. The response action plan must set forth the actions to be taken if the action leakage rate has been exceeded. At a minimum, the response action plan must describe the actions specified in paragraph (b) of this section.

* * * * *

■ 67. Section 265.314 is amended by:
■ a. Removing paragraph (a);
■ b. Redesignating paragraphs (b) through (g) as paragraphs (a) through (f); and,
■ c. Revising newly designated paragraph (a), and the introductory text of newly designated paragraph (f) to read as follows:

§ 265.314 Special requirements for bulk and containerized liquids.

(a) The placement of bulk or non-containerized liquid hazardous waste or hazardous waste containing free liquids (whether or not sorbents have been added) in any landfill is prohibited.

* * * * *

(f) The placement of any liquid which is not a hazardous waste in a landfill is prohibited unless the owner or operator of such landfill demonstrates to the Regional Administrator or the Regional Administrator determines that:

* * * * *

Subpart W—Drip Pads

■ 68. Section 265.441 is amended by revising paragraphs (a), (b), and (c) to read as follows:

§ 265.441 Assessment of existing drip pad integrity.

(a) For each existing drip pad as defined in § 265.440, the owner or operator must evaluate the drip pad and determine that it meets all of the requirements of this subpart, except the requirements for liners and leak detection systems of § 265.443(b). No later than the effective date of this rule, the owner or operator must obtain and keep on file at the facility a written assessment of the drip pad, reviewed and certified by a qualified Professional Engineer that attests to the results of the evaluation. The assessment must be reviewed, updated, and re-certified annually until all upgrades, repairs, or modifications necessary to achieve compliance with all the standards of § 265.443 are complete. The evaluation must document the extent to which the drip pad meets each of the design and operating standards of § 265.443, except the standards for liners and leak detection systems, specified in § 265.443(b).

(b) The owner or operator must develop a written plan for upgrading, repairing, and modifying the drip pad to meet the requirements of § 265.443(b), and submit the plan to the Regional Administrator no later than 2 years before the date that all repairs, upgrades, and modifications are complete. This written plan must describe all changes to be made to the drip pad in sufficient detail to document compliance with all the requirements of § 265.443. The plan must be reviewed and certified by a qualified Professional Engineer.

(c) Upon completion of all repairs and modifications, the owner or operator must submit to the Regional Administrator or state Director, the as-built drawings for the drip pad together with a certification by a qualified Professional Engineer attesting that the drip pad conforms to the drawings.

* * * * *

■ 69. Section 265.443 is amended by revising paragraphs (a)(4)(ii) and (g) to read as follows:

§ 265.443 Design and operating requirements.

(a) * * *

(4)(i) * * *

(ii) The owner or operator must obtain and keep on file at the facility a written assessment of the drip pad, reviewed and certified by a qualified Professional Engineer that attests to the results of the evaluation. The assessment must be reviewed, updated and recertified annually. The evaluation must document the extent to which the drip pad meets the design and operating standards of this section, except for paragraph (b) of this section.

* * * * *

(g) The drip pad must be evaluated to determine that it meets the requirements of paragraphs (a) through (f) of this section and the owner or operator must obtain a statement from a qualified Professional Engineer certifying that the drip pad design meets the requirements of this section.

* * * * *

■ 70. Section 265.444 is amended by revising paragraph (a) to read as follows:

§ 265.444 Inspections.

(a) During construction or installation, liners and cover systems (e.g., membranes, sheets, or coatings) must be inspected for uniformity, damage and imperfections (e.g., holes, cracks, thin spots, or foreign materials). Immediately after construction or installation, liners must be inspected and certified as meeting the requirements of § 265.443 by a qualified Professional Engineer. This certification must be maintained at the facility as part of the facility operating record. After installation, liners and covers must be inspected to ensure tight seams and joints and the absence of tears, punctures, or blisters.

* * * * *

Subpart BB—Air Emission Standards for Equipment Leaks

§ 265.1061 [Amended]

■ 71. Section 265.1061 is amended by removing paragraphs (b)(1) and (d), and redesignating paragraphs (b)(2) and (b)(3) as paragraphs (b)(1) and (b)(2).

§ 265.1062 [Amended]

■ 72. Section 265.1062 is amended by removing paragraph (a)(2) and redesignating paragraph (a)(1) as paragraph (a).

Subpart DD—Containment Buildings

■ 73. Section 265.1100 is amended by revising the introductory text to read as follows:

§ 265.1100 Applicability.

The requirements of this subpart apply to owners or operators who store or treat hazardous waste in units designed and operated under § 265.1101 of this subpart. The owner or operator is not subject to the definition of land disposal in RCRA section 3004(k) provided that the unit:

* * * * *

■ 74. Section 265.1101 is amended revising paragraphs (c)(2) and (c)(4) to read as follows:

§ 265.1101 Design and operating standards.

* * * * *

(c) * * *

(2) Obtain and keep on-site a certification by a qualified Professional Engineer that the containment building design meets the requirements of paragraphs (a), (b), and (c) of this section.

* * * * *

(4) Inspect and record in the facility's operating record at least once every seven days, except for Performance Track member facilities, that must inspect up to once each month, upon approval of the director, data gathered from monitoring and leak detection equipment as well as the containment building and the area immediately surrounding the containment building

to detect signs of releases of hazardous waste. To apply for reduced inspection frequency, the Performance Track member facility must follow the procedures described in § 265.15(b)(5).

* * * * *

PART 266—STANDARDS FOR THE MANAGEMENT OF SPECIFIC HAZARDOUS WASTES AND SPECIFIC TYPES OF HAZARDOUS WASTE MANAGEMENT FACILITIES

■ 75. The authority citation for part 266 continues to read as follows:

Authority: 42 U.S.C. 1006, 2002(a), 3001–3009, 3014, 6905, 6906, 6912, 6921, 6922, 6924–6927, 6934, and 6937.

Subpart H—Hazardous Waste Burned in Boilers and Industrial Furnaces

■ 76. Section 266.102 is amended by revising paragraph (e)(10) to read as follows:

§ 266.102 Permit standards for burners.

* * * * *

(e) * * *

(10) *Recordkeeping.* The owner or operator must maintain in the operating record of the facility all information and data required by this section for five years.

* * * * *

■ 77. Section 266.103 is amended by revising paragraphs (d) and (k) to read as follows:

§ 266.103 Interim status standards for burners.

* * * * *

(d) *Periodic Recertifications.* The owner or operator must conduct compliance testing and submit to the Director a recertification of compliance under provisions of paragraph (c) of this section within five years from submitting the previous certification or recertification. If the owner or operator seeks to recertify compliance under new operating conditions, he/she must comply with the requirements of paragraph (c)(8) of this section.

* * * * *

(k) *Recordkeeping.* The owner or operator must keep in the operating record of the facility all information and data required by this section for five years.

* * * * *

PART 268—LAND DISPOSAL RESTRICTIONS

■ 78. The authority citation for part 268 continues to read as follows:

Authority: 42 U.S.C. 6905, 6912(a), 6921, and 6924.

Subpart A—General

■ 79. Section 268.7 is amended by revising paragraphs (a)(1), (a)(2), and (b)(6) to read as follows:

§ 268.7 Testing, tracking and recordkeeping requirements for generators, treaters, and disposal facilities.

(a) *Requirements for generators:* (1) A generator of hazardous waste must determine if the waste has to be treated before it can be land disposed. This is done by determining if the hazardous waste meets the treatment standards in § 268.40, 268.45, or § 268.49. This determination can be made concurrently with the hazardous waste determination required in § 262.11 of this chapter, in either of two ways: testing the waste or using knowledge of the waste. If the generator tests the waste, testing would normally determine the total concentration of hazardous constituents, or the concentration of hazardous constituents in an extract of the waste obtained using test method 1311 in "Test Methods of Evaluating Solid Waste, Physical/Chemical Methods," EPA Publication SW–846, (incorporated by reference, see § 260.11 of this chapter), depending on whether the treatment standard for the waste is expressed as a total concentration or concentration of hazardous constituent in the waste's extract. (Alternatively, the generator must send the waste to a RCRA-permitted hazardous waste treatment facility, where the waste treatment facility must comply with the requirements of § 264.13 of this chapter and paragraph (b) of this section. In addition, some hazardous wastes must be treated by particular treatment methods before they can be land disposed and some soils are contaminated by such hazardous wastes. These treatment standards are also found in § 268.40, and are described in detail in § 268.42, Table 1. These wastes, and solids contaminated with such wastes, do not need to be tested (however, if they are in a waste mixture, other wastes with concentration level treatment standards would have to be tested). If a generator determines they are managing a waste or soil contaminated with a waste, that displays a hazardous characteristic of ignitability, corrosivity, reactivity, or toxicity, they must comply with the special requirements of § 268.9 of this part in addition to any applicable requirements in this section.

(2) If the waste or contaminated soil does not meet the treatment standards, or if the generator chooses not to make the determination of whether his waste must be treated, with the initial shipment of waste to each treatment or storage facility, the generator must send a one-time written notice to each treatment or storage facility receiving the waste, and place a copy in the file. The notice must include the information in column "268.7(a)(2)" of the Generator Paperwork Requirements Table in paragraph (a)(4) of this section. (Alternatively, if the generator chooses not to make the determination of whether the waste must be treated, the notification must include the EPA Hazardous Waste Numbers and Manifest Number of the first shipment and must state "This hazardous waste may or may not be subject to the LDR treatment standards. The treatment facility must make the determination.") No further notification is necessary until such time that the waste or facility change, in which case a new notification must be sent and a copy placed in the generator's file.

* * * * *

(b) * * *

(6) Where the wastes are recyclable materials used in a manner constituting disposal subject to the provisions of § 266.20(b) of this chapter regarding treatment standards and prohibition levels, the owner or operator of a treatment facility (*i.e.*, the recycler) must, for the initial shipment of waste, prepare a one-time certification described in paragraph (b)(4) of this section, and a one-time notice which includes the information in paragraph (b)(3) of this section (except the manifest number). The certification and notification must be placed in the facility's on-site files. If the waste or the receiving facility changes, a new certification and notification must be prepared and placed in the on site files. In addition, the recycling facility must also keep records of the name and location of each entity receiving the hazardous waste-derived product.

* * * * *

■ 80. Section 268.9 is amended by revising paragraphs (a) and (d) introductory text to read as follows:

§ 268.9 Special rules regarding wastes that exhibit a characteristic.

(a) The initial generator of a solid waste must determine each EPA Hazardous Waste Number (waste code) applicable to the waste in order to determine the applicable treatment standards under subpart D of this part. This determination may be made concurrently with the hazardous waste determination required in § 262.11 of this chapter. For purposes of part 268, the waste will carry the waste code for any applicable listed waste (40 CFR part

261, subpart D). In addition, where the waste exhibits a characteristic, the waste will carry one or more of the characteristic waste codes (40 CFR part 261, subpart C), except when the treatment standard for the listed waste operates in lieu of the treatment standard for the characteristic waste, as specified in paragraph (b) of this section. If the generator determines that their waste displays a hazardous characteristic (and is not D001 nonwastewaters treated by CMBST, RORGS, OR POLYM of § 268.42, Table 1), the generator must determine the underlying hazardous constituents (as defined at § 268.2(i)) in the characteristic waste.

* * * * *

(d) Wastes that exhibit a characteristic are also subject to § 268.7 requirements, except that once the waste is no longer hazardous, a one-time notification and certification must be placed in the generator's or treater's on-site files. The notification and certification must be updated if the process or operation generating the waste changes and/or if the subtitle D facility receiving the waste changes.

* * * * *

PART 270—EPA ADMINISTERED PERMIT PROGRAMS: THE HAZARDOUS WASTE PERMIT PROGRAM

■ 81. The authority citation for part 270 continues to read as follows:

Authority: 42 U.S.C. 6905, 6912, 6924, 6925, 6927, 6939, and 6974.

Subpart B—Permit Application

■ 82. Section 270.14 is amended by revising paragraph (a) to read as follows:

§ 270.14 Contents of part B: General requirements.

(a) Part B of the permit application consists of the general information requirements of this section, and the specific information requirements in §§ 0.14 through 270.29 applicable to the facility. The part B information requirements presented in §§ 270.14 through 270.29 reflect the standards promulgated in 40 CFR part 264. These information requirements are necessary in order for EPA to determine compliance with the part 264 standards. If owners and operators of HWM facilities can demonstrate that the information prescribed in part B can not be provided to the extent required, the Director may make allowance for submission of such information on a case-by-case basis. Information required in part B shall be submitted to the Director and signed in accordance with the requirements in § 270.11. Certain technical data, such as design drawings and specification, and engineering studies shall be certified by a qualified Professional Engineer. For post-closure permits, only the information specified in § 270.28 is required in part B of the permit application.

* * * * *

■ 83. Section 270.16 is amended by revising paragraph (a) to read as follows:

§ 270.16 Specific part B information requirements for tank systems.

* * * * *

(a) A written assessment that is reviewed and certified by a qualified Professional Engineer as to the structural integrity and suitability for handling hazardous waste of each tank system, as required under §§ 264.191 and 264.192 of this chapter;

* * * * *

■ 84. Section 270.26 is amended by revising paragraph (c)(15) to read as follows:

§ 270.26 Special part B information requirements for drip pads.

* * * * *

(c) * * *

(15) A certification signed by a qualified Professional Engineer, stating that the drip pad design meets the requirements of paragraphs (a) through(f) § 264.573 of this chapter.

* * * * *

Subpart D—Changes to Permits

■ 85. Section 270.42 is amended by adding new paragraph (l) and by adding new entry O to the table in Appendix I to § 270.42. to read as follows:

§ 270.42 Permit modification at the request of the permittee.

* * * * *

(l) *Performance Track member facilities.* The following procedures apply to Performance Track member facilities that request a permit modification under Appendix I of this section, section O(1).

(1) Performance Track member facilities must have complied with the requirements of § 264.15(b)(5) in order to request a permit modification under this section.

(2) The Performance Track member facility should consider the application approved if the Director does not: deny the application, in writing; or notify the Performance Track member facility, in writing, of an extension to the 60-day deadline within 60 days of receiving the request. In these situations, the Performance Track member facility must adhere to the revised inspection schedule outlined in its application and maintain a copy of the application in the facility's operating record.

* * * * *

Appendix 1 To § 270.42—Classification of Permit Modification

Modifications	Class
* * * * * * *	
O. Burden Reduction	
1. Approval of reduced inspection frequency for Performance Track member facilities for:	
a. Tanks systems pursuant to § 264.195	[1] 1
b. Containers pursuant to § 264.174	[1] 1
c. Containment buildings pursuant to § 264.1101(c)(4)	[1] 1
d. Areas subject to spills pursuant to § 264.15(b)(4)	[1] 1
2. Development of one contingency plan based on Integrated Contingency Plan Guidance pursuant to § 264.52(b)	1
3. Changes to recordkeeping and reporting requirements pursuant to: §§ 264.56(i), 264.343(a)(2), 264.1061(b)(1),(d), 264.1062(a)(2), 264.196(f), 264.100(g), and 264.113(e)(5)	1
4. Changes to inspection frequency for tank systems pursuant to § 264.195(b)	1
5. Changes to detection and compliance monitoring program pursuant to §§ 264.98(d), (g)(2), and (g)(3), 264.99(f), and (g)	1

[1] Class 1 modifications requiring prior Agency approval.

PART 271—REQUIREMENTS FOR AUTHORIZATION OF STATE HAZARDOUS WASTE PROGRAMS

■ 86. The authority citation for part 271 continues to read as follows:

Authority: 42 U.S.C. 6905, 6912(a) and 6926.

■ 87. Section 271.1(j) is amended by adding the following entries to Table 1 in chronological order by date of publication in the Federal Register, to read as follows:

§ 271.1 Purpose and scope.

* * * * *

(j) * * *

TABLE 1.—REGULATIONS IMPLEMENTING THE HAZARDOUS AND SOLID WASTE AMENDMENTS OF 1984

Promulgation date	Title of regulation	Federal Register reference	Effective date
*	*	*	*
May 4, 2006	Office of Solid Waste Burden Reduction Project	[Insert FR page numbers]	May 4, 2006.
*	*	*	*

[FR Doc. 06–2690 Filed 4–3–06; 8:45 am]
BILLING CODE 6560–50–P

NOTICE OF PUBLIC HEARING AND PUBLIC COMMENT PERIOD

On Monday, July 9, 2007 beginning at 6 p.m., the West Virginia Department of Environmental Protection, Division of Air Quality (DAQ) will hold a public hearing on proposed revisions to existing legislative rules. Oral and written comments shall be limited only to the proposed revisions to the following existing legislative rules:

45CSR6	To Prevent and Control Air Pollution From Combustion of Refuse;
45CSR8	Ambient Air Quality Standards for Sulfur Oxides and Particulate Matter;
45CSR16	Standards of Performance for New Stationary Sources Pursuant to 40 CFR Part 60;
45CSR18	To Prevent and Control Emissions From Commercial and Industrial Solid Waste Incineration Units;
45CSR25	To Prevent and Control Air Pollution from Hazardous Waste Treatment, Storage, or Disposal Facilities;
45CSR34	Emission Standards for Hazardous Air Pollutants for Source Categories Pursuant to 40 CFR Part 63;
45CSR39	Control of Annual Nitrogen Oxide Emissions to Mitigate Interstate Transport of Fine Particulate Matter and Nitrogen Oxides;
45CSR40	Control of Ozone Season Nitrogen Oxide Emissions to Mitigate Interstate Transport of Ozone and Nitrogen Oxides; and
45CSR41	Control of Annual Sulfur Dioxide Emissions to Mitigate Interstate Transport of Fine Particulate Matter and Sulfur Dioxide.

On Monday, July 9, 2007, after public hearings on the above proposed legislative rules, the West Virginia Department of Environmental Protection, DAQ will hold a public hearing on the following proposed legislative rule:

45CSR42	Greenhouse Gas Emissions Inventory Program.

Upon authorization and promulgation of revisions to 45CSR6, 45CSR8, 45CSR39, 45CSR40 and 45CSR41, the DAQ will submit the final rules to the U.S. Environmental Protection Agency (U.S. EPA) as revisions to the State Implementation Plan, pursuant to the federal Clean Air Act.

Upon authorization and promulgation of revisions to 45CSR16, the DAQ will submit the final rule to the U.S. EPA for approval as a part of West Virginia's program delegation of the federal New Source Performance Standards.

Upon authorization and promulgation of revisions to 45CSR18, the DAQ will submit the final rule to the U.S. EPA for approval as a part of West Virginia's Section 111(d)/129 Plan and program delegation of the federal New Source Performance Standards.

Upon authorization and promulgation of revisions to 45CSR25, the DAQ will submit the final rule to the U.S. EPA for approval as part of the West Virginia Hazardous Waste Management Program.

Upon authorization and promulgation of revisions to 45CSR34, the DAQ will submit the final rule to the U.S. EPA for approval as a part of West Virginia's program delegation of the National Emission Standards for Hazardous Air Pollutants.

Upon authorization and promulgation of 45CSR42, the DAQ will begin implementation of a Greenhouse Gas Inventory Program.

The public hearing will be held at the Department of Environmental Protection, Dolly Sods Conference Room, 601 57th Street SE, Charleston and is open to the public. Written and oral comments will be accepted until the close of the hearing and will be made a part of the rulemaking record. Comments will also be accepted by fax (304-926-0479), U.S. Mail, or e-mail if postmarked or delivered by the close of business on July 9, 2007.

Copies of the proposed legislative rules may be viewed between 8:30 a.m. and 4:30 p.m. at the Division of Air Quality, 601 57th SE, Charleston, WV 25304 beginning June 8, 2007 or electronically upon e-mail request to: tmowrer@wvdep.org. For a copy of the proposed rules, access the following web address: www.wvdep.org/daq. Choose Public Notice and Comment.

Send written comments to John A. Benedict, Director, Division of Air Quality at the above address. Please identify the draft document to which the comments apply, the commenter's name, address, and telephone number. Comments will also be accepted by e-mail if transmitted by 5:00 p.m. on July 9, 2007 to: tmowrer@wvdep.org. Comments submitted by U.S. Mail must be postmarked by July 9, 2007.

CHARLESTON NEWSPAPERS
P O Box 2993
Charleston, West Virginia 25330
Billing 348-4898
Classified 348-4848
1 800-WVA-NEWS

LEGAL ADVERTISING

INVOICE DATE	06/11/07
ACCOUNT NBR	034320005
SALES REP ID	0020
INVOICE NBR	421127001

M

BILLED TO
WV DIV ENVIRONMENTAL PROTECT
OFFICE OF AIR QUALITY
601 57TH STREET
CHARLESTON WV 25304 USA

05-13-07F01:42 RCVD

Please return this portion with your payment. AMOUNT PAID: _____
Make checks payable to: Charleston Newspapers

CHARLESTON NEWSPAPERS
P.O. Box 2993
Charleston, West Virginia 25330
Billing 348-4898
Classified 348-4848
1-800-WVA-NEWS
FEIN 55-0676079

INVOICE DATE	06/11/07
ACCOUNT NBR	034320005
SALES REP ID	0020
INVOICE NBR	421127001

Legal pricing is based upon 63 words per column inch.
Each successive insertion is discounted by 25% of the first insertion rate
The Daily Mail is at a rate of $.14 per word, and the Charleston Gazette is at a rate of $.14 per word.

ISSUE DATE	AD TYPE	PUB	DESCRIPTION / REFERENCE NBR / PURCHASE ORDER #	AD NUMBER	AD SIZE / TOTAL RUN	RATE	GROSS AMOUNT	NET AMOUNT
06/08	LEG	DM	Public Notice - Legi 421127001 Jessica Gr	0287864	2X1125 22.50	8.82	198.45	198.45
06/08	LEG	GZ	Public Notice - Legi 421127002 Jessica Gr		2X1125 22.50	8.82	198.45	198.45
			TOTAL INVOICE AMOUNT					396.90

State of West Virginia. **AFFIDAVIT OF PUBLICATION**

I, Sandra Riggs of
THE CHARLESTON GAZETTE, A DAILY DEMOCRATIC NEWSPAPER
THE DAILY MAIL, A DAILY REPUBLICAN NEWSPAPER,
published in the city of Charleston, Kanawha County, West Virginia, do solemnly swear that the annexed notice of:
Public Notice - Legislat
was duly published in said paper(s) during the dates listed below, and was posted at the front door of the court house of said Kanawha County West Virginia, on the 9TH day of JUNE 2007 Published during the following dates: 06/08/07-06/08/07
Subscribed and sworn to before me this 12 day of June
Printers fee $ 396.90

OFFICIAL SEAL
NOTARY PUBLIC
STATE OF WEST VIRGINIA
LYNN B. FIELDER
ASI FRAZIER WAY
SCOTT DEPOT, WV 25560
My commission expires June 11, 2016

Notary Public

Division of Mining and Reclamation

38CSR2 - Surface Mining Reclamation Rule. The public hearing will be held at 5 p.m. on July 10, 2007, in the Canaan Valley Room. The comment period will end at the conclusion of the hearing.

47CSR5A - Individual State Certification of Activities Requiring a Federal Permit. The public hearing will be held at 6 p.m. on July 10, 2007, in the Canaan Valley Room. The comment period will end at the conclusion of the hearing.

47CSR30 - WV/NPDES Rules for Coal Mining Facilities. The public hearing will be held at 6 p.m. on July 10, 2007, in the Canaan Valley Room. The comment period will end at the conclusion of the hearing.

199CSR1 - Surface Mining Blasting Rule. The public hearing will be held at 5 p.m. on July 10, 2007, in the Canaan Valley Room. The comment period will end at the conclusion of the hearing.

For more information on any of the DWWM rules, call 926-0490.

Office of Oil and Gas

35CSR3 - Coalbed Methane Wells Rule. The public hearing will be held at 6 p.m. on July 17, 2007, in the Coopers Rock Training Room. The comment period will end at the conclusion of the hearing. For more information, call 926-0450.

Division of Land Restoration

33CSR10 - Recycling Assistance Grant Program. The public hearing will be held at 6 p.m. on July 12, 2007, in the Coopers Rock Training Room. The comment period will end at the conclusion of the hearing.

60CSR3 - Voluntary Remediation and Redevelopment Rule. The public hearing will be held at 6:30 p.m. on July 12, 2007, in the Coopers Rock Training Room. The comment period will end at the conclusion of the hearing.

For more information on any of the DLR rules, call 926-0455.

Public Information Office

60CSR8 - Environmental Excellence Rule. The public hearing will be held at 7 p.m. on July 17, 2007, in the Coopers Rock Training Room. The comment period will end at the conclusion of the hearing. For more information, call 926-0440.

(287864)

Division of Water and Waste Management

33CSR9 - Standards for Beneficial use of Filtrate from Water Treatment Plants. The public hearing will be held at 6 p.m. on July 2, 2007, in the Coopers Rock Training Room. The comment period will end at the conclusion of the hearing.

33CSR20 - Hazardous Waste Management System. The public hearing will be held at 6 p.m. on July 17, 2007, in the Coopers Rock Training Room. The comment period will end at the conclusion of the hearing.

33CSR30 - Underground Storage Tanks. The public hearing will be held at 6:30 p.m. on July 17, 2007, in the Coopers Rock Training Room at DEP's Charleston headquarters. The comment period will end at the conclusion of the hearing.

47CSR2 - Rules Governing Water Quality Standards. The public hearing will be held at 6 p.m. on July 16, 2007, in the Coopers Rock Training Room. The comment period will end at 5 p.m. on July 17, 2007. The rule includes a proposed use redesignation for Pat's Branch in the Guyandotte River Basin (see addional information in the information sheet attached to the briefing document).

47CSR10 - National Pollutant Discharge Elimination System (NPDES). The public hearing will be held at 6:30 p.m. on July 17, 2007, in the Coopers Rock Training Room. The comment period will end at the conclusion of the hearing.

47CSR34 - Dam Safety. The public hearing will be held at 7 p.m. on July 11, 2007, in the Coopers Rock Training Room. The comment period will end at the conclusion of the hearing.

60CSR5 - Antidegradation Implementation Procedures. The public hearing will be held at 7 p.m. on July 16, 2007, in the Coopers Rock Training Room. The comment period will end at 5:00 p.m. on July 17, 2007.

For more information on any of the DWWM rules, call 926-0495.

PUBLIC NOTICE

The West Virginia Department of Environmental Protection has scheduled public hearings for its 2008 proposed legislative rules. All hearings will be held at DEP's Charleston headquarters, 601 57th Street S.E., Charleston, WV 25304. Oral and written comments shall be limited to the proposed revisions to the following rules. All comments will be made a part of the rulemaking record. Copies of the rules and other rule documents are available from the Secretary of State's office or from the agency at www.wvdep.org/2008rules. You may also obtain hardcopies of the information by calling the phone numbers listed below.

Written comments may be submitted to the Public Information Office at the above address. Comments may also be e-mailed to comments@wvdep.org. The hearing dates, locations and comment deadlines are as follows:

Division of Air Quality

45CSR6 - Control of Air Pollution from Combustion of Refuse.

45CSR8 - Ambient Air Quality Standards.

45CSR16 - Standards of Performance for New Stationary Sources.

45CSR18 - Control of Air Pollution from Combustion of Solid Waste.

45CSR25 - Control of Air Pollution from Hazardous Waste Treatment, Storage and Disposal Facilities.

45CSR34 - Emission Standards for Hazardous Air Pollutants.

45CSR39 - Control of Annual Nitrogen Oxides Emissions.

45CSR40 - Control of Ozone Season Nitrogen Oxides Emissions.

45CSR41 - Control of Annual Sulfur Dioxide Emissions.

45CSR42 - Greenhouse Gas Emissions Inventory Program.

The public hearing for all air quality rules will be held at 6 p.m. on July 9, 2007, in the Daily Soda conference room. The comment period will end at the conclusion of the hearing. Upon authorization and promulgation of revisions to 45CSR6, 45CSR8, 45CSR39, 45CSR40 and 45CSR41, the DAQ will submit the rules to the U.S. Environmental Protection Agency (EPA) as revisions to the State Implementation Plan pursuant to the federal Clean Air Act (CAA). Rules 45CSR16, 45CSR18, 45CSR25, and 45CSR34 will also be submitted to EPA to fulfill other federal obligations under the CAA, including delegations, plans and program approvals. For more information on any of the air rules, call 926-0475.

dep

west virginia department of environmental protection

DAQ 2008 Proposed Rules Hearing
Dolly Sods Conference Room
601 57th Street SE, Charleston
July 9, 2007 6:00 p.m.

Sign-In

NAME (Please Print)	ADDRESS	ORGANIZATION	PHONE/FAX	E-MAIL	COMMENT YES/NO
LINDA K TENNANT	300 KANAWHA BLVD	SPILMAN THOMAS	304.720.3420	ltennant@spilmanlaw.com	Written
Tim Mallan	707 Va. Street E.	Appalachian Power	304-348-4136	tpmallan@aep.com	No.
Anne Blankenship	700 Virginia St E	Robinson + McElwee	304-347-8314	acb@ramlaw.com	written only
Jon Mason	601 57th St	WVDEP	920 0499 ext 1203	Jmason@WVDep.org	No

ORIGINAL

BEFORE THE WEST VIRGINIA DEPARTMENT OF
ENVIRONMENTAL PROTECTION
DIVISION OF AIR QUALITY

In the matter of: PROPOSED REVISIONS TO 45CSR25- Control of Air Pollution from Hazardous Waster Treatment, Storage and Disposal Facilities

Transcript of proceedings had at a public hearing in the above-styled matter taken by Missy L. Young, Certified Court Reporter, at the West Virginia Department of Environmental Protection, Division of Air Quality, Dolly Sods Conference Room, 601 57th Street, S.E. Charleston, West Virginia, commencing at 6:16 p.m., on the 9th day of July 2007, pursuant to notice.

MISSY L. YOUNG, C.C.R.
POST OFFICE BOX 13221
SISSONVILLE, WEST VIRGINIA 25360
(304) 984-2300

PROCEEDINGS

MS. CHANDLER: The purpose of this public hearing is to accept comments on the proposed revisions to 45CSR25 - Control of Air Pollution from Hazardous Waste Treatment, Storage and Disposal Facilities..

This rule establishes and adopts emission standards for the treatment, storage and disposal of hazardous waste promulgated by the U.S. Environmental Protection Agency pursuant to the Resource Conservation and Recovery Act, as amended. This rule codifies general procedures and criteria to implement emission standards set forth in 40 CFR Parts 260, 261, 262, 264, 265, 266, 270 and 279, as listed in Table 25-A of the rule.

The rule also adopts associated appendices, reference methods, performance specifications and other test methods which are appended to these standards. Any person who constructs, reconstructs, modifies or operates any hazardous waste treatment, storage and disposal facility must comply with the West Virginia Hazardous Waste Management System, the codified federal emission standards, and this rule.

45CSR25 establishes a program of regulation over the treatment, storage and disposal of hazardous

wastes in order to achieve and maintain such levels of air quality as will protect the public health and safety and the environment from the effects of improper, inadequate, or unsound treatment, storage or disposal of hazardous wastes.

This revised rule incorporates by reference the following provisions of 40 CFR Parts 260, 261, 264, 265, 266 and 270 promulgated as of June 1, 2007; National Emission Standards for Hazardous Air Pollutants; Final Standards for Hazardous Air Pollutants for Hazardous Waste Combustors (Phase I Final Replacement Standards and Phase II), Resource Conservation and Recovery Act Burden Reduction Initiative, and Waste Management System; Testing and Monitoring Activities, Methods Innovation Rule; Solid Waste 846 Final Update IIIB; Hazardous Waste and used Oil; Corrections to Errors in the Code of Federal Regulations; Modification of the Hazardous Waste Program; Cathode Ray Tubes; Hazardous Waste Management System; Identification and Listing of Hazardous Waste; and Final Exclusion.

Promulgation of this rule will enable the Department of Environmental Protection to continue to be the primary enforcement authority for the RCRA Hazardous Waste

Management System in West Virginia. Revisions to this rule are necessary to maintain consistency with current federal regulations, the Office of Waste Management's Hazardous Waste management System rule 33CSR20, and to fulfill the State's responsibilities under the Clean Air Act.

Revisions to the rule include revised title, improved citing to federal counterpart language, annual incorporation by reference updates, revised definition of pathological waste, clarified language for pathological waste incinerators, a new exclusion for pathological waste incinerators subject to 45CSR6 or 45CSR18, and general language clarification and correction.

Upon authorization and promulgation of revisions to 45CSR25, the Division of Air Quality will submit the final rules to the U.S. Environmental Protection Agency to fulfill other federal obligations under the Clean Air Act, including delegations, plans and program approvals.

The floor is now open for comments.

There being nothing further, this public hearing for the proposed revisions to 45CSR25 is concluded.

(WHEREUPON, the hearing was concluded at 6:20 p.m.)

STATE OF WEST VIRGINIA,

COUNTY OF KANAWHA, to-wit:

I, the undersigned, Missy L. Young, a Certified Court Reporter and Commissioner within and for the State of West Virginia, duly commissioned and qualified, do hereby certify that the foregoing, is to the best of my skill and ability, a true and accurate transcript of all the proceedings had in the aforementioned matter.

Given under my hand and official seal this 20th day of July 2007.

Missy L. Young, C.C.R.

Missy L. Young
Certified Court Reporter
Commissioner for the State of West Virginia

My commission expires April 15, 2008.

From: Paula Finck <paulafinck@yahoo.com>
To: <comments@wvdep.org>
Date: 6/27/2007 10:08:43 PM
Subject: Re: air quality rules

Now is the time to put into effects the toughest air quality rules for the sake of the present and future health of the citizens of these United States of America. It is your job and your responsibility to the people.

Respectfully yours,
Paula Finck

Finding fabulous fares is fun.
Let Yahoo! FareChase search your favorite travel sites to find flight and hotel bargains.
http://farechase.yahoo.com/promo-generic-14795097

45CSR25

CONTROL OF AIR POLLUTION FROM HAZARDOUS WASTE TREATMENT, STORAGE AND DISPOSAL FACILITIES

RESPONSE TO COMMENTS

On June 8, 2007, the Division of Air Quality (DAQ) commenced a thirty day public comment period and subsequently held a public hearing on July 9, 2007 to accept oral comments on proposed revisions to legislative rule 45CSR25. Written comments were also accepted through 6:00 PM on Monday, July 9, 2007. No commenter submitted written comments regarding proposed revisions to rule 45CSR25, and no commenter provided verbal comments.