

TITLE 36  
LEGISLATIVE RULES  
BOARD OF COAL MINE HEALTH AND SAFETY

SERIES 33  
UNDERGROUND MINE CAR LOADING POINTS

§36-33-1. General.

1.1. Scope. -- This legislative rule establishes safety requirements for mine car loading points in underground coal mines.

1.2. Authority. -- W. Va. Code §22-6-4

1.3. Filing Date. -- May 8, 1985

1.4. Effective Date. -- June 1, 1985

§36-33-2. Definitions.

2.1. All terms used in these rules and regulations, not defined herein, shall have the meanings set forth in Chapter 22A, Article 1A Section 1 of the West Virginia Code.

§36-33-3. Underground Mine Car Loading Points.

3.1. Six (6) months after the effective date of this regulation, skids shall not be placed on mine rails adjacent to the wheels of moving mine cars, unless remote means can be used to place the skids without getting underneath or between the cars.

3.2. There shall be no unnecessary visual obstructions in the immediate working area of the underground mine car loading point operator.

3.3. These requirements shall be conspicuously posted at the underground mine car loading point, along with any other operation instructions for that facility.

*obsolete  
v4/c June 1, 1985  
to April 10, 1988*

Title 36

~~WEST VIRGINIA~~ LEGISLATIVE RULE  
BOARD OF COAL MINE HEALTH AND SAFETY  
~~CHAPTER 22-2A~~  
SERIES 49 33

FILED  
1985 MAY -8 AM 9: 21  
OFFICE OF THE ATTORNEY GENERAL  
SECRETARY OF STATE

Title: Underground Mine Car Loading Points

Section 1. General

- 1.1 Scope - This legislative rule establishes safety requirements for mine car loading points in underground coal mines.
- 1.2 Authority - W.Va. Code 22-2A-4
- 1.3 Filing Date - May 8, 1985
- 1.4 Effective Date - June 1, 1985

Section 2. Definitions

- 2.1 All terms used in these rules and regulations, not defined herein, shall have the meanings set forth in Chapter 22A.22, Article 1A, Section 1 of the West Virginia Code.

Section 3. Underground Mine Car Loading Points

- 3.1 Six months after the effective date of this regulation, skids shall not be placed on mine rails adjacent to the wheels of moving mine cars, unless remote means can be used to place the skids without getting underneath or between the cars.
- 3.2 There shall be no unnecessary visual obstructions in the immediate working area of the underground mine car loading point operator.
- 3.3 These requirements shall be conspicuously posted at the underground mine car loading point, along with any other operation instructions for that facility.