

**WEST VIRGINIA
SECRETARY OF STATE
BETTY IRELAND
ADMINISTRATIVE LAW DIVISION**

Form #3

Do Not Mark In This Box

FILED

2005 JUL 28 P 4: 48

OFFICE WEST VIRGINIA
SECRETARY OF STATE

**NOTICE OF AGENCY APPROVAL OF A PROPOSED RULE
AND
FILING WITH THE LEGISLATIVE RULE-MAKING REVIEW COMMITTEE**

AGENCY: DHHR - Bureau for Public Health TITLE NUMBER: 64

CITE AUTHORITY: WV Code §§ 16-1-4 and 16-35-4

AMENDMENT TO AN EXISTING RULE: YES NO

IF YES, SERIES NUMBER OF RULE BEING AMENDED: 45

TITLE OF RULE BEING AMENDED: Lead Abatement Licensing

IF NO, SERIES NUMBER OF RULE BEING PROPOSED: _____

TITLE OF RULE BEING PROPOSED: _____

THE ABOVE PROPOSED LEGISLATIVE RULE HAVING GONE TO A PUBLIC HEARING OR A PUBLIC COMMENT PERIOD IS HEREBY APPROVED BY THE PROMULGATING AGENCY FOR FILING WITH THE SECRETARY OF STATE AND THE LEGISLATIVE RULE-MAKING REVIEW COMMITTEE FOR THEIR REVIEW.

Martha Jean Walker

Authorized Signature

FISCAL NOTE FOR PROPOSED RULES

Rule Title: 64CSR45 - LEAD ABATEMENT LICENSING

Type of Rule: X Legislative Interpretive Procedural

Agency: HEALTH AND HUMAN RESOURCES

Address: BUILDING 3, ROOM 206
1900 KANAWHA BLVD., EAST
CHARLESTON, WV 25305

Phone Number: (304) 558-2971 Email: annspaner@wvdhhr.org

Fiscal Note Summary

Summarize in a clear and concise manner what effect this measure will have on costs and revenues of state government.

This rule is being amended at the request of the U.S. EPA. The proposed revisions do not alter the intent of the original rule and have no impact on costs. Passage of the amendments will make the state rule as protective as the federal requirements and allow the state to receive full authorization for the State Lead Program. If passage is not achieved, a loss of federal grant funding could occur.

Fiscal Note Detail

Show over-all effect in Item 1 and 2 and, in Item 3, give an explanation of Breakdown by fiscal year, including long-range effect.

Effect of Proposal	Fiscal Year		
	2005 Increase/Decrease (use "-")	2006 Increase/Decrease (use "-")	Fiscal Year (Upon Full Implementation)
1. Estimated Total Cost	0	0	0
Personal Services	0	0	0
Current Expenses	0	0	0
Repairs and Alterations	0	0	0
Equipment	0	0	0
Other	0	0	0
2. Estimated Total Revenues	0	0	0

3. Explanation of above estimates (including long-range effect):

Please include any increase or decrease in fees in your estimated total revenues.

No impact on costs or revenues.

Memorandum

Please identify any areas of vagueness, technical defects, reasons the proposed rule would not have a fiscal impact, and/or any special issues not captured elsewhere on this form.

The proposed rule changes clarify definitions and environmental clearance standards and will have no fiscal impact on state government. Failure to achieve the proposed rule changes may result in a loss of federal grant funding.

Date

1/28/05

Agency

Department of Health and Human Resources

Authorized Representative

Martha Yeager Walker

Martha Walker
Secretary

QUESTIONNAIRE

(Please include a copy of this form with each filing of your rule: Notice of Public Hearing or Comment Period; Proposed Rule, and if needed, Emergency and Modified Rule.)

DATE: July 29, 2005

TO: LEGISLATIVE RULE-MAKING REVIEW COMMITTEE

FROM: *(Agency Name, Address & Phone No.)* Department of Health and Human Resources,
Bureau for Public Health
350 Capitol Street, Room 702
Charleston, WV 25301
(304) 558-2971

LEGISLATIVE RULE TITLE: Lead Abatement Licensing

1. Authorizing statute(s) citation WV Code §§16-1-4 and 16-35-4

2. a. Date filed in State Register with Notice of Hearing or Public Comment Period:
June 27, 2005, rule filed for Public Comment

b. What other notice, including advertising, did you give of the hearing?
n/a

c. Date of Public Hearing(s) *or* Public Comment Period ended:
July 27, 2005 at noon

d. Attach list of persons who appeared at hearing, comments received, amendments, reasons for amendments.

Attached _____ No comments received X

- e. Date you filed in State Register the agency approved proposed Legislative Rule following public hearing: (be exact)

July 29, 2005

- f. Name, title, address and **phone/fax/e-mail numbers** of agency person(s) to receive all *written correspondence* regarding this rule: (Please type)

<u>Ann A. Spaner</u>	<u>John D. Law</u>
Bureau for Public Health	Secretary's Office, DHHR
350 Capitol Street, Room 702	Building 3, Room 206
Charleston, WV 25301	Charleston, WV 25305
558-0035 Phone, 558-1035 Fax	558-7899 Phone; 558-7075 Fax
<u>annspaner@wvdhhr.org</u>	<u>johnlaw@wvdhhr.org</u>

- g. **IF DIFFERENT FROM ITEM 'f'**, please give Name, title, address and phone number(s) of agency person(s) who wrote and/or has responsibility for the contents of this rule: (Please type)

Randy Curtis, Director, Radiation, Toxics and Indoor Air Division
Office of Environmental Health Services
Bureau for Public Health
1 Davis Square, Suite 200
Charleston, WV 25301
558-2891 Phone; 558-1289 Fax
randycurtis@wvdhhr.org

3. If the statute under which you promulgated the submitted rules requires certain findings and determinations to be made as a condition precedent to their promulgation:

- a. Give the date upon which you filed in the State Register a notice of the time and place of a hearing for the taking of evidence and a general description of the issues to be decided.

n/a

b. Date of hearing or comment period:

Comment period ran from June 27 to July 27, 2005

c. On what date did you file in the State Register the findings and determinations required together with the reasons therefor?

n/a

d. Attach findings and determinations and reasons:

Attached n/a

**Department of Health and Human Resources
Bureau for Public Health
Legislative Rule
Title 64, Series 45**

LEAD ABATEMENT LICENSING

BRIEF SUMMARY OF PROPOSED RULE

This amendment is proposed to comply with recommendations from the US Environmental Protection Agency to make the West Virginia lead abatement program substantially equivalent to and as protective as the federal program. In enacting these changes our state will be able to meet the federal requirements to receive full authorization of our program and to maintain federal funding for the program.

TITLE 64
WEST VIRGINIA LEGISLATIVE RULE
~~DIVISION OF HEALTH~~
BUREAU FOR PUBLIC HEALTH
DEPARTMENT OF HEALTH AND HUMAN RESOURCES
SERIES 45
LEAD ABATEMENT LICENSING

FILED
2005 JUL 28 P 4: 49
OFFICE WEST VIRGINIA
SECRETARY OF STATE

§64-45-1. General.

1.1. Scope. -- This legislative rule establishes procedures and standards for the licensure and training of persons who engage in activities related to lead abatement and for the operation of lead abatement projects. This rule should be read in conjunction with the definitions and provisions of W-Va. Code §16-35-1 et seq. (Lead Abatement).

1.2. Authority. -- W-Va. Code §§16-1-4 and 16-35-4 ~~and 16-1-7~~.

1.3. Filing Date. -- ~~April 29, 1999~~.

1.4. Effective Date. -- ~~July 1, 1999~~.

§64-45-2. Application and Enforcement.

2.1. Applications. - This rule applies to persons who conduct lead abatement projects in target housing or child-occupied facilities, and requires licensure of lead contractors, inspectors, risk assessors, workers, supervisors, and designers.

2.2. Enforcement. - This rule shall be enforced by the ~~director~~ commissioner of the West Virginia ~~division of health~~ bureau for public health.

§64-45-3. Definitions.

3.1. Abatement. - Any measure or set of measures designed to permanently eliminate lead-based paint hazards. Abatement includes, but is not limited to:

3.1.a. The removal of lead-based paint and lead-contaminated dust, the permanent containment or encapsulation of lead-based paint, the replacement of lead-painted surfaces or fixtures,

and the removal or covering of lead-contaminated soil;

3.1.b. All preparation, cleanup, disposal, and post-abatement clearance testing activities associated with such measures;

3.1.c. Projects for which there is a written contract to permanently eliminate lead-based paint hazards from a dwelling unit or child-occupied building;

3.1.d. Projects involving the permanent elimination of lead-based paint or lead contaminated soil;

3.1.e. Projects involving the permanent elimination of lead-based paint hazards or lead contaminated soil that are conducted by persons who advertise or hold themselves out to conduct lead related activities; and

3.1.f. Projects involving the permanent elimination of lead-based paint hazards that are conducted in response to federal, state or local abatement orders.

3.2. EPA. - The United States environmental protection agency.

3.3. HEPA. - High efficiency particulate air.

3.4. Lead abatement contractor. - A person engaged by oral or written contract to perform a lead abatement project.

3.5. Lead-based paint. - Paint or other surfacing coatings that contain lead at or in excess of five thousand (5000) parts per million, or one half of one percent (0.5%) by weight, or 1.0 milligram

per square centimeter (1.0 mg/cm²).

3.6. Lead-contaminated dust. - Surface dust containing lead at or in excess of ~~one hundred (100)~~ forty (40) micrograms per square foot for floors, at or in excess of ~~five hundred (500)~~ two hundred-fifty (250) micrograms per square foot for interior window sills, at or in excess of ~~eight hundred (800)~~ four hundred (400) micrograms per square foot for window troughs and exterior concrete or other rough surfaces.

3.7. Lead-contaminated soil. - Soil containing lead at or in excess of ~~two thousand (2000)~~ one thousand two hundred (1200) parts per million, or four hundred (400) parts per million for bare, high-contact play areas.

3.8. Lead-contaminated waste. - Any discarded materials with lead toxicity equal to or in excess of five (5) parts per million as determined by the total characteristic leachate procedure (TCLP).

3.9. License. - A document authorizing an individual to perform specific lead abatement activities.

3.10. Public building. - Any building that is generally open to the public, including but not limited to museums, airport terminals, hospitals, stores, restaurants, convention centers and other office buildings, corporate facilities and government buildings that do not expressly prohibit access to the public.

3.11. Target Housing. - Residential structures built prior to one thousand nine hundred seventy-eight or residential structures that are confirmed by inspection to contain lead-based paint.

~~3.11.~~ 3.12. XRF analyzer. - An instrument that determines lead concentration in milligrams per square centimeter (mg/cm²) using the principle of x-ray fluorescence (XRF).

§64-45-4. Initial and Renewal License.

4.1. Initial license.

4.1.a. Applicants for licensure as a lead inspector, risk assessor, worker, supervisor, designer or contractor shall submit to the ~~director~~ commissioner an application which shall include:

4.1.a.1. Proof of passage of an applicable state accredited lead training course. A copy of the certificate indicating the date on which training was completed, the location at which training was conducted, the signature of the instructor, and examination score is required;

4.1.a.2. Proof of passage of an examination from a State accredited discipline examiner for the license discipline. A copy of the examination certificate indicating the applicant's name, the date on which the examination took place, the location of the examination, the license discipline and the score of the examination is required;

4.1.a.3. The applicant's date of birth, social security number, current address, driver's license number and telephone phone number. Applicants shall be at least eighteen (18) years of age;

4.1.a.4. The signature of the applicant;

4.1.a.5. A history of all environmental enforcement actions taken against the applicant by any federal or state agency or court;

4.1.a.6. Attachment of all applicable license fees. A schedule of fees is set forth in Table A of this rule;

4.1.a.7. Evidence that an applicant for a lead supervisor license has one year experience as a lead abatement worker, or at least two years of experience in a related field, such as lead, asbestos, or environmental remediation work, or the building trades;

4.1.a.8. Evidence that an applicant for a lead risk assessors license possesses a valid lead inspector's license and one of the following:

4.1.a.8.A. A bachelor degree and one year of experience in a related field, such as lead, asbestos, environmental remediation work or construction;

4.1.a.8.B. An associate degree and two-year experience in a related field such as lead, asbestos, environmental remediation work or construction;

4.1.a.8.C. A certification as an industrial hygienist, professional engineer, registered architect, registered sanitarian, or certification in a related engineering/health/environmental field, such as safety professional, environmental scientist; or

4.1.a.8.D. A high-school diploma or equivalent, and at least three years of experience in a related field, such as lead, asbestos, environmental remediation work or construction;

4.1.a.9. Evidence that an applicant for a project designer license:

4.1.a.9.A. Possesses a bachelor's degree in engineering, architecture, or a related profession and one year experience in building construction and design or a related field; or

4.1.a.9.B. Four years experience in building construction and design or a related field; and

4.1.a.9.C. Proof of passage of a lead supervisor training course.

4.1.a.10. Evidence that an applicant for a contractor license has a licensed supervisor on staff.

4.1.b. Applicants and their employers or agents shall demonstrate to the satisfaction of the ~~director~~ commissioner that the applicant is familiar with and capable of complying fully with all applicable requirements, procedures and standards of the EPA, OSHA and of the State agencies of the ~~division of health~~ bureau for public health, division of natural resources, bureau of commerce, division of labor, air quality board and division of

environmental protection covering any part of a lead abatement project. An applicant who has passed an applicable state accredited training course and passed an examination from a discipline examiner meets this requirement.

4.1.c. The ~~director~~ commissioner may deny a license and retain the license fee if the applicant fails to satisfy the requirements of this section. A written notice of denial and an opportunity for reapplication shall be afforded to all applicants.

4.1.d. Licenses issued under this rule expire one year from the last day of the month in which they were issued.

4.2. Renewal application.

4.2.a. Prior to the expiration date shown on the license, each licensee who desires to retain a valid license shall submit a renewal application, appropriate refresher course certification, and all applicable fees. Licensees should apply for renewal no less than (10) ten days prior to the expiration of the license to avoid a temporary lapse of license. A schedule of license fees is set forth in Table A of this rule.

4.2.b. Applicants shall submit proof of passage of an applicable State accredited refresher course every third year from the date of the original training and certification.

§64-45-5. Licensed Lead Abatement Contractor Duties.

5.1. A licensed lead abatement contractor shall:

5.1.a. Ensure that each contractors' employees or agents who will come into contact with lead or who will be responsible for a lead abatement project is properly licensed;

5.1.b. Ensure that each lead abatement project is supervised by an on-site licensed lead supervisor;

5.1.c. Notify the division and all other entities as may be required by state or federal law at least ten (10) days prior to the commencement of each lead abatement project. Notification to the division shall be by certified mail or by hand-delivery to the division;

5.1.d. Ensure that a lead abatement project is designed by a licensed lead abatement designer;

5.1.e. Ensure that each lead abatement project meets the minimum clearance standards as set forth in section 11 of this rule;

5.1.f. Ensure proper disposal of lead contaminated waste in accordance with applicable federal, state, and local laws, rules and regulations;

5.1.g. Keep a record of each lead abatement project. The records shall include:

5.1.g.1. The name, address and lead abatement license number of the individual who supervised the lead abatement project and of each employee or agent who worked on the project;

5.1.g.2. The location and a description of the lead abatement project and the amount of lead material that was removed;

5.1.g.3. The starting and completion dates of each lead abatement project and a summary of the procedures that were used to comply with all federal and state standards;

5.1.g.4. The name and address of each disposal site where waste containing lead was deposited and the disposal site receipts. Contractors shall use disposal sites which are in conformance with applicable federal, state and local laws and regulations; and

5.1.g.5. The clearance sample results or air monitoring results required by section 11 of this rule for each lead abatement project. The records shall include:

5.1.g.5.A. The name and signature of the lead inspector who collected the clear-

ance samples;

5.1.g.5.B. Where the samples were collected;

5.1.g.5.C. The date of collection;

5.1.g.5.D. The name and address of all laboratories analyzing the samples;

5.1.g.5.E. The date of analysis;

5.1.g.5.F. The results of analysis;

5.1.g.5.G. The method of analysis;

5.1.g.5.H. The name and signature of the person performing the analysis; and

5.1.g.5.I. Certification that the laboratory is EPA certified to analyze lead samples.

5.2. The records required by this section shall be available to the state agencies of the ~~division of health~~ bureau for public health, division of natural resources, division of environmental protection, division of labor and air quality board upon request during normal business hours. Records for current projects shall be immediately available. For completed projects, the ~~director~~ commissioner may afford the contractor a reasonable time to comply with the requests, depending upon the length of time since the project's completion and whether or not the advance notice might adversely affect an investigation being conducted by any of the agencies. Records required by this section shall be kept for at least three (3) years.

§64-45-6. Lead Inspector Duties.

6.1. A licensed lead inspector shall:

6.1.a. Thoroughly inspect interior and exterior surfaces suspected of containing lead that may be affected by renovation or demolition, and sample the materials for lead content or confirm lead content with an XRF analyzer.

6.1.b. Generate a written report that at a minimum:

6.1.b.1. Identifies by narrative any sampling location where the presence of lead containing material has been confirmed;

6.1.b.2. Details the location and amount of all materials that contain lead;

6.1.b.3. Lists analysis, XRF results, or both for all samples; ~~and~~

6.1.b.4. Includes drawings and narrative descriptions of locations of samples and/or XRF readings; and

6.1.b.5 Includes a statement that the inspection is not a risk assessment.

6.1.c. Adequately sample each area or room of an abatement project for clearance to verify that dust, soil and waste material lead levels are below the contamination standards as defined in subsections 3.6., 3.7. and 3.8. of this rule.

§64-45-7. Lead Abatement Designer Duties.

7.1. A licensed lead abatement designer shall generate a written report that provides:

7.1.a. A chronological time frame for each facet of the abatement activity;

7.1.b. The name and address of the building or structure where the lead abatement project is to occur;

7.1.c. The name, address, phone number, and lead abatement training certificates and licenses for the project designer;

7.1.d. A schematic floor plan showing the lead abatement project area, including a description of the characteristics of the material;

7.1.e. A statement identifying the abatement activity as repair, removal, encapsulation, or enclosure;

7.1.f. A schematic floor plan of the project area which shows the physical dimensions, entrance, exit, windows, decontamination unit, load-out area, emergency exits, placement of the HEPA exhaust air filtration units, if applicable, and any measuring devices, warning signs, and barrier tape;

7.1.g. The sampling protocol for project clearance for re-occupancy, including the number of samples, collection points and the analytical method to be employed;

7.1.h. A schematic of the heating, ventilation and air-conditioning system shut-offs, electrical power, water source, fire exits, fire extinguisher, fire alarm, telephone, tool and equipment room, supply box, project field office, bathrooms and decontamination area;

7.1.i. A description of the work procedures to be used; ~~and~~

7.1.j. A description of the materials and tools to be used in the abatement project; and

7.1.k. An occupant protection plan in accordance with section 16.1 and 16.4 of this rule.

§64-45-8. Lead Risk Assessor Duties.

8.1. A licensed lead abatement risk assessor shall generate a written risk assessment report that provides:

8.1.a. Background information regarding the age, condition and physical characteristics of the structure and residential use patterns;

8.1.b. A schematic site plan showing each room within the structure, its use and the location and condition of lead-based paint;

8.1.c. A copy of any previous test results or inspections regarding lead-based paint or other assessments for lead hazards;

8.1.d. An assessment of the potential routes of lead exposure for occupants or lead abatement professionals, which is based upon

adequate dust, water, soil and paint chip sampling; and

8.1.e. A detailed description of recommended control strategies for reducing lead-based paint hazards and justification for the strategy selected, the locations where the recommended actions should take place, and a suggested prioritization for taking each action based on the degree of the hazard.

8.2. The risk assessment shall be maintained by the risk assessor or his or her firm for a period of three years.

§64-45-9. Prohibited Lead Abatement Project Methods.

9.1. The following lead abatement project methods are prohibited:

9.1.a. The use of open flame burning, torching, fossil fuel-powered heat plates, welding, cutting torches, and heat guns operating at temperatures greater than one thousand one hundred (1,100) degrees F as a means of lead based paint removal;

9.1.b. Uncontained machine sanding or grinding;

9.1.c. Uncontained hydro-blasting and high-pressure water washing;

9.1.d. Uncontained abrasive blasting or sandblasting;

9.1.e. Chemical paint removers that contain methylene chloride; and

9.1.f. Dry scraping lead-based paint, except for areas around electrical outlets.

§64-45-10. Recommended Lead Abatement Project Methods.

10.1. The following lead abatement project methods are recommended:

10.1.a. Electric-powered flameless heat

guns operating below one thousand one hundred (1,100) degrees F, provided that proper respiratory protection is used;

10.1.b. Mechanical HEPA sanding, HEPA vacuum blasting and HEPA vacuuming needle guns;

10.1.c. Wet scraping, provided that no electrical hazards are present while doing so;

10.1.d. The removal of building components to be stripped of lead-based paint off site, provided that dust generation during the removal and transportation of the building components is kept to a minimum;

10.1.e. Chemical removal methods which do not contain methylene chloride, provided that product material safety data sheet recommendations for safety, and OSHA regulations are implemented;

10.1.f. The enclosure of building components that contain lead-based paint, provided that the enclosure material becomes a permanent part of the building structure and is properly sealed to ensure that lead dust is permanently contained;

10.1.g. Encapsulation of lead-based paint, provided that the encapsulating material becomes a permanent part of the building component and will be guaranteed by the lead abatement company and manufacturer from defect for a minimum of twenty (20) years; and

10.1.h. Total removal of lead-contaminated soil or the covering of lead-contaminated areas with a suitable material that will limit exposure. For purposes of this subdivision, suitable material includes but is not limited to stone, pavement, gravel or vegetative cover.

§64-45-11. Lead Abatement Project Clearance Levels and Minimum Sampling.

11.1. A licensed lead inspector shall conduct a visual inspection at the conclusion of a lead abatement project and collect samples as set forth in Table D of this rule.

11.2. A lead abatement project shall be ready for occupation when the following clearance levels of lead are obtained:

11.2.a. Below ~~one hundred (100)~~ forty (40) micrograms of lead per square foot for interior floors or other horizontal surfaces;

11.2.b. Below ~~five hundred (500)~~ two hundred-fifty (250) micrograms of lead per square foot for interior window sills;

11.2.c. Below ~~eight hundred (800)~~ four hundred (400) micrograms of lead per square foot for window troughs and exterior concrete or other rough surfaces;

11.2.d. Below four hundred (400) parts per million for bare soil areas that are child play areas;

11.2.e. Below ~~two thousand (2000)~~ one thousand two hundred (1200) parts per million for residential bare soil areas; and

11.2.f. A total characteristic leachate procedure (TCLP) below five (5) parts per million lead toxicity for discarded building materials.

11.3. The minimum numbers of samples to be obtained from a lead abatement project area are defined in Table D of this rule.

11.4. In addition to the required number of samples as defined in Table D of this rule, a licensed lead inspector will obtain one (1) soil sample for each four hundred (400) square feet of bare soil area of a lead abatement project and one (1) composite sample from homogeneous building materials that is representative of the waste stream.

§64-45-12. Exemption from Notification and Licensing.

Exemption from notification and licensure is as provided in W.-Va. Code §16-35-7.

§64-45-13. Notification of Elevated Blood Lead Levels.

Any person, contractor or laboratory shall notify the ~~director~~ commissioner of any medically confirmed elevated blood-lead levels within thirty-six (36) hours of discovery.

§64-45-14. Notification of Lead Abatement Projects.

Each owner or other person responsible for the operation of a building, facility, residence or structure where a lead abatement project is to occur shall notify the division ten (10) days prior to commencement of the project and pay the notification fee set forth in Table B of this rule.

§64-45-15. Accreditation/Reaccreditation of Lead Abatement Initial/Refresher Training Courses.

15.1. Applicants for accreditation /reaccreditation as lead abatement training providers shall submit the following:

15.1.a. The name, address and telephone number of the lead training provider;

15.1.b. A full description of the course curriculum;

15.1.c. A list of instructors, their resumes and qualifications;

15.1.d. A copy of the course examination;

15.1.e. The annual lead training course accreditation fee set forth in Table C of this rule;

15.1.f. Any additional information required by W.-Va. Code §16-35-10; and

15.1.g. Any and all applications or certifications required by the commissioner.

15.2. Initial/refresher lead abatement training ~~Training~~ providers to be accredited/reaccredited by the ~~division of health bureau for public health~~ shall ~~adhere to~~ comply with subsection 16.1 and 16.4 of this rule regarding including, but not limited to

curriculum, length of training, record keeping and training manager and instructor qualifications.

§64-45-16. Applicable Federal Standards.

All individuals licensed under this rule shall comply with the following applicable federal standards, which are hereby incorporated in this rule by reference:

16.1. EPA: Lead; Requirements for Lead-Based Paint Activities in Target Housing and Child-Occupied Facilities: Final Rule. 40 CFR Part 745.227. (January 5, 2001) ~~(August 29, 1996)~~.

16.2. OSHA: Lead Exposure in Construction; Interim Final Rule. 29 CFR 1926.62 (May 4, 1993); and

16.3. HUD: Guidelines for the Evaluation and Control of Lead-Based Paint Hazards in Housing (June 1995).

16.4. EPA: Lead; Requirements for Lead-Based Paint Activities in Target Housing and Child-Occupied Facilities; Final Rule. 40 CFR Part 745.225 (b),(c),(d),(e),(f),(g),(h),(i).

~~16.5. EPA: Lead; Requirements for Lead-Based Paint Activities in Target Housing and Child-Occupied Facilities: Final Rule. 40 CFR Part 745.227.~~

§64-45-17. Penalties.

17.1. The ~~director~~ commissioner may, depending upon the severity of the violation and upon the degree of health hazard created, suspend or revoke the license of a contractor, inspector, designer, risk assessor, supervisor, or worker if the licensee:

17.1.a. Fraudulently or deceptively obtains or attempts to obtain a license;

17.1.b. Fails at any time to meet the qualifications for license or to comply with the requirements of W.-Va. Code §16-35-1 et seq. or this rule;

17.1.c. Knowingly falsifies or attempts to falsify documents related to a lead abatement project or license;

17.1.d. Fails to meet the applicable federal or state standard for lead abatement; or

17.1.e. Fails to remit an assessed civil penalty or fine.

17.2. The commissioner may suspend, or revoke the accreditation/reaccreditation of an initial/refresher lead training provider if the training provider fails to meet the requirements of this rule as outlined in Section 16.1. and 16.4.

~~17.2.~~17.3. The ~~director~~ commissioner may investigate all alleged violations of this rule or of W.-Va. Code §16-35-1 et seq. reported to the division. Upon the finding of a violation in connection with a lead abatement project the ~~director~~ commissioner shall, depending upon the severity of the violation and upon the degree of health hazard created, initiate an appropriate enforcement action which may include the issuance of a cease and desist order directing that all work on the project be halted immediately. Posting of the cease and desist order on the project site constitutes notice of its contents to the property owner and all individuals working on the lead abatement project. Where practicable, however, the ~~director~~ commissioner shall deliver a copy of the order by certified mail, return receipt requested, to the property owner and to the contractor.

~~17.3.~~17.4. Fines and penalties are as provided in W.-Va. Code §16-35-13.

§64-45-18. Administrative Due Process.

Those individuals adversely affected by the enforcement of this rule desiring a contested case hearing to determine any rights, duties, interests or privileges shall do so in a manner prescribed in the Division of Health's bureau for public health's rule, Rules and Procedures for Contested Case Hearings and Declaratory Rulings, 64CSR1.

TABLE 65-45 A

LICENSE FEES

Type of License	Fee
Worker	\$ 50.00
Supervisor	\$ 100.00
Inspector	\$ 100.00
Risk Assessor	\$ 100.00
Project Designer	\$ 100.00
Contractor	\$ 300.00

TABLE 65-45 B

NOTIFICATION FEE

All Projects	\$ 60.00
--------------	----------

TABLE 65-45 C

ACCREDITATION FEES FOR LEAD TRAINING PROVIDERS

Initial Accreditation	\$1,000.00 per Discipline	(max. \$3,000.00)
Annual Reaccreditation	\$ 500.00 per Discipline	(max. \$1,500.00)

TABLE 64-45 D

MINIMUM NUMBER AND LOCATION OF SINGLE-SURFACE DUST SAMPLES

Clearance Category	Category Description	Number and location of Single-Surface Wipe Samples in Each Area ¹	Number and Location of Composite Wipe Samples
1	Interior treatments No containment within dwelling	Two dust samples from at least four rooms in dwelling (treated or untreated): ★One interior window sill or window trough, alternating between rooms. ★One floor. AND ★For common areas, one for every 2,000 ft ² of a common area room floor (if present)	Three composite samples for every batch of four rooms (whether treated or untreated): ★ One floor composite. ★ One interior window sill composite ★ One window trough composite. AND ★ For common areas, one floor subsample for every 2,000 ft ² (if present); up to 8,000 ft ² can be sampled for every composite.
2	Interior treatments With containment (Plastic sheeting as airlock on doors between treated and untreated areas)	Same as Category 1 but only in every <i>treated</i> room (up to four rooms) AND One floor sample outside the containment area but within 10 feet of the airlock to determine the effectiveness of the containment system. This extra single-surface sample is recommended in 20 percent of the treated dwellings in multifamily housing and all single-family homes. ★ For common areas, one floor sample for every 2,000 ft ² and one floor sample outside containment.	Same as Category 1 but only in every <i>treated</i> room AND One floor sample outside the containment area but within 10 feet of the airlock to determine the effectiveness of the containment system. This extra single-surface sample is recommended in 20 percent of the treated dwellings in multifamily housing and all single-family homes. ★ For common areas, one floor subsample for every 2,000 ft ² (up to 8,000 ft ² for each composite) and one floor sample outside containment.
3	Exterior treatments	Two dust samples as follows: ★At least one dust sample on a horizontal surface in part of the outdoor living area (e.g., a porch floor or entryway). ★One window trough sample on each floor where exterior work was performed. An additional trough sample should be collected from a few lower floors to determine if troughs below the area were contaminated by the work above.	Two dust samples as follows: ★One composite on a horizontal surface in part of the outdoor living area (e.g., a porch floor or entryway). ★One window trough composite for every four floors where exterior work was performed, including lower floors where exterior work was not done, if present.
4	Routine maintenance work	At least 1 floor dust sample for every 20 high-hazard jobs near the work area.	Same as single-surface sampling.
5	Soil treatment	One dust sample from the entryway.	One dust sample from the entryway.

¹ A room includes a hallway or a stairway. If no window, just one floor sample must be collected. When a closet is treated, the room to which it is attached should be tested. A closet is not considered to be a separate room. If all rooms received similar treatments and cleaning, only four rooms need to be sampled for clearance purposes. More rooms may need to be sampled in larger dwellings. The room to be sampled should be selected based on where most of the dust-generating work was done or in the judgement of the clearance examiner.